


WHMIS Code

N/A
None

Material Safety Data Sheet

NG Paint Sealant



Section 1 - Material Identification and Use

Manufacturer's Name..... **Cal-Tex Protective Coatings, Incorporated**
 Manufacturer's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 Emergency Phone Number..... INFOTRAC 1-800-535-5053 24 Hours Per Day, 7 Days Per Week
 Supplier Name and Identifier..... **Cal-Tex Protective Coatings, Incorporated**
 Supplier's Address..... 7455 Natural Bridge Caverns Road Schertz TX 78154
 MSDS Prepared By Ronnie Meadows (210) 564-3200
 Trade Name..... **NG Paint Sealant**
 Product Use..... Automotive paint sealant and protector

Section 2 - Hazardous Ingredients of Material

No.	Chemical Identity	Concentration	CAS	PEL	TLV	STEL	IDLH
1	Hydrocarbon Solvent	Trade Secret	64742-88-7	100	100	N/A	
2	Low Odor - Kerosene	Trade Secret	8008-20-6	400			
3	Carnauba Wax Emulsion	Trade Secret	BLEND	N/A	N/A		
4	Poly (Dimethylsiloxane)	Trade Secret	63148-62-9				
5	Cyclomethicone Fluid Blend	Trade Secret	Blend				
6	Fatty Alkanolamide Blend	Trade Secret	68155-20-4				
7	Isopropyl alcohol	Trade Secret	67-63-0	400	400	500	2000

NA = Not Applicable ND = No Data Available < = Less Than > = More Than * Ceiling Value ** Chemical Believed to be a Potential Carcinogen (NIOSH)

Section 3 - Hazardous Identification

EYE	☒	This chemical may affect the eye or visual capacity
SKIN	☒	This chemical may affect the dermal layer of the body
LUNGS	☒	This chemical may irritate or damage pulmonary tissue
NERVOUS SYSTEM	☐	This chemical may produce a toxic affect on the nervous system
REPRODUCTIVE	☐	May affect reproductive capabilities including mutations and effects on the fetus.
BLOOD	☐	This chemical may act on the blood or hematopoietic system; decrease hemoglobin function; deprive tissue of oxygen
LIVER	☐	This chemical may produce liver damage - Hepatotoxins
KIDNEYS	☐	This chemical may produce kidney damage - Nephrotoxins

WHMIS Warning:

None

Section 4 - First Aid Measures


INGESTION	☒	DO NOT induce vomiting. Rinse mouth with water and give plenty of milk. Never give liquids to an unconscious victim - Seek Immediate Medical Attention
EYE CONTACT	☒	Flush immediately with plenty of water for at least 15 minutes - Seek Medical Attention
SKIN CONTACT	☒	Wash thoroughly with soap and water - Seek Medical Attention if irritation persists
INHALATION	☐	Remove to fresh air. If breathing is difficult give oxygen - If not breathing give artificial respiration -Get Medical Attention
SPECIAL	☐	None Identified

WHMIS Code

N/A
None

Material Safety Data Sheet

NG Paint Sealant



Section 5 - Fire-Fighting Measures

Flashpoint F	N/A	Upper Explosion Limit	Not Determined	Extinguishing Media ☐ DO NOT USE WATER	Carbon dioxide, dry chemical, water fog, water spray, foam.
Flashpoint C	N/A	Lower Explosion Limit	Not Determined		
		Auto-Ignition Temp.	Not Determined		
Special Fire Fighting Procedures		Use self contained breathing apparatus when fighting large fires.			

Section 6 - Accidental Release Measures

Spill and Leak Requirements	Small leaks-mop up, wipe up, or soak up immediately. Large spills-contain material and ventilate area. Do not dump into sewers, on the ground, or into any body of water.
-----------------------------	---

Section 7 - Handling and Special Storage

Handling and Special Storage	Keep containers closed when not in use. Store in a cool place with adequate ventilation. Storage location should be constructed for containment and dilution/neutralization of spills.
Additional Storage Requirements	

Section 8 - Exposure Controls and Personal Protection

Eye Protection	Wear approved eye protection to safeguard against potential eye contact, irritation or injury.
Skin Protection	Wear chemical resistant gloves, avoid long term exposure.
Comments	None needed with proper engineering controls. Use when concentrations exceed the PEL/TLV. Maintain ventilation to keep vapor concentration below the PEL/TLV.

Section 9 - Physical and Chemical Properties

Physical State	Paste	Evaporation Rate	Not Determined
Odor and Appearance	Slight solvent odor, off white cream	Boiling Point	Not Determined
Specific Gravity	Not Determined	Freezing Point	Not Determined
Vapour Pressure	Not Determined	pH	Not Determined
Vapour Density	Not Determined	Density (g/ml)	Not Determined

Section 10 - Stability and Reactivity


Stability	☒ Material is Stable ☐ Material is NOT Stable
Incompatibility	Strong Oxidizing Material
Hazardous Decomposition Products	Thermal decomposition may yield carbon monoxide and/or carbon dioxide
Hazardous Polymerization	☐ May Occur ☒ Will NOT Occur

WHMIS Code

N/A
None

Material Safety Data Sheet

NG Paint Sealant



Section 11 - Toxicological Information

Acute Over Exposure Effects	Not Determined
Chronic Over Exposure Effects	Not Determined
Eye Contact	Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
Skin Contact	Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.
If Inhaled	Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
If Swallowed	Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting.

Section 12 - Ecological Information

Section 13 - Disposal Considerations

Dispose in accordance with local, state, and federal regulations.

Section 14 - Transportation Information

Ship as per DOT requirements in 49 CFR. Ship in accordance with local, state, and federal regulations.

Section 15 - Regulatory Information

No.	Chemical Identity	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
1	Hydrocarbon Solvent																						
2	Low Odor - Kerosene										+												X
3	Carnauba Wax Emulsion																						
4	Poly (Dimethylsiloxane)																						
5	Cyclomethicone Fluid Blend																						
6	Fatty Alkanolamide Blend																						
7	Isopropyl alcohol						X					X									X		X

(1) EHS-RQ (2) CERCLA (3) RQ (4) CAA 122r (5) TPQ (6) FIFRA (7) RCRA Code (8) Cal-CARC (9) Priority Pollutant (10) Cal-Well Monitoring (11) SARA 313 (12) SARA 302 (13) MCL (14) Cal-HOT SPOT (15) Cal-Drinking Water (16) Cal-Toxic Air (17) NESHAP (18) Cal-Prop 65 (19) DOT Inhalation (20) Director's List (21) EPA Air (22) Cal-Reg Pest.

An "X" in Column 11 indicates that this product contains a toxic chemical subject to the reporting requirements of Section 313 of EPCRA (40 CFR 372)

MSDS No.	227	Date Reviewed	1/21/2010	Prepared By	Ronnie Meadows
Trade Name	NG Paint Sealant	Supersedes	1/21/2010	Phone Number	(210) 564-3200

TLV - Threshold Limit Value. An estimate of the average safe airborne concentration of a substance in representative conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. TLVs are published annually by the ACGIH (American Conference of Governmental Industrial Hygienists).

PEL - Permissible Exposure Limit. The OSHA limit of employee exposure to chemicals; found primarily in 29 CFR 1910.1000.

STEL - Short Term Exposure Limit. The maximum concentration for a continuous 15-minute exposure period.

IDLH - Immediately Dangerous to Life and Health. The concentration of a airborne chemical which may cause irreversible health effects or death.

Ceiling - The maximum allowable concentration to which an employee may be exposed.

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the users responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using this product, read label. The information contained in this publication is intended for general information purposes only. This publication is not a substitute for review of the applicable government regulations and standards, and should not be construed as legal advice or opinion. Readers with specific questions should refer to the cited references.