



Material Safety Data Sheet

Copyright, 2010, Meguiar's, Inc. Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: G95, Hot Rims® All Wheel Cleaner (20-45E): G9524

MANUFACTURER: Meguiar's, Inc.

DIVISION: Automotive Aftermarket
Automotive Aftermarket

ADDRESS: Meguiar's, Inc.
17991 Mitchell South, Irvine, CA

EMERGENCY PHONE: Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

Issue Date: 11/17/10

Supersedes Date: 08/03/10

Document Group: 26-8083-3

Product Use:

Intended Use: Automotive
Specific Use: Cleaner

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
NON-HAZARDOUS INGREDIENTS	Mixture	70 - 90
DECYLAMINE OXIDE	2605-79-0	1 - 5
ALCOHOL ETHOXYLATE	68991-48-0	1 - 5
OXALIC ACID DIHYDRATE	6153-56-6	1 - 5
GLYCOLIC ACID	79-14-1	1 - 5
LINEAR ALKYL QUATERNARY AMMONIUM COMPOUND	Trade Secret	0.5 - 1.5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Mild acidic odor; Clear

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause chemical eye burns. May cause chemical skin burns. May cause chemical gastrointestinal burns. May cause chemical respiratory tract burns.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Inhalation:

Respiratory Tract Corrosion: Signs/symptoms may include nasal discharge, severe nose and throat pain, chest tightness and pain, coughing up blood, wheezing, and breathlessness, possibly progressing to respiratory failure.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Prolonged or repeated exposure may cause:

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water for at least 15 minutes. Get immediate medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. Get immediate medical attention.

If Swallowed: Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

No Data Available

Flash Point

> 93 °C [*Test Method:* Closed Cup]

Flammable Limits - LEL

Not Applicable

Flammable Limits - UEL

Not Applicable

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

Environmental procedures

Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Dispose of collected material as soon as possible.

Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully cover the spill with soda ash (sodium carbonate) or sodium bicarbonate. Work from around the perimeter inward. Avoid splashing. Add enough water to ease mixing and stir. Continue stirring and adding water and neutralizing agent until the reaction stops. Let cool before collecting. Or use a commercially available 'Acid spill' clean-up kit. Follow the kit directions exactly, as specified. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with a dilute solution (approximately 1 to 5%) of soda ash (sodium carbonate) or baking soda (sodium bicarbonate) in water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Keep out of the reach of children. Avoid contact with oxidizing agents. Avoid breathing of vapors, mists or spray. Avoid skin contact. Avoid eye contact with vapors, mists, or spray. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not spray near flames or sources of ignition. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material.

7.2 STORAGE

Store out of direct sunlight. Store away from heat. Store away from acids. Store away from flammable and combustible materials. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Full Face Shield
Indirect Vented Goggles

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene. The following protective clothing material(s) are recommended: Apron - Neoprene.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with N95 particulate filters.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingr</u> redient	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
GLYCOLIC ACID	CMRG	TWA	10 mg/m3	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor, Color, Grade:

Mild acidic odor; Clear

General Physical Form:

Liquid

Autoignition temperature

No Data Available

Flash Point

> 93 °C [Test Method: Closed Cup]

Flammable Limits - LEL	Not Applicable
Flammable Limits - UEL	Not Applicable
Boiling point	>=93 °C
Density	1.02 - 1.03 g/ml
Vapor Density	No Data Available
Vapor Pressure	Not Applicable
Specific Gravity	1.02 - 1.03 [Ref Std: WATER=1]
pH	1.5 - 2.5
Melting point	Not Applicable
Solubility in Water	Complete
Evaporation rate	No Data Available
Volatile Organic Compounds	0.0 %
Volatile Organic Compounds	0.0 g/l
Kow - Oct/Water partition coef	Not Applicable
Percent volatile	No Data Available
Viscosity	1 centipoise [Details: Approximate]

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Sparks and/or flames
Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D002 (Corrosive)

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

DOTG

Consumer Commodity, ORM-D or Limited Quantity

DOTW

Consumer Commodity, ORM-D

IATA

UN3265, Corrosive Liquid, Acidic, Organic N.O.S., (Glycolic Acid and Oxalic Acid Dihydrate), 8, III

IMO

UN3265, Corrosive Liquid, Acidic, Organic N.O.S., (Glycolic Acid and Oxalic Acid Dihydrate), 8, III, Limited Quantity

ID Number(s):

14-1000-0999-3, 14-1000-1000-9, 14-1000-1001-7, 14-1000-1002-5, 14-1000-1003-3

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact Meguiar's for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

STATE REGULATIONS

Contact Meguiar's for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact Meguiar's for more information.

INTERNATIONAL REGULATIONS

Contact Meguiar's for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 14: Transportation legal text was modified.

Section 2: Ingredient table was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. Meguiar's MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from Meguiar's.

Meguiar's MSDSs are available at www.Meguiar's.com