

MATERIAL SAFETY DATA SHEET

Revision



Date Issued: 03/24/2011

MSDS No: WGR

WAX & GREASE REMOVER

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WAX & GREASE REMOVER**PRODUCT CODE:** WGR**MANUFACTURER**

Tarr, LLC

P.O. Box 12570

Portland, OR 97212

Service Number: 503-288-5294**24 HR. EMERGENCY TELEPHONE NUMBERS****CHEMTREC (US Transportation) :**(800) 424 - 9300**CANUTEC (Canadian Transportation) :**(613) 996 - 6666

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Can cause severe lung damage and may be fatal if swallowed. Causes eye and skin irritation or injury. May be harmful if swallowed. May cause CNS depression.

POTENTIAL HEALTH EFFECTS

EYES: Liquid is moderately irritating to the eyes. High vapor concentrations may also be irritating. Direct contact with the liquid or exposure to its vapors or mists may cause stinging, tearing, redness.

SKIN: Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Liquid is moderately toxic and may be harmful if swallowed. May be irritating to the gastrointestinal tract, causing abdominal pain and vomiting, sometimes bloody. Ingestion of product may result in low blood pressure, rapid heart beat, liver damage, vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspir. pneumonitis. Serious lung damage and possibly fatal chemical pneumonia (chemical pneumonitis) can develop if this occurs. May cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Significant exposure may result in unconsciousness and death.

INHALATION: Breathing of high vapor concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Vapors expected to be slightly irritating. Prolonged and repeated exposures to high concentrations may cause hearing loss. Chronic hydrocarbon abuse (for example, sniffing glue or light hydrocarbons such as contained in this material) has been associated with irregular heart rhythms and potential cardiac arrest.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE TOXICITY: Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

CHRONIC EFFECTS: Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impaired function from preexisting disorders may be aggravated by exposure to this product. The following organs and/or organ systems may be damaged by overexposure to the material. Heart, kidney, liver, auditory system. In severe cases death may result.

CARCINOGENICITY: Toluene is not known to be mutagenic or carcinogenic. However, the available human and experimental data are limited and insufficient to assess carcinogenic potential. Toluene is not listed as a carcinogen by NTP, IARC, or OSHA. Intentional abuse of toluene vapors has been linked to damage of brain, liver, kidney and to death. Many case studies involving abuse during pregnancy clearly indicate that toluene is a developmental toxicant. Developmental toxic effects comparable to those observed in humans have been seen in lab animals but the effects were generally associated with maternal toxicity.

REPRODUCTIVE TOXICITY

TERATOGENIC EFFECTS: Contains Methanol which has been established as a teratogen by inhalation. See Sec.11 for details.

MEDICAL CONDITIONS AGGRAVATED: Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product. Impaired function from preexisting disorders may be aggravated by exposure to this product. The following organs and/or organ systems may be aggravated and/or damaged by overexposure to the material. Heart, kidney, liver, auditory system, blood, nervous system, lungs. In severe cases death may result.

SENSITIZATION: While there is no evidence that industrially acceptable levels of toluene vapors (e.g., the TLV) have produced cardiac effects in humans, animal studies have shown that inhalation of high levels of toluene produced cardiac sensitization. Such sensitization may cause fatal changes in heart rhythms. This latter effect was shown to be enhanced by hypoxia or the injection of adrenalinlike agents. Prolonged and repeated exposures to high concentrations of toluene have resulted in hearing loss in laboratory rats. While the effect of solvents on the human auditory system is uncertain, solvent abusers exposed to high doses of toluene show signs of hearing loss, and occupational exposure to toluene may interact with noise in causing hearing loss in the work environment. The effects of solvents on human hearing are uncertain. Solvent abusers and noise interaction with toluene in the work environment may cause signs of hearing loss.

COMMENTS HEALTH: Male rats exposed for 90 days by inhalation to vapors of similar solvents showed evidence of kidney damage. The relevance of this effect to humans is unknown. In one of the studies a low grade anemia was also observed.

HEALTH HAZARDS: Light hydrocarbons like this one have been associated with cardiac sensitization in abuser situations. Hypoxia or the injection of adrenaline-like substances enhances these effects.

COMMENTS: Diacetone alcohol has caused liver damage and destruction of red blood cells after a single administration at high dosage levels (2ML/KG) to laboratory animals.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS	EINECS
Xylenes (o-,m-,p- isomers)	15 - 25	1330-20-7	215-535-7
Solvent naphtha (petroleum), medium aliphatic	5 - 15	64742-88-7	265-191-7
2-Propanol	5 - 15	67-63-0	200-661-0
Solvent naphtha, light aliphatic	55 - 60	64742-89-8	265-192-2
Diacetone alcohol	2 - 6	123-42-2	- -

COMMENTS: Xylene may contain ethyl benzene (100-41-4) at 1-4 % by wt., Toluene (108-88-3) at less than 1 % by wt. and benzene (71-43-2) at less than 0.01 % by wt. Solvent naphtha (petroleum), medium aliphatic contains the following constituents: Trimethylbenzene, 1,2,4,- (95-63-6); Butoxyethanol, 2- (111-76-2); Ethylene Glycol (107-21-1); Ethylene oxide (75-21-8). Solvent Naphtha, light aliphatic contains n-Heptane (CAS 142-82-5) and cyclohexane (CAS 110-82-7).

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision or swelling persist, contact a physician.

SKIN: Remove contaminated clothing/shoes. Wipe off excess material from exposed area. Flush with large amounts of water for at least 15 minutes, by the clock, and follow by washing with soap, if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment. Do not reuse clothing until cleaned.

INGESTION: If swallowed, DO NOT INDUCE vomiting. If conscious, have victim rinse mouth out with water, then drink sips of water to remove taste from mouth. DO NOT GIVE LIQUIDS TO A DROWSY, CONVULSING OR UNCONSCIOUS PERSON. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Transport to nearest medical facility for additional treatment.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

NOTES TO PHYSICIAN: Causes central nervous system depression. Dermatitis may result from prolonged or repeated exposure. Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: (65°F)

FLAMMABLE LIMITS: 0.009 to 0.127

EXTINGUISHING MEDIA: Use water fog or "alcohol" foam. Dry chemical powder, carbon dioxide, sand, or earth may be used for small fires only. Do not use a direct stream of water. Material will float and can be re-ignited on surface of water. To prevent frothing, do not use a water jet.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear fire area of unprotected

personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Product will float and can be reignited on surface water. Vapors are heavier than air. Vapors may travel across the ground and distant ignition is possible. Keep adjacent containers cool by spraying with water. Do not use water in a jet.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: For small liquid spills (less than 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

LARGE SPILL: For large liquid spills (greater than 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Under Section 311 of the Clean Water Act (CWA) this material is considered an oil. As such, spills into surface waters must be reported to the National Response Center at (800) 424-8802.

LAND SPILL: This material is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Petroleum Exclusion. Therefore, releases to the environment may not be reportable under CERCLA.

AIR SPILL: Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Vapor may form an explosive mixture with air. U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity to the National Response Center at (800) 424-8802.

GENERAL PROCEDURES: Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Section 8 of the Material Safety Data Sheet (MSDS). For guidance on disposal of spilled material see Section 13 of this MSDS. Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapor or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.

RELEASE NOTES: Reacts vigorously with strong oxidizers and acids.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid breathing of or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to risk assessment of local circumstances to help determine appropriate controls for safe handling storage and disposal of this material.

HANDLING: Avoid contact with skin, eyes, and clothing. Extinguish any naked flames. Do Not smoke. Remove ignition sources. Avoid sparks. The vapor is heavier than air, spreads along the ground and distant ignition is possible. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (less than or

equal to 1 m/sec until fill pipe submerged to twice its diameter, then less than or equal to 7 m/sec). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Handle an open container with care in a well-ventilated area. Ventilate workplace in such a way that the Permissible Exposure Limit is not exceeded. Do not empty into drains.

STORAGE: Must be stored in a diked, well-ventilated area, away from sunlight, ignition sources and other sources of heat. Bulk storage tanks should be diked.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Xylenes (o-,m-,p- isomers)	TWA	100	435	100	434		
	STEL			150	651		
2-Propanol	TWA	400	980	200	490	NL ^[1]	NL ^[1]
	STEL			400	960	NL	NL
Solvent naphtha, light aliphatic	TWA	[2]	[2]		350	100 ^[3]	400 ^[3]
Diacetone alcohol	TWA	50	240	50	238		
OSHA TABLE COMMENTS: 1. NL = Not Listed 2. Our supplier has adopted, as Interim Standards, the OSHA PELs that were established in 1989 and later rescinded. 3. In the absence of occupational exposure standards for this product, it is recommended that these values are adopted.							

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible.

Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific

conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for organic gases and vapors (boiling point greater than 65 degrees C (149 degrees F). Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

PROTECTIVE CLOTHING: Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: May be harmful or fatal if swallowed. May irritate body tissues. Use with adequate ventilation. Avoid breathing vapor. Do not get in eyes, on skin, on clothing. Wash thoroughly after handling.

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)	Auto Ignition (°C)	Solubility in Water	Specific Gravity
Xylenes (o-,m-,p- isomers)	27 TAG CC	ASTM D2155	Solubility negligible in water.	0.87
Solvent naphtha (petroleum), medium aliphatic	61 TAG CC		Solubility negligible in water.	
Solvent naphtha, light aliphatic	19		Solubility negligible in water.	0.743
Diacetone alcohol	129	643	Soluble	0.94

PHYSICAL STATE: Liquid

ODOR: Aromatic hydrocarbon odor.

COLOR: Clear, colorless liquid.

pH: Essentially neutral.

PERCENT VOLATILE: 100

BOILING POINT: (180°F) to (372°F)

FLASHPOINT AND METHOD: (65°F)

DENSITY: 6.456

SPECIFIC GRAVITY: 0.750 to 0.80

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

POLYMERIZATION: Will not occur under normal conditions.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with alkalies and strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

INCOMPATIBLE MATERIALS: Do not store near oxidizing agents or acidic material.

COMMENTS: Xylene will attack some forms of plastics, rubber and coatings.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Xylenes (o-,m-,p- isomers)	4300 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	6700 ppm / 4 hours (rat)
Solvent naphtha (petroleum), medium aliphatic	25000	> 4000	> 700
Solvent naphtha, light aliphatic	> 2000 mg/kg (Rat)	> 2000 mg/kg (rat)	> 5000 ppm / 1 hour (rat)

DERMAL LD₅₀: LD50 for Benzene, a constituent of Toluene: greater than 14000 mg/kg (rabbit). This product may contain benzene (CAS 71-43-2) at a concentration less than 300 ppm.

ORAL LD₅₀: LD50 for Benzene is 5,000 mg/kg (rat). This product may contain benzene (CAS 71-43-2) at a concentration less than 300 ppm.

INHALATION LC₅₀: Solvent naphtha, light aliphatic: Male rats exposed by prolonged and repeated inhalation to high vapor concentrations of similar solvents showed evidence of kidney damage. The relevance of this effect to humans is unknown.

CHRONIC: Laboratory studies have shown that petroleum distillates may cause kidney, liver, or lung damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

CARCINOGENICITY

Chemical Name	IARC Status
Xylenes (o-,m-,p- isomers)	3

IARC: While there is no evidence that industrially acceptable levels of toluene vapors (e.g., the TLV) have produced cardiac effects in humans, animal studies have shown that inhalation of high levels of toluene produced cardiac sensitization. Such sensitization may cause fatal changes in heart rhythms. This latter effect was shown to be enhanced by hypoxia or the injection of adrenalinlike agents. Prolonged and repeated exposures to high concentrations of toluene have resulted in hearing loss in laboratory rats. While the effect of solvents on the human auditory system is uncertain, solvent abusers exposed to high doses of toluene show signs of hearing loss, and occupational exposure to toluene may interact with noise in causing hearing loss in the work environment. The effects of solvents on human

hearing are uncertain. Solvent abusers and noise interaction with toluene in the work environment may cause signs of hearing loss.

Notes: This product may contain benzene (CAS No. 71-43-2) at a concentration less than 300 ppm.

SENSITIZATION: Repeat Dose Testing: While there is no evidence that industrially acceptable levels of light hydrocarbon vapors (e.g., the occupational exposure limit) have produced cardiac effects in humans, animals studies have shown that inhalation of high levels produced cardiac sensitization. Such sensitization may cause fatal changes in heart rhythms, which was shown to be enhanced by hypoxia or the injection of adrenaline-like substances.

REPRODUCTIVE EFFECTS: Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans. Methanol has caused birth defects in laboratory animals, but only when inhaled at extremely high vapor concentrations. The relevance of this finding to humans is uncertain.

MUTAGENICITY: Toluene is not known to be mutagenic or carcinogenic. However, the available human and experimental data are limited and insufficient to assess carcinogenic potential. Toluene is not listed as a carcinogen by NTP, IARC, or OSHA. Intentional abuse of toluene vapors has been linked to damage of brain, liver, kidney and to death. Many case studies involving abuse during pregnancy clearly indicate that toluene is a developmental toxicant. Developmental toxic effects comparable to those observed in humans have been seen in lab animals but the effects were generally associated with maternal toxicity.

COMMENTS: This product may contain benzene (CAS No. 71-43-2) and Toluene (CAS 108-88-3) at less than 1% weight. **Acute Toxicity for Xylene:** Dermal - LD50, results: Approximately 5 ml/kg (rabbit); Inhalation - LC50, results: 6700 ppm (v) (rat) 4 hour(s); Oral - LD50, results: 3.523 g/kg (rat). **Eye Irritation:** Draize - 9.0/110 (rabbit), skin irritation: Slight to moderate (rabbit). **Repeat Dose Testing:** While there is no evidence that industrially acceptable levels of light hydrocarbon vapors (e.g., the occupational exposure limit) have produced cardiac effects in humans, animals studies have shown that inhalation of high levels produced cardiac sensitization. Such sensitization may cause fatal changes in heart rhythms, which was shown to be enhanced by hypoxia or the injection of adrenaline-like substances. **Carcinogenicity:** Chronic inhalation exposure to 750 ppm ethyl benzene vapor produced increased incidences of renal tubular hyperplasia and neoplasma (males and females) and testicular adenomas in F344/N rats and alveolar/bronchiolar (males) and hepatocellular (females) neoplasma in B6C3F1 mice. Genetic toxicology studies found ethyl benzene not to be mutagenic or clastogenic. The relevance of these effects to humans are unclear. Ethylbenzene is listed by the IARC as a Group 2B - possible carcinogen. **Reproductive and Developmental Toxicity:** In developmental toxicity studies conducted in laboratory animals, there is no evidence of teratogenicity following inhalation exposure to xylene, but delayed development and behavioral impairments have been observed at doses levels causing no or only slight maternal toxicity. **Neurotoxicity:** Prolonged and repeated exposures to high concentrations of some volatile hydrocarbon solvents have resulted in hearing loss in rats. Solvent abusers and noise interaction with these solvents in the work environment may cause symptoms of hearing loss. Short term repeated inhalation exposure of humans to m-xylene (200 ppm or greater) was reported to produce slight impairment of vestibular and visual function and reaction time. In these studies, there was no evidence of cumulative effects but some evidence of tolerance or adaptation. **Other Information:** Over exposures of humans to xylene or xylene solvent mixtures produced predominated central nervous system (CNS) effects with less common effects reported to the lung, gastrointestinal tract, liver, kidney and heart. High exposures to xylene in some animal studies, often at levels toxic to the mother, affected embryo/fetal development. The significance of this finding to humans is not known. **Ethylbenzene Acute Data:** LD50 Oral Rat = 3500 mg/kg, LC50 Inhalation Rat = 4000 ppm for 4 hours, LD50 Dermal Rabbit = 17.8 mL/kg.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Absorbs to soil and has low mobility. Readily biodegradable. Oxidizes rapidly by photo-chemical reactions in air. Has the potential to bioaccumulate.

ECOTOXICOLOGICAL INFORMATION: VM&P Acute Toxicity:

Fish: Expected to be toxic: LC/EC/IC50 greater than or equal to 10 mg/l

Aquatic Invertebrates: Expected to be toxic: LC/EC/IC50 greater than or equal to 10 mg/l

Algae: Expected to be toxic: LC/EC/IC50 greater than or equal to 10 mg/l

Microorganisms: Expected to be toxic: LC/EC/IC50 greater than or equal to 10 mg/l

BIOACCUMULATION/ACCUMULATION: Has potential to bioaccumulate.

DISTRIBUTION: Mobility: Floats on water.

GENERAL COMMENTS: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

PRODUCT DISPOSAL: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Flammable Liquids, N.O.S.

TECHNICAL NAME: (Petroleum Naphtha, Xylenes)

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1993


PACKING GROUP: II

NAERG: 128

LABEL: Flammable liquid

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

Flammable Liquid

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes
CHRONIC: Yes

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt. %	CAS	Comments
Xylenes (o-,m-,p- isomers)	15 - 25	1330-20-7	
Solvent naphtha, light aliphatic	55 - 60	64742-89-8	Contains: Cyclohexane (110-82-7) 1.50% n-Hexane (110-54-3) 0.02%

TITLE III NOTES: This product contains Solvent naphtha, light aliphatic, which may contain the following constituents: heptane, n- (CAS 142-82-5) less than 2.5% by weight, methylcyclohexane (CAS 108-87-2) less than 2.5% by weight and cyclohexane (CAS 110-82-7) less than 1.5% by weight.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt. %	CERCLA RQ
Xylenes (o-,m-,p- isomers)	15 - 25	100

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Xylenes (o-,m-,p- isomers)	1330-20-7
Solvent naphtha (petroleum), medium aliphatic	64742-88-7
2-Propanol	67-63-0
Solvent naphtha, light aliphatic	64742-89-8
Diacetone alcohol	123-42-2

TSCA REGULATORY: All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following chemicals known to the State of California to cause cancer and reproductive toxicity:
Benzene, Toluene

GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. OTHER INFORMATION

REASON FOR ISSUE: Updated MSDS information and changed to new format.


PREPARED BY: E. MIRANDA

REVISION SUMMARY: New MSDS

HMIS RATING

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	H

NFPA CODES



HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the MSDS must be considered.

ADDITIONAL MSDS INFORMATION: Last revision 11/10/2003.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Tarr Acquisition, LLC (Tarr, LLC) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Tarr, LLC assumes no responsibility for injuries from the use of the product described herein.