

BS 0123



13400 SATICOY STREET  
NORTH HOLLYWOOD, CALIFORNIA 91605

# MATERIAL HEALTH AND SAFETY BULLETIN



## MANUFACTURER'S NAME

Wesmar Products, Inc  
1440 NW 45th St

## STREET ADDRESS

Seattle, Wa 98107  
(206)782-8186

## CITY, STATE, AND ZIP CODE

## EMERGENCY TELEPHONE NO.

PRODUCT: #123 VINYL-LEATHER CLEANER CONC. WARNING STATEMENT:

#506 VINYL-LEATHER CLEANER

GENERIC NAME:

CHEMICAL FAMILY:

DOT PROPER SHIPPING NAME:

COMPOUND, CLEANING, LIQUID

WARNING: CONCENTRATED ALKALINE SOLUTION  
FOR INDUSTRIAL USE ONLY. IN CASE OF  
SKIN CONTACT, FLUSH FREELY WITH WATER.  
FOR EYES, FLUSH FREELY WITH WATER AND  
OBTAIN MEDICAL ATTENTION.  
KEEP OUT OF REACH OF CHILDREN.

## Section I — INGREDIENTS

PHOSPHATE

ISOPROPANOL

CHELATING AGENT

CAUSTIC SODA

ETHYLENE GLYCOL BUTYL  
ETHER

TLV\*

400

50

CAS #10101-89-0

CAS #67-63-0

LESS THAN 1%

CAS #111-76-2 LESS THAN 3%

TLV\*

HMIS HAZARD INDEX

4 - Severe

3 - Serious

2 - Moderate

1 - Slight

0 - Minimal

HMIS RATINGS

Health.....1

Flammability..0

Reactivity.....0

\*Threshold Limit Value

A. OSHA ☒

B. ACGIH ☐

C. See Section III ☐

D. Other ☐

## Section II —EMERGENCY AND FIRST AID PROCEDURES

EMERGENCY: Have a physician call LOS ANGELES POISON CONTROL CENTER (24 hrs.) 213/664-2121

|              |                                                                                                                                                                                                                                                                                                                                                                            |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye Contact  | If this product comes in contact with the eyes, flush with large quantities of water for at least 15 minutes and seek immediate medical attention.                                                                                                                                                                                                                         |
| Skin Contact | If this product comes in contact with the skin, wash with large quantities of water and seek medical attention if irritation from contact persists.                                                                                                                                                                                                                        |
| Inhalation   | If breathing difficulties, dizziness, or lightheadedness occur when working in the areas with high vapor concentrations, victim should seek air free of vapors. If victim experiences continued breathing difficulties, administer oxygen until medical assistance can be rendered. If breathing stops, begin artificial respiration and seek immediate medical attention. |
| Ingestion    | If this product is swallowed, DO NOT induce vomiting, drink water or milk and seek immediate medical advice and/or attention.                                                                                                                                                                                                                                              |

## Section III — PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

|                  |                                                                                                                                                             |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye Effects      | This is an eye irritant, and may cause a chemical burn.                                                                                                     |
| Skin Effects     | Prolonged or repeated skin contact may result in dermatitis or chemical burn.                                                                               |
| Systemic Effects | Various studies have shown a possible association with exposure to this product and the following:<br>Nausea and vomiting.<br>Respiratory tract irritation. |

**Section IV — SPECIAL PROTECTION INFORMATION**

|                                        |                                                                                                                                                                                                                                                                                                                                                                                         |                |                                                                                                                                         |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Respiratory Protection<br>Specify Type | The use of respiratory protection depends on vapor concentration above the time-weighted TLV; use of a NIOSH approved cartridge respirator or gas mask.                                                                                                                                                                                                                                 |                |                                                                                                                                         |
| Ventilation                            | General mechanical ventilation may be sufficient to keep product vapor concentrations within specified time-weighted TLV ranges. If general ventilation proves inadequate to maintain safe vapor concentrations, supplemental local exhaust may be required. Other special precautions such as respiratory masks or environmental containment devices may be required in extreme cases. |                |                                                                                                                                         |
| Protective Gloves                      | The use of impermeable gloves is advised to prevent skin irritation in sensitive individuals.                                                                                                                                                                                                                                                                                           | Eye protection | Safety glasses, chemical goggles and/or face shields are recommended to safeguard against potential eye contact, irritation, or injury. |
| Other Protective Equipment             | Impermeable aprons are advised when working with this product. The availability of eye washes and safety showers in work areas is recommended.                                                                                                                                                                                                                                          |                |                                                                                                                                         |

**Section V — REACTIVITY DATA**

|                                            |                                                                                               |   |                      |
|--------------------------------------------|-----------------------------------------------------------------------------------------------|---|----------------------|
| Stability                                  | Unstable                                                                                      |   | Conditions to Avoid: |
|                                            | Stable                                                                                        | X |                      |
| Incompatibility<br>(Materials<br>to Avoid) | This product is incompatible with:<br><br>Anhydride, Isocyanate, Organometallic Contaminants. |   |                      |
| Hazardous<br>Decomposition<br>Products     | Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide. |   |                      |
| Hazardous<br>Polymerization                | May Occur                                                                                     |   | Conditions to Avoid: |
|                                            | Will Not Occur                                                                                | X |                      |

**Section IV — SPILL OR LEAK PROCEDURES****HIGHWAY OR RAILWAY SPILLS—CALL CHEMTREC 800/424-9300**

|                                         |                                                                                                                                                                                                                                                              |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautions In Case Of Release or Spill | Keep sources of ignition and hot metal surfaces isolated from the spill. Flush spilled material into suitable retaining areas or containers with large quantities of water. Small amounts of spilled material may be absorbed into an appropriate absorbant. |
| Reportable Quantity                     | Notify Coast Guard National Response Center; Phone No. 800-424-8802, If Spill Is Greater Than <u>      </u> lbs. (Kilograms)                                                                                                                                 |
| Waste Disposal Method                   | Dispose of the product in accordance with applicable local, county, state and federal regulations.                                                                                                                                                           |

**Section VII — STORAGE AND SPECIAL PRECAUTIONS**

|                                  |                                                                                                                                                                                                                                                 |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Handling and Storing Precautions | Keep product containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. (See Section IV).                                                                                                    |
| Other Precautions                | Personnel should avoid inhalation of vapors (See Sections I, II, III, V, VI). Personal contact with product should be avoided. Should contact be made, remove saturated clothing and flush affected areas with water (See Sections II, IV, VI). |

**Section VIII — FIRE AND EXPLOSION HAZARD DATA**

|                                    |                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                           |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOT Flammability Classification    | NON-FLAMMABLE                                                                                                                                                                                                                                            | Flash Point Range: <input type="checkbox"/> Below 20° F, <input type="checkbox"/> 20° F - 100° F<br><input type="checkbox"/> 100° F - 200° F, <input checked="" type="checkbox"/> Over 200° F<br><input type="checkbox"/> None to boiling |
| Extinguishing Media                | Use foam, CO <sub>2</sub> or dry chemical fire fighting apparatus.                                                                                                                                                                                       |                                                                                                                                                                                                                                           |
| Unusual Fire and Explosion Hazards | Keep work areas free of hot metal surfaces and other sources of ignition.                                                                                                                                                                                |                                                                                                                                                                                                                                           |
| Fire Fighting Procedures           | The use of self-contained breathing apparatus is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used for cooling purposes. |                                                                                                                                                                                                                                           |

**Section IX — PHYSICAL DATA**

|                                                                                                              |               |                                                                                                         |
|--------------------------------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------------------------|
| Approximate Boiling Range, ° F                                                                               | NON-FLAMMABLE | Vapor Density: <input checked="" type="checkbox"/> Heavier Than Air<br><input type="checkbox"/> Lighter |
| Evaporation Rate: <input type="checkbox"/> Faster Than Ether<br><input checked="" type="checkbox"/> Slower   |               | Percent Volatile: Less than 5%<br>Solubility in Water: YES                                              |
| Specific Gravity: <input type="checkbox"/> Lighter Than Water<br><input checked="" type="checkbox"/> Heavier |               | Weight per Gallon. 9-LBS.                                                                               |
| Appearance and Odor: Yellow or green in color with a characteristic odor.                                    |               |                                                                                                         |

**Section X — DOCUMENTARY INFORMATION**

Product Code No. #123 #506 Issue Date 06/01/04 Prepared By D. KLINGGERMAN

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

The information in this document is believed to be correct as of the date issued.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.