

CA 1312

MATERIAL SAFETY DATA SHEET

Page 001
Date Prepared: 03/22/06
Date Printed: 06/05/06
MSDS No: 525.0408197-002.001

XTRA-DUTY AERO #0170-020CB 12/1 CS

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: XTRA-DUTY AERO #0170-020CB 12/1 CS
SAP Material No: CBOOE006-18

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Telephone Number
Emergency: 1-800-274-5263

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
LIQUIFIED PETROLEUM GAS, SWEETENED	68476-86-8	2.5- 13.0
2-BUTOXYETHANOL	111-76-2	1.0- 8.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye
Can cause eye irritation.

Skin
May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin. Passage through the skin may add to toxic effects from breathing or swallowing.

Swallowing
Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation
Breathing aerosol and/or mist is possible when material is sprayed. Aerosol and mist may present a greater risk of injury because more material may be present in the air than from vapor alone. Breathing this material may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), difficult breathing, blood in the urine, blood abnormalities (breakage of red blood cells), kidney damage, liver damage, coma, and death.

Target Organ Effects
Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities.

Continued on next page

MATERIAL SAFETY DATA SHEET

Page 002
Date Prepared: 03/22/06
Date Printed: 06/05/06
MSDS No: 525.0408197-002.001

XTRA-DUTY AERO #0170-020CB 12/1 CS

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration. Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (for example, asthma-like conditions), liver, kidneys, blood-forming system.

5. FIRE FIGHTING MEASURES

Flash Point

.0 F (-17.7 C)

Continued on next page

MATERIAL SAFETY DATA SHEET

Page 003
Date Prepared: 03/22/06
Date Printed: 06/05/06
MSDS No: 525.0408197-002.001

XTRA-DUTY AERO #0170-020CB 12/1 CS

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

No data

Extinguishing Media

alcohol foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 2, Flammability - 1, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Do not puncture or incinerate containers. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot organic chemical vapors or

Continued on next page

MATERIAL SAFETY DATA SHEET

Page 004
Date Prepared: 03/22/06
Date Printed: 06/05/06
MSDS No: 525.0408197-002.001

XTRA-DUTY AERO #0170-020CB 12/1 CS

mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in a cool, dry, ventilated area away from sources of heat, moisture, and incompatible substances. Under oxidation conditions, peroxides may be formed. If they become concentrated, these peroxides may present an explosion hazard.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

LIQUIFIED PETROLEUM GAS, SWEETENED (68476-86-8)
No exposure limits established

2-BUTOXYETHANOL (111-76-2)
OSHA VPEL 25.000 ppm - TWA ((Skin))
ACGIH TLV 20.000 ppm - TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

Page 005
Date Prepared: 03/22/06
Date Printed: 06/05/06
MSDS No: 525.0408197-002.001

XTRA-DUTY AERO #0170-020CB 12/1 CS

Vapor Pressure
(for product) .000

Specific Vapor Density
No data

Specific Gravity
No data

Liquid Density
No data

Percent Volatiles (Including Water)
No data

Evaporation Rate
No data

Appearance
No data

State
No data

Physical Form
No data

Color
No data

Odor
No data

pH
No data

10. STABILITY AND REACTIVITY

Hazardous Polymerization
Product will not undergo hazardous polymerization.

Hazardous Decomposition
May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability
Stable.

Incompatibility
Avoid contact with: aluminum, heat, salts of strong bases, strong acids, strong alkalies, strong oxidizing agents.

Continued on next page

MATERIAL SAFETY DATA SHEET

Page 006
Date Prepared: 03/22/06
Date Printed: 06/05/06
MSDS No: 525.0408197-002.001

XTRA-DUTY AERO #0170-020CB 12/1 CS

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Container/Mode:

CASES/SURFACE - ORM-D EXCEPTION

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire() Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)

CAS Number

2-BUTOXYETHANOL

111-76-2

Continued on next page

MATERIAL SAFETY DATA SHEET

Page 007
Date Prepared: 03/22/06
Date Printed: 06/05/06
MSDS No: 525.0408197-002.001

XTRA-DUTY AERO #0170-020CB 12/1 CS

International Regulations
Inventory Status
Not determined

State and Local Regulations
California Proposition 65
None

New Jersey RTK Label Information
2-BUTOXY ETHANOL 111-76-2

Pennsylvania RTK Label Information
ETHANOL, 2-BUTOXY- 111-76-2

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.