

CA 1314

ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE
COMPANY/UNDERTAKING**

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Emergency telephone number 1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® AEROSOL GLASS CLEANER GLASS CLEANER
Product code	CBOOE009-18
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: aerosol

WARNING! Toxic by inhalation, Toxic by ingestion, Toxic by skin absorption,
Moderate skin irritant, Moderate eye irritant, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin Contact

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, and may add to toxic effects from breathing or swallowing.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

Breathing of vapor or mist is possible. Breathing this material may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, central nervous system, pancreas, blood-forming system, male reproductive system. Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), involuntary eye movement, respiratory depression (slowing of the breathing rate), loss of coordination, confusion, difficult breathing, irregular heartbeat, blood in the urine, blood abnormalities (breakage of red blood cells), anesthesia, kidney damage, liver damage, respiratory failure, coma, and death.

Target Organs

This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of these findings to ethanol exposure in industrial environments is uncertain. Acute lethal exposure to ethylene glycol monobutyl ether in animal studies has resulted in congestion of organs including kidney, spleen, and lung. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible kidney effects, blood abnormalities, pancreatic damage, liver damage, brain damage, testis damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: liver damage.

Carcinogenicity

This product contains ethanol. The International Agency for Research on Cancer (IARC) has determined that exposure to ethanol through chronic human consumption of alcoholic beverages can cause cancer. The relevance of this finding to ethanol exposure in industrial environments is uncertain. Ethylene glycol monobutyl ether has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain.

Reproductive Hazard

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain., This product contains ethanol. Alcoholic beverage consumption has been associated with birth defects in humans. The relevance of this finding to ethanol exposure in industrial environments is uncertain.

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
ETHANOL	64-17-5	>=5-<10%
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	>=5-<10%
ISOBUTANE	75-28-5	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

alcohol-resistant foam, carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

No data

Precautions for Fire-Fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

No data

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or repeated contact. Do not

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

puncture or incinerate containers. Under oxidation conditions, peroxides may be formed. If they become concentrated, these peroxides may present an explosion hazard.

Storage

Keep containers closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

BUTANE NORMAL		106-97-8
NIOSH	Recommended exposure limit (REL):	800 ppm
NIOSH	Recommended exposure limit (REL):	1,900 mg/m3
OSHA Z1A	time weighted average	800 ppm
OSHA Z1A	time weighted average	1,900 mg/m3
US CA OEL	Time Weighted Average (TWA)	800 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	1,900 mg/m3
	Permissible Exposure Limit (PEL):	
ETHANOL		64-17-5
ACGIH	time weighted average	1,000 ppm
NIOSH	Recommended exposure limit (REL):	1,000 ppm
NIOSH	Recommended exposure limit (REL):	1,900 mg/m3
OSHA Z1	Permissible exposure limit	1,000 ppm
OSHA Z1	Permissible exposure limit	1,900 mg/m3
PROPANE		74-98-6
NIOSH	Recommended exposure limit (REL):	1,000 ppm
NIOSH	Recommended exposure limit (REL):	1,800 mg/m3
OSHA Z1	Permissible exposure limit	1,000 ppm
OSHA Z1	Permissible exposure limit	1,800 mg/m3
OSHA Z1A	time weighted average	1,000 ppm
OSHA Z1A	time weighted average	1,800 mg/m3
US CA OEL	Time Weighted Average (TWA)	1,000 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	1,800 mg/m3
	Permissible Exposure Limit (PEL):	
ACGIH	time weighted average	1,000 ppm
ETHYLENE GLYCOL MONOBUTYL ETHER		111-76-2

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	5 ppm
NIOSH	Recommended exposure limit (REL):	24 mg/m3
OSHA Z1	Permissible exposure limit	50 ppm
OSHA Z1	Permissible exposure limit	240 mg/m3

ISOBUTANE 75-28-5

NIOSH	Recommended exposure limit (REL):	800 ppm
NIOSH	Recommended exposure limit (REL):	1,900 mg/m3
ACGIH	time weighted average	1,000 ppm

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV(s).

Eye Protection

Not required under normal conditions of use.

Skin and Body Protection

Not required under normal conditions of use.

Respiratory Protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	aerosol
Form	No data
Colour	No data
Odour	No data
Boiling point/range	No data
pH	No data

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	No data
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with:, acids, alkalis, reducing agents, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

ETHANOL	LD 50 Rat: 7,060 mg/kg
ETHYLENE GLYCOL MONOBUTYL	LD 50 Rat: 470 mg/kg

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

ETHER

Acute Inhalation Toxicity

ETHANOL	LC 50 Rat: 20000 ppm, 10 h
ETHYLENE GLYCOL MONOBUTYL ETHER	LC 50 Rat: 450 ppm, 4 h
ISOBUTANE	LC 50 Mouse: 520000 ppm, 2 h

Acute Dermal Toxicity

ETHANOL	LD Lo Rabbit: 20 g/kg
ETHYLENE GLYCOL MONOBUTYL ETHER	LD 50 Rabbit: 220 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

14. TRANSPORT INFORMATION

IMDG:

UN1950, AEROSOLS 2.1,

IATA_P:

UN1950, Aerosols, flammable 2.1,

IATA_C:

UN1950, Aerosols, flammable 2.1,

CFR_ROAD:

UN1950, Aerosols 2.1,

CFR_RAIL:

UN1950, Aerosols 2.1,

CFR_INWTR:

UN1950, Aerosols 2.1,

IMDG_INWTR:

UN1950, AEROSOLS 2.1,

IMDG_ROAD:

UN1950, AEROSOLS 2.1,

IMDG_RAIL:

UN1950, AEROSOLS 2.1,

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

SARA Hazard Classification Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards Toxic by inhalation
Toxic by ingestion
Toxic by skin absorption
Moderate skin irritant
Moderate eye irritant

ASHLAND
SAFETY DATA SHEET

Page: 10
Revision Date: 04/04/2007
Print Date: 4/24/2007
MSDS Number: R0408203
Version: 1.

CAR BRITE® AEROSOL GLASS
CLEANER GLASS CLEANER
CBOOE009-18

Carcinogen

	Health	Flammability	Reactivity	Other
HMIS				No data
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).