

CA 1330



Material Safety Data Sheet

HMIS Ratings
 Health 1
 Flammability 4
 Reactivity 0
 Protection X

1 Chemical Product and Company Identification

Manufacturer Information Wesmar Products, Inc
 1440 NW 45th St
 Seattle, WA 98107
Phone (206) 782-8186
Emergency Phone 1-800-424-9300
 FOR INTERNATIONAL
 CALLS
 703-527-3887
Date Prepared 2002-Oct-16
Supersedes 2002-Oct-10
Product Identity RUBBERIZED AEROSOL UNDERCOAT
Product Code Number G012
Product Use Automotive Reconditioning Products
Version # 1.0
CAS # Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	Exposure Limits		Carcinogen
			PEL-OSHA	TLV-ACGIH	
SOLVENT NAPHTHA, PETROLEUM, LIGHT ALIPH.	64742-89-8	20 - 25			No
LIMESTONE	1317-65-3	20 - 25	15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction	10 mg/m3 TWA particulate matter containing no asbestos and <1% crystalline silica	No
PROPANE	74-98-6	12.5 - 15	1000 ppm TWA; 1800 mg/m3 TWA	2500 ppm TWA	No
BUTANE	106-97-8	12.5 - 15	800 ppm TWA; 1900 mg/m3 TWA	800 ppm TWA	No
BENZENE, METHYL-	108-88-3	10 - 15	100 ppm TWA; 375 mg/m3 TWA	50 ppm TWA	No
Non-hazardous and other ingredients below reportable levels	Proprietary	15	N/AP	N/AP	N/AP

3 Hazards Identification

Potential Health Effects

Skin Prolonged or repeated contact with this product may dry and/or defat the skin.

Potential Health Effects

Eyes	This product may be severely irritating to the eyes. Symptoms include itching, burning, redness and tearing.
Inhalation	This product may cause irritation to the respiratory system. Excessive inhalation of this product may cause headache, dizziness, blurred vision, nausea and vomiting.
Ingestion	Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazard Statements

EXTREMELY FLAMMABLE
CONTENTS UNDER PRESSURE.

4 First Aid Measures

First Aid

Skin	For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen.
Ingestion	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Alcohol foam. Carbon dioxide. Dry chemical.

General Fire Hazards

Pressurized Container: May explode when exposed to heat or flame.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Flash Point	Extremely flammable per 16CFR 1500.45
Flammability Limits in Air, Lower, % by Volume	1.8 % (propellant)
Flammability Limits in Air, Upper, % by Volume	9.2 % (propellant)

6 Accidental Release Measures

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Keep this product from heat, sparks, or open flame.

Storage Procedures

Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Do not freeze.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of aerosols or mists, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material.

9 Physical & Chemical Properties

Specific Gravity	< 1
Vapor Pressure	90 psig
Evaporation Rate	< 1
Vapor Density	> 1

10 Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

None known.

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

US DOT HMR Information

Proper Shipping Name	Consumer commodity
Hazard Class	ORM-D

15 Regulatory Information

US Federal Regulations

CERCLA/SARA - Section 313 - Emission Reporting

2-PROPANOL
BENZENE, METHYL-
ETHANOL, 2-BUTOXY-

16 Other Information

Prepared By	Technical Department
Issue Date	16-Oct-2002