

CA 2031  
**ASHLAND**  
**SAFETY DATA SHEET**

Page: 1  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

Wesmar Products, Inc  
1440 NW 45th ST  
Seattle, WA 98107  
(206) 782-8186

Emergency telephone number

1-800-ASHLAND  
(1-800-274-5263)

|                         |                                  |
|-------------------------|----------------------------------|
| Product name            | CAR BRITE® CB C/V DYE KHAKI DYES |
| Product code            | CBOOG014-0031                    |
| Product Use Description | No data                          |

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: aerosol  
DANGER! Toxic by inhalation, Moderate skin irritant, Severe eye irritant, Carcinogen.

**Potential Health Effects**

**Routes of Exposure**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

**Eye Contact**

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

**Skin Contact**

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Passage of this material into the body through the skin is possible, and may add to toxic effects from breathing or swallowing.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

**Inhalation**

# ASHLAND

## SAFETY DATA SHEET

Page: 2  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

### Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidney, central nervous system, male reproductive system, auditory system. Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias. Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

### Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), tight feeling in the chest, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, muscle weakness, respiratory depression (slowing of the breathing rate), blurred vision, shortness of breath, loss of coordination, confusion, irregular heartbeat, high blood sugar, narcosis (dazed or sluggish feeling), coma, and death.

### Target Organs

This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Based on animal studies, exposure to methyl ethyl ketone (MEK) increases the onset of peripheral neuropathy caused by exposure to methyl butyl ketone (MBK), and/or n-hexane, and/or ethyl butylketone. MEK alone has not been shown to cause peripheral neuropathy. Prolonged intentional toluene abuse may lead to damage to many organ systems having effects on: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: cardiac sensitization, anemia, respiratory tract damage (nose, throat, and airways), testis damage, kidney damage, liver damage, lung damage, effects on hearing, central nervous system damage. Overexposure to this material (or its components) has been suggested as a cause

# ASHLAND

## SAFETY DATA SHEET

Page: 3  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

of the following effects in humans:; central nervous system effects, cardiac sensitization, anemia, effects on hearing, kidney damage

### Carcinogenicity

Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. The International Agency for Research on Cancer (IARC) has classified ethylbenzene as a possible human carcinogen.

### Reproductive Hazard

Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans.

### Other Information

No data

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components          | CAS-No.    | Concentration |
|---------------------|------------|---------------|
| ACETONE             | 67-64-1    | >=20-<30%     |
| TOLUENE             | 108-88-3   | >=15-<20%     |
| METHYL ETHYL KETONE | 78-93-3    | >=10-<15%     |
| BUTANOL NORMAL      | 71-36-3    | >=5-<10%      |
| TALC                | 14807-96-6 | >=5-<10%      |
| CALCIUM CARBONATE   | 1317-65-3  | >=5-<10%      |
| XYLENE              | 1330-20-7  | >=1.5-<5%     |
| ETHYL BENZENE       | 100-41-4   | >=1-<1.5%     |

## 4. FIRST AID MEASURES

### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

### Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

### Ingestion

# ASHLAND

## SAFETY DATA SHEET

Page: 4  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

### Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

### Notes to Physician

**Hazards:** Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

**Treatment:** No information available.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Water mist, carbon dioxide (CO<sub>2</sub>), dry chemical

### Hazardous Combustion Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

### Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

# ASHLAND

## SAFETY DATA SHEET

Page: 5  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

### Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

### Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

## 7. HANDLING AND STORAGE

### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

### Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

| ACETONE |                            | 67-64-1     |
|---------|----------------------------|-------------|
| ACGIH   | time weighted average      | 500 ppm     |
| ACGIH   | Short term exposure limit  | 750 ppm     |
| NIOSH   | Recommended exposure limit | 250 ppm     |
|         | (REL):                     |             |
| NIOSH   | Recommended exposure limit | 590 mg/m3   |
|         | (REL):                     |             |
| OSHA Z1 | Permissible exposure limit | 1,000 ppm   |
| OSHA Z1 | Permissible exposure limit | 2,400 mg/m3 |

# ASHLAND

## SAFETY DATA SHEET

Page: 6  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

| <b>TOLUENE</b>             |                                                     | <b>108-88-3</b>   |                      |
|----------------------------|-----------------------------------------------------|-------------------|----------------------|
| ACGIH NIC                  | time weighted average                               | 20 ppm            |                      |
| ACGIH                      | time weighted average                               | 50 ppm            |                      |
| NIOSH                      | Recommended exposure limit (REL):                   | 100 ppm           |                      |
| NIOSH                      | Recommended exposure limit (REL):                   | 375 mg/m3         |                      |
| NIOSH                      | Short term exposure limit                           | 150 ppm           |                      |
| NIOSH                      | Short term exposure limit                           | 560 mg/m3         |                      |
| OSHA Z2                    | time weighted average                               | 200 ppm           |                      |
| OSHA Z2                    | Ceiling Limit Value:                                | 300 ppm           |                      |
| OSHA Z2                    | Maximum concentration:                              | 500 ppm           |                      |
| <b>METHYL ETHYL KETONE</b> |                                                     | <b>78-93-3</b>    |                      |
| ACGIH                      | time weighted average                               | 200 ppm           |                      |
| ACGIH                      | Short term exposure limit                           | 300 ppm           |                      |
| NIOSH                      | Recommended exposure limit (REL):                   | 200 ppm           |                      |
| NIOSH                      | Recommended exposure limit (REL):                   | 590 mg/m3         |                      |
| NIOSH                      | Short term exposure limit                           | 300 ppm           |                      |
| NIOSH                      | Short term exposure limit                           | 885 mg/m3         |                      |
| OSHA Z1                    | Permissible exposure limit                          | 200 ppm           |                      |
| OSHA Z1                    | Permissible exposure limit                          | 590 mg/m3         |                      |
| <b>BUTANOL NORMAL</b>      |                                                     | <b>71-36-3</b>    |                      |
| ACGIH                      | time weighted average                               | 20 ppm            |                      |
| NIOSH                      | Ceiling Limit Value and Time Period (if specified): | 50 ppm            |                      |
| NIOSH                      | Ceiling Limit Value and Time Period (if specified): | 150 mg/m3         |                      |
| OSHA Z1                    | Permissible exposure limit                          | 100 ppm           |                      |
| OSHA Z1                    | Permissible exposure limit                          | 300 mg/m3         |                      |
| OSHA Z1A                   | Ceiling Limit Value:                                | 50 ppm            |                      |
| OSHA Z1A                   | Ceiling Limit Value:                                | 150 mg/m3         |                      |
| US CA OEL                  | Ceiling Limit Value:                                | 50 ppm            |                      |
| US CA OEL                  | Ceiling Limit Value:                                | 150 mg/m3         |                      |
| <b>TALC</b>                |                                                     | <b>14807-96-6</b> |                      |
| ACGIH                      | time weighted average                               | 2 mg/m3           | Respirable fraction. |
| NIOSH                      | Recommended exposure limit (REL):                   | 2 mg/m3           | Respirable.          |
| OSHA Z1A                   | time weighted average                               | 2 mg/m3           | Respirable dust.     |
| Z3                         | time weighted average                               | 0.1 mg/m3         | Respirable.          |
| Z3                         | time weighted average                               | 0.3 mg/m3         | Total dust.          |
| US CA OEL                  | Time Weighted Average (TWA)                         | 2 mg/m3           | Respirable dust.     |
|                            | Permissible Exposure Limit (PEL):                   |                   |                      |
| <b>CALCIUM CARBONATE</b>   |                                                     | <b>1317-65-3</b>  |                      |
| NIOSH                      | Recommended exposure limit (REL):                   | 5 mg/m3           | Respirable.          |
| NIOSH                      | Recommended exposure limit (REL):                   | 10 mg/m3          | Total                |

# ASHLAND

## SAFETY DATA SHEET

Page: 7  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

|           |                                   |          |                      |
|-----------|-----------------------------------|----------|----------------------|
| NIOSH     | Recommended exposure limit (REL): | 5 mg/m3  | Respirable.          |
| NIOSH     | Recommended exposure limit (REL): | 10 mg/m3 | Total                |
| NIOSH     | Recommended exposure limit (REL): | 5 mg/m3  | Respirable.          |
| NIOSH     | Recommended exposure limit (REL): | 10 mg/m3 | Total                |
| OSHA Z1   | Permissible exposure limit        | 5 mg/m3  | Respirable fraction. |
| OSHA Z1   | Permissible exposure limit        | 5 mg/m3  | Respirable fraction. |
| OSHA Z1   | Permissible exposure limit        | 15 mg/m3 | Total dust.          |
| OSHA Z1   | Permissible exposure limit        | 15 mg/m3 | Total dust.          |
| OSHA Z1   | Permissible exposure limit        | 5 mg/m3  | Respirable fraction. |
| OSHA Z1   | Permissible exposure limit        | 15 mg/m3 | Total dust.          |
| OSHA Z1A  | time weighted average             | 5 mg/m3  | Respirable fraction. |
| OSHA Z1A  | time weighted average             | 15 mg/m3 | Total dust.          |
| OSHA Z1A  | time weighted average             | 5 mg/m3  | Respirable fraction. |
| OSHA Z1A  | time weighted average             | 15 mg/m3 | Total dust.          |
| OSHA Z1A  | time weighted average             | 5 mg/m3  | Respirable fraction. |
| OSHA Z1A  | time weighted average             | 15 mg/m3 | Total dust.          |
| US CA OEL | Time Weighted Average (TWA)       | 5 mg/m3  | Respirable fraction. |
|           | Permissible Exposure Limit (PEL): |          |                      |
| US CA OEL | Time Weighted Average (TWA)       | 10 mg/m3 | Total dust.          |
|           | Permissible Exposure Limit (PEL): |          |                      |
| US CA OEL | Time Weighted Average (TWA)       | 10 mg/m3 | Total dust.          |
|           | Permissible Exposure Limit (PEL): |          |                      |
| US CA OEL | Time Weighted Average (TWA)       | 5 mg/m3  | Respirable fraction. |
|           | Permissible Exposure Limit (PEL): |          |                      |

### XYLENE

1330-20-7

|         |                                   |           |
|---------|-----------------------------------|-----------|
| ACGIH   | time weighted average             | 100 ppm   |
| ACGIH   | Short term exposure limit         | 150 ppm   |
| OSHA Z1 | Permissible exposure limit        | 100 ppm   |
| OSHA Z1 | Permissible exposure limit        | 435 mg/m3 |
| NIOSH   | Recommended exposure limit (REL): | 100 ppm   |
| NIOSH   | Recommended exposure limit (REL): | 435 mg/m3 |
| NIOSH   | Short term exposure limit         | 150 ppm   |
| NIOSH   | Short term exposure limit         | 655 mg/m3 |
| NIOSH   | Recommended exposure limit (REL): | 100 ppm   |
| NIOSH   | Recommended exposure limit (REL): | 435 mg/m3 |
| NIOSH   | Short term exposure limit         | 150 ppm   |
| NIOSH   | Short term exposure limit         | 655 mg/m3 |
| NIOSH   | Recommended exposure limit (REL): | 100 ppm   |
| NIOSH   | Recommended exposure limit (REL): | 435 mg/m3 |
| NIOSH   | Short term exposure limit         | 150 ppm   |

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

|                      |                                      |           |
|----------------------|--------------------------------------|-----------|
| NIOSH                | Short term exposure limit            | 655 mg/m3 |
| <b>ETHYL BENZENE</b> | <b>100-41-4</b>                      |           |
| ACGIH                | time weighted average                | 100 ppm   |
| ACGIH                | Short term exposure limit            | 125 ppm   |
| NIOSH                | Recommended exposure limit<br>(REL): | 100 ppm   |
| NIOSH                | Recommended exposure limit<br>(REL): | 435 mg/m3 |
| NIOSH                | Short term exposure limit            | 125 ppm   |
| NIOSH                | Short term exposure limit            | 545 mg/m3 |
| OSHA Z1              | Permissible exposure limit           | 100 ppm   |
| OSHA Z1              | Permissible exposure limit           | 435 mg/m3 |

## General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

## Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

## Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

## Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Other protective equipment: eyewash station, emergency shower.

## Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                |         |
|----------------|---------|
| Physical state | aerosol |
|----------------|---------|



# ASHLAND

## SAFETY DATA SHEET

Page: 9  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

|                                         |                                    |
|-----------------------------------------|------------------------------------|
| Form                                    | aerosol,                           |
| Colour                                  | No data                            |
| Odour                                   | No data                            |
| Boiling point/range                     | No data                            |
| pH                                      | No data                            |
| Flash point                             | No data                            |
| Evaporation rate                        | No data                            |
| Explosion limits                        | 1.0 %(V) 12.8 %(V)                 |
| Vapour pressure                         | 85.0000 mmHg @ 60.00 °F / 15.56 °C |
| Vapour density                          | No data                            |
| Density                                 | < 1 g/cm3 @ 59.9 °F / 15.5 °C      |
|                                         | No data                            |
| Solubility                              | No data                            |
| Partition coefficient (n-octanol/water) | No data                            |
| Autoignition temperature                | No data                            |

### 10. STABILITY AND REACTIVITY

#### Stability

Stable.

#### Conditions to Avoid

Avoid contact with:

#### Incompatible Products

Avoid contact with:, strong oxidizing agents

#### Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, various hydrocarbons

#### Hazardous Reactions

Product will not undergo hazardous polymerization.

#### Thermal Decomposition

No data

### 11. TOXICOLOGICAL INFORMATION

#### Acute Oral Toxicity

# ASHLAND

## SAFETY DATA SHEET

Page: 10  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

|                     |                                                      |
|---------------------|------------------------------------------------------|
| ACETONE             | LD 50 Rat: 5,800 mg/kg                               |
| TOLUENE             | LD 50 Rat: 5,000 mg/kg                               |
| METHYL ETHYL KETONE | LD 50 Mouse: 670 mg/kgLD 50 Rat: 2,300 - 3,500 mg/kg |
| BUTANOL NORMAL      | LD 50 Rat: 790 mg/kg                                 |
| XYLENE              | LD 50 Rat: 4,300 mg/kg                               |
| ETHYL BENZENE       | LD 50 Rat: 3,500 mg/kg                               |

### Acute Inhalation Toxicity

|                     |                             |
|---------------------|-----------------------------|
| ACETONE             | LC 50 Rat: 16000 ppm, 4 h   |
| TOLUENE             | LC 50 Rat: 8000 ppm, 4 h    |
| METHYL ETHYL KETONE | LC 50 Rat: 11,700 mg/l, 4 h |
| ETHYL BENZENE       | LC Lo Rat: 4000 ppm, 4 h    |

### Acute Dermal Toxicity

|                     |                            |
|---------------------|----------------------------|
| ACETONE             | LD 50 Rabbit: 20,000 mg/kg |
| TOLUENE             | LD 50 Rabbit: 12,124 mg/kg |
| METHYL ETHYL KETONE | LD 50 Rabbit: 5 g/kg       |
| BUTANOL NORMAL      | LD 50 Rabbit: 3,400 mg/kg  |
| XYLENE              | LD 50 Rabbit: 2,000 mg/kg  |
| ETHYL BENZENE       | LD 50 Rabbit: 15,433 mg/kg |

# ASHLAND

## SAFETY DATA SHEET

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

Page: 11  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

### 12. ECOLOGICAL INFORMATION

#### Aquatic Toxicity

##### Acute and Prolonged Toxicity to Fish

No data

##### Acute Toxicity to Aquatic Invertebrates

No data

#### Environmental Fate and Pathways

No data

### 13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

### 14. TRANSPORT INFORMATION

#### IMDG:

UN1950, AEROSOLS 2.1,

#### IATA\_P:

UN1950, Aerosols, flammable 2.1,

#### IATA\_C:

UN1950, Aerosols, flammable 2.1,

#### CFR\_ROAD:

UN1950, Aerosols 2.1,

#### CFR\_RAIL:

UN1950, Aerosols 2.1,

#### CFR\_INWTR:

# ASHLAND

## SAFETY DATA SHEET

Page: 12  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

UN1950, Aerosols 2.1,  
**IMDG\_INWTR:**  
UN1950, AEROSOLS 2.1,  
**IMDG\_ROAD:**  
UN1950, AEROSOLS 2.1,  
**IMDG\_RAIL:**  
UN1950, AEROSOLS 2.1,

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

### 15. REGULATORY INFORMATION

#### California Prop. 65

#### Additional Regulations

US. Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

**SARA Hazard Classification**     Acute Health Hazard  
Chronic Health Hazard

#### SARA 313 Component(s)

**OSHA Hazards**     Toxic by inhalation  
Moderate skin irritant  
Severe eye irritant  
Carcinogen

|             | <b>Health</b> | <b>Flammability</b> | <b>Reactivity</b> | <b>Other</b> |
|-------------|---------------|---------------------|-------------------|--------------|
| <b>HMIS</b> | 2             | 4                   | 0                 |              |
| <b>NFPA</b> | 2             | 4                   | 0                 |              |

### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

**ASHLAND**  
**SAFETY DATA SHEET**

CAR BRITE® CB C/V DYE KHAKI  
DYES CBOOG014-0031

Page: 13  
Revision Date: 04/04/2007  
Print Date: 4/24/2007  
MSDS Number: R0411195  
Version: 1.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department  
(1-800-325-3751).