

CG 1413- CQ 1413- CR 1020

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: CRYSTAL SHIELD - A046

Company

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
-----	-----	-----
LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)	64742-89-8	10.0- 20.0
ALUMINUM SILICATE	66402-68-4	2.9- 13.0
ALIPHATIC HYDROCARBONS (STODDARD TYPE)	8052-41-3	1.9- 12.0
KEROSINE, STRAIGHT RUN, KEROSENE	8008-20-6	1.0- 9.0
POLY(DIMETHYLSILOXANE)	63148-62-9	1.0- 7.0
TALL OIL FATTY ACID	61790-12-3	1.0- 7.0
MORPHOLINE	110-91-8	1.0- 6.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Material is corrosive to eyes. May cause burns. Additional symptoms of eye exposure may include: halo vision (blurred vision around bright objects).

Skin

Can cause skin burns and other permanent skin damage. Additional symptoms of skin contact may include: skin blistering, Passage of this material through the skin may be harmful.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

Swallowing

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation, burns and tissue damage. Shock may occur. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing this material may be harmful or fatal. May cause severe irritation and burns to the nose, throat, and respiratory tract. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8). Prolonged or repeated breathing of dust may result in progressive and irreversible lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity.

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) thirst, irritation (nose, throat, airways), runny nose, lung irritation, cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, muscle weakness, pain in the abdomen, loss of coordination, confusion, difficult breathing, irregular heartbeat, narcosis (dazed or sluggish feeling), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, convulsions, coma, and death. Exposure to this product (or a component) may cause an allergic reaction (narrowing of the air passages of the lungs resulting in difficult breathing, tightness in the chest, coughing and wheezing) in some sensitive individuals. Other symptoms of an allergic reaction may include itchy and watery eyes, runny and stuffy nose, sweating, flushing, hives, rapid heart rate, and lowered blood pressure.

Target Organ Effects

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate preexisting disorders of these organs in humans: nasal damage, eye damage, kidney damage, liver damage, lung damage.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

Developmental Information

Tall oil fatty acids did not cause harm to the fetus when given in the diet of laboratory animals.

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration. This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

Other Health Effects

Nitrites should not be added to this material because this can result in formation of nitrosamines. Many nitrosamines cause cancer in laboratory animals. When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes. Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and discard contaminated shoes.

Swallowing

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidneys, eye. Individuals with pre-existing heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

5. FIRE FIGHTING MEASURES

Flash Point

90.0 F (32.2 C)

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons.

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Not determined

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

Skin Protection

Wear impervious gloves (consult your safety equipment supplier).
To prevent skin contact, wear impervious full-body protective
clothing. Other protective equipment: eyewash station, emergency
shower.

Respiratory Protections

If workplace exposure limit(s) of product or any component is
exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air
supplied respirator is advised in absence of proper environmental
control. OSHA regulations also permit other NIOSH/MSHA
respirators (negative pressure type) under specified conditions
(consult your industrial hygienist). Engineering or
administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust)
ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM) (64742-89-8)

OSHA VPEL 300.000 ppm - TWA

OSHA VPEL 400.000 ppm - STEL

ACGIH TLV 300.000 ppm - TWA

ALUMINUM SILICATE (66402-68-4)

No exposure limits established

ALIPHATIC HYDROCARBONS (STODDARD TYPE) (8052-41-3)

OSHA VPEL 100.000 ppm - TWA

ACGIH TLV 100.000 ppm - TWA

KEROSINE, STRAIGHT RUN, KEROSENE (8008-20-6)

ACGIH TLV 200.000 mg/m3 - TWA ((Skin))

POLY(DIMETHYLSILOXANE) (63148-62-9)

No exposure limits established

TALL OIL FATTY ACID (61790-12-3)

No exposure limits established

MORPHOLINE (110-91-8)

OSHA VPEL 20.000 ppm - TWA ((Skin))

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

OSHA VPEL 30.000 ppm - STEL ((Skin))

ACGIH TLV 20.000 ppm - TWA ((Skin))

ACGIH TLV 30.000 ppm - STEL ((Skin))

Provide adequate ventilation to control formaldehyde exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for product) > 150.0 F (65.5 C) @ 760.00 mmHg

Vapor Pressure

(for component) 7.000 mmHg

Specific Vapor Density

No data

Specific Gravity

.961 @ 60.00 F

Liquid Density

8.020 lbs/gal @ 60.00 F

8.020 lbs/gal @ 60.00 F

Percent Volatiles (Including Water)

No data

Evaporation Rate

No data

Appearance

No data

State

LIQUID

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 009

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

Physical Form

No data

Color

PINK

Odor

CHERRY

pH

No data

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: acids, halogenated hydrocarbons, strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

Chronic/Carcinogenicity

One study with morpholine in laboratory animals produced cancer, while others have not. The tumors in the one study may have resulted from exposure to N-nitrosomorpholine, an animal carcinogen. N-nitrosomorpholine can occur as a contaminant in morpholine or as a result of the interaction of morpholine with nitrite of unknown origin. There is no evidence that morpholine causes cancer in humans.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 010

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

FLAMMABLE LIQUIDS, N.O.S., 3, UN1993, II

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

PETROLEUM DISTILLATES

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 011

Date Prepared: 10/12/05

Date Printed: 07/14/06

MSDS No: 525.0405604-001.002

CRYSTAL SHIELD - A046

SARA 302 Components - 40 CFR 355 Appendix A
None

Section 311/312 Hazard Class - 40 CFR 370.2
Immediate(X) Delayed(X) Fire(X) Reactive() Sudden
Release of Pressure()

SARA 313 Components - 40 CFR 372.65
None

International Regulations
Inventory Status
Not determined

State and Local Regulations
California Proposition 65
None

New Jersey RTK Label Information

NAPHTHA, SOLVENT	64742-89-8
STODDARD SOLVENT	8052-41-3
KEROSENE	8008-20-6
MORPHOLINE	110-91-8

Pennsylvania RTK Label Information

LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLE	64742-89-8
STODDARD SOLVENT	8052-41-3
KEROSINE (PETROLEUM)	8008-20-6
MORPHOLINE	110-91-8

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.