

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 07/20/05

Date Printed: 01/26/06

MSDS No: 525.0405448-001.001

YELLOW TRIPLE FOAM COND 5 GAL SQUARE

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: YELLOW TRIPLE FOAM COND 5 GAL SQUARE

SAP Material No: CBOOAE307-05-S5

Wesmar Products, Inc

1440 NW 45th St

Seattle, WA 98107

(206) 782-8186

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by volume)
SURFACTANT BLEND		18.0- 28.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation.

Skin

Can cause skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects.

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects.

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways).

Target Organ Effects

No data

Developmental Information

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002
Date Prepared: 07/20/05
Date Printed: 01/26/06
MSDS No: 525.0405448-001.001

YELLOW TRIPLE FOAM COND 5 GAL SQUARE

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions).

5. FIRE FIGHTING MEASURES

Flash Point

Not applicable

Explosive Limit

No data

Autoignition Temperature

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 07/20/05

Date Printed: 01/26/06

MSDS No: 525.0405448-001.001

YELLOW TRIPLE FOAM COND 5 GAL SQUARE

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

No data

Extinguishing Media

alcohol foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Not determined

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Flush area with water.

Large Spill

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Spills of this material are very slippery.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. This material is slippery when wet. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 07/20/05

Date Printed: 01/26/06

MSDS No: 525.0405448-001.001

YELLOW TRIPLE FOAM COND 5 GAL SQUARE

Storage

Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier).

Respiratory Protections

If needed use a NIOSH/MSHA jointly approved respirator suitable for the potential exposure level.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below level of overexposure (from known, suspected or apparent adverse effects).

Exposure Guidelines

Component

SURFACTANT BLEND

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

No data

Vapor Pressure

(for product) .000

Specific Vapor Density

No data

Specific Gravity

1.003 @ 60.00 F

Liquid Density

8.370 lbs/gal @ 60.00 F

8.370 lbs/gal @ 60.00 F

Percent Volatiles (Including Water)

No data

Evaporation Rate

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 07/20/05

Date Printed: 01/26/06

MSDS No: 525.0405448-001.001

YELLOW TRIPLE FOAM COND 5 GAL SQUARE

Appearance

No data

State

LIQUID

Physical Form

No data

Color

YELLOW

Odor

BANANA

pH

9.0

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 07/20/05

Date Printed: 01/26/06

MSDS No: 525.0405448-001.001

YELLOW TRIPLE FOAM COND 5 GAL SQUARE

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed() Fire() Reactive() Sudden Release of
Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.