

CP 1005

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: BRITE STIK PURPLE - B082

Wesmar Products Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Telephone Numbers

Emergency: 1-800-274-5263

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
CALCIUM CARBONATE	471-34-1	45.0- 55.0
POLYISOBUTENE	9003-29-6	25.0- 35.0
SILICA, FUSED	60676-86-0	15.0- 25.0
PIGMENT		0.0- 10.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

May cause mild eye irritation.

Skin

May cause skin irritation. This material is unlikely to pass into the body through the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects.

Inhalation

Breathing this material is unlikely during normal use.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea).

Target Organ Effects

No data

Developmental Information

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Cancer Information

This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

Swallowing

First aid is not normally required. If symptoms develop, seek medical attention.

Inhalation

First aid is not normally required. If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention.

Note to Physicians

No data

5. FIRE FIGHTING MEASURES

Flash Point

Not applicable

Explosive Limit

No data

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide.

Fire and Explosion Hazards

No data

Extinguishing Media

Use an extinguishing media appropriate for surrounding fire.

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

NFPA Rating

Health - 0, Flammability - 0, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Scoop or scrape up. Put in container for recovery or disposal.

Large Spill

Shovel material into containers. Thoroughly sweep area of spill to clean up any residual material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material.

Storage

Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Wear safety glasses in compliance with OSHA regulations. (Consult your safety representative.)

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

Skin Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

CALCIUM CARBONATE (471-34-1)

No exposure limits established

POLYISOBUTENE (9003-29-6)

No exposure limits established

SILICA, FUSED (60676-86-0)

OSHA VPEL 0.100 mg/m3 - TWA respirable dust

ACGIH TLV 0.100 mg/m3 - TWA

PIGMENT

No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

Vapor Pressure
(for product) .000

Specific Vapor Density
No data

Specific Gravity
2.000 @ 60.00 F

Liquid Density
No data

Percent Volatiles (Including Water)
No data

Evaporation Rate
No data

Appearance
No data

State
SOLID

Physical Form
No data

Color
No data

Odor
No data

pH
No data

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide.

Chemical Stability

Stable.

Incompatibility

No data

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

Container/Mode:

No data

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate() Delayed() Fire() Reactive() Sudden

Release of Pressure()

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

SILICA, AMORPHOUS (FUSED)

60676-86-0

Continued on next page

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 009

Date Prepared: 08/23/06

Date Printed: 09/02/06

MSDS No: 525.0409218-001.001

BRITE STIK PURPLE - B082

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.