

CG 1750 - CQ 1600

ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® PERFECT CUT Medium-Duty Compound
Product code	CBOOB064-03
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, fruity, orange

CAUTION! Combustible Liquid, Highly toxic by inhalation, Moderate skin irritant, Moderate eye irritant, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin Contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Additional symptoms of skin contact may include: skin blistering. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. Another form of fibrosis, acute silicosis, can occur with exposures to very high concentrations of respirable silica over shorter periods of time, sometimes as short as a few months. Symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal.

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), kidney, Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material., Silicosis predisposes the individual to the development mycobacterial infections including tuberculosis or to fungal infections. This is most likely to occur after the age of 50 and in association with moderate to severe silicosis.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, loss of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), convulsions, coma, and death

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans., Chronic feeding studies with white oils (greater than 0.5% in the diet) have resulted in increased organ weights (liver, kidney, spleen), and in microscopic areas of oil accumulation in the liver and the lymph nodes of the gut in experimental animals. These changes have occasionally been associated with cell damage. In humans, cell damage resulting from accumulation of these oil droplets has only occurred following prolonged ingestion of mineral oil. These

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

effects are not expected to occur as a result of occupational exposure to white oils., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: chronic bronchitis, emphysema, kidney damage

Carcinogenicity

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke. White mineral oil was not carcinogenic in laboratory animals by any route of exposure other than by injection into the abdomen. Results of abdominal injection are not relevant to possible human exposure to this material.

Reproductive Hazard

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

Other Information

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of immunological disorders and autoimmune diseases such as scleroderma (a disorder manifested by fibrosis of the lungs, skin and other internal organs), systemic lupus erythematosus and sarcoidosis (chronic inflammatory diseases).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
SILICA, CRYSTALLINE TRIPOLI	1317-95-9	>=15-<20%
MINERAL SPIRITS REGULAR (BASE DATA)	8052-41-3	>=15-<20%
KEROSENE	8008-20-6	>=15-<20%
FLUX CALCINED DIATOMACEOUS	68855-54-9	>=5-<10%

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

EARTH		
GLYCERINE	56-81-5	>=1.5-<5%
ALIPHATIC HYDROCARBON	NJTS#	>=1.5-<5%
	254504001-	
	5164	
TRIMETHYLBENZENE, 1,3,5-	108-67-8	>=1-<1.5%
TRIMETHYLBENZENE 1,2,4-	95-63-6	>=1-<1.5%
Fatty Acid	NJTS# 800986-	>=1-<1.5%
	5166P	
ETHYL BENZENE	100-41-4	>=0.1-<0.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Acute aspiration of large amounts of oil-laden material may

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

regular foam (such as AFFF), Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Flammability Class for Flammable Liquids

Combustible Liquid Class II

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Handling equipment must be properly grounded.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

SILICA, CRYSTALLINE TRIPOLI		1317-95-9
ACGIH	time weighted average	0.025 mg/m3
MINERAL SPIRITS REGULAR (BASE DATA)		8052-41-3
ACGIH	time weighted average	100 ppm
NIOSH	Recommended exposure limit (REL):	350 mg/m3
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3
OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	2,900 mg/m3
OSHA Z1A	time weighted average	100 ppm
OSHA Z1A	time weighted average	525 mg/m3
US CA OEL	Time Weighted Average (TWA)	100 ppm
US CA OEL		Permissible Exposure Limit (PEL):
		Time Weighted Average (TWA)
		Permissible Exposure Limit (PEL):
KEROSENE		8008-20-6

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-03

ACGIH	time weighted average	200 mg/m3	Non-aerosol
NIOSH	Recommended exposure limit (REL):	100 mg/m3	

FLUX CALCINED DIATOMACEOUS EARTH 68855-54-9

OSHA Z1A	time weighted average	5 mg/m3	Respirable fraction.
OSHA Z1A	time weighted average	15 mg/m3	Total dust.
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	5 mg/m3	Respirable fraction.
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	10 mg/m3	Total dust.
	Permissible Exposure Limit (PEL):		
Z3	time weighted average	0.8 mg/m3	
NIOSH	Recommended exposure limit (REL):	6 mg/m3	

GLYCERINE 56-81-5

ACGIH	time weighted average	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.

TRIMETHYLBENZENE, 1,3,5- 108-67-8

NIOSH	Recommended exposure limit (REL):	25 ppm	
NIOSH	Recommended exposure limit (REL):	125 mg/m3	
ACGIH	time weighted average	25 ppm	
OSHA Z1A	time weighted average	25 ppm	
OSHA Z1A	time weighted average	125 mg/m3	

TRIMETHYLBENZENE 1,2,4- 95-63-6

NIOSH	Recommended exposure limit (REL):	25 ppm	
NIOSH	Recommended exposure limit (REL):	125 mg/m3	
ACGIH	time weighted average	25 ppm	
OSHA Z1A	time weighted average	25 ppm	
OSHA Z1A	time weighted average	125 mg/m3	
US CA OEL	Time Weighted Average (TWA)	25 ppm	
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	125 mg/m3	
	Permissible Exposure Limit (PEL):		

General Advice

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	orange
Odour	fruity
Boiling point/range	150 °F / 66 °C@ 760.00 mmHg
pH	No data
Flash point	118.0 °F / 47.8 °C
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	1.15 g/cm3

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

	9.6 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to Avoid

Incompatible Products
Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products
May form:, carbon dioxide and carbon monoxide, various hydrocarbons

Hazardous Reactions
Product will not undergo hazardous polymerization.

Thermal Decomposition
No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

MINERAL SPIRITS REGULAR (BASE DATA)	LD 50 Rat: 5 g/kg
KEROSENE	LD 50 Rat: 5,000 mg/kg
GLYCERINE	LD 50 Rat: 12,600 mg/kg
ALIPHATIC HYDROCARBON	LD 50 Rat: 8,000 mg/kg
TRIMETHYLBENZENE, 1,3,5-	LD 50 Rat: 5,000 mg/kg

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

TRIMETHYLBENZENE 1,2,4-	LD 50 Rat: 6 g/kg
Fatty Acid	LD 50 Rat: 10,000 mg/kg
ETHYL BENZENE	LD 50 Rat: 3,500 mg/kg

Acute Inhalation Toxicity

KEROSENE	LC 50 Rat: 5,000 mg/m ³ , 4 h
GLYCERINE	LC 50 Rat: 570 mg/m ³ , 1 h
ALIPHATIC HYDROCARBON	LD 50 Rat: 2500 ppm, 4 h
TRIMETHYLBENZENE 1,2,4-	LC 50 Rat: 18 g/m ³ , 4 h
ETHYL BENZENE	LC Lo Rat: 4000 ppm, 4 h

Acute Dermal Toxicity

MINERAL SPIRITS REGULAR (BASE DATA)	LD 50 Rabbit: 3 g/kg
KEROSENE	LD 50 Rabbit: 2 g/kg
GLYCERINE	LD 50 Rabbit: 10 g/kg
ALIPHATIC HYDROCARBON	LD 50 Rabbit: 4,000 mg/kg
Fatty Acid	LD 50 Rabbit: 2,000 mg/kg
ETHYL BENZENE	LD 50 Rabbit: 15,433 mg/kg

ASHLAND

SAFETY DATA SHEET

Page: 11
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_P:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_C:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_ROAD:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

ASHLAND

SAFETY DATA SHEET

Page: 12
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

CFR_RAIL:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,
) 3, III

CFR_INWTR:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,
) 3, III

IMDG_INWTR:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_ROAD:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_RAIL:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

SILICA, CRYSTALLINE TRIPOLI

ETHYL BENZENE

BENZENE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

TOLUENE

BENZENE

SARA Hazard Classification

Fire Hazard

Acute Health Hazard

Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards

Combustible Liquid

Highly toxic by inhalation

Moderate skin irritant

ASHLAND

SAFETY DATA SHEET

Page: 13
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405359
Version: 1.

CAR BRITE® PERFECT CUT
Medium-Duty Compound CBOOB064-
03

Moderate eye irritant
Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	1	2	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).