

CG 2000, CQ 2000
ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number

1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® WORKOUT 2000 Cleaner & Glaze
Product code	CBOOA045-03
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, solvent, off-white

DANGER! Highly toxic by inhalation, Moderate skin irritant, Moderate eye irritant.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Causes eye burns. Additional symptoms of eye exposure may include: halo vision (blurred vision around bright objects)

Skin Contact

Can cause permanent skin damage. Symptoms may include redness, burning, and swelling of skin, burns, and other skin damage. Additional symptoms of skin contact may include: skin blistering. Passage of this material into the body through the skin is possible, and skin contact may be harmful.

Ingestion

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03**Inhalation**

Breathing of vapor or mist is possible. Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. This product may give off a fine particulate fume when heated above 300 degrees C. Smoking cigarettes or tobacco contaminated with polymer dust may give off this fume. Inhalation of polymer fumes may cause "polymer fume fever", a flu-like illness with fever, chills, nausea, shortness of breath, chest tightness, muscle or joint ache, and sometimes cough. The symptoms may not occur until several hours after exposure and are generally temporary, lasting 24-48 hours, even without treatment. In addition to polymer fume fever, exposure to decomposition products given off from heating this product above 400 degrees C, may cause lung inflammation, and bleeding and swelling in the lungs.

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidney, eye. Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), thirst, irritation (nose, throat, airways), runny nose, lung irritation, cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, muscle weakness, pain in the abdomen, pain in the abdomen and lower back, shortness of breath, loss of coordination, confusion, difficult breathing, irregular heartbeat, narcosis (dazed or sluggish feeling), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, convulsions, coma, and death. Exposure to this product (or a component) may cause an allergic reaction (narrowing of the air passages of the lungs resulting in difficult breathing, tightness in the chest, coughing and wheezing) in some sensitive individuals. Other symptoms of an allergic reaction may include itchy and watery eyes, runny and stuffy nose, sweating, flushing, hives, rapid heart rate, and lowered blood pressure.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03**Target Organs**

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Chronic feeding studies with white oils (greater than 0.5% in the diet) have resulted in increased organ weights (liver, kidney, spleen), and in microscopic areas of oil accumulation in the liver and the lymph nodes of the gut in experimental animals. These changes have occasionally been associated with cell damage. In humans, cell damage resulting from accumulation of these oil droplets has only occurred following prolonged ingestion of mineral oil. These effects are not expected to occur as a result of occupational exposure to white oils. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: nasal damage, eye damage, kidney damage, liver damage, lung damage

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. White mineral oil was not carcinogenic in laboratory animals by any route of exposure other than by injection into the abdomen. Results of abdominal injection are not relevant to possible human exposure to this material.

Reproductive Hazard

Tall oil fatty acids did not cause harm to the fetus when given in the diet of laboratory animals.

Other Information

Nitrites should not be added to this material because this can result in formation of nitrosamines. Many nitrosamines cause cancer in laboratory animals.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
MINERAL SPIRITS ODORLESS (BASE DATA)	8052-41-3	>=10-<15%
KEROSENE	8008-20-6	>=5-<10%
ALUMINUM SILICATE CALCINED	66402-68-4	>=5-<10%
GLYCERINE	56-81-5	>=1.5-<5%

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

ALIPHATIC HYDROCARBON	NJTS#	>=1.5-<5%
	254504001-5164	
Fatty Acid	NJTS# 800986-5166P	>=1.5-<5%
MORPHOLINE	110-91-8	>=1.5-<5%
ETHYLENE POLYMER	NJTS#	>=1-<1.5%
	254504001-5136	
GLYCOL ETHER	NJTS#	>=1-<1.5%
	254504001-5451	

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention.

Skin

Immediately flush skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and discard contaminated shoes. If skin contact with molten material occurs, flush exposed area with cool water. Do not forcibly remove material adhering to the skin. Seek immediate medical attention.

Ingestion

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

regular foam (such as AFFF), Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, carbonyl fluoride, fluoride compounds, formaldehyde, hydrogen fluoride, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Handling equipment must be properly grounded.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

MINERAL SPIRITS ODORLESS (BASE DATA)

8052-41-3

ACGIH	time weighted average	100 ppm	
NIOSH	Recommended exposure limit (REL):	350 mg/m3	
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3	
OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,900 mg/m3	
OSHA Z1A	time weighted average	100 ppm	
OSHA Z1A	time weighted average	525 mg/m3	
US CA OEL	Time Weighted Average (TWA)	100 ppm	
	Permissible Exposure Limit (PEL):		
US CA OEL	Time Weighted Average (TWA)	525 mg/m3	
	Permissible Exposure Limit (PEL):		

KEROSENE

8008-20-6

ACGIH	time weighted average	200 mg/m3	Non-aerosol
NIOSH	Recommended exposure limit (REL):	100 mg/m3	

GLYCERINE

56-81-5

ACGIH	time weighted average	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.

MORPHOLINE

110-91-8

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	20 ppm
NIOSH	Recommended exposure limit (REL):	70 mg/m3
NIOSH	Short term exposure limit	30 ppm
NIOSH	Short term exposure limit	105 mg/m3
OSHA Z1	Permissible exposure limit	20 ppm
OSHA Z1	Permissible exposure limit	70 mg/m3

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	off-white

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

Odour	solvent
Boiling point/range	150 °F / 66 °C @ 760.00 mmHg
pH	No data
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	0.990 g/cm ³ 8.26 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

Avoid contact with: acids, halogenated hydrocarbons, strong oxidizing agents

Hazardous Decomposition Products

May form: carbon dioxide and carbon monoxide, formaldehyde, various hydrocarbons, The fluoroadditives in this product may contain small amounts of hydrogen fluoride and carbonyl fluoride, and small amounts may be present in closed containers. Additional amounts may be given off upon heating, especially in the presence of moisture.

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

Acute Oral Toxicity

MINERAL SPIRITS ODORLESS (BASE DATA)	LD 50 Rat: 5 g/kg
KEROSENE	LD 50 Rat: 5,000 mg/kg
GLYCERINE	LD 50 Rat: 12,600 mg/kg
ALIPHATIC HYDROCARBON	LD 50 Rat: 8,000 mg/kg
Fatty Acid	LD 50 Rat: 10,000 mg/kg
MORPHOLINE	LD 50 Rat: 1,050 mg/kg
GLYCOL ETHER	LD 50 Rat: 2,504 mg/kg

Acute Inhalation Toxicity

KEROSENE	LC 50 Rat: 5,000 mg/m ³ , 4 h
GLYCERINE	LC 50 Rat: 570 mg/m ³ , 1 h
ALIPHATIC HYDROCARBON	LD 50 Rat: 2500 ppm, 4 h
MORPHOLINE	LC 50 Rat: 8000 ppm, 8 h

Acute Dermal Toxicity

MINERAL SPIRITS ODORLESS (BASE DATA)	LD 50 Rabbit: 3 g/kg
KEROSENE	LD 50 Rabbit: 2 g/kg
GLYCERINE	LD 50 Rabbit: 10 g/kg
ALIPHATIC HYDROCARBON	LD 50 Rabbit: 4,000 mg/kg

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

Fatty Acid	LD 50 Rabbit: 2,000 mg/kg
MORPHOLINE	LD 50 Rabbit: 500 mg/kg
GLYCOL ETHER	LD 50 Rabbit: 3,550 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Aliphatic Petroleum Distillates, KEROSENE) 3, III

IATA_P:

ASHLAND

SAFETY DATA SHEET

Page: 11
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

UN1993, Flammable liquid, n.o.s. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

IATA_C:

UN1993, Flammable liquid, n.o.s. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

CFR_ROAD:

UN1993, Flammable liquids, n.o.s. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

CFR_RAIL:

UN1993, Flammable liquids, n.o.s. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

CFR_INWTR:

UN1993, Flammable liquids, n.o.s. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

IMDG_INWTR:

UN1993, FLAMMABLE LIQUID, N.O.S. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

IMDG_ROAD:

UN1993, FLAMMABLE LIQUID, N.O.S. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

IMDG_RAIL:

UN1993, FLAMMABLE LIQUID, N.O.S. (Aliphatic Petroleum Distillates,
KEROSENE) 3, III

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

BENZENE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

TOLUENE

BENZENE

SARA Hazard Classification Acute Health Hazard

ASHLAND

SAFETY DATA SHEET

Page: 12
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405602
Version: 1.

CAR BRITE® WORKOUT 2000
Cleaner & Glaze CBOOA045-03

SARA 313 Component(s)

OSHA Hazards

Highly toxic by inhalation
Moderate skin irritant
Moderate eye irritant

	Health	Flammability	Reactivity	Other
HMIS	3	2	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).