

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/19/2006

Reviewed on 09/05/2005

1 Identification of substance

- Product details
- Trade name: 4CR 4330 1K-Kunststoff-Primer
- Application of the substance / the preparation Primer
- Manufacturer/Supplier:

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

DE 4330.1000

- Information department: Laboratory
- Emergency information: Tel.1-800-535-5053

2 Composition/Data on components

- Chemical characterization
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

108-88-3	toluene	50-100%
64742-95-6	Solvent naphtha (petroleum), light arom.	10-25%
108-90-7	chlorobenzene	≤ 2.5%
98-82-8	cumene	≤ 2.5%

3 Hazards identification

· Hazard description:



Harmful
Highly flammable

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Has a narcotizing effect.

Highly flammable.

Irritating to skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Possible risk of harm to the unborn child.

Vapours may cause drowsiness and dizziness.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 3
Fire = 3
Reactivity = 0

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/19/2006

Reviewed on 09/05/2005

Trade name: 4CR 4330 1K-Kunststoff-Primer

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	3	Health = *3
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

4 First aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/19/2006

Reviewed on 09/05/2005

Trade name: 4CR 4330 1K-Kunststoff-Primer

(Contd. of page 2)

Components with limit values that require monitoring at the workplace:

108-88-3 toluene (50-100%)

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	188 mg/m ³ , 50 ppm Skin; BEI

Additional information: The lists that were valid during the creation were used as basis.

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

General Information

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/19/2006

Reviewed on 09/05/2005

Trade name: 4CR 4330 1K-Kunststoff-Primer

(Contd. of page 3)

· Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 110°C (230°F)	
· Flash point:	10°C (50°F)
· Ignition temperature:	450.0°C (842°F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	0.7 Vol % 7.5 Vol %
· Vapor pressure at 20°C (68°F):	29.0 hPa (22 mm Hg)
· Density at 20°C (68°F):	0.894 g/cm ³
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Viscosity: Kinematic at 20°C (68°F):	13 s (DIN 53211/4)
· Solvent content: Organic solvents: VOC content:	95.0 % 95.0 % 849.0 g/l / 7.09 lb/gl
· Solids content:	4.3 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
on the skin: Irritant to skin and mucous membranes.
on the eye: No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 5)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/19/2006

Reviewed on 09/05/2005

Trade name: 4CR 4330 1K-Kunststoff-Primer

(Contd. of page 4)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

12 Ecological information

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations

· **Product:**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **DOT regulations:**



· **Hazard class:**

3

· **Identification number:**

UN1263

· **Packing group:**

II

· **Proper shipping name (technical name):** PAINT

· **Label**

3

· **Land transport ADR/RID (cross-border):**



· **ADR/RID class:**

3 (F1) Flammable liquids

· **Danger code (Kemler):**

33

· **UN-Number:**

1263

· **Packaging group:**

II

· **Label:**

3

· **Description of goods:**

1263 PAINT, special provision 640D

(Contd. on page 6)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/19/2006

Reviewed on 09/05/2005

Trade name: 4CR 4330 1K-Kunststoff-Primer

(Contd. of page 5)

· Maritime transport IMDG:



· IMDG Class: 3
 · UN Number: 1263
 · Label: 3
 · Packaging group: II
 · EMS Number: F-E,S-E
 · Marine pollutant: No
 · Proper shipping name: PAINT

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3
 · UN/ID Number: 1263
 · Label: 3
 · Packaging group: II
 · Proper shipping name: PAINT

15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3	toluene
108-90-7	chlorobenzene
98-82-8	cumene
1330-20-7	xylene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

108-88-3	toluene	D
108-90-7	chlorobenzene	D
98-82-8	cumene	D; CBD
1330-20-7	xylene	D

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/19/2006

Reviewed on 09/05/2005

Trade name: 4CR 4330 1K-Kunststoff-Primer

(Contd. of page 6)

· IARC (International Agency for Research on Cancer)			
108-88-3	toluene		3
1330-20-7	xylene		3
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· TLV (Threshold Limit Value established by ACGIH)			
108-88-3	toluene	A4	50-100%
108-90-7	chlorobenzene	A3	≤2,5%
1330-20-7	xylene	A4	≤2,5%
· NIOSH-Ca (National Institute for Occupational Safety and Health)			
None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:

Harmful

Highly flammable

· Hazard-determining components of labelling:

toluene

· Risk phrases:

Highly flammable.

Irritating to skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Possible risk of harm to the unborn child.

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Keep container in a well-ventilated place.

Keep away from food, drink and animal feedingstuffs.

Keep away from sources of ignition - No smoking.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

· National regulations:**· Information about limitation of use:**

None of the ingredients is listed.

Class	Share in %
NK	95.6

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Laboratory**· Contact:** Ingo Bolls

USA