

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th ST
Seattle, WA 98107
(206) 782-8186

Emergency telephone number 1-800-ASHLAND
(1-800-274-5263)

Product name	CAR BRITE® CLEAR COAT SEALER & DRYING AGENT CONCENTRATED DRYING AGENT
Product code	CBOOAE489-09-CP
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, colourless

DANGER! Moderate skin irritant, Corrosive to eyes.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Causes eye burns.

Skin Contact

Can cause permanent skin damage. Symptoms may include redness, burning, and swelling of skin, burns, and other skin damage.

Ingestion

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405473
Version: 1.

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, difficult breathing, lung edema (fluid buildup in the lung tissue)

Target Organs

No data

Carcinogenicity

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive Hazard

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

Other Information

No data

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
DIMETHYL DICOCO AMMONIUM CHLORIDE	61789-77-3	>=5-<10%

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405473
Version: 1.

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

MINERAL SEAL OIL	64741-44-2	>=5-<10%
AMINES, C14-18 AND C16-18-UNSATD.	68155-39-5	>=1.5-<5%
ALKYL, ETHOXYLA		
ISOPROPANOL	67-63-0	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If material gets into the eyes, immediately flush eyes gently with water for at least 15 minutes while holding eyelids apart. If symptoms develop as a result of vapor exposure, immediately move individual away from exposure and into fresh air before flushing as recommended above. Seek immediate medical attention. Do not remove the victim from water access for transport to a medical facility unless instructed to do so by qualified medical personnel. If possible, continue flushing the eye gently with water while transporting the victim.

Skin

Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Seek immediate medical attention. Wash clothing before reuse and decontaminate or discard contaminated shoes.

Ingestion

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to Physician

Hazards: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

Suitable Extinguishing Media

alcohol-resistant foam, Agents approved for class B hazards or water fog., carbon dioxide (CO2), dry chemical

Hazardous Combustion Products

May form: amines, carbon dioxide and carbon monoxide, hydrogen chloride, methyl chloride, nitrogen oxides, various hydrocarbons

Precautions for Fire-Fighting

No special fire hazards are known to be associated with this product. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition"

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in closed containers in a dry, well-ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Guidelines****ISOPROPANOL****67-63-0**

ACGIH	time weighted average	200 ppm
ACGIH	Short term exposure limit	400 ppm
NIOSH	Recommended exposure limit (REL):	400 ppm
NIOSH	Recommended exposure limit (REL):	980 mg/m3
NIOSH	Short term exposure limit	500 ppm
NIOSH	Short term exposure limit	1,225 mg/m3
OSHA Z1	Permissible exposure limit	400 ppm
OSHA Z1	Permissible exposure limit	980 mg/m3

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Eye Protection

Chemical splash goggles and face shield (8" min.) in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist.)

Skin and Body Protection

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405473
Version: 1.

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious full-body protective clothing. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	colourless
Odour	No data
Boiling point/range	No data
pH	No data
Flash point	No data
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	0.975 g/cm ³ 8.14 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability
Stable.

Conditions to Avoid

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405473
Version: 1.

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

Incompatible Products

Avoid contact with: strong acids, strong oxidizing agents, strong reducing agents

Hazardous Decomposition Products

May form: amines, carbon dioxide and carbon monoxide, hydrogen chloride, methyl chloride, nitrogen oxides, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

MINERAL SEAL OIL	LD 50 Rat: 5 g/kg
ISOPROPANOL	LD 50 Rat: 5,045 mg/kg

Acute Inhalation Toxicity

MINERAL SEAL OIL	LC 50 Rat: 1,700 mg/m ³ , 4 h
ISOPROPANOL	LC 50 Rat: 16000 ppm, 4 h

Acute Dermal Toxicity

MINERAL SEAL OIL	LD 50 Rabbit: 2 g/kg
ISOPROPANOL	LD 50 Rabbit: 5,030 - 7,900 mg/kg

12. ECOLOGICAL INFORMATION

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405473
Version: 1.

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

METHYL CHLORIDE

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 6/14/2007
MSDS Number: R0405473
Version: 1.

CAR BRITE® CLEAR COAT
SEALER & DRYING AGENT
CONCENTRATED DRYING AGENT
CBOOAE489-09-CP

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

OSHA Hazards Moderate skin irritant
Corrosive to eyes

	Health	Flammability	Reactivity	Other
HMIS	3	2	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).