

LO 37513

Wesmar Products, Inc.
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Material Safety Data Sheet

 Technologies

Revision Date: 06/01/2004

Issue date: 06/01/2004

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Epoxy Mixer Cups Fast Cure
Product type: Epoxy Resin

Item number: 37513_RESIN
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Alumina trihydrate 21645-51-2	30-60	None	None	None
Reaction product of epichlorohydrin and bisphenol A 25085-99-8	10-30	None	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	10-30	None	None	None
Titanium dioxide 13463-67-7	5-10	10 mg/m ³ TWA	15 mg/m ³ TWA	None

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Paste
Color: White
Odor: Mild

HEALTH: 2
FLAMMABILITY: 1
PHYSICAL HAZARD: 1
Personal Protection: See Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Eye contact, Ingestion, Inhalation, Skin contact

Potential Health Effects

Inhalation: Mild respiratory tract irritation. May cause irritation to nose and throat.
Skin contact: Allergic skin reaction. Moderate skin irritation. Itching. Redness.
Eye contact: Moderate eye irritation. Redness.
Ingestion: Not expected under normal conditions of use.

Existing conditions aggravated by exposure:

Skin disorders. Skin allergies. Respiratory disorders. Eye disorders.

See Section 11 for additional toxicological information.

Item number: 37513_RESIN

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm. Get medical attention if symptoms develop and persist.
Notes to physician:	None.

5. FIRE-FIGHTING MEASURES

Flash point:	Greater than 93°C (200°F) Tagliabue closed cup
Autoignition temperature:	Not available
Flammable/Explosive limits-lower %:	Not available
Flammable/Explosive limits-upper %:	Not available
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:	Prevent product from entering drains or open waters.
Clean-up methods:	Remove all ignition sources. Immediately contact emergency personnel. Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Keep away from heat, spark and flame. Do not breathe mist or vapors. Keep container closed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Storage:	Store in original container until ready to use. Keep in a cool, well-ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.
Incompatible products:	Refer to Section 10.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
Skin protection:	Chemical resistant, impermeable gloves.

Eye/face protection:

Chemical splash goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	White
Odor:	Mild
Vapor pressure:	Nil
pH:	Not applicable
Boiling point/range:	Greater than 149°C (300°F)
Melting point/range:	Not available
Specific gravity:	1.68
Vapor density:	Not available
Evaporation rate:	Not available
Solubility in water:	Slightly soluble
Partition coefficient (n-octanol/water):	Not available
VOC content:	0.47%; 7.9 grams/liter 0.038% (value for resin and hardener together)

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	None
Incompatibility:	Strong acids. Strong bases. Strong oxidizers.
Conditions to avoid:	Excessive heat. Storage with incompatible materials.

11. TOXICOLOGICAL INFORMATIONCarcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Alumina trihydrate 21645-51-2	No	No	No
Reaction product of epichlorohydrin and bisphenol A 25085-99-8	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	No	No	No
Titanium dioxide 13463-67-7	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Alumina trihydrate 21645-51-2	Irritant, Lung, Respiratory
Reaction product of epichlorohydrin and bisphenol A 25085-99-8	Allergen, Irritant
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	Allergen, Irritant
Titanium dioxide 13463-67-7	Irritant, Respiratory

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose according to EPA and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Marine pollutant:	None known

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	Bisphenol A diglycidyl ether (CAS# 1675-54-3).

CERCLA/SARA Section 302 EHS:	None above reporting de minimus.
CERCLA/SARA Section 311/312:	Immediate Health Hazard
CERCLA/SARA 313:	None above reporting de minimus.

California Proposition 65:	This product contains a chemical known to the State of California to cause cancer, 1,4-Dioxane (CAS# 123-91-1), Acetaldehyde (CAS# 75-07-0), Ethylene oxide (CAS# 75-21-8), Benz[a]anthracene (56-55-3).
-----------------------------------	--

Canada Regulatory Information

CEPA DSL/NDL Status:	Contains one or more components listed on the Non-Domestic Substances list.
WHMIS hazard class:	D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Revised to new format.

Prepared by:

Gary Pierson, Health and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.