

MATERIAL SAFETY DATA SHEET 91/155/EEC
AIRCOLOR COBRE
Revision date: 03.18.02
Page: 1
MSDS-813/USA-CAN
1. IDENTIFICATION OF THE PRODUCT AND COMPANY
WESMAR PRODUCTS, INC.
 1440 N.W. 45th STREET
 SEATTLE, WA 98107
 (206) 782-8186

 1.1 Company:
 ROBERLO, S.A.

Carretera N-II, Km. 706,5 - E-17457 - Riudellots de la Selva (Girona) - SPAIN

Phone: +34 972 478060 - Fax: +34 972 477394 - info@roberlo.com - www.roberlo.com

 1.2 Emergency phone number: USA CHEMTREC 888 424 9300
 CANADA CANUTEC 613 996 6666
 SPAIN INT 91 5620420
 1.3 Product description: AIRCOLOR COBRE Code: 36000040
 1.4 Chemical description: Copper paint in aerosol

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances taking part in a percentage higher than the exemption limit and presenting a health or environment hazard, and/or with a recognised exposure limit value:

INGREDIENTS	CAS Nr	INTERVAL OF CONC. %	EU SYMBOL	VAPOR PRESSURE (20°C/MMH)	SARA 313 REPORT	EXPOSURE LIMITS			
						OSHA/ NIOSH	ACGIH	STEL	CEILING
1. Toluene	108-88-3	25<c<50	F Xn	22	Yes	200 ppm	N/E	300 ppm	200 ppm
2. Butane	106-97-8	10<c<25	F+	N/E	No	N/E	N/E	N/E	N/E
3. Propane	74-98-6	10<c<25	F+	N/E	No	N/E	N/E	N/E	N/E
4. Copper	7440-50-8	10<c<25	Xn	N/E	No	1 mg/m3	1 mg/m3	N/E	N/E

N/E = no evaluation results available at the time this MSDS was printed.

For more information on dangerous ingredients, see sections 8, 11, 12 and 16.

3. IDENTIFICATION OF HAZARDS

Extremely flammable. Harmful by inhalation.

4. FIRST AID MEASURES

When in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

4.1 By inhalation: Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.

4.2 By contact with eyes: Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, until the irritation is reduced. Call a physician immediately.

4.3 By contact with the skin: Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.

4.4 By ingestion: In case of accidental swallowing, seek immediate medical attention. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

5. FIRE-FIGHTING MEASURES

5.1 Means of Extinction: In case of fire, use alcohol-resistant foam, dry chemical powder, carbon dioxide, AFFF. Do not use for extinguishing: direct water jet.

5.2 Specific risks: Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous decomposition products may be produced, such as: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products may be a hazard to health.

5.3 Fire-proof protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots.

5.4 Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

6. ACCIDENTAL SPILLAGE MEASURES

6.1 Personal precautions: Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. For exposure controls and personal protection measures, see section 8.

6.2 Environmental precautions: Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sews, inform the appropriate authorities in accordance with local regulations.

6.3 Cleaning-up methods: Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Clean preferably with a detergent. Keep the remains in a closed container. For subsequent waste disposal, follow the recommendations in section 13.

7. HANDLING AND STORAGE

7.1 Handling precautions: Comply with the health and safety at work laws.

- General recommendations: Avoid any type of leakage or escape.

- Recommendations for the prevention of fire and explosion risks: Vapours are heavier than air and may spread along floors to a considerable distance. Vapours can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Do not smoke. Electrical equipment should be protected to the appropriate standard. No tools with a potential for sparks should be used. Use explosion protected equipment. Switch mobile phones off. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50° C. Do not pierce or burn aerosol even after use. Do not spray on a naked flame or any incandescent material.

- Recommendations for the prevention of toxicological risks: Avoid applying the product directly to people, animals, plants or foodstuffs. Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.

7.2 Storage conditions: Prevent unauthorized access. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area.

Class of store: According to current legislation. OSHA Storage: 1C. Maximum storage period: 12. months. Temperature interval: min:5.°C 41°F, max: 35.°C 95°F.

7.3 Materials to avoid: Keep away from oxidizing agents, acids, alkalis

7.4 Conditions to avoid: Heat: Keep away from sources of heat. Light: Avoid direct contact with sunlight. Humidity: Avoid extreme humidity conditions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION (98/24/CE)

8.1 Occupational Exposure Limits (TLV) AGCIH 2000

	TWA		STEL		Year
	ppm	mg/m3	ppm	mg/m3	
Toluene	50	188			A4 Derm. 1996

A4 - Non classified as carcinogenic in humans.

8.2 Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particles and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Ventilation requirement: 1788 m3/l (maximum) Air/Preparation
to keep below the Occupational Exposure Limit of the product. Special ventilation is required.

8.3 Protection of respiratory system: Avoid the inhalation of vapours.

Mask: Filter mask.

8.4 Protection of eyes and face: Install emergency eye baths close to the working area. Goggles: Safety goggles designed to protect against liquid splashes. Face shield: No.

8.5 Protection of hands and skin: Install emergency showers close to the working area. Gloves: Protective gloves of a suitable material. Boots: No. Apron: No. Clothing: Personnel should wear antistatic clothing made of natural fibre or of high temperature resistant synthetic fibre.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state: Liquid
- Colour: Grey/Black
- Odour: Characteristic.
- Viscosity: 35.000 cps 20°C 68°F
- Specific gravity: 0.82 g/cc at 20°C 68°F
6.8 lb/gal at 68°F
- Flash point: - 41 °C -42 °F Setaflash
- Autoignition temperature: 441 °C 826 °F
- Decomposition temperature: 350 °C 662 °F

13. CONSIDERATIONS FOR DISPOSAL

13.1 Handling of waste: Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local/national regulations. For exposure controls and personal protection measures, see section 8.

13.2 Disposal of empty containers: Emptied containers and packaging should be disposed of in accordance with currently local/national regulations.

13.3 Procedures for neutralising or destroying the product: In accordance with local regulations. Do not incinerate closed containers.

14. TRANSPORT INFORMATION

AEROSOL

- 14.1 Land: Transport by road: ADR-1999
Transport by rail: RID/TPF
Class: 2 Item: 5F UN n°1950
Transport document: Consignment paper
- 14.2 Sea: Transport by ship: IMDG
Class: 2 UN n°1950 Marine pollutant: no Packaging group: II
IMDG Code Page: 2102
Emergency Sheet (EmS): 2-13
First Aid Guide (MFAG): 620*
Transport document: Shipping Bill of Lading
- 14.3 Air: Transport by plane: IATA/ICAO
Class: 2 UN n°1950 Packaging group: II
Transport document: Air Bill of Lading

15. INFORMATION ON REGULATIONS CONCERNING PACKAGING AND LABELLING

15.1 UE Regulations

Labelling F+, Xn

This product is extremely flammable and harmful in accordance with RD.363/1995 (67/548/CEE) and RD.1078/1993 (88/379/CEE).

R20 Harmful by inhalation.

S16 Keep away from sources of ignition- No smoking.

S23 Do not breathe vapour/spray.

S51 Use only in well-ventilated areas.

10. STABILITY AND REACTIVITY

10.1 Stability: Stable under recommended storage and handling conditions.

10.2 Dangerous reactions: Possible dangerous reaction with oxidizing agents and acids.

10.3 Thermal decomposition: As consequence of thermal decomposition, hazardous products may be produced.

11. TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available.

11.1 Toxicological effects: Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Symptoms and signs include: headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Ingestion may result in the following effects: sore throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea; other effects may be as described for exposure to vapours. Repeated or prolonged contact with the solvents of the preparation, may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Liquid splashes in the eyes may cause irritation and reversible damage.

11.2 Dose and lethal concentrations for individual ingredients:

	DL50 Oral mg/kg	DL50 Cutaneous mg/kg	CL50 Inhalation mg/l.4hours
Toluene	5000 Rat	12124 Rabbit	15 Rat

For more information about ingredients dangerous to health, see sections 2 and 8.

12. ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available.

12.1 Spills on the soil: Prevent contamination of soil.

12.2 Spills in water: Do not allow to escape into drains, sewers or water courses.

12.3 Emissions to the atmosphere: Avoid any solvent release into the atmosphere.

Wt % Solids:	30
Vol. % Solids:	15.3
Coating VOC:	4.16 lbs./gallon
Solvent Density:	5.65 lbs./gallon
Aromatic hydrocarbons:	36% Weight

12.4 Ecotoxicological data for individual ingredients:

	CL50 mg/l.96hours	CE50 mg/l.48hours	CI50 mg/l.72hours
Toluene	24 Fishes	12 Daphnia	400 Algae

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50° C. Do not pierce or burn aerosol even after use. Do not spray on a naked flame or any incandescent material.

Dangerous ingredients: Toluene.

Type of packaging: According to current legislation.

15.2 US (Federal) Regulations

TSCA: All components of this product are either listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA regulations.

NFPA 704:



15.3 Canadian Regulations

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

According to the WHMIS this product is classified as: B5, D2A

16. OTHER INFORMATION

Intended use

Only for professional use.

Text of R-phrases listed in section 2:

R11 Highly flammable.

R20 Harmful by inhalation.

Labelling regulations: The information provided in this Material Safety Data Sheet has been written in accordance with annex III of RD.1078/1993 (88/379/EEC and 91/155/EEC) dated on July 2, published in the BOE on September 9, 1993 updated to the RD.1425/1998 (96/65/EC and 93/112/EEC) dated on July 3, published in the BOE on July 4, 1998, and also with RD.363/1995 (67/548/EEC) dated on March 10, published in the BOE on June 5, 1995, which approves the Regulations on Notification of New Substances and Classification, Packaging and Labelling of Dangerous Substances, whose technical annexes have been updated to the Order of April 5, 2001 (2000/32/EC and 2000/33/EC), published in the BOE on April 19, 2001.

The information of this Material Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material

Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.
