

SC 0091 - SC 0093
Thermo-55

Material Safety Data Sheet

1. Chemical Product & Company Data

Product Name: Thermo 55 (series) Generic MSDS *see Section 2*	
Wesmar Products 1440 NW 45th St Seattle, WA 98107 (206) 782-8186	

2. Ingredients

Name	CAS #	UN #	% by volume
Blended synthetic isoparaffinic hydrocarbon	64742-47-8		60-100
Fragrance - Aromatics (aldehydes, esters & ketones) and alcohols	n. av.		5-10
This MSDS pertains to the following "Thermo 55" fragrances			
Cherry, Citrus, Kentucky Bluegrass			
Mint, Unsmoke Neutral, Tabac-Attack			

3. Hazards Identification

Emergency Overview
Combustible Liquid. May cause severe eye irritation.
NOTE: Hazard information is based on the characteristics of the components of this mixture.
Ingestion - May cause abdominal discomfort, nausea, vomiting and diarrhea.
Inhalation - High concentration of the vapor may cause irritation of the respiratory tract.
Eye Contact - Causes slight eye irritation.
Skin Contact - Prolonged contact may cause discomfort, redness, drying and defatting of the skin.

4. First Aid

Ingestion - If patient is conscious give two glasses of water. Do not induce vomiting. Seek medical attention immediately.
Inhalation - Remove to fresh air. Administer artificial respiration if not breathing.
Eye Contact - Flush eyes with water for 15 minutes. Seek immediate medical attention.
Skin Contact - Remove contaminated clothing. Wash skin with soap and water. Obtain medical attention if irritation persists.

5. Fire Fighting Measures

Flammability Yes ☒ No ☐	If yes, under which conditions?	Combustible liquid. Potential fire hazard when exposed to excessive heat, flame or other sources of ignition.
Flashpoint: *see Section 16*	Upper flammable limit % by volume 5.0	Lower flammable limit % by volume 0.7
Autoignition temperature 638.6 °F (337 °C)	Hazardous combustion products Carbon monoxide and/or carbon dioxide	Explosion data n. ap.
Means of extinction:	Apply alcohol type or all purpose foam for large fires. Use dry chemical media or carbon dioxide extinguishers for small fires. SCBA and bunker gear for fire department personnel.	

6. Accidental Release Measures

Eliminate all sources of ignition. Wear personal protective equipment. Do not allow spill to reach watercourse or sewers. Contain spill with absorbent mats or booms or inert materials such as sand. Material should be readily available in the workplace. Collect and store waste materials in suitable containers for disposal i.e. metal drums.

7. Handling & Storage

Extinguish all sources of ignition in the work area. If the product is stored in metal containers the container must be grounded and bonded prior to dispensing the liquid. To prevent vapor escaping to the atmosphere keep all containers closed or covered. The product should be stored in a separate room equipped for flammable liquid storage or small volumes may be stored in a flammable liquid cabinet. Eyewash stations are required in the workplace. If eye irritation is encountered the use of a full facepiece respirator is recommended. Mechanical ventilation is recommended in enclosed workspaces. Area should be evacuated of all non essential personnel prior to application of product.
--

8. Exposure Controls & Personal Protection

Personal Protective Equipment		
Gloves Natural Rubber	Respirator NIOSH TC-23C organic vapor respirator or equivalent	Eye Goggles or full face respirator
Footwear n. ap.	Clothing Coveralls or equivalent	Other n. ap.
Exposure Guidelines		
none established for product		

9. Physical and Chemical Properties

Physical state Liquid	Odor and appearance Clear liquid, colorless to light yellow color, various odors (see Sec. 2)	
Odor threshold (ppm) n. av.	Vapor pressure (mm Hg) < 1 mm	Vapor density (Air=1) 4.5
Evaporation (butyl acetate = 1) n. av.	Boiling point 431.6 °F - 483.3 °F (222 °C - 251 °C)	Freezing point n. av.
pH 4.0 - 7.0	Specific gravity 0.79	Coefficient water/oil distribution n. av.
Solubility in water 0%	Viscosity @ 77 °F (25 °C) 3 cs	% Volatiles (by weight) n. av.

10. Stability and Reactivity

Chemical Stability Yes ☒ No ☐	If no, under which conditions?
Incompatibility with other substances Yes ☒ No ☐	If yes, under which conditions? Avoid contact with strong oxidizers.
Reactivity, and under what conditions? Stable under normal conditions.	
Hazardous decomposition products? Carbon monoxide and/or carbon dioxide as combustion by-products.	

11. Toxicological Information

Route of Entry Skin Contact ☒ Skin Absorption ☐ Eye Contact ☒ Inhalation ☒ Ingestion ☒			
No toxicity studies have been conducted for the product.			
Carcinogenicity No	Mutagenicity No	Teratogenicity No	Reproductive toxicity No
Synergistic products No	Sensitization No	Neurotoxicity No	Target organs Eyes and Skin

12. Ecological Information

n. av.

13. Disposal Considerations

Do not dispose of product in storm or sanitary sewer systems.
Do not allow discharge into groundwater or a watercourse.
If product is to be disposed of, contact a licensed or registered waste disposal firm to incinerate the product.

14. Transport Information

Shipping Name: NOT REGULATED
Hazard Class:
UN Identification #:

Note: In containers of 119 gallons (US) capacity or less this product is not regulated by D.O.T.
*Thermo-55 Mint ships ORM-D Ground in the United States.

15. Regulatory Information

This material safety data sheet has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Hazardous Products Act (Can.) and the Controlled Products Regulations (Can.) This product has been classified in accordance with the hazard criteria of the CPR (Can.) and the MSDS contains all the information required by the CPR (Can.).

This product is classed as a **combustible liquid** - 29 CFR 1910.1200 and Controlled Products Regulations (Can.)

WHMIS classification **B3**

This product is not subject to the reporting requirement of Section 313 of Title III of Superfund Amendments and Reauthorization Act (SARA) 1986 and 40 CFR part 372.

16. Other Information

Citrus - 179 °F (81.5 °C)	Cherry - 154 °F (67.7 °C)
*Mint - 99 °F (37 °C)	KBG - 183 °F (84 °C)
Unsmoke Neutral - 190 °F (87.8 °C)	Tabac-Attack - 174 °F (79 °C)

For chemical emergency during transportation call INFOTRAC (US) **1-800-535-5053** (INT'L) **1-352-323-3500**

Prepared by: Il Rep-Z, Inc., Coraopolis, PA / Cliff Zlotnik

Date: February 19, 2007

Abbreviations:

n. av. = not available
mm Hg = millimeters of Mercury
COC = Cleveland Open Cup
LD = Lethal Dose

n. ap. = not applicable
PMCC = Pensky Martens Closed Cup
TWA = Time Weighted Average
LC = Lethal Concentration

ppm = parts per million
TCC = Tagliabue Closed Cup
STEL = Short Term Exposure Limit
CS = centistokes