

SF 1516

Material Safety Data Sheet

1516

acc. to ISO/DIS 11014

12/16/2002

1 Identification of substance

- Product Name: URETHANE PRIMER, BLACK MSDS DATED 12/16/2002
- Product Number: 1516
- Application of the substance / the preparation :
Primer for adhesive or sealant

Wesmar Products, Inc

1440 NW 45th St

RS 24 HOUR EMERGENCY PHONE (INFOTRAC) 800-535-5053

Seattle, WA 98107

(206) 782-8186

INFORMATION TELEPHONE (800) 451-7206

2 Composition/Data on components

- Chemical characterization
- Description: Mixture of polyisocyanates in organic solution
- Dangerous components:

123-86-4 n-butyl acetate	15-25 %
R 10-66-67	
108-65-6 2-methoxy-1-methylethyl acetate	< 2 %
Xi; R 10-36	
822-06-0 hexamethylene diisocyanate	<0.15 %
T; R 23-36/37/38-42/43	
584-84-9 toluene 2,4-di-isocyanate	* %
T+; R 26-36/37/38-40-42/43-52/53	
91-08-7 toluene 2,6-di-isocyanate	* %
T+; R 26-36/37/38-40-42/43-52/53	
1333-86-4 Carbon black	5-10 %
78-93-3 butanone	40-60 %
Xi, F; R 11-36-66-67	
28182-81-2 aliphatic polyisocyanate	4-9 %
Xi; R 43	
- Additional information:
For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- Hazard description:
 - Xi Irritant
 - F Highly flammable
- Information pertaining to particular dangers for man and environment:
 - R 36 Irritating to eyes.
 - R 43 May cause sensitization by skin contact.
 - R 66 Repeated exposure may cause skin dryness or cracking
 - R 67 Vapours may cause drowsiness and dizziness (Contains isocyanates.
 - See information supplied by the manufacturer.
- Classification system:
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data
- NFPA ratings (scale 0 - 4)
 - Health = 3
 - Fire = 3
 - Reactivity = 2

Material Safety Data Sheet

1516

acc. to ISO/DIS 11014

12/16/2002

4 First aid measures

• General information:

Immediately remove any clothing soiled by the product.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness stabilize patient in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor

• After swallowing:

Do not induce vomiting; immediately call for medical help.

• The following symptoms may occur:

Headache

Dizziness

Gastric or intestinal disorders

Dizziness

Breathing difficulty

5 Fire fighting measures

• Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• For safety reasons unsuitable extinguishing agents: Water with full jet!

• Special hazards caused by the material, its products of combustion or resulting gases.

In case of fire, the following can be released:

Carbon monoxide (CO)

Hydrogen chloride (HCl)

Nitrogen oxides (NOx)

In certain fire conditions, traces of other toxic gases cannot be excluded

Hydrogen cyanide (HCN)

Isocyanates

• Protective equipment: Mount respiratory protective device.

6 Accidental release measures

• Person-related safety precautions:

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Keep away from ignition sources

• Measures for environmental protection:

Do not allow to enter sewers/ surface or ground water.

• Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

Do not close them (reaction with water forming carbon dioxide)

7 Handling and storage

• Handling:

• Information for safe handling:

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

• Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

• Storage:

Material Safety Data Sheet

1516

acc. to ISO/DIS 11014

12/16/2002

- Requirements to be met by storerooms and receptacles:
Store in a cool location.
Provide ventilation for receptacles.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
Keep receptacle tightly sealed.

8 Exposure controls and personal protection

- Additional information about design of technical systems:
No further data; see item 7.
Components with limit values that require monitoring at the workplace:
78-93-3 butanone
ACGIH TLV: Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI
NIOSH REL: Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
OSHA PEL: 590 mg/m³, 200 ppm

123-86-4 n-butyl acetate

- ACGIH TLV: Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm
NIOSH REL: Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm
OSHA PEL: 710 mg/m³, 150 ppm

822-06-0 hexamethylene diisocyanate

- ACGIH TLV: 0.034 mg/m³, 0.005 ppm
NIOSH REL: Short-term value: C 0.14* mg/m³, C 0.2 ppm
Long-term value: 0.035 mg/m³, 0.005 ppm
*10-min

584-84-9 toluene 2,4-di-isocyanate

- ACGIH TLV: Short-term value: 0.14 mg/m³, 0.02 ppm
Long-term value: 0.036 mg/m³, 0.005 ppm
NIC-SEN
NIOSH REL: Reduce exp. to lowest feasible. conc.
OSHA PEL: Short-term value: C 0.14 mg/m³, C 0.02 ppm

91-08-7 toluene 2,6-di-isocyanate

- ACGIH TLV: Short-term value: A4; mg/m³, 0.14 ppm
Long-term value: 36 0.02 mg/m³, 0.005 0.00 ppm
NIC-SEN

- NIOSH REL: Reduce exp. to lowest feasible. conc.

- Additional information:
The lists that were valid during the creation were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.
Wash hands before breaks and at the end of work.
Do not eat, drink or smoke while working.
Immediately remove all soiled and contaminated clothing.
Pregnant women should strictly avoid inhalation or skin contact.
- Breathing equipment:

Material Safety Data Sheet

1516

acc. to ISO/DIS 11014

12/16/2002

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device:

Filter AB/P3

• Protection of hands:

PVA or natural rubber gloves of superior quality.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• Eye protection: Goggles recommended during refilling.

• Body protection: Protective work clothing

9 Physical and chemical properties

• General Information

• Form: Fluid

• Color: Black

• Odor: Pungent

•

	Value/Range	Unit	Method
--	-------------	------	--------

• Change in condition

• Melting point/Melting range: Undetermined.

• Boiling point/Boiling range: 79 ° C

• Flash point: -4 ° C

• Ignition temperature: >200 ° C

• Auto igniting: Product is not selfigniting.

• Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

• Explosion limits:

• Lower: 1.8 Vol. %

• Upper: 11.5 Vol. %

• Density: at 20 ° C 1

• Solubility in / Miscibility with

• Water: Partly miscible.

• Viscosity:

• Dynamic: at 20 ° C 50 mPa.s

• Solvent content:

• Solids content: 30 %

10 Stability and reactivity

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

• Materials to be avoided:

• Dangerous reactions

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with water forming carbon dioxide. Danger of receptacles bursting because of vapour overpressure.

Reacts with strong oxidizing agents.

• Dangerous products of decomposition:

None to our knowledge at room temperature.

Material Safety Data Sheet

1516

acc. to ISO/DIS 11014

12/16/2002

11 Toxicological information

- Acute toxicity:
- Primary irritant effect:
 - on the skin:
Frequent or prolonged contact may irritate and cause dermatitis.
 - on the eye: Irritating effect
- Sensitization: Sensitization possible through skin contact.

12 Ecological information

- General notes:
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- Product:
- Recommendation: Must be disposed of in an incinerator for hazardous waste according to official regulations.
- Uncleaned packaging:
- Recommendation:
Disposal must be made according to official regulations.

14 Transport information

- DOT regulations:
- Hazard class: 3
- Identification number: UN1866
- Packing group: II
- Proper shipping name (technical name):
RESIN SOLUTION
- Label 3
- Land transport ADR/RID (cross-border):
- ADR/RID class: 3 Flammable liquids
- Danger code (Kemler): 339
- UN-Number: 1866
- Packaging group: II
- Maritime transport IMDG:
- IMDG Class: 3
- UN Number: 1866
- Label 3
- Packaging group: II
- EMS Number: 3-05
- Marine pollutant: No
- Proper shipping name: RESIN SOLUTION
- Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class: 3
- UN/ID Number: 1866
- Label 3
- Packaging group: II
- Proper shipping name: RESIN SOLUTION

15 Regulations

- Sara
Section 355 (extremely hazardous substances):
None of the ingredient is listed.
Section 313 (Specific toxic chemical listings):
78-93-3 butanone
TSCA (Toxic Substances Control Act):
78-93-3 butanone

Material Safety Data Sheet

1516

acc. to ISO/DIS 11014

12/16/2002

- Proposition 65
Chemicals known to cause cancer: None of the ingredients is listed.
Chemicals known to cause reproductive toxicity: None of the ingredients is listed.
- Cancerogenity categories
EPA (Environmental Protection Agency)
78-93-3 butanone: D
IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
NTP (National Toxicology Program)
None of the ingredients is listed.
TLV (Threshold Limit Value established by ACGIH)
584-84-9 toluene 2,4-di-isocyanate: A4
MAK (German Maximum Workplace Concentration)
584-84-9 toluene 2,4-di-isocyanate: 3
NIOSH-Ca (National Institute for Occupational Safety and Health)
584-84-9 toluene 2,4-di-isocyanate
OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.
- Product related hazard information: -
- Hazard symbols:
Xi Irritant
F Highly flammable
- Hazard-determining components of labelling: aliphatic polyisocyanate
- Risk phrases:
36 Irritating to eyes.
43 May cause sensitization by skin contact.
66 Repeated exposure may cause skin dryness or cracking
67 Vapours may cause drowsiness and dizziness
- Safety phrases:
7/9 Keep container tightly closed and in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
24 Avoid contact with skin.
33 Take precautionary measures against static discharges.
37 Wear suitable gloves.
- Special labeling of certain preparations:
Contains isocyanates. See information supplied by the manufacturer.

: 16 Other information

DISCLAIMER: The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and **International Epoxies & Sealers** disclaims any and all liability or legal responsibility or use or reliance upon same.