

SF 1548

1548
11/1/2001

MATERIAL SAFETY DATA SHEET

SECTION I PRODUCT IDENTIFICATION AND USE

PRODUCT NAME / IDENTIFICATION

IES 1548 SEAM SEALER (CLEAR)

W.H.M.I.S. STATUS

CONTROLLED

W.H.M.I.S. CLASSIFICATION

CLASS B-2 FLAMMABLE, D2B TOXIC

PRODUCT IDENTIFICATION NUMBER

MIXTURE

PRODUCT DESCRIPTION

SEALER

MANUFACTURER

INTERNATIONAL EPOXIES & SEALERS
30241 COMMERCE DR.
SAN ANTONIO, FL 33576

24 HOUR EMERGENCY PHONE

INFOTRAC (800) 451-7206

SUPPLIER

WESMAR PRODUCTS, INC.
1440 NW 45th St
Seattle, WA 98107
11(206) 782-8186

SECTION II HAZARDOUS INGREDIENTS

%	HAZARDOUS INGREDIENTS	UN/CAS #	LC50(TLV)	LD50(ORAL)	LD50(DERMAL)
40-45	Toluene	108-88-3	*8000 PPM (RATS)	2500 Mg/Kg (RATS)	14200 Mg/Kg (RABBITS)
10-15	Styrene- Alphamethylstyrene resin	9011-11-4	N/D	N/D	N/D

Actual LC 50 numbers are preceded by an asterisk *. Where this information is not available a Threshold Limit value (ppm in brackets) may be provided as an indication of the inhalation severity of the ingredient.

SECTION III PHYSICAL DATA

PHYSICAL STATE	COLOR	ODOR THRESHOLD (PPM)
GEL	CLEAR WITH ESTER SOLVENT ODOR	N/D
VAPOR PRESSURE (mm Hg)	VAPOR DENSITY (Air=1)	EVAPORATION RATE
N/D	>1.0	N/D
pH	SPECIFIC GRAVITY (Kg/l)	BOILING POINT (C)
N/D	.92	110
	COEFF. WATER/OIL DIST.	SOLUBILITY IN WATER (20 C)
	N/D	NOT SOLUBLE

SECTION IV FIRE AND EXPLOSION DATA

FLAMMABILITY IF YES, UNDER WHICH CONDITIONS?
YES ☒ NO ☐ ON CONTACT WITH IGNITION SOURCE, FLAME OR TEMPERATURE ABOVE FLASHPOINT

MEANS OF EXTINCTION

☒ CARBON DIOXIDE
☒ DRY CHEMICAL☒ FOAM
☒ WATER STREAM☐ FOG SPRAY
☐ OTHER (SEE SPECIAL PROCEDURES)

SPECIAL PROCEDURES

FIRE FIGHTERS CLOSE ENOUGH TO BE IN CONTACT WITH FUMES SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. SOLVENT VAPOURS CAN FLASH-BACK AND FORM EXPLOSIVE MIXTURES WITH AIR. USE FOG SPRAY TO COOL DOWN NEARBY CONTAINERS ONLY.

FLASHPOINT (C) (METHOD)	LOWER FLAMMABLE LIMIT (% BY VOLUME)	UPPER FLAMMABLE LIMIT (% BY VOLUME)
45 F (TCC)	1.2	7.0

AUTO-IGNITION TEMPERATURE (C)	HAZARDOUS COMBUSTION PRODUCTS
N/D	OXIDES OF NITROGEN

EXPLOSIVE DATA	SENSITIVITY TO IMPACT	SENSITIVITY TO STATIC DISCHARGE
	NONE	NONE

SECTION V REACTIVITY DATA

CHEMICAL STABILITY IF NO, UNDER WHICH CONDITIONS
YES ☒ NO ☐

INCOMPATIBLE SUBSTANCES IF YES, WHICH ONES
YES ☒ NO ☐ ALKALINE MATERIALS, STRONG ACIDS AND OXIDIZING AGENTS.

REACTIVITY AND UNDER WHICH CONDITIONS?

NONE KNOWN

HAZARDOUS DECOMPOSITION

CARBON MONOXIDE, CARBON DIOXIDE AND OXIDES OF NITROGEN

SECTION VI TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY

☒ SKIN CONTACT☒ SKIN ABSORPTION☒ EYE CONTACT☒ INHALATION☒ INGESTION

EFFECTS OF ACUTE EXPOSURE TO PRODUCT

IRRITATION OF EYES, NOSE, THROAT AND LUNGS. HEADACHE, DIZZINESS, IMPAIRMENT OF CO-ORDINATION, DERMATITIS AND DEFATTING OF SKIN IS POSSIBLE. CAN CAUSE GASTROINTESTINAL IRRITATION.

EFFECTS IF CHRONIC EXPOSURE TO PRODUCT

REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS MAY LEAD TO PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

LD-50-(ORAL)

N/D

LD-50-(DERMAL)

N/D

LC-50

N/D

EXPOSURE LIMITS

200 PPM (EST)

IRRITANCY OF PRODUCT

MODERATE

SENSITIZATION

NON-SENSITIZING

CARCINOGENICITY

NON-CARCINOGENIC

TERATOGENICITY

NON-TERATOGENIC

REPRODUCTIVE TOXICITY

NONE KNOWN

MUTAGENICITY

NONE KNOWN

SYNERGISTIC PRODUCTS

NONE KNOWN

SECTION VII PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

SELF CONTAINED RESPIRATOR IF VENTILATION IS INADEQUATE. WEAR GOGGLES, FACE SHIELD AND RUBBER GLOVES WHEN HANDLING.

ENGINEERING CONTROLS

USE WITH ADEQUATE VENTILATION. ELECTRICAL AND MECHANICAL EQUIPMENT SHOULD BE SPARK PROOF.

LEAK AND SPILL PROCEDURES

REMOVE ALL IGNITION SOURCES, TURN OFF ALL ELECTRIC MOTORS, ABSORB WITH INERT MATERIAL KEEP SPILLS AWAY FROM MUNICIPAL SEWERS.

WASTE DISPOSAL

DISPOSE OF IN ACCORDANCE WITH LOCAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT

KEEP CONTAINER CLOSED WHEN NOT IN USE

STORAGE REQUIREMENTS

STORE IN FLAMMABLE GOODS AREA

SPECIAL SHIPPING INSTRUCTIONS

NONE

SECTION VIII FIRST AID MEASURES

EYE CONTACT

FLUSH EYES WITH GENTLE STREAM OF WATER FOR AT LEAST 15 MINUTES. CONTACT A PHYSICIAN.

SKIN CONTACT

RINSE EFFECTED AREAS WITH MILD SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. WASH CLOTHING BEFORE REUSE.

INHALATION

REMOVE VICTIM TO FRESH AIR. PROVIDE CPR AND OXYGEN, IF NECESSARY. CONTACT PHYSICIAN.

ASPIRATION / INGESTION

DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

OTHER

IN ALL CASES SEE A PHYSICIAN IF ANY PROBLEMS PERSIST.

SECTION IX PREPARATION DATE OF MSDS

PREPARED BY

INTERNATIONAL EPOXIES & SEALER

INFORMATION PHONE

(800) 451-7206

DATED

NOV 1 2001

WARRANTY AND DISCLAIMER: The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of Pro Form Products knowledge. The information relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Customer should read and understand this MSDS sheet and package labeling before using the product. SELLER DISCLAIMS ANY IMPLIED WARRANTIES OR MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Seller will at its option, either replace the goods sold or refund the purchase price. No warranty will apply if the goods are in any way altered or modified after delivery by the seller.