

# SF 4519-European Black Trim Paint

## M A T E R I A L   S A F E T Y   D A T A   S H E E T

4519

### SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : IES 4519 EUROPEAN BLACK TRIM PAINT  
 IDENTIFICATION NUMBER: DATE PRINTED: 04/23/01  
 PRODUCT USE/CLASS : EUROPEAN BLACK PAINT

Wesmar Products  
 1440 NW 45th St  
 Seattle, WA 98107  
 (206) 782-8186  
 24 HOUR EMERGENCY PHONE (INFOTRAC) 800 535-5053

### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

| ITEM | CHEMICAL NAME              | CAS NUMBER | WT/WT %<br>LESS THAN |
|------|----------------------------|------------|----------------------|
| 01   | PROPANE/ISOBUTANE/N-BUTANE | 68476-86-8 | 35.0 %               |
| 02   | TOLUENE                    | 108-88-3   | 20.0 %               |
| 03   | 2-PROPANONE                | 67-64-1    | 20.0 %               |
| 04   | DIMETHYLBENZENE            | 1330-20-7  | 10.0 %               |
| 05   | 2-BUTANONE                 | 78-93-3    | 10.0 %               |
| 06   | TALC                       | 14807-96-6 | 5.0 %                |
| 07   | ETHYLBENZENE               | 100-41-4   | 5.0 %                |
| 08   | CARBON BLACK               | 1333-86-4  | 5.0 %                |
| 09   | CALCIUM CARBONATE          | 1317-65-3  | 5.0 %                |

| EXPOSURE LIMITS |           |          |           |             |         |      |
|-----------------|-----------|----------|-----------|-------------|---------|------|
| ITEM            | ACGIH     |          | OSHA      |             | COMPANY | SKIN |
|                 | TLV-TWA   | TLV-STEL | PEL-TWA   | PEL-CEILING | TLV-TWA |      |
| 01              | 800 PPM   | N.E.     | 800 PPM   | N.E.        | N.E.    | YES  |
| 02              | 100 PPM   | 150 PPM  | 50 PPM    | N.E.        | N.E.    | NO   |
| 03              | 750 PPM   | 1000 PPM | 750 PPM   | N.E.        | N.E.    | NO   |
| 04              | 100 PPM   | 150 PPM  | 100 PPM   | N.E.        | N.E.    | NO   |
| 05              | 200 PPM   | 300 PPM  | 200 PPM   | N.E.        | N.E.    | YES  |
| 06              | 2 MG/M3   | N.E.     | 2 MG/M3   | N.E.        | N.E.    | NO   |
| 07              | 100 PPM   | 125 PPM  | 100 PPM   | N.E.        | N.E.    | YES  |
| 08              | 3.5 MG/M3 | N.E.     | 3.5 MG/M3 | N.E.        | N.E.    | NO   |
| 09              | 10 MG/M3  | N.E.     | 15 MG/M3  | N.E.        | N.E.    | NO   |

(See Section 16 for abbreviation legend)

(Continued on Page 2)

---

SECTION 3 - HAZARDS IDENTIFICATION

---

\*\*\* EMERGENCY OVERVIEW \*\*\*: Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: No hazard in normal industrial use. This material may be harmful or fatal if swallowed. Corrosive and may cause severe and permanent damage to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Overexposure may cause lung damage. Overexposure may cause kidney damage.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION  
INGESTION EYE CONTACT

---

SECTION 4 - FIRST AID MEASURES

---

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: Get medical attention immediately. If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

---

SECTION 5 - FIRE FIGHTING MEASURES

---

FLASH POINT: -156 F  
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: 0.8 %  
UPPER EXPLOSIVE LIMIT: 12.8 %

(Continued on Page 3)

---

**SECTION 5 - FIRE FIGHTING MEASURES**

---

AUTOIGNITION TEMPERATURE: ND

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

---

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

---

**SECTION 7 - HANDLING AND STORAGE**

---

HANDLING: Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep from freezing.

---

**SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

(Continued on Page 4)

---

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

---

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

---

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

|                                                   |               |                   |                              |
|---------------------------------------------------|---------------|-------------------|------------------------------|
| BOILING RANGE                                     | : -43 - 284 F | VAPOR DENSITY     | : Is heavier than air        |
| ODOR                                              | : SOLVENT     | ODOR THRESHOLD    | : ND                         |
| APPEARANCE                                        | : BLACK       | EVAPORATION RATE: | Is faster than Butyl Acetate |
| SOLUBILITY IN H2O                                 | : NEGLIGIBLE  | SPECIFIC GRAVITY: | 0.7494                       |
| FREEZE POINT                                      | : 32          | pH @ 0.0 %        | : NA                         |
| VAPOR PRESSURE                                    | : 80-90       | VISCOSITY         | : NA                         |
| PHYSICAL STATE                                    | : LIQUID      |                   |                              |
| COEFFICIENT OF WATER/OIL DISTRIBUTION: NEGLIGIBLE |               |                   |                              |

(See Section 16 for abbreviation legend)

---

SECTION 10 - STABILITY AND REACTIVITY

---

CONDITIONS TO AVOID: ALL SOURCES OF IGNITION, WELDING ARCS, AND OPEN FLAMES.

INCOMPATIBILITY: STRONG ACIDS, ALKALIS, OXIDIZERS, AND AMINES.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, OXIDES OF NITROGEN, AND MAY PRODUCE FORMS OF CHLORIDE, CHLORINE, AND PHOSGENE.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

---

SECTION 11 - TOXICOLOGICAL PROPERTIES

---

PRODUCT LD50: 636 mg/kg

PRODUCT LC50: 49 ppm

COMPONENT TOXICOLOGICAL INFORMATION:

| CHEMICAL NAME              | LD50          | LC50            |
|----------------------------|---------------|-----------------|
| PROPANE/ISOBUTANE/N-BUTANE | NE            | 57 PPH/15M/RAT  |
| TOLUENE                    | 636 MG/KG/RAT | 49 GM/M3/4H/RAT |

(Continued on Page 5)

-----  
SECTION 11 - TOXICOLOGICAL PROPERTIES  
-----

| ----- CHEMICAL NAME ----- | ----- LD50 ----- | ----- LC50 -----   |
|---------------------------|------------------|--------------------|
| 2-PROPANONE               | 5800 MG/M3 RAT   | 50100 MG/M3/8H RAT |
| DIMETHYLBENZENE           | 4300 MG/M3 RAT   | 5000 PPM/4H RAT    |
| E-7657-A FLAT BLACK       | NE               | NE                 |
| 2-BUTANONE                | 2737 MG/KG/RAT   | 23500 MG/M3/8H/RAT |
| TALC                      | NE               | TCLO               |
| ETHYLBENZENE              | 3500 MG/KG/RAT   | NE                 |
| CARBON BLACK              | >15400 MG/KG/RAT | NE                 |
| CALCIUM CARBONATE         | NE               | NE                 |

-----  
SECTION 12 - ECOLOGICAL INFORMATION  
-----

ECOLOGICAL INFORMATION: No Information.

-----  
SECTION 13 - DISPOSAL CONSIDERATIONS  
-----

DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

-----  
SECTION 14 - TRANSPORTATION INFORMATION  
-----

DOT PROPER SHIPPING NAME: AEROSOL - CONSUMER COMMODITY

DOT TECHNICAL NAME: ORM-D

DOT HAZARD CLASS: 2.1

HAZARD SUBCLASS: NA

DOT UN/NA NUMBER: UN1950

PACKING GROUP: NA

RESP. GUIDE PAGE: 126

-----  
SECTION 15 - REGULATORY INFORMATION  
-----

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD   CHRONIC HEALTH HAZARD   FIRE HAZARD   PRESSURIZED  
GAS HAZARD

(Continued on Page 6)

-----  
SECTION 15 - REGULATORY INFORMATION  
-----

## SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

| ----- CHEMICAL NAME ----- | CAS NUMBER | WT/WT % IS LESS THAN |
|---------------------------|------------|----------------------|
| TOLUENE                   | 108-88-3   | 20.0 %               |
| DIMETHYLBENZENE           | 1330-20-7  | 10.0 %               |
| 2-BUTANONE                | 78-93-3    | 10.0 %               |
| ETHYLBENZENE              | 100-41-4   | 5.0 %                |

## TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

| ----- CHEMICAL NAME -----    | CAS NUMBER |
|------------------------------|------------|
| No information is available. |            |

## U.S. STATE REGULATIONS: AS FOLLOWS -

## NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

| ----- CHEMICAL NAME ----- | CAS NUMBER |
|---------------------------|------------|
| E-7657-A FLAT BLACK       | MIXTURE    |

## PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

| ----- CHEMICAL NAME ----- | CAS NUMBER |
|---------------------------|------------|
| E-7657-A FLAT BLACK       | MIXTURE    |

## CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

| ----- CHEMICAL NAME ----- | CAS NUMBER |
|---------------------------|------------|
| TOLUENE                   | 108-88-3   |

## INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

(Continued on Page 7)

---

SECTION 16 - OTHER INFORMATION

---

HMIS RATINGS - HEALTH: 3      FLAMMABILITY: 4      REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 04/23/01

REASON FOR REVISION: NEW FORMAT

VOLATILE ORGANIC COMPOUNDS (VOCS): 2.99 lbs/gal,    359 grams/ltr

LEGEND:   N.A. - Not Applicable, N.E. - Not Established,  
          N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.