

SF 8414

8414

MATERIAL SAFETY DATA SHEET

8/15/00

Wesmar Products, Inc.

1440 NW 45th St

Seattle, Wa 98107

(206) 782-8186

24 HOUR EMERGENCY INFORMATION TELEPHONE

CALL INFOTRAC (800)535-5053

INFORMATION PHONE (800)451-7206

SECTION 1 - PRODUCT IDENTIFICATION

PART NUMBER: 8414
 PRODUCT NAME: Inter-Mix 60 SMC Panel Bonding Adhesive
 TRADE NAME/SYNONYMS: Inter-Mix 60 SMC Panel Bonding Adhesive
 CHEMICAL FAMILY: Epoxy Adhesive

SECTION 11 - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NO.	WT%	PEL	TLV	STEL	UNITS	LC50 PPM	LD50	MG/KG
Part A -BASE									
Bisphenol A	25068-38-6	83-95	0.1	0.1	N/A	PPM	N/A	RAT 1	1100
Polyglycidyl Ether									
Silica (Fumed)	112945-52-53-6	<6	6*	10*	N/A	MG/M3	N/A	RAT 1	3160
Pigment Purple	N/A	<1	1*	1*	N/A	MG/M3	N/A	N/A	N/A
PART B - HARDENER									
Polyamid Curing Agent	Proprietary	35-55	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Polymercaptan Resin	Proprietary	7-15	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Tris (2,3,6-Dimethylaminomonomethyl) Phenol	90-72-2	5-9	N/A	N/A	N/A	N/A	N/A	RAT 1	1200
Polyamid Resin	Proprietary	15-30	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Silica (Fumed)	112945-52-53-6	<6	6*	10*	N/A	MG/M3	N/A	RAT 1	3160
Glass Beads	65997-17-3	1-3	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Zinc Phosphate	7779-90-0	1-4	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Titanium Dioxide	13463-67-7	<1	10*	10*	N/A	MG/M3	N/A	N/A	N/A

Symbols, Abbreviations and Notations:

N/A=Not applicable or available, C=Ceiling limit, S=Skin designation, #=Listed in SARA Title 111 Section 313, *=If found as dust, mist or fume, I=Ingestion, A=Skin absorption, LO=Little observable effect, NO=No effect, PEL=OSHA Permissible exposure limit, TLV=ACGIH Threshold limit value, STEL= Short term exposure limit, @=Non-Haz. Incred. Among 5 most Predom. Subst.

SECTION 111 - PHYSICAL DATA

Boiling Point DEG F/C: A=500/260(B=601/316)
 Specific Gravity: A=1.20-1.23 B=1.06-1.10
 Vapor Pressure (MM HG): A=N/A B=0.01
 %Volatile Volume: A&B=0.0%
 Vapor Density (AIR=1): A=Heavier B=9.0
 Evaporation Rate: (Water=1)0.01
 Solubility in Water: A=N/A B=Slight
 Water/Oil Dist COEFF: A&B=0
 Appearance and Odor: A=Purple Paste/<Mild Odor B=White Paste/Mercaptan Odor
 Physical State: Paste PH: N/A Freeze Point DEG F/C: N/A
 Threshold Odor, PPM: N/A Other: N/A Voc: LBS/GAS=N/A; Grams/Liter=N/A;
 Grams Voc/Gram Solid=N/A; % Voc N/A

MATERIAL SAFETY DATA SHEET

8414

8/15/00

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Classification: N/A
NFPA Rating: N/A
Combustion Products: Sulfur, Oxides of Nitrogen
Flash Point DEG F/C: A=200F(93C) TOC/B=315F (257C)COC LEL%: N/A
UEL%: N/A
Extinguishing Media: Water, Fog, Foam, Dry Chemical, Carbon Dioxide
UN/NA/PIN#: N/A
Special Fire Fighting Procedures: A & B= Firefighters should wear self-contained breathing equipment.
Auto IGN. Temp DEG F/C: N/A
Unusual fire and explosion Hazards: A & B=Contact with flame or hot surfaces may produce toxic gases.
Explosive Power: No
Impact Sensitive: No
Burning Rate: Low
Static Sensitive: No

SECTION V - HEALTH HAZARD DATA

Product Guide: TLV (See Section II) STEL: (See Section II)
Routes of Entry: Skin contact, absorption, eye, inhalation, ingestion
Effects of Overexposure:
A&B=Causes eye irritation, may cause skin sensitization or other allergic responses. Prolonged and repeated inhalation may be harmful to respiratory system or central nervous system.
Listed as a suspected carcinogen: No
Emergency and First Aid Procedures:
A&B=Eye: Immediately flush with plenty of water for 15 minutes and call physician.
Skin: Wash thoroughly with plenty of water and soap. Inhalation: If affected, remove to fresh air and see physician.
Ingestion: Seek Physician immediately. Show MSDS or label. Induce Vomiting.

SECTION VI - REACTIVITY DATA

Stable: Yes Conditions to Avoid: A&B=Keep away from heat or flame
Incompatibility (Materials to Avoid): Yes Acids, Amines, Mercaptan, STRG Oxidant
Hazardous decomposition products: es Amines, CO, H2S, SO2, NO2
Hazardous Polymerization: No conditions to avoid: A&B=N/A

SECTION VII - SPILL OR LEAK PROCEDURES

LISTED IN: SARA Title 111, #302: NO #304, CERCLA: No #313: No
Steps to be taken in case material is released or spilled:
A&B=In case of spill: Ventilate the area, wear approved respiratory protection, wear eye/face protection, clean up with absorbent material, contain & pick-up waste materials, put in a sealed approved container.
Report Quantity, LB: N/A KG: N/A TPQ, LB: N/A
Regulations: PROV/State, WHMIS
Hazard Waste: No
No.: N/A
A&B=Do not empty into drains. Dispose of wastes in accordance with Federal, State, and Local regulations.

MATERIAL SAFETY DATA SHEET

8414

8/15/00

SECTION VIII-SAFE HANDLING AND PROTECTION INFORMATION

Respiratory Protection: Use only in well ventilated areas.

Ventilation-Local: Recommended

Special: Keep away from heat/flame.

Mechanical: Required

Other: N/A

Protective Gloves: Solvent Resistant

Eye Protection: Goggles

Other Protective Equipment:

If ventilation is inadequate, wear approved respiratory equipment

Wear suitable protective clothing, gloves, and eye/face protection.

Estimated L 50, MG/KG: Yes ORAL RAT 1100; DERMAL RABBIT 1280

Estimated LC50, PPM: No

Sensitization: Yes Possible skin.

Irritant: Yes eyes & skin

Synergistic Agents: No

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage:

A&B=Keep in a cool place. Avoid contact with eyes and skin. Do not take internally. Wash thoroughly after using. In case of accident or illness, seek Physician immediately, show label or MSDS. Keep away from food, drink & animal feeds.

Other Precautions:

A&B=Keep out of reach of children. Keep only in original labeled containers.

Always read and follow directions on product label or data sheet. Additional technical data sheets and/or material safety data sheets MSDS are available upon request.

The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and International Epoxies and Sealers disclaims any and all liability or legal responsibility or use or reliance upon same.