

TM 1107

ASHLAND
SAFETY DATA SHEET

Page: 1
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Wesmar Products, Inc
1440 NW 45th St
Seattle, WA 98107
(206) 782-8186

Emergency telephone number 1-800-ASHLAND
(1-800-274-5263)

Product name	WESMAR TROPHY WAX Cleaner & Glaze
Product code	CBWPA056-03-U
Product Use Description	No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid, fruity, light orange

DANGER! Combustible Liquid, Highly toxic by inhalation, Moderate skin irritant, Moderate eye irritant, Carcinogen.

Potential Health Effects

Routes of Exposure

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye Contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Additional symptoms of eye exposure may include: halo vision (blurred vision around bright objects)

Skin Contact

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Additional symptoms of skin contact may include: skin blistering. Passage of this material into the body through the skin is possible, and skin contact may be harmful.

Ingestion

Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the

ASHLAND

SAFETY DATA SHEET

Page: 2
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), liver, kidney, eye. Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), thirst, irritation (nose, throat, airways), runny nose, lung irritation, cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, muscle weakness, pain in the abdomen, loss of coordination, confusion, difficult breathing, irregular heartbeat, narcosis (dazed or sluggish feeling), lung edema (fluid buildup in the lung tissue), kidney damage, liver damage, lung damage, convulsions, coma, and death

Target Organs

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Chronic feeding studies with white oils (greater than 0.5% in the diet) have resulted in increased organ weights (liver, kidney, spleen), and in microscopic areas of oil accumulation in the liver and the lymph nodes of the gut in experimental animals. These changes have occasionally been associated with cell damage. In humans, cell damage resulting from accumulation of these oil droplets has only occurred following prolonged ingestion of mineral oil. These effects are not expected to occur as a result of occupational exposure to white oils. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: nasal damage, eye damage, kidney damage, liver damage, lung damage

ASHLAND

SAFETY DATA SHEET

Page: 3
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

Carcinogenicity

This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal. The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have determined that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite. In addition, IARC has determined that there is sufficient evidence for the carcinogenicity of quartz and cristobalite in experimental animals. Among individuals with silicosis, lung cancer occurs more frequently in those who smoke. White mineral oil was not carcinogenic in laboratory animals by any route of exposure other than by injection into the abdomen. Results of abdominal injection are not relevant to possible human exposure to this material.

Reproductive Hazard

Tall oil fatty acids did not cause harm to the fetus when given in the diet of laboratory animals.

Other Information

Nitrites should not be added to this material because this can result in formation of nitrosamines. Many nitrosamines cause cancer in laboratory animals. When heated to temperatures above 150 degrees C in the presence of air, this product can form formaldehyde vapors. Formaldehyde has been identified as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and the Occupational Safety and Health Administration (OSHA). Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin. Formaldehyde is irritating to the eyes, nose, throat, and airways, and can cause an allergic reaction (causes narrowing of the air passages of the lungs, sweating, flushing, hives, rapid heart rate, and lowered blood pressure). In addition, formaldehyde can cause an allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects). It is harmful if inhaled, swallowed or absorbed through skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
MINERAL SPIRITS REGULAR (BASE DATA)	8052-41-3	>=20-<30%

ASHLAND

SAFETY DATA SHEET

Page: 4
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

ALUMINUM SILICATE CALCINED	66402-68-4	>=10-<15%
KEROSENE	8008-20-6	>=1.5-<5%
Fatty Acid	NJTS# 800986-5166P	>=1-<1.5%
TRIMETHYLBENZENE 1,2,4-	95-63-6	>=1-<1.5%
TRIMETHYLBENZENE, 1,3,5-	108-67-8	>=1-<1.5%
MORPHOLINE	110-91-8	>=1-<1.5%
GLYCERINE	56-81-5	>=1-<1.5%
ETHYL BENZENE	100-41-4	>=0.1-<0.5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek immediate medical attention. Do not induce vomiting. Vomiting will cause further damage to the mouth and throat. If individual is conscious and alert, immediately rinse mouth with water and give milk or water to drink. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Notes to Physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small

ASHLAND

SAFETY DATA SHEET

Page: 5
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

regular foam (such as AFFF), Agents approved for class B hazards or water fog., carbon dioxide (CO₂), dry chemical

Hazardous Combustion Products

May form: carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Precautions for Fire-Fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Flammability Class for Flammable Liquids

Combustible Liquid Class II

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

For personal protection see section 8. Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks.

Environmental Precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for Cleaning Up

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

ASHLAND

SAFETY DATA SHEET

Page: 6
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Handling equipment must be properly grounded.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

MINERAL SPIRITS REGULAR (BASE DATA) 8052-41-3

ACGIH	time weighted average	100 ppm
NIOSH	Recommended exposure limit (REL):	350 mg/m3
NIOSH	Ceiling Limit Value and Time Period (if specified):	1,800 mg/m3
OSHA Z1	Permissible exposure limit	500 ppm
OSHA Z1	Permissible exposure limit	2,900 mg/m3
OSHA Z1A	time weighted average	100 ppm
OSHA Z1A	time weighted average	525 mg/m3
US CA OEL	Time Weighted Average (TWA)	100 ppm
	Permissible Exposure Limit (PEL):	
US CA OEL	Time Weighted Average (TWA)	525 mg/m3
	Permissible Exposure Limit (PEL):	

KEROSENE 8008-20-6

ACGIH	time weighted average	200 mg/m3	Non-aerosol
NIOSH	Recommended exposure limit (REL):	100 mg/m3	

TRIMETHYLBENZENE 1,2,4- 95-63-6

NIOSH	Recommended exposure limit (REL):	25 ppm
NIOSH	Recommended exposure limit (REL):	125 mg/m3
ACGIH	time weighted average	25 ppm
OSHA Z1A	time weighted average	25 ppm
OSHA Z1A	time weighted average	125 mg/m3
US CA OEL	Time Weighted Average (TWA)	25 ppm

ASHLAND

SAFETY DATA SHEET

Page: 7
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

US CA OEL Permissible Exposure Limit (PEL):
Time Weighted Average (TWA) 125 mg/m3
Permissible Exposure Limit (PEL):

TRIMETHYLBENZENE, 1,3,5- 108-67-8

NIOSH	Recommended exposure limit (REL):	25 ppm
NIOSH	Recommended exposure limit (REL):	125 mg/m3
ACGIH	time weighted average	25 ppm
OSHA Z1A	time weighted average	25 ppm
OSHA Z1A	time weighted average	125 mg/m3

MORPHOLINE 110-91-8

ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	20 ppm
NIOSH	Recommended exposure limit (REL):	70 mg/m3
NIOSH	Short term exposure limit	30 ppm
NIOSH	Short term exposure limit	105 mg/m3
OSHA Z1	Permissible exposure limit	20 ppm
OSHA Z1	Permissible exposure limit	70 mg/m3

GLYCERINE 56-81-5

ACGIH	time weighted average	10 mg/m3	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m3	Respirable fraction.
OSHA Z1	Permissible exposure limit	15 mg/m3	Total dust.

General Advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Provide adequate ventilation to control formaldehyde exposures to within the OSHA permissible exposure limits of 0.75 ppm (TWA) and 2 ppm (STEL) or 0.3 ppm (ACGIH ceiling).

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin and Body Protection

ASHLAND

SAFETY DATA SHEET

Page: 8
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

Wear impervious gloves (consult your safety equipment supplier). To prevent skin contact, wear impervious clothing and boots. Other protective equipment: eyewash station, emergency shower.

Respiratory Protection

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH-approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	No data
Colour	light orange
Odour	fruity
Boiling point/range	150 °F / 66 °C @ 760.00 mmHg
pH	No data
Flash point	133.9 °F / 56.6 °C
Evaporation rate	No data
Explosion limits	No data
Vapour pressure	No data
Vapour density	No data
Density	0.979 g/cm ³ 8.17 lb/gal @ 60.00 °F / 15.56 °C
Solubility	No data
Partition coefficient (n-octanol/water)	No data
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to Avoid

Incompatible Products

ASHLAND

SAFETY DATA SHEET

Page: 9
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

Avoid contact with:, strong oxidizing agents

Hazardous Decomposition Products

May form:, carbon dioxide and carbon monoxide, formaldehyde, hydrogen, silicon oxides, various hydrocarbons

Hazardous Reactions

Product will not undergo hazardous polymerization.

Thermal Decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute Oral Toxicity

MINERAL SPIRITS REGULAR (BASE DATA)	LD 50 Rat: 5 g/kg
KEROSENE	LD 50 Rat: 5,000 mg/kg
Fatty Acid	LD 50 Rat: 10,000 mg/kg
TRIMETHYLBENZENE 1,2,4-	LD 50 Rat: 6 g/kg
TRIMETHYLBENZENE, 1,3,5-	LD 50 Rat: 5,000 mg/kg
MORPHOLINE	LD 50 Rat: 1,050 mg/kg
GLYCERINE	LD 50 Rat: 12,600 mg/kg
ETHYL BENZENE	LD 50 Rat: 3,500 mg/kg

Acute Inhalation Toxicity

KEROSENE	LC 50 Rat: 5,000 mg/m3, 4 h
TRIMETHYLBENZENE 1,2,4-	LC 50 Rat: 18 g/m3, 4 h
MORPHOLINE	LC 50 Rat: 8000 ppm, 8 h

ASHLAND

SAFETY DATA SHEET

Page: 10
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

GLYCERINE

LC 50 Rat: 570 mg/m3, 1 h

ETHYL BENZENE

LC Lo Rat: 4000 ppm, 4 h

Acute Dermal Toxicity

MINERAL SPIRITS REGULAR (BASE
DATA)

LD 50 Rabbit: 3 g/kg

KEROSENE

LD 50 Rabbit: 2 g/kg

Fatty Acid

LD 50 Rabbit: 2,000 mg/kg

MORPHOLINE

LD 50 Rabbit: 500 mg/kg

GLYCERINE

LD 50 Rabbit: 10 g/kg

ETHYL BENZENE

LD 50 Rabbit: 15,433 mg/kg

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental Fate and Pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

ASHLAND

SAFETY DATA SHEET

Page: 11
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_P:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IATA_C:

UN1993, Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_ROAD:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_RAIL:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

CFR_INWTR:

UN1993, Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES,) 3, III

IMDG_INWTR:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_ROAD:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

IMDG_RAIL:

UN1993, FLAMMABLE LIQUID, N.O.S. 3, III

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

ASHLAND

SAFETY DATA SHEET

Page: 12
Revision Date: 04/03/2007
Print Date: 4/24/2007
MSDS Number: R0405617
Version: 1.

WESMAR TROPHY WAX Cleaner &
Glaze CBWPA056-03-U

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

ETHYL BENZENE

BENZENE

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

TOLUENE

BENZENE

SARA Hazard Classification Fire Hazard
 Acute Health Hazard
 Chronic Health Hazard

SARA 313 Component(s)

OSHA Hazards Combustible Liquid
 Highly toxic by inhalation
 Moderate skin irritant
 Moderate eye irritant
 Carcinogen

	Health	Flammability	Reactivity	Other
HMIS	1	2	0	
NFPA				No data

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).