

UP 0735  
Paint Rocket

# U-POL™

## SAFETY DATA SHEET PAINT ROCKET

Page 1

Issued: 12/05/2004

Revision No: 4

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** PAINT ROCKET

**Product code:** ROC/S

**Use / description of product:** PAINT PRODUCT CONTAINING XYLENE, MIXTURE OF ISOMERS

**Company name:**

Wesmar Products, Inc.  
1440 NW 45th St  
Seattle, Wa 98107  
(206) 782-8186

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** XYLENE 30-50%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

• N-BUTYL ACETATE 30-50%

EINECS: 204-658-1 CAS: 123-86-4

[-] R10; [Xi] R66; [-] R67

### 3. HAZARDS IDENTIFICATION

**Main hazards:** Flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Repeated exposure may cause skin dryness or cracking.

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

### 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

[cont...]

**SAFETY DATA SHEET**  
**PAINT ROCKET**

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**Protection of fire-fighters:** Wear self-contained breathing apparatus.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

**Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

**7. HANDLING AND STORAGE**

**Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.

**Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** XYLENE

TWA (8 hr exposure limit): 220 mg/m<sup>3</sup> STEL (15 min exposure limit): 441 mg/m<sup>3</sup> (OES)

• N-BUTYL ACETATE

TWA (8 hr exposure limit): 724 mg/m<sup>3</sup> STEL (15 min exposure limit): 966 mg/m<sup>3</sup> (OES)

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Compressed airline breathing apparatus (EN139).

**Hand protection:** Nitrile gloves.

**Eye protection:** Face-shield.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Colourless

**Odour:** Aromatic

**Evaporation rate:** Moderate

**Solubility in water:** Not miscible

**Viscosity:** Non-viscous

**Flammability limits %: lower:** 2.6

**Flash point°C:** 23

**Autoflammability°C:** 420

**Relative density:** 0.88

**VOC g/l:** 840

# SAFETY DATA SHEET

## PAINT ROCKET

### 10. STABILITY AND REACTIVITY

- Stability:** Stable under normal conditions.
- Conditions to avoid:** Heat. Direct sunlight. Sources of ignition.
- Materials to avoid:** Oxidising agents. Strong acids. Strong bases.
- Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### 11. TOXICOLOGICAL INFORMATION

- Hazardous ingredients:** XYLENE
- ORL MUS LD50 2119 mg/kg
- ORL RAT LD50 4300 mg/kg
- SCU RAT LD50 1700 mg/kg
- N-BUTYL ACETATE
- ORL MUS LD50 6 gm/kg
- ORL RAT LD50 10768 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

### 12. ECOLOGICAL INFORMATION

- Mobility:** Volatile. Floats on water.
- Persistence and degradability:** Only slightly biodegradable.
- Bioaccumulative potential:** No data available.
- Other adverse effects:** No data available.

### 13. DISPOSAL CONSIDERATIONS

- Disposal operations:** D10 Incineration on land.
- R1 Solvent reclamation/regeneration.
- Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
- NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### 14. TRANSPORT INFORMATION

#### ADR / RID

- |                                              |                                |
|----------------------------------------------|--------------------------------|
| <b>UN no:</b> 1263                           | <b>ADR Class:</b> 3            |
| <b>Packing group:</b> III                    | <b>Classification code:</b> F1 |
| <b>Shipping name:</b> PAINT RELATED MATERIAL |                                |
| <b>Labelling:</b> 3                          | <b>Hazard ID no:</b> 30        |



## IMDG / IMO


|                   |      |            |         |
|-------------------|------|------------|---------|
| UN no:            | 1263 | Class:     | 3       |
| Packing group:    | III  | EmS:       | F-E,S-E |
| Marine pollutant: | .    | Labelling: | 3       |

## IATA / ICAO

|                           |                                                  |
|---------------------------|--------------------------------------------------|
| <b>UN no:</b> 1263        | <b>Class:</b> 3                                  |
| <b>Packing group:</b> III | <b>Packing instructions:</b> 309(P&CA); 310(CAO) |
| <b>Labelling:</b> 3       |                                                  |

## 15. REGULATORY INFORMATION

**Hazard symbols:** Harmful.



**Risk phrases:** R10: Flammable.  
R20/21: Harmful by inhalation and in contact with skin.  
R38: Irritating to skin.  
R66: Repeated exposure may cause skin dryness or cracking.

**Safety phrases:** S7: Keep container tightly closed.  
S23: Do not breathe vapour/spray  
S36/37: Wear suitable protective clothing and gloves.  
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

VbF: All

**Water hazard class:** 1 Classification by VwVwS

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. OTHER INFORMATION

**Risk phrases used in s.2:** R10: Flammable.  
R20/21: Harmful by inhalation and in contact with skin.  
R38: Irritating to skin.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.