

U-POL

PRODUCTS

MATERIAL SAFETY DATA SHEET

=====

COMMERCIAL PRODUCT NAME: SYSTEM 20 WAX GREASE REMOVER

PREPARATION: PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

UK ADDRESS: Denington Industrial Estate,
Denington Road,
Wellingborough,
Northants NN8 2QP, United Kingdom

EMERGENCY TELEPHONE NO:- 1-800-424-9300 (CHEMTREC)
1-703 527 3887 (CHEMTREC INTERNATIONAL)

US ADDRESS: Sanders and Associates inc.,
1263 Route 31 South
Lebanon, NJ 08833, USA

FAX NO:- 1-800 787 5150

COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>LEVEL</u>	<u>SYMBOL</u>	<u>RISK</u>
PETROLEUM NAPHTHA	64741-84-0	0 - 100%	Xn - Harmful	R65
			F - Highly Flammable	R11
PETROLEUM NAPHTHA	64742-88-7	0 - 100%	Xn - Harmful	R65
				R10

HAZARDS IDENTIFICATION

INHALATION: May cause drowsiness and irritation of respiratory tract.

SKIN: May cause irritation on prolonged contact, which can lead to dermatitis.

EYES: Irritation and soreness.

INGESTION: Sore throat, stomachache, nausea.

FIRST AID MEASURES

INHALATION:	Move affected person to the fresh air without delay. If drowsiness persists seek medical attention.
SKIN CONTACT:	Wash affected area with warm soapy water. Do not use solvents.
EYE CONTACT:	Irrigate with copious quantities of water and seek medical attention immediately.
INGESTION:	Do not induce vomiting, drink plenty of water and seek medical attention.

FIRE FIGHTING MEASURES

Fight fires with CO₂, dry powder, or chemical foam. Do not use water jets. Burning material emits toxic fumes and smoke, so avoid inhalation of burning products.

ACCIDENTAL RELEASE MEASURES

The product will readily flow. Contain and collect any spillage with sand or earth. Keep product away from drains. Avoid sources of ignition. Dispose of in accordance with the requirements of the Environmental Protection Act.

HANDLING AND STORAGE

HANDLING:	Keep away from heat. Keep away from sources of ignition. Avoid contact with skin and eyes. Use only in well ventilated areas, and for extensive spraying, in a suitable booth.
STORAGE:	Store in accordance with The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations.

EXPOSURE CONTROLS/PERSONAL PROTECTION

A good standard of personal and industrial hygiene should be maintained at all times. Persons who suffer from skin complaints or other allergic effects should not work with the product.

OEL (UK)	Component	8 HR TWA	15 mins STEL
	Petroleum Naphtha	250 mg/m ³	300 mg/m ³

EYE PROTECTION:	Recommended.
PROTECTIVE CLOTHING:	Recommended.
RESPIRATORY PROTECTION:	Suitable respiratory protection necessary, when using in areas of poor ventilation.
SKIN PROTECTION:	Barrier cream recommended.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear liquid.
ODOUR:	Mild, typical.
DENSITY:	Approx. 0.8.
FLASH POINT:	Below 21°C.
AUTO FLAMMABILITY TEMPERATURE:	Approx. 230°C.
VOLATILE CONTENT:	100%.
SOLUBILITY:	Immiscible with water.
VISCOSITY:	Water like consistency.

STABILITY AND REACTIVITY

Stable under normal conditions. Heat increase may be sufficient to raise the temperature above the product flash point. Thermal decomposition can give rise to acrid fumes.

TOXICOLOGICAL INFORMATION

None quoted.

ECOLOGICAL INFORMATION

Marine pollutant and partially biodegradable.

Panel wipes are low viscosity compositions which lose solvents by evaporation, leaving virtually no residue.

DISPOSAL CONSIDERATIONS

The material and any contaminated container should be disposed of in accordance with the Environmental Protection Act.

TRANSPORT INFORMATION*

SHIPPING NAME: PAINT RELATED MATERIAL

UNITED NATION NO: UN 1263.

CLASS NO: 3.2.

HARMONISED SYSTEMS NO: 320890 91 5.

PACKING GROUP: II.

Complies with The Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations.

For current International Maritime Dangerous Goods Declaration, please contact our Export Department
Telephone No: 44-(0)20-8492-5950

REGULATORY INFORMATION

CONTAINS: Mixture of solvents.

SYMBOL:

F	Highly Flammable .
Xn	Harmful.

RISK PHRASES:

R11	Highly flammable.
R65	Harmful, may cause lung damage if swallowed.

SAFETY PHRASES:

S16	Keep away from sources of ignition - No smoking.
S51	Use only in well ventilated areas.

FURTHER INFORMATION

Reference should be made to the following official publications:-

EH40, COSHH Regulations, Environmental Protection Act.

ISSUE NUMBER: 00034
(*Denotes changes to previous issue)

ISSUE DATE: 21/11/02