

Material Safety Data Sheet
ALUMA KLEEN 800

WESMAR CO. INC.

1451 NW 46 ST
SEATTLE, WA. 98107
(206) 783-5344

DATE PREPARED: MAR 1, 2003

REVISED DATE: MAR 1, 2003

24 HOUR EMERGENCY PHONE NUMBER:

CHEMTREC: 800-424-9300

STOCK NO: WM 3221 - 3225

SECTION I - IDENTIFICATION

PRODUCT NAME: ALUMA KLEEN 800

CHEMICAL FAMILY: HIGHLY ACIDIC MATERIAL

FORMULA: N/A

CAS NUMBER: N/A

SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER	ACGIH/TLV	STEL/PEL
Sulfuric acid	10-20	7664-93-9	1 mg/M ³	3 mg/M ³
Ammonium hydrogen difluoride	10-20	1341-49-7	2.5 mg/M ³ (as Fluoride)	NOT EST.

(See section VI for additional TLV
information. Also contains biodegradable
surfactant.)

SECTION III - PHYSICAL DATA

APPEARANCE: Clear liquid with sharp odor

BOILING POINT: 212° F.

VAPOR PRESSURE: NOT EST.

VAPOR DENSITY (AIR=1): NOT EST.

SPECIFIC GRAVITY: 1.14

pH: < 2.0

SOLUBILITY IN WATER: Completely soluble in water.

SECTION IV - FIRE AND EXPLOSION DATA

FLASHPOINT: > 200° F.

LOWER EXPLOSIVE LIMIT: .. N/A

UPPER EXPLOSIVE LIMIT: N/A

EXTINGUISHING MEDIA: Use extinguishing media appropriate to primary cause of fire.

SPECIAL FIRE FIGHTING

PROCEDURES: Avoid contact with fire fighting personnel as burns may result from contact with skin. When fighting a fire near or involving this product, wear a self-contained breathing apparatus (SCBA).

UNUSUAL FIRE AND

EXPLOSION HAZARDS: None known

Material Safety Data Sheet

ALUMA KLEEN 800

SECTION V - REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY: Chlorinated products such as bleach, alkaline materials, metals, metal powder, carbides, chlorates, fumigates, nitrates, picrates, strong oxidizing, reducing, or combustible organic material. Hazardous gases are evolved on contact with chemicals such as chlorine bleach, cyanides, sulfides and carbides. Chlorinated products such as bleach, alkaline materials, metals, metal powder, carbides, chlorates, fumigates, nitrates, picrates, strong oxidizing, reducing, or combustible organic material. Hazardous gases are evolved on contact with chemicals such as chlorine bleach, cyanides, sulfides and carbides.

HAZARDOUS

DECOMPOSITION: Carbon monoxide, carbon dioxide. Oxides of sulfur, nitrogen and/or phosphorous may be released at extremely high temperatures. Reactions with chlorinated products produces deadly chlorine gas.

HAZARDOUS

POLYMERIZATION: Will not occur.

SECTION VI - HEALTH DATA

THRESHOLD LIMIT VALUE: . The TLV in section II is the ACGIH/TLV-TWA and OSHA/PEL, (the time weighted average concentration for an eight hour work day.) The STEL is the (short term exposure limit.) (C) is the ceiling limit.

OSHA PEL: Since this product is a mixture, there is no defined PEL(s) established by OSHA. Hazardous components are listed in the Hazardous Ingredients Section of this data sheet.

LISTED CARCINOGEN: This product does not contain any components listed by NTP, IARC, or OSHA as carcinogens at the OSHA reportable levels.

MEDICAL CONDITION AGGRAVATED: Existing skin and/or respiratory disorders may be aggravated by exposure.

EYES: Vapors, liquid and mists are extremely corrosive to the eyes. Brief contact of the liquids or mists will severely damage the eyes and may cause permanent eye injury which may be followed by permanent impairment of vision or blindness.

SKIN (DERMAL): Vapors, mists, and liquid are extremely corrosive to the skin. A short single exposure will severely burn the skin. Prolonged contact with liquid will burn or destroy surrounding tissue.

INGESTION: Vapors, mists and liquid are extremely corrosive to the mouth and throat. Swallowing the liquid burns the tissue and causes severe abdominal pain, nausea, vomiting, kidney damage and collapse. Swallowing large amounts can cause death.

INHALATION: Vapors, mists and liquid are extremely corrosive to the respiratory system. Irritation, coughing, chest pain and breathing difficulty may occur with short exposure. Prolonged exposure may result in more severe irritation and tissue damage.

CHRONIC OVEREXPOSURE: . May cause bronchial irritation, coughing and pneumonia. Persons with pre-existing skin disorders, eye, cardio pulmonary and lung disease may be more susceptible to the effects of this products.

Material Safety Data Sheet

ALUMA KLEEN 800

SECTION VII FIRST AID

EYES: Water is the only accepted method of removal of this product from the eyes or skin. You may have 10 seconds or less to avoid serious permanent injury. Therefore, **IMMEDIATE** first aid must be given after any exposure. Moving the victim from water access for transport to medical aid should be done only on the advice of qualified medical personnel. While transporting victim to a medical facility, continue washing if possible. In case of contact, immediately flush eyes with lots of running water for at least 15 minutes. Call for medical assistance. In case of contact, immediately flush eyes with lots of running water for at least 15 minutes. Call for medical assistance.

SKIN (DERMAL):..... In case of skin contact, wash thoroughly with soap and water.

INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. (If available, give several glasses of milk.) If vomiting occurs spontaneously, keep airway clear and give more water. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION:..... Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen as directed by medical personnel.

SECTION VIII EMPLOYEE PROTECTION

EYE PROTECTION:..... Chemical safety splash goggles and full face shield (8" min.) to protect against splashing in compliance with OSHA regulations are advised. OSHA regulations also permit other type safety glasses. (Consult your industrial hygienist) Contact lenses should not be worn when working with any chemicals.

RESPIRATORY PROTECTION: Respiratory protection should be worn if levels exceed defined PEL(s) for this product or any hazardous component listed in the Hazardous Ingredient Section of this DATA SHEET.

PROTECTIVE CLOTHING: Impervious protective clothing and chemical resistant safety shoes should be worn to minimize contact. Emergency shower and eyewash facility should be in close proximity. (ANSI Z358.1)

VENTILATION: Local exhaust sufficient to maintain TLV below permissible exposure limits.

SECTION IX - SPILL AND DISPOSAL DATA

SPILL: Always use appropriate protective equipment during clean-up. Stop leaks if possible. Review "Fire, reactivity hazards, and precautions" before proceeding with clean-up. Soak up small spills with dry sand, clay, or diatomaceous earth. Dike large spills. Cautiously dilute with water, neutralize with lime or soda ash and transfer to waste water treatment system. Prevent liquid from entering sewers and waterways. If this product is spilled and not recovered, or is recovered as a waste for treatment or disposal, the REPORTABLE QUANTITY is 1000 lbs. (based on the sulfuric or nitric acid content of the solution) or 5000 lbs. (based on the phosphoric or hydrochloric acid content). Comply with federal, state and local regulations on reporting releases.

WASTE DISPOSAL: Consult all LOCAL, STATE, and FEDERAL regulations with regard to proper and suitable disposal methods.

Material Safety Data Sheet

ALUMA KLEEN 800

SECTION X - TRANSPORTATION DATA

HAZARD CLASS AND LABEL: 8 (CORROSIVE)

PROPER SHIPPING NAME:..... CORROSIVE LIQUID, TOXIC, N.O.S. (SULFURIC ACID, AMMONIUM HYDROGEN DIFLUORIDE) 8 UN-2922 PG-II

UN NUMBER: UN-2922

PACKAGING GROUP: PG – II

REPORTABLE QUANTITY:..... 1000 lbs. (based on sulfuric or nitric acid content of the solution) or 5000 lbs. (based on phosphoric or hydrochloric acid content).

SECTION XI - OTHER REGULATORY INFORMATION

TSCA STATUS:..... All components in this product are listed on the TSCA inventory.

SARA SECTION 313:..... This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372):

C A S #	CHEMICAL NAME	PERCENT BY WEIGHT
7664-93-9	* Sulfuric acid	16.5

..... * (Acid aerosols including mists, vapors, gas, fog and other airborne forms of any particle size)

HEALTH:..... 3

FLAMMABILITY: 0

REACTIVITY: 1

OTHER: N/A

SECTION XII - PRECAUTIONARY LABEL STATEMENTS

WARNING: DANGER! HIGHLY ACIDIC MATERIAL. Causes sever burns to skin, eyes and throat. Eye contact may cause blindness. Harmful or fatal if swallowed. Reacts with chlorinated compounds to form hazardous vapors.

HANDLING:..... Do not get in eyes, on skin or on clothing. Avoid breathing dust, mists, or spray. Do not take internally. Wash thoroughly after handling or contact. Exposure can cause burns which are not immediately painful or visible. Do not add water to contents while in container because of possible violent reaction. Keep out of sun and away from heat, sparks and flames. Keep container tightly closed when not in use to prevent leakage. Do not use pressure to empty container. Do not wash out container or use it for other purposes. Replace closure after each withdrawal and return it with empty container. Empty containers retain product residue and must be handled as if they were full. KEEP OUT OF REACH OF CHILDREN.

SECTION XIII - ADDITIONAL INFORMATION

REFERENCES:..... The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. WESMAR CO. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.

Material Safety Data Sheet

ALUMA KLEEN 800

FOOTNOTES: ACGIH = American Conference of Governmental Industrial Hygienists

CAS = Chemical Abstracts Service Registry Number

CEILING = Ceiling Limit (15 minutes)

CEL = Corporate Exposure Limit

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limits (OSHA)

STEL = Short Term Exposure Limit (15 minutes)

TDG = Transportation Of Dangerous Goods (Canada)

TLV = Threshold Limit Value (ACGIH)

TWA = Time Weighted Average (8 hours)