

MATERIAL SAFETY DATA SHEET

RENEW CG

SECTION I - IDENTIFICATION

COMPANY NAME..... Wesmar Products, Inc.
EMERGENCY PHONE NUMBER..... 1440 NW 45th St
EFFECTIVE DATE..... Seattle, Wa 98107
REVISED DATE..... APRIL 17, 1996 (206) 782-8186
CHEMICAL NAME..... N/A
TRADE NAME..... RENEW CG
CHEMICAL FAMILY..... HIGHLY ACIDIC COMPOUND
CHEMICAL FORMULA..... N/A

SECTION II - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	HAZARDOUS %	TLV (Units)	PROD. CAS #
HYDROCHLORIC ACID	10-20	5 PPM	7647-01-0

(SEE SECTION V FOR
ADDITIONAL TLV
INFORMATION)

(ALSO CONTAINS
BIODEGRADABLE
SURFACTANT)

SECTION III - PHYSICAL DATA

BOILING Point(F)..... N/D
FREEZING POINT (F)..... N/D
VOLATILITY/VOL(%)..... N/D
MELTING POINT..... N/D
VAPOR PRESSURE (mm Hg)... N/D
VAPOR DENSITY (Air=1).... N/D
SOLUBILITY IN H2O..... COMPLETELY SOLUBLE IN WATER
APPEARANCE/ODOR..... CLEAR RED LIQUID WITH SHARP ODOR
SPECIFIC GRAVITY (H2O=1). 1.1
EVAPORATION RATE..... N/D
PH..... < 2.0

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT..... NON COMBUSTIBLE
LOWER FLAME LIMIT..... N/A
HIGHER FLAME LIMIT..... N/A
EXTINGUISH MEDIA..... Use extinguishing media appropriate to primary cause of fire.

MATERIAL SAFETY DATA SHEET

RENEW CG

FOR FIRE..... Avoid contact with fire fighting personnel as burns may result from contact with skin. Wear complete protective clothing and self contained breathing apparatus.

UNUSUAL FIRE HAZARD..... Contact with soft metals may produce flammable or explosive hydrogen gas.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE.... The TLV in section II is the ACGIH TLV-TWA and OSHA-PEL, (the time-weighted average concentration for an eight hour work day.) TLV-STEL's (short term exposure limits) have been established for the following products:

HYDROCHLORIC ACID: OSHA/PEL and ACGIH/TLV is 5 PPM.
This is also the ceiling.

None of the components present in this material at concentrations of 0.1% or greater are listed by IARC, NTP or WISHA/OSHA as carcinogens.

MATERIAL SAFETY DATA SHEET

RENEW CG

OVER EXPOSURE EFFECTS.... ACUTE HAZARDS:

EYES: Vapors, liquid and mists are extremely corrosive to the eyes. Brief contact of the liquids or mists will severely damage the eyes and may cause permanent eye injury which may be followed by permanent impairment of vision or blindness.

SKIN CONTACT: Vapors, mists, and liquid are extremely corrosive to the skin. A short single exposure will severely burn the skin. Prolonged contact with liquid will burn or destroy surrounding tissue.

INGESTION: Vapors, mists and liquid are extremely corrosive to the mouth and throat. Swallowing the liquid burns the tissue and causes severe abdominal pain, nausea, vomiting, kidney damage and collapse. Swallowing large amounts can cause death.

INHALATION: Vapors, mists and liquid are extremely corrosive to the respiratory system. Irritation, coughing, chest pain and breathing difficulty may occur with short exposure. Prolonged exposure may result in more severe irritation and tissue damage.

CHRONIC EFFECTS OF EXPOSURE:

May cause bronchial irritation, coughing and pneumonia. Persons with pre-existing skin disorders, eye, cardio pulmonary and lung disease may be more susceptible to the effects of this product.

NOTE: This product may not produce an immediate burning sensation upon skin contact, delaying the awareness of the worker that contact has occurred. Follow first aid procedures for all suspected contact.

MATERIAL SAFETY DATA SHEET

RENEW CG

FIRST AID PROCEDURES..... EYES: WATER is the only accepted method of removal of this product from the eyes or skin. You may have 10 seconds or less to avoid serious permanent injury. Therefore, IMMEDIATE first aid must be given after any injurious exposure. Moving the victim from water access for transport to medical aid should be done only on the advice of qualified medical personnel. While transporting victim to a medical facility, continue washing if possible.

EYES: In case of eye contact, immediately flush eyes with lots of running water for at least 30 minutes. Call for immediate medical assistance.

SKIN: Immediate continued and thorough washing in flowing water for 30 minutes is imperative while removing contaminated clothing. Prompt medical consultation is essential. Wash contaminated clothing before reuse. Destroy contaminated shoes or boots.

INGESTION: Do not induce vomiting. Give large amounts of water or milk if available and transport to medical facility. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air if effects occur. Consult medical personnel.

SECTION VI - REACTIVITY DATA

CHEMICAL STABILITY..... STABLE

CONDITIONS TO AVOID..... Excessive heat and contact with incompatible materials.

INCOMPATIBLE MATERIALS... Chlorinated products such as bleach, alkaline materials, metals, metal powder, carbides, chlorates, fumigates, nitrates, picrates, strong oxidizing, reducing, or combustible organic material. Hazardous gases are evolved on contact with chemicals such as chlorine bleach, cyanides, sulfides and carbides.

DECOMPOSITION PRODUCTS... Carbon monoxide, carbon dioxide. Oxides of sulfur, nitrogen and/or phosphorous may be released at extremely high temperatures. Reactions with chlorinated products produces deadly chlorine gas.

HAZARDOUS POLYMERIZATION. Will not occur.

POLYMERIZATION AVOID..... N/A

SECTION VII - SPILL OR LEAK PROCEDURE

MATERIAL SAFETY DATA SHEET

RENEW CG

FOR SPILL Always use appropriate protective equipment during clean-up. Stop leaks if possible. Review "Fire, reactivity hazards, and precautions" before proceeding with clean-up. Soak up small spills with dry sand, clay, or diatomaceous earth. Dike large spills. Cautiously dilute with water, neutralize with lime or soda ash and transfer to waste water treatment system. Prevent liquid from entering sewers and waterways. If this product is spilled and not recovered, or is recovered as a waste for treatment or disposal, the REPORTABLE QUANTITY is 1000 lbs. (based on the sulfuric or nitric acid content of the solution) or 5000 lbs. (based on phosphoric or hydrochloric acid content) Comply with federal, state and local regulations on reporting releases.

WASTE DISPOSAL METHOD.... Dispose of in approved chemical disposal area or in a manner which complies with all local, state and federal regulations.

SECTION VIII - SPECIAL PROTECTION

RESPIRATORY PROTECTION... Use NIOSH/MSHA approved dust/mist filter respirator when exposure to mists exceed the permissible exposure limits or if irritation occurs. The respirator use limitations made by NIOSH/MSHA or the manufacturer must be observed. Respirator protection programs must be in accordance with 29 CFR 1910.134.

VENTILATION..... Local exhaust sufficient to maintain TLV below permissible exposure limits.

PROTECTIVE GLOVES..... Rubber, polyethylene or other acid proof gloves.

EYE PROTECTION..... Chemical safety goggles plus full face shield to protect against splashing. Contact lenses should not be worn when working with any chemicals.

OTHER PROTECTIVE EQUIPMENT..... Impervious protective clothing and chemical resistant safety shoes should be worn to minimize contact. Emergency shower and eyewash facility should be in close proximity. (ANSI Z358.1).

MATERIAL SAFETY DATA SHEET

RENEW CG

HANDLING AND STORAGE..... Do not get into eyes, on skin or on clothing. Avoid breathing dust, mists, or spray. Do not take internally. Wash thoroughly after handling or contact- exposure can cause burns which are not immediately painful or visible. Do not add water to contents while in container because of possible violent reaction. Keep out of sun and away from heat, sparks and flames. Keep container tightly closed when not in use to prevent leakage. Do not use pressure to empty. Be sure closure is securely fastened before moving container. Do not wash out container or use it for other purposes. Replace closure after each withdrawal and return it with empty container. Empty containers retain product residue and must be handled as if they were full.
KEEP OUT OF REACH OF CHILDREN!

SECTION IX - SPECIAL PRECAUTIONS

HAZARD CLASS..... 8 (CORROSIVE)
DOT SHIPPING NAME..... HYDROCHLORIC ACID, SOLUTION
8 UN-1789 PG-II

REPORTABLE QUANTITY (RQ). SEE SECTION VII
UN NUMBER..... UN-1789
NA #..... N/A
PACKAGING SIZE..... N/A

FOOT NOTES SECTION 313:
THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL(S) SUBJECT TO THE reporting requirements of section 313 of TITLE III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR PART 372 if over 10,000 lbs. are used:

HYDROCHLORIC ACID

REFERENCES The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. WESMAR CO. INC. assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.