



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product information

Commercial Product Name : SILICONE SPRAY - 500 ML

Product code : 0893221
MSDS-Identcode : 10009293
Company : A. Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau
Germany

Telephone : +49 (0)7940 15 0
Telefax : +49 (0)7940 15 10 00

Responsible/issuing person : prodsafe.wurth@technidata.com
Emergency telephone : Giftnotrufzentrale Berlin
+49 (0)30 30686 790
Gesellschaft (07:00 – 18:00 Uhr) :
+49 (0)7940 15 2552

Use : Polishing agent and lubricant

2. HAZARDS IDENTIFICATION



F+ Extremely flammable
Xi Irritant

Extremely flammable.
Irritating to skin.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Vapours may cause drowsiness and dizziness.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	EC-No. / Registration number	Classification	Concentration [%]
butane	106-97-8	203-448-7	F+; R12	>= 25 - < 35
isobutane	75-28-5	200-857-2	F+; R12	>= 25 - < 35



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

Chemical Name	CAS-No.	EC-No. / Registration number	Classification	Concentration [%]
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0	265-151-9	F; R11 Xi; R38 N; R51/53 Xn; R65 R67	>= 20 - < 25
propane	74-98-6	200-827-9	F+; R12	>= 3 - < 5
low boiling point hydrogen treated naphtha	64742-48-9	265-150-3	R10 Xn; R65 R66-R67	>= 2 - < 3
propan-2-ol	67-63-0	200-661-7	F; R11 R67 Xi; R36	>= 1 - < 1,5
dodecylethyldimethylammonium ethyl sulphate	3006-13-1	221-108-6	Xn; R22 N; R50/53	>= 0,0025 - < 0,1

4. FIRST AID MEASURES

- General advice : If you feel unwell, seek medical advice (show the label where possible). First aider needs to protect himself. Move out of dangerous area. Never give anything by mouth to an unconscious person. Take off contaminated clothing and shoes immediately.
- Inhalation : If breathed in, move person into fresh air. In the case of inhalation of aerosol/mist consult a physician if necessary. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Skin contact : In case of contact, immediately flush skin with soap and plenty of water. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
- Eye contact : Protect unharmed eye. If easy to do, remove contact lens, if worn. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- Ingestion : If swallowed, seek medical advice immediately and show this container or label. If swallowed, DO NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Dry powder, Foam, Carbon dioxide (CO₂), Water mist
- Unsuitable extinguishing media : High volume water jet
- Specific hazards : Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products may be formed under fire conditions (see section 10). Exposure to decomposition products may be a hazard to health.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
- Further information : Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. In the event of fire and/or explosion do not breathe fumes. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Refer to protective measures listed in sections 7 and 8. Use personal protective equipment. Remove all sources of ignition. Avoid contact with skin and eyes. Ensure adequate ventilation, especially in confined areas. Immediately evacuate personnel to safe areas. Avoid inhalation of vapour or mist. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. Avoid release to the environment. Refer to special instructions/ Safety data sheets.
- Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Clean contaminated surface thoroughly.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

7. HANDLING AND STORAGE

Handling

Advice on safe handling : For personal protection see section 8. Limit the stocks at work place. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Do not spray on a naked flame or any other incandescent material. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Take precautionary measures against static discharges.

Advice on protection against fire and explosion : Normal measures for preventive fire protection. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard.

Dust explosion class : not applicable

Storage

Requirements for storage areas and containers : Store in original container. BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep containers tightly closed in a dry, cool and well-ventilated place. Please observe the storage instructions for aerosols!

To be observed: TRG 300

Advice on common storage : Keep away from food, drink and animal feedingstuffs. Do not store together with oxidizing and self-igniting products.

German storage class : 2B, Compressed Gas (Aerosol cans)

Other data : No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

AGW - Calculated according to TRGS 900 RCP-method : 600 mg/m³



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

Other information on limit values: see chapter 16

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Product contains low-boiling liquids. Respiratory protective equipment must be air supplied respirators.

Hand protection

Material : Nitrile rubber

Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

Eye protection : Tightly fitting safety goggles

Skin and body protection : Flame retardant antistatic protective clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice.
General industrial hygiene practice.
Do not inhale aerosol.
Avoid contact with skin, eyes and clothing.
When using do not eat, drink or smoke.
Wash hands before breaks and at the end of workday.
Follow the skin protection plan.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form : aerosol
Propellant : butane, isobutane, propane
Colour : colourless
Odour : characteristic

Safety data

Ignition temperature : ca. 250 °C
Lower explosion limit : 1,0 %(V)
Upper explosion limit : 2,0 %(V)
Vapour pressure : 3,6 bar at 20 °C
Density : no data available
Water solubility : insoluble

10. STABILITY AND REACTIVITY

Conditions to avoid : Heat, flames and sparks.
Hazardous decomposition products : Smoke
Hazardous reactions : Vapours may form explosive mixtures with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Stability : No decomposition if stored and applied as directed.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity:

low boiling point hydrogen treated naphtha	: LD50 (rat): > 5.000 mg/kg
low boiling point hydrogen treated naphtha	: LD50 (rat): > 15.000 mg/kg
propan-2-ol	: LD50 (rat): 5.045 mg/kg

Acute inhalation toxicity:

butane	: LC50 (rat): 658 mg/l Exposure time: 4 h
propane	: LC50 (rat): 57000 ppm Exposure time: 15 min
low boiling point hydrogen treated naphtha	: LC50 (rat): > 12 mg/l Exposure time: 6 h
propan-2-ol	: LC50 (rat): 46,5 mg/l Exposure time: 4 h

Acute dermal toxicity:

low boiling point hydrogen treated naphtha	: LD50 (rabbit): > 3.160 mg/kg
propan-2-ol	: LD50 (rabbit): 12.800 mg/kg

Skin irritation : Irritating to skin.

Eye irritation : May irritate eyes.

Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Vapours may cause drowsiness and dizziness.

12. ECOLOGICAL INFORMATION

Toxicity to fish:

propan-2-ol	: LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l
-------------	---



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates.:

propan-2-ol : EC50 (Daphnia magna (Water flea)): 13.299 mg/l
Exposure time: 48 h

dodecylethyldimethylammo- : EC50 (Daphnia magna (Water flea)): 4,3 µg/l
nium ethyl sulphate Exposure time: 24 h

EC50 (Daphnia magna (Water flea)): 2,4 µg/l
Exposure time: 48 h

Adsorbed organic bound : not included
halogens (AOX)

Additional ecological informa- : The product should not be allowed to enter drains, water
tion courses or the soil.

13. DISPOSAL CONSIDERATIONS

Advice on disposal and : Disposal:
packaging In accordance with local and national regulations. This materi-
al and its container must be disposed of as hazardous waste.

Waste Code (EWC) : Waste Key (unused product):
160504, gases in pressure containers (including halons) con-
taining dangerous substances

Waste key (used product):
160504, gases in pressure containers (including halons) con-
taining dangerous substances

14. TRANSPORT INFORMATION

ADR

UN-Number : 1950
Description of the goods : AEROSOLS
Class : 2
Packing group : --
Classification Code : 5F
Labels : 2.1
Limited quantity : LQ2
Tunnel restriction code : (D)

RID



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

UN-Number : 1950
Description of the goods : AEROSOLS
Class : 2
Packing group : --
Classification Code : 5F
Hazard identification No : 23
Labels : 2.1

IATA

UN-Number : 1950
Description of the goods : Aerosols, flammable
Class : 2.1
Packing group : --
Labels : 2.1
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203

IMDG

UN-Number : 1950
Description of the goods : AEROSOLS
Class : 2.1
Packing group : --
Labels : 2.1
EmSNumber 1 : F-D
EmSNumber 2 : S-U
Marine pollutant : no

15. REGULATORY INFORMATION

Labelling according to EC Directives

1999/45/EC

Symbol(s)	: F+ Xi	Extremely flammable Irritant
R-phrases(s)	: R12 R38 R52/53 R67	Extremely flammable. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
S-phrases(s)	: S23 S24 S35	Do not breathe spray. Avoid contact with skin. This material and its container must be



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

S51

disposed of in a safe way.
Use only in well-ventilated areas.

Special labelling of certain mixtures : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any other incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Further information : Reserved for industrial and professional use.

VOC : Directive 1999/13/EC
92,7 %
VOC content less water: 741,57 g/l

Seveso Directive (96/82/EC)	:	Extremely flammable	Quantity 1 10 t	Quantity 2 50 t
		Petroleum products	2.500 t	25.000 t

Other regulations : Take note of Dir 94/33/EC on the protection of young people at work.

Observe national used protectional regulations.

16. OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R22	Harmful if swallowed.
R36	Irritating to eyes.
R38	Irritating to skin.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SILICONE SPRAY - 500 ML

Version 1.2

Revision Date 26.03.2010

Print Date 31.03.2010

REG_EU / EN

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by: : TechniData BCS GmbH
Birlenbacher Str. 19
D-57078 Siegen
Germany
Telephone: +49-(0)271-88072-0

Ref.: WIAG00000663