

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name X-5 Fabric Protector
Version # 02
Revision date 06-29-2010
CAS # Mixture
Product use Fabric protector.
Manufacturer/Supplier Xzilon, Inc.
11022 Vulcan Street
South Gate, CA 90280-0893 US
Telephone: (562) 923-5438
Emergency CHEMTREC: (800) 424-9300
CHEMTREC International: 00 1-703-527-3887

2. Hazards Identification

Physical state Liquid.
Appearance Liquid.
Emergency overview WARNING!
Flammable liquid and vapor. Will be easily ignited by heat, spark or flames.

Irritating to eyes. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness and dizziness. Prolonged or repeated skin contact may cause drying, cracking, or irritation. Prolonged exposure may cause chronic effects.
OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects
Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.
Eyes Causes eye irritation.
Skin Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).
Inhalation In high concentrations, vapors and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.
Ingestion Harmful: may cause lung damage if swallowed. Irritating to mouth, throat, and stomach. Aspiration of this product may cause a pneumonia-like reaction of lung tissue.
Target organs Eyes. Skin. Central nervous system. Reproductive system.
Chronic effects May cause adverse reproductive effects - such as birth defects, miscarriages, or infertility based on animal data.
Potential environmental effects The product contains a substance which may cause long-term adverse effects in the aquatic environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Isopropanol	67-63-0	30 - 85
Cyclomethicone	556-67-2	15 - 65
Stoddard solvent	8052-41-3	0.5 - 1.5

Composition comments Components not listed are either non-hazardous or are below reportable limits. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First Aid Measures

First aid procedures
Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact Wash skin thoroughly with soap and water. Get medical attention if irritation develops and persists.

Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Get medical attention, if needed.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention immediately.
Notes to physician	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General advice	Take off contaminated clothing and shoes immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

5. Fire Fighting Measures

Flammable properties	Flammable by OSHA criteria. Heat may cause the containers to explode.
Extinguishing media	
Suitable extinguishing media	Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Protection of firefighters	
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors are heavier than air and may travel along the floor and in the bottom of containers. Vapors may be ignited by a spark, a hot surface or an ember.
Protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Containers should be cooled with water to prevent vapor pressure build up. Cool containers exposed to flames with water until well after the fire is out. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Special protective equipment for fire-fighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Specific methods	In the event of fire and/or explosion do not breathe fumes.
Hazardous combustion products	Carbon monoxide. Carbon Dioxide. Silicon oxides.

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See Section 8 of the MSDS for Personal Protective Equipment.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.
Methods for containment	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Small Spills: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste. Should not be released into the environment. Large Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Do not allow material to contaminate ground water system.
Other information	Clean up in accordance with all applicable regulations.

7. Handling and Storage

Handling	Wear personal protective equipment. Avoid breathing high vapor concentrations. Avoid contact with eyes and prolonged or repeated contact with skin. Do not taste or swallow. Use only with adequate ventilation. Wash thoroughly after handling. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Take precautionary measures against static discharges. When using, do not eat, drink or smoke.
-----------------	---

Storage

Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep away from food, drink and animal feeding stuffs. Keep out of the reach of children.

8. Exposure Controls / Personal Protection**Occupational exposure limits****ACGIH****Components****Type****Value**

Isopropanol (67-63-0)

STEL

400 ppm

TWA

200 ppm

Stoddard solvent (8052-41-3)

TWA

100 ppm

U.S. - OSHA**Components****Type****Value**

Isopropanol (67-63-0)

PEL

980 mg/m3

400 ppm

Stoddard solvent (8052-41-3)

PEL

2900 mg/m3

500 ppm

Canada - Alberta**Components****Type****Value**

Isopropanol (67-63-0)

STEL

400 ppm

984 mg/m3

TWA

492 mg/m3

200 ppm

Stoddard solvent (8052-41-3)

TWA

100 ppm

572 mg/m3

Canada - British Columbia**Components****Type****Value**

Isopropanol (67-63-0)

STEL

400 ppm

TWA

200 ppm

Stoddard solvent (8052-41-3)

STEL

580 mg/m3

TWA

290 mg/m3

Canada - Ontario**Components****Type****Value**

Isopropanol (67-63-0)

STEL

400 ppm

TWA

200 ppm

Stoddard solvent (8052-41-3)

TWA

525 mg/m3

Canada - Quebec**Components****Type****Value**

Isopropanol (67-63-0)

STEL

500 ppm

1230 mg/m3

TWA

983 mg/m3

400 ppm

Stoddard solvent (8052-41-3)

TWA

100 ppm

525 mg/m3

Mexico**Components****Type****Value**

Isopropanol (67-63-0)

STEL

1225 mg/m3

500 ppm

TWA

400 ppm

980 mg/m3

Stoddard solvent (8052-41-3)

STEL

200 ppm

1050 mg/m3

TWA

523 mg/m3

100 ppm

Engineering controls

Use explosion-proof ventilation equipment. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Personal protective equipment**Eye / face protection**

Wear approved safety goggles.

Skin protection	Wear chemical-resistant gloves, footwear and protective clothing appropriate for risk of exposure. Contact glove manufacturer for specific information.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
General hygiene considerations	Avoid contact with eyes. Avoid contact with skin. When using, do not eat, drink or smoke. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance	Liquid.
Color	Colorless.
Odor	Alcohol.
Odor threshold	Not available.
Physical state	Liquid.
Form	Liquid.
pH	Not available.
Melting point	Not available.
Freezing point	Not available.
Boiling point	Not available.
Flash point	53.6 °F (12 °C) Closed Cup (Estimated)
Evaporation rate	Not available.
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Specific gravity	Not available.
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.

10. Chemical Stability & Reactivity Information

Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents. Strong acids. Strong bases.
Hazardous decomposition products	Silicon oxides.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

Components	Test Results
Cyclomethicone (556-67-2)	Acute Dermal LD50 Rat: 1770 mg/kg Acute Inhalation LC50 Rat: 36000 mg/m3 4 Hours Acute Oral LD50 Rat: 1540 mg/kg
Isopropanol (67-63-0)	Acute Dermal LD50 Rabbit: 5030 - 7900 mg/kg Acute Oral LD50 Rat: 4700 - 5800 mg/kg
Acute effects	May be fatal if swallowed and enters airways.

Local effects	Irritating to eyes. Prolonged skin contact may cause dermatitis. High concentration of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects.
Sensitization	May cause allergic skin disorders in sensitive individuals.
Chronic effects	Prolonged or repeated exposure may cause lung injury.
Carcinogenicity	Not available.
ACGIH Carcinogens	
Isopropanol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
Epidemiology	Not available.
Mutagenicity	Not available.
Neurological effects	High vapor/aerosol concentrations (attainable only at elevated temperatures) may cause central nervous system effects such as dizziness, drowsiness or headaches.
Reproductive effects	Isopropyl alcohol has demonstrated animal effects of reproductive toxicity. Possible risk of impaired fertility.
Teratogenicity	Not available.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data

Components	Test Results
Cyclomethicone (556-67-2)	LC50 Bluegill (Lepomis macrochirus): > 1000 mg/l 96 Hours LC50 Zebra danio (Danio rerio): > 500 mg/l 96 Hours
Isopropanol (67-63-0)	LC50 Bluegill (Lepomis macrochirus): > 1400 mg/l 96 hours
Ecotoxicity	The product contains a substance which may cause long-term adverse effects in the aquatic environment.
Environmental effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Aquatic toxicity	This material is not expected to be harmful to aquatic life.
Persistence and degradability	Not available.
Bioaccumulation / Accumulation	No data available.
Partition coefficient (n-octanol/water)	Not available.
Mobility in environmental media	No data available.

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 °F
Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations. This material and its container must be disposed of as hazardous waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not contaminate ponds, waterways or ditches with chemical or used container.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1219
Proper shipping name	Isopropanol Solution
Hazard class	3
Packing group	II
Labels required	3

Additional information:

Special provisions	IB2, T4, TP1
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242

ERG number 129

IATA

Basic shipping requirements:

UN number 1219
Proper shipping name Isopropanol Solution
Hazard class 3
Packing group II

IMDG

Basic shipping requirements:

UN number 1219
Proper shipping name ISOPROPANOL Solution
Hazard class 3
Packing group II
EmS No. F-E, S-D

TDG

Basic shipping requirements:

Proper shipping name Isopropanol Solution
Hazard class 3
UN number UN1219
Packing group II



DOT



IATA



IMDG



TDG

15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Isopropanol (CAS 67-63-0) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Isopropanol (CAS 67-63-0) Listed.

CERCLA (Superfund) reportable quantity (lbs)

Isopropanol 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	No
Drug Enforcement Agency (DEA)	Not controlled
Canadian regulations	This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.
WHMIS status	Controlled
WHMIS classification	B2 - Flammable/Combustible D2A - Other Toxic Effects-VERY TOXIC D2B - Other Toxic Effects-TOXIC

WHMIS labeling**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations	This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
--------------------------	--

US - California Hazardous Substances (Director's): Listed substance

Isopropanol (CAS 67-63-0)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US - Massachusetts RTK - Substance: Listed substance

Isopropanol (CAS 67-63-0)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

Isopropanol (CAS 67-63-0)	500 LBS
---------------------------	---------

US - New Jersey RTK - Substances: Listed substance

Stoddard solvent (CAS 8052-41-3)	Listed.
----------------------------------	---------

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Isopropanol (CAS 67-63-0)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.

16. Other Information

Further information	HMIS® is a registered trade and service mark of the NPCA.
----------------------------	---

HMIS® ratings

Health: 2*
Flammability: 3
Physical hazard: 0

NFPA ratings

Health: 2
Flammability: 3
Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.

Issue date

06-29-2010

**This data sheet contains
changes from the previous
version in section(s):**

First Aid Measures: Inhalation
First Aid Measures: Notes to physician