

# SSL Manager — Administrator Guide

---

## SSL Manager — System Requirements

### Table of Contents

1. Operating System
2. Minimum Hardware
3. System Packages
4. Python Packages
5. Network Requirements
6. File System Layout

## SSL Manager — Installation Guide

### Deployment Options

#### Bare Metal / Ubuntu Server

#### RHEL / Rocky Linux / AlmaLinux

#### Configure Email (Optional)

#### Cloud Deployment Prerequisites

#### AWS (EC2)

#### Azure (VM)

#### Docker (Local Development)

#### Pre-Deployment Testing (deploy/test/)

#### Managing SSH Users on the Server

#### Upgrading from Previous Versions

#### Choosing Between AWS and Azure

## SSL Manager — AWS Deployment

### What is created

### Prerequisites

### Deploy

### Using a Graviton (ARM) instance

### Adding SSH IPs

### Verify EBS encryption

### Upgrade SSL Manager

### Network considerations

### Tear down

## SSL Manager — Azure Deployment

### What is created

### Prerequisites

### Deploy

### Adding SSH IPs

### Verify disk encryption

### Upgrade SSL Manager

### Network considerations

### Tear down

# SSL Manager — System Requirements

---

## Table of Contents

---

1. [Operating System](#)
  2. [Minimum Hardware](#)
    - [Sizing Rationale](#)
    - [When to Upsize](#)
  3. [System Packages](#)
    - [Installed by the Installer](#)
    - [Recommended Hardening Packages](#)
  4. [Python Packages](#)
  5. [Network Requirements](#)
  6. [File System Layout](#)
- 

## 1. Operating System

---

### Ubuntu (recommended)

| Requirement    | Value                                                              |
|----------------|--------------------------------------------------------------------|
| Supported OS   | Ubuntu 24.04 LTS (Noble Numbat) — recommended                      |
| Also supported | Ubuntu 22.04 LTS (Jammy Jellyfish), Ubuntu 20.04 LTS (Focal Fossa) |
| Architecture   | x86_64 (amd64), arm64 (aarch64)                                    |
| Install type   | Server (minimal) or standard server image                          |

Ubuntu 24.04 LTS is the recommended target. The installer ( `install.sh` ) detects the OS and enforces Ubuntu 20.04 or later.

## RHEL-family

| Requirement    | Value                                                                            |
|----------------|----------------------------------------------------------------------------------|
| Supported OS   | RHEL 9, Rocky Linux 9, AlmaLinux 9, CentOS Stream 9                              |
| Also supported | RHEL 8, Rocky Linux 8, AlmaLinux 8                                               |
| Architecture   | x86_64 (amd64), arm64 (aarch64)                                                  |
| Install type   | Minimal install                                                                  |
| Installer      | <code>install-rhel.sh</code> (separate from the Ubuntu <code>install.sh</code> ) |

RHEL-family deployments require SELinux configuration, which `install-rhel.sh` handles automatically. See the [RHEL](#) section of [INSTALL.md](#) for full instructions.

## 2. Minimum Hardware

The following sizing targets installations with up to **1,000 certificate records** and **2–3 concurrent users** accessing via SSH tunnel.

| Resource | Minimum   | Recommended |
|----------|-----------|-------------|
| CPU      | 1 vCPU    | 2 vCPU      |
| RAM      | 1 GB      | 2 GB        |
| Disk     | 10 GB SSD | 20 GB SSD   |
| Network  | Any       | Any         |

### 2.1 Sizing Rationale

The table below shows the expected steady-state memory footprint of all running components:

| Component               | Memory     | Notes                                                                                     |
|-------------------------|------------|-------------------------------------------------------------------------------------------|
| Ubuntu 24.04 minimal OS | 200–300 MB | systemd, journald, base services                                                          |
| nginx (2 workers)       | 10–20 MB   | Loopback reverse proxy + static file serving                                              |
| gunicorn (2 workers)    | 100–160 MB | Each Python worker loads Flask, SQLAlchemy, and the cryptography library (~50–80 MB each) |

| Component                 | Memory             | Notes                                                      |
|---------------------------|--------------------|------------------------------------------------------------|
| SQLite                    | 5–10 MB            | Page cache; under 1,000 records the database remains small |
| fail2ban                  | 30–50 MB           | Python-based log watcher; resident in memory at all times  |
| sshd (2–3 active tunnels) | 15–30 MB           | ~5–10 MB per active SSH tunnel session                     |
| <b>Total steady-state</b> | <b>~360–570 MB</b> |                                                            |

**1 GB RAM** runs all components comfortably with 40–60% headroom under normal load.

**CPU** is nearly idle between requests. The two operations that briefly spike CPU are:

- **RSA key generation** — RSA-2048 takes 50–200 ms per key; RSA-4096 takes 500 ms–2 s on a single vCPU. Each generation occupies one gunicorn worker for its duration.
- **Certificate format export** (PKCS#12, JKS, P7B) — subprocess calls to `openssl` and `keytool`, each completing in under 1 second.

With 2 gunicorn workers, one worker can generate a key while another concurrently serves a page request.

**Disk** usage for 1,000 certificates:

| Item                                                        | Size           |
|-------------------------------------------------------------|----------------|
| Ubuntu OS + installed packages                              | 3–5 GB         |
| Python virtual environment + app files                      | 150–200 MB     |
| SQLite database (1,000 certs × ~8 KB PEM data)              | 20–50 MB       |
| 7-day backup retention (PEM text compresses ~75% with gzip) | 20–50 MB       |
| nginx + gunicorn logs (1 year, light usage)                 | 100–300 MB     |
| <b>Total</b>                                                | <b>~4–6 GB</b> |

A **10 GB** disk is sufficient; **20 GB** provides comfortable headroom for log accumulation and OS updates.

## 2.2 When to Upsize

| Scenario                                                                                                       | Recommendation                                                      |
|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| fail2ban configured with aggressive regex scanning against large nginx log files                               | 2 GB RAM                                                            |
| Server runs other services alongside SSL Manager                                                               | 2 GB RAM                                                            |
| Users frequently generate RSA-4096 keys concurrently (3 simultaneous users can briefly queue behind 2 workers) | 2 vCPU                                                              |
| Backup retention extended significantly beyond 7 days                                                          | Larger disk                                                         |
| Certificate records exceed ~10,000                                                                             | Review disk and RAM; SQLite remains performant well past this point |

**Representative instance tiers** matching the minimum and recommended specifications:

| Provider      | Tier                    | Spec                      | Est. Cost   | Notes                                                                          |
|---------------|-------------------------|---------------------------|-------------|--------------------------------------------------------------------------------|
| Hetzner       | CX11                    | 2 vCPU / 2 GB / 20 GB SSD | ~€4/month   | Best value; storage included                                                   |
| DigitalOcean  | Basic Droplet           | 1 vCPU / 1 GB / 25 GB SSD | ~\$6/month  | Storage included                                                               |
| Linode/Akamai | Nanode                  | 1 vCPU / 1 GB / 25 GB SSD | ~\$5/month  | Storage included                                                               |
| Vultr         | Cloud Compute           | 1 vCPU / 1 GB / 25 GB SSD | ~\$6/month  | Storage included                                                               |
| AWS           | t4g.micro (minimum)     | 2 vCPU / 1 GB             | ~\$6/month  | Add ~\$1.60/month for 20 GB gp3 EBS; ARM Graviton2; Ubuntu 24.04 supported     |
| AWS           | t4g.small (recommended) | 2 vCPU / 2 GB             | ~\$12/month | Add ~\$1.60/month for 20 GB gp3 EBS; ARM Graviton2; eligible for Savings Plans |
| Azure         | B1s (minimum)           | 1 vCPU / 1 GB             | ~\$8/month  | 4 GB managed OS disk included; Standard HDD additional                         |
| Azure         |                         | 1 vCPU / 2 GB             | ~\$15/month |                                                                                |

| Provider | Tier                  | Spec | Est. Cost | Notes                                                    |
|----------|-----------------------|------|-----------|----------------------------------------------------------|
|          | B1ms<br>(recommended) |      |           | 4 GB managed OS disk included; add Standard SSD for data |

**AWS pricing notes:** EC2 compute and EBS storage are billed separately. A 20 GB gp3 EBS volume adds approximately \$1.60/month. New AWS accounts receive 750 hours/month of t2.micro or t3.micro (x86) On-Demand usage free for 12 months under the Free Tier. Prices shown are On-Demand Linux rates for us-east-1; Reserved Instances (1-year, no upfront) reduce compute cost by approximately 30–40%.

**Azure pricing notes:** Azure VM pricing includes a small managed OS disk but application data and backups should use a separate managed disk. Prices shown are Pay-As-You-Go Linux rates for East US. Azure Reserved VM Instances (1-year) reduce cost by approximately 30–40%. The B-series (burstable) is appropriate for this workload as CPU usage is low between certificate operations.

**All prices are estimates** based on public list pricing at time of writing and will vary by region, commitment term, and provider promotions. Verify current pricing on each provider's pricing page before provisioning.

Hetzner CX11 offers the best value for this workload — 2 vCPU and 2 GB RAM with storage included at the lowest monthly cost. AWS and Azure become more competitive when an organisation already has existing cloud credits, reserved capacity, or consolidated billing agreements.

## 3. System Packages

### 3.1 Installed by the Installer

Ubuntu ( `install.sh` )

The packages below are installed automatically by `install.sh` :

| Package                  | Purpose                                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <code>nginx</code>       | Reverse proxy; listens on <code>127.0.0.1</code> only; serves static files directly and forwards dynamic requests to gunicorn via Unix socket |
| <code>python3-pip</code> |                                                                                                                                               |

| Package                   | Purpose                                                                                            |
|---------------------------|----------------------------------------------------------------------------------------------------|
|                           | pip package manager used to install the Python virtual environment dependencies                    |
| <code>python3-venv</code> | Creates the isolated Python virtual environment at <code>/opt/ssl-manager/venv</code>              |
| <code>python3-dev</code>  | C header files required to compile the <code>cryptography</code> package's native extensions       |
| <code>gcc</code>          | C compiler required to build the <code>cryptography</code> package during <code>pip install</code> |
| <code>sqlite3</code>      | CLI tool used by <code>backup.sh</code> for WAL checkpointing and database integrity checks        |

`python3` and `openssl` are present in a default Ubuntu 24.04 LTS server install; the installer includes them in the `apt-get install` call as an explicit dependency declaration.

`sqlite3` is installed automatically as of the current release. On an **existing** install upgraded from an earlier version it may be missing — if backups fail with `sqlite3 not found`, install it manually:

```
sudo apt-get install -y sqlite3 # RHEL: sudo dnf install -y sqlite
```

**Documentation tooling** ( `weasyprint`, `playwright` ) is **not** installed on the server. It lives in `requirements-docs.txt` for development use only — `weasyprint` requires Python 3.10+, while the server runtime supports Python 3.9 (RHEL 9).

### RHEL-family ( `install-rhel.sh` )

The packages below are installed automatically by `install-rhel.sh`:

| Package                                   | Purpose                                                                                                                                                       |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>nginx</code>                        | Reverse proxy (same role as Ubuntu)                                                                                                                           |
| <code>python3-pip</code>                  | pip package manager                                                                                                                                           |
| <code>python3-devel</code>                | C header files for native extension builds (RHEL equivalent of <code>python3-dev</code> )                                                                     |
| <code>gcc</code>                          | C compiler                                                                                                                                                    |
| <code>policycoreutils-python-utils</code> | Provides <code>semanage</code> , used to configure SELinux file contexts and port permissions                                                                 |
| <code>epel-release</code>                 | Extra Packages for Enterprise Linux — installed automatically on Rocky/AlmaLinux/CentOS Stream; skipped on registered RHEL (use subscription-manager instead) |



`python3` and `openssl` are present in RHEL 9 / Rocky 9 minimal installs.

### 3.2 Recommended Hardening Packages

The following packages are **not installed by either installer** because they affect system-wide services and require manual review before enabling.

| Package                          | Ubuntu             | RHEL-family                                     | Purpose                                                                    |
|----------------------------------|--------------------|-------------------------------------------------|----------------------------------------------------------------------------|
| <code>ufw</code>                 | Included, inactive | Not available (use <code>firewalld</code> )     | Host firewall; restrict inbound traffic to SSH only                        |
| <code>firewalld</code>           | Not default        | Included, active                                | RHEL host firewall; restrict inbound traffic to SSH only                   |
| <code>fail2ban</code>            | Not included       | Not included                                    | Monitors nginx and sshd logs; bans IPs that repeatedly fail authentication |
| <code>unattended-upgrades</code> | Included, inactive | Not available (use <code>dnf-automatic</code> ) | Automatically installs security updates                                    |
| <code>dnf-automatic</code>       | Not available      | Not included                                    | RHEL equivalent of unattended-upgrades                                     |

#### Optional — JKS export format:

| Package                               | Ubuntu       | RHEL-family  | Purpose                                                                      |
|---------------------------------------|--------------|--------------|------------------------------------------------------------------------------|
| <code>default-jdk-headless</code>     | Not included | —            | Provides <code>keytool</code> for Java KeyStore ( <code>.jks</code> ) export |
| <code>java-17-openjdk-headless</code> | —            | Not included | RHEL equivalent; provides <code>keytool</code>                               |

Install on Ubuntu:

```
sudo apt-get install -y default-jdk-headless
```

Install on RHEL-family:

```
sudo dnf install -y java-17-openjdk-headless
```

If `keytool` is not installed, the JKS download button returns an error. All other export formats continue to work.

## 4. Python Packages

All Python dependencies are installed into an isolated virtual environment at `/opt/ssl-manager/venv` and are **not installed system-wide**.

| Package                       | Version | Purpose                                                                                                          |
|-------------------------------|---------|------------------------------------------------------------------------------------------------------------------|
| <code>Flask</code>            | 3.1.3   | Web framework — routing, templating, session management                                                          |
| <code>Flask-SQLAlchemy</code> | 3.1.1   | SQLAlchemy ORM integration for Flask; manages the SQLite connection pool                                         |
| <code>Flask-Login</code>      | 0.6.3   | User session management, login/logout, <code>current_user</code> context, <code>@login_required</code> decorator |
| <code>cryptography</code>     | 46.0.7  | RSA key generation, CSR construction, certificate parsing, PKCS#12 export; uses OpenSSL bindings                 |
| <code>gunicorn</code>         | 23.0.0  | Production WSGI server; runs the Flask app as multiple worker processes behind the nginx Unix socket             |

**Java KeyStore ( `.jks` ) export has no dependency.** It is produced by a small, self-contained writer ( `app/jks_writer.py` , standard library only) — no `pyjks` package and no Java/JRE are required. The writer's output is verified byte-for-byte against a fixture confirmed loadable by Java `keytool` (see `tests/fixtures/jks/` ).

The `pip install` step runs during `install.sh` / `install-rhel.sh` and again during `--upgrade` .

## 5. Network Requirements

SSL Manager is designed to be **unreachable from the network** by default. No inbound port other than SSH needs to be open.

| Interface                         | Port                   | Protocol    | Direction       | Purpose                                                      |
|-----------------------------------|------------------------|-------------|-----------------|--------------------------------------------------------------|
| All interfaces                    | 22                     | TCP         | Inbound         | SSH — required for tunnel access and server administration   |
| 127.0.0.1                         | 5001<br>(configurable) | TCP         | Loopback only   | nginx listener; not exposed to the network                   |
| /run/ssl-manager/ssl-manager.sock | —                      | Unix socket | Internal        | nginx → gunicorn communication                               |
| Any                               | 25, 465, or 587        | TCP         | <b>Outbound</b> | SMTP — only required if email (password reset) is configured |

**Remote access** is provided exclusively via SSH port forwarding:

```
ssh -L 5001:127.0.0.1:5001 user@your-server
```

No HTTP/HTTPS ports are opened to the network. A firewall rule allowing only port 22 inbound is sufficient for all functionality except outbound email.

**Outbound SMTP** is only needed if the password reset feature is configured. The specific port depends on your mail provider:

| Auth method                                  | Typical port |
|----------------------------------------------|--------------|
| STARTTLS                                     | 587          |
| SSL/TLS                                      | 465          |
| Plain SMTP (internal relay, not recommended) | 25           |

## 6. File System Layout

All paths created by `install.sh` / `install-rhel.sh` :

| Path                                                        | Owner                                | Mode             | Purpose                                                                  |
|-------------------------------------------------------------|--------------------------------------|------------------|--------------------------------------------------------------------------|
| <code>/opt/ssl-manager/</code>                              | <code>root:ssl-manager</code>        | <code>750</code> | Application code, templates, static files, Python venv                   |
| <code>/opt/ssl-manager/venv/</code>                         | <code>root:ssl-manager</code>        | <code>750</code> | Isolated Python virtual environment                                      |
| <code>/opt/ssl-manager/backup.sh</code>                     | <code>root:ssl-manager</code>        | <code>750</code> | Database backup script                                                   |
| <code>/var/lib/ssl-manager/</code>                          | <code>ssl-manager:ssl-manager</code> | <code>700</code> | SQLite database — accessible only by the service user                    |
| <code>/var/lib/ssl-manager/ssl_manager.db</code>            | <code>ssl-manager:ssl-manager</code> | <code>600</code> | Live SQLite database (WAL mode)                                          |
| <code>/var/log/ssl-manager/</code>                          | <code>ssl-manager:ssl-manager</code> | <code>750</code> | gunicorn access and error logs                                           |
| <code>/var/backups/ssl-manager/</code>                      | <code>root:root</code>               | <code>700</code> | Compressed database backups (7-day retention by default)                 |
| <code>/etc/ssl-manager/</code>                              | <code>root:ssl-manager</code>        | <code>750</code> | Application configuration directory                                      |
| <code>/etc/ssl-manager/env</code>                           | <code>root:ssl-manager</code>        | <code>640</code> | Environment file — <code>SECRET_KEY</code> , <code>DATABASE_URL</code>   |
| <code>/run/ssl-manager/ssl-manager.sock</code>              | <code>ssl-manager:ssl-manager</code> | <code>660</code> | Unix socket between nginx and gunicorn (recreated at each service start) |
| <code>/etc/systemd/system/ssl-manager.service</code>        | <code>root</code>                    | <code>644</code> | gunicorn systemd service unit                                            |
| <code>/etc/systemd/system/ssl-manager-backup.service</code> | <code>root</code>                    | <code>644</code> | Backup job systemd unit (Type=oneshot)                                   |
| <code>/etc/systemd/system/ssl-manager-backup.timer</code>   | <code>root</code>                    | <code>644</code> | Backup timer unit (daily at 02:00, Persistent=true)                      |

**Ubuntu-specific paths:**

| Path                                                      | Owner | Mode | Purpose                                            |
|-----------------------------------------------------------|-------|------|----------------------------------------------------|
| <code>/etc/nginx/sites-available/ssl-manager</code>       | root  | 644  | nginx reverse proxy configuration                  |
| <code>/etc/nginx/conf.d/ssl-manager-ratelimit.conf</code> | root  | 644  | nginx rate-limit zone definition (10 req/s per IP) |

**RHEL-family-specific paths:**

| Path                                                      | Owner | Mode | Purpose                                                                  |
|-----------------------------------------------------------|-------|------|--------------------------------------------------------------------------|
| <code>/etc/nginx/conf.d/ssl-manager.conf</code>           | root  | 644  | nginx reverse proxy configuration (RHEL uses conf.d; no sites-available) |
| <code>/etc/nginx/conf.d/ssl-manager-ratelimit.conf</code> | root  | 644  | nginx rate-limit zone definition                                         |

# SSL Manager — Installation Guide

---

## Deployment Options

| Method                                         | Best for                                                           |
|------------------------------------------------|--------------------------------------------------------------------|
| <a href="#">Bare Metal / Ubuntu Server</a>     | Physical hardware, on-premises VMs, self-managed VPS               |
| <a href="#">RHEL / Rocky Linux / AlmaLinux</a> | Red Hat-based enterprise or on-premises environments               |
| <a href="#">AWS (EC2)</a>                      | Existing AWS accounts, consolidated billing, Graviton cost savings |
| <a href="#">Azure (VM)</a>                     | Existing Azure accounts, enterprise agreements, Azure credits      |
| <a href="#">Docker (local development)</a>     | Development, testing, and feature validation — not for production  |

Cloud deployments (AWS and Azure) require Terraform **or** [OpenTofu](#) (its open-source fork — the configurations work with either) and the relevant cloud CLI. See [Cloud Deployment Prerequisites](#) for installation instructions covering macOS, Linux, and Windows — including [SSH key generation](#) for all platforms and [server-side user management](#).

All production methods share the same runtime stack: nginx → gunicorn → Flask → SQLite, with access via SSH tunnel only. See [REQUIREMENTS.md](#) for hardware sizing guidance.

---

## Bare Metal / Ubuntu Server

Use this method for physical hardware, on-premises virtual machines, or any VPS where you provision the OS yourself.

### Requirements

- Ubuntu 26.04 LTS, 24.04 LTS (recommended), 22.04 LTS, or 20.04 LTS
- Root or `sudo` access
- Outbound internet access (for `apt-get` and `pip`)
- Minimum: 1 vCPU, 1 GB RAM, 10 GB disk
- Recommended: 1–2 vCPU, 2 GB RAM, 20 GB disk

**Python version:** The installer uses the distribution's default Python 3 — from 3.8 on 20.04 through **3.14 on 26.04** — and all dependencies install as prebuilt wheels, so no compiler toolchain is exercised at install time. `requirements.txt` selects a compatible `gunicorn` per interpreter via environment markers (23.0.0 on Python < 3.10, 26.0.0 on  $\geq 3.10$ ), so a single file spans every supported release (including RHEL 9's Python 3.9). All combinations are validated by the test harness — see [Pre-Deployment Testing](#).

## 1. Get the code

```
git clone https://github.com/your-org/ssl-manager.git
cd ssl-manager
```

Or transfer the files to the server:

```
scp -r ssl-manager/ user@your-server:~/ssl-manager
```

## 2. Run the installer

```
sudo bash install.sh
```

The installer prompts for three values:

| Prompt                    | Default        | Notes                                                                                              |
|---------------------------|----------------|----------------------------------------------------------------------------------------------------|
| nginx listen port         | 5001           | nginx binds to <code>127.0.0.1:&lt;port&gt;</code> — loopback only, not reachable from the network |
| Gunicorn worker processes | 2              | Increase for higher concurrent load; 2 is sufficient for 2–3 users                                 |
| Secret key                | auto-generated | 256-bit random hex used to sign Flask sessions; leave blank to auto-generate                       |

The installer:

1. Installs system packages ( `nginx` , `python3-pip` , `python3-venv` , `gcc` , `python3-dev` )
2. Creates the `ssl-manager` service account (no login shell, no home directory)

3. Creates all directories with enforced ownership and permissions
4. Copies application files to `/opt/ssl-manager/`
5. Creates a Python virtual environment and installs all dependencies
6. Writes the secret key and database URL to `/etc/ssl-manager/env` (on a re-run, an existing `SECRET_KEY` is preserved — never regenerated — because it encrypts stored SMTP/OAuth secrets)
7. Installs and starts the `ssl-manager` systemd service
8. Configures nginx as a reverse proxy with rate limiting
9. Installs and enables the `ssl-manager-backup.timer` for daily database backups

**sqlite3:** The backup script requires the `sqlite3` CLI. Ubuntu 24.04 minimal server may not include it. If the first scheduled backup fails, install it with `sudo apt-get install -y sqlite3`.

**Re-running the installer:** Running `sudo bash install.sh` again on a host that already has SSL Manager auto-detects the existing installation and switches to **upgrade mode** — it skips the prompts and preserves your configuration, secret key, and database. See [Upgrading](#). Use `--reinstall` to force the interactive installer instead.

### 3. Verify the service is running

```
sudo systemctl status ssl-manager
sudo systemctl status ssl-manager-backup.timer
```

### 4. Connect via SSH tunnel

From your local machine:

```
ssh -L 5001:127.0.0.1:5001 user@your-server
```

Open `http://localhost:5001` in your browser. Complete the first-run setup to create the superadmin account.

For a persistent tunnel, add to `~/.ssh/config`:



```
Host ssl-manager
  HostName your-server
  User your-user
  LocalForward 5001 127.0.0.1:5001
  ServerAliveInterval 60
```

Then `ssh ssl-manager` is all that is needed.

## 5. Recommended post-install hardening

The following steps are not automated because they affect system-wide services. Review each before applying.

### Firewall (UFW):

```
sudo ufw default deny incoming
sudo ufw default allow outgoing
sudo ufw allow ssh
sudo ufw enable
sudo ufw status verbose
```

### fail2ban:

```
sudo apt-get install -y fail2ban
sudo systemctl enable --now fail2ban
```

Create `/etc/fail2ban/jail.d/ssl-manager.conf`:

```
[sshd]
enabled = true
port    = ssh
maxretry = 5
bantime = 1h
findtime = 10m

[nginx-limit-req]
enabled = true
port    = http,https
logpath = /var/log/nginx/ssl-manager-error.log
maxretry = 10
bantime = 1h
```

```
sudo systemctl restart fail2ban
```

### Unattended security updates:

```
sudo dpkg-reconfigure --priority=low unattended-upgrades
```

## Service management

```
# Status and logs
sudo systemctl status ssl-manager
sudo journalctl -u ssl-manager -f
sudo tail -f /var/log/ssl-manager/error.log

# Restart after config change
sudo nano /etc/ssl-manager/env
sudo systemctl restart ssl-manager

# Backup management
sudo systemctl status ssl-manager-backup.timer
sudo systemctl list-timers ssl-manager-backup.timer
sudo bash /opt/ssl-manager/backup.sh # run a backup immediately
```

## Upgrading

After pulling or transferring updated code:

```
sudo bash install.sh --upgrade
```

Re-running the installer with no flag does the same thing — it auto-detects the existing install and upgrades.

The upgrade backs up the database, then refreshes the application files, Python dependencies, systemd unit, and nginx config from the new code. Your `SECRET_KEY`, database, and existing port/worker settings are **preserved** (the port and worker count are re-derived from the current nginx/systemd config, so there are no prompts). Schema migrations run automatically on the next service start — no manual SQL steps are required. See [Upgrading from Previous Versions](#) for version-specific notes.

## Uninstalling

```
sudo bash install.sh --uninstall
```

Removes the service, application files, nginx config, and optionally the database and service user. The database at `/var/lib/ssl-manager/` is not deleted unless explicitly confirmed.

## RHEL / Rocky Linux / AlmaLinux

---

Use this method for RHEL 8/9, Rocky Linux 8/9, AlmaLinux 8/9, or CentOS Stream 9. The RHEL installer ( `install-rhel.sh` ) handles SELinux configuration and `dnf` -based package management automatically.

### Requirements

- RHEL 9 / Rocky Linux 9 / AlmaLinux 9 (recommended), or 8-series equivalents
- Root or `sudo` access
- Outbound internet access (for `dnf` and `pip` )
- Minimum: 1 vCPU, 1 GB RAM, 10 GB disk
- Recommended: 1–2 vCPU, 2 GB RAM, 20 GB disk
- **Registered RHEL only:** An active Red Hat subscription with the AppStream and BaseOS repositories enabled

### 1. Get the code

```
git clone https://github.com/your-org/ssl-manager.git
cd ssl-manager
```

Or transfer the files to the server:

```
scp -r ssl-manager/ user@your-server:~/ssl-manager
```

### 2. Run the installer

```
sudo bash install-rhel.sh
```

The installer prompts for the same three values as the Ubuntu installer (port, worker count, secret key).

The installer additionally:

1. Enables EPEL (on Rocky/AlmaLinux/CentOS Stream; skipped on registered RHEL)

2. Installs `policycoreutils-python-utils` for SELinux management
3. Configures SELinux to allow nginx to communicate with the unicorn Unix socket:
  - Sets `httpd_var_run_t` file context on the socket directory
  - Enables `httpd_can_network_connect` boolean
  - Adds the chosen port to the `http_port_t` SELinux port type
4. Writes the nginx config to `/etc/nginx/conf.d/` (RHEL uses `conf.d` ; there is no `sites-available` / `sites-enabled` )
5. Uses `nginx` as the nginx user (not `www-data` as on Ubuntu)

**SELinux note:** If you later change the nginx port after installation, re-run the SELinux port permission manually:

```
sudo semanage port -a -t http_port_t -p tcp <new-port>
sudo systemctl restart nginx
```

### 3. Verify the service is running

```
sudo systemctl status ssl-manager
sudo systemctl status ssl-manager-backup.timer
```

### 4. Connect via SSH tunnel

Identical to the Ubuntu procedure — from your local machine:

```
ssh -L 5001:127.0.0.1:5001 user@your-server
```

Open `http://localhost:5001` and complete the first-run setup.

### 5. Recommended post-install hardening

**Firewall (firewalld):**

```
# Allow SSH only – all other inbound ports are blocked by default on RHEL
sudo firewall-cmd --permanent --add-service=ssh
sudo firewall-cmd --permanent --remove-service=cockpit # optional
sudo firewall-cmd --reload
sudo firewall-cmd --list-all
```

## fail2ban:

```
sudo dnf install -y fail2ban
sudo systemctl enable --now fail2ban
```

Create `/etc/fail2ban/jail.d/ssl-manager.conf` with the same content as the Ubuntu example above, then:

```
sudo systemctl restart fail2ban
```

## Automatic security updates (dnf-automatic):

```
sudo dnf install -y dnf-automatic
sudo sed -i 's/^apply_updates = .*/apply_updates = yes/' /etc/dnf/automatic.conf
sudo systemctl enable --now dnf-automatic.timer
```

## Service management

Identical commands to Ubuntu — `systemctl status ssl-manager`, `journalctl -u ssl-manager`, etc.

## Upgrading

```
sudo bash install-rhel.sh --upgrade
```

As on Ubuntu, re-running `install-rhel.sh` with no flag auto-detects the existing install and upgrades, preserving your `SECRET_KEY`, database, and port/worker settings (and re-applying the SELinux and nginx configuration). Use `--reinstall` to force the interactive installer. See [Upgrading from Previous Versions](#) for version-specific notes.

## Uninstalling

```
sudo bash install-rhel.sh --uninstall
```

## Configure Email (Optional)

SSL Manager can send password reset emails via SMTP. This step is optional — the application functions fully without email; only the password reset flow requires it.

### Supported authentication methods

| Method                     | When to use                                                                                                                                                                                                                                                                      |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Standard SMTP</b>       | Any mail provider reached over SMTP — with username/password (Gmail app password, SendGrid, Amazon SES, Mailgun, your own server) <b>or</b> unauthenticated against an internal relay (Authentication Method <i>None</i> ). STARTTLS or implicit SSL can be enabled on any port. |
| <b>Microsoft 365 OAuth</b> | Microsoft 365 / Exchange Online accounts where modern authentication is required                                                                                                                                                                                                 |
| <b>Google OAuth</b>        | Google Workspace accounts using OAuth 2.0                                                                                                                                                                                                                                        |

### Configure via the web UI

1. Log in as a **superadmin** user.
2. Navigate to **Settings** → **Email** ( `/settings/smtp` ).
3. Fill in the fields for your provider:

#### Standard SMTP fields:

| Field             | Example                                               |
|-------------------|-------------------------------------------------------|
| SMTP Host         | <code>smtp.sendgrid.net</code>                        |
| Port              | <code>587</code> (STARTTLS) or <code>465</code> (SSL) |
| Username          | Your SMTP login or API key name                       |
| Password          | Your SMTP password or API key                         |
| From address      | <code>noreply@yourdomain.com</code>                   |
| From name         | <code>SSL Manager</code>                              |
| Use TLS / Use SSL | Match your provider's requirement                     |

**Unauthenticated, encrypted relay (e.g. port 25 + STARTTLS):** For an internal relay that requires no login but supports TLS, set **Authentication Method** to **None**, set **Port** to your relay's port (commonly **25**), enable **STARTTLS**, and leave Username/Password blank. STARTTLS is not tied to a specific port — it upgrades the connection to TLS on whatever port you configure.

### Microsoft 365 OAuth:

1. Register an application in [Azure Active Directory](#).
2. Add the redirect URI: `http://localhost:5001/settings/smtp/oauth/microsoft/callback`
3. Grant the **Mail.Send** permission (delegated).
4. In the SSL Manager SMTP settings, select **Microsoft 365 OAuth**, enter the **Client ID**, **Client Secret**, and **Tenant ID**, then click **Connect** to complete the OAuth flow.

### Google OAuth:

1. Create an OAuth 2.0 Client ID in [Google Cloud Console](#).
2. Add the redirect URI: `http://localhost:5001/settings/smtp/oauth/google/callback`
3. Enable the **Gmail API** in your project.
4. In the SSL Manager SMTP settings, select **Google OAuth**, enter the **Client ID** and **Client Secret**, then click **Connect**.

### Test email delivery

After saving your settings, click **Send Test Email** on the SMTP settings page. A test message will be sent to your own account (the logged-in superadmin's email address). Check the audit log if the test fails — delivery errors are recorded there.

### Network requirements

Ensure outbound TCP is permitted on the port your provider uses:

```
# Ubuntu (UFW)
sudo ufw allow out 587/tcp # STARTTLS
sudo ufw allow out 465/tcp # SSL (if used instead)

# RHEL (firewalld)
sudo firewall-cmd --permanent --add-port=587/tcp
sudo firewall-cmd --reload
```

## Recovering email after a SECRET\_KEY change

The SMTP password and all OAuth tokens are encrypted with a key derived from `SECRET_KEY`. If `SECRET_KEY` is ever changed — for example, an older installer re-run regenerated it instead of preserving the existing key — those stored secrets can no longer be decrypted and email fails **silently**: the configuration still appears enabled, but authentication uses an empty secret.

`remediate_secret_key.py` detects and cleans up this situation. It is read-only by default:

```
# Report which stored secrets can no longer be decrypted (no changes):
sudo -u ssl-manager /opt/ssl-manager/venv/bin/python \
/opt/ssl-manager/remediate_secret_key.py

# Clear the dead secrets and disable SMTP, then re-enter them in the web UI
# (Settings → SMTP) and re-enable:
sudo -u ssl-manager /opt/ssl-manager/venv/bin/python \
/opt/ssl-manager/remediate_secret_key.py --apply

# If you still have the PREVIOUS key, recover the secrets instead of clearing
# them (decrypt with the old key, re-encrypt under the current one):
sudo -u ssl-manager /opt/ssl-manager/venv/bin/python \
/opt/ssl-manager/remediate_secret_key.py --old-secret-key <previous-key> --apply
```

Certificate and CA private keys are **not** affected — they are stored without `SECRET_KEY`-based encryption and survive a key change. Note that `backup.sh` backs up the database only, not `/etc/ssl-manager/env`, so a rotated key is not recoverable from a backup; keep a copy of `SECRET_KEY` if you need portability.



## Cloud Deployment Prerequisites

The AWS and Azure deployments both use Terraform — or, equivalently, [OpenTofu](#), its open-source fork. Install **one** of the two (plus the relevant cloud CLI) on your local machine before proceeding. The SSL Manager configurations in `deploy/aws/` and `deploy/azure/` are identical for both tools.

### Terraform

#### macOS

```
brew tap hashicorp/tap
brew install hashicorp/tap/terraform
terraform version # confirm install
```

#### Linux (Ubuntu / Debian)

```
sudo apt-get install -y gnupg software-properties-common
wget -O- https://apt.releases.hashicorp.com/gpg \
| sudo gpg --dearmor -o /usr/share/keyrings/hashicorp-archive-keyring.gpg
echo "deb [signed-by=/usr/share/keyrings/hashicorp-archive-keyring.gpg] \
https://apt.releases.hashicorp.com $(lsb_release -cs) main" \
| sudo tee /etc/apt/sources.list.d/hashicorp.list
sudo apt-get update && sudo apt-get install -y terraform
terraform version # confirm install
```

#### Linux (RHEL / Fedora / Amazon Linux)

```
sudo yum install -y yum-utils
sudo yum-config-manager --add-repo https://rpm.releases.hashicorp.com/RHEL/hashicorp.repo
sudo yum install -y terraform
terraform version # confirm install
```

### Windows

Option A — winget (Windows 10/11, recommended):

```
winget install HashiCorp.Terraform
terraform version # confirm install
```

Option B — Chocolatey:

```
choco install terraform
terraform version # confirm install
```

Option C — Manual: download the `.zip` from [developer.hashicorp.com/terraform/downloads](https://developer.hashicorp.com/terraform/downloads), extract `terraform.exe`, and add its folder to your `PATH`.

## OpenTofu (drop-in alternative to Terraform)

OpenTofu is an open-source, Linux Foundation fork of Terraform. The SSL Manager configurations work with it unchanged — same HCL, same `terraform.tfvars`, same state files. Install OpenTofu **instead of** Terraform if you prefer it; everywhere the deployment guides say `terraform <command>`, substitute `tofu <command>` (e.g. `tofu init`, `tofu plan`, `tofu apply`, `tofu destroy`). You do not need both tools.

## macOS

```
brew install opentofu
tofu --version # confirm install
```

## Linux (Debian / Ubuntu / RHEL / Fedora)

```
# Official installer — auto-detects the distribution and configures the package repo
curl --proto 'https' --tlsv1.2 --fsSL https://get.opentofu.org/install-opentofu.sh -o
install-opentofu.sh
chmod +x install-opentofu.sh
./install-opentofu.sh --install-method deb # use 'rpm' on RHEL / Fedora
rm -f install-opentofu.sh
tofu --version # confirm install
```

## Windows

Option A — winget (Windows 10/11, recommended):

```
winget install --exact --id=OpenTofu.Tofu
tofu --version # confirm install
```

Option B — Chocolatey:

```
choco install opentofu
tofu --version # confirm install
```

## AWS CLI (required for AWS deployments only)

### macOS

```
brew install awscli  
aws --version # confirm install
```

### Linux

```
curl "https://awscli.amazonaws.com/awscli-exe-linux-x86_64.zip" -o awscliv2.zip  
unzip awscliv2.zip  
sudo ./aws/install  
aws --version # confirm install
```

For ARM (Graviton) systems replace `x86_64` with `aarch64` in the URL.

### Windows

Option A — winget:

```
winget install Amazon.AWSCLI  
aws --version # confirm install
```

Option B — MSI installer: download and run AWSCLIv2.msi from AWS, then confirm with `aws --version` in a new terminal.

---

## Azure CLI (required for Azure deployments only)

### macOS

```
brew install azure-cli  
az version # confirm install
```

### Linux (Ubuntu / Debian)

```
curl -sL https://aka.ms/InstallAzureCLIDeb | sudo bash  
az version # confirm install
```

### Linux (RHEL / Fedora / Amazon Linux)

```
sudo rpm --import https://packages.microsoft.com/keys/microsoft.asc  
sudo dnf install -y azure-cli  
az version # confirm install
```

## Windows

Option A — winget:

```
winget install Microsoft.AzureCLI
az version # confirm install
```

Option B — MSI installer: download and run the installer from [aka.ms/installazurecliwindows](https://aka.ms/installazurecliwindows), then confirm with `az version` in a new terminal.

---

## SSH key pair

Every user who needs to connect to the server requires an SSH key pair. Generate one on the machine you will connect from, then provide the public key to the server administrator (or paste it into `terraform.tfvars` for Terraform deployments).

### macOS

OpenSSH is included with macOS. Open **Terminal** and check whether a key already exists:

```
ls -la ~/.ssh/id_ed25519 ~/.ssh/id_ed25519.pub 2>/dev/null
```

**If a key already exists** and you are comfortable reusing it for SSL Manager, skip to the “View / copy” step below.

**If no key exists**, or you prefer a dedicated key for this server, generate one:

```
# Default name – use if you have no existing key
ssh-keygen -t ed25519 -C "your-name-ssl-manager"

# Named key – use if you want to keep this separate from existing keys
ssh-keygen -t ed25519 -C "your-name-ssl-manager" -f ~/.ssh/id_ed25519_ssl_manager
```

Set a passphrase when prompted — this protects the private key if your machine is compromised.

```
# View the public key (share this – never the private key)
cat ~/.ssh/id_ed25519.pub          # default key
cat ~/.ssh/id_ed25519_ssl_manager.pub # named key

# Copy the public key to the clipboard
pbcopy < ~/.ssh/id_ed25519.pub
pbcopy < ~/.ssh/id_ed25519_ssl_manager.pub # named key
```

Keys are stored in `~/.ssh/`:

| File                               | Description                                    |
|------------------------------------|------------------------------------------------|
| <code>~/.ssh/id_ed25519</code>     | Private key — keep this secret, never share it |
| <code>~/.ssh/id_ed25519.pub</code> | Public key — safe to share; goes on the server |

**Connecting with a named key** — use the `-i` flag to specify which private key to use:

```
ssh -i ~/.ssh/id_ed25519_ssl_manager user@<server-ip>

# With tunnel
ssh -i ~/.ssh/id_ed25519_ssl_manager -L 5001:127.0.0.1:5001 user@<server-ip>
```

To avoid typing `-i` every time, add an entry to `~/.ssh/config`:

```
Host ssl-manager
  HostName <server-ip>
  User <username>
  IdentityFile ~/.ssh/id_ed25519_ssl_manager
  LocalForward 5001 127.0.0.1:5001
  ServerAliveInterval 60
```

Then connect with just `ssh ssl-manager`.

## Linux

OpenSSH is included on most distributions. If it is missing:

```
sudo apt-get install -y openssh-client # Ubuntu / Debian
sudo dnf install -y openssh            # Fedora / RHEL
```

Check whether a key already exists:

```
ls -la ~/.ssh/id_ed25519 ~/.ssh/id_ed25519.pub 2>/dev/null
```

**If no key exists**, or you want a dedicated key:

```
# Default name
ssh-keygen -t ed25519 -C "your-name-ssl-manager"

# Named key - keeps this separate from existing keys
ssh-keygen -t ed25519 -C "your-name-ssl-manager" -f ~/.ssh/id_ed25519_ssl_manager
```

Set a passphrase when prompted.

```
# View the public key
cat ~/.ssh/id_ed25519.pub
cat ~/.ssh/id_ed25519_ssl_manager.pub # named key

# Copy to clipboard (install xclip first if needed)
xclip -selection clipboard < ~/.ssh/id_ed25519.pub # X11
wl-copy < ~/.ssh/id_ed25519.pub # Wayland
```

## Connecting with a named key:

```
ssh -i ~/.ssh/id_ed25519_ssl_manager user@<server-ip>

# With tunnel
ssh -i ~/.ssh/id_ed25519_ssl_manager -L 5001:127.0.0.1:5001 user@<server-ip>
```

Or add to `~/.ssh/config` :

```
Host ssl-manager
  HostName <server-ip>
  User <username>
  IdentityFile ~/.ssh/id_ed25519_ssl_manager
  LocalForward 5001 127.0.0.1:5001
  ServerAliveInterval 60
```

## Windows

### Option A — OpenSSH (recommended, built into Windows 10/11)

Open **PowerShell** or **Windows Terminal** and check whether a key already exists:

```
Test-Path $env:USERPROFILE\.ssh\id_ed25519
```

A result of `True` means a key exists. You can reuse it, or generate a named key to keep SSL Manager separate.

**If no key exists**, or you want a dedicated key:

```
# Default name
ssh-keygen -t ed25519 -C "your-name-ssl-manager"

# Named key
ssh-keygen -t ed25519 -C "your-name-ssl-manager" -f
"$env:USERPROFILE\.ssh\id_ed25519_ssl_manager"
```

Set a passphrase when prompted. Keys are written to **C:\Users\<you>\.ssh\**.

```
# View the public key
type $env:USERPROFILE\.ssh\id_ed25519.pub
type $env:USERPROFILE\.ssh\id_ed25519_ssl_manager.pub # named key

# Copy the public key to the clipboard
Get-Content $env:USERPROFILE\.ssh\id_ed25519.pub | Set-Clipboard
```

### Connecting with a named key:

```
ssh -i $env:USERPROFILE\.ssh\id_ed25519_ssl_manager user@<server-ip>
ssh -i $env:USERPROFILE\.ssh\id_ed25519_ssl_manager -L 5001:127.0.0.1:5001 user@<server-ip>
```

Or add to **C:\Users\<you>\.ssh\config** :

```
Host ssl-manager
  HostName <server-ip>
  User <username>
  IdentityFile C:\Users\<you>\.ssh\id_ed25519_ssl_manager
  LocalForward 5001 127.0.0.1:5001
  ServerAliveInterval 60
```

### Option B — Git Bash

If you have Git for Windows installed, open **Git Bash** and follow the Linux instructions above. Keys are stored in **~/ .ssh/** within Git Bash, which maps to **C:\Users\<you>\.ssh\**.

### Option C — PuTTYgen (PuTTY users)

If you use PuTTY for SSH sessions:

1. Open **PuTTYgen** (included with PuTTY)
2. Check whether an existing **.ppk** file exists — if so, load and reuse it via **File → Load private key**
3. To create a new key: select **EdDSA** and click **Generate**, then move the mouse to generate entropy

4. Set a **Key passphrase**
5. Click **Save private key** — save the `.ppk` file (e.g. `ssl-manager.ppk`)
6. Copy the text in the **Public key for pasting into OpenSSH** `authorized_keys` box

To specify the key in a PuTTY session: go to **Connection** → **SSH** → **Auth** → **Credentials** and set the **Private key file** to your `.ppk`.

The `.ppk` format is PuTTY-specific. When asked for your public key, provide the text from the “Public key for pasting into OpenSSH” box, not the `.ppk` file itself.

## Find your current public IP

You will need your public IP address to populate `allowed_ssh_ips` in `terraform.tfvars`.

```
# macOS / Linux
curl -s https://checkip.amazonaws.com

# Windows (PowerShell)
(Invoke-WebRequest -Uri "https://checkip.amazonaws.com").Content.Trim()
```

---

## AWS (EC2)

SSL Manager can be deployed to AWS using the Terraform configuration in `deploy/aws/`. It provisions a hardened EC2 instance (Ubuntu 24.04 LTS) with an encrypted EBS root volume and a security group that restricts SSH access to specified IP addresses only.

**Full instructions:** [DEPLOY-AWS.md](#)



## Summary of steps

```
# 1. Install prerequisites – see "Cloud Deployment Prerequisites" above

# 2. Authenticate
aws configure
aws sts get-caller-identity    # confirm the correct account

# 3. Configure
cd deploy/aws
cp terraform.tfvars.example terraform.tfvars
# Edit terraform.tfvars: set admin_ssh_public_key and allowed_ssh_ips

# 4. Deploy
terraform init
terraform plan
terraform apply

# 5. Install SSL Manager on the provisioned instance
ssh ubuntu@<public_ip_from_output>
# Then follow the bare metal steps above from "Get the code"
```

## What Terraform provisions

| Resource                      | Detail                                                                          |
|-------------------------------|---------------------------------------------------------------------------------|
| VPC, subnet, internet gateway | Isolated network with public routing                                            |
| Security group                | SSH (port 22) from <code>allowed_ssh_ips</code> only; all other inbound blocked |
| EC2 instance                  | <code>t3.small</code> (2 vCPU / 2 GB), Ubuntu 24.04 LTS                         |
| EBS root volume               | 30 GB gp3, encrypted with AWS-managed key                                       |
| Elastic IP                    | Static public IP, persists through reboots                                      |

## Adding SSH IPs later

```
# terraform.tfvars
allowed_ssh_ips = [
  "203.0.113.10/32", # existing
  "198.51.100.5/32", # new IP
]
```

```
terraform apply    # updates the security group in seconds, no restart needed
```

## Azure (VM)

SSL Manager can be deployed to Azure using the Terraform configuration in `deploy/azure/`. It provisions a hardened Linux VM (Ubuntu 24.04 LTS) with hypervisor-level disk encryption and a Network Security Group that restricts SSH access to specified IP addresses only.

**Full instructions:** [DEPLOY-AZURE.md](#)

### Summary of steps

```
# 1. Install prerequisites – see "Cloud Deployment Prerequisites" above

# 2. Authenticate
az login
az account show                # confirm the correct subscription

# 3. Register the EncryptionAtHost feature (one-time per subscription)
az feature register --name EncryptionAtHost --namespace Microsoft.Compute
az feature show --name EncryptionAtHost --namespace Microsoft.Compute \
  --query "properties.state" -o tsv
# Wait until output is "Registered" (5–10 minutes)
az provider register --namespace Microsoft.Compute

# 4. Configure
cd deploy/azure
cp terraform.tfvars.example terraform.tfvars
# Edit terraform.tfvars: set admin_ssh_public_key and allowed_ssh_ips

# 5. Deploy
terraform init
terraform plan
terraform apply

# 6. Install SSL Manager on the provisioned VM
ssh sslmgr@<public_ip_from_output>
# Then follow the bare metal steps above from "Get the code"
```

### What Terraform provisions

| Resource                     | Detail                                                                          |
|------------------------------|---------------------------------------------------------------------------------|
| Resource group, VNet, subnet | Isolated network                                                                |
| Network Security Group       | SSH (port 22) from <code>allowed_ssh_ips</code> only; all other inbound blocked |
| VM                           | <code>Standard_B1ms</code> (1 vCPU / 2 GB), Ubuntu 24.04 LTS                    |
| OS disk                      | 30 GB Premium SSD, encrypted at host                                            |

| Resource         | Detail                                 |
|------------------|----------------------------------------|
| Static public IP | Standard SKU, persists through reboots |

## Adding SSH IPs later

```
# terraform.tfvars
allowed_ssh_ips = [
  "203.0.113.10/32", # existing
  "198.51.100.5/32", # new IP
]
```

```
terraform apply # updates the NSG rule in seconds, no restart needed
```

## Docker (Local Development)

Docker is provided for local development and testing only. It runs the Flask application directly without nginx, gunicorn, systemd, or the hardening applied by `install.sh`. **Do not use Docker in production.**

### App only

```
docker compose up --build
```

The app is available at `http://localhost:5001`.

### App + backup test service

Adds a `backup-test` container that runs `backup.sh` 10 seconds after startup, then every hour. Use this to verify backup execution and audit log entries without waiting for the systemd timer.

```
docker compose -f docker-compose.yml -f docker-compose.test.yml up --build
```

Watch backup output:

```
docker compose -f docker-compose.yml -f docker-compose.test.yml logs -f backup-test
```

## App + design seed data

Populates the database with representative seed data (certificates, chains, CAs, users) for UI development and screenshot generation:

```
docker compose -f docker-compose.yml -f docker-compose.design.yml up --build
```

Seed credentials: `designer / design123` (superadmin), `alice / design123` (user). See `seed_design.py` for the full dataset.

Full developer workflow documentation, including the complete Docker command reference, is in [WORKFLOW.md — Section 1](#).

## Pre-Deployment Testing (deploy/test/)

For maintainers: `deploy/test/` is a Docker-based harness that validates the installers against every supported OS and CPU architecture in disposable containers — before any real server is touched. It is **not** required to deploy SSL Manager; use it when changing dependencies, the installers, or qualifying a new OS release.

### Requirements

- Docker (Desktop or Engine) with the daemon running
- For cross-architecture runs on a single host, the QEMU/binfmt emulators:

```
docker run --privileged --rm tonistiigi/binfmt --install amd64,arm64
```

### Two layers of checks

| Script                     | What it proves                                                                                                                                                                                                                                                                                                                      |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>run-matrix.sh</code> | <b>Dependency + app layer.</b> In a clean container per OS/arch: installs the same apt packages as <code>install.sh</code> , builds the venv, runs <code>pip install -r requirements.txt</code> (asserting wheels resolve — no source builds), runs the full <code>pytest</code> suite, and boots gunicorn to serve a live request. |

| Script                         | What it proves                                                                                                                                                                                                                                                                                                        |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>install-matrix.sh</code> | <b>Full installer, end-to-end.</b> Boots a systemd-enabled container, runs <code>install.sh</code> non-interactively, then <code>verify-install.sh</code> asserts the service + timers are active, the socket and file permissions are correct, and a request through nginx → gunicorn returns a valid HTTP response. |

Supporting files: `Dockerfile.systemd` (Ubuntu systemd image), `Dockerfile.systemd-rhel` (AlmaLinux 9 image for `install-rhel.sh`), `preflight.sh` (the in-container dependency check), and `verify-install.sh` (the OS-agnostic post-install assertions).

## Running

```
# Dependency + app matrix across Ubuntu 24.04/26.04, amd64 + arm64 (default)
bash deploy/test/run-matrix.sh

# Full install.sh matrix (systemd containers)
bash deploy/test/install-matrix.sh

# Narrow the matrix with env vars
IMAGES="ubuntu:26.04" PLATFORMS="linux/arm64" bash deploy/test/install-matrix.sh

# install-rhel.sh on AlmaLinux 9 (Python 3.9 – the supported floor)
docker build --build-arg BASE=almalinux:9 -t ssl-mgr-rhel \
  -f deploy/test/Dockerfile.systemd-rhel deploy/test

# then run it with systemd (see the Dockerfile header for the exact flags) and
# execute install-rhel.sh + deploy/test/verify-install.sh inside the container.
```

## Known container/emulation limitations

These are artifacts of testing in containers and do **not** affect real servers:

- **systemd sandboxing is not fully reproducible in a container.**

The unit's hardening directives ( `ProtectSystem` , `PrivateDevices` , `SystemCallFilter` , ...) are validated on the **native** architecture; under QEMU emulation a service start can fail with `status=226/NAMESPACE` because the emulation layer cannot set up the required mount namespaces (notably Ubuntu 26.04 / systemd 259 under `linux/amd64` emulation on an arm64 host). Run the install matrix on the native arch and rely on `run-matrix.sh` for the other.

- **Rocky Linux 9's minimal arm64 image** ships broken DNF `module` metadata, which breaks `dnf install nginx`; the RHEL harness uses **AlmaLinux 9** instead (both are accepted by `install-rhel.sh`).

## Managing SSH Users on the Server

This section applies to all deployment methods. Perform these steps as the initial admin user after connecting to the server for the first time.

### Creating a user account

```
# Create a standard user (no sudo)
sudo adduser alice

# Create a user with sudo access
sudo adduser bob
sudo usermod -aG sudo bob      # Ubuntu
sudo usermod -aG wheel bob     # RHEL-family
```

`adduser` / `useradd` is interactive — it prompts for a password. The password is used only for `sudo` prompts on the server itself; SSH login uses keys.

**Tip:** For users who only need SSH tunnel access to the SSL Manager web UI and will never run commands on the server, a standard account without sudo is sufficient.

### Adding a user's SSH public key

Each user generates their key pair on their own machine and sends their **public key** to the administrator.

#### As the admin, placing a key for another user:

```
sudo mkdir -p /home/alice/.ssh
sudo chmod 700 /home/alice/.ssh
echo "ssh-ed25519 AAAAC3Nz...rest-of-key... alice-laptop" \
| sudo tee -a /home/alice/.ssh/authorized_keys
sudo chmod 600 /home/alice/.ssh/authorized_keys
sudo chown -R alice:alice /home/alice/.ssh
```

## Adding multiple keys for one user

Each line in `authorized_keys` is one public key. A user can have keys for multiple devices:

```
sudo tee -a /home/alice/.ssh/authorized_keys <<'EOF'
ssh-ed25519 AAAAC3Nz...key-one... alice-laptop
ssh-ed25519 AAAAC3Nz...key-two... alice-home-desktop
EOF
sudo chmod 600 /home/alice/.ssh/authorized_keys
```

## Disabling password authentication (recommended)

Once all users have working key-based login, disable password authentication:

```
sudo nano /etc/ssh/sshd_config
```

Set or confirm:

```
PasswordAuthentication no
PubkeyAuthentication yes
PermitRootLogin no
AuthorizedKeysFile .ssh/authorized_keys
```

```
sudo sshd -t          # test config before applying
sudo systemctl reload ssh
```

**Important:** Do not close your current session until you have confirmed key-based login works in a new terminal window.

## Revoking access

To remove a user's access, delete their line in `authorized_keys` :

```
sudo nano /home/alice/.ssh/authorized_keys
# Delete the line containing the key to revoke
```

To remove the user entirely:

```
sudo deluser --remove-home alice    # Ubuntu
sudo userdel --remove alice         # RHEL-family
```

## Upgrading from Previous Versions

---

The `--upgrade` flag handles all routine upgrades: it backs up the database, then refreshes the application files, Python dependencies, systemd unit, and nginx config. Your `SECRET_KEY`, database, and port/worker settings are preserved. Re-running the installer with no flag auto-detects the existing install and does the same thing. **Schema changes are applied automatically** on the next service start — no manual SQL steps are ever required.

```
sudo bash install.sh --upgrade      # Ubuntu
sudo bash install-rhel.sh --upgrade # RHEL-family
```

### Version history and migration notes

**Current release — Expiry notifications, platform support, installer & chain-PEM hygiene**

No manual steps required on upgrade (one optional cleanup for older installs — see *Chain PEM hygiene* below).

**New features:**

- **Expiry notification emails** — an optional daily digest (superadmin → Settings → Notifications) emails a colour-coded list of certificates, CAs, and intermediates expiring within a configurable threshold. Delivered by the new `ssl-manager-notify.timer`.
- **Ubuntu 26.04 LTS / Python 3.14 support** — `requirements.txt` selects a compatible `gunicorn` per interpreter via environment markers, so a single dependency set spans RHEL 9's Python 3.9 through Ubuntu 26.04's Python 3.14. Validated on Ubuntu 24.04/26.04 and AlmaLinux 9, amd64 and arm64.
- **OpenTofu supported** — the AWS and Azure Terraform configurations work unchanged with `OpenTofu`; substitute `tofu` for `terraform`. See [Cloud Deployment Prerequisites](#).

**Reliability fixes:**

- **Worker-boot race fixed** — concurrent gunicorn workers no longer race on schema initialization at startup. Previously a boot could fail with `table ... already exists` (service `status=3`, “Worker failed to boot”); schema bootstrap is now serialized with an exclusive lock.
- **Installer auto-upgrade** — re-running `install.sh` /



`install-rhel.sh` on an existing host now detects the installation and upgrades instead of starting a fresh interactive install. A new `--reinstall` flag forces the interactive installer. - **SECRET\_KEY preserved on re-run** — the installer no longer regenerates the key on an existing install. Previously this could rotate the key and make stored SMTP/OAuth secrets undecryptable. - **Installer hardening** — secret generation no longer assumes `python3` exists before the package step, and the Ubuntu installer enables and reload-or-restarts nginx rather than assuming it is already running (robust on lean/container/cloud-init bases).

**Chain PEM hygiene:** - **Intermediate PEM rendering fixed** — the chain edit modal previously showed PEM with literal `&#10;` instead of line breaks (a display-only double-escape; stored data was unaffected). - **Line endings normalized on import** — pasting a bundle into a text area submits it with CRLF (standard browser behaviour), which was stored verbatim and surfaced as stray characters in exported `fullchain.pem`. Imports now store LF. - **Optional cleanup for older installs** — if a chain was imported before this release, normalize the stored rows in place with the bundled tool (dry-run first): `bash /opt/ssl-manager/venv/bin/python /opt/ssl-manager/remediate_chain_entities.py # report /opt/ssl-manager/venv/bin/python /opt/ssl-manager/remediate_chain_entities.py --apply # fix`

**Schema migrations (automatic):** - `notification_config` — new table created to store expiry-notification settings.

### Smart bundle import

Added in a prior update. No manual steps required on upgrade.

**New features:** - **Smart P12/PFX import** — uploading a `.p12` or `.pfx` file now shows a live File Analysis preview (key type, certificate CN, expiry, detected intermediates, chain action) before import is confirmed. - **Keypair import** — a new Import Private Key + Certificate flow accepts a separate PEM key and certificate (or bundle, including P7B). Live preview confirms key/certificate match before import. - **Smart bundle upload** — uploading a signed certificate via the Certificate Detail page now performs role-based detection: the leaf certificate is identified by its CA flag,

intermediates are split out and deduplicated against the assigned chain. P7B bundles are supported. - **Security update** — `cryptography` library updated to 46.0.7 (addresses CVE-2025-61727).

#### v1.2 — Password reset and SMTP

**New features:** - **Password reset by email** — users can request a password reset link from the login page. Requires SMTP to be configured (see [Configure Email](#)). - **Microsoft 365 and Google OAuth** — SMTP authentication via OAuth 2.0, removing the need to store an application password. - **Automatic session invalidation** — changing a user's password immediately invalidates all existing sessions for that account. - **15-minute idle timeout** — unauthenticated sessions are invalidated after 15 minutes of inactivity.

**Schema migrations (automatic):** - `user.session_version` — integer column added to support session invalidation on password change. - `smtp_config.*` — new table (and additional OAuth columns) created to store SMTP configuration.

**Upgrade action required:** None — migrations run automatically on first start after upgrade.

#### v1.1 — Certificate Authorities (internal CA)

**New features:** - **Internal CA module** — create self-signed root CAs entirely within SSL Manager and use them to sign pending certificates without an external CA portal. - **Certificate Profiles** — reusable templates for CSR subject fields (organisation, country, key size, etc.). - **Named Certificate Chains** — intermediate certificates are now grouped into named chains that can be shared across multiple certificates. - **Import CSR** — import an externally generated CSR (from a network appliance, load balancer, etc.) as a pending certificate record.

**Schema migrations (automatic):** - `cert_chain` — new table for named certificate chains. - `intermediate_cert.chain_id` — foreign key added to link intermediates to a chain. - `certificate.chain_id` — foreign key

added to link certificates to a chain. - `certificate.profile_id` — foreign key added to link certificates to a profile. - `settings.name` / `settings.is_default` — columns added to support named profiles.

**Upgrade action required:** None — all migrations and data backfills run automatically on first start. Existing intermediates are migrated into a “Default Chain” automatically.

#### v1.0 — Initial release

Base feature set: certificate lifecycle management (generate key + CSR, upload signed cert), intermediate certificate management, user accounts, audit log, daily backup timer.

## Choosing Between AWS and Azure

| Consideration         | AWS                                                    | Azure                                                               |
|-----------------------|--------------------------------------------------------|---------------------------------------------------------------------|
| Disk encryption setup | None — <code>encrypted = true</code> works immediately | One-time <code>az feature register</code> per subscription required |
| Cheapest option       | t4g.small (ARM Graviton2) ~\$12/month + ~\$1.60 EBS    | B1ms ~\$15/month                                                    |
| Minimum viable        | t4g.micro ~\$6/month + EBS                             | B1s ~\$8/month                                                      |
| Static IP billing     | EIP free when attached; ~\$0.005/hr when unattached    | Included in VM cost                                                 |
| Existing account      | Prefer if you have AWS credits or consolidated billing | Prefer if you have Azure credits or EA                              |
| Admin username        | <code>ubuntu</code> (fixed by AMI)                     | Configurable (default: <code>sslmgr</code> )                        |

See [REQUIREMENTS.md](#) for full hardware sizing rationale and a complete provider comparison table.

# SSL Manager — AWS

## Deployment

---

Terraform (or [OpenTofu](#)) configuration that provisions a hardened AWS EC2 instance running SSL Manager. The configuration is identical for both tools.

## What is created

| Resource         | Details                                                                                            |
|------------------|----------------------------------------------------------------------------------------------------|
| VPC              | Isolated network ( <code>10.0.0.0/16</code> ) with DNS enabled                                     |
| Internet Gateway | Provides outbound internet access (for apt, pip, OS updates)                                       |
| Subnet           | Public subnet ( <code>10.0.1.0/24</code> ) in <code>&lt;region&gt;a</code>                         |
| Route Table      | Default route → Internet Gateway                                                                   |
| Security Group   | SSH (port 22) allowed from <code>allowed_ssh_ips</code> only; all other inbound blocked by default |
| Key Pair         | SSH public key registered in EC2                                                                   |
| EC2 Instance     | Ubuntu 24.04 LTS, <code>t3.small</code> (2 vCPU / 2 GB RAM)                                        |
| Root EBS Volume  | 30 GB gp3, encrypted with AWS-managed key                                                          |
| Elastic IP       | Static public IP; persists through stop/start and reboots                                          |

## EBS encryption

`encrypted = true` on the root EBS volume encrypts all data at rest using the AWS-managed key ( `alias/aws/ebs` ) at no additional cost. This requires no prerequisite registration and is applied immediately at provisioning time, covering the SQLite database, log files, backup archives, SSL certificate private keys, and CA private keys generated by the internal CA module.

To use a Customer Managed Key (CMK) from AWS KMS instead, uncomment and set `kms_key_id` in the `root_block_device` block in `main.tf`.

## Security Group IP management

All permitted SSH source addresses are stored in the `allowed_ssh_ips` Terraform variable. Each IP gets its own ingress rule (AWS best practice). To add or remove an IP:

1. Edit `terraform.tfvars` — add or remove entries from `allowed_ssh_ips`

## 2. Run `terraform apply`

The security group rules update in place in seconds; no instance restart is required.

---

## Prerequisites

---

### 1. Tools

| Tool                                                         | Install                                                                          |
|--------------------------------------------------------------|----------------------------------------------------------------------------------|
| <a href="#">Terraform</a> <b>or</b> <a href="#">OpenTofu</a> | <code>brew install terraform</code> <b>or</b> <code>brew install opentofu</code> |
| <a href="#">AWS CLI v2</a>                                   | <code>brew install awscli</code> / <a href="#">AWS docs</a>                      |

### 2. AWS credentials

Configure credentials for the account and region you want to deploy into:

```
aws configure
# Prompts for: AWS Access Key ID, Secret Access Key, region, output format
```

Or for SSO / assumed roles:

```
aws sso login --profile your-profile
export AWS_PROFILE=your-profile
```

Confirm the correct account is active:

```
aws sts get-caller-identity
```

### 3. SSH key pair

If you do not already have an SSH key pair:

```
ssh-keygen -t ed25519 -C "ssl-manager-aws"
# Keys written to ~/.ssh/id_ed25519 and ~/.ssh/id_ed25519.pub
```

## Deploy

**Terraform or OpenTofu:** Every `terraform` command below works identically with `OpenTofu` — substitute `tofu` for `terraform` ( `tofu init` , `tofu plan` , `tofu apply` , `tofu destroy` , `tofu output` ). The `.tf` files, `terraform.tfvars` , and state files are the same for either tool. Use whichever you installed in the prerequisites.

### 1. Configure variables

```
cd deploy/aws
cp terraform.tfvars.example terraform.tfvars
```

Edit `terraform.tfvars` and set at minimum:

- `admin_ssh_public_key` — contents of `~/.ssh/id_ed25519.pub`
- `allowed_ssh_ips` — your current public IP (find it with `curl -s https://checkip.amazonaws.com` )
- `timezone` — tz database name for the server clock, e.g. `"America/New_York"` (controls backup filenames, log timestamps, and the daily backup timer; defaults to `"UTC"` )

### 2. Initialise and apply

```
terraform init
terraform plan    # review what will be created
terraform apply   # type 'yes' to confirm
```

`terraform apply` completes in approximately 1–3 minutes. On success, the outputs section displays:

## Outputs:

```

allowed_ssh_ips = ["203.0.113.10/32"]
ami_id          = "ami-0xxxxxxxxxxxxxxxxx"
ami_name        = "ubuntu/images/hvm-ssd-gp3/ubuntu-noble-24.04-amd64-server-20240423"
ebs_encrypted   = true
instance_id     = "i-0xxxxxxxxxxxxxxxxx"
public_ip_address = "54.x.x.x"
region          = "us-east-1"
ssh_command     = "ssh ubuntu@54.x.x.x"
ssh_tunnel_command = "ssh -L 5001:127.0.0.1:5001 ubuntu@54.x.x.x"

```

### 3. Connect and install SSL Manager

```

# Connect to the instance
ssh ubuntu@<public_ip_address>

# On the instance – update packages
sudo apt-get update && sudo apt-get upgrade -y

# Clone the repository (or copy files via scp)
git clone https://github.com/your-org/ssl-manager.git
cd ssl-manager

# Run the installer
sudo bash install.sh

```

Follow the interactive installer prompts (port, Gunicorn workers, secret key). When complete, the SSL Manager service is running and the daily backup timer is enabled.

### 4. Open the web UI via SSH tunnel

From your **local machine**:

```
ssh -L 5001:127.0.0.1:5001 ubuntu@<public_ip_address>
```

Then open `http://localhost:5001` in your browser and complete first-run setup.

For a persistent tunnel configuration, add to `~/.ssh/config` :

```

Host ssl-manager
  HostName <public_ip_address>
  User ubuntu
  IdentityFile ~/.ssh/id_ed25519
  LocalForward 5001 127.0.0.1:5001
  ServerAliveInterval 60

```



Then simply `ssh ssl-manager`.

---

## Using a Graviton (ARM) instance

---

Graviton2 instances ( `t4g` ) offer approximately 20% lower cost for equivalent performance. To switch:

1. In `terraform.tfvars`, set:

```
instance_type = "t4g.small"
ami_arch      = "arm64"
```

2. Run `terraform apply`

The AMI data source selects the correct Ubuntu 24.04 ARM image automatically. All SSL Manager dependencies support ARM — the `cryptography` package includes ARM native extensions.

**Note:** Switching between `x86_64` and `arm64` replaces the EC2 instance. Take a manual backup before switching architecture.

---

## Adding SSH IPs

---

Edit `terraform.tfvars` :

```
allowed_ssh_ips = [
  "203.0.113.10/32", # Office
  "198.51.100.5/32", # New IP to add
]
```

Apply:

```
terraform apply
```

The security group rules update in seconds. No instance restart needed.

## Verify EBS encryption

---

After the instance is running:

```
aws ec2 describe-volumes \
  --filters "Name=attachment.instance-id,Values=$(terraform output -raw instance_id)" \
  --query "Volumes[*].{ID:VolumeId,Encrypted:Encrypted,KmsKeyId:KmsKeyId}" \
  --output table
# Encrypted column should show True
```

**Note:** AWS EBS encryption is applied at the hypervisor/storage layer and is transparent to the guest OS. Running `lsblk` inside the instance will not show any encryption indicator — the volume appears as a normal block device. The AWS CLI command above is the authoritative verification method.

---

## Upgrade SSL Manager

---

After pulling new code, copy it to the instance and run the upgrade:

```
# From your local machine — copy updated files
scp -r wsgi.py app/ backup.sh requirements.txt \
  ubuntu@<public_ip>:/tmp/ssl-manager-update/

# On the instance
sudo cp -r /tmp/ssl-manager-update/* /opt/ssl-manager/
sudo bash /opt/ssl-manager/install.sh --upgrade
```

The upgrade preserves your `SECRET_KEY`, database, and port/worker settings while refreshing the application files, systemd unit, and nginx config. Re-running `install.sh` with no flag does the same thing — it auto-detects the existing install and upgrades.

## Network considerations

---

### Outbound SMTP

The default Terraform security group allows **all outbound traffic**, so no additional rule is needed for email delivery. However, some AWS accounts or VPCs have outbound restrictions. If password reset emails are not delivered, verify that outbound TCP on port 587 (STARTTLS) or 465 (SSL) is not blocked by a VPC Network ACL or an account-level firewall policy.

To check the effective outbound rules on the instance's security group:

```
aws ec2 describe-security-groups \
  --group-ids $(terraform output -raw security_group_id) \
  --query "SecurityGroups[*].IpPermissionsEgress" \
  --output table
```

---

## Tear down

```
terraform destroy
```

This terminates the EC2 instance and releases the Elastic IP. The EBS volume is deleted ( `delete_on_termination = true` ). Take a manual backup first:

```
ssh ubuntu@<public_ip> \
  "sudo bash /opt/ssl-manager/backup.sh --dest /tmp/ssl-final-backup && \
  sudo ls -lh /tmp/ssl-final-backup/"

# Copy the backup archive locally before destroying
scp "ubuntu@<public_ip>:/tmp/ssl-final-backup/*.db.gz" .
```

**Elastic IP note:** An unassociated Elastic IP is billed at ~\$0.005/hour. `terraform destroy` releases it, stopping the charge.

# SSL Manager — Azure Deployment

---

Terraform (or [OpenTofu](#)) configuration that provisions a hardened Azure VM running SSL Manager. The configuration is identical for both tools.

## What is created

| Resource                 | Details                                                                                 |
|--------------------------|-----------------------------------------------------------------------------------------|
| Resource Group           | Contains all SSL Manager resources                                                      |
| Virtual Network + Subnet | Isolated network ( <code>10.0.0.0/16</code> / <code>10.0.1.0/24</code> )                |
| Network Security Group   | SSH (port 22) allowed from <code>allowed_ssh_ips</code> only; all other inbound blocked |
| Static Public IP         | Standard SKU — address persists through VM restarts                                     |
| Network Interface        | NSG applied at both NIC and subnet level (defence in depth)                             |
| Linux VM                 | Ubuntu 24.04 LTS, <code>Standard_B1ms</code> (1 vCPU / 2 GB RAM)                        |
| OS Disk                  | 30 GB Premium SSD, encrypted at host                                                    |

### Disk encryption

`encryption_at_host_enabled = true` encrypts all data written by the VM at the hypervisor level — OS disk, temporary disk, and their caches — using Azure platform-managed keys. This requires a one-time subscription feature registration (see Prerequisites below).

This approach covers everything written to disk by the SSL Manager application: the SQLite database, log files, backup archives, SSL certificate private keys, and CA private keys generated by the internal CA module.

### NSG IP management

All permitted SSH source addresses are stored in the `allowed_ssh_ips` Terraform variable. To add or remove an IP:

1. Edit `terraform.tfvars` — add or remove entries from `allowed_ssh_ips`
2. Run `terraform apply`

The NSG rule updates in place in seconds; no VM restart is required.

## Prerequisites

### 1. Tools

| Tool                                                  | Install                                                                   |
|-------------------------------------------------------|---------------------------------------------------------------------------|
| <a href="#">Terraform</a> or <a href="#">OpenTofu</a> | <code>brew install terraform</code> or <code>brew install opentofu</code> |
| <a href="#">Azure CLI</a>                             | <code>brew install azure-cli</code> / <a href="#">Microsoft docs</a>      |

### 2. Azure login

```
az login
az account show # confirm the correct subscription is active
```

To switch subscriptions:

```
az account set --subscription "<subscription-id-or-name>"
```

### 3. Register the EncryptionAtHost feature

This is a one-time step per subscription. It takes 5–10 minutes.

```
az feature register --name EncryptionAtHost --namespace Microsoft.Compute

# Poll until state is "Registered"
az feature show --name EncryptionAtHost --namespace Microsoft.Compute \
  --query "properties.state" -o tsv

az provider register --namespace Microsoft.Compute
```

### 4. SSH key pair

If you do not already have an SSH key pair:

```
ssh-keygen -t ed25519 -C "ssl-manager-azure"
# Keys written to ~/.ssh/id_ed25519 and ~/.ssh/id_ed25519.pub
```

## Deploy

**Terraform or OpenTofu:** Every `terraform` command below works identically with `OpenTofu` — substitute `tofu` for `terraform` ( `tofu init` , `tofu plan` , `tofu apply` , `tofu destroy` , `tofu output` ). The `.tf` files, `terraform.tfvars` , and state files are the same for either tool. Use whichever you installed in the prerequisites.

### 1. Configure variables

```
cd deploy/azure
cp terraform.tfvars.example terraform.tfvars
```

Edit `terraform.tfvars` and set at minimum:

- `admin_ssh_public_key` — contents of `~/.ssh/id_ed25519.pub`
- `allowed_ssh_ips` — your current public IP (find it with `curl -s https://checkip.amazonaws.com` )
- `timezone` — tz database name for the server clock, e.g. `"America/New_York"` (controls backup filenames, log timestamps, and the daily backup timer; defaults to `"UTC"` )

### 2. Initialise and apply

```
terraform init
terraform plan    # review what will be created
terraform apply   # type 'yes' to confirm
```

`terraform apply` completes in approximately 2–4 minutes. On success, the outputs section displays:

```
Outputs:

allowed_ssh_ips           = ["203.0.113.10/32"]
encryption_at_host_enabled = true
public_ip_address         = "20.x.x.x"
resource_group_name       = "ssl-manager-rg"
ssh_command               = "ssh sslmgr@20.x.x.x"
ssh_tunnel_command        = "ssh -L 5001:127.0.0.1:5001 sslmgr@20.x.x.x"
vm_name                   = "ssl-manager-vm"
```

### 3. Connect and install SSL Manager

```
# Connect to the VM
ssh sslmgr@<public_ip_address>

# On the VM – update packages
sudo apt-get update && sudo apt-get upgrade -y

# Clone the repository (or copy files via scp)
git clone https://github.com/your-org/ssl-manager.git
cd ssl-manager

# Run the installer
sudo bash install.sh
```

Follow the interactive installer prompts (port, Gunicorn workers, secret key). When complete, the SSL Manager service is running and the daily backup timer is enabled.

### 4. Open the web UI via SSH tunnel

From your **local machine**:

```
ssh -L 5001:127.0.0.1:5001 sslmgr@<public_ip_address>
```

Then open `http://localhost:5001` in your browser and complete first-run setup.

For persistent tunnel configuration, add to `~/.ssh/config` :

```
Host ssl-manager
  HostName <public_ip_address>
  User sslmgr
  IdentityFile ~/.ssh/id_ed25519
  LocalForward 5001 127.0.0.1:5001
  ServerAliveInterval 60
```

Then simply `ssh ssl-manager` .

---

## Adding SSH IPs

Edit `terraform.tfvars` :



```
allowed_ssh_ips = [
    "203.0.113.10/32", # Office
    "198.51.100.5/32", # New IP to add
]
```

Apply:

```
terraform apply
```

The NSG rule updates in seconds. No VM restart needed.

---

## Verify disk encryption

---

After the VM is running:

```
az vm show \
  --resource-group ssl-manager-rg \
  --name ssl-manager-vm \
  --query "securityProfile.encryptionAtHost" \
  --output tsv
# Expected output: true
```

---

## Upgrade SSL Manager

---

After pulling new code, upload it to the VM and run the upgrade:

```
# From your local machine – copy updated files
scp -r wsgi.py app/ backup.sh requirements.txt \
  sslmgr@<public_ip>:/tmp/ssl-manager-update/

# On the VM
sudo cp -r /tmp/ssl-manager-update/* /opt/ssl-manager/
sudo bash /opt/ssl-manager/install.sh --upgrade
```

The upgrade preserves your `SECRET_KEY`, database, and port/worker settings while refreshing the application files, systemd unit, and nginx config. Re-running `install.sh` with no flag does the same thing — it auto-detects the existing install and upgrades.

## Network considerations

---

### Outbound SMTP

The Terraform NSG allows **all outbound traffic** by default, so no additional rule is needed for email delivery. However, some Azure subscriptions or policies restrict outbound traffic. If password reset emails are not delivered, verify that outbound TCP on port 587 (STARTTLS) or 465 (SSL) is not blocked by a subscription-level Azure Policy or a custom NSG rule.

To list effective outbound security rules for the VM's NIC:

```
az network nic list-effective-nsg \
  --resource-group ssl-manager-rg \
  --name ${az network nic list --resource-group ssl-manager-rg \
    --query "[0].name" -o tsv) \
  --query "effectiveSecurityRules[?direction=='Outbound']" \
  --output table
```

---

## Tear down

```
terraform destroy
```

This removes all resources in the resource group. The SQLite database is on the VM's OS disk and will be deleted. Take a manual backup first:

```
ssh sslmgr@<public_ip> \
  "sudo bash /opt/ssl-manager/backup.sh --dest /tmp/ssl-final-backup && \
  sudo ls -lh /tmp/ssl-final-backup/"

# Copy the backup archive locally before destroying
scp "sslmgr@<public_ip>:/tmp/ssl-final-backup/*.db.gz" .
```