Relational Calculus

CSE 132a Winter 2016

Existential and Universal Quantifiers

```
\exists b \in \mathsf{Books}[...]
```

There exists a book b where this condition holds.

```
\exists b \in \mathsf{Books}[\forall c \in \mathsf{Customers}[\exists p \in \mathsf{Purchases}[...]]]
```

There exists a book, where for each customer, there exists a purchase where this condition holds.

Analagous to "FROM Books b WHERE ..." in SQL.

Tuples

Tuples are like rows in a database

```
\exists b \in \mathsf{Books}[b(\mathsf{title})...]
```

```
\exists b \in \mathsf{Books}[\forall c \in \mathsf{Customers}[\exists p \in \mathsf{Purchases}[\ c(\mathsf{customerid})...p(\mathsf{bookid})...p(\mathsf{bookid})]]]
```

Similar to b.title and p.price

Additional Operators

```
Operators: \land, \lor, =, \neq, \rightarrow, <, >, \leq, \geq
\exists b \in \mathsf{Books}[b(\mathsf{title}) = \mathsf{'Twilight'}]
\exists b \in \mathsf{Books}[\forall c \in \mathsf{Customers}[\exists p \in \mathsf{Purchases}[c(\mathsf{customerid}) = p(\mathsf{customerid}) \land p(\mathsf{bookid}) = b(\mathsf{bookid})]]]
```

SELECT Analogy

```
\{r : \mathsf{bookid} \mid \exists b \in \mathsf{Books}[b(\mathsf{title}) = \mathsf{'Twilight'} \land r(\mathsf{bookid}) = b(\mathsf{bookid})]\}
\{r : \mathsf{title} \mid \exists b \in \mathsf{Books}[\forall c \in \mathsf{Customers}[\exists p \in \mathsf{Purchases}[c(\mathsf{customerid}) = p(\mathsf{customerid}) \land p(\mathsf{bookid}) = b(\mathsf{bookid})]] \land b(\mathsf{title}) = r(\mathsf{title})]\}
```

SELECT title FROM Books WHERE author = 'EDMUND MORGAN' AND year >= 1990;

```
SELECT title
FROM Books
WHERE author = 'EDMUND MORGAN'
AND year >= 1990;

{r: title | ...}
```

```
SELECT title
FROM Books
WHERE author = 'EDMUND MORGAN'
AND year >= 1990;
\{r: \text{title} \mid \exists b \in \text{Books[...]}\}
```

```
SELECT title FROM Books WHERE author = 'EDMUND MORGAN' AND year >= 1990; \{r: \text{title } | \exists b \in Books[b(author) = 'EDMUND MORGAN' <math>\land b(\text{year}) \ge 1990]\} DONE?
```

```
SELECT title
FROM Books
WHERE author = 'EDMUND MORGAN'
AND year >= 1990;
\{r: \text{title} \mid \exists b \in \text{Books}[b(\text{author}) = \text{'EDMUND MORGAN'} \land b(\text{year}) \geq 1990 \land r(\text{title}) = b(\text{title})]\}
```

```
{r : title | ...}
```

```
\{r : \mathsf{title} \mid \exists b \in \mathsf{Books}[...]\}
```

```
\{r : \mathsf{title} \mid \exists b \in \mathsf{Books}[\forall o \in \mathsf{Books}[...]]\}
```

```
\{r : \text{title } | \exists b \in \text{Books}[\forall o \in \text{Books}[b(\text{year}) \ge o(\text{year})]]\} DONE?
```

```
\{r : \text{title} \mid \exists b \in \text{Books}[\forall o \in \text{Books}[b(\text{year}) \geq o(\text{year})] \land b(\text{title}) = r(\text{title})]\}
```

```
\{r : \mathsf{title} \mid \exists b \in \mathsf{Books}[\neg \exists o \in \mathsf{Books}[b(\mathsf{year}) < o(\mathsf{year})] \land b(\mathsf{title}) = r(\mathsf{title})]\}
```

What are the titles of the newest books?

```
\{r : \text{title} \mid \exists b \in \text{Books}[\neg \exists o \in \text{Books}[b(\text{year}) < o(\text{year})] \land b(\text{title}) = r(\text{title})]\}
```

SELECT b.title FROM Books b WHERE ...

What are the titles of the newest books?

WHERE b.vear < o.vear);

```
\{r: \text{title} \mid \exists b \in \text{Books}[\neg \exists o \in \text{Books}[b(\text{year}) < o(\text{year})] \land b(\text{title}) = r(\text{title})]\}
SELECT b.title
FROM Books b
WHERE NOT EXISTS( SELECT ... FROM Books o
```

4□ > 4□ > 4 = > 4 = > = 900

Example 2

Relational Calculus to SQL

```
\{r: \text{title} \mid \exists b \in \text{Books}[\neg \exists o \in \text{Books}[b(\text{year}) < o(\text{year})] \land b(\text{title}) = r(\text{title})]\}
SELECT b.title
FROM Books b
WHERE NOT EXISTS( SELECT *
FROM Books o
WHERE b.year < o.year);
```