

SER 502

Emerging Programming Languages and Paradigms (Spring 2020) Project Phase 1 – Language

Name: Trace

Akhilesh Krishnan (akrish84)

Rahul Suresh(rahul0717)

Swarnalatha Srenigarajan (Swar-jain)

Idhant Haldankar(idhant96)

Description:

Program begins with the keyword “execute”.

It is followed by a block. A block starts and ends with curly braces and comprises declarations, statements.

The user can declare variables of type: Number, Boolean or string.

Data types supported in our language:

Number: Comprises integer or floating point number. Default Value: 0

Boolean: true or false. Default value: false

String: It is a sequence of characters enclosed within double quotes. Default value: "" (Empty)

Arithmetic Operators:

1. Modulus: %
2. Multiplication: *
3. Division: /
4. Addition: +

5. Subtraction: -

6. Increment: ++

7. Decrement: --

Arithmetic Operator Precedence:

1. Parenthesis: ()

2. Modulus, Multiplication, Division: %, *, /

3. Addition, Subtraction: +, -

Relational Operators:

1. Lesser : "<"

2. Greater : ">"

3. Less than or equal to : "<="

4. Greater than or equal to : ">="

5. Not equal to : "!="

6. Equality check : "=="

Logical Operators:

1. and

2. or

3. Not

Assignment Operator:

1. Equals: "="

Ternary operator:

This operator requires **3 operands** and can be used as a replacement for if then else then statements.

Example for ternary operator :

```
a = false;
```

```
a ? print("true") : print("false");
```

Declarations:

A block can have zero or more number of declaration statements. Our program is strongly typed and data type has to be explicitly mentioned. Have a signal declaration in a line. Every declaration should end with semicolon “;”

Example of declaration.

1. number a = 10;
2. number a;
3. bool isValid = true;
4. string name;

Conditional Statement

The “if (condition) then” statement executes a block if the condition evaluates to true. If the condition evaluates to false, the block following the “else then” gets executed. This is used to execute different blocks based on different conditions. The keyword “elseif (condition) then” is used to check for another condition when the “if (condition) then” condition evaluates to false.

Examples of conditionals: if (x == 2

```
) then {x = x + 2} else then {x = x + 1}
```

```
if (x == 2) then {x = x + 2}
```

```
elseif (x == 3) then {x = x + 1} else then {x
```

```
= x + 3}
```

```
if (x == 2) then { x = x + 2 }
```

Statement Lists:

Statement Lists is the part which follows Block. Statement List part can contain one or more of many of the types of statements.

Different kinds of statements: Print statement, Assignment statements, Loop Statement List, Conditional Statement List.

Print statement:

The print statement is used to write to the screen. The print statements start with a 'print' keyword and then followed by a string, boolean expression or number expression to be printed inside '()'.
Example: `print("Hello World!")`

Loop statement:

Simple for pattern

A loop statement starts with "for" followed by parenthesis (). Inside the parentheses we have three parts which are namely "declaration", "conditional expression" and "increment statement". In declaration we would declare the iterable variable, later the bool_expr will evaluate the iteration limit for the loop and lastly the update statement will update the iterable variable.

Examples of Simple for pattern :

```
for(i=0; i<10; i=i+1){ i = i+1;  
  
}
```

Range pattern

A loop statement starts with "for" followed by iterable variable initialization. In declaration we would declare the iterable variable, and range of iterable values the iterable variable can take. The range function generates a list of iterable values which the iterable variable can take in each iteration.

Examples of Simple for pattern :

```
for i in range(1,10){ i = i +
```

```
1;
```

```
}
```

Simple While Loop

The while loop will begin with the “while” keyword followed by parenthesis (). Inside the parentheses the `bool_expr`, which gets executed each time the while loop is called. The loop continues until `bool_expr` returns true and ends when it returns false.

Examples of Simple for pattern :

```
while (i < 10){ i = i +
```

```
1;
```

```
}
```

Assignment Statement:

This statement is used to set a value given to a variable. Examples of

assignment statement :

1. `X = 5;`

2. `X = "HelloWorld!";`

3. `X = "true";`

Example Program:

```
execute {
```

```
number a;
```

```
bool isValid = false;
```

```
string name = "team22";

if(name == "team22" ) then {

print("team 22");

} else then {

print("not eam 22");

}

for(numberi=0;i<22;i++){ a = i;

print("hi");

}

a = (20 % 5) + 2;

isValid = true;

while(isValid) { int b =

10;

print("isValid");

isValid = false;

}

print("This is a sample program");

}
```

Grammar

program -> [execute], block

block -> ['{'], declarationList, statementList, ['}']

/* Declaration part */

%-----

declarationList -> declaration, [';'], declarationList

declarationList -> []

%-----

declaration-> numberDeclaration

declaration -> booleanDeclaration

declaration -> stringDeclaration

%-----

numberDeclaration -> [number], var_name, ['='], number_expr

numberDeclaration -> [number], var_name

%-----

booleanDeclaration -> [bool], var_name, ['='], bool_expr

booleanDeclaration -> [bool], var_name

%-----

stringDeclaration-> [string], var_name, ['='], string_expr

stringDeclaration -> [string], var_name

%-----

/* Statements part */

statementList -> statement, [';'], statementList

statementList -> loopStatement, statementList

statementList -> conditionalStatement, statementList

statementList -> []

%-----

statement -> print_statement

statement -> var_name, ['='], number_expr

statement -> var_name, ['='], bool_expr

statement -> var_name, ['='], string_expr

statement -> var_name, ['++']

statement -> var_name, ['--']

%---

print_statement -> [print],['('], string_expr, [')']

print_statement -> [print],['('], number_expr, [')']

```
print_statement -> [print],['('], bool_expr, [')']
print_statement -> [println],['('], string_expr, [')']
print_statement -> [println],['('], number_expr, [')']
print_statement -> [println],['('], bool_expr, [')']
```

%---

/* Looping Statements -> (for loop, for in range() loop and while loop) */

loopStatement -> [for], ['('], declaration, [';'], bool_expr , [';'], statement, [')'], block

loopStatement -> [for], var_name, [in], [range], ['('], number_expr, [,'], number_expr ,[')'], block

loopStatement -> [while], ['('], bool_expr ,[')'], block

/* Conditional Statements -> (empty, if then, if then else, if then else if...) */

conditionalStatement -> [if], ['('], bool_expr , [')'], [then], block

conditionalStatement -> [if], ['('], bool_expr , [')'], [then], block , [else], [then], block

conditionalStatement -> [if], ['('], bool_expr , [')'], [then], block , [else], conditionalStatement

conditionalStatement -> bool_expr, ['?'], statement, [':'], statement,[;]

/Number expression with precedence/

number_expr-> [len],['('],string_expr,[')']

number_expr -> number_expr, ['+'], level_1

number_expr -> number_expr, ['-'], level_1

number_expr -> level_1

level_1 -> level_1, ['*'], level_2

level_1 -> level_1, ['/'], level_2

level_1 -> level_1, ['%'], level_2

level_1 -> level_2

level_2 -> ['('], number_expr, [')']

level_2 -> number

level_2 -> var_name

/* Boolean Expression -> (true, false, not, and ,or, ==, !=, >, <, >=, <=, ()) */

bool_expr -> [not], bool_expr

bool_expr -> bool_expr, [and] , bool_expr

bool_expr-> bool_expr, [or] , bool_expr

bool_expr -> number_expr, ['=='], number_expr

bool_expr -> number_expr, ['!='], number_expr

bool_expr -> number_expr, ['>'], number_expr

bool_expr -> number_expr, ['<'], number_expr

bool_expr -> number_expr, ['>='], number_expr

bool_expr -> number_expr, ['<='], number_expr

bool_expr -> string_expr, ['=='], string_expr

bool_expr -> string_expr, ['!='], string_expr


```
bool_expr -> bool_expr, ['=='], bool_expr
bool_expr -> bool_expr, ['!='], bool_expr
bool_expr -> bool_expr2
bool_expr -> var_name
bool_expr -> ['true']
bool_expr -> ['false']
bool_expr2 -> ['('], bool_expr, [')']
```

/* String Expression -> checks for string type.*/

```
string_expr -> string
string_expr -> var_name
string_expr -> [str],['('], number_expr, [')']
string_expr -> [str],['('], bool_expr, [')']
string_expr -> string_expr, ['+'], string_expr
```

```
var_name -> atom.
number --> number
string --> string
```

Parsing Technique:

We will be using python to parse our program. Using ply library we will tokenize the input. Our grammar will be written in DCG. We will use pylog library to run prolog code. We will use DCG to generate our abstract parse tree and evaluate it using prolog. The final output will be displayed by python. Since we are using python our program will run on python's runtime environment. The tokenized result will be stored in a list and passed to DCG.

Future Work:

1. Adding support for functions
2. Including switch conditional statement.