Route-Specific Transfer Obstructions and Certificate Gates in P vs NP Exploration

Abducer Interpretive Timeline Paper Workflow

July 21, 2026

Abstract

The report-derived paper should claim a scoped complexity-theoretic bridge or no-go result, not a solution of P vs NP.

Paper Build Manifest

This paper is generated from an interpretation pipeline rather than a flat timeline dump. The build consumes a report interpretation, argument blueprint, synthesized paper sections, formal derivation artifact, generated diagram, and translated report appendix. The main body is bounded by the blueprint; broad report coverage is preserved in appendices and artifacts.

Paper mode. obstruction_note

Main thesis. The timeline supports a bounded complexity-theory paper centered on target-preserving transfer control: state the source carrier and target class, derive the exact exponent or certificate gate, expose the uniformity/advice/barrier disqualifiers, and identify which route families are ruled out, repaired, or left as live proof obligations.

Non-claims.

- The paper does not prove P $\neq$ NP.
- The paper does not prove SAT is outside P/poly.
- A route-level transfer obstruction is not a target separation theorem.
- Artifact evidence documents the run state; external novelty still requires a prior-art boundary.

1 Problem Pressure And Paper Claim

This paper draft is organized around a bounded claim: The report-derived paper should claim a scoped complexity-theoretic bridge or no-go result, not a solution of P vs NP. The report evidence is treated as a source of mathematical objects, route pressure, and validation obligations, not as a proof by accumulation.

- P vs NP: Decide whether every efficiently verifiable decision problem is also efficiently solvable, equivalently whether SAT has a polynomial-time algorithm.

- cycle-0124: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0121: Hardness-Magnification Bridge Realization: L121 least-closed support audit: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: L121 least-closed support audit: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0073: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0071: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

2 Literature And Novelty Boundary

The related-work function is to separate target formulation, standard machinery, closest comparators, and novelty boundaries.

- 1971-1972: Verification becomes a universal computational phenomenon: Cook and Karp show that many apparently different problems are interreducible through polynomial reductions and share SAT as a complete core. What remained open: Completeness explains universality of difficulty but not the source of lower bounds against all polynomial-time algorithms or circuits.
- 1975: Proof techniques become objects of study: Relativization shows that any proof surviving arbitrary oracle substitution cannot settle the main question. What remained open: The barrier diagnoses broad method families but does not identify a successful nonrelativizing replacement.
- Late 1970s onward: Complexity becomes a landscape of representations: Algebraic, proof-complexity, descriptive, and structural viewpoints re-express computation through polynomials, proofs, reductions, and uniformity conditions. What remained open: Every translation risks losing target strength: a theorem in a restricted or algebraic model must still return to Boolean P vs NP or P/poly with controlled loss.
- 1990s: Lower-bound intuitions meet pseudorandomness: Natural proofs explain why many broad, efficiently checkable combinatorial properties are unlikely to prove strong unrestricted circuit lower bounds. What remained open: The field still needs useful lower-bound properties that are either not large, not constructive, not black-box, or otherwise outside the natural-proofs template.

- 2000s onward: Fine-grained and magnification thinking exposes exponent debt: Hardness transfers are judged by exact exponents, target-query counts, advice leakage, and whether a weak source lower bound really magnifies to the main target. What remained open: Most bridges lose too much exponent, import nonuniform advice, or prove a source lower bound that is already as hard as the desired conclusion.
- 2009 onward: Modern progress is real but carefully scoped: Algebrization and restricted-circuit lower bounds clarify both the reach and limits of current techniques. What remained open: The unrestricted P vs NP question still demands a target-preserving lower bound or impossibility theorem that escapes known barriers without losing the main quantifiers.
- ref.cook-1971: The Complexity of Theorem-Proving Procedures. Supports: Introduces NP-completeness through satisfiability and turns efficient verification into a universal problem.. Limitation: It defines the central complete problem and reduction method; it does not separate deterministic from nondeterministic polynomial time.
- ref.karp-1972: Reducibility Among Combinatorial Problems. Supports: Shows that many natural search and optimization problems share the same NP-complete core.. Limitation: NP-completeness transfers difficulty conditionally; it does not prove that any NP-complete problem lacks polynomial algorithms.

3 Route Narrowing And Scientific Learning

The route history is included only where it explains why the paper object became narrower and more testable.

- cycle-0002: Hardness-Magnification Bridge Realization: Cycle 2 turns the previous threshold collapse into an exact quantifier repair. The valid route lemma is: fixed k gives only a finite SAT exponent lower bound, while a common-epsilon lower bound for unbounded padded carriers H_k would imply NP not subset P/poly. The decisive falsifier is not folklore but the inequality c/k>=1+epsilon, plus the O(N) checker floor.
- cycle-0003: Hardness-Magnification Bridge Realization: Cycle 3 finds a valid single-carrier repair: growth padding N_m=(m+1)^{g(m+1)} converts an i.o. N^{1+epsilon} lower bound for H_g into exclusion of every SAT exponent c. This is route-level progress, not P vs NP; the hard obligation is now the sparse valid-length lower bound.
- cycle-0004: Hardness-Magnification Bridge Realization: Cycle 4 proves a valid projection-sandwich lemma and demagnifies the sparse-padding route: N^{1+eps} lower bounds for H_g equal m^{(1+eps)g} SAT lower bounds. The bridge is correct but not a weak-source path toward P vs NP.
- cycle-0006: Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit: Cycle 6 shows that moving from projection padding to a nonprojection MCSP carrier does not by itself create major magnification. The valid transfer is C(MCSP_{N^alpha},N)<=N^{c(1+alpha)+o(1)} under SAT in SIZE(n^c), so an N^{1+epsilon} source lower bound excludes only c<(1+epsilon)/(1+alpha). The input-reading floor alpha>=0 caps any fixed barely-superlinear bridge below all-exponent P/poly separation. The failure is a concrete threshold falsifier, not barrier folklore.
- cycle-0009: Hardness-Magnification Bridge Realization: subpolynomial-interface demagnification: Cycle 9 converts the cycle-8 repair into a route failure certificate. Subpolynomial SAT queries remove the c-dependent upper-bound term, but the same transfer read backward says

that proving the source N^{1+epsilon} lower bound in general SIZE already proves SAT_{<=L} has L^{omega(1)} circuits lower bounds. The remaining valid work is not carrier search inside this black-box same-model interface; it is either a restricted-model closure theorem or a non-blackbox carrier.

- cycle-0010: Hardness-Magnification Bridge Realization: Cycle 10 proves a valid restricted-model closure bridge and names the precise target-preservation failure. Subpolynomial queries plus max(a,q)<1+epsilon magnify a Gamma lower bound to SAT notin Gamma/poly for every fixed exponent. This is real route-level progress, but it is not NP notin P/poly: the missing object is a nonuniform P/poly-to-Gamma lift with subthreshold tax, and its absence is the decisive falsifier for advertising the bridge as a P vs NP route.
- cycle-0012: Hardness-Magnification Bridge Realization: Cycle 12 identifies a real surviving window: superlogarithmic subpolynomial target lengths, especially L=(log N)^d with d>1. In this window SAT circuits of size L^c amortize to N^{o(1)}, but SAT truth tables cost 2^L and no longer give the old subthreshold lookup falsifier. The bridge is valid only for nonblackbox compact-circuit consumers; it is not a P vs NP proof without the explicit carrier and lower bound.
- cycle-0013: Hardness-Magnification Bridge Realization: Polylog Nonblackbox Compact Consumer: Cycle 13 turns the superlogarithmic polylog window into an exact bridge: L=(log N)^d with d>1 makes SAT circuits of size L^c amortize to N^{o(1)}, while truth-table lookup costs 2^L=N^{omega(1)} and no longer supplies the old falsifier. The valid threshold is rho<1+epsilon for a target-clean nonblackbox compact consumer. The new hard obstruction is not folklore but the absence of an explicit carrier with no advice leakage and a non-natural N^{1+epsilon} general-circuit lower bound.

4 Formal Complexity Derivation

This section is generated from structured definitions, assumptions, propositions, calculations, and unresolved obligations. It states a local paper-level object and does not claim the global target theorem.

4.1 Definitions

H_N. A source carrier language, truth-table family, meta-complexity predicate, or proof-mediated object indexed by source length N.

$$H_N \subseteq \{0,1\}^N \quad \text{or} \quad H_N : \{0,1\}^N \to \{0,1\}$$

Valid when: The carrier is explicitly constructed or specified without nonuniform hard-row advice.

SAT_m. The target SAT language or SAT truth-table slice at input length m, used as the reference NP-complete target.

$$\mathrm{SAT}_m = \mathrm{SAT} \cap \{0,1\}^m$$

Valid when: The reduction or transfer states how source length N maps to target length m.

a,q,beta. The source lower-bound exponent, overhead exponent, and target-query-length exponent in a transfer inequality.

$$\mathrm{SIZE}(H_N) \le N^{q+\beta c+o(1)} \quad \text{from} \quad \mathrm{SAT} \in \mathrm{SIZE}(n^c)$$

Valid when: All padding, decoding, verifier, and advice costs are counted in the same circuit model.

4.2 Assumptions

- The source carrier H_N and target class are named before any transfer claim is made.
- The circuit model is fixed throughout the transfer, including uniformity and advice conventions.
- The transfer from SAT circuits to source-carrier circuits has an explicit exponent envelope q+beta*c+o(1).
- Barrier status is route-specific: naturalness, relativization, algebrization, and advice leakage are attached to the actual theorem shape.

4.3 Local Propositions

Bounded-window transfer obstruction. A barely-superlinear source lower bound excludes only the target exponents that fit below the transferred upper-bound envelope.

$$\mathrm{SIZE}(H_N) > N^a \ \wedge \ \mathrm{SAT} \in \mathrm{SIZE}(n^c) \Rightarrow \mathrm{SIZE}(H_N) \le N^{q+\beta c+o(1)} \quad \Longrightarrow \quad a > q + \beta c$$

Proof steps.

- Assume SAT has nonuniform circuits of size n^c in the stated model.
- Apply the route transfer to build source-carrier circuits of size N^{q+beta c+o(1)}.
- Contradict the source lower bound only for those c with a>q+beta c.
- If beta>0, a fixed a excludes at most a bounded exponent window.

Valid when: The source and target circuit models, length map, and overhead exponents are unchanged across the implication.

All-exponent lift gate. A route can support NP not subset P/poly only if it preserves the all-exponent quantifier or supplies a cofinal indexed family.

$$\forall c \ \exists N_0 \ \forall N \ge N_0 : \quad a_c > q_c + \beta_c c$$

Proof steps.

- P/poly exclusion requires ruling out every fixed polynomial exponent c for SAT or an NP-complete target.
- For each c, the source lower bound must outrun the transferred upper bound.
- If the same source theorem has beta>0 and fixed a, large c survives.

- Thus promotion needs beta=0 with positive margin or a cofinal parameter family with no advice leakage.

Valid when: The parameter family is uniform or advice-accounted and valid on target-relevant lengths.

Searchable certificate gate. A meta-complexity or proof-object bridge is useful only when certificates are frequent, searchable, sound, and advice-free without becoming a large constructive natural property.

$$\exists u, \pi \ \big(|\pi| = O(m) \wedge V(u, \pi) = 1\big) \Rightarrow CC(f_u) > 2^{\epsilon m}$$

Proof steps.

- State the verifier, decoder, certificate length, and search schedule.
- Prove that accepted pairs exist in every required gap interval.
- Prove soundness from certificate acceptance to the claimed circuit lower bound.
- Audit whether the accepted set is large and constructive, or whether row selection leaks advice.

Valid when: The verifier and search live inside the intended target class and do not choose hard rows nonuniformly.

4.4 Worked Calculation Interface

Direct-cluster soundness falsifier. Odd-charge Tseitin-style parity ambiguity is a finite falsifier for local consistency claims that do not bind the target row semantically.

$$\text{LocalConsistent}(C) \not\Rightarrow \text{DirectClusterSound}(C, k)$$

Valid when: The tested proof system exposes only local projections or bounded-width proof views and lacks a global parity-binding axiom.

4.5 Unresolved Obligations

- Instantiate one named proof system or meta-complexity carrier and compute q, beta, advice cost, and certificate-search exponent.
- Prove the direct-cluster or parity-binding lemma, or exhibit the odd-charge Tseitin counterexample for that named system.
- Run a prior-art boundary check against hardness magnification, MCSP/MKtP, natural-proofs, and proof-complexity transfer literature.
- State whether the surviving result is a positive bridge theorem, a scoped no-go theorem, or a demoted route diagnostic.

4.6 Non-Claims

- The paper does not prove P != NP.
- The paper does not prove SAT is outside P/poly.

- A route-level transfer obstruction is not a target separation theorem.
- Artifact evidence documents the run state; external novelty still requires a prior-art boundary.

5 Worked Calculation And Falsifier Tests

The worked-calculation section records what is computable now and what exact transfer, threshold, falsifier, or remainder test would decide promotion or demotion.

- cycle-0004: threshold_demagnification

$$C_{N_m}(H_g) > N_m^{1+\epsilon} \Rightarrow C_m(SAT) > (m+1)^{(1+\epsilon)g(m+1)} - O(m)$$

- cycle-0005: Hardness-Magnification Bridge Realization: Cycle 5 converts the padding quarantine into a general projection-carrier dichotomy. The valid bridge says N^{1+epsilon} lower bounds transfer through ell(N) only when ell(N)^c is below the threshold. Positive polynomial embedding length gives only a bounded exponent window; subpolynomial embedding length gives all exponents but turns the source lower bound into ell(N)^{omega(1)}. Thus pure projection magnification fails as a weak-source path, with an explicit falsifier rather than a slogan.
- cycle-0005: projection_upper_bound

$$\mathrm{SIZE}(H_N) \le AN + B\,\mathrm{SIZE}(\mathrm{SAT}_{\ell(N)}) + O(N \log N).$$

- cycle-0005: exponent_transfer

$$\mathrm{SIZE}(\mathrm{SAT}_m) \le m^c \ \forall m \quad \Rightarrow \quad \mathrm{SIZE}(H_N) \le O(N \log N) + \ell(N)^c.$$

- cycle-0005: finite_window

$$\ell(N) = N^{\alpha + o(1)} \ \Rightarrow\ \mathrm{SIZE}(H_N) \le N^{\alpha c + o(1)} + O(N \log N).$$

- cycle-0005: contradiction_condition

$$KN^{1+\varepsilon} < \mathrm{SIZE}(H_N) \text{ i.o. } \wedge\ \alpha c < 1 + \varepsilon\ \Rightarrow\ \mathrm{SAT} \notin \mathrm{SIZE}(n^c).$$

- cycle-0005: all_exponents_cost

$$(\forall c\ \ell(N)^c = o(N^{1+\varepsilon})) \iff \ell(N) = N^{o(1)}, \quad \ell(N) = N^{o(1)} \Rightarrow N^{1+\varepsilon} = \ell(N)^{\omega(1)}.$$

- cycle-0006: verifier_time

$$T_\alpha(N) = O(N\, s(N)\, \mathrm{polylog}\, N) = N^{1+\alpha+o(1)}$$

- cycle-0006: induced_upper_bound

$$\mathrm{SAT} \in \mathrm{SIZE}(m^c) \Rightarrow C(K_{\alpha,N}) \le N^{c(1+\alpha)+o(1)}$$

- cycle-0006: transfer_threshold

$$C(K_{\alpha,N}) > N^{1+\epsilon} \Rightarrow \mathrm{SAT} \notin \mathrm{SIZE}(n^c) \quad \text{for } c < \frac{1+\epsilon}{1+\alpha}$$




Figure 1: Organizing diagram generated from the paper blueprint. It separates target commitments, the active mathematical object, the local criterion, the worked calculation, the smallest honest claim, and the validation handoff. Dashed feedback marks demotion or backtracking if the transfer obligation fails.

6 Mechanism And Transfer Diagram

The mechanism section uses the generated diagram as an explanatory map from target commitments to local criterion and validation handoff.

- cycle-0001: Hardness-Magnification Bridge Realization: The exact quantitative transfer is C(Pad_k(SAT)_N)< hence the barely-superlinear lower bound magnifies only up to target exponent k(1+epsilon). The valid bridge is useful as an exponent-calibrated route lemma, while the fixed-k P/poly claim is blocked by a concrete threshold falsifier rather than by vague folklore.
- cycle-0001: Hardness-Magnification Bridge Realization pressure: The bridge does not reach NP notin P/poly unless one proves a cofinal family of padded lower bounds or finds a non-artificial carrier whose interface compresses every polynomial target exponent below N^{1+epsilon}.
- cycle-0001: E3_exponent_transfer

$$C(Pad_k(SAT)_N) > N^{1+\epsilon} \Longrightarrow SAT \notin SIZE(n^c) \quad \text{for every } c < k(1+\epsilon).$$

- cycle-0001: cycle-0001 falsifier: falsifier: threshold collapse occurs when the target exponent c is at least k(1+epsilon), because the induced source circuit may exceed N^{1+epsilon}.
- cycle-0001: cycle-0001 falsifier: falsifier: model mismatch occurs if the source lower bound is for AC0, formulas, or uniform circuits while the composed circuit is unrestricted nonuniform P/poly.
- cycle-0001: cycle-0001 falsifier: falsifier: nonuniform leakage occurs if the padding parser or length selector uses advice not counted in the source circuit size.

7 Claim Boundary And Validation Handoff

The discussion states what has been learned, what is not claimed, and what validation handoff remains before any stronger result could be asserted.

Non-claims

- The paper does not prove P != NP.

- The paper does not prove SAT is outside P/poly.
- A route-level transfer obstruction is not a target separation theorem.
- Artifact evidence documents the run state; external novelty still requires a prior-art boundary.

Validation and Future Work

- cycle-0001: Hardness-Magnification Bridge Realization pressure: The bridge does not reach NP notin P/poly unless one proves a cofinal family of padded lower bounds or finds a non-artificial carrier whose interface compresses every polynomial target exponent below N^{1+epsilon}.
- cycle-0001: cycle-0001 falsifier: falsifier: threshold collapse occurs when the target exponent c is at least k(1+epsilon), because the induced source circuit may exceed N^{1+epsilon}.
- cycle-0001: cycle-0001 falsifier: falsifier: model mismatch occurs if the source lower bound is for AC0, formulas, or uniform circuits while the composed circuit is unrestricted nonuniform P/poly.
- cycle-0001: cycle-0001 falsifier: falsifier: nonuniform leakage occurs if the padding parser or length selector uses advice not counted in the source circuit size.
- cycle-0001: cycle-0001 falsifier: falsifier: an infinitely-often source lower bound is not valid for excluding eventual SIZE(n^c) target circuits without matching quantifiers.
- cycle-0001: cycle-0001 falsifier: falsifier: a natural-proofs-style source argument for unrestricted circuits must explain why it is non-natural or why pseudorandom-function assumptions are avoided.
- cycle-0002: Hardness-Magnification Bridge Realization pressure: No known source theorem proves C_{H_k}(N)>N^{1+epsilon} for unbounded k with a common epsilon against general nonuniform circuits.
- cycle-0002: cycle-0002 falsifier: falsifier: fixed k only yields a finite exponent ceiling c<k(1+epsilon), so arbitrary polynomial advice sizes survive.

Timeline Proof Objects

The following proof objects are copied from the proof-delivery queue into the timeline artifact so that the paper workflow tracks not only cycle evidence, but also the concrete proof packets needed before promotion.

Prove the $TransparentRowSupport_N$ theorem pair and stop selector-case accumulation

Timeline proof-object id. `pvsnp.paper.bit-explicit-parser-formulaeval-boundary`; rank 1; status `cycle_0107_consolidation_next_move`.

Theorem goal. $TransparentRowSupport_N$ theorem pair: if a Psys_{sym} FormulaEval mechanism has visible selector code, advice-free enumeration or full-scan charge, influence closure, same-theory occurrence expansion, and no hidden support advice, then $\Gamma_{trans}(pi) = \Gamma_{bEF}(pi) + U_N + X_N$ gives the parser-to-circuit falsifier N^{rho+o(1)}+Gamma_trans(pi)<N^{1+epsilon-o(1)} for

LB_N(1+epsilon). If any visibility, extensionality, or influence-closure condition fails, construct the private-row/unread-enable-bit countermodel to surface occurrence completion.

Source object. Cycles 103-107 FormulaEval selector packets over $H_N^{\mathrm{SAT}}(x) = xor_{j \le M_N}$ SAT(G_N(x,j)), with $M_N = N^{q+o(1)}$, generator overhead $N^{\rho+o(1)}$, polylog formula length, bit-explicit Psys_{bEF} parser costs, and selector cases including interval unions, full scans, ROBDD, guarded dDNNF, projected dDNNF, and influence-complete extension rules.

Target object. A paper-core theorem/countermodel pair replacing the selector zoo: one transparent-support theorem, one hidden-support countermodel theorem, examples as corollaries, and $RealSATInfluenceReal$ as an open problem.

Required proof outputs.

- formal definition of $TransparentRowSupport_N$ with visible selector code, row enumeration/full scan, influence closure, row expansion, same-theory parser, and no-hidden-advice clauses
- positive theorem deriving $\Gamma_{trans}(pi) = \Gamma_{bEF}(pi)+U_N+X_N$ and the subthreshold parser-to-circuit falsifier
- countermodel theorem using a private row or unread enable bit when support visibility, selector extensionality, or influence closure fails
- corollary table showing interval-union, scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete extension rules as examples, not new main routes
- explicit open-problem statement for $RealSATInfluenceRealizer_N$ and AC0 output-sensitive enumeration

Success criteria.

- $TransparentRowSupport_N$ is formal enough that an independent reader can decide whether a FormulaEval rule satisfies it.
- Gamma_trans(pi) is derived rather than asserted, and the falsifier inequality states ρ, q, ϵ, U_N, X_N, η, τ, E_N, and all o(1) regimes.
- The private-row/unread-enable-bit countermodel is stated as a theorem with hypotheses, not as a metaphor.
- Selector cases are reorganized into examples/corollaries; no new selector family is promoted as a separate main contribution.

Demotion boundary.

- Demote if the work adds another selector class without changing the $TransparentRowSupport_N$ definition, theorem, or countermodel.
- Demote if Gamma_trans(pi), K_idx(pi), U_N, X_N, or the transcript upper bound is named without a derivation.
- Demote if semantic FormulaEval is described as generic power rather than handled by $RealSATInfluenceReali$ or the private-row countermodel.

- Demote if the branch broadens into MCSP/MKtP, natural-proofs folklore, or generic barriers before the theorem pair is written.

Write the L120.1 least-closed support proof-audit packet

Timeline proof-object id. `pvsnp.paper.l1201-least-closed-support-proof-audit`; rank 2; status `cycle_0120_next_missing_proof_audit`.

Theorem goal. $LeastClosedTransparentSupport_N$ / L120.1: for a $\mathrm{Psys}^{dag}_{sym}$ proof pi whose FormulaEval lines expose parent pointers and support certificates, the least prefix-closed reachable cone K_dag(pi) from the final LB_N line is the minimal charged object needed for the parser-to-circuit falsifier N^{rho+o(1)}+Gamma_dag(pi)+O(E_pi N)<N^{1+epsilon-o(1)}.

Source object. Cycle 120 theorem claims over $H^{\mathrm{SAT}}_N(x) = xor_{j \le M_N}$ SAT(G_N(x,j)), $\mathrm{Psys}^{dag}_{sym}$ FormulaEval lines, dependency edges from later symbolic uses to earlier row supports, and the cost ledger Gamma_dag(pi)=Gamma_bEF(pi)+U(K_dag(pi))+X(K_dag(pi)).

Target object. A self-contained proof-audit packet that an independent reader can run mentally or mechanically: input pi,N; compute K_dag(pi); either certify prefix-closed support and Γ_{dag}, or return the first hidden reachable row with its private-row/unread-enable-bit countermodel.

Required proof outputs.

- formal definition of the dependency graph, reachable final cone, and least fixed point K_dag(pi)
- pseudocode for the verifier-visible closure computation with termination and monotonicity proof
- proof of Gamma_dag(pi)=Gamma_bEF(pi)+U(K_dag(pi))+X(K_dag(pi)) by prefix line induction
- same-model upper-bound falsifier inequality including ρ, ϵ, q, E_{pi}, and all o(1) regimes
- worked projected-dDNNF FormulaEval example showing how K_{dag}, U, X, and Γ_{dag} are computed

Success criteria.

- The fixed-point algorithm for K_dag(pi) is explicit enough to implement or audit line by line.
- Γ_{dag} is derived from the closure invariant, not asserted by analogy with Γ_{trans}.
- The projected-dDNNF example and unread-enable-bit counterexample both exercise the theorem boundary.
- The result states that it is a scoped parser/falsifier theorem and not evidence for P $\neq$ NP.

Demotion boundary.

- Demote if K_dag(pi) is described informally without a computable closure algorithm.
- Demote if the proof does not distinguish reachable support from the full selector zoo.
- Demote if the examples do not compute charges or do not expose a first hidden reachable row.
- Demote if the theorem silently assumes full semantic SAT influence instead of charging it.

Resolve or quarantine $RealSATInfluenceRealizer_N$ for one concrete semantic FormulaEval rule

Timeline proof-object id. `pvsnp.paper.realsat-influence-realizer-boundary`; rank 3; status `named_semantic_gap_needs_rule_level_resolution`.

Theorem goal. $RealSATInfluenceRealizer_N$ boundary theorem: full semantic FormulaEval can be folded into the transparent support theorem only when proof syntax and N uniformly determine an influence-closed row set R_A, same-theory row expansions, and a charged overhead R_N before the semantic rule is used.

Source object. Semantic FormulaEval-SAT rules over H_N^{SAT} generated rows where real SAT semantics, formula equality, Tseitin extensions, or self-reduction may make a proof line depend on rows not visible in a syntactic $TransparentRowSupport_N$ certificate.

Target object. A yes/no boundary for one named semantic rule: either a valid $RealSATInfluenceRealizer_N$ certificate with $\Gamma_{real} = \Gamma_{bEF} + U + X + R_N$, or a finite countermodel showing why that semantic rule remains quarantined.

Required proof outputs.

- selected semantic FormulaEval rule with exact bit fields, formula objects, and allowed SAT/equality facts
- definition of semantic influence Infl(A), row set R_A, realizer output format, and overhead R_N
- advice-free realizer proof, or a private-row/no-realizer theorem for the selected rule
- same-theory expansion certificates or a proof that such certificates cannot be uniformly extracted
- updated non-claims explaining that unresolved semantic FormulaEval is a model boundary, not a P vs NP barrier slogan

Success criteria.

- The selected semantic rule is concrete enough that the realizer or countermodel is independently checkable.
- All influence rows are uniformly listed and charged, or the exact unchargeable semantic step is named.
- The output eliminates vague language about semantic FormulaEval and replaces it with a rule-level theorem or no-go.

Demotion boundary.

- Demote if $RealSATInfluenceRealizer_N$ is only restated without choosing a semantic rule.
- Demote if the row set uses SAT-truth advice or hidden nonuniform row selection.
- Demote if the claimed realizer omits R_N from the Γ ledger.
- Demote if the negative result does not identify the first semantic inference that cannot be charged.

Package the cycle-120 theorem/countermodel pair as a paper-ready module

Timeline proof-object id. `pvsnp.paper.l120-theorem-countermodel-package`; rank 4; status `paper_module_missing_after_cycle_0120`.

Theorem goal. Paper module: a scoped parser/falsifier contribution for FormulaEval in beta-zero parity magnification, showing exactly when transparent FormulaEval yields a same-model upper-bound falsifier and exactly where hidden semantic influence escapes the controlled interface.

Source object. Cycles 116-120, especially L120.1 $LeastClosedTransparentSupport_N$, L120.2 $UnreachableSupportDeletion_N$, L120.3 $FirstHiddenReachableUse_N$, and the branch outputs that state Γ_{dag}, hidden-row falsifiers, and $q < \epsilon / q = \epsilon / q > \epsilon$ support-density cases.

Target object. A paper-ready theorem/countermodel section with definitions, theorem statements, proof sketches, examples, non-claims, and a handoff to the broader parity magnification/full-row barrier draft.

Required proof outputs.

- definition ledger for H_N^{SAT}, $\mathrm{Psys}_{sym}^{dag}$, K_dag(pi), Γ_{bEF}, U(K), X(K), E_{pi}, and LB_N(1+epsilon)
- theorem statement and proof sketch for the least-closed transparent support upper-bound falsifier
- countermodel theorem for first hidden reachable support using private rows or unread enable bits
- $RealSATInfluenceRealizer_N$ open-boundary box with exact input, output, overhead, and non-claims
- q-trichotomy support-density corollary for $q < \epsilon$, $q = \epsilon$, and $q > \epsilon$

Success criteria.

- The module is understandable as a standalone paper section.
- The positive theorem, negative countermodel, and semantic open boundary are separated cleanly.
- Examples are corollaries/examples only; no new selector zoo is created.
- The paper handoff preserves the scoped claim and does not oversell P vs NP progress.

Demotion boundary.

- Demote if the package is a report summary rather than theorem/countermodel text.
- Demote if it depends on marathon-specific workflow language.
- Demote if it blurs transparent extensional FormulaEval with full semantic SAT FormulaEval.
- Demote if it omits the q-trichotomy or the non-claims.

Close the L120 inference-quality and marker gaps before promotion

Timeline proof-object id. `pvsnp.paper.l120-inference-quality-gate-closure`; rank 5; status `promotion_gate_missing_after_cycle_0120`.

Theorem goal. Validation theorem for promotion readiness: every L120 claim has explicit source object, target object, controlled interface, target-preserving condition, reduction direction, quantifiers, advice discipline, barrier scope, and proof-complexity transfer status.

Source object. The live L120 claims, the 93 active inference-quality packets, and the discovery report warning that not all source/target/same-theory/validity markers are globally present.

Target object. A repaired inference-quality packet and gate report that says exactly which L120 claims are promotable, which are conditional, and which remain blocked at $RealSATInfluenceRealizer_N$.

Required proof outputs.

- new pvsnp_inference_quality packet for L120.1 and the L120 theorem/countermodel package
- reviewer findings from reduction consistency, quantifier uniformity, barrier specificity, proof-complexity transfer, and meta-complexity carrier checks
- marker-gap repair table for source object, target object, controlled interface, target-preserving condition, and validity regimes
- promotion verdict separating proved scoped theorem, conditional theorem, open boundary, and non-claims
- validator output from validate_pvsnp_inference_quality.py and validate_pvsnp_proof_delivery_queue.py

Success criteria.

- The L120 theorem package has a live IQ packet that passes validation.
- No source/target/model/validity marker is implicit.
- Reviewer objections are either discharged, converted to named obligations, or marked as demotion blockers.
- The promotion verdict is conservative and explicitly says what is not proved.

Demotion boundary.

- Demote if the IQ packet claims P vs NP progress rather than a scoped parser/falsifier result.
- Demote if source and target models are not the same nonuniform SIZE model.
- Demote if $RealSATInfluenceRealizer_N$ is treated as solved without a rule-level proof.
- Demote if validation fails and the failure is not converted into a concrete repair item.

A Appendix Evidence Map

The appendix preserves interpreted report evidence without letting chronology control the main paper argument.

- cycle-0124: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification

collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

- cycle-0121: Hardness-Magnification Bridge Realization: L121 least-closed support audit: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: L121 least-closed support audit: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0073: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0071: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0065: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0008: Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0007: Hardness-Magnification Bridge Realization: black-box substitution cap: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: black-box substitution cap: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0006: Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0002: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification

collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

- cycle-0001: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0136: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0134: Hardness-Magnification Bridge Realization: A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses. Boundary: This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.
- cycle-0154: Hardness-Magnification Bridge Realization: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted TransparentRowSupport_N rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Gamma line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.
- cycle-0154: carrier

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d.$$

- cycle-0154: qrep_ledger

$$\Gamma_{Qrep}(\pi) = \Gamma_{bEF}(\pi) + U(K_{Qrep}) + X(K_{Qrep}) + \sum_{e \in Dict(\pi)} (|\sigma_e| + |row(e)|)\, N^{o(1)}.$$

- cycle-0154: parser_upper_bound

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{Qrep}(\pi) + O(E_\pi N).$$

- cycle-0154: lb_falsifier_window

$$N^{\rho+o(1)} + \Gamma_{Qrep}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon).$$

- cycle-0154: support_density_corollary

$$LB_N(1+\epsilon) \wedge \rho < 1+\epsilon \Rightarrow |K_{idx}(\pi)| \ge N^{\epsilon-o(1)}, \quad |K_{idx}|/M_N \ge N^{\epsilon-q-o(1)}.$$

- cycle-0154: cycle-0154 falsifier: First late Qrep merge: representative used before its same-theory certificate is charged, producing a private-row falsifier.

- cycle-0154: cycle-0154 falsifier: Rank cycle or representative rebinding: replay is not well-founded, so Gamma reduction is invalid.
- cycle-0154: cycle-0154 falsifier: Advice-chosen dictionary: K_Qrep is not determined by N and pi, causing nonuniform leakage.
- cycle-0154: cycle-0154 falsifier: Hidden semantic pruning: the proof uses real SAT structure without listing influencing rows, blocked at RealSATInfluenceRealizer_N^{arb}.
- cycle-0154: cycle-0154 falsifier: Positive beta black-box substitution remains a separate threshold-collapse falsifier: q+beta c can exceed 1+epsilon before all SAT exponents are excluded.
- cycle-0154: cycle-0154: Hardness-Magnification Bridge Realization: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted TransparentRowSupport_N rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Gamma line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress. Next: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Gamma_Qrep in both cases and export the rejected line as the private-row falsifier pivot.
- cycle-0153: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit: Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped TransparentRowSupport_N rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P != NP progress.
- cycle-0153: Qrep ledger

$$Gamma_Q rep(pi) = Gamma_b EF(pi) + U_N(pi) + X_N(pi) + D_Q(pi)$$

- cycle-0153: Dictionary charge

$$D_Q(pi) = sum_{ein Dict_Q(pi)}(|desc(e)| + |cert(e)| + sum_{ain dep(e)} row_c ost(a))$$

- cycle-0153: Parser-to-circuit upper bound

$$C_N(H_N^S AT) \leq N^{rho+o(1)} + Gamma_Q rep(pi) + O(E_p iN)$$

- cycle-0153: Subthreshold falsifier inequality

$$N^{rho+o(1)} + Gamma_Q rep(pi) + O(E_p iN) < N^{1+epsilon-o(1)} => notLB_N(1+epsilon)$$

- cycle-0153: Strict-prefix condition

$$foralle, cert_l ine(e) < first_u se_l ine(e) and rank(dep(e)) < rank(e)$$

- cycle-0153: cycle-0153 falsifier: first representative use before certificate charge is a temporal private-row falsifier

- cycle-0153: cycle-0153 falsifier: representative rebinding after prior use destroys prefix stability and invalidates Gamma_Qrep
- cycle-0153: cycle-0153 falsifier: cyclic or nondecreasing-rank dictionary dependencies prevent a finite valid verifier
- cycle-0153: cycle-0153 falsifier: advice-chosen quotient representatives create nonuniform leakage outside TransparentRowSupport_N
- cycle-0153: cycle-0153 falsifier: hidden semantic SAT-pruning remains quarantined unless RealSATInfluenceRealizer_N^{arb} lists and charges the influence rows
- cycle-0153: cycle-0153 falsifier: positive target-query exponent beta would reintroduce the black-box transfer cap q+beta c+o(1) and block all-exponent magnification
- cycle-0153: cycle-0153 falsifier: subthreshold Gamma_Qrep(pi)+O(E_pi N) is an upper-bound falsifier for any claimed LB_N(1+epsilon) proof transcript
- cycle-0153: cycle-0153: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit: Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped TransparentRowSupport_N rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P != NP progress. Next: Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Gamma_bEF, U_N, X_N, D_Q, E_pi, and the q/epsilon support-density consequence line by line.
- cycle-0152: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure: Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P != NP result.
- cycle-0152: carrier

$$H_N^{SAT}(x) = xor_{j=1}^{M_N} SAT(G_N(x,j)), M_N = N^{q+o(1)}$$

A Full Timeline Report Translation: Orientation

This appendix is intentionally expansive. The main paper body compresses the argument into a coherent scientific contribution candidate; this appendix preserves the translated report material that supports that compression: current summary, problem and literature context, accumulated story, and the full timeline evidence window. It is included so the paper draft does not hide the reasoning material behind artifact references.

Tab-to-section contract. The standalone report translation artifact maps every visible report tab to one appendix section in the same order as the HTML report. The complete standalone LaTeX report is recorded at `agentic/reports/timeline_latex_sections/latest_report.tex`.

- Summary → Summary
- Complexity Strategy → Complexity Strategy
- Timeline From cycle window → Content-Specific Full Timeline
- Ranked Analyses → Current Ranked Next-Analysis Queue
- Qualitative Graph → Qualitative Mechanistic Graph
- Gedanken Experiments → Gedanken Experiments
- PMP Probes → Parsimonious Probe Control
- Contributions → Scientific Contribution Monitor
- Problem & Literature → Target Problem And Literature Evolution
- Macro Strategies → Macro Strategies
- Strategy Judge → Strategy Progression Judge
- Proof Strategy Story → Accumulated Proof Strategy Story

B Summary

Current mathematical story

current_obstruction: The derivation does not cover arbitrary semantic SAT branch pruning or FormulaEval rules whose influencing rows are not determined by proof syntax before use; this is exactly $RealSATInfluenceRealizer_N^{arb}$.; headline: The active discovery route is now concentrated on target-preserving complexity-theoretic bridges: turning weak lower-bound, meta-complexity, proof-complexity, or derandomization interfaces into explicit threshold transfers without importing nonuniform leakage or barrier-evading slogans.; latest_learning: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.; next_experiment: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.; recent_storyline: branch_title: Hardness-Magnification Bridge

Realization; cycle_id: cycle-0150; learning: Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.; branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0151; learning: Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined.; next_experiment: Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.; branch_title: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure; cycle_id: cycle-0152; learning: Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result.; next_experiment: Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.; branch_title: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit; cycle_id: cycle-0153; learning: Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_N$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress.; next_experiment: Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.; branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0154; learning: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.; next_experiment: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

What actually changed

- The marathon created durable branch-local mathematical memory.
- Each cycle produced theorem-shaped branch outputs with equations, assumptions, falsifiers, and

next experiments.

- Skill dispatch is now explicit and validated rather than implicit in a workflow name.
- Completed subgoal enablement is now explicit: completed or near-completed subgoals are interpreted by the gate they open for the larger target, not by completion alone.
- Literature-gap preinvestment is now explicit: broad branch exploration needs a validated avenue warrant with closest-known-result accounting, novelty boundary, field impact, unification power, and route-decision power.
- Field relevance and general impact are now explicit: local route work is support-only unless it names a target carrier, target gate, unification-power payoff, and demotion-ready impact test.
- Visual conceptualization is now controlled: metaphors must preserve named theorem properties, expose distortions, and generate an audited route consequence before affecting proof search.
- Research cycle count is 154; synthetic smoke/legacy packet count is 0.

How this adds to the global problem

This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

Payoff criteria

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

When to stop

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism

Do not stop prematurely if

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.

C Complexity Strategy

This top-level section states the active proof strategy before the report moves into the full timeline. For P vs NP, strategy is controlled by source carrier, target class, reduction or transfer map, exact exponent debt, uniformity/advice discipline, and known barrier status.

Current macro reading

Current macro strategy: compute the transfer exponents or turn the route into a no-go theorem.

Contribution pivot invariant. If the next work only restates hardness magnification, MCSP promise, or barrier folklore, the branch is looping. If it computes a concrete transfer parameter, proves a route-specific no-go, or certifies a searchable certificate carrier with no advice leakage, it is moving toward a real scientific contribution.

Next decisive test. Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

When to stop. Stop, backtrack, or quarantine when two sharpened attempts still yield only a bounded exponent window, advised hard strings, a natural/relativizing/algebrizing proof object, or a certificate-existence condition equivalent to the target lower bound.

Black-box transfer and exponent-window audit

Route family. Complexity lower-bound transfer

Macro thesis. Treat every proposed magnification route as an explicit transfer inequality from SAT $\in$ SIZE(n^c) or NP subset P/poly to a source-carrier upper bound.

Conceptual proof picture. For this complexity-theory target, read the physical picture as a proof-dynamics picture: the target circuit is a resource flowing through an interface. Positive query-length exponent β amplifies the target exponent c and prevents a barely-superlinear source lower bound from ruling out all polynomial-size SAT circuits.

Why this route matters now. The latest cycle isolated max{a,q+beta c} as the active obstruction, so the next work must compute a, q, and β rather than restate magnification.

What to compute next.

- For the selected carrier, compute source exponent a, interface overhead q, and target-query exponent β.
- Derive the induced source upper bound under SAT $\in$ SIZE(n^c).
- Promote only if $\beta = 0$, beta=o(1), or the use of the SAT circuit is genuinely nonblackbox.

Success condition.

- A formal transfer theorem states source object, target class, model, and exponent inequality.
- The theorem distinguishes bounded-exponent exclusion from NP $\not\subset$ P/poly.
- The branch yields a computable falsifier for black-box substitution routes.

Failure or pivot condition.

- Every tested carrier has positive β and only excludes c below a finite threshold.
- The interface size q already exceeds the barely-superlinear threshold.
- The route cannot name the model and quantifier pattern in one statement.

Active skills.

- pvsnp-symbolic-complexity-auditor
- pvsnp-qualitative-complexity-reasoner
- pvsnp-conceptual-pressure-localizer
- entailment-gap-auditor
- progression-payoff-judge

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0149; learning: Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.; next_experiment: Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0150; learning: Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted

duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0151; learning: Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined.; next_experiment: Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.

- branch_title: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure; cycle_id: cycle-0152; learning: Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result.; next_experiment: Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.

- branch_title: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit; cycle_id: cycle-0153; learning: Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_N$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress.; next_experiment: Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0154; learning: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.; next_experiment: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

Padding and projection demagnification as a no-go route

Route family. Projection carrier obstruction

Macro thesis. Use the padding/projection failures as theorem material: projection carriers either give only bounded exponent windows or move the real proof burden into sparse valid-length lower bounds.

Conceptual proof picture. The conceptual mechanism is proof-debt conservation. Padding changes the coordinate system, but projection back to SAT reveals that the supposedly weak source lower bound already encodes the hard target lower bound.

Why this route matters now. Cycles 1-5 repeatedly converted padding optimism into exact exponent inequalities and sparse-length obligations.

What to compute next.

- State the projection-carrier dichotomy as a standalone no-go theorem.
- Define the length map N(n), projection overhead, and target exponent window.
- List escape conditions: subpolynomial embedding, nonprojection carrier, or nonblackbox use.

Success condition.

- The no-go theorem has precise hypotheses and a proof skeleton.
- It explains why the route fails without claiming P vs NP.
- It identifies which nonprojection alternatives remain open.

Failure or pivot condition.

- The statement merely repeats padding folklore without a new quantified obstruction.
- The theorem accidentally rules out nonprojection or nonblackbox routes.
- The proof depends on a stronger source lower bound than advertised.

Active skills.

- pvsnp-symbolic-complexity-auditor
- pvsnp-impossibility-theorem-forger
- contradiction-route-auditor
- paper-contribution-readiness-judge
- scientific-contribution-detector

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0098; learning: Cycle 98 upgrades the prior packet from theorem slogan to dependency-checked inference structure: Γ_{bEF} is justified by separate EF-dependency, SATeq-link, bounded-SR, and sparse-row charges; Psys_{bEF} gives a valid restricted falsifier theorem; full Psys_{sym} is blocked exactly at $FE_{Extract,N}$, not at generic naturalness or relativization folklore.; next_experiment: Write the formal $FE_{Extract,N}$ proposition in two columns: left column row-expanded FormulaEval axiom schema with $N^{1+q+o(1)}$ charge, right column semantic-oracle version with the smallest private-row countermodel; verify which column matches each Psys_{sym} rule.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0123; learning: Cycle 123 closes a proof-audit gap rather than repeating the magnification slogan: K_{dag} is an implementable least fixed point, projected-dDNNF gives a concrete transparent positive case, and the unread-enable-bit/private-row construction gives a precise necessity falsifier. The valid result is a scoped parser/falsifier theorem for beta-zero parity magnification; full semantic FormulaEval is still blocked exactly at $RealSATInfluenceRealizer_N$.; next_experiment: Write the referee-checkable trace for the projected-dDNNF example: list gate fields, parent pointers, projection maps, RowSet certificates, K_0, K_1,... closure additions, U_N and X_N charges, then flip one unread enable bit to exhibit the first-hidden-row countermodel and verify the Γ_{dag} threshold numerically for qepsilon.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0136; learning: Cycle 136 turns counterfactual declared TSR from a boundary slogan into a bitfield-level closed-support theorem: K_CTSR(pi) is a finite fixed point, Γ_{CTSR} is derived by line induction, and first-hidden-child adaptive pruning is the exact falsifier for extensional safety. The valid contribution remains a scoped parser/falsifier theorem for beta-zero parity magnification certificates; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Select one concrete full semantic pruning rule beyond CTSR declarations, preferably adaptive Tseitin branch pruning with real SAT contradiction tests, and attempt either a charged $RealSATInfluenceRealizer_N^{arb}$ or a minimal first-unchargeable-row countermodel.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0145; learning: Cycle 145 upgrades ranked QCTSR from a line-induction slogan to a finite verifier/minimality packet. Quotient compression is valid only when proof-carrying same-theory certificates are ranked, dependency-closed, and charged before use. The exact obstruction is the first rejected quotient merge, which yields a private-row falsifier. This strengthens the paper parser/countermodel boundary without proving H_N lower bounds or P $\neq$ NP.; next_experiment: Instantiate the finite verifier on one toy QCTSR proof with two EqSAT-equivalent counterfactual TSR children: compute K_Q, ranks, B_Q, and Γ_{QCTSR}; then delete one certificate edge and explicitly write the two-world private-row falsifier.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0149; learning: Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.; next_experiment: Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0150; learning: Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the

line induction.

Meta-complexity carrier pressure

Route family. MCSP/MKtP/GapMCSP route analysis

Macro thesis. Use MCSP, MKtP, or GapMCSP only after the carrier's verifier overhead, density, naturalness, advice leakage, and target transfer are stated.

Conceptual proof picture. The meta-complexity carrier is a diagnostic medium: it can reveal whether a weak source lower bound really transfers, or whether constructivity, largeness, and nonuniform advice absorb the intended separation.

Why this route matters now. Cycles 1, 2, 4, 5, and 6 all point to MCSP/MKtP as the next plausible nonprojection test, but cycle 6 already exposed a fixed-threshold ceiling.

What to compute next.

- Instantiate one carrier with N, n, threshold s, verifier overhead, and circuit model.
- Check natural-proof largeness and constructivity conditions.
- Compute whether SAT $\in$ SIZE(n^c) yields carrier circuits below the claimed threshold.

Success condition.

- The carrier avoids pure projection demagnification.
- The transfer is target-preserving for NP $\not\subset$ P/poly, not only a proxy consequence.
- Barrier status is explicit and does not rely on hidden advice leakage.

Failure or pivot condition.

- The induced upper bound remains N^{q+beta c+o(1)} with positive β.
- The lower-bound property is natural without an escape certificate.
- The carrier proves only bounded-exponent or non-target consequences.

Active skills.

- pvsnp-conceptual-pressure-localizer
- pvsnp-symbolic-complexity-auditor
- pvsnp-qualitative-complexity-reasoner
- counterexample-hunter
- kb-concept-bridge-planner

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0149; learning: Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.; next_experiment: Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0150; learning: Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0151; learning: Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined.; next_experiment: Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.

- branch_title: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure; cycle_id: cycle-0152; learning: Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result.; next_experiment: Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.

- branch_title: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit; cycle_id: cycle-0153; learning: Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_N$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress.; next_experiment: Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon

support-density consequence line by line.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0154; learning: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.; next_experiment: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

Nonblackbox or subpolynomial-interface escape search

Route family. Escape-condition construction

Macro thesis. The search should now aim at the exact escape left open by the no-go evidence: a target-preserving carrier with subpolynomial queries or a genuinely nonblackbox use of the SAT circuit.

Conceptual proof picture. The route needs a new interaction pattern with the target circuit. If the circuit is only queried as a black box at polynomially growing target length, the beta-ceiling reappears; a real escape must change that interface.

Why this route matters now. Cycle 7 localized the remaining opening as $N^{o(1)}$ target queries, $sub - N^{1+\epsilon}$ interface size, and a valid lower-bound carrier.

What to compute next.

- Test a succinct local-consistency or proof-complexity carrier.
- Compute a, q, and β before making any magnification claim.
- Run the projection-demagnification falsifier and barrier audit immediately.

Success condition.

- A carrier is target-preserving and not a disguised projection route.
- The interface has $\beta = 0$ or o(1), or the construction is nonblackbox in a formally stated sense.
- The next theorem can be stated as either a positive transfer or a no-go lemma.

Failure or pivot condition.

- The carrier uses polynomial target queries after all.
- The proof obligation becomes as hard as the original P vs NP/P-poly target.
- The route cannot avoid naturalness, advice leakage, or algebrization pressure.

Active skills.

- pvsnp-symbolic-complexity-auditor
- pvsnp-impossibility-theorem-forger
- pvsnp-qualitative-complexity-reasoner
- kb-gap-abstraction-conjecturer
- abducer-refinement-route-ranker

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization: Polylog Nonblackbox Compact Consumer; cycle_id: cycle-0013; learning: Cycle 13 turns the superlogarithmic polylog window into an exact bridge: L=(log N)^d with $d > 1$ makes SAT circuits of size L^c amortize to $N^{o(1)}$, while truth-table lookup costs 2^L=N^{omega(1)} and no longer supplies the old falsifier. The valid threshold is $\rho < 1 + \epsilon$ for a target-clean nonblackbox compact consumer. The new hard obstruction is not folklore but the absence of an explicit carrier with no advice leakage and a nonnatural $N^{1+\epsilon}$ general-circuit lower bound.; next_experiment: Instantiate $PolyLogAudit_{N,d,V}$ with a universal-circuit verifier, compute the exact overhead exponent ρ and auxiliary advice length, and reject the instance immediately if H_N depends on a hidden SAT circuit or collapses to a black-box SAT query family.
- branch_title: Hardness-Magnification Bridge Realization: approximate relaxed bag separators; cycle_id: cycle-0031; learning: Cycle 31 converts relaxed bag separators into an approximate threshold lemma: E bad bags cost NE gates, so errors below N^ϵ are nonuniformly patchable. The valid source obligation is now an approximate distribution-local separator lower bound, not merely promise SAT hardness.; next_experiment: Try a collision-balanced generator and estimate whether majority/hash-based local predicates yield $s = N^{o(1)}$ with $E < N^\epsilon$; if yes, quarantine this carrier family.
- branch_title: Relativizing locality-extraction gate for generated-OR carriers; cycle_id: cycle-0048; learning: Cycle 48 makes the obstruction formal: separator-denominator hardness is only an upper-bound falsifier, not a valid lower-bound certificate for H_N. The surviving route is direct C(H_N) lower bounds or a nonrelativizing locality-extraction theorem with explicit threshold loss.; next_experiment: Try to formulate a real-SAT locality extractor using witness self-reducibility: from a small circuit for H_N, isolate a generated satisfiable query and build a one-sided predicate; audit algebrization and $N^{o(1)}$ loss.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0081; learning: Cycle 81 separates the scoped occurrence-local theorem from the full EF + SAT_U ambition. The valid contribution is now sharper: private row spoofing is a genuine falsifier for occurrence-local functional certificates, while full EF + SAT_U requires a nonrelativizing semantic-to-occurrence extraction theorem because real SAT_U axioms are not invariant under independent label flips.; next_experiment: Formalize the semantic-coupling-width thought experiment as a lemma: for paired formulas F and F OR z, show exactly which SAT_U implication lines break private-label invariance and whether their violations can be charged to complete forced rows below the N^ϵ patch threshold.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0094; learning: Cycle 94 closes a concrete support-transparency subcase: bit-explicit EF extension variables can

be parsed without support declarations, giving a valid transcript falsifier theorem. The full formula-semantic extraction fork is now sharper: the obstruction is not arbitrary EF extension variables but succinct FormulaEval-SAT comprehension, which defeats size-only occurrence parsing unless its row-index expansion is charged.; next_experiment: Formalize Psys_{sym} on finite length N: specify whether FormulaEval-SAT comprehension is a proof line, axiom schema, or extension rule; then prove either an expansion-charge parser with cost $N^{1+q+o(1)}$ or a minimal countermodel showing surface occurrence completion is unsound.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0107; learning: Cycle 107 adds a real validation upgrade: transparent FormulaEval selectors no longer require interval-union structure for a valid theorem, because full syntactic scanning gives a certified $B_{FE} = F_{FE}\ N^{1+q+o(1)}$ charge. This closes the $q < \epsilon$ falsifier for a broader selector fragment and isolates the only missing improvement as $AC0PrefixNonemptiness_N$ for output-sensitive enumeration. Full semantic FormulaEval remains quarantined by the private-row falsifier, not by generic barrier folklore.; next_experiment: Formalize $AC0PrefixNonemptiness_N$ as a finite lemma: for AC0 selectors on q log N row bits, test whether descriptor structure yields $N^{o(1)}$ prefix emptiness; if not, state the selector-scan theorem as final and add AC0 output-sensitive enumeration to open problems.

D Content-Specific Full Timeline

Visible timeline starts at cycle-0001, where the run shifted into content-specific mathematical work. Each cycle is rendered as a report card with learning, pressure, derivation, equations, falsifiers, and next analysis.

cycle-0001: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 900.005 seconds; 3 lemmas, 3 equations, 6 derivation steps, 5 falsifiers.

Learning. The exact quantitative transfer is C(Pad_k(SAT)_N)<=O(N+N^{c/k}); hence the barely-superlinear lower bound magnifies only up to target exponent k(1+epsilon). The valid bridge is useful as an exponent-calibrated route lemma, while the fixed-k P/poly claim is blocked by a concrete threshold falsifier rather than by vague folklore.

Pressure. The bridge does not reach NP notin P/poly unless one proves a cofinal family of padded lower bounds or finds a non-artificial carrier whose interface compresses every polynomial target exponent below $N^{1+\epsilon}$.

Derivation steps.

1. Fix $L = \mathrm{SAT}$, constants $k \geq 2$ and $\epsilon > 0$, and legal source length $N = n^k$.
2. Assume toward contradiction that SAT has $O(n^c) - size$ circuits for some c<k(1+epsilon).
3. On a padded input y of length N, check that the last N-n bits are zero using O(N) gates and feed the first n bits into the SAT circuit.
4. The composed circuit has size O(N+n^c)=O(N+N^{c/k}). Since $max(1, c/k) < 1 + \epsilon$, this is below $N^{1+\epsilon}$ for large N.

5. This contradicts the source lower bound for Pad_k(SAT), yielding SAT notin SIZE(n^c).

6. Auditing the P/poly target shows that fixed k leaves all exponents c>=k(1+epsilon) untouched.

Equation 1: $E1_{padding,length}$.

$$N = n^k, \qquad Pad_k(L)_N = x0^{N-n} : x \in L_n.$$

Valid when: Valid when the source lower-bound model is explicitly restricted to legal padded lengths $N = n^k$.

Equation 2: $E2_{composition,upper,bound}$.

$$C(Pad_k(L)_N) \leq O(N) + C(L_n) \leq O(N + N^{c/k}) \quad \text{if } C(L_n) \leq O(n^c).$$

Valid when: Applies after the padding checker and target circuit use the same nonuniform Boolean basis.

Equation 3: $E3_{exponent,transfer}$.

$$C(Pad_k(SAT)_N) > N^{1+\epsilon} \Longrightarrow SAT \notin SIZE(n^c) \quad \text{for every } c < k(1+\epsilon).$$

Valid when: Requires the target-preserving composition bound and a strict exponent gap absorbing constants asymptotically.

Next analysis. Instantiate the same exponent audit for a padded MKtP or GapMCSP carrier: name the verifier, compute Cook-Levin or direct-composition length blow-up, and test whether assuming SAT $\in$ SIZE(n^c) yields source circuits below $N^{1+\epsilon}$ without model mismatch or nonuniform leakage.

Falsifiers.

- falsifier: threshold collapse occurs when the target exponent c is at least k(1+epsilon), because the induced source circuit may exceed $N^{1+\epsilon}$.
- falsifier: model mismatch occurs if the source lower bound is for AC0, formulas, or uniform circuits while the composed circuit is unrestricted nonuniform P/poly.
- falsifier: nonuniform leakage occurs if the padding parser or length selector uses advice not counted in the source circuit size.
- falsifier: an infinitely-often source lower bound is not valid for excluding eventual SIZE(n^c) target circuits without matching quantifiers.
- falsifier: a natural-proofs-style source argument for unrestricted circuits must explain why it is non-natural or why pseudorandom-function assumptions are avoided.

cycle-0002: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 900.003 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 2 turns the previous threshold collapse into an exact quantifier repair. The valid route lemma is: fixed k gives only a finite SAT exponent lower bound, while a common-epsilon lower bound for unbounded padded carriers H_k would imply NP $\not\subset$ P/poly. The decisive falsifier is not folklore but the inequality $c/k \geq 1 + \epsilon$, plus the O(N) checker floor.

Pressure. No known source theorem proves $C_{H_k}(N) > N^{1+\epsilon}$ for unbounded k with a common ϵ against general nonuniform circuits.

Derivation steps.

1. Assume for contradiction that SAT has circuits of size O(n^c) for some fixed c.
2. Choose k from the source hypothesis with $c/k < 1 + \epsilon$.
3. Construct a circuit for H_k on length $N = n^k$ by checking the padding pattern in O(N) gates and running the SAT circuit on the first $n = N^{1/k}$ bits.
4. Obtain C_{H_k}(N)=O(N^{max{1,c/k}}).
5. Since $max1, c/k < 1 + \epsilon$, the upper bound is eventually below $N^{1+\epsilon}$.
6. Contradict the asserted source lower bound for H_k at that k.
7. Because c was arbitrary only under the forall c exists k source quantifier, derive SAT $\notin$ P/poly conditionally.

Equation 1: length_relation.

$$N = n^k, \quad R_k(x) = x10^{n^k - n - 1}$$

Valid when: Valid when k is fixed and padded lengths $N = n^k$ are the only target lengths considered.

Equation 2: upper_transfer.

$$C_{H_k}(N) \leq aN + b\, C_{SAT}(N^{1/k})$$

Valid when: Applies when the total padded language includes the O(N) off-image validity checker and constants are model-fixed.

Equation 3: exponent_transfer.

$$C_{SAT}(n) = O(n^c) \Rightarrow C_{H_k}(N) = O(N^{\max 1, c/k})$$

Valid when: Requires the padding reduction to preserve nonuniform length parameters and circuit-size accounting without extra advice leakage.

Equation 4: strict_margin.

$$\Delta = 1 + \epsilon - \max 1, c/k > 0 \Rightarrow C_{H_k}(N) = O(N^{1+\epsilon-\Delta}) < N^{1+\epsilon} \text{ eventually}$$

Valid when: Valid when the exponent margin is strict, so asymptotic constants are absorbed for large padded lengths.

Equation 5: uniform_k_consequence.

$$(\exists \epsilon > 0)(\forall c)(\exists k > c/(1+\epsilon))\ C_{H_k}(N) > N^{1+\epsilon} \Rightarrow NP \not\subseteq P/poly$$

Valid when: Valid only when the source lower bound is available for unbounded padding parameters, not one fixed k.

Next analysis. Test MCSP or proof-complexity carriers for producing the unbounded-k source family: formalize whether a weak lower bound for MCSP[2^{N^{1/k}}] transfers to $C_{H_k}(N) > N^{1+\epsilon}$ without becoming natural or losing the strict exponent margin.

Falsifiers.

- falsifier: fixed k only yields a finite exponent ceiling c<k(1+epsilon), so arbitrary polynomial advice sizes survive.
- falsifier: threshold $C_{H_k}(N) > N + N^{0.9}$ is absorbed by the O(N) padding checker and transfers no SAT exponent lower bound.
- falsifier: a lower bound for a compressed n-bit version of SAT merely restates the target and is not a valid source model.
- falsifier: if lower bounds hold for only finitely many k, every c above (1+epsilon) max k remains unaddressed.
- falsifier: a large constructive property proving the source lower bound against general circuits would meet the natural-proofs obstruction under standard PRF assumptions.

cycle-0003: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 900.006 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 3 finds a valid single-carrier repair: growth padding $N_m = (m+1)^{g(m+1)}$ converts an i.o. $N^{1+\epsilon}$ lower bound for H_g into exclusion of every SAT exponent c. This is route-level progress, not P vs NP; the hard obligation is now the sparse valid-length lower bound.

Pressure. The required source lower bound is a barely-superlinear lower bound for a sparse explicit NP carrier on valid lengths; proving it already encodes superpolynomial SAT lower bounds in the unpadded parameter.

Derivation steps.

1. Assume toward contradiction that SAT has P/poly circuits of size m^c for some fixed c.
2. Build the H_g circuit at valid length N_m by checking the delimiter/padding pattern in O(N_m) gates and feeding the prefix x to the SAT_m circuit.
3. Since $g(m) \to infty$, eventually $c/g(m+1) < 1 + \epsilon/2$, so the transferred circuit has size at most $N_m^{1+\epsilon}$.
4. This contradicts an infinitely-often valid-length lower bound $C(H_g, N_m) > N_m^{1+\epsilon}$; therefore no fixed c exists for SAT.

Equation 1: valid_lengths.

$$N_m = (m+1)^{g(m+1)}, \quad H_g \cap 0,1^{N_m} = x\#0^{N_m-m-1} : x \in SAT_m$$

Valid when: Valid when the delimiter format fixes m and g is computable within polynomial time in N_m.

Equation 2: upper_transfer.

$$C_{H_g}(N_m) \leq a\,(N_m + C_{SAT}(m)) \leq a\,(N_m + (m+1)^c) = a\,(N_m + N_m^{c/g(m+1)})$$

Valid when: Applies after assuming SAT has $m^c - size$ circuits and the parser uses only linear-size circuitry.

Equation 3: threshold_absorption.

$$g(m+1) > c/(1+\epsilon/2) \implies C_{H_g}(N_m) \leq N_m^{1+\epsilon} \text{ for all large } m$$

Valid when: Requires sufficiently large valid lengths so constants and the O(N_m) checker floor are absorbed.

Next analysis. Instantiate g(r)=ceil(log log(r+4)); prove the verifier and length test are poly(N), then analyze whether valid-slice lower bounds for H_g admit a proof-complexity or MCSP carrier formulation.

Falsifiers.

- falsifier: If g is bounded by k, the consequence collapses to ruling out only SAT circuits below exponent about k(1+epsilon).
- falsifier: If the source claim is all-length rather than valid-length/i.o., invalid lengths have trivial rejecting circuits and kill the lower bound.
- falsifier: If a bundled carrier includes small k slices, those slices dominate the threshold and reintroduce the finite-exponent obstruction.
- falsifier: If length validity or prefix recovery needs super-polynomial time in N, H_g may leave NP and the target-preserving transfer is invalid.

cycle-0004: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 900.012 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 4 proves a valid projection-sandwich lemma and demagnifies the sparse-padding route: N^{1+eps} lower bounds for H_g equal $m^{(1+eps)g}$ SAT lower bounds. The bridge is correct but not a weak-source path toward P vs NP.

Pressure. The bridge is valid, but its source obligation is not barely nontrivial in the original SAT length; it already asks for $m^{\omega(1)}$ SAT lower bounds.

Derivation steps.

1. Fix a valid length N_m and define H_g by copying the first m input bits into the SAT_m instance; invalid lengths are not part of the source lower-bound claim.
2. If SAT_m has a circuit of size m^c, wire the first m inputs into it and ignore all padding bits, giving an H_g circuit of size m^c+O(m).
3. If H_g at N_m has a circuit of size s, restrict the padding bits to constants; the resulting m-input circuit decides SAT_m with size s+O(1).
4. Substitute $N_m = (m+1)^{g(m+1)}$. A barely superlinear bound in N is a superpolynomial SAT lower bound when g is unbounded.

Equation 1: valid_length_carrier.

$$N_m = (m+1)^{g(m+1)}, \quad H_g(x) = SAT_m(x_1, \ldots, x_m) \text{ for } |x| = N_m$$

Valid when: Valid when the source lower-bound model is explicitly restricted to these padded valid lengths.

Equation 2: projection_sandwich.

$$C_m(SAT) \leq C_{N_m}(H_g) + O(1), \quad C_{N_m}(H_g) \leq C_m(SAT) + O(m)$$

Valid when: Valid when the padding map is a projection and circuits may nonuniformly know the length.

Equation 3: threshold_demagnification.

$$C_{N_m}(H_g) > N_m^{1+\epsilon} \Rightarrow C_m(SAT) > (m+1)^{(1+\epsilon)g(m+1)} - O(m)$$

Valid when: Applies after the reduction preserves the valid length and the lower-bound threshold exactly.

Next analysis. Test an MCSP or KT-complexity carrier with source model, threshold N^{1+eps}, and target NP $\not\subset$ P/poly; compute the reduction overhead and state whether the needed proof must be non-natural or non-algebrizing.

Falsifiers.

- falsifier: if the lower bound is asserted on all lengths, invalid lengths are constant slices and the statement becomes false.
- falsifier: if the encoding is not a projection and needs an Omega(N) decoder, the O(N) floor collapses the N^{1+eps} threshold.
- falsifier: if g is bounded on the lower-bound subsequence, the consequence excludes only finitely many SAT exponents.
- falsifier: a large constructive proof property would meet the natural-proofs obstruction; this route needs a specific non-natural lower-bound argument.

cycle-0005: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 900.006 seconds; 2 lemmas, 5 equations, 7 derivation steps, 4 falsifiers.

Learning. Cycle 5 converts the padding quarantine into a general projection-carrier dichotomy. The valid bridge says $N^{1+\epsilon}$ lower bounds transfer through ell(N) only when $ell(N)^c$ is below the threshold. Positive polynomial embedding length gives only a bounded exponent window; subpolynomial embedding length gives all exponents but turns the source lower bound into $ell(N)^{\omega(1)}$. Thus pure projection magnification fails as a weak-source path, with an explicit falsifier rather than a slogan.

Pressure. Projection carriers cannot simultaneously keep the lower bound weak in the semantic source size and transfer it to exclusion of all polynomial SAT exponents.

Derivation steps.

1. Generalize the padded SAT carrier to a projection family H_N with embedded SAT length ell(N) and linear validity/decoder overhead.
2. Assume the target negation: SAT has nonuniform circuits of size m^c for a fixed exponent c at every length m.
3. Compose the $\mathrm{SAT}_{ell(N)}$ circuit with pi_N and V_N, obtaining SIZE(H_N)<=O(N log N)+ell(N)^c.
4. Combine with the source lower bound $\mathrm{SIZE}(H_N) > K\ N^{1+\epsilon}$ on infinitely many N.
5. If $ell(N) = N^{\alpha+o(1)}$, contradiction is forced only for $c < (1+\epsilon)/\alpha$.
6. To rule out all fixed c, require $ell(N) = N^{o(1)}$ on the lower-bound support.
7. But then the source threshold $N^{1+\epsilon}$ equals $ell(N)^{\omega(1)}$, so the lower bound is no longer barely nontrivial relative to the embedded SAT instance size.

Equation 1: projection_upper_bound.

$$\mathrm{SIZE}(H_N) \le AN + B\,\mathrm{SIZE}(\mathrm{SAT}_{\ell(N)}) + O(N \log N).$$

Valid when: Valid when the source carrier is a fixed-output projection of SAT with linear decoding overhead.

Equation 2: exponent_transfer.

$$\mathrm{SIZE}(\mathrm{SAT}_m) \le m^c\ \forall m \quad \Rightarrow \quad \mathrm{SIZE}(H_N) \le O(N \log N) + \ell(N)^c.$$

Valid when: Applies after the target SAT circuit family is available at every embedded length.

Equation 3: finite_window.

$$\ell(N) = N^{\alpha+o(1)} \ \Rightarrow\ \mathrm{SIZE}(H_N) \le N^{\alpha c+o(1)} + O(N \log N).$$

Valid when: Valid when the embedding length has a stable polynomial exponent along the lower-bound support.

Equation 4: contradiction_condition.

$$KN^{1+\varepsilon} < \mathrm{SIZE}(H_N) \text{ i.o. } \wedge \ \alpha c < 1+\varepsilon \ \Rightarrow \ \mathrm{SAT} \notin \mathrm{SIZE}(n^c).$$

Valid when: Requires the lower-bound lengths to be infinite and the overhead to be below the threshold.

Equation 5: all_exponents_cost.

$$(\forall c \, \ell(N)^c = o(N^{1+\varepsilon})) \iff \ell(N) = N^{o(1)}, \quad \ell(N) = N^{o(1)} \Rightarrow N^{1+\varepsilon} = \ell(N)^{\omega(1)}.$$

Valid when: Valid when ell(N) is unbounded and asymptotics are taken on the same infinite support.

Next analysis. Audit an MCSP-based route: set source object $\mathrm{MCSP}_{n,s}$ on $N = 2^n - bit$ truth tables, choose a concrete circuit model for the lower bound, state the exact threshold $N^{1+\epsilon}$ or smaller, and test whether the known magnification transfer is non-natural, target-preserving, and strong enough to imply SAT $\notin$ P/poly rather than only EXP or subexponential derandomization consequences.

Falsifiers.

- falsifier: $ell(N) = N^{1/2}$, $\epsilon = 0.1$, and target exponent $c = 3$ leave the composed H_N upper bound above $N^{1.1}$, so the bridge cannot refute $\mathrm{SAT} \in \mathrm{SIZE}(n^3)$.
- falsifier: interface overhead $N^{1+\delta}$ with $\delta \geq \epsilon$ masks any target-circuit saving and collapses the quantitative transfer.
- falsifier: a decoder using N-bit nonuniform advice can make H_N hard for reasons unrelated to SAT, causing nonuniform leakage and invalid target preservation.
- falsifier: proving $H_N > N^{1+\epsilon}$ only at lengths where the projection image is empty or bounded gives no target-class consequence.

cycle-0006: Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit

Execution. research; azure_responses_api; attempt primary; 900.016 seconds; 3 lemmas, 4 equations, 7 derivation steps, 4 falsifiers.

Learning. Cycle 6 shows that moving from projection padding to a nonprojection MCSP carrier does not by itself create major magnification. The valid transfer is $C(\mathrm{MCSP}_{N^\alpha}, N) = 0$ caps any fixed barely-superlinear bridge below all-exponent P/poly separation. The failure is a concrete threshold falsifier, not barrier folklore.

Pressure. For NP $\not\subset$ P/poly one must contradict every constant c, but fixed ϵ and α certify only c<(1+epsilon)/(1+alpha). Even $\alpha = 0$ leaves the input-reading ceiling $c < 1 + \epsilon$.

Derivation steps.

1. Fix $\alpha \geq 0$ and $K_{\alpha,N} = \text{MCSP}_{N^\alpha}$ on valid truth-table lengths N.
2. Assume for contradiction that SAT has nonuniform circuits of size O(m^c).
3. Given an N-bit truth table T, construct the Cook-Levin formula Phi_T expressing that there exists a circuit of size at most N^α matching T on all N inputs.
4. The construction has length M(N)=O(N^{1+alpha} polylog N) because it enumerates every table position and evaluates the guessed circuit locally.
5. A circuit for $K_{\alpha,N}$ hardwires the SAT circuit for length M(N), computes Phi_T, and outputs the SAT circuit's answer.
6. Therefore $C(K_{\alpha,N}) \leq N^{c(1+\alpha)+o(1)}$.
7. A lower bound $C(K_{\alpha,N}) > N^{1+\epsilon}$ contradicts the SAT hypothesis exactly when $c(1+\alpha) < 1+\epsilon$.

Equation 1: verifier_time.

$$T_\alpha(N) = O(N\, s(N) \operatorname{polylog} N) = N^{1+\alpha+o(1)}$$

Valid when: Valid when MCSP membership is verified by exhaustive truth-table checking of the guessed small circuit.

Equation 2: induced_upper_bound.

$$\text{SAT} \in \text{SIZE}(m^c) \Rightarrow C(K_{\alpha,N}) \leq N^{c(1+\alpha)+o(1)}$$

Valid when: Applies after the Cook-Levin reduction preserves uniformity and the SAT circuit is substituted nonuniformly.

Equation 3: transfer_threshold.

$$C(K_{\alpha,N}) > N^{1+\epsilon} \Rightarrow \text{SAT} \notin \text{SIZE}(n^c) \quad \text{for } c < \frac{1+\epsilon}{1+\alpha}$$

Valid when: Requires the source lower bound and the induced SAT-based upper bound to hold on aligned valid lengths.

Equation 4: major_target_ceiling.

$$\sup c \text{ certified by fixed } (\epsilon, \alpha) \leq \frac{1+\epsilon}{1+\alpha} \leq 1+\epsilon$$

Valid when: Valid when α is nonnegative, as forced by input-reading verification of N-bit instances.

Next analysis. Test a self-referential meta-complexity carrier, such as Gap-MCSP or MKtP with succinctly generated truth tables, where the target SAT circuit is used nonblack-box. Compute whether the induced carrier upper bound can avoid the multiplicative c factor; if not, quarantine it by the same beta-ceiling lemma.

Falsifiers.

- falsifier: choose SAT circuit exponent c>=(1+epsilon)/(1+alpha); then the induced MCSP upper bound is not below $N^{1+\epsilon}$.
- falsifier: any hidden reduction overhead $M(N) = N^{\beta+o(1)}$ with $\beta > 1 + \alpha$ further shrinks the certified target range to $c < (1 + \epsilon)/\beta$.
- falsifier: nonuniform leakage occurs if the MCSP-to-SAT construction uses length-specific advice not already present in the hypothesized SAT circuit family.
- falsifier: invoking natural proofs alone is invalid here because the small-threshold MCSP accepted set is not large; the route fails quantitatively.

cycle-0007: Hardness-Magnification Bridge Realization: black-box substitution cap

Execution. research; azure_responses_api; attempt primary; 900.005 seconds; 2 lemmas, 3 equations, 6 derivation steps, 4 falsifiers.

Learning. Cycle 7 generalizes the MCSP and padding failures to an oracle-interface theorem. A barely-superlinear carrier lower bound transfers through a black-box SAT interface as max{a,q+beta c}; hence positive target-query length exponent β is the decisive threshold-collapse falsifier. The remaining valid route must either use subpolynomial target queries with a genuinely nonprojection carrier or abandon black-box substitution.

Pressure. The only unquarantined escape is to construct a nonprojection carrier with $N^{o(1)}$ target query length, $sub - N^{1+\epsilon}$ interface size, and a valid $N^{1+\epsilon}$ nonuniform lower bound.

Derivation steps.

1. Assume SAT has nonuniform circuits of size O(m^c) for every queried formula length m.
2. Model the carrier algorithm as an oracle circuit A_N with explicit ordinary gates and explicit SAT-query gates; adaptivity is absorbed into the circuit DAG.
3. Replace each SAT-query gate of length at most $N^{\beta+o(1)}$ by the corresponding SAT circuit of size N^{beta c+o(1)}.
4. The resulting L_N circuit has size at most N^{a+o(1)}+N^{q+beta c+o(1)}.
5. Contrapose against SIZE(L_N) $> N^{1+\epsilon}$: only exponents c satisfying q+beta $c < 1 + \epsilon$ and $a < 1 + \epsilon$ are ruled out.
6. Therefore a positive polynomial query-length exponent β is a quantitative threshold-collapse falsifier for deriving NP $\not\subset$ P/poly from one fixed barely-superlinear source lower bound.

Equation 1: substitution_upper_bound.

$$SIZE(L_N) \leq N^{a+o(1)} + N^{q+o(1)} \cdot (N^{\beta+o(1)})^c = N^{\max a, q+\beta c+o(1)}$$

Valid when: Valid when the source oracle circuit explicitly counts advice, preprocessing, and every SAT oracle gate before substitution.

Equation 2: contrapositive_window.

$$SIZE(L_N) > N^{1+\epsilon} \Rightarrow SAT \notin SIZE(m^c) \text{ for } c < \frac{1+\epsilon-q}{\beta},\ a < 1+\epsilon,\ \beta > 0$$

Valid when: Applies after the reduction preserves target lengths and the lower bound holds on matching valid source lengths.

Equation 3: all_exponent_obstruction.

$$\forall c\ [SAT \notin SIZE(m^c)] \text{ from fixed } \epsilon \text{ requires } \beta = 0 \text{ and } \max a, q < 1+\epsilon$$

Valid when: Requires fixed ϵ and black-box substitution as the only target-preserving complexity-class transfer mechanism.

Next analysis. Test a succinct local-consistency or proof-complexity carrier with $N^{o(1)}$ SAT queries: compute a,q,beta, then run the projection-demagnification falsifier before claiming any magnification.

Falsifiers.

- falsifier: $\beta > 0$ leaves only the finite window $c < (1+\epsilon-q)/\beta$, so all-exponent NP/poly separation cannot follow.
- falsifier: $q \geq 1+\epsilon$ means the oracle interface alone already exceeds the source lower-bound threshold.
- falsifier: $a \geq 1+\epsilon$ means preprocessing or advice leakage consumes the entire barely-superlinear margin.
- falsifier: projection or padding carriers with subpolynomial query length demagnify the source lower bound into a strong target lower bound, as in the earlier projection-sandwich quarantine.

cycle-0008: Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair

Execution. research; azure_responses_api; attempt primary; 111.459 seconds; 3 lemmas, 4 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 8 repairs the remaining route exactly: subpolynomial SAT-query length is sufficient to remove the c-dependent threshold term, so $N^{1+\epsilon}$ lower bounds magnify only when $max(a, q) < 1+\epsilon$. The valid contribution is a quantified bridge plus a model-preservation gate; the unresolved hard task is finding a concrete carrier satisfying the interface and source lower bound without natural-proof or nonuniform-leakage failure.

Pressure. No concrete non-natural carrier K is known with both a near-linear subpolynomial-query SAT interface and an $N^{1+\epsilon}$ nonuniform circuit lower bound. MCSP-like truth-table carriers fail because their SAT-verification queries have polynomial, usually linear, dependence on N.

Derivation steps.

1. Fix an arbitrary constant c and assume for contradiction that SAT has nonuniform circuits of size n^c for all sufficiently large n.
2. Pad all SAT queries made by the K_N oracle circuit to one length s(N)+O(1); finite small exceptions are hardwired and do not affect the exponent.
3. Replace each SAT oracle gate by the corresponding SAT circuit. Adaptivity causes no exponential blowup because the oracle computation is already represented as a circuit DAG with oracle gates.
4. The resulting K_N circuit has size at most A(N)+Q(N)(s(N)^c+O(s(N)))+O(1).
5. With $A = N^{a+o(1)}$, $Q = N^{q+o(1)}$, and $s = N^{o(1)}$, this size is $N^{max(a,q)+o(1)}$ for the fixed c.
6. Choose $\eta > 0$ with $max(a, q) + \eta < 1 + \epsilon$. For all large N the substituted K_N circuits have size $< N^{1+\epsilon}$, contradicting the source lower bound.
7. Since c was arbitrary, SAT is not in SIZE(n^c) for any fixed c; therefore SAT $\notin$ P/poly and NP $\not\subset$ P/poly.

Equation 1: oracle-substitution-size.

$$C_K(N) \le A(N) + Q(N) \cdot (C_{SAT}(s(N)) + O(s(N))) + O(1).$$

Valid when: Valid when the source oracle circuit explicitly counts all query-building wires outside the SAT oracle gates.

Equation 2: polynomial-query-transfer.

$C_{SAT}(n) \le n^c$, $A(N) \le N^{a+o(1)}$, $Q(N) \le N^{q+o(1)}$, $s(N) = N^{\beta(N)} \Rightarrow C_K(N) \le N^{\max a, q+\beta(N)\max(c,1)+o(1)}$.

Valid when: Applies after the reduction preserves nonuniformity and pads all SAT queries to one controlled length.

Equation 3: subpoly-query-collapse.

$$s(N) = N^{o(1)} \Rightarrow C_K(N) \le N^{\max a, q+o(1)} \quad \text{for each fixed } c.$$

Valid when: Valid when c is fixed before taking N large, so c times the query-length exponent is still o(1).

Equation 4: magnified-consequence.

$$C_K(N) > N^{1+\epsilon} \ \wedge \ \max a, q < 1 + \epsilon \ \Rightarrow \ \forall c \ C_{SAT}(n) \not\le n^c.$$

Valid when: Requires the target-preserving complexity-class transfer and an eventual source lower bound on the same circuit basis.

Next analysis. Search for non-truth-table carriers in P^{SAT} with near-linear ordinary work and subpolynomial SAT queries, e.g. succinct consistency or decompression-check problems, then compute A,Q,s and test against L8.1 before discussing P vs NP.

Falsifiers.

- falsifier: $s(N) = N^{\beta}$ for $\beta > 0$ causes threshold collapse and excludes only $c < (1 + \epsilon - q)/\beta$.
- falsifier: $q \geq 1 + \epsilon$ or ordinary overhead $a \geq 1 + \epsilon$ leaves no room below the source lower-bound threshold.
- falsifier: the source theorem is uniform-only or restricted-model, while SAT $\notin$ P/poly requires a nonuniform target-preserving contradiction.
- falsifier: a hidden advice string used to choose queries or decompressions is not counted in A(N), creating nonuniform leakage.
- falsifier: the proposed carrier is a large constructive useful truth-table property; under standard PRF assumptions a natural proof of its P/poly usefulness is blocked.
- falsifier: if both the bridge and the source lower-bound proof relativize, oracle worlds with NP^O subset P^O/poly prevent promotion to a main P vs NP proof.

cycle-0009: Hardness-Magnification Bridge Realization: subpolynomial-interface demagnification

Execution. research; azure_responses_api; attempt primary; 166.602 seconds; 2 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 9 converts the cycle-8 repair into a route failure certificate. Subpolynomial SAT queries remove the c-dependent upper-bound term, but the same transfer read backward says that proving the source $N^{1+\epsilon}$ lower bound in general SIZE already proves $\text{SAT}_{\leq L}$ has $L^{\omega(1)}$ circuits lower bounds. The remaining valid work is not carrier search inside this black-box same-model interface; it is either a restricted-model closure theorem or a nonblackbox carrier.

Pressure. The branch has no concrete carrier that is simultaneously a weak same-model source lower bound and target-preserving. Same-model sources demagnify; restricted sources need an unproved substitution-closure theorem.

Derivation steps.

1. Start from the repaired cycle-8 interface: reduction overhead exponent a, query-count exponent q, and SAT query length $L(N) = N^{o(1)}$ with $max(a, q) < 1 + \epsilon$.
2. Inline a hypothetical $size - L^c$ SAT circuit into every SAT oracle gate of the carrier reduction, obtaining C(K_N)<=s_R(N)+Q(N)L(N)^c+O(Q(N)L(N)).
3. Observe that this proves the valid target transfer: an eventual $N^{1+\epsilon}$ lower bound for K_N excludes every fixed c because L(N)^c=N^{o(1)}.
4. Read the same inequality contrapositively: the source lower bound implies C(SAT_{(N^{1+epsilon}-s_R-O(QL))/Q.
5. For $Q \leq N^q$ with $q < 1 + \epsilon$ and $L = N^{o(1)}$, the induced SAT lower bound is N^{1+epsilon-q-o(1)}=L^{omega(1)}, already superpolynomial at the target query length.
6. Add the unconditional lookup upper bound $C(K_N)$ = (1+epsilon-q-o(1))log_2 N for any possible $N^{1+\epsilon}$ source lower bound.

Equation 1: upper_transfer.

$$C_{\mathrm{SIZE}}(K_N) \leq s_R(N) + Q(N)\, C_{\mathrm{SIZE}}(\mathrm{SAT}_{\leq L(N)}) + O(Q(N)L(N))$$

Valid when: Applies when every oracle answer is replaced by a target SAT circuit and the reduction overhead is counted explicitly.

Equation 2: contrapositive_demagnification.

$$C_{\mathrm{SIZE}}(K_N) > N^{1+\epsilon} \Rightarrow C_{\mathrm{SIZE}}(\mathrm{SAT}_{\leq L(N)}) > \frac{N^{1+\epsilon} - s_R(N) - O(Q(N)L(N))}{Q(N)}$$

Valid when: Valid when the source lower bound exceeds the complete substituted reduction size threshold in the same circuit model.

Equation 3: subpoly_query_consequence.

$$L(N) = N^{o(1)},\ Q(N) \leq N^q,\ s_R(N) \leq N^a,\ a, q < 1+\epsilon \Rightarrow C_{\mathrm{SIZE}}(\mathrm{SAT}_{\leq L(N)}) \geq N^{1+\epsilon-q-o(1)} = L(N)^{\omega(1)}$$

Valid when: Requires the subpolynomial query-length regime and polynomially bounded query count below the claimed source threshold.

Equation 4: lookup_falsifier_bound.

$$C_{\mathrm{SIZE}}(K_N) \leq s_R(N) + O(Q(N)L(N)2^{L(N)})$$

Valid when: Valid when the source model is unrestricted nonuniform circuits and lookup tables may encode SAT truth tables.

Next analysis. Pivot to a nonblackbox object: test a proof-complexity or derandomization carrier where SAT in P/poly yields the required source upper bound through a named nonrelativizing theorem rather than through black-box SAT-query substitution.

Falsifiers.

- same-model demagnification falsifier: an $N^{1+\epsilon}$ lower bound for K_N entails $\mathrm{SAT}_{\leq L(N)}$ lower bounds of size $L(N)^{\omega(1)}$, so the source is not barely nontrivial relative to the target.
- lookup-table falsifier: if Q(N)L(N)2^{L(N)}=o(N^{1+epsilon}) after reduction overhead, unrestricted nonuniform circuits decide K_N below the claimed threshold.
- model-mismatch falsifier: replacing the source model by AC0, formulas, or another restricted class invalidates the transfer unless a quantitative substitution-closure lemma Phi_M is proved.
- nonuniform leakage falsifier: if R_N or the compressor is chosen with advice encoding a hard truth table, the carrier lower bound is not target-preserving.
- relativizing-interface falsifier: a proof using only black-box oracle substitution remains within a relativizing interface and cannot by itself overcome the known oracle barrier for the main P vs NP conjecture.

cycle-0010: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 142.192 seconds; 2 lemmas, 4 equations, 8 derivation steps, 4 falsifiers.

Learning. Cycle 10 proves a valid restricted-model closure bridge and names the precise target-preservation failure. Subpolynomial queries plus $max(a, q) < 1 + \epsilon$ magnify a Γ lower bound to SAT notin Γ/poly for every fixed exponent. This is real route-level progress, but it is not NP notin P/poly: the missing object is a nonuniform P/poly-to-Gamma lift with subthreshold tax, and its absence is the decisive falsifier for advertising the bridge as a P vs NP route.

Pressure. The target-preserving lift from arbitrary P/poly SAT circuits to $\Gamma - circuits$ is absent; without it, restricted-source magnification leaks the target model.

Derivation steps.

1. Fix Γ and an oracle $\Gamma - circuit$ A_N for H_N with N^a internal gates and at most N^q SAT queries of length at most L(N).
2. Assume the restricted target negation: $\text{SAT}_{\leq n}$ has $\Gamma - circuits$ of size n^c for all large n.
3. Replace each SAT oracle gate in A_N by the corresponding $\Gamma - circuit$ for $\text{SAT}_{\leq L(N)}$ and use Γ substitution closure.
4. Obtain $S_{Gamma}(H_N) \leq \widetilde{O}(N^a + N^q L(N)^c)$.
5. For $L = N^\beta$, compare the exponent max(a,q+beta c) with 1+epsilon to exclude only c below (1+epsilon-q)/beta.
6. For $L = N^{o(1)}$, obtain $S_{Gamma}(H_N) \leq N^{max(a,q)+o(1)}$ for each fixed c, contradicting the source bound if $max(a, q) < 1 + \epsilon$.
7. Attempt to replace the restricted target assumption SAT in Γ/poly by SAT in P/poly. This requires converting arbitrary SAT circuits into $\Gamma - circuits$ on the queried lengths.
8. No such conversion follows from the interface. Therefore the valid conclusion is Γ/poly separation, while the P/poly consequence remains unproved.

Equation 1: substitution_upper_bound.

$$S_\Gamma(H_N) \leq \widetilde{O}\big(N^a + N^q\, S_\Gamma(SAT_{\leq L(N)})\big)$$

Valid when: Valid when Γ is explicitly closed under oracle-gate substitution and query-generation circuits are counted.

Equation 2: polynomial_query_length_transfer.

$$L(N) = N^\beta,\ S_\Gamma(SAT_n) \leq n^c \implies S_\Gamma(H_N) \leq N^{\max a, q+\beta c+o(1)}$$

Valid when: Applies when query lengths have fixed polynomial exponent β and c is fixed.

Equation 3: finite_exponent_exclusion.

$$S_\Gamma(H_N) > N^{1+\epsilon} \implies SAT \notin \Gamma[n^c] \quad \text{for } c < (1+\epsilon-q)/\beta \text{ and } a < 1+\epsilon$$

Valid when: Requires positive β and compares the transferred exponent with the source threshold.

Equation 4: subpolynomial_query_magnification.

$$L(N) = N^{o(1)},\ \max a, q < 1+\epsilon \implies SAT \notin \Gamma[n^c] \text{ for every fixed } c$$

Valid when: Valid when the o(1) term is uniform for each fixed target exponent c.

Next analysis. Test a non-natural nonblackbox carrier whose query length is $N^{o(1)}$ and whose use of a SAT circuit is semantic rather than oracle substitution; compute whether its lift tax δ is below the source slack ϵ.

Falsifiers.

- falsifier: if $\beta > 0$, the transfer excludes only $c < (1+\epsilon-q)/\beta$, so all-exponent magnification collapses.
- falsifier: if $max(a, q) \geq 1+\epsilon$, even subpolynomial SAT queries do not beat the source threshold.
- falsifier: if Γ is weaker than P/poly and no P/poly-to-Gamma lift is valid, the target class silently changes to Γ/poly.
- falsifier: a natural-proof style dense useful property computable in Γ/poly would not be a credible P/poly route under standard pseudorandom-function assumptions; it must be non-natural or outside that barrier's scope.

cycle-0011: Hardness-Magnification Bridge Realization: lookup-lift collapse for restricted target repair

Execution. research; azure_responses_api; attempt primary; 128.594 seconds; 3 lemmas, 4 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 11 turns the cycle-10 target split into a sharper impossibility triangle. To lift Γ lower bounds to P/poly by unrolling arbitrary SAT circuits, queries must be so short that every SAT query can also be answered by unconditional lookup inside Γ. That gives H_N a subthreshold Γ upper bound and falsifies the source lower bound. Intermediate log-query lengths either collapse the source or preserve only exponent $c \leq 1$. Thus black-box formula-style P/poly repair is quarantined; progress now requires a genuinely nonblackbox carrier or a proof object where target circuits are used without independent short-query lookup.

Pressure. The missing bridge is not merely an efficient P/poly-to-Gamma simulation; it must be efficient for SAT-derived query computations while not enabling small lookup for all short query predicates. Generic unrolling cannot satisfy both requirements.

Derivation steps.

1. Start from the cycle-10 restricted bridge: a Γ lower bound for H_N magnifies to SAT notin Γ/poly when H_N has subpolynomial SAT queries and $max(a, q) < 1 + \epsilon$.
2. Try to repair the missing P/poly target by setting Γ to De Morgan formulas and converting any hypothesized length-L SAT circuit of size L^c into a formula of size 2^{O(L^c)}.
3. To preserve every fixed P/poly exponent c, require L(N)^c=o(log N) for every fixed c, hence L(N)=(log N)^{o(1)}.
4. In that same regime, $\text{SAT}_{\leq L(N)}$ has an unconditional DNF lookup of size 2^{O(L(N))}poly(L(N))=N^{o(1)}.
5. Substituting this lookup into the $\Gamma - oracle$ skeleton gives $S_{Gamma}(H_N) \leq N^{max(a,q)+o(1)}$, contradicting the desired $N^{1+\epsilon}$ source lower bound whenever $max(a, q) < 1 + \epsilon$.

Equation 1: oracle-substitution-bound.

$$S_\Gamma(H_N) \leq O(N^a) + N^q T_\Gamma(SAT_{\leq L(N)})$$

Valid when: Valid when the source carrier is represented by a Γ oracle skeleton and each oracle occurrence is replaced independently.

Equation 2: lookup-upper-bound.

$$T_\Gamma(SAT_{\leq L}) \leq 2^{O(L)}\,\text{poly}(L)$$

Valid when: Valid when Γ contains DNF or decision-tree lookup implementations for every Boolean predicate on L bits.

Equation 3: ultrashort-collapse.

$$L(N) = (\log N)^{o(1)} \Rightarrow 2^{O(L(N))}\,\text{poly}(L(N)) = N^{o(1)}$$

Valid when: Valid in the ultra-short query regime needed to preserve every fixed target exponent under exponential unrolling.

Equation 4: source-lower-bound-contradiction.

$$S_\Gamma(H_N) \leq N^{\max a,q+o(1)} < N^{1+\epsilon}$$

Valid when: Applies after the threshold assumption $maxa, q < 1 + \epsilon$ is combined with the lookup substitution bound.

Next analysis. Test a nonblackbox proof-complexity carrier: encode a SAT circuit as a verifier object whose correctness is checked globally rather than by short oracle leaves, and compute whether the verifier overhead stays below $N^{1+\epsilon}$ without allowing $\text{SAT}_{\leq L}$ truth-table substitution.

Falsifiers.

- falsifier: ultra-short query lookup gives an unconditional Γ upper bound below the proposed barely-superlinear source lower bound.
- falsifier: generic circuit unrolling preserves all fixed P/poly exponents only in the same ultra-short regime where lookup collapse is valid.
- falsifier: log-length queries with $\alpha \geq 1$ avoid $N^{o(1)}$ lookup only by preserving at most $c \leq 1$, which is not a meaningful P/poly target for SAT.
- falsifier: any independent oracle-leaf substitution argument remains relativizing and cannot certify the needed nonblackbox target transfer.
- falsifier: Γ classes lacking DNF lookup also lack the advertised generic P/poly lift unless an explicit nonnatural replacement is proved.

cycle-0012: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 140.028 seconds; 2 lemmas, 4 equations, 6 derivation steps, 4 falsifiers.

Learning. Cycle 12 identifies a real surviving window: superlogarithmic subpolynomial target lengths, especially L=(log N)^d with $d > 1$. In this window SAT circuits of size L^c amortize to $N^{o(1)}$, but SAT truth tables cost 2^L and no longer give the old subthreshold lookup falsifier. The bridge is valid only for nonblackbox compact-circuit consumers; it is not a P vs NP proof without the explicit carrier and lower bound.

Pressure. No explicit carrier H_N and evaluator E_N are yet exhibited whose computation genuinely exploits compact SAT circuits rather than ordinary oracle answers, and no $N^{1+\epsilon}$ lower bound for such an H_N is known.

Derivation steps.

1. Fix $d > 1$ and L(N)=(ceil log N)^d. Assume for contradiction SAT $\in$ SIZE(n^c) for some fixed c, eventually.
2. For each large N choose a correct $\mathrm{SAT}_{L(N)}$ circuit $D_{L(N)}$ of size at most $L(N)^c$. Nonuniformity allows this circuit to be hardwired into the H_N upper-bound circuit.
3. Substitute $D_{L(N)}$ into E_N. By the interface bound, $C(H_N) \leq K\ N^a\ L(N)^{bc+r}$.
4. Since $L(N) = N^{o(1)}$, for any $\delta > 0$ and all large N, L(N)^{bc+r}<=N^delta. Choose delta<(1+epsilon-a).
5. Then SAT $\in$ SIZE(n^c) implies $C(H_N)N^{1+\epsilon}$.
6. Check against the old black-box falsifier: the unconditional lookup implementation has size N^a2^{L(N)}, which is superpolynomial for L=(log N)^d, $d > 1$, so it does not itself refute the source lower bound.

Equation 1: conditional_upper.

$$C(H_N) \leq KN^a |D_{L(N)}|^b L(N)^r$$

Valid when: Valid when the evaluator has fixed nonuniform circuits and the only target-dependent advice is an exact SAT circuit $D_{L(N)}$ substituted into it.

Equation 2: target_amortization.

$$C(SAT_L) \leq L^c \;\Rightarrow\; C(H_N) \leq KN^a L(N)^{bc+r} = N^{a+o(1)}$$

Valid when: Applies when L(N) is subpolynomial in N and c,b,r are fixed constants independent of the carrier length.

Equation 3: magnification_contrapositive.

$$(\exists^\infty N)\, C(H_N) > N^{1+\epsilon} \;\Rightarrow\; SAT \notin P/poly$$

Valid when: Requires the conditional upper bound for all large N under SAT in P/poly and the strict threshold gap $a < 1 + \epsilon$.

Equation 4: lookup_boundary.

$$N^a 2^{L(N)} < N^{1+\epsilon} \text{ if } L(N) < (1 + \epsilon - a - o(1)) \log_2 N$$

Valid when: Valid when the interface can be replaced by a full SAT truth-table lookup rather than a compact nonblackbox target circuit.

Next analysis. Instantiate H_N as a proof-checking or self-reduction transcript language whose verifier can call a compact SAT_L circuit nonblackbox; compute its exact overhead a and test whether full truth-table substitution or input-encoded D leakage gives a subthreshold upper bound.

Falsifiers.

- falsifier: logarithmic L(N) permits full SAT truth-table substitution of size below $N^{1+\epsilon}$, collapsing the carrier lower bound unconditionally.
- falsifier: if the target circuit D is part of the input, then input-reading or nonuniform leakage reintroduces the positive target-size exponent and destroys all-exponent transfer.
- falsifier: if E_N is merely a black-box SAT-query algorithm, superlogarithmic L blocks lookup but gives no reason that compact SAT circuits can be used without duplicating queries above threshold.
- falsifier: if the source lower bound is only for formulas, AC0, or another Γ not containing the substituted evaluator, the conclusion is only SAT notin Γ/poly, not NP notin P/poly.

cycle-0013: Hardness-Magnification Bridge Realization: Polylog Nonblackbox Compact Consumer

Execution. research; azure_responses_api; attempt primary; 155.298 seconds; 3 lemmas, 4 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 13 turns the superlogarithmic polylog window into an exact bridge: L=(log N)^d with $d > 1$ makes SAT circuits of size L^c amortize to $N^{o(1)}$, while truth-table lookup costs 2^L=N^{omega(1)} and no longer supplies the old falsifier. The valid threshold is $\rho < 1 + \epsilon$ for a target-clean nonblackbox compact consumer. The new hard obstruction is not folklore but the absence of an explicit carrier with no advice leakage and a non-natural $N^{1+\epsilon}$ general-circuit lower bound.

Pressure. No explicit carrier H_N is yet supplied with both a target-clean polylog nonblackbox compact consumer and an i.o. $N^{1+\epsilon}$ general-circuit lower bound. The lower-bound proof also must be non-natural or otherwise outside the natural-proofs obstruction.

Derivation steps.

1. Fix a target exponent c and assume, for contradiction, that SAT_m has circuits D_m of size m^c for all sufficiently large m.
2. For each sufficiently large valid carrier length N, set m=L(N)=floor((log N)^d), so the assumed SAT family supplies D_m.
3. Run the compact nonblackbox consumer T_N with D_m wired into its universal evaluator; no SAT truth table and no independent advice are allowed.
4. Because m^c=(log N)^{dc}=N^{o(1)}, the produced H_N circuit has size N^ρ poly(m^c,m,log N)=N^{rho+o(1)}.
5. Choose $\delta > 0$ with $\rho + deltaN^{1+\epsilon}$ on infinitely many valid lengths.
6. Since c was arbitrary and ρ does not depend on c, the conditional bridge excludes every fixed polynomial exponent for SAT circuits.

Equation 1: polylog target length.

$$L(N) = \lfloor (\log N)^d \rfloor, \quad d > 1$$

Valid when: Valid when d is fixed and N ranges over the carrier's valid input lengths.

Equation 2: fixed exponent amortization.

$$L(N)^c = (\log N)^{dc} = N^{o(1)}$$

Valid when: Valid when c and d are constants, not growing with N.

Equation 3: compact substitution bound.

$$\mathrm{SIZE}(H_N) \leq N^\rho \,\mathrm{poly}(L(N)^c, L(N), \log N) = N^{\rho + o(1)}$$

Valid when: Applies after the reduction preserves the source circuit model and target circuit descriptions.

Equation 4: magnification threshold.

$$\rho < 1 + \varepsilon \ \wedge \ \mathrm{SIZE}(H_N) > N^{1+\varepsilon} \text{ i.o. } \Rightarrow \ \mathrm{SAT} \notin \mathrm{SIZE}(n^c)$$

Valid when: Requires the source lower bound and compact upper bound to hold on overlapping valid lengths.

Next analysis. Instantiate $PolyLogAudit_{N,d,V}$ with a universal-circuit verifier, compute the exact overhead exponent ρ and auxiliary advice length, and reject the instance immediately if H_N depends on a hidden SAT circuit or collapses to a black-box SAT query family.

Falsifiers.

- falsifier: compact consumer exponent ρ reaches or exceeds 1+epsilon, causing quantitative threshold collapse.
- falsifier: L(N)=O(log N), because hardwired SAT truth tables give an unconditional lookup simulation.
- falsifier: the carrier reduces to a black-box projection SAT(G(x)) in the same model, reviving the demagnification from earlier cycles.
- falsifier: auxiliary advice A_N is not uniformly computable from N and the hypothesized SAT circuit $D_{L(N)}$.
- falsifier: the produced upper circuit is not in the same SIZE model as the claimed source lower bound.
- falsifier: a dense constructive natural property is the only known path to the general-circuit lower bound, triggering the natural-proofs barrier under standard PRG assumptions.

cycle-0014: Hardness-Magnification Bridge Realization: polylog generated-OR carrier

Execution. research; azure_responses_api; attempt primary; 142.763 seconds; 3 lemmas, 4 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 14 identifies a concrete carrier template, $H_N = OR$ of N^q generated SAT instances of length (log N)^d, and computes the exact transfer: SAT $\in$ SIZE(n^c) gives H_N in SIZE(N^{max{rho,q}+o(1)}). The valid magnification window is max{rho,q}1, exhaustive lookup is $N^{q+\omega(1)}$, so the previous short-query falsifier is avoided, but the source lower bound remains the hard non-natural obligation.

Pressure. The bridge is valid, but no explicit target-clean G_N, A_N is known with a provable unrestricted circuit lower bound SIZE(H_N) $> N^{1+\epsilon}$. A proof of that source bound must also avoid natural-proof density, relativizing oracle, and advice-leakage obstructions.

Derivation steps.

1. Fix constants $d > 1$, q, ρ, ϵ with $max\rho, q < 1 + \epsilon$, and define H_N by a target-clean generated OR or more general consumer over $M = N^q$ length-L SAT instances.

2. Assume toward contradiction that SAT is in P/poly, so for some c every sufficiently large length l has SAT circuits C_l of size O(l^c).

3. For each valid N, copy $C_{L(N)}$ into every generated target slot and wire these copies to A_N; the generator/consumer contributes N^ρ gates and the target copies contribute $N^q\ L^c$ gates.

4. Since L=(log N)^d, the copy cost is $N^{q+o(1)}$ for fixed c,d. Hence SIZE(H_N) $\le N^{max\rho,q+o(1)}$.

5. Choose $\delta > 0$ with $max\rho, q + \delta < 1 + \epsilon$. For all large valid N the composed circuit has size below $N^{1+\epsilon}$, contradicting the i.o. source lower bound.

6. Audit the unconditional falsifier: replacing each SAT call by exhaustive search costs N^rho+N^q2^L poly(L), which is $N^{q+\omega(1)}$ for $d > 1$, so it does not itself refute an $N^{1+\epsilon}$ lower bound.

Equation 1: carrier_definition.

$$H_N(x) = A_N\big(x, \mathrm{SAT}_L(G_N(x,1)), \ldots, \mathrm{SAT}_L(G_N(x,M))\big)$$

Valid when: Valid when G_N emits exactly M generated SAT instances and A_N consumes only their SAT bits.

Equation 2: composition_upper_bound.

$$\mathrm{SIZE}(H_N) \le O\big(N^\rho + M(N)(L(N)^c + L(N))\big)$$

Valid when: Valid when SAT_L has size O(L^c) circuits and each target call is substituted as a separate subcircuit.

Equation 3: polylog_amortization.

$$M(N)L(N)^c = N^q(\log N)^{dc} = N^{q+o(1)}$$

Valid when: Valid when c and d are fixed constants and N tends through the chosen valid lengths.

Equation 4: threshold_contradiction.

$$\max\rho, q < 1 + \epsilon \implies \mathrm{SIZE}(H_N) < N^{1+\epsilon} \text{ for all large valid } N$$

Valid when: Applies after choosing a positive margin between max{rho,q} and the claimed source lower-bound exponent.

Next analysis. Instantiate G_N as a near-linear Cook-Levin micro-instance generator with $M = N$ and L=(log N)^d; compute exact ρ, verify H_N is in NP with poly(N) uniform verification, and test whether any structural simplification gives an $N^{1+\epsilon}$ upper-bound falsifier.

Falsifiers.

- falsifier: threshold collapse occurs if $max\rho, q \geq 1 + \epsilon$, because SAT circuits then give no contradiction to the claimed source lower bound.
- falsifier: lookup collapse occurs when N^rho+N^q2^{L(N)}poly(L(N))<N^{1+epsilon} on infinitely many valid lengths.
- falsifier: nonuniform leakage occurs if G_N or A_N encodes SAT_L advice not charged to N^ρ.
- falsifier: model mismatch occurs if the source lower bound is for formulas, AC0, or another restricted model while the target substitution requires unrestricted P/poly circuits.
- falsifier: a large constructive natural property proving the source lower bound would collide with pseudorandom-function assumptions at the same $N^{1+\epsilon}$ scale.
- falsifier: a fully relativizing source lower-bound proof would be suspect because oracle worlds with NP^O subset P^O/poly should invalidate the target consequence.

cycle-0015: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 289.508 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 15 adds the exact lookup boundary. Polylog queries always preserve all SAT polynomial exponents in the substitution term, but source plausibility requires q+A(log N)^{d-1} not fall below 1+epsilon. Thus d1 is safely valid from lookup.

Pressure. No explicit no-advice generator G_N is known for which H_N has an i.o. $N^{1+\epsilon}$ general-circuit lower bound by a non-natural method.

Derivation steps.

1. Fix G_N of size N^ρ producing $m = N^q$ SAT queries of length L=A(log N)^d and define H_N as their OR.
2. Assume SAT has circuits of size n^c. Substitute the length-L circuit S_L into every query and add the generator plus OR overhead.
3. Since L^c=N^{o(1)}, the composed circuit has size $N^{max\rho,q+o(1)}$, contradicting any i.o. H_N lower bound above $N^{1+\epsilon}$ when $max\rho, q < 1 + \epsilon$.
4. Audit the independent lookup circuit for SAT_L. It is subthreshold exactly when q+A(log N)^{d-1}<1+epsilon eventually, producing a source-level falsifier.

Equation 1: carrier.

$$H_N(x) = \bigvee_{i \leq N^q} \mathrm{SAT}(G_{N,i}(x)), \qquad |G_{N,i}(x)| = L(N) = A(\log_2 N)^d$$

Valid when: Valid when G_N is a uniform generator whose outputs are well-formed SAT encodings of length L(N).

Equation 2: sat_substitution_upper.

$$\mathrm{SAT} \in \mathrm{SIZE}(n^c) \Rightarrow C(H_N) \leq N^{\rho} + N^q L(N)^c + O(N^q) = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the assumed SAT circuit is length-uniform nonuniform advice for exactly L(N)-bit formulas.

Equation 3: lookup_audit.

$$C_{\mathrm{lookup}}(H_N) \leq N^{\rho} + N^q 2^{L(N)}, \quad \lambda(N) = \log_N 2^{L(N)} = A(\log_2 N)^{d-1}$$

Valid when: Requires the lookup audit to be compared with the same $N^{1+\epsilon}$ source threshold.

Next analysis. Instantiate the boundary cases $d = 1$ with $A = 1 + \epsilon - q$ and $d = 2$; search for a generator whose H_N avoids known small-circuit constructions without smuggling SAT advice.

Falsifiers.

- Lookup falsifier: if $d < 1$, or $d = 1$ with $q + A < 1 + \epsilon$, the table for SAT_L gives $C(H_N) < N^{1+\epsilon}$ and the source premise is impossible.
- Threshold falsifier: if $\rho \geq 1 + \epsilon$ or $q \geq 1 + \epsilon$, SAT-substitution no longer yields a contradiction to the H_N lower bound.
- Advice-leakage falsifier: if G_N or the lower-bound proof embeds satisfiability bits for the generated query set, the target-preserving interface to SAT in P/poly is invalid.
- Natural-proof falsifier: if the H_N lower bound is obtained via a large constructive property useful against SIZE(N^{1+epsilon}), standard PRF assumptions block it for general circuits.

cycle-0016: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 244.266 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 16 sharpens the generated-OR route: the valid transfer to SAT $\notin$ P/poly needs only $q, \rho < 1 + \epsilon$, but source plausibility additionally requires variable entropy q+v/log N at least 1+epsilon. The old 2^L lookup audit was too weak; the real falsifier is low variable count.

Pressure. No explicit target-clean generator is known whose OR carrier has a non-natural unrestricted $N^{1+\epsilon}$ circuit lower bound while also passing the variable-entropy gate.

Derivation steps.

1. Fix H_N with $M = N^q$ generated SAT queries, length L=(log N)^d, generator cost N^{ρ}, and $maxq, \rho < 1 + \epsilon$.
2. Assume SAT has circuits of size n^c. Substitute the length-L SAT circuit into every query; since L^c=N^{o(1)}, H_N has size $N^{maxq,\rho+o(1)}$.
3. For large valid N this contradicts $\mathrm{SIZE}(H_N) > N^{1+\epsilon}$; hence the bridge would imply SAT $\notin$ P/poly, not merely a weak restatement of P vs NP.
4. Audit the source: independent of SAT circuits, each query can be solved by enumerating v(N) variables, so the lower bound is impossible below the threshold $q + v(N)/log_2$ N $\geq$ 1+epsilon.

Equation 1: carrier_definition.

$$H_N(x) = \bigvee_{i=1}^{M} SAT(\Phi_i(x)), \quad M = N^q, \quad |\Phi_i(x)| \le L = (\log N)^d$$

Valid when: Valid when the compact generator computes each queried SAT instance uniformly without embedding SAT advice.

Equation 2: sat_substitution_upper_bound.

$$SAT \in SIZE(n^c) \Rightarrow SIZE(H_N) \le N^\rho + N^q L^c \, polylog(N) = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the reduction preserves nonuniform target circuits and q,rho are constants independent of c.

Equation 3: variable_enumeration_falsifier.

$$SIZE(H_N) \le N^\rho + N^q 2^{v(N)} poly(L) = N^{\max \rho, q+v(N)/\log_2 N+o(1)}$$

Valid when: Valid when generated formulas have at most v(N) variables and deterministic exhaustive assignment evaluation is allowed.

Next analysis. Instantiate G_N with high-essential-variable polylog 3CNF queries and test whether any structural simplification gives SIZE(H_N) $\le N^{1+\epsilon-o(1)}$ despite v(N) superlogarithmic.

Falsifiers.

- Entropy falsifier: if generated formulas use only $v(N) < (1+\epsilon-q-\eta)log_2$ N variables, exhaustive assignment gives subthreshold circuits for H_N.
- Advice-leakage falsifier: if G_N encodes SAT truth bits or hard functions as nonuniform advice, the transfer no longer certifies SAT $\notin$ P/poly.
- Sparsity falsifier: if the query family lands in an easy SAT fragment or repeats $N^{o(1)}$ essential formulas, H_N may have circuits below $N^{1+\epsilon}$.
- Naturality falsifier: a large constructive property proving the H_N lower bound would collide with standard PRG-based natural-proofs barriers unless the proof is non-natural or outside their scope.

cycle-0017: Hardness-Magnification Bridge Realization: positioned-range entropy audit

Execution. research; azure_responses_api; attempt primary; 103.969 seconds; 3 lemmas, 5 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 17 adds a sharper necessary condition for the generated-OR route: not only $q, \rho < 1 + \epsilon$, but the positioned effective range entropy sum_g $min|R_g|, 2^v$ must reach the lower-bound threshold. This converts low-range query generation into an explicit falsifier and preserves the valid target transfer only for high-entropy, target-clean carriers.

Pressure. No explicit target-clean carrier is known with q,rho=1+epsilon-o(1), and a non-natural $N^{1+\epsilon}$ lower bound against general circuits.

Derivation steps.

1. Fix K_N with ordinary gates plus SAT oracle gates $g = 1, ..., t_N$, $t_N \leq N^q$, query length L_N=(log N)^d, and overhead size N^ρ.
2. Assume SAT has circuits C_L of size L^c. Replace every SAT gate by C_{L_N}; the resulting H_N circuit has size N^rho+t_NL_N^c=N^{max{rho,q}+o(1)}.
3. Thus an eventual lower bound H_N notin SIZE(N^{1+epsilon}) contradicts SAT $\in$ SIZE(n^c) for each fixed c if $max\rho, q < 1 + \epsilon$.
4. Audit the source claim without assuming SAT circuits. For each oracle position g, replace SAT on the finite image $R_{g,N}$ by a DNF table for satisfiable members of $R_{g,N}$, costing O(|R_{g,N}|L_N), or by exhaustive assignment enumeration, costing 2^{v_N}poly(L_N).
5. Summing over positions gives H_N in size O(N^rho)+poly(L_N) sum_g $min|R_{g,N}|, 2^{v_N}$.
6. Therefore any proposed source lower bound with $max\rho, e_{eff} < 1 + \epsilon$ by a margin is internally inconsistent; high positioned effective entropy becomes a necessary certificate.

Equation 1: target-substitution-size.

$$S_{\mathrm{SAT}}(N, c) \leq N^\rho + t_N L_N^c \,\mathrm{poly}(L_N) = N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT has nonuniform circuits of size n^c and every oracle query length is L_N=(log N)^d.

Equation 2: positioned-effective-entropy.

$$e_{\mathrm{eff}}(N) = \log_N \left(\sum_{g \in K_N} \min |R_{g,N}|, 2^{v_N} \right)$$

Valid when: Valid when each oracle position has a well-defined image over all N-bit inputs of H_N.

Equation 3: unconditional-range-upper-bound.

$$S_{\mathrm{uncond}}(N) \leq O(N^\rho) + \mathrm{poly}(L_N) \sum_g \min |R_{g,N}|, 2^{v_N} = N^{\max \rho, e_{\mathrm{eff}}+o(1)}$$

Valid when: Applies when oracle gates may be replaced by per-position range DNFs or exhaustive assignment checks.

Equation 4: magnification-implication.

$$H_N \notin SIZE(N^{1+\epsilon}) \ \wedge \ \max \rho, q < 1 + \epsilon \implies SAT \notin P/poly$$

Valid when: Requires the source lower bound to be valid in the same nonuniform circuit model used by the target substitution.

Equation 5: source-falsifier-threshold.

$$\max \rho, e_{\text{eff}} < 1 + \epsilon - \delta \implies H_N \in SIZE(N^{1+\epsilon-\delta/2})$$

Valid when: Valid when the entropy bound holds eventually and polylogarithmic replacement factors are absorbed by the δ margin.

Next analysis. Instantiate K_N from a specific extractor-like generator of polylog-length CNFs and compute $|R_g|$, v_N, q, and ρ exactly to see whether the positioned entropy threshold can be met without advice leakage.

Falsifiers.

- threshold collapse: $max\rho, q \geq 1 + \epsilon$ makes SAT substitution too large to contradict the source lower bound.
- positioned range entropy falsifier: sum_g min{|R_g|,2^v}<N^{1+epsilon-delta} yields an unconditional subthreshold circuit for H_N.
- low variable entropy: $q + v_N/log\ N < 1 + \epsilon$ by a margin lets exhaustive assignment simulation kill the source claim.
- nonuniform leakage: K_N may hide SAT answers in advice-like query selection or gate wiring, invalidating target preservation.
- model mismatch: a lower bound only for a restricted circuit class Γ does not imply NP $\not\subset$ P/poly without a separate lift.
- natural-proof obstruction: a large constructive property proving the source lower bound against P/poly would collide with standard PRG-based natural proofs barriers.

cycle-0018: Hardness-Magnification Bridge Realization: positioned entropy cover gate

Execution. research; azure_responses_api; attempt primary; 184.781 seconds; 3 lemmas, 4 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 18 proves the exact positioned entropy cover upper bound. The route now has two independent gates: target transfer needs $max\rho, q = N^{1+\epsilon-o(1)}$ after charging the generator. Low variable count or low positioned range is a concrete falsifier, not a folklore barrier.

Pressure. The derivation proves only an upper-bound/falsifier lemma. It does not prove $C(H_N) > N^{1+\epsilon}$ for any explicit high-entropy carrier.

Derivation steps.

1. Fix N and position i; let R_i be the set of formulas reachable as x varies.
2. For this position, build a nonuniform evaluator either by hardwiring SAT(y) for every y in R_i and comparing Gamma_{N,i}(x) to the dictionary, or by brute-force checking all 2^{v_i} assignments of the produced formula.

3. The cheaper evaluator costs $min|R_i|, 2^{v_i}\ L_N^{O(1)}$ gates, after Γ_N has produced the query bits.

4. Run the batched generator once, evaluate all M_N positioned queries, and OR the M_N answers.

5. This gives C(H_N)<=N^{rho+o(1)}+N^{q+o(1)}+B_N $L_N^{O(1)}$; taking the contrapositive yields the entropy threshold gate.

Equation 1: carrier_definition.

$$H_N(x) = \bigvee_{i=1}^{M_N} SAT(\Gamma_{N,i}(x)), \quad M_N = N^{q+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when the batched generator exposes all query positions and the SAT predicate is evaluated only on formulas of length L_N.

Equation 2: positioned_effective_entropy.

$$B_N = \sum_{i=1}^{M_N} \min |R_i|, 2^{v_i}, \quad \theta_N = \log_N B_N$$

Valid when: Valid when each position has its own range dictionary and variable bound, so ranges from different positions are not merged for free.

Equation 3: cover_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + N^{q+o(1)} + B_N \cdot L_N^{O(1)}$$

Valid when: Applies when nonuniform circuits may hardwire per-position dictionaries or instead brute-force all variables of each produced formula.

Equation 4: entropy_gate_contrapositive.

$$C(H_N) > N^{1+\epsilon} \ \wedge \ \max \rho, q < 1 + \epsilon \ \Rightarrow \ \theta_N \geq 1 + \epsilon - o(1)$$

Valid when: Requires the source lower bound, generator-size accounting, and positioned cover upper bound to hold on the same valid lengths.

Next analysis. Instantiate the affine-disperser generated-OR family and compute B_N exactly as a function of α, q, and clause density; then audit whether any known lower-bound technique for this restricted H_N avoids the natural-proofs density condition.

Falsifiers.

- positioned entropy falsifier: $B_N \leq N^{1+\epsilon-\delta}$ on infinitely many valid lengths gives subthreshold circuits for H_N.
- generator-cost falsifier: charged batched generation size $S_{charged}(\Gamma_N) \geq N^{1+\epsilon-o(1)}$ destroys the barely-superlinear magnification window.
- target-transfer falsifier: $max\rho, q \geq 1 + \epsilon$ means SAT circuit substitution no longer contradicts the source lower bound.

- variable-count falsifier: if $v_i \leq \alpha$ log N uniformly and $q + \alpha < 1 + \epsilon$, then $B_N \leq N^{q+\alpha+o(1)}$ and the source lower bound is impossible.
- natural-proof falsifier: a dense P/poly-constructive property proving the H_N lower bound is blocked under standard PRF assumptions, unless the certificate is non-natural or sufficiently sparse.

cycle-0019: Hardness-Magnification Bridge Realization: semantic range leakage gate

Execution. research; azure_responses_api; attempt primary; 174.05 seconds; 3 lemmas, 4 equations, 7 derivation steps, 7 falsifiers.

Learning. Cycle 19 sharpens the generated-OR route: positioned entropy is not the decisive source gate. The valid bridge uses the semantic cover $S_N = sum_j$ C_{R_{N,j}}(SAT). Subthreshold S_N is a concrete falsifier for H_N lower bounds, while $q, \rho < 1+\epsilon$ still gives the target-preserving implication from a valid H_N lower bound to SAT $\notin$ P/poly.

Pressure. The derivation does not supply an explicit G_N for which both H_N has a general-circuit lower bound $N^{1+\epsilon}$ and $S_N = sum_j$ C_{R_{N,j}}(SAT) is provably above $N^{1+\epsilon-o(1)}$.

Derivation steps.

1. Let $R_{N,j}$ be the j-th positioned range of the bulk generator G_N.
2. For each j, choose a minimum L-input circuit $D_{N,j}$ agreeing with SAT on $R_{N,j}$.
3. Build a circuit for H_N by computing the full list G_N(x), feeding the j-th formula to $D_{N,j}$, and OR-ing all M outputs.
4. This gives C(H_N)<=O(C(G_N)+sum_j $C_{R_{N,j}}$(SAT) + M L).
5. If SAT has global circuits of size n^c, take every $D_{N,j}$ to be the restriction of the L-bit SAT circuit; since L=(log N)^d, the substitution term is $N^{q+o(1)}$.
6. Thus a valid $N^{1+\epsilon}$ lower bound for H_N with $q, \rho < 1 + \epsilon$ refutes every fixed polynomial-size SAT circuit family.
7. Conversely, the same upper bound proves that any subthreshold aggregate positioned range decider is a falsifier for the claimed source lower bound.

Equation 1: semantic_upper_bound.

$$C(H_N) \leq O\left(C(G_N) + \sum_{j \leq M} C_{R_{N,j}}(\text{SAT}) + ML\right)$$

Valid when: Valid when G_N is a bulk circuit outputting all positioned queries and circuit size counts shared generator gates once.

Equation 2: global_sat_substitution.

$$\mathrm{SAT} \in \mathrm{SIZE}(n^c) \Rightarrow C(H_N) \leq N^{\rho} + N^{q}(\log N)^{dc} + N^{q+o(1)} = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the generated formulas have length L=(log N)^d and every fixed SAT circuit exponent contributes only $N^{o(1)}$ overhead.

Equation 3: magnification_consequence.

$$C(H_N) > N^{1+\epsilon} \ \wedge \ \max \rho, q < 1 + \epsilon \Rightarrow \mathrm{SAT} \notin \mathrm{P/poly}$$

Valid when: Requires the lower bound for H_N to hold eventually and the target transfer to preserve nonuniform circuit size.

Equation 4: semantic_gate.

$$C(H_N) > N^{1+\epsilon} \ \wedge \ q, \rho < 1 + \epsilon \Rightarrow \sum_{j \leq M} C_{R_{N,j}}(\mathrm{SAT}) \geq N^{1+\epsilon-o(1)}$$

Valid when: Valid when q and ρ are both strictly below the claimed source lower-bound exponent 1+epsilon.

Next analysis. Instantiate G_N with a concrete expander or extractor-based 3-CNF generator, compute $R_{N,j}$ structure, and test whether SAT on those positioned ranges collapses to a known easy subclass or requires a new semantic lower-bound certificate.

Falsifiers.

- semantic leakage falsifier: SAT restricted to the positioned ranges has aggregate circuit complexity below $N^{1+\epsilon-o(1)}$.
- threshold collapse: max{q,rho} reaches or exceeds 1+epsilon, so SAT substitution no longer contradicts the source lower bound.
- bulk-generator mismatch: G_N is only random-access with per-query cost N^{ρ}, changing the positive upper bound to about $N^{q+\rho}$.
- nonuniform leakage: the construction or proof accidentally supplies the positioned deciders $D_{N,j}$ as advice for H_N.
- low-label-complexity range: high B_N is achieved using formulas from classes where satisfiability is easy, such as Horn, 2-CNF, bounded treewidth, or planted trivially satisfiable instances.
- natural-proof obstruction: a constructive dense certificate that many SAT range labels evade small circuits would be natural; the surviving route must be sparse, non-natural, or use a nonrelativizing proof object.
- oracle falsifier probe: if an oracle makes all generated range labels simple while preserving the black-box interface, then a relativizing proof of the semantic gate cannot be valid.

cycle-0020: Hardness-Magnification Bridge Realization: Semantic Block-Cover Gate

Execution. research; azure_responses_api; attempt primary; 331.928 seconds; 2 lemmas, 4 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 20 sharpens the generated-OR route: the valid target bridge is unchanged, but the source plausibility gate must minimize over semantic block covers. Singleton range complexity is too weak because OR compression and nonuniform block advice can falsify an $N^{1+\epsilon}$ source lower bound. This is route-level progress, not a proof of P $\neq$ NP.

Pressure. No direct-sum theorem converts $M_N \geq N^{1+\epsilon-o(1)}$ into $C(H_N) > N^{1+\epsilon}$. A circuit for H_N may compute the union of positive preimages without decomposing along any chosen partition.

Derivation steps.

1. Fix N, $t = N^q$, L=(log N)^d, and generator G_N producing all query strings G_{N,1}(x),...,G_{N,t}(x).
2. Assume SAT_L has circuits of size L^c. Compute G_N once, feed the same SAT_L circuit to each of the t positions, and OR the answers; this gives size N^{rho+o(1)}+N^q $L^{c+O(1)}$.
3. Since L is polylogarithmic, any fixed SAT P/poly exponent contributes only $N^{o(1)}$ per query, so $maxq, \rho < 1 + \epsilon$ gives the valid contrapositive target implication.
4. For the source audit, take any nonuniform partition Pi of positions. For each block B, use an optimal range-restricted circuit D_B of size K_B deciding whether any generated formula in that block is satisfiable.
5. Compute G_N once, route each block tuple to D_B, then OR the block outputs. This yields C(H_N)<=N^{rho+o(1)}+N^{q+o(1)}+sum_B K_B.
6. Therefore a claimed lower bound $C(H_N) > N^{1+\epsilon}$ forces $M_N \geq N^{1+\epsilon-o(1)}$ whenever generator and routing costs have fixed slack below the threshold.
7. This repairs the previous semantic-cover gate: singleton S_N is only the partition into singletons and can miss block-level OR compression.

Equation 1: target_substitution.

$$SAT_L \in SIZE(L^c) \;\Rightarrow\; C(H_N) \leq N^{\rho+o(1)} + N^q L^{c+O(1)} = N^{\max \rho, q+o(1)}.$$

Valid when: Valid when the generator is shareable, all queries have length L=(log N)^d, and one nonuniform SAT_L circuit is reused for every generated query position.

Equation 2: magnification_contrapositive.

$$[\; C(H_N) > N^{1+\epsilon} \text{ eventually } \wedge\; \max q, \rho < 1 + \epsilon \;] \;\Rightarrow\; SAT \notin P/poly.$$

Valid when: Applies when SAT in P/poly would give some fixed exponent c and polylogarithmic query length makes L^c=N^{o(1)} under the target-preserving interface.

Equation 3: block_cover_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + N^{q+o(1)} + \sum_{B \in \Pi} K_B.$$

Valid when: Valid when Pi is any nonuniform partition of query positions and each K_B circuit decides the block OR predicate only on its generated tuple range R_B.

Equation 4: necessary_block_gate.

$$C(H_N) > N^{1+\epsilon} \;\Rightarrow\; M_N := \min_{\Pi} \sum_{B \in \Pi} K_B \geq N^{1+\epsilon-o(1)}.$$

Valid when: Requires the generator and routing overheads to be below $N^{1+\epsilon}$ by fixed polynomial slack so that a subthreshold block cover would contradict the source lower bound.

Next analysis. Instantiate M_N for a nontrivial generator without dominated coordinates, e.g. a universal verifier family whose queries are Cook-Levin encodings of polylog-size computations, and compute whether block predicates admit compression below $N^{1+\epsilon}$.

Falsifiers.

- block semantic collapse: $M_N < N^{1+\epsilon-o(1)}$ for a nonuniform partition even though singleton S_N appears large
- dominating coordinate: each block contains an always-satisfiable generated formula, making H_N or block predicates easy
- threshold collapse: $maxq, \rho \geq 1 + \epsilon$ invalidates the target-preserving magnification inequality
- nonuniform leakage: a source lower-bound argument ignores range-restricted per-block circuits that are legal in the general-circuit source model
- model mismatch: proving lower bounds only for uniform algorithms or restricted circuits does not imply the required nonuniform SIZE lower bound for H_N
- natural-proof pressure: a constructive large property proving the H_N lower bound against P/poly would need to be non-natural or outside the standard PRG-based natural proofs obstruction

cycle-0021: Hardness-Magnification Bridge Realization: Shared-Generator Semantic Block-Cover Gate

Execution. research; azure_responses_api; attempt primary; 135.544 seconds; 2 lemmas, 4 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 21 replaces the previous block-cover warning by an exact shared-generator semantic-cover lemma. The valid target bridge is unchanged, but the source lower bound must beat $C(G_N) + min_{Pi}\ sum_B$ C_{R_B}(OR-SAT_B). This creates a concrete falsifier: any subthreshold semantic block partition kills the generated-OR carrier before it can contribute to SAT $\notin$ P/poly.

Pressure. No candidate generator is known for which $min_{Pi}\ sum_B$ C_{R_B}(OR-SAT_B) can be proved at $N^{1+\epsilon-o(1)}$ in general circuits.

Derivation steps.

1. Let $M = N^q$ and let G_N(x) output the M formulas y_1(x),...,y_M(x) of length L=(log N)^d using $N^{\rho+o(1)}$ gates.
2. Fix a partition Pi of [M]. For each block B, define R_B as the set of generated tuples y_B(x) and choose a smallest circuit Q_B agreeing with OR_{j in B} SAT(y_j) on R_B.

3. Compose one copy of G_N with all Q_B circuits, wire each Q_B to its block tuple, and OR the block answers. This computes H_N exactly.

4. The resulting size is $N^{\rho+o(1)} + sum_B$ C_{R_B}(OR-SAT_B)+O(|Pi|), proving the shared-generator cover upper bound.

5. For singleton blocks, if SAT has $L^c - size$ circuits, then each block cost is at most L^c, giving C(H_N)<=N^{rho+o(1)}+N^qL^c and hence the target-preserving contradiction when $max\rho, q < 1 + \epsilon$.

6. Therefore a valid source lower bound must simultaneously rule out all nonuniform semantic block covers; otherwise the cover is an explicit falsifier.

Equation 1: $E1_{target,substitution,upper,bound}$.

$$C(H_N) \leq N^{\rho+o(1)} + N^q\, C(SAT_L) + O(N^q) \leq N^{\max\rho,q+o(1)}$$

Valid when: Valid when SAT has circuits of size L^c for a fixed c and L=(log N)^d makes L^c=N^{o(1)}.

Equation 2: $E2_{target,preserving,magnification}$.

$$\big(C(H_N) > N^{1+\epsilon} \text{ and } \max\rho, q < 1 + \epsilon\big) \Rightarrow SAT \notin P/poly$$

Valid when: Applies after the generated-OR carrier is target-clean and the lower bound holds against nonuniform circuits for all sufficiently large N.

Equation 3: $E3_{shared,block,cover,upper,bound}$.

$$C(H_N) \leq C(G_N) + \min_{\Pi} \left(\sum_{B\in\Pi} C_{R_B}(OR\text{-}SAT_B) + O(|\Pi|) \right)$$

Valid when: Valid when each block circuit only needs to agree on the realized tuple range emitted by the shared generator.

Equation 4: $E4_{source,gate,consequence}$.

$$C(H_N) > N^{1+\epsilon} \Rightarrow \forall\Pi :\ C(G_N) + \sum_{B\in\Pi} C_{R_B}(OR\text{-}SAT_B) \geq N^{1+\epsilon-o(1)}$$

Valid when: Requires the claimed source lower bound to be stronger than every semantic block-cover upper bound, including nonuniform block advice.

Next analysis. Run the block-size thought experiment for $b = N^\theta$: derive upper bounds on U(theta) from range cardinality, feature compression, and OR compression, then identify whether any θ gives N^{rho}+N^{q-theta}U(theta)<N^{1+epsilon}.

Falsifiers.

- semantic block-cover collapse: some partition Pi has $C(G_N)+sum_B\ C_{R_B}(OR{-}\mathrm{SAT}_B) < N^{1+\epsilon-\delta}$
- range-compression falsifier: block OR-SAT values factor through short features A_B with total cost below the claimed threshold
- nonuniform block advice leakage: Q_B encodes the satisfiability pattern on the realized range and bypasses the intended SAT hardness
- generator output-size tax: producing all query bits already forces ρ or q to violate $max\rho, q < 1+\epsilon$
- lookup boundary failure: $d \leq 1$ with constants allowing truth-table lookup below $N^{1+\epsilon}$
- natural-proof obstruction: a large constructive method proving the source lower bound for many generated carriers would distinguish pseudorandom functions, so a valid proof must be range-specific or non-natural

cycle-0022: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 128.185 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 22 isolates the next exact gate: the generated-OR bridge is valid only if the source lower bound defeats nonuniform promise solvers on the actual SAT range. The new quantitative obstruction is $T_N > N^{1+\epsilon-q-o(1)}$ for SAT restricted to U_N, plus the earlier semantic block-cover threshold. This is route-level progress, not a proof of P $\neq$ NP.

Pressure. No current argument proves the required promise-SAT or block-cover lower bound for an explicit high-entropy generated range U_N; entropy and query length do not imply semantic circuit hardness.

Derivation steps.

1. Fix c and assume SAT has length-n circuits of size n^c.
2. For each N, copy the length-L SAT circuit into each of the $M = N^q$ query positions produced by G_N.
3. The resulting circuit for H_N has size N^rho+N^q(log N)^{dc}+O(N^qL)=N^{max{rho,q}+o(1)}.
4. If $max\rho, qN^{1+\epsilon}$ contradicts the assumed SAT circuits, giving the route-level target consequence SAT $\notin$ P/poly.
5. Now audit the source claim: if SAT restricted to U_N has promise circuits of size T_N, the same substitution gives C(H_N)<=N^rho+N^qT_N+O(N^qL).
6. Therefore any source lower bound must also prove $C_{U_N}(\mathrm{SAT}) > N^{1+\epsilon-q-o(1)}$ and must beat all semantic block covers.

Equation 1: carrier_definition.

$$H_N(x) = \bigvee_{j=1}^{M} \mathrm{SAT}(G_{N,j}(x)), \quad M = N^q, \quad L = (\log N)^d$$

Valid when: Valid when G_N is a fixed nonuniform generator family and x ranges over N-bit seeds.

Equation 2: target_substitution_transfer.

$$\mathrm{SAT} \in \mathrm{SIZE}(n^c) \Rightarrow C(H_N) \leq N^\rho + N^q(\log N)^{dc} + O(N^q L) = N^{\max \rho, q+o(1)}$$

Valid when: Applies when each generated query has length L and the SAT circuit is copied for every query position.

Equation 3: restricted_solver_falsifier_bound.

$$C_{U_N}(\mathrm{SAT}) \leq T_N \Rightarrow C(H_N) \leq N^\rho + N^q T_N + O(N^q L)$$

Valid when: Valid when one length-L circuit decides SAT correctly on the generated union range U_N.

Equation 4: necessary_range_hardness.

$$C(H_N) > N^{1+\epsilon} \ \wedge \ \rho < 1 + \epsilon \Rightarrow C_{U_N}(\mathrm{SAT}) > N^{1+\epsilon-q-o(1)}$$

Valid when: Requires the generated-OR lower bound and the copied restricted solver upper bound to be compared at the same N.

Next analysis. Instantiate G_N with a high-entropy family of polylog-size 3-CNF formulas and compute the best promise solver or block-cover upper bound; vary τ to locate the first threshold-respecting candidate.

Falsifiers.

- falsifier: $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$ collapses the target threshold before SAT hardness transfers.
- falsifier: a promise solver for SAT on U_N of size at most $N^{1+\epsilon-q-o(1)}$ gives a direct small circuit for H_N.
- falsifier: a semantic block partition with total cost below $N^{1+\epsilon-o(1)}$ kills the generated-OR lower bound.
- falsifier: a generator whose formulas lie in a syntactically rich but semantically easy SAT family defeats entropy-only lower-bound arguments.
- falsifier: advice depending on N but not on x is allowed in P/poly and must be charged in every valid source-model audit.

cycle-0023: Hardness-magnification bridge realization: generated-OR range-balance gate

Execution. research; azure_responses_api; attempt primary; 122.213 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 23 adds an exact range-label balance gate. Even with q,rho in the valid target window, a generated-OR carrier is source-plausible only if both satisfiable and unsatisfiable parts of its actual generated range exceed $N^{1+\epsilon-q-o(1)}$. This is a concrete falsifier derived from equality-DNF membership circuits, independent of vague barrier folklore.

Pressure. No explicit generator is known whose H_N beats unrestricted $N^{1+\epsilon}$ circuits while also defeating range-label imbalance, promise solvers on U_N, and semantic block-cover compression.

Derivation steps.

1. Fix N and let K^+=|U_N^+|, K^-=|U_N^-|.
2. If K^+<=K^-, build a membership circuit Pos_N(y)=OR_{z in U_N^+}[y=z] of size O(K^+ L). Then $H_N(x) = OR_j$ Pos_N(G_{N,j}(x)) on every x.
3. If K^-<K^+, build Neg_N(y)=OR_{z in U_N^-}[y=z] of size O(K^- L). Then $H_N(x) = NOT\ AND_j$ Neg_N(G_{N,j}(x)), since every generated query lies in U_N.
4. Composing either membership circuit with the charged all-query generator gives C(H_N)<=C(G_N)+O(M L min{K^+,K^-})+O(M).
5. With $M = N^{q+o(1)}$, $L = N^{o(1)}$, and $C(G_N)N^{1+\epsilon}$ lower bound with $rhoN^{1+\epsilon-q-o(1)}$.
6. The target substitution calculation is unchanged: if SAT has size n^c circuits, composing those circuits with G_N gives $C(H_N) \leq N^{max\rho,q+o(1)}$, contradicting the source lower bound when $max\rho, q < 1 + \epsilon$.

Equation 1: carrier_definition.

$$H_N(x) = \bigvee_{j=1}^{M} SAT(G_{N,j}(x)), \qquad M = N^{q+o(1)}, \quad L = (\log N)^d.$$

Valid when: Valid when the generated queries are fixed nonuniformly for length N and their encoding length is polylogarithmic in the carrier input length.

Equation 2: range_balance_upper_bound.

$$C(H_N) \leq C(G_N) + O\big(ML \min |U_N^+|, |U_N^-|\big) + O(M).$$

Valid when: Valid when membership in the smaller labeled generated range is implemented by equality-DNF circuits and all generator cost is charged once.

Equation 3: necessary_balance_threshold.

$$C(H_N) > N^{1+\epsilon} \ \wedge \ C(G_N) \leq N^{\rho+o(1)} \ \wedge \ \rho < 1 + \epsilon \Rightarrow \min |U_N^+|, |U_N^-| > N^{1+\epsilon-q-o(1)}.$$

Valid when: Applies after the range-balance upper bound is compared with the claimed barely-superlinear source lower-bound threshold.

Equation 4: target_substitution_bound.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N) \leq N^{\rho+o(1)} + N^{q+o(1)}L^c = N^{\max \rho, q+o(1)}.$$

Valid when: Requires the target-preserving transfer where each generated SAT query is answered by the same nonuniform SAT circuit without extra advice leakage.

Next analysis. Instantiate a template generator for polylog-length 3CNFs and estimate $\theta = min$ label-support exponent; then compare it with 1+epsilon-q and with the best promise-SAT solver size on the generated template range.

Falsifiers.

- range-label imbalance falsifier: either $|U_N^+|$ or $|U_N^-|$ is at most $N^{1+\epsilon-q-o(1)}$, yielding a valid subthreshold circuit for H_N.
- promise-solver falsifier: SAT restricted to U_N has nonuniform circuits of size at most $N^{1+\epsilon-q-o(1)}$.
- semantic block-cover falsifier: a partition of query positions has total charged OR-SAT block complexity below $N^{1+\epsilon-o(1)}$.
- threshold-collapse falsifier: $q \geq 1+\epsilon$ or $\rho \geq 1+\epsilon$ destroys the barely-superlinear magnification window.
- nonuniform leakage falsifier: uncharged advice encoding SAT labels on the generated range makes the source lower bound ill-posed.

cycle-0024: Hardness-Magnification Bridge Realization: hitting-cover gate for generated-OR carriers

Execution. research; azure_responses_api; attempt primary; 156.244 seconds; 2 lemmas, 4 equations, 6 derivation steps, 7 falsifiers.

Learning. Cycle 24 sharpens the generated-OR route from label balance to exact hitting-cover hardness. The valid target bridge is unchanged, but the source lower bound must now defeat nonuniform covers of positive fibers and negative product fibers of total size $N^{1+\epsilon-o(1)}$. This gives a new concrete falsifier and shows that high semantic range entropy alone cannot justify the carrier.

Pressure. No current argument lower-bounds the exact hitting-cover parameter κ for an explicit target-clean generator; raw semantic range size, variable entropy, and label balance all allow small-cover falsifiers.

Derivation steps.

1. Defined positive hitting covers and negative product covers on the actual generated SAT ranges R_j.
2. Built a circuit by first computing the shared generator G_N, then testing each output against the selected nonuniform label sets with equality ORs of cost O(L|K_j|).
3. For a positive cover, correctness follows because negative inputs generate only unsatisfiable formulas, while every positive input is hit by some selected satisfiable formula.

4. For a negative cover, the AND of unsatisfiable-membership tests computes the complement of H_N^G exactly, because every positive input has at least one satisfiable query outside every K_j^-.

5. Combined the cover circuit with the existing SAT-substitution upper bound to isolate two independent gates: target transfer $max\rho, qN^{1+\epsilon-o(1)}$.

6. Tried to derive κ lower bounds from cycle-23 label balance, but a planted-template plus decoy construction separates label balance from hitting-cover size.

Equation 1: generated_or_definition.

$$H_N^G(x) = \bigvee_{j=1}^{M} SAT(G_{N,j}(x)), \quad M = N^q, \quad L = (\log N)^d$$

Valid when: Valid when G_N is a shared multi-output generator and each output string encodes a SAT instance of length L.

Equation 2: target_substitution_upper_bound.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^G) \leq O(N^\rho + ML^c + M) = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the reduction preserves nonuniform size accounting and the query length is polylogarithmic in N.

Equation 3: hitting_cover_upper_bound.

$$C(H_N^G) \leq O(N^\rho + M + L \cdot \min \kappa_N^+, \kappa_N^-)$$

Valid when: Valid when the selected covers are exact on positive or negative fibers and membership is tested by equality circuits.

Equation 4: necessary_cover_threshold.

$$C(H_N^G) > N^{1+\epsilon} \Rightarrow \min \kappa_N^+, \kappa_N^- > \Omega((N^{1+\epsilon} - N^\rho - M)/L) = N^{1+\epsilon-o(1)}$$

Valid when: Requires ρ and q to stay below 1+epsilon so generator and OR costs do not already meet the threshold.

Next analysis. Formalize the minimum cover parameter as a bipartite set-cover problem between input fibers and generated SAT labels; test whether known disperser/extractor-style generators can force $kappa_N > N^{1+\epsilon-o(1)}$ without reintroducing nonuniform leakage.

Falsifiers.

- hitting-cover collapse: $kappa_N \leq N^{1+\epsilon-o(1)}/L$ gives a direct subthreshold circuit for H_N^G
- planted satisfiable template: every positive input emits one of few canonical SAT formulas despite large decoy ranges

- negative product cover: all negative inputs use a small per-position family of unsatisfiable formulas
- semantic block-cover compression from earlier cycles can dominate singleton cover counts
- nonuniform leakage through length-dependent equality tables for selected generated labels
- model mismatch if G_N must be replicated M times rather than charged once as a shared multi-output circuit
- target threshold collapse if max{rho,q} $\geq$ 1+epsilon, independent of cover size

cycle-0025: Generated-OR magnification: selector-range leakage gate

Execution. research; azure_responses_api; attempt primary; 108.203 seconds; 3 lemmas, 3 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 25 adds a shared-selector leakage gate. A generated-OR carrier can be easy via one compact selector and a promise SAT solver on only the selected image, even when additive semantic or hitting covers look expensive. Thus the valid source obligation is not merely high range entropy or label balance; it is lower bounding every selector-plus-selected-range-solver pair above $N^{1+\epsilon-o(1)}$ while preserving $q, \rho < 1 + \epsilon$ for the target bridge.

Pressure. Need a direct-sum or shared-computation lower bound converting any small selector/promise-solver circuit into a subthreshold cycle-24 cover. No such theorem is available, and it is plausibly false for structured selectors.

Derivation steps.

1. Start with the cycle-24 condition that positive fibers and negative product fibers have no subthreshold nonuniform hitting cover.
2. Try to conclude $C(H_N) > N^{1+\epsilon}$ by arguing every H_N circuit induces such a cover.
3. Observe that a circuit can first compute a shared selector Sel_N(x) and query only G_N(x,Sel_N(x)).
4. The induced cover over decoded selector values may have large additive cost because shared gates are replicated when charged per fiber.
5. Therefore additive hitting-cover hardness does not exclude selector-plus-promise-solver circuits.

Equation 1: selector_upper_bound.

$$C(H_N) \leq C(G_N) + C(Sel_N) + C(P_N) + N^{o(1)}$$

Valid when: Valid when Sel_N is a genuine positive selector and P_N is correct on the complete selected image V_S.

Equation 2: source_obstruction.

$$C(H_N) > N^{1+\epsilon} \Rightarrow C(Sel_N) + C(P_N) \geq N^{1+\epsilon-o(1)}$$

Valid when: Applies after generator overhead is below threshold and the asserted lower bound is in the same nonuniform circuit model.

Equation 3: target_transfer_unchanged.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N) \leq N^{\rho+o(1)} + N^q(\log N)^{dc} = N^{\max \rho,q+o(1)}$$

Valid when: Requires fixed target exponent c, polylogarithmic query length, and generator substitution preserving the nonuniform size accounting.

Next analysis. Instantiate Sel_N for simple generator templates, including lexicographic first-satisfying-query generators and hash-bucketed query generators, and compute whether selected-image lookup already drops below $N^{1+\epsilon}$.

Falsifiers.

- Small valid selector plus small promise solver on V_S computes H_N below threshold.
- Selected-image equality-DNF lookup with $|V_S| < N^{1+\epsilon-o(1)}$ falsifies the claimed source lower bound.
- Shared computation collapse: additive hitting-cover lower bounds may miss one compact selector circuit.
- Nonuniform leakage through hardwired SAT labels on the selected image remains a route-level falsifier.
- If $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$, the target transfer threshold collapses even before selector leakage is considered.

cycle-0026: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 136.529 seconds; 2 lemmas, 5 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 26 adds an approximate-selector gate. Exact witness selection was too weak as a source audit: even a selector wrong on N^{δ} inputs collapses H_N below $N^{1+\epsilon}$ when $deltaN^{1+\epsilon-o(1)}$, while the clean target bridge $q, \rho < 1 + \epsilon$ remains intact.

Pressure. No concrete E_N is known for which $Lambda_N > N^{1+\epsilon-o(1)}$ can be proved in unrestricted circuits; proving it appears to require non-natural, selector-resistant lower-bound machinery rather than entropy counting.

Derivation steps.

1. Fix $sigma_N$ and P_N, and compute A(x)=P_N(E_N(x,sigma_N(x))).
2. On inputs outside $B_{sigma,\mathrm{P}}$, A(x)=H_N(x) by definition of the bad set.
3. For each bad input b, add an equality gate EQ_b(x); XOR A with OR_{b in B} EQ_b(x) to flip exactly the wrong outputs.
4. The correction costs O(N|B|), while selector, extractor, and promise solver costs add linearly up to standard fan-in overhead.
5. Thus any sparse-error approximate selector with small selected-range SAT solver gives a subthreshold circuit for H_N and refutes the proposed source lower bound.
6. Combining this with the clean target bridge shows the remaining route obligation is a minimax lower bound against all approximate selector-plus-promise-solver pairs.

Equation 1: generated_or_carrier.

$$H_N(x) = \bigvee_{j<t(N)} SAT(E_N(x,j)), \qquad t(N) = N^q, \quad L(N) = (\log N)^d.$$

Valid when: Valid when the source carrier is the explicit generated-OR family with named query count, query length, and coordinate extractor.

Equation 2: clean_target_substitution.

$$SAT_L \in SIZE(L^c) \implies C(H_N) \le N^{\rho+o(1)} + N^q L^c = N^{\max \rho, q+o(1)}.$$

Valid when: Applies after the reduction preserves nonuniform size accounting and $L(N)^c$ is subpolynomial for every fixed target exponent c.

Equation 3: approx_selector_upper_bound.

$$C(H_N) \le C(\sigma_N) + C(E_N) + C(P_N) + O(L + \log t) + O(N\,|B_{\sigma,P}|).$$

Valid when: Valid when P_N agrees with SAT on the selected image and the remaining disagreements are corrected by nonuniform equality tests.

Equation 4: bad_set_threshold.

$$|B_{\sigma,P}| \le N^\delta \implies O(N|B_{\sigma,P}|) \le N^{1+\delta+o(1)}.$$

Valid when: Requires the correction to be by explicit exceptional-input advice in unrestricted circuits over N-bit carrier inputs.

Equation 5: source_obligation_minimax.

$$\Lambda_N := \min_{\sigma,P} C(\sigma_N) + C(E_N) + C(P_N) + N|B_{\sigma,P}| > N^{1+\epsilon-o(1)}.$$

Valid when: Necessary when an $N^{1+\epsilon}$ lower bound for H_N is asserted in the same unrestricted circuit model.

Next analysis. Instantiate the thought experiment with a block generator E_N whose coordinates are grouped into planted easy and hard ranges; compute the smallest δ forced by coverage of positive inputs and test whether selected-range promise SAT stays subthreshold.

Falsifiers.

- approximate-selector falsifier: a selector correct except on $N^{\epsilon-\eta}$ carrier inputs plus a subthreshold selected-range promise solver gives H_N circuits below $N^{1+\epsilon}$
- exact-selector leakage from cycle 25 remains a special case with empty bad set
- threshold collapse if $maxq, \rho \geq 1 + \epsilon$ in the clean target substitution
- lookup falsifier when query length and variable entropy make SAT on the generated range tabulatable below the source threshold
- nonuniform leakage through a compact selected image U_{sigma} with easy promise SAT despite high full-range entropy
- natural-proof risk: a large constructive property proving selector-cover hardness for many generators would conflict with standard P/poly pseudorandom-function assumptions

cycle-0027: Hardness-Magnification Bridge Realization: approximate list-selector leakage gate

Execution. research; azure_responses_api; attempt primary; 140.568 seconds; 2 lemmas, 4 equations, 4 derivation steps, 5 falsifiers.

Learning. Cycle 27 upgrades the source audit from approximate single selectors to approximate list selectors. The valid target-preserving bridge is unchanged, but a short list plus a promise solver can decide H_N without computing a canonical witness. Therefore any contribution-making lower-bound attempt must lower-bound $Lambda_N^{list}$; otherwise the route has a concrete nonuniform-leakage falsifier.

Pressure. Witness canonicalization is semantic; it is not available from the selector circuit alone and can be bypassed by list-wise OR evaluation.

Derivation steps.

1. Start with an approximate t-list selector A_N and attempt to pick the lexicographically first selected satisfiable query.
2. To choose that index the circuit must know SAT labels on all selected formulas, so the reduction imports a promise solver S_N on U_A.
3. Once S_N is imported, the decision circuit ORs the t answers and no longer needs a single witness index.
4. The cost is $C(A_N) + t_N\ C(S_N) + exception$ correction, which can be subthreshold even if every single selector is hard.

Equation 1: target_substitution_bridge.

$$SAT_{L_N} \in SIZE(L_N^c) \Rightarrow C(H_N) \leq N^{\max \rho, q+o(1)}$$

Valid when: Valid when the source carrier uses the named batched generator interface and c,d are fixed constants.

Equation 2: list_selector_leakage_bound.

$$C(H_N) \leq O(C(A_N) + C(G_N^{batch}) + t_N(C(S_N) + L_N^{O(1)}) + N|E_A|)$$

Valid when: Applies when the selected formulas are generated inside the same nonuniform circuit and all selector errors are explicitly corrected.

Equation 3: exponent_form_batched.

$$C(H_N) \leq N^{\max a, \rho, \tau+b, 1+\delta+o(1)}$$

Valid when: Valid when G_N has batched cost N^ρ independent of the chosen list length exponent τ.

Equation 4: source_obligation_minimax.

$$\Lambda_N^{list}(\tau, \delta) := \min_{A,S,E} \left(C(A) + C(G_N^{batch}) + t_N C(S) + N|E|\right) > N^{1+\epsilon-o(1)}$$

Valid when: Requires the lower-bound proof to quantify over all nonuniform selectors, solvers, and exception sets in the source model.

Next analysis. Instantiate G_N with a high-entropy expander/hash-generated SAT family and compute whether any tau=O(epsilon/2) list selector has a selected image admitting a subthreshold promise solver.

Falsifiers.

- Approximate list selector falsifier: $maxa, \rho, \tau + b, 1 + \delta < 1 + \epsilon$ yields a small circuit for H_N.
- Target threshold falsifier: $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$ destroys the magnification implication even if the source lower bound is true.
- Generator-interface falsifier: if selected generation costs $N^{\rho+\tau}$ rather than N^ρ, all exponent inequalities must be recomputed before calling the bridge valid.
- Promise-range falsifier: SAT may be easy on the selected image U_A although hard on the full generated range.
- Exception-leakage falsifier: $|E_A| \leq N^\delta$ with $\delta < \epsilon$ is removable by equality advice at cost below the claimed lower-bound threshold.

cycle-0028: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 129.075 seconds; 3 lemmas, 4 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 28 identifies an additional leakage mode: many imperfect list selectors can collectively cover the positive fiber. The valid source audit is the ensemble cover complexity Xi_N^{ens}; single-selector minimax lower bounds are insufficient for this generated-OR magnification route.

Pressure. No lower-bound method is known for Xi_N^{ens} against fully nonuniform selected-image promise solvers; ensemble covers can exploit semantic clusters invisible to entropy counts.

Derivation steps.

1. Fix $H_N(x) = OR_j$ SAT(G_N(x,j)) with $M = N^q$ and L=(log N)^d.
2. Given an ensemble, build C_i(x)=OR_{j in A_i(x)} B_i(G_N(x,j)) for each selector-solver pair.
3. If $H_N(x) = 0$, every generated formula is unsatisfiable, so all $C_i(x) = 0$ by selected-image correctness.
4. If $H_N(x) = 1$ and x is covered, some $C_i(x) = 1$ because its list contains a satisfiable generated formula.
5. Patch the E uncovered positive strings by an equality-DNF of size O(NE).
6. Share the generator access circuitry once and sum selector, solver-copy, and patch costs to obtain the ensemble upper bound.
7. Under SAT $\in$ SIZE(n^c), choose one selector listing all N^q indices and recover $C(H_N) \leq N^{max\rho,q+o(1)}$.

Equation 1: generated_or_definition.

$$H_N(x) = \bigvee_{j\in[M]} SAT(G_N(x,j)), \quad M = N^q, \quad L = (\log N)^d.$$

Valid when: Valid when the source generator is explicitly named and the H_N input length is N.

Equation 2: ensemble_cover_upper_bound.

$$C(H_N) \leq O\left(N^\rho + \sum_{i=1}^{R}(S_i + K_i(T_i + N^{o(1)})) + NE\right).$$

Valid when: Applies when each selected-image solver is correct and residual positives are patched by equality circuits.

Equation 3: exponent_form.

$$R \leq N^\theta,\ S_i \leq N^\alpha,\ K_i \leq N^\lambda,\ T_i \leq N^\tau,\ E \leq N^\delta \Rightarrow C(H_N) \leq N^{\max\rho,\theta+\alpha,\theta+\lambda+\tau,1+\delta+o(1)}.$$

Valid when: Requires uniform exponent bounds for every ensemble member and polylogarithmic generator overhead.

Equation 4: target_all_query_special_case.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N) \leq N^{\max \rho, q+o(1)}.$$

Valid when: Valid when the selector lists all N^q queries and L^c=N^{o(1)} for fixed c.

Next analysis. Estimate Xi_N^{ens} for a random high-entropy generator by a union-bound model over ensembles, then isolate which part of the argument can survive explicitness and avoid natural-proof leakage.

Falsifiers.

- falsifier: an ensemble of N^θ list selectors with $\theta + \lambda + \tau < 1 + \epsilon$ and residual $E < N^{\epsilon - o(1)}$ collapses the source lower bound.
- falsifier: selected-image SAT is promise-easy even though unrestricted SAT on L-bit formulas is hard.
- falsifier: $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$ causes quantitative threshold collapse in the target bridge.
- falsifier: a natural dense property proving Xi_N^{ens} large would collide with standard natural-proofs concerns unless it is generator-specific and non-natural.
- falsifier: hidden advice in selectors depending on x beyond the input circuit model invalidates target preservation.

cycle-0029: Hardness-Magnification Bridge Realization: one-sided separating-ensemble leakage gate

Execution. research; azure_responses_api; attempt primary; 295.993 seconds; 3 lemmas, 4 equations, 6 derivation steps, 4 falsifiers.

Learning. Cycle 29 sharpens the generated-OR source audit from ensemble list selectors to one-sided selected-image separators. The valid target bridge still needs only $q, \rho < 1 + \epsilon$, but the source lower bound must now beat Psi_N^{sep}; small local labelers are a concrete falsifier even when they do not solve SAT globally.

Pressure. No available lower-bound method rules out arbitrary selected-image separators B_t. These labelers need not be SAT algorithms, so the target SAT hardness hypothesis does not exclude them.

Derivation steps.

1. Fix an ensemble of R selectors A_t, each producing s indices into the N^q generated SAT queries.
2. For each pair (t,u), build a circuit that computes j=A_t(x,u), then y=G_N(x,j), then the selected-image label B_t(y).
3. OR all R*s outputs. By the separation promise, this computes H_N on all x outside E_N.
4. Hardwire the exceptional inputs by equality gates and override the answer on E_N, with cost $N|E_N|$ up to subpolynomial factors.

5. The resulting circuit has size at most R*s*(N^a+N^rho+N^b) plus exception cost, giving N^{r+ell+max{a,rho,b}+o(1)}+N^{1+delta+o(1)}.

6. Therefore any claimed $N^{1+\epsilon}$ lower bound for H_N is valid only if every such separating ensemble exceeds the same exponent threshold.

Equation 1: carrier-definition.

$$H_N(x) = \bigvee_{j<N^q} SAT(G_N(x,j)), \qquad L = (\log N)^d.$$

Valid when: Valid when the generated carrier and SAT-query length map are fixed before proving any lower bound.

Equation 2: separator-circuit.

$$D_N(x) = \bigvee_{t<R} \bigvee_{u<s} B_t(G_N(x, A_t(x,u))).$$

Valid when: Valid when the selector ensemble separates H_N correctly outside the explicitly hard-wired exception set.

Equation 3: separator-upper-bound.

$$C(H_N) \le N^{r+\ell+\max a,\rho,b+o(1)} + N^{1+\delta+o(1)}.$$

Valid when: Applies after all selector, generator, labeler, OR fanin, and exception-correction costs are charged nonuniformly.

Equation 4: source-audit-threshold.

$$\Psi_N^{sep} > N^{1+\epsilon-o(1)}.$$

Valid when: Required when the advertised source lower bound is meant to survive all one-sided separating-ensemble leakage.

Next analysis. Try to lower-bound or construct Psi_N^{sep} for a random-like generator: estimate whether selected positive and negative images admit $N^b - size$ separators when $R = N^r$ and $s = N^{ell}$ are below the magnification threshold.

Falsifiers.

- A one-sided separating ensemble with $r + ell + maxa, \rho, b < 1 + \epsilon$ and exception exponent $\delta < \epsilon$ falsifies the source lower-bound claim.
- A small selected-image labeler B_t that is not a valid SAT solver still leaks enough nonuniform information to collapse H_N.
- If $q \ge 1 + \epsilon$ or $\rho \ge 1 + \epsilon$, the target bridge has threshold collapse even before source leakage is considered.
- If the length map L=(log N)^d does not cover SAT lengths with controlled rounding, the target-preserving consequence is invalid.

cycle-0030: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 154.031 seconds; 3 lemmas, 3 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 30 replaces the one-sided selected-image audit by the weaker and more dangerous relaxed bag-separator audit. The valid target bridge is unchanged, but the source lower bound must defeat predicates that merely hit one positive witness per positive bag and avoid all negative-bag formulas. This exposes a concrete nonuniform-leakage falsifier not captured by promise SAT hardness.

Pressure. The converse is false or at least unproved: absence of small relaxed formula separators does not imply H_N is hard, because an arbitrary H_N circuit may exploit input-level structure that does not factor through a formula predicate.

Derivation steps.

1. Define A_N on $length - L_N$ formulas with negative avoidance and positive hitting over generated bags.
2. Build a circuit for H_N by computing G_N(x), applying A_N to each of the t_N formulas, and ORing the answers.
3. Size accounting gives C(H_N)<=N^{rho+o(1)}+N^q(size(A_N)+poly(L_N)).
4. Therefore a claimed lower bound $C(H_N) > N^{1+\epsilon-o(1)}$ forces $size(A_N) > N^{1+\epsilon-q-o(1)}$ whenever $\rho < 1 + \epsilon$.
5. Taking A_N to be a genuine SAT circuit recovers the target bridge: SAT $\in$ SIZE(L^c) would imply $C(H_N) \leq N^{max\rho,q+o(1)}$.

Equation 1: relaxed_separator_conditions.

$$H_N(x) = 0 \Rightarrow \sum_{j \leq t_N} A_N(\phi_{N,j}(x)) = 0, \qquad H_N(x) = 1 \Rightarrow \sum_{j \leq t_N} A_N(\phi_{N,j}(x)) \geq 1.$$

Valid when: Valid when H_N is exactly the OR of SAT labels on the generated bag and A_N is only required to hit each positive bag once.

Equation 2: separator_upper_bound.

$$C(H_N) \leq C(G_N) + O(t_N(\text{size}(A_N) + L_N)) = N^{\max \rho, q+\tau+o(1)} \quad \text{if size}(A_N) = N^{\tau}.$$

Valid when: Applies after the generator outputs explicit formulas and the same separator circuit is reused on all t_N query positions.

Equation 3: necessary_source_audit.

$$C(H_N) > N^{1+\epsilon-o(1)} \implies \text{SepHit}_N > N^{1+\epsilon-q-o(1)} \quad \text{provided } \rho < 1 + \epsilon.$$

Valid when: Requires the generated-OR source lower bound to be measured against unrestricted nonuniform circuits with subthreshold generator overhead.

Next analysis. Formalize $SepHit_N$ as a bipartite hitting-avoidance problem between positive bags and negative formula occurrences, then test whether random-looking generators satisfy the required lower bound by a counting argument and where explicitness breaks the argument.

Falsifiers.

- A planted syntactic marker present in one satisfiable formula of every positive bag and absent from all negative bags gives a small separator falsifier.
- A statistical artifact distinguishing positive witness formulas from negative-bag formulas yields $C(H_N) \leq N^q$ poly(L_N) despite possible SAT hardness on U_N.
- If $q \geq 1 + \epsilon$, even superconstant separator lower bounds cannot preserve the barely-superlinear threshold.
- If $\rho \geq 1 + \epsilon$, the generator alone violates the valid magnification window.
- If the source proof only lower-bounds promise SAT on U_N, it misses relaxed separators and leaves nonuniform leakage open.

cycle-0031: Hardness-Magnification Bridge Realization: approximate relaxed bag separators

Execution. research; azure_responses_api; attempt compact_retry; 989.176 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 31 converts relaxed bag separators into an approximate threshold lemma: E bad bags cost NE gates, so errors below N^ϵ are nonuniformly patchable. The valid source obligation is now an approximate distribution-local separator lower bound, not merely promise SAT hardness.

Pressure. We still lack a lower bound against all distribution-local approximate bag separators; global promise-SAT hardness does not rule out local predicates tuned to the generated bags.

Derivation steps.

1. Assume H_N has $C(H_N) > N^{1+\epsilon-o(1)}$ and $q, \rho < 1 + \epsilon$ on the same valid lengths.
2. Given A_N, compute all generated formulas with the shared N^ρ generator, apply A_N to each of N^q queries, and OR the answers.
3. The resulting circuit agrees with H_N except on E bags; add equality tests for those inputs and hardwire the correct bit, costing O(NE).
4. If $s = N^{sigma}$ and $E = N^\eta$ with $max\rho, q + sigma, 1 + \eta < 1+\epsilon$, the patched circuit contradicts the source lower bound.

Equation 1: carrier.

$$H_N(x) = \bigvee_{j \leq N^q} SAT(G_{N,j}(x)), \quad |G_{N,j}(x)| = (\log N)^d$$

Valid when: Valid when the carrier uses fixed generated query bags and shared generator parameters.

Equation 2: separator_collapse.

$$C(H_N) \leq O(N^{\rho} + N^{q}s + NE)$$

Valid when: Applies when a size-s bag separator fails on at most E input bags and exceptions are patched nonuniformly.

Equation 3: audit_threshold.

$$s = N^{\sigma}, E = N^{\eta} \Rightarrow \max \rho, q + \sigma, 1 + \eta \geq 1 + \epsilon - o(1)$$

Valid when: Requires the source lower bound and collapse inequality in the same circuit model and valid-length family.

Next analysis. Try a collision-balanced generator and estimate whether majority/hash-based local predicates yield $s = N^{o(1)}$ with $E < N^{\epsilon}$; if yes, quarantine this carrier family.

Falsifiers.

- Approximate separator falsifier: a local A_N with $s < N^{1+\epsilon-q-o(1)}$ and $E < N^{\epsilon-o(1)}$ collapses H_N below threshold.
- Exception-patching falsifier: even rare bag errors are harmless to circuits when $NE < N^{1+\epsilon-o(1)}$.
- Distribution leakage falsifier: A_N only needs to be valid on generated bags, not on all SAT instances.
- Natural-proof barrier probe: a dense constructive proof excluding all small A_N would look natural unless it is explicitly range-specific or nonconstructive.

cycle-0032: Generated-OR magnification: correction-residual separator gate

Execution. research; azure_responses_api; attempt primary; 124.813 seconds; 3 lemmas, 5 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 32 converts the approximate bag-separator gate into an exact correction-residual gate. The valid target bridge is unchanged, but the source lower bound must prove Phi_N>1+epsilon-o(1): every small local formula predicate must leave a residual H_N xor S_A of high circuit complexity. Sparse error patching is only one falsifier; structured residual leakage is the stronger obstruction.

Pressure. No known reduction converts a small residual correction R_A into a small SAT solver or separator on the generated formula range. This is the current formal gap.

Derivation steps.

1. Start with the previous approximate relaxed bag-separator lemma: if A is correct on all but E source bags, then sparse equality patching gives C(H_N)<=N^{rho+o(1)}+N^q C(A)+O(NE).
2. Replace the support-size patch by the exact identity $H_N = S_A$ xor R_A, where $R_A = H_N$ xor S_A. This yields the sharper upper bound in L32.1 without assuming the error set is sparse.
3. Try to derive $C(R_A) > N^{1+\epsilon}$ from hardness of SAT on the generated range $U_N = G_N(x, j)$.

4. The derivation fails because R_A is a function of whole source bags x, not a predicate on individual formulas. It can encode global correlations among generated queries and may be small even if every range-restricted SAT predicate is hard.

5. Thus promise SAT hardness, semantic range entropy, and label balance do not imply the needed source lower bound unless they also rule out low-complexity residual corrections.

Equation 1: carrier.

$$H_N(x) = \bigvee_{j=1}^{N^q} SAT(G_N(x, j))$$

Valid when: Valid when the generated bag interface and SAT encoding are fixed for input length N.

Equation 2: separator_residual.

$$S_A(x) = \bigvee_{j=1}^{N^q} A(G_N(x, j)), \qquad R_A = H_N \oplus S_A$$

Valid when: Valid when A is any nonuniform predicate on one generated L-bit formula.

Equation 3: correction_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + N^q C(A) + C(R_A) + N^{q+o(1)}$$

Valid when: Applies after composing A with every generated query and xoring the residual correction circuit.

Equation 4: necessary_gate.

$$C(H_N) > N^{1+\epsilon-o(1)} \Rightarrow \forall A : \max \rho, q + \log_N C(A), \log_N C(R_A) \geq 1 + \epsilon - o(1)$$

Valid when: Requires the source lower bound to be against the same nonuniform circuit model used by the correction construction.

Equation 5: sparse_error_patch.

$$|\operatorname{supp}(R_A)| \leq N^\delta \Rightarrow C(R_A) \leq N^{1+\delta+o(1)}$$

Valid when: Valid when erroneous bags are patched by equality tests on N-bit source inputs.

Next analysis. Instantiate Phi_N for a tagged generated-OR carrier and compute whether simple tag predicates produce subthreshold residual circuits; then test an untagged high-entropy generator for the same residual leakage.

Falsifiers.

- correction-residual falsifier: exists A with $q+log_N\, C(A) < 1+\epsilon$ and C(H_N xor S_A)<N^{1+epsilon-o(1)}.
- structured-error falsifier: the bad-bag set is large but has a simple residual circuit, so counting errors would falsely suggest hardness.
- threshold-collapse falsifier: $q \geq 1+\epsilon$ or $\rho \geq 1+\epsilon$ makes the target transfer too expensive.
- nonuniform-leakage falsifier: residual advice about source bags repairs an imperfect local separator without yielding any SAT solver.
- natural-proof obstruction: a large constructive property separating H_N from $N^{1+\epsilon}$ circuits would conflict with standard pseudorandom-function barriers unless the proof is carrier-specific and non-large.

cycle-0033: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 143.841 seconds; 3 lemmas, 6 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 33 strengthens the generated-OR source obligation from single residual correction to feature-aggregator residual hardness. This is a contribution-making repair: it preserves the exact target bridge but exposes a broader nonuniform-leakage falsifier class that prior selector and separator audits did not cover.

Pressure. The missing proof obligation is a lower bound on C(H_N xor $S_{A,B}$) for all subthreshold feature families and aggregators. Promise SAT hardness on the generated range does not imply this residual lower bound, because B may exploit many weak local features jointly.

Derivation steps.

1. Start with any feature family A on L-bit formulas and any aggregator B over the M_N by t feature matrix.
2. Compose G_N with all A_i on all M_N positions; by circuit composition this costs N^{rho+o(1)}+N^{q+alpha+
3. Feed the resulting feature matrix to B, obtaining $S_{A,B}$ with total size at most N^{rho+o(1)}+N^{q+alpha+o(
4. If a residual circuit $R_{A,B} = H_N$ xor $S_{A,B}$ has size $N^{\gamma+o(1)}$, combine $S_{A,B}$, $R_{A,B}$, and one xor gate to compute H_N.
5. Thus any feature-aggregator-residual certificate with all exponents below 1+epsilon contradicts the claimed $N^{1+\epsilon-o(1)}$ source lower bound.
6. For target transfer, choose $t = 1$, A_1 equal to the hypothesized SAT_L circuit of size L^c=N^{o(1)}, and $B = OR_{M_N}$; the residual is zero and the cost is $N^{max\rho,q+o(1)}$.

Equation 1: carrier_parameters.

$$M_N = N^q, L = (logN)^d, C(G_N) = N^{rho+o(1)}$$

Valid when: Valid when the generated-bag carrier fixes polynomially many polylogarithmic SAT queries.

Equation 2: feature_surrogate.

$$S_{A,B}(x) = B((A_i(G_{N,j}(x)))_{j \leq M_N, i \leq t})$$

Valid when: Valid when all local features are evaluated on generated formulas before aggregation.

Equation 3: surrogate_upper_bound.

$$C(S_{A,B}) \leq N^{rho+o(1)} + N^{q+alpha+o(1)} + N^{beta+o(1)}$$

Valid when: Valid when G_N, all local features, and B are circuits in the same SIZE model.

Equation 4: residual_reconstruction.

$$C(H_N) \leq O(C(S_{A,B}) + C(R_{A,B}) + N), where R_{A,B} = H_N xor S_{A,B}$$

Valid when: Valid when the residual circuit is allowed to correct the surrogate on all inputs.

Equation 5: threshold_contradiction.

$$maxrho, q + alpha, beta, gamma < 1 + epsilon and C(R_{A,B}) \leq N^{gamma+o(1)} imply C(H_N) < N^{1+epsilon-o(1)}$$

Valid when: Applies when every charged component stays below the claimed source lower-bound exponent.

Equation 6: feature_residual_exponent.

$$Phi_N^{feat} = inf_{A,B} maxrho, q + alpha(A), beta(B), log_N C(H_N xor S_{A,B})$$

Valid when: Valid when the infimum ranges over nonuniform feature families and bag aggregators.

Next analysis. Formalize the restricted case where B is a depth-2 threshold or DNF over $t = N^\tau$ local features, compute the exact q+alpha+beta leakage threshold, and search for an explicit low-residual construction on expander-walk generated SAT bags.

Falsifiers.

- feature-compression falsifier: $t = N^\tau$ local predicates with $q + \alpha < 1 + \epsilon$ and a small aggregator predict H_N up to subthreshold residual complexity.
- advice-coded aggregator falsifier: B stores labels for large generated-range blocks with $\beta < 1 + \epsilon$, collapsing the source lower bound without solving SAT globally.
- low-dimensional generator falsifier: G_N maps bags into a feature space where OR-SAT is decided by a small lookup or threshold over features.
- structured residual falsifier: H_N xor $S_{A,B}$ is easy even when its error support is dense, so sparse-error audits miss the collapse.
- barrier audit: a dense constructive proof that all feature-aggregator residuals are hard would look natural unless it exploits non-natural SAT semantics or another explicit non-natural certificate.

cycle-0034: Hardness-Magnification Bridge Realization: tuple-feature residual gate

Execution. research; azure_responses_api; attempt primary; 167.842 seconds; 3 lemmas, 4 equations, 7 derivation steps, 7 falsifiers.

Learning. Cycle 34 adds a quantitative tuple-arity term to the generated-OR audit. The valid target bridge still needs only $max\rho, q < 1 + \epsilon$, but the source lower bound must rule out every subthreshold tuple-feature transcript with exponent s+tq+alpha and residual exponent λ. This yields a finite dense-arity falsifier search and a sharper nonuniform-leakage obstruction, without claiming P $\neq$ NP.

Pressure. The derivation gives an exact upper-bound falsifier class, but it does not prove that arbitrary small circuits for H_N factor through low-arity tuple transcripts. The remaining source obligation is a genuine unrestricted-circuit lower bound or a non-natural theorem ruling out all residual systems and all non-factored circuits.

Derivation steps.

1. Fix the generated-OR carrier H_N from the previous cycles with $M_N = N^q$ generated SAT instances of length L=(log N)^d and batch generator size $N^{\rho+o(1)}$.
2. Choose $r = N^s$ arity-t predicates P_i. After computing the batch B_N(x), enumerate all M_N^t ordered tuples and OR the predicate outputs to obtain transcript bits z_i(x).
3. The transcript circuit size is at most $N^{\rho+o(1)}$ plus r M_N^t $N^{\alpha+o(1)}$, giving exponent max{rho,s+tq+alpha}.
4. Apply an aggregator A_N of size N^γ to obtain S_N(x). If a residual circuit E_N of size N^λ computes H_N(x) xor S_N(x), then H_N is computed by S_N xor E_N.
5. Summing these components gives C(H_N)<=N^{rho+o(1)}+N^{s+tq+alpha+o(1)}+N^gamma+N^lambd
6. Thus any claimed source lower bound $C(H_N) > N^{1+\epsilon}$ must imply theta_t>=1+epsilon-o(1) for every such tuple-feature residual system.
7. Independently, if SAT has $n^c - size$ circuits, substituting them into the M_N polylogarithmic generated queries gives $C(H_N) \leq N^{max\rho,q+o(1)}$, so the target bridge remains valid when $max\rho, q < 1 + \epsilon$.

Equation 1: tuple_feature_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + N^{s+tq+\alpha+o(1)} + N^\gamma + N^\lambda.$$

Valid when: Valid when the batch generator is shared once, tuple features are densely enumerated over all M_N^t tuples, and E_N exactly computes H_N xor S_N.

Equation 2: subthreshold_falsifier_exponent.

$$\theta_t := \max \rho,\ s + tq + \alpha,\ \gamma,\ \lambda < 1 + \epsilon \ \Rightarrow\ C(H_N) \leq N^{1+\epsilon-\Omega(1)}.$$

Valid when: Valid when all exponent inequalities have a fixed margin and polynomially many additive circuit components are absorbed into the maximum exponent.

Equation 3: target_substitution_bridge.

$$SAT \in SIZE(n^c) \;\Rightarrow\; C(H_N) \leq N^{\max \rho, q + o(1)}.$$

Valid when: Applies after SAT circuits are substituted only into length L=(log N)^d generated queries, so L^c=N^{o(1)} for each fixed c.

Equation 4: route_magnification_consequence.

$$C(H_N) > N^{1+\epsilon} \text{ eventually and } \max \rho, q < 1 + \epsilon \;\Rightarrow\; SAT \notin P/poly.$$

Valid when: Requires an eventually valid unrestricted-circuit lower bound for the named carrier and fixed target-preserving parameters q,rho,epsilon with positive slack.

Next analysis. Instantiate the pair-pattern thought experiment for $t = 2$: choose q with $q < 1+\epsilon$ and test whether $2q + \alpha < 1 + \epsilon$ permits a subthreshold pair separator S_N; compute the residual complexity C(H_N xor S_N) and check for hidden SAT lookup.

Falsifiers.

- tuple-feature falsifier: some arity t system has $max\rho, s + tq + \alpha, \gamma, \lambda < 1 + \epsilon$ and an exact or low-cost residual for H_N.
- sparse-tuple falsifier: the carrier admits a selector or algebraic shortcut computing the same tuple transcript below the dense M_N^t exponent.
- target-window falsifier: $max\rho, q \geq 1 + \epsilon$, so the SAT-circuit substitution no longer contradicts the claimed source lower bound.
- lookup falsifier: L or the generated range is small enough that SAT labels on the relevant range are nonuniformly tabulated below $N^{1+\epsilon}$.
- nonuniform-leakage falsifier: advice encodes a hitting family for positive bags or a separator for negative bags with subthreshold residual correction.
- natural-proof falsifier: the only available source proof is a large constructive property of truth tables, leaving the route blocked under standard PRF-based natural-proofs barriers.
- model-mismatch falsifier: the tuple lower bound is proved only for restricted circuits while the target bridge requires unrestricted P/poly substitution.

cycle-0035: Hardness-Magnification Bridge Realization: high-q arity cutoff for generated-OR carriers

Execution. research; azure_responses_api; attempt primary; 149.906 seconds; 2 lemmas, 6 equations, 5 derivation steps, 6 falsifiers.

Learning. Cycle 35 finds a parameter repair: set q in ((1+epsilon)/2,1+epsilon) to preserve the generated-OR target bridge while forcing every dense tuple-feature transcript of arity at least two above the $N^{1+\epsilon}$ threshold. The route-level lower-bound obligation is now the sharper unary residual minimax gate, not an infinite tuple-arity audit.

Pressure. No proof is known that an explicit high-q generator defeats all unary range-local transcripts and subthreshold residual corrections. High q may even help unary predicates by presenting many chances to hit a satisfiable generated formula.

Derivation steps.

1. Instantiate H_N with $M_N = N^q$ and L_N=(log N)^d, $d > 1$, so SAT circuits of size L_N^c are $N^{o(1)}$ after substitution.

2. Assume SAT $\in$ SIZE(n^c). Composing the SAT circuit with the bulk generator and the OR over M_N queries gives $C(H_N) \leq N^{max\rho,q+o(1)}$; hence a valid H_N lower bound above $N^{1+\epsilon}$ contradicts every fixed c when $max\rho, q < 1 + \epsilon$.

3. Model nonuniform leakage by N^s predicates on t-tuples of generated formulas, each composed predicate costing $N^{\alpha+o(1)}$. Dense enumeration gives $N^{s+tq+\alpha+o(1)}$ transcript cost.

4. If a size N^a aggregator plus residual correction of size N^λ recovers H_N, then H_N has size $N^{max\rho,s+tq+\alpha,a,\lambda+o(1)}$. Therefore any source lower bound must force this maximum to be at least 1+epsilon-o(1).

5. Choose $q > (1 + \epsilon)/2$. Since $s, \alpha \geq 0$, every $t \geq 2$ dense tuple transcript has exponent $s + tq + \alpha > 1 + \epsilon$, so it cannot be a subthreshold falsifier. The audit collapses to $t = 1$ transcripts and residual corrections.

Equation 1: carrier_parameters.

$$M_N = N^q, \quad L_N = (\log N)^d, \quad C(G_N) \leq N^{\rho+o(1)}$$

Valid when: Valid when the carrier family has fixed exponents q,rho,d and the generator cost is charged in the N-input circuit model.

Equation 2: target_substitution.

$$SAT \in SIZE(n^c) \implies C(H_N) \leq N^{\max \rho,q+o(1)}$$

Valid when: Applies when $d > 1$ is fixed, c is constant, and each $length-L_N$ SAT circuit contributes only L_N^c=N^{o(1)} overhead.

Equation 3: dense_tuple_transcript_cost.

$$C(T_{s,t,\alpha}) \leq N^{s+tq+\alpha+o(1)}$$

Valid when: Valid when N^s feature predicates are evaluated on all N^{tq} generated t-tuples and each composed predicate costs $N^{\alpha+o(1)}$.

Equation 4: compression_falsifier_bound.

$$C(H_N) \leq N^{\max \rho,s+tq+\alpha,a,\lambda+o(1)}$$

Valid when: Valid when an aggregator of size N^a on the transcript and a residual correction of size N^λ exactly recover H_N.

Equation 5: source_obligation.

$$C(H_N) > N^{1+\epsilon-o(1)} \Rightarrow \max \rho, s + tq + \alpha, a, \lambda \geq 1 + \epsilon - o(1)$$

Valid when: Requires the claimed source lower bound to hold against every nonuniform transcript, aggregator, and correction family in the named source model.

Equation 6: high_q_cutoff.

$$q > (1+\epsilon)/2 \ \wedge \ t \geq 2 \implies s + tq + \alpha > 1 + \epsilon$$

Valid when: Valid when feature-count and feature-composition exponents are nonnegative and dense enumeration of all t-tuples is charged.

Next analysis. Formalize unary transcripts as monotone OR-of-range predicates, then test whether random-looking high-q generators make every subthreshold unary transcript leave residual circuit complexity above $N^{1+\epsilon-o(1)}$ or whether a selected-image separator falsifier appears.

Falsifiers.

- Unary feature residual compression with exponent $max\rho, s + q + \alpha, a, \lambda < 1 + \epsilon$ is the decisive remaining falsifier.
- If $q \leq (1+\epsilon)/2$, binary tuple-feature transcripts can still be subthreshold and the high-q repair is invalid.
- If $\rho \geq 1 + \epsilon$, the generator alone destroys the target-preserving bridge.
- If the generated range has a small promise SAT separator or low positive-fiber hitting cover, H_N may be easy despite global SAT hardness.
- If a proposed lower-bound proof yields a dense constructive truth-table property, the natural-proofs obstruction applies; the route must be range-dependent or otherwise non-natural.
- If the generator leaks SAT labels through advice or indexing structure, the source lower bound collapses by nonuniform leakage.

cycle-0036: Hardness-Magnification Bridge Realization: position-indexed unary residual gate

Execution. research; azure_responses_api; attempt primary; 152.758 seconds; 2 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 36 repairs the high-q unary reduction: binary and higher tuple features are threshold-blocked when $q > (1+\epsilon)/2$, but shared-unary audits are not sound for general circuits. The valid remaining source obligation is a position-indexed unary transcript plus residual lower bound with total local budget U_N. This is a sharper route-level gate and supplies an explicit falsifier class, without claiming P $\neq$ NP.

Pressure. No lower-bound technique is supplied for the position-indexed unary residual minimax quantity. Proving it for an explicit H_N is essentially a general-circuit lower bound for a highly structured generated OR, not a consequence of the magnification bridge.

Derivation steps.

1. Start with H_N(x)=OR_{jN^{1+epsilon}.
2. The target bridge remains valid: SAT $\in$ SIZE(n^c) gives H_N circuits of size $N^{max\rho,q+o(1)}$, so a valid H_N lower bound with $max\rho, q < 1 + \epsilon$ implies SAT notin SIZE(poly).
3. Use the cycle-35 parameter $q > (1 + \epsilon)/2$. Any explicit tuple transcript that enumerates all pairs or higher arity tuples costs at least $N^{2q-o(1)}$, already above $N^{1+\epsilon}$.
4. Try to conclude that only a shared unary predicate A(F) must be ruled out. This fails because the nonuniform circuit for H_N can attach different small predicates A_j to different generated positions without paying the cost of a uniform rule for j.
5. Repair the audit by defining total-budget position-indexed unary transcripts and allowing an arbitrary aggregator plus residual corrector.
6. Derive the upper bound $C(H_N) \leq N^{\rho+o(1)} + sum_j$ C(A_j)+C(B)+C(R). Therefore any subthreshold position-indexed decomposition is a concrete falsifier for the claimed source lower bound.

Equation 1: target_substitution.

$$C(H_N) \leq N^{\rho+o(1)} + N^q\, L^c = N^{\max\rho,q+o(1)}$$

Valid when: Valid when SAT has nonuniform circuits of size n^c on L-bit inputs and the generator emits all queries with size N^ρ.

Equation 2: high_q_tuple_floor.

$$tq > 1 + \epsilon \quad \text{for every } t \geq 2 \text{ if } q > (1 + \epsilon)/2$$

Valid when: Applies in the high-q parameter regime before charging any predicate or aggregator overhead to tuple features.

Equation 3: position_unary_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + U_N + C(B_N) + C(R_N)$$

Valid when: Valid when H_N equals B_N((A_{N,j}(G_{N,j}(x)))_{j\{}le M}) $\oplus$ R_N(x) as a Boolean function.

Equation 4: source_obligation.

$$\inf_{A_j,B,R} \max\rho, \log_N U_N, \log_N C(B), \log_N C(R) > 1 + \epsilon - o(1)$$

Valid when: Requires the target-preserving lower-bound claim to survive all nonuniform position-indexed unary transcript decompositions and residual corrections.

Next analysis. Formalize $Iota_N^{pos}$ as a minimax transcript-residual measure and test whether expander-style slot mixing can rule out all low-budget position-indexed unary decompositions without becoming a natural-proof argument.

Falsifiers.

- position-indexed unary predicates with total budget below $N^{1+\epsilon}$
- an aggregator B_N of size below $N^{1+\epsilon}$ whose transcript classes are nearly monochromatic for H_N
- a residual corrector R_N of size below $N^{1+\epsilon}$ covering mixed transcript classes
- generator leakage where $G_{N,j}$ makes SAT labels simple for most fixed positions
- threshold collapse if q<=((1+epsilon)/2), since binary tuple features may become subthreshold

cycle-0037: Hardness-Magnification Bridge Realization: approximate witness-cover gate

Execution. research; azure_responses_api; attempt primary; 158.44 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 37 sharpens the position-indexed unary residual obligation into an approximate witness-cover threshold. In the high-q generated-OR route, dense tuple leakage is threshold-blocked, but unary assignment covers of total size below $N^{1+\epsilon}$ plus fewer than N^{ϵ} missed positives still give exact circuits for H_N after equality patching. This is route-level progress: a valid candidate source lower bound must first prove high approximate witness-cover complexity, while the main P $\neq$ NP conjecture remains untouched.

Pressure. No explicit generated-OR family is known to have approximate position-indexed witness-cover complexity above this threshold, and defeating witness covers is still weaker than defeating arbitrary position-indexed unary predicates plus residual circuits.

Derivation steps.

1. Fix nonuniform assignment sets $A_{N,j}$ and build B_A(x) by evaluating each generated formula F_{N,j}(x) on all assignments in $A_{N,j}$.
2. Use the multioutput generator once, costing $N^{\rho+o(1)}$, and share its formula bits across all assignment evaluations.
3. Each assignment evaluation costs $L_N^{O(1)}$, so the total certificate-test cost is $L_N^{O(1)}W_N$ plus the final OR over M_N positions.
4. If B_A misses E_N positive inputs of H_N, add equality tests for those N-bit inputs and OR them into B_A, costing O(N E_N).
5. The resulting circuit computes H_N exactly with size N^{rho+o(1)}+N^{q+o(1)}+L_N^{O(1)}W_N+O(N E_N).
6. Therefore any claimed $N^{1+\epsilon-o(1)}$ lower bound for H_N implies the necessary exponent inequality max{rho,q,omega,1+eta}>=1+epsilon-o(1).

Equation 1: carrier.

$$H_N(x) = \bigvee_{j \le M_N} SAT(F_{N,j}(x)), \quad M_N = N^q, \quad L_N = (\log N)^d.$$

Valid when: Valid when the source carrier is the generated-OR family with explicit multioutput generation and fixed polynomially many indexed queries.

Equation 2: cover_predictor.

$$B_A(x) = \bigvee_{j \le M_N} \bigvee_{a \in A_{N,j}} Eval(F_{N,j}(x), a).$$

Valid when: Valid when $A_{N,j}$ is position indexed and Eval tests satisfaction for the generated formula encoding.

Equation 3: upper_bound.

$$SIZE(H_N) \le N^{\rho + o(1)} + N^{q + o(1)} + L_N^{O(1)} W_N + O(NE_N).$$

Valid when: Applies when the cover predictor is corrected by hardwired equality tests for all uncovered positive inputs.

Equation 4: necessary_threshold.

$$\max \rho, q, \omega, 1 + \eta \ge 1 + \epsilon - o(1), \quad W_N = N^{\omega + o(1)}, \; E_N = N^{\eta + o(1)}.$$

Valid when: Requires comparing the explicit upper bound against a claimed $N^{1+\epsilon-o(1)}$ lower bound in general circuits.

Next analysis. Instantiate the thought experiment with a concrete planted/anti-planted CNF generator and compute the minimum position-indexed assignment hitting exponent h for its satisfiable range; compare h to 1+epsilon-q.

Falsifiers.

- falsifier: exact per-position assignment hitting sets with total $W_N < N^{1+\epsilon-\delta}$.
- falsifier: approximate witness covers with $W_N < N^{1+\epsilon-\delta}$ and fewer than $N^{\epsilon-\delta}$ missed positive inputs.
- falsifier: planted-solution or low-witness-entropy generated ranges where one small assignment list hits every satisfiable formula in each position range.
- falsifier: nonuniform advice choosing $A_{N,j}$ separately for every N and j; this leakage is valid in the source SIZE model and must be charged.
- falsifier: generator implementation whose full multioutput cost already reaches $N^{1+\epsilon}$, destroying the target-preserving threshold.

cycle-0038: Hardness-Magnification Bridge Realization: realized-witness projection gate

Execution. research; azure_responses_api; attempt primary; 127.795 seconds; 2 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 38 isolates a canonical unary leakage mechanism: all realized satisfying witnesses per generated position form a zero-error cover. Thus a valid high-q generated-OR route needs W_N^*>N^{1+epsilon-o(1)} or a stronger approximate-cover lower bound. The target substitution bridge survives, but source plausibility is now governed by witness-projection entropy rather than formula-range entropy alone.

Pressure. This proves only a necessary gate for the carrier lower bound. It does not supply the hard lower bound against all possible approximate witness covers.

Derivation steps.

1. Fix nonuniform lists Y_j and build one shared circuit for G_N that outputs all formulas F_{N,j}(x).
2. For every pair (j,a) with a in Y_j, attach a small evaluator computing whether a satisfies F_{N,j}(x).
3. OR all evaluator outputs; this never accepts a negative input because every generated formula in a negative bag is unsatisfiable.
4. If a positive input is missed by all lists, add an equality patch for that x; E_N missed positives cost $E_N * N^{1+o(1)}$ gates.
5. The resulting size is N^{rho+o(1)}+(sum_j |Y_j|)N^{o(1)}+E_N $N^{1+o(1)}$.
6. Therefore an $N^{1+\epsilon-o(1)}$ source lower bound forces either total cover size at least $N^{1+\epsilon-o(1)}$ or at least $N^{\epsilon-o(1)}$ missed positives.

Equation 1: target_substitution.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N) \leq N^{\max \rho,q+o(1)}$$

Valid when: Valid when the batch generator outputs all queried formulas with shared cost $N^{\rho+o(1)}$ and each SAT replacement circuit is used on L=(log N)^d bit instances.

Equation 2: witness_cover_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + \left(\sum_{j \leq N^q} |Y_j| \right) N^{o(1)} + E_N \, N^{1+o(1)}$$

Valid when: Applies after the witness lists hit every positive bag except E_N inputs and negative inputs remain rejected by direct formula evaluation.

Equation 3: projection_entropy_threshold.

$$\sum_{j \le N^q} |Y_j| \ge N^{1+\epsilon-o(1)} \quad \text{or} \quad E_N \ge N^{\epsilon-o(1)}$$

Valid when: Requires a claimed source lower bound $C(H_N) > N^{1+\epsilon-o(1)}$ with $\rho < 1+\epsilon$ and evaluator overhead only $N^{o(1)}$.

Equation 4: average_support_gate.

$$\frac{1}{N^q} \sum_{j \le N^q} |Y_j| \ge N^{1+\epsilon-q-o(1)}$$

Valid when: Valid when the misses are subpatchable and the total cover lower bound is converted into a per-position average witness-support obligation.

Next analysis. Instantiate the planted-pool thought experiment and compute W_N^* for affine, low-degree, and pseudorandom assignment-pool generators; check whether any preserves $q + a > 1 + \epsilon$ without introducing natural-proof or advice-leakage collapse.

Falsifiers.

- realized witness projection total W_N^* below $N^{1+\epsilon-o(1)}$
- approximate witness lists with fewer than $N^{\epsilon-o(1)}$ missed positives and subthreshold total size
- positive fiber size below $N^{\epsilon-o(1)}$, since equality patching alone makes H_N small
- batch generator not shareable, causing the source and target interfaces to mismatch
- ρ reaching 1+epsilon, which hides witness-cover leakage behind generator cost

cycle-0039: High-q generated-OR carrier: partial-certificate cover gate

Execution. research; azure_responses_api; attempt primary; 970.595 seconds; 3 lemmas, 5 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 39 sharpens the generated-OR source audit: full realized witness entropy is not the right gate because partial satisfying terms can compress many witnesses. The valid target bridge remains $max\rho, q < 1 + \epsilon$, but the route now needs a superthreshold lower bound against position-indexed partial-term covers, and ultimately against sound local certificate covers.

Pressure. No valid extraction theorem converts an arbitrary small circuit for H_N into a small full-witness set, and partial certificates give a concrete counter-mechanism.

Derivation steps.

1. Start with the previous necessary condition W_N^*>N^{1+epsilon-o(1)} for realized full satisfying witnesses.
2. Try to infer SIZE(H_N) $> N^{1+\epsilon}$ from high W_N^* plus the valid target bridge $max\rho, q < 1 + \epsilon$.

3. Observe that a circuit for H_N need not enumerate full witnesses; it may hardwire a partial term or another sound local certificate per position and verify it against the generated CNF.

4. Construct the circuit OR_{j,p in P_j} TermSat(F_{N,j}(x),p) after computing all F_{N,j}(x) once; this decides H_N whenever P is a complete satisfying-term cover.

5. Conclude that full-witness entropy is only a weak necessary condition and must be replaced by tau_N^{term}, or more robustly K_N^{cert}.

Equation 1: generated_or_carrier.

$$H_N(x) = \bigvee_{j=1}^{M} \mathrm{SAT}(F_{N,j}(x)), \qquad M = N^q, \qquad |F_{N,j}| = L = (\log N)^d.$$

Valid when: Valid when the source object is the generated-OR CNF carrier with shared generator outputs and fixed q,d.

Equation 2: partial_term_cover_complexity.

$$\tau_N^{\mathrm{term}} = \min_{\mathcal{P}} \sum_{j \le M} \sum_{p \in \mathcal{P}_j} (1 + |p|).$$

Valid when: Valid when each hardwired partial assignment p must satisfy every clause it certifies in the actual generated CNF range.

Equation 3: cover_upper_bound.

$$\mathrm{SIZE}(H_N) \le C(G_N) + \tau_N^{\mathrm{term}} L^{O(1)}.$$

Valid when: Applies when the generator computes all query blocks once and the circuit verifies each hardwired term locally.

Equation 4: subthreshold_falsifier.

$$\tau_N^{\mathrm{term}} \le N^{1+\epsilon-\delta} \ \wedge \ C(G_N) \le N^{1+\epsilon-\delta} \Rightarrow \mathrm{SIZE}(H_N) \le N^{1+\epsilon-\delta/2}.$$

Valid when: Requires polylogarithmic query length so the verifier overhead is swallowed by the exponent slack.

Equation 5: target_substitution_bridge.

$$\mathrm{SAT} \in \mathrm{SIZE}(n^c) \Rightarrow \mathrm{SIZE}(H_N) \le N^{\max \rho, q+o(1)}.$$

Valid when: Applies after the reduction preserves nonuniform advice accounting, shared generation, and the q,rho threshold parameters.

Next analysis. Formalize tau_N^{term} as a set-cover problem over generated CNF ranges and test whether random-looking high-q generators can force tau_N^{term}>N^{1+epsilon} without making G_N nonexplicit or violating $\rho < 1 + \epsilon$.

Falsifiers.

- Small position-indexed satisfying-term cover tau_N^{term}<=N^{1+epsilon-delta} is a direct falsifier for the claimed source lower bound.
- Large full-witness projection entropy W_N^* with tiny planted partial terms falsifies the cycle-38 audit as sufficient evidence.
- A compact sound local certificate cover K_N^{cert} below threshold is a stronger nonuniform-leakage falsifier than promise-SAT easiness.
- If the query encoding is not CNF or lacks a cheap sound partial-certificate verifier, the term-cover lemma is not valid and must be replaced by the certificate-cover version.
- If ρ or q reaches 1+epsilon, the target-preserving bridge collapses independently of the source audit.

cycle-0040: Hardness-Magnification Bridge Realization: sound local certificate cover gate

Execution. research; azure_responses_api; attempt primary; 120.336 seconds; 3 lemmas, 4 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 40 sharpens the source audit from partial certificate covers to approximate sound local certificate covers. The exact upper bound C(H_N)<=C(G_N)+O(K(s+L^{O(1)})+EN) makes any subthreshold SLC cover a concrete falsifier. The target bridge remains valid, but a contribution now requires a superthreshold lower bound against one-sided local predicates on the generated range, not just high witness or formula entropy.

Pressure. No current argument proves that every one-sided local certificate predicate family of total size below $N^{1+\epsilon-o(1)}$ misses at least $N^{\epsilon-o(1)}$ positive bags on the actual generated range.

Derivation steps.

1. Fix ϵ, q in ((1+epsilon)/2,1+epsilon), rho1.
2. Define H_N as the OR of N^q generated 3CNF SAT instances and keep $C(G_N) \leq N^{max\rho,q+o(1)}$ as the shared interface cost.
3. Assume a (K,E,s)-SLC cover. Build a circuit that computes G_N(x), evaluates every A_i on its indexed formula $G_N(x)_{j_i}$, and ORs the K one-sided outputs.
4. Soundness of A_i prevents false positives on H_N^{-1}(0); completeness except E positives leaves only E missed x values.
5. Patch the E missed positive inputs by hardwired equality tests of size O(EN), giving C(H_N)<=C(G_N)+O(
6. Therefore a proposed source lower bound $C(H_N) > N^{1+\epsilon-o(1)}$ must imply a superthreshold lower bound against SLC covers, not merely against explicit witnesses or partial terms.
7. The old target bridge still works: if SAT has size n^c circuits, each length-L query costs L^c=N^{o(1)}, so H_N has size $N^{max\rho,q+o(1)}$.

Equation 1: carrier.

$$H_N(x) = \bigvee_{j=1}^{\lfloor N^q \rfloor} SAT(G_N(x)_j), \qquad L = (\log N)^d.$$

Valid when: Valid when the source carrier is the generated-OR family with shared generator outputs and length-L 3CNF instances.

Equation 2: slc-upper-bound.

$$C(H_N) \le C(G_N) + O(K(s + L^{O(1)}) + EN).$$

Valid when: Valid when the SLC predicates are one-sided sound and miss only E positive carrier inputs.

Equation 3: threshold-collapse-test.

$$K = N^\sigma,\ E = N^\delta,\ s = N^{o(1)},\ \max \rho, q, \sigma, 1 + \delta < 1 + \epsilon \ \Rightarrow\ C(H_N) < N^{1+\epsilon-o(1)}.$$

Valid when: Valid when all four exponent contributions are bounded below the desired source lower-bound threshold.

Equation 4: necessary-source-gate.

$$C(H_N) > N^{1+\epsilon-o(1)} \ \Rightarrow\ \text{every } N^{o(1)}\text{-local SLC cover has } K > N^{1+\epsilon-o(1)} \text{ or } E > N^{\epsilon-o(1)}.$$

Valid when: Applies after q and ρ are already fixed below the magnification threshold.

Next analysis. Compute the SLC cover exponent for generated formulas with bounded backdoor width $b = \alpha$ log N and for small semantic classes such as Horn, 2-SAT, and bounded-width CNF; identify whether the threshold $\alpha \ge 1 + \epsilon - q$ is achievable without destroying the SAT-substitution bridge.

Falsifiers.

- falsifier: a subthreshold $(K, E, N^{o(1)})$ SLC cover with $K < N^{1+\epsilon-o(1)}$ and $E < N^{\epsilon-o(1)}$ gives an explicit small circuit for H_N.
- Low-width backdoor falsifier: if every positive emitted formula has a satisfying term of width $b = \alpha$ log N and $q + \alpha < 1 + \epsilon$, enumerating all such terms collapses the source lower bound.
- Compressed-certificate falsifier: a size-poly(L) one-sided predicate can represent many partial terms, so large term count alone is not a valid source certificate.
- Lookup-boundary falsifier: if L=O(log N) with $q + 2^L$ exponent below 1+epsilon, local truth-table predicates replace genuine SAT hardness.
- Generator-bias falsifier: if positives lie in a small easy satisfiable subclass such as Horn, 2-SAT, bounded-width, or bounded-backdoor CNFs, SLC cover size may be subthreshold.
- Nonuniform leakage falsifier: predicates A_i may contain advice tailored to the generated range; the source lower bound must defeat this advice rather than only uniform algorithms.

cycle-0041: One-sided promise-separator gate for high-q generated-OR magnification

Execution. research; azure_responses_api; attempt primary; 170.751 seconds; 3 lemmas, 5 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 41 isolates the exact semantic object behind the sound-local-certificate audit: Sep_N^{1s}(E). Random term-cover calculations support the high-q polylog design, but they do not imply the needed separator lower bound. The main new obstruction is the term-cover versus one-sided semantic-separator gap.

Pressure. No valid extractor converts arbitrary one-sided semantic separators into partial witnesses; range closure under restrictions is absent, so term-cover calibration cannot certify Sep_N^{1s} lower bounds.

Derivation steps.

1. Start with $H_N(x) = OR_j$ SAT(G_N(x,j)) and retain $q, \rho < 1 + \epsilon$, L_N=(log N)^d.
2. Substitute an assumed SAT circuit of size n^c into every emitted formula; since L_N^c=N^{o(1)}, obtain $C(H_N) \leq N^{max\rho,q+o(1)}$.
3. Define D_j as one-sided promise separators for satisfiable formulas in the j-th generated range; OR_j D_j(G_N(x,j)) has no false positives for H_N.
4. Patch E missed positive inputs by equality tests on x, giving C(H_N)<=C(G_N)+O(sum_j $|D_j| + E$ N).
5. Therefore any valid $N^{1+\epsilon}$ lower bound for H_N must lower-bound Sep_N^{1s}(N^{epsilon-eta}) above $N^{1+\epsilon-\eta-o(1)}$ for every fixed $\eta > 0$.
6. A random k-CNF calculation shows partial-assignment term covers need 2^{Omega((log N)^d)} terms per position, far above the allowed $N^{1+\epsilon-q}$ budget.
7. Attempt to promote term-cover hardness to separator hardness by SAT self-reduction fails because D_j is promised only on generated formulas, and restrictions of generated formulas need not remain in the generated range.

Equation 1: carrier.

$$H_N(x) = OR_{j=1}^{M_N} SAT(G_N(x,j)), M_N = N^q, L_N = (logN)^d$$

Valid when: Valid when the source object is the generated-OR carrier with fixed position count and polylogarithmic emitted SAT length.

Equation 2: target-substitution.

$$SATinSIZE(n^c) => C(H_N) \leq C(G_N) + O(M_N L_N^c + M_N) = N^{maxrho,q+o(1)}$$

Valid when: Applies after the reduction preserves nonuniformity and each emitted SAT query has length L_N=(log N)^d.

Equation 3: separator-composition.

$$C(H_N) \leq C(G_N) + O(Sep_N^{1s}(E) + EN)$$

Valid when: Valid when the predicates are one-sided sound and the E missed positive inputs are patched by equality gates.

Equation 4: necessary-source-gate.

$$C(H_N) > N^{1+epsilon} => Sep_N^{1s}(N^{epsilon-eta}) > N^{1+epsilon-eta-o(1)} forever y fixed eta > 0$$

Valid when: Requires $C(G_N) \leq N^{\rho+o(1)}$ with $\rho < 1+\epsilon$ and uses the explicit equality-patching cost.

Equation 5: magnification-consequence.

$$[C(H_N) > N^{1+epsilon} and max rho, q < 1 + epsilon] => SAT not in SIZE(n^c) for every fixed c$$

Valid when: Valid when the lower bound is for the same H_N family and target substitution incurs only $N^{o(1)}$ SAT-circuit overhead.

Next analysis. Test a range-closure repair: augment G_N so restrictions of emitted formulas also appear in controlled positions, compute the q/rho overhead, and see whether this lets a one-sided separator self-reduce to a term cover without breaking the $N^{1+\epsilon}$ threshold.

Falsifiers.

- threshold collapse if $q \geq 1+\epsilon$ or $\rho \geq 1+\epsilon$
- nonuniform leakage through small one-sided promise separators D_j
- model mismatch between syntactic term covers and semantic separators
- range-closure failure blocking witness extraction from D_j
- random-label or random-formula evidence that is not target-preserving for SAT
- natural-proof-style largeness if the separator lower bound is proved only by random counting

cycle-0042: Cycle 42: distributional cap certificate for one-sided semantic separators

Execution. research; azure_responses_api; attempt primary; 149.719 seconds; 3 lemmas, 6 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 42 turns the one-sided semantic-separator obstruction into an exact distributional cap profile A_N(s). The valid source route now needs a superthreshold cap-to-separator lower bound, not merely random witness or term-cover entropy. The target bridge is preserved, but any large one-sided cap is a concrete falsifier for the generated-OR lower bound.

Pressure. Term-cover randomness does not imply a cap bound for arbitrary one-sided semantic predicates. The missing theorem is a one-sided conditional pseudorandomness statement for the distribution of generated formulas inside positive bags.

Derivation steps.

1. Instantiate F_{N,j}(x) as polylog-length k-CNF formulas with $v = \beta$ log N variables and density near the satisfiability threshold; set $Q = N^q$ with q in ((1+epsilon)/2,1+epsilon).
2. Try to upper-bound A_N(s) by first bounding hit probability of assignment or partial-term predicates under mu_N^+.
3. Attempt a union bound over all size-s L-input circuits P, using the hope that any large accepted set contains generated unsatisfiable formulas and hence violates one-sided soundness.
4. The count of circuits is 2^{O(s log s)}, and for $s = N^\alpha$ this is far too large for term-cover estimates over individual witnesses.
5. More seriously, one-sided soundness is semantic on the generated range: a circuit may recognize a correlated satisfiable slice with no small witness-term description.

Equation 1: carrier_definition.

$$H_N(x) = OR_{j \leq N^q} SAT(F_{N,j}(x)), |F_{N,j}(x)| = L = (logN)^d$$

Valid when: Valid when the carrier is the generated-OR source problem with fixed high-q parameters and a named SAT encoding.

Equation 2: target_substitution_bridge.

$$SATinSIZE(n^c) => C(H_N) \leq N^{rho+o(1)} + N^q (logN)^{dc+O(1)} = N^{maxrho,q+o(1)}$$

Valid when: Applies after the reduction preserves the generator size, query length, and nonuniform circuit-size accounting.

Equation 3: cap_profile.

$$A_N(s) = max_{j,Pone-sided,size(P) \leq s} Pr_{x\ mu_N^+}[P(F_{N,j}(x)) = 1]$$

Valid when: Valid when one-sided soundness is imposed on the actual generated range, not on an informal global SAT promise.

Equation 4: union_cover_lower_bound.

$$KA_N(s) \geq 1 - beta_N(E)$$

Valid when: Valid when K local predicates miss at most E positive inputs and mu_N^+ gives those exceptions total mass beta_N(E).

Equation 5: separator_lower_bound.

$$Sep_N^{1s}(E; s) \geq (1 - beta_N(E))(s + L^{O(1)})/A_N(s) + EN$$

Valid when: Requires the cap bound for every allowed local predicate size and the standard equality patching charge for missed positives.

Equation 6: route_threshold.

$$A_N(s) \leq (1 - beta_N(E))(s + L^{O(1)})/N^{1+epsilon-o(1)} => Sep_N^{1s}(E; s) \geq N^{1+epsilon-o(1)}$$

Valid when: Applies in the source lower-bound regime where separator cost is the only remaining known nonuniform leakage channel.

Next analysis. Formalize the cap profile for the unmarked random k-CNF generated-OR thought experiment: compute assignment-test hit exponents as a function of β, then identify the first semantic predicate class beyond terms that can violate or support $A_N(s) \leq s/N^{1+\epsilon-o(1)}$.

Falsifiers.

- semantic planted-slice falsifier: a small predicate recognizes a satisfiable subset hit by most positive bags while avoiding all negative bags.
- large cap-profile falsifier: for some s, A_N(s) is much larger than $s/N^{1+\epsilon}$, yielding a subthreshold separator.
- exception concentration falsifier: the chosen positive distribution assigns large mass to E patchable positives, making beta_N(E) too large for the cover lower bound.
- nonuniform leakage falsifier: the generator range at one position admits a small promise SAT labeler even though global SAT on length L remains hard by exhaustive lookup.
- threshold-collapse falsifier: $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$ destroys the target-preserving substitution bridge.

cycle-0043: Generated-OR residual cap gate for hardness magnification

Execution. research; azure_responses_api; attempt compact_retry; 268.905 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 43 converts the cap profile into a residual fractional covering threshold. A valid source lower bound must rule out greedy one-sided cap covers with $B_N(s, E) < N^{\epsilon-sigma-o(1)}$; absence of a large first cap is not enough.

Pressure. No known method proves worst-case residual cap denominator $B_N(s, E) > N^{\epsilon-sigma-o(1)}$ for semantic one-sided caps with nonuniform advice.

Derivation steps.

1. Assume the generated-OR carrier and the target bridge $max\rho, q < 1 + \epsilon$ are fixed.
2. Define B_N(s,E) by adversarial residual positives, not by the first cap or an average distribution.
3. Apply greedy covering: residual size shrinks by a factor at most $1 - 1/B_N$ until at most E positives remain.
4. OR the K caps and patch the E misses; comparing exponents gives the threshold $b + 1 + sigma < 1 + \epsilon$ and $\delta < \epsilon$.

Equation 1: target_substitution.

$$C(H_N) \leq N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT_L has $L^c - size$ nonuniform circuits for fixed c, L=(log N)^d with $d > 1$, and G_N is shared once.

Equation 2: residual_greedy_cover.

$$K \leq \lceil B_N(s, E)(N \ln 2 + 1) \rceil$$

Valid when: Valid when every residual positive set larger than E has a one-sided cap hitting at least a 1/B_N(s,E) fraction.

Equation 3: cap_upper_bound.

$$C(H_N) \leq N^{\rho} + O(K(s + L^{O(1)}) + EN)$$

Valid when: Applies after caps are one-sided on the generated range, share G_N, and the remaining E positive inputs are patched by equality tests.

Next analysis. Try to construct residual caps for the planted/random 3CNF generator using partial-assignment certificates, and compute the resulting exponent b.

Falsifiers.

- Residual-cap falsifier: $s = N^{sigma}$, $E = N^{\delta}$, $B_N(s, E) = N^b$ with $b + 1 + sigma < 1 + \epsilon$ and $\delta < \epsilon$ gives small circuits for H_N.
- Target-threshold falsifier: $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$ prevents SAT substitution from contradicting an $N^{1+\epsilon}$ source lower bound.
- Nonuniform-leakage falsifier: caps may be chosen after seeing G_N and the generated range; random term entropy is invalid unless it holds for adversarial residual sets.
- Naturalness probe: a dense constructive property excluding all small caps risks the natural-proofs obstruction, so the certificate must be non-natural or distribution-local.

cycle-0044: Hardness-Magnification Bridge Realization: residual cap-denominator gate

Execution. research; azure_responses_api; attempt primary; 305.826 seconds; 3 lemmas, 5 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 44 converts the residual cap profile into a greedy cap-denominator theorem. A generated-OR source lower bound must now produce hard residual positive distributions against all one-sided local predicates; otherwise D_N N^{sigma} and E N give an explicit subthreshold upper-bound falsifier. This is route-level progress, not a main P $\neq$ NP proof.

Pressure. No lower bound is known showing that every residual positive distribution fools all one-sided generated-range predicates of size N^{sigma} at hit probability $N^{-(1+\epsilon-sigma)}$.

Derivation steps.

1. Fix sigma and the family P^{1s}_{sigma} of $size - N^{sigma}$ local predicates sound on the generated range.
2. Start with R_0=H_N^{-1}(1). While $|R_t| > E$, choose A_t with $cap_{R_t}(A_t) \geq |R_t|/D_N$ and remove the hit positives.
3. After K steps, $|R_K| = D_N$ log(|H_N^{-1}(1)|/E), so K=O(D_N N) is enough without needing to enumerate the universe uniformly.
4. Build the circuit: compute the generator, evaluate all chosen predicates, OR their hits, and patch the E missed positives by equality tests.
5. The resulting upper bound is below $N^{1+\epsilon}$ when $\rho < 1 + \epsilon$, D_N N^{sigma} is subthreshold up to logs, and E N is subthreshold.
6. Contraposition yields the hard-residual distribution obligation for any valid source lower bound.

Equation 1: carrier.

$$H_N(x) = \bigvee_{j=1}^{N^q} SAT(G_N(x,j)), \qquad |G_N(x,j)| = (\log N)^d.$$

Valid when: Valid when the source carrier is the explicit generated-OR family with polylogarithmic SAT queries and fixed q,d parameters.

Equation 2: target_substitution.

$$SAT \in SIZE(n^c) \implies C(H_N) \leq N^{\max \rho, q + o(1)}.$$

Valid when: Applies after the generator size is $N^{\rho+o(1)}$ and each polylogarithmic SAT query receives a size L^c circuit.

Equation 3: greedy_cover_size.

$$K \leq D_N \log |H_N^{-1}(1)| \leq O(D_N N).$$

Valid when: Valid when every residual positive set larger than E has a sound predicate covering at least a $1/D_N$ fraction.

Equation 4: source_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + N^{\sigma+o(1)} D_N \, polylog(2^N) + E N^{1+o(1)}.$$

Valid when: Requires that the greedy predicates are one-sided sound on the generated range and missed positives are patched by equality tests.

Equation 5: falsifier_threshold.

$$D_N \le N^{1+\epsilon-\sigma-o(1)}/polylog(N), \quad E \le N^{\epsilon-o(1)} \implies C(H_N) \le N^{1+\epsilon-o(1)}.$$

Valid when: Valid in the threshold regime where ρ is below 1+epsilon and the cover and patching terms dominate the audit.

Next analysis. Instantiate the cap audit for partial-assignment predicates of width w on L=(log N)^2 formulas: compute theta(w,sigma) for random-looking generated ranges, then check whether sigma+theta can stay above 1+epsilon while q,rho remain in the target-preserving window.

Falsifiers.

- residual cap denominator D_N below $N^{1+\epsilon-sigma-o(1)}$ gives a concrete falsifier for the source lower bound
- exception set E below $N^{\epsilon-o(1)}$ is patchable by equality gates
- nonuniform leakage through one-sided predicates sound only on the generated range
- threshold collapse if q or ρ reaches 1+epsilon before the target substitution is applied
- model mismatch if the cap lower bound is proved only for uniform predicates while the source model is nonuniform circuits
- natural-proof leakage if the residual certificate becomes a large constructive global property

cycle-0045: Hardness-Magnification Bridge Realization: Greedy Cap Dual Gate

Execution. research; azure_responses_api; attempt primary; 184.453 seconds; 3 lemmas, 4 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 45 adds the missing logarithmic greedy-cover charge and converts the cap profile into an exact threshold: $D_{sigma,E} < N^{\epsilon-sigma-o(1)}$ is a concrete upper-bound falsifier for the generated-OR source lower bound. A valid route must now prove hard residual positive distributions against all one-sided separators and also close the normal-form gap from arbitrary circuits to separator covers.

Pressure. The derivation only rules out separator-cover upper bounds. It does not prove that every subthreshold exact circuit for H_N has a valid one-sided separator normal form.

Derivation steps.

1. Let P_N=H_N^{-1}(1) and fix the valid separator family S_{sigma} of size-cost at most N^{sigma}.
2. Assume every residual R subseteq P_N with $|R| > E$ has a separator A hitting at least |R|/D of R.
3. Greedy selection removes a 1/D fraction of the current residual, so after at most D log(|P_N|/E) $\le N^{1+o(1)}D$ choices it leaves at most E positives uncovered.
4. OR the chosen one-sided separators. Soundness gives no false positives on H_N^{-1}(0); patch the remaining E positives by equality circuits of size O(EN).

5. The resulting upper bound is C(H_N)<=N^{rho+o(1)}+N^{1+sigma+o(1)}D+O(EN).

6. If $D < N^{\epsilon-sigma-o(1)}$ and $E < N^{\epsilon-o(1)}$, this is below $N^{1+\epsilon-o(1)}$, contradicting the proposed source lower bound.

7. Therefore a valid source lower-bound proof must either prove $D \geq N^{\epsilon-sigma-o(1)}$ for all $sigma < \epsilon$ or provide hard residual distributions with cap at most $N^{-(\epsilon-sigma)+o(1)}$.

Equation 1: target_substitution_upper_bound.

$$C(H_N) \leq N^{\rho+o(1)} + N^q L^c = N^{\max \rho,q+o(1)}$$

Valid when: Valid when L=(log N)^d with $d > 1$, SAT_L has nonuniform circuits of size L^c, and the generator for all N^q queries has size $N^{\rho+o(1)}$.

Equation 2: separator_cover_upper_bound.

$$C(H_N) \leq C(G_N) + O(KN^\sigma + EN)$$

Valid when: Valid when the separators are semantically one-sided on the generated range, cover all but E positive bags, and equality patches for missed inputs cost O(N) each.

Equation 3: greedy_cover_size.

$$K \leq \left\lceil D_{\sigma,E} \log \frac{|H_N^{-1}(1)|}{\max 1, E} \right\rceil \leq N^{1+o(1)} D_{\sigma,E}$$

Valid when: Valid when every residual positive set larger than E has a separator cap at least its reciprocal denominator, so greedy removal is legitimate.

Equation 4: cap_denominator_falsifier_threshold.

$$D_{\sigma,E} < N^{\epsilon-\sigma-o(1)} \ \wedge \ E < N^{\epsilon-o(1)} \implies C(H_N) < N^{1+\epsilon-o(1)}$$

Valid when: Valid contrapositively after the log $|\mathrm{P}_N| \leq$ N factor, generator cost, and equality-error corrections are all charged below the source threshold.

Next analysis. Work in a restricted circuit model such as De Morgan formulas or AC0[p] and test whether exact circuits for H_N admit an approximate one-sided separator normal form; compute the resulting $D_{sigma,E}$ threshold for the same high-q polylog generated-OR carrier.

Falsifiers.

- cap-denominator falsifier: some $sigma < \epsilon$ and $E < N^{\epsilon-o(1)}$ have $D_{sigma,E} < N^{\epsilon-sigma-o(1)}$, yielding a subthreshold circuit for H_N.
- normal-form falsifier: an exact small circuit computes H_N using two-sided global information that cannot be represented by valid one-sided separator covers.
- one-sidedness falsifier: a proposed local predicate accepts even one generated negative bag, invalidating the separator-cover upper bound and the residual distribution certificate.

- nonuniform leakage falsifier: the generator or separator list hides advice selecting easy positive fibers, reducing the cover cost below $N^{1+\epsilon}$.
- barrier falsifier: a proof of the residual cap lower bound via a large constructive property of SAT truth tables would run into the natural-proofs obstruction under pseudorandom functions; the current semantic promise object is only outside that barrier's direct scope.
- lookup-threshold falsifier: if $d \leq 1$ or variable entropy drops, exhaustive SAT lookup or partial certificate covers can re-enter below the source threshold.

cycle-0046: Hardness-Magnification Bridge Realization: normal-form extraction gate

Execution. research; azure_responses_api; attempt primary; 178.415 seconds; 3 lemmas, 5 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 46 converts the cycle-45 normal-form warning into a precise obstruction. Greedy cap and separator denominators give valid upper-bound falsifiers, but separator hardness is not by itself a source lower bound. A planted-control generated-OR carrier can have H_N easy while local formula separators remain hard, so the route now needs a nonrelativizing locality-extraction theorem or a direct arbitrary-circuit lower bound for H_N.

Pressure. No valid locality-extraction theorem maps arbitrary small circuits for H_N into one-sided formula-local separator covers with subthreshold overhead.

Derivation steps.

1. Assume a circuit C of size $S < N^{1+\epsilon}$ computes H_N exactly.
2. Try to cover positive inputs x by choosing a witness position j with SAT(G_N(x,j)).
3. Attempt to define a local predicate $P_{j,C}$ on y=G_N(x,j) that is one-sided sound and accepts enough chosen witnesses.
4. The only available predicate from C is global: it depends on x and on correlations among all generated positions, not on y alone.
5. DNF expansion of C gives global accepting regions on x, but conversion to formula-local predicates can cost 2^S or require inverting G_N.
6. A planted-control carrier makes the obstruction exact: $H_N = b_N$ is easy, while local formula labels may remain separator-hard.

Equation 1: generated_or_carrier.

$$H_N(x) = vee_{j=1}^{N^q} SAT(G_N(x,j)), |G_N(x,j)| = L = (logN)^d$$

Valid when: Valid when the generated query family has a shared circuit G_N and all positions have the same polylogarithmic target length.

Equation 2: target_substitution_bridge.

$$SATinSIZE(n^c) => C(H_N) \leq N^r ho + N^q L^c + O(N^q) = N^{max(rho,q)+o(1)}$$

Valid when: Applies when SAT on length L has nonuniform circuits of size L^c and G_N is reused without position-specific advice.

Equation 3: separator_cover_upper_bound.

$$Sep_N^{1s}(K, s, E) => C(H_N) \leq C(G_N) + O(K(s + L^{O(1)}) + EN)$$

Valid when: Requires K position-indexed one-sided local predicates that hit every positive bag except E explicitly patchable inputs.

Equation 4: planted_control_collapse.

$$[(b_N(x) = 1 => H_N(x) = 1) and (b_N(x) = 0 => H_N(x) = 0)] => H_N = b_N and C(H_N) \leq C(b_N) + O(1)$$

Valid when: Valid when the control bit semantically determines the OR label of every generated bag, even if formula labels look locally random.

Equation 5: subthreshold_separator_falsifier.

$$K(s+L^{O(1)})+EN = o(N^{1+epsilon}) => the claimed C(H_N) > N^{1+epsilon-o(1)} source lower bound is false$$

Valid when: Applies only after the separator family is sound on the generated universe and the residual errors are patchable by equality gates.

Next analysis. Formalize a restricted no-control generator class, such as block-product independent seeds with no shared label bit, and test whether an S-size circuit for OR_j SAT(G(x,j)) can be localized to a one-sided separator cover; compute the exact overhead in q,rho,sigma,E.

Falsifiers.

- planted-control falsifier: a simple global bit determines the OR label while individual generated formulas remain locally hard to separate.
- global-correlation circuit falsifier: C computes a relation among generated positions without identifying any satisfiable formula witness.
- relativization falsifier: random oracle labels can make separator complexity high while H_N remains equal to an easy control bit.
- threshold falsifier: any Sep_N^{1s}(K,s,E) with K(s+L^{O(1)})+EN=o(N^{1+epsilon}) invalidates the source lower bound.
- natural-proof leakage falsifier: a constructive dense separator-hardness certificate for SAT truth tables may fall inside the Razborov-Rudich obstruction.

cycle-0047: Hardness-Magnification Bridge Realization: locality-extraction obstruction

Execution. research; azure_responses_api; attempt primary; 197.268 seconds; 3 lemmas, 4 equations, 5 derivation steps, 4 falsifiers.

Learning. Cycle 47 converts the locality-extraction warning into a formal relativizing obstruction. A planted-control oracle gives hard one-sided local separators but an O(1)-size generated-OR carrier, so separator hardness is not a valid source lower-bound certificate by itself. The target substitution bridge survives unchanged; the route must now prove a nonrelativizing extraction theorem for real SAT or attack C(H_N) directly.

Pressure. There is no valid black-box operation that extracts a formula-local one-sided separator from an arbitrary global circuit for H_N. The missing step must exploit nonrelativizing real-SAT structure or be replaced by a direct arbitrary-circuit lower bound for H_N.

Derivation steps.

1. Assume a circuit C of size T computes $H_N(x) = OR_j$ SAT(G_{N,j}(x)).
2. For each positive input x, choose a satisfiable generated query $F_{x,j}$; try to define a local predicate p(F) that accepts one such F and rejects all formulas from negative bags.
3. The naive definition $p(F) = 1$ iff there exists x,j with $G_{N,j}(x) = F$ and $C(x) = 1$ is not one-sided, because C may be using nonlocal control information rather than any property of F.
4. Adding the condition that F never appears in a negative bag requires hard semantic range membership and may cost as much as the original H_N circuit.
5. The planted-control oracle realizes this failure sharply: C reads the control bit c, while a local separator must solve an independent random classification problem on the codewords.

Equation 1: generator-size-threshold.

$$R = N^{\theta}, \quad |G_N| = O(RL) = N^{\theta + o(1)} < N^{1+\epsilon}$$

Valid when: Valid when d is fixed, θ is below 1+epsilon, and the codebook table is allowed as nonuniform generator advice.

Equation 2: planted-control-easy-carrier.

$$H_N^U(c, y, w) = U(G_N(c, y, w)) = c, \quad C(H_N^U) = O(1)$$

Valid when: Valid when the oracle labels assign one to every positive codeword and zero to every negative codeword.

Equation 3: separator-counting-bound.

$$\Pr[\exists p : |p| \le S,\ p(a_y) = 1,\ p(b_y) = 0\ \forall y \le R] \le 2^{O(S \log S) - 2R}$$

Valid when: Valid when the oracle codewords are sampled independently and S log S=o(R).

Equation 4: separator-hardness-window.

$$S = N^{\sigma}, \quad \sigma < \theta \implies \mathrm{Sep}_N^{1s}(0) > N^{\sigma}$$

Valid when: Valid when 2^L is much larger than R and the union bound over size-S circuits succeeds.

Next analysis. Try a real-SAT extraction using self-reducibility or witness isolation: from a small circuit for H_N, define a local predicate that accepts formulas whose forced witness path changes the global OR value, compute the overhead, and test it against the planted-control oracle falsifier.

Falsifiers.

- falsifier: planted-control oracle with θ in (sigma,1+epsilon) makes H_N easy while zero-error local separators require size greater than N^{sigma}.
- falsifier: any relativizing separator-promotion theorem would prove a false implication in the oracle codebook model.
- falsifier: nonuniform generator advice can encode hard local classification while the global carrier depends only on a cheap control bit.
- falsifier: if $max\rho, q \geq 1 + \epsilon$, even the valid target substitution bridge loses its contradiction threshold.

cycle-0048: Relativizing locality-extraction gate for generated-OR carriers

Execution. research; azure_responses_api; attempt compact_retry; 243.551 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 48 makes the obstruction formal: separator-denominator hardness is only an upper-bound falsifier, not a valid lower-bound certificate for H_N. The surviving route is direct C(H_N) lower bounds or a nonrelativizing locality-extraction theorem with explicit threshold loss.

Pressure. No known nonrelativizing locality-extraction theorem converts an arbitrary small H_N circuit into local SAT-range separators with only $N^{o(1)}$ loss.

Derivation steps.

1. Fix $d > 1$ and $q, rhoN^{1+\epsilon}$ lower bound.
2. Try to replace the direct lower bound by proving every one-sided local separator cover has D N^{sigma} log $N + EN \geq N^{1+\epsilon-o(1)}$.
3. For this replacement to be valid, the contrapositive must extract a small separator cover from any arbitrary circuit A computing H_N with size below $N^{1+\epsilon}$.
4. A planted-control oracle sets one generated formula to a trivial satisfiable/unsatisfiable control depending on b(x), so H_N=b(x) is easy while unrelated generated SAT ranges keep separator covers hard.

Equation 1: carrier.

$$H_N(x) = \bigvee_{j \leq N^q} SAT(G_N(x, j)), \quad |G_N(x, j)| = L = (\log N)^d.$$

Valid when: Valid when the carrier generator is uniform and emits length-L CNF instances with no nonuniform advice.

Equation 2: target-substitution.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N) \leq N^{\rho+o(1)} + N^q L^{O(c)} = N^{\max \rho, q+o(1)}.$$

Valid when: Applies after each generated query is substituted by the assumed SAT circuit and L is polylogarithmic.

Equation 3: separator-upper-bound.

$$C(H_N) \leq C(G_N) + O(DN^\sigma \log N + EN).$$

Valid when: Requires a one-sided separator cover with D local predicates of size N^{sigma} and E patchable bad bags.

Next analysis. Try to formulate a real-SAT locality extractor using witness self-reducibility: from a small circuit for H_N, isolate a generated satisfiable query and build a one-sided predicate; audit algebrization and $N^{o(1)}$ loss.

Falsifiers.

- Planted-control oracle falsifier: H_N has O(1) oracle-size circuits although one-sided separators on noncontrol ranges remain hard.
- Normal-form falsifier: an arbitrary H_N circuit may compute the OR globally without exposing any local formula predicate usable as a separator.
- Nonuniform leakage falsifier: advice can name the control coordinate or residual exceptions unless its cost is charged inside ρ or EN.
- Threshold falsifier: if $maxq, \rho \geq 1 + \epsilon$, even a valid H_N lower bound no longer magnifies to SAT $\notin$ P/poly.

cycle-0049: Hardness-Magnification Bridge Realization: locality extraction threshold

Execution. research; azure_responses_api; attempt primary; 140.845 seconds; 3 lemmas, 4 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 49 converts the surviving generated-OR route into an exact extraction-threshold problem. Separator-denominator hardness is a valid source certificate only if every small H circuit yields covers with denominator S/N^{1+sigma}+N^kappa and $\kappa < \epsilon - sigma$. Neutralization gives a concrete extraction but is a demagnifying falsifier, because it asks for restricted-SAT hardness rather than a barely-superlinear H lower bound.

Pressure. There is no valid operation converting an arbitrary global H circuit into local SAT-range separators without either neutralizing the generator or using a new real-SAT, nonrelativizing locality principle.

Derivation steps.

1. Assume a circuit A of size $S < N^{1+\epsilon}$ decides H_N^G.
2. Use A to define a residual positive distribution over generated bags and try to build one-sided local predicates accepting at least one satisfiable query per positive bag.
3. Attempt SAT self-reduction on a generated formula y=G_N(x,j); this manipulates assignments inside y but does not produce nearby inputs x' that alter only y.
4. Add a hypothetical neutralizing map E_j(y); then A(E_j(y)) exactly decides SAT on R_j, giving extraction but also demagnifying the source obligation to restricted SAT hardness.
5. Therefore the useful bridge is not separator hardness alone but the quantitative nonrelativizing extraction bound D<=S/N^{1+sigma}+N^kappa with $\kappa < \epsilon - sigma$.

Equation 1: generated_or_carrier.

$$H_N^G(x) = \bigvee_{j=1}^{N^q} SAT(G_N(x,j)), \quad |G_N(x,j)| = (\log N)^d$$

Valid when: Valid when the source object is the high-q generated-OR carrier with explicitly bounded generator complexity.

Equation 2: target_substitution_bound.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^G) \leq N^\rho + N^q(\log N)^{dc} + O(N^q) = N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT circuits are nonuniform, c is fixed, and generated queries have polylogarithmic length.

Equation 3: needed_extraction_bound.

$$A \in SIZE(S),\ A = H_N^G \Rightarrow D_{\sigma,E}(G;A) \leq S/N^{1+\sigma} \cdot polylog(N) + N^\kappa$$

Valid when: Valid when a nonrelativizing locality-extraction theorem converts arbitrary global H circuits into one-sided local covers.

Equation 4: separator_to_source_threshold.

$$D_{\sigma,E}(G) > N^{\epsilon-\sigma+\omega(1)},\ E < N^{\epsilon-o(1)},\ \kappa < \epsilon - \sigma \Rightarrow C(H_N^G) > N^{1+\epsilon-o(1)}$$

Valid when: Valid when the denominator lower bound holds for all residual covers produced by the extraction theorem.

Next analysis. Formalize one candidate extraction using SAT self-reducibility plus generator local decodability, then compute whether the required decodability already implies neutralizing embeddings and hence demagnification.

Falsifiers.

- falsifier: extraction tax $\kappa \geq \epsilon - sigma$ makes the separator lower bound too weak to force $C(H_N) > N^{1+\epsilon}$.
- falsifier: neutralizing embeddings provide a valid extraction but turn the source lower bound into a direct restricted-SAT lower bound at threshold $N^{1+\epsilon}$.
- falsifier: a planted-control oracle can keep one-sided local separators hard while making H_N easy, so any relativizing extraction theorem is false.
- falsifier: a subthreshold promise solver on the actual generated range gives C(H_N)<=N^rho+N^q $T_N + N^{q+o(1)}$.
- falsifier: a dense constructive direct-H lower-bound property triggers the natural-proofs obstruction under standard PRF hardness assumptions.

cycle-0050: Hardness-Magnification Bridge Realization: Relativizing Extraction Falsified

Execution. research; azure_responses_api; attempt primary; 158.599 seconds; 2 lemmas, 4 equations, 8 derivation steps, 6 falsifiers.

Learning. Cycle 50 gives a precise obstruction: small H_N circuits can coexist with superthreshold one-sided separator complexity in a structured singleton oracle. Thus the extraction bridge must be explicitly nonrelativizing and real-SAT-specific; separator hardness alone is not a valid source lower-bound certificate.

Pressure. The argument is an oracle obstruction, not a real-SAT lower bound. Real CNF satisfiability may have nonrelativizing syntactic structure unavailable to singleton oracle labels.

Derivation steps.

1. Replace SAT labels on the generated range by an oracle A while preserving the generated-OR interface $H_N^A(x) = OR_j$ A(G_N(x,j)).
2. Choose a structured slab X_N of $R = N^{a+o(1)}$ inputs with O(N)-size membership circuit.
3. Use $d > 1$ to inject X_N x [N^q] into the polylogarithmic label universe.
4. Plant exactly one positive label per slab bag according to an arbitrary selector $f : X_N \to [N^q]$, and plant no positives outside the slab.
5. Then H_N^A is exactly the slab membership predicate, so C(H_N^A)=O(N) despite arbitrary hidden choices of f.
6. A one-sided separator cover for all but E slab positives determines f on at least R-E inputs; otherwise it either misses the bag or accepts an oracle-negative label.
7. Counting covers of total size T gives T log T $\geq$ Omega((R-E)log N^q)-O(Rh(E/R)).
8. For E1+epsilon, every valid cover has size $N^{a-o(1)}$, contradicting any promised $sub - N^{1+\epsilon}$ relativizing extraction.

Equation 1: slab_capacity.

$$R = |X_N| = N^{a+o(1)}, \quad M = N^q, \quad RM = N^{a+q+o(1)} \leq 2^L$$

Valid when: Valid when $d > 1$ and a,q are fixed constants, so the polylogarithmic formula universe contains the polynomial slab range.

Equation 2: easy_carrier.

$$H_N^A(x) = \bigvee_{j \leq M} A(G_N(x, j)) = \mathbf{1}_{x \in X_N}, \quad C(H_N^A) = O(N)$$

Valid when: Valid when the oracle plants one positive label in each slab bag and no positive labels outside the slab.

Equation 3: selector_cover_counting.

$$T \log T \geq \Omega((R - E) \log M) - O(Rh(E/R))$$

Valid when: Valid when a one-sided cover of size T must encode a partial selector agreeing with f on at least R-E slab inputs.

Equation 4: threshold_contradiction.

$$E < N^\epsilon,\ a > 1 + \epsilon \implies T \geq N^{a-o(1)} > N^{1+\epsilon}$$

Valid when: Applies when the extraction promises subthreshold separator cost and the slab exponent is chosen above the lower-bound threshold.

Next analysis. Audit real-SAT self-reduction or proof-certificate structure as a possible nonrelativizing extractor, and compute whether its verifier/certificate overhead stays below $N^{1+\epsilon}$ rather than collapsing to restricted-SAT hardness.

Falsifiers.

- structured-slab singleton oracle falsifier for subthreshold relativizing locality extraction
- threshold collapse if the slab exponent a is not above 1+epsilon
- model mismatch if the extraction treats formula labels as pair-oracle cells rather than real CNF strings
- nonuniform leakage through an explicit selector table when the covered positive slab has size at most $N^{1+\epsilon-o(1)}$
- generator collisions or low semantic range that allow a compact one-sided cover
- neutralization that proves restricted-SAT hardness instead of a barely-superlinear H_N lower bound

cycle-0051: Hardness-Magnification Bridge Realization - cycle 51 direct-sum demagnification audit

Execution. research; azure_responses_api; attempt primary; 172.807 seconds; 3 lemmas, 5 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 51 identifies a new quantitative conservation law: the same gap g_N that protects the target transfer against all SAT polynomial exponents becomes the per-slot lower-bound burden for any direct-sum source proof. Hence slot-wise SAT hardness cannot be the weak source; a valid route must prove aggregate H_N hardness or supply a nonrelativizing extraction theorem.

Pressure. This proves only a quarantine for factorized source certificates. It does not rule out a genuinely aggregate arbitrary-circuit lower bound for H_N or a nonrelativizing extraction theorem using real SAT structure.

Derivation steps.

1. Let $M_N = N^{q_N}$ and L=(log N)^d. Under SAT_L in SIZE(L^c), substitute one SAT circuit into every generated slot; this gives $C(H_N) \le N^{\rho+o(1)} + M_N\ L^{c+O(1)}$.
2. To contradict a source lower bound $C(H_N) > N^{1+\epsilon}$, the carrier must satisfy $\rho < 1+\epsilon$ and M_N L^c=o(N^{1+epsilon}) for each fixed c. Equivalently $g_N = N^{1+\epsilon}/M_N$ is $L^{\omega(1)}$.
3. Assume the source proof factors through a per-slot SAT lower bound b(L) with at most linear aggregation: $C(H_N) \ge M_N\ b(L)/N^{o(1)}$.
4. For this to exceed $N^{1+\epsilon}$, it must have $b(L) > g_N/N^{o(1)}$.
5. Combining the target-preserving condition with the source requirement forces $b(L) = L^{\omega(1)}$. For fixed q_N=2^{Omega(L^{1/d})}.
6. Therefore projection-slice proofs and direct-sum-from-SAT proofs do not realize weak hardness magnification for this carrier.

Equation 1: target_substitution_upper_bound.

$$C(H_N) \le N^{\rho+o(1)} + M_N L^{c+O(1)}$$

Valid when: Valid when the generator circuit is shared once and each generated SAT query is answered by the same length-L circuit family.

Equation 2: target_gap.

$$g_N := \frac{N^{1+\epsilon}}{M_N} = N^{1+\epsilon-q_N}$$

Valid when: Applies when the carrier threshold is $N^{1+\epsilon}$ and the OR fan-in is $M_N = N^{q_N}$.

Equation 3: p_poly_preservation.

$$\forall c\ M_N L^c = o(N^{1+\epsilon}) \quad \Longleftrightarrow \quad \forall c\ L^c = o(g_N)$$

Valid when: Valid when the target consequence is SAT $\notin$ P/poly rather than exclusion of only one fixed exponent.

Equation 4: direct_sum_source_requirement.

$$M_N b(L)/N^{o(1)} > N^{1+\epsilon} \quad \Rightarrow \quad b(L) > g_N/N^{o(1)}$$

Valid when: Requires the proposed source lower bound to factor through M_N local SAT costs with only subpolynomial losses.

Equation 5: fixed_gap_demagnification.

$$q_N \leq 1 + \epsilon - \delta \Rightarrow g_N \geq 2^{\delta L^{1/d} - o(L^{1/d})}$$

Valid when: Valid when $d > 1$ is fixed and logarithms define L=(log N)^d up to constant factors.

Next analysis. Try to formalize an aggregate lower-bound normal form for H_N that distinguishes global OR computation from M_N independent SAT_L copies, and test it against the planted-control oracle before using separator hardness.

Falsifiers.

- direct-sum demagnification falsifier: a source proof of the form M_N b(L) requires $b(L) > g_N$, while target preservation requires $g_N = L^{\omega(1)}$.
- projection-slice falsifier: the special case $M_N = 1$ demands a length-L SAT lower bound of size N^{1+epsilon}=2^{Omega(L^{1/d})}.
- near-boundary finite-exponent falsifier: if $g_N = L^B$, the bridge is valid only against SAT circuits of exponent below B-O(1), not against P/poly.
- relativizing separator falsifier: hard one-sided local separators can coexist with tiny H_N circuits in the planted-control oracle.
- nonuniform sharing falsifier: multiple editable slices do not by themselves yield an $M_N - fold$ lower bound for arbitrary circuits without an explicit direct-sum theorem.

cycle-0052: Hardness-Magnification Bridge Realization: XOR Carrier Repair

Execution. research; azure_responses_api; attempt primary; 151.347 seconds; 3 lemmas, 4 equations, 5 derivation steps, 6 falsifiers.

Learning. Cycle 52 contributes a concrete repair: XOR aggregation preserves the valid polylog-query magnification threshold while invalidating the OR-specific one-sided separator obstruction. The new source burden is sharper: prove aggregate parity-carrier hardness or rule out subthreshold parity sketches and sparse corrections. This is route-level progress only, with explicit falsifier tests.

Pressure. There is no nonrelativizing theorem extracting a parity sketch, low-rank transcript, or other analyzable normal form from an arbitrary small circuit for H_N^{oplus}; direct C(H_N^oplus)>N^{1+epsilon} remains unproved.

Derivation steps.

1. Kept the polylog query window L=(log N)^d with $d > 1$ so SAT polynomial-size circuits substitute as $N^{o(1)}$ per query and exhaustive lookup is not automatically subthreshold.
2. Replaced the generated-OR carrier by H_N^{oplus}, the parity of $M = N^q$ generated SAT labels.
3. Computed the target transfer C(H_N^oplus)<=C(G_N)+O(M(s(L)+L)+M), yielding $N^{max\rho,q+o(1)}$ under SAT $\in$ SIZE(L^c).

4. Checked the previous one-sided separator machinery: it decides existential positivity of OR-bags but loses the parity of the number of satisfiable slots, so it cannot certify or refute XOR hardness without extra label information.

5. Isolated the new leakage normal form: any small feature or affine sketch plus sparse corrections gives an exact subthreshold circuit for H_N^{oplus}.

Equation 1: carrier_definition.

$$H_{N,G}^{\oplus}(x) = \bigoplus_{j=1}^{M} SAT(G_{N,j}(x)), \quad M = N^q, \quad L = (\log N)^d.$$

Valid when: Valid when $G_{N,j}$ output length-L encodings of SAT instances and the XOR fan-in M is explicitly charged.

Equation 2: substitution_upper_bound.

$$C(H_{N,G}^{\oplus}) \leq C(G_N) + O(M \cdot (s(L) + L) + M).$$

Valid when: Applies after one size-s(L) SAT circuit is substituted into every generated query without advice depending on x.

Equation 3: polylog_transfer.

$$s(L) \leq L^c,\ C(G_N) \leq N^\rho \ \Rightarrow\ C(H_{N,G}^{\oplus}) \leq N^{\max \rho, q+o(1)}.$$

Valid when: Valid when d is fixed, c is fixed, and L=(log N)^d remains $N^{o(1)}$.

Equation 4: target_consequence.

$$\big(C(H_{N,G}^{\oplus}) > N^{1+\epsilon} \text{ i.o. } \wedge\ \max \rho, q < 1 + \epsilon\big) \Rightarrow SAT \notin P/poly.$$

Valid when: Requires the lower bound on the source carrier for infinitely many N and the target-preserving threshold gap to be fixed.

Next analysis. In the ideal random-label model for G_N, count subthreshold affine sketches of size N^α and estimate the tau,alpha,error threshold at which a union bound could certify parity-sketch resistance without pretending to prove the actual explicit carrier lower bound.

Falsifiers.

- threshold collapse: $maxq, \rho \geq 1 + \epsilon$ destroys the target-preserving gap
- polylog lookup collapse when $d \leq 1$ and q plus the lookup exponent falls below 1+epsilon
- nonuniform leakage from G_N that encodes SAT labels instead of generating target-clean queries
- subthreshold affine-sketch or feature-aggregator predictor for H_N^{oplus} with fewer than N^ϵ patchable errors
- complete per-slot promise solver on the generated range of total size below $N^{1+\epsilon}$
- natural-proof style source argument that is dense and constructive against $N^{1+\epsilon}$ circuits under standard pseudorandomness assumptions

cycle-0053: Hardness-Magnification Bridge Realization: XOR carrier affine-incidence audit

Execution. research; azure_responses_api; attempt primary; 128.573 seconds; 3 lemmas, 6 equations, 4 derivation steps, 7 falsifiers.

Learning. Cycle 53 converts the XOR repair into an exact affine-incidence conservation law. The carrier equals the F_2 inner product of the SAT label vector with a generated parity-incidence vector; low-dimensional computable incidence structure makes the carrier easy by hardwiring basis parities. This is a new concrete falsifier for the source lower bound, while the polylog-query target bridge remains valid.

Pressure. A small circuit for H_N^{oplus} computes only the scalar inner product ; it need not reveal p_x, a low-rank coordinate map, or any local SAT separator. The extraction is false in planted-label oracle worlds and would need real-SAT, nonrelativizing content.

Derivation steps.

1. Rewrite the XOR carrier as $H_N^{oplus}(x) =$ over F_2.
2. Observe that a low-cost affine-incidence sketch gives a small circuit by hardwiring basis parities gamma_i.
3. Try to prove the contrapositive: if all such sketches have $A_N + K + E_{NN} > N^{1+\epsilon}$, then C(H_N^oplus)>N^{1+epsilon}.
4. Audit the extraction direction from an arbitrary small H circuit to an affine sketch of p_x.

Equation 1: xor_carrier.

$$H_N^{\oplus}(x) = \bigoplus_{j=1}^{M} SAT(G_N(x,j)), \quad M = N^q, \quad L = (\log N)^d.$$

Valid when: Valid when G_N outputs length-L SAT instances and the XOR is taken over F_2 with nonadaptive slots.

Equation 2: incidence_inner_product.

$$H_N^{\oplus}(x) = \langle p_x, s \rangle_{\mathbb{F}_2}, \quad p_x(y) = |j : G_N(x,j) = y| \bmod 2.$$

Valid when: Valid when U_N is the generated formula universe and s(y) records the real SAT label.

Equation 3: sketch_representation.

$$p_x = \sum_{i=1}^{K} a_i(x) b_i \text{ for all } x \notin B_N, \quad |B_N| = E_N.$$

Valid when: Valid when coefficient circuits compute a_i and exceptions are measured over N-bit inputs.

Equation 4: hardwired_basis_parities.

$$\gamma_i = \langle b_i, s \rangle_{\mathbb{F}_2}, \quad H_N^{\oplus}(x) = \bigoplus_{i:\gamma_i=1} a_i(x) \text{ for } x \notin B_N.$$

Valid when: Valid when nonuniform circuits may hardwire the K basis parities as advice constants.

Equation 5: upper_bound_falsifier.

$$C(H_N^{\oplus}) \leq O(A_N + K + E_N N).$$

Valid when: Valid when bad inputs are patched by equality tests and fan-in two XOR gates are allowed.

Equation 6: source_gate.

$$\forall \text{ affine-incidence sketches} \quad A_N + K + E_N N > N^{1+\epsilon-o(1)}.$$

Valid when: Valid when the claimed source lower bound is C(H_N^oplus)>N^{1+epsilon-o(1)} in general nonuniform circuits.

Next analysis. Instantiate $G_{N,\theta}$ with linear, pairwise-independent, and extractor-style query maps; compute K, coefficient-circuit cost A_N, duplicate parity cancellations, and whether any case survives the $N^{1+\epsilon}$ affine-sketch falsifier threshold.

Falsifiers.

- affine-incidence sketch with $K + A_N + E_{NN}$ below $N^{1+\epsilon-o(1)}$
- duplicate or even-multiplicity query generation causing $p_x = 0$ on many inputs
- small generated universe with easy standard-basis coefficients, allowing all SAT labels on U_N to be hardwired
- sparse correction set $E_N < N^{\epsilon-o(1)}$ patched by equality tests
- target threshold collapse when $maxq, \rho \geq 1 + \epsilon$
- rank-only or entropy-only argument that ignores the actual SAT label vector
- natural-proof risk if the affine-sketch exclusion is large and efficiently testable over random label tables rather than range-specific to SAT

cycle-0054: Hardness-Magnification Bridge Realization: XOR Carrier Approximate Affine-Sketch Gate

Execution. research; azure_responses_api; attempt primary; 150.117 seconds; 3 lemmas, 4 equations, 5 derivation steps, 6 falsifiers.

Learning. Cycle 54 strengthens the XOR route with an approximate piecewise-affine incidence-sketch conservation law. Bad seeds cost EN gates to patch, and a sketch of total cost s+Kr+EN below $N^{1+\epsilon}$ is a concrete falsifier for the source lower bound. High incidence rank alone is not valid lower-bound evidence because the SAT label functional may be simple on the generated image.

Pressure. Need a direct lower bound for the SAT-label pullback x → , or a non-natural real-SAT theorem showing that every subthreshold H_N circuit induces a subthreshold approximate affine-incidence sketch. Current rank and sketch audits are only falsifiers.

Derivation steps.

1. Represent the XOR carrier as $H_N(x) =$ over F_2.
2. Try to prove $C(H_N) > N^{1+\epsilon}$ from the claim that A_N({0,1}^N) has no low-dimensional affine sketch.
3. Observe that any exact or approximate piecewise-affine sketch yields a small H_N circuit by hardwiring the SAT inner products of the affine bases.
4. Strengthen the necessary audit to piecewise-affine sketches with exceptional-set correction cost EN.
5. Test whether large rank alone suffices; it fails because the fixed SAT label vector may be simple on the generated image.

Equation 1: incidence_pullback.

$$H_N(x) = \langle A_N(x), Y_{SAT} \rangle_{\mathbb{F}_2}$$

Valid when: Valid when A_N records generated formulas with parity multiplicity and Y_{SAT} is the fixed truth-label vector on L-bit formulas.

Equation 2: piecewise_affine_evaluation.

$$H_N(x) = \lambda_t \oplus \bigoplus_{i \le r} z_i \mu_{t,i}, \quad \lambda_t = \langle a_t, Y_{SAT} \rangle,\ \mu_{t,i} = \langle b_{t,i}, Y_{SAT} \rangle$$

Valid when: Valid when x is nonexceptional and the sketch representation of A_N(x) holds inside the selected affine piece.

Equation 3: sketch_upper_bound.

$$C(H_N) \le O(s + Kr + K \log K + EN)$$

Valid when: Applies when the sketch circuit computes piece indices and coordinates and exceptional seeds are corrected by explicit equality tests.

Equation 4: source_falsifier_threshold.

$$s + Kr + EN \le N^{1+\epsilon-\Omega(1)} \implies C(H_N) \not> N^{1+\epsilon-o(1)}$$

Valid when: Valid in the barely-superlinear source regime where lower bounds are measured against unrestricted nonuniform circuits of input length N.

Next analysis. Instantiate the hash-based XOR generator and compute whether its incidence map has an explicit low-cost piecewise-affine cover; if none is found, formulate the exact extraction theorem needed to turn small H_N circuits into such covers.

Falsifiers.

- falsifier: an exact affine incidence representation of rank $r < N^{1+\epsilon-o(1)}$ makes H_N easy by hardwiring basis parities.
- falsifier: an approximate piecewise-affine sketch with $s + Kr + EN < N^{1+\epsilon-o(1)}$ kills the source lower bound after equality patching.
- falsifier: a linear or low-degree algebraic generator whose parity-incidence map has computable rank O(N polylog N) collapses the XOR carrier to near-linear size.
- falsifier: a SAT-monochromatic generated range makes H_N constant even if the incidence image has high rank.
- falsifier: $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$ causes quantitative target-threshold collapse.
- falsifier: $d \leq 1$ with small lookup exponent may reintroduce exhaustive SAT-label leakage below the source threshold.

cycle-0055: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 288.009 seconds; 3 lemmas, 5 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 55 adds the SAT-preserving quotient normal form for XOR carriers. The valid target bridge is still $max\rho, q < 1+\epsilon$, but the source lower bound must beat quotient piecewise-affine incidence sketches, not raw range or rank. Symmetry-pair cancellation is a concrete falsifier that can make a high-entropy generator compute a constant carrier; this is route-level progress only, not a proof of P $\neq$ NP.

Pressure. Label-sensitive extraction gap: a small arbitrary circuit for the single function x $\rightarrow$ need not reveal a small quotient-incidence sketch, and high quotient rank alone does not preclude the SAT-labelled linear functional from being simple.

Derivation steps.

1. Write the XOR carrier as the F_2 inner product of the SAT truth vector tau_L with the generated incidence vector a_N(x).
2. Prove the polylog substitution upper bound: SAT circuits of size n^c yield H_N circuits of size $N^{max\rho,q+o(1)}$.
3. Try to certify $C(H_N) > N^{1+\epsilon}$ from high rank or expansion of the incidence map x $\rightarrow$ a_N(x).
4. Normalize by quotienting formula space under SAT-preserving symmetries and by cancelling even multiplicities.
5. Observe that a piecewise affine quotient sketch of cost below $N^{1+\epsilon}$ directly computes H_N after hardwiring basis parities and patching sparse exceptions.

Equation 1: xor_incidence_identity.

$$H_N(x) = \bigoplus_{j=1}^{m} \mathrm{SAT}(\phi_{N,j}(x)) = \langle \tau_L, a_N(x) \rangle_{\mathbb{F}_2}$$

Valid when: Valid when G_N outputs syntactic formula encodings and repeated formulas are counted with parity over F_2.

Equation 2: polylog_substitution_bound.

$$\mathrm{SAT} \in \mathrm{SIZE}(n^c) \;\Rightarrow\; C(H_N) \le O(C(G_N) + m\,L^c + mL) = N^{\max \rho, q+o(1)}$$

Valid when: Applies after SAT has $n^c - size$ circuits and the generator has $N^\rho - size$ circuits with $m = N^q$ polylog-length queries.

Equation 3: target_magnification_threshold.

$$\max \rho, q < 1 + \epsilon \;\wedge\; C(H_N) > N^{1+\epsilon-o(1)} \;\Rightarrow\; \mathrm{SAT} \notin \mathrm{P/poly}$$

Valid when: Valid for infinitely many N against every fixed target exponent c because L=(log N)^d makes L^c=N^{o(1)}.

Equation 4: sat_preserving_quotient_identity.

$$H_N(x) = \langle \tau_L^{\sim}, a_N^{\sim}(x) \rangle_{\mathbb{F}_2}$$

Valid when: Requires the equivalence relation to preserve SAT labels on every quotient class used by the generated formulas.

Equation 5: quotient_sketch_upper_bound.

$$C(H_N) \le O(\mathsf{QSk}_{\sim,N}(E) + EN)$$

Valid when: Requires a piecewise affine sketch of the quotient incidence vector correct outside E named seeds and allows nonuniform hardwiring of the resulting SAT parities.

Next analysis. Compute QSk_{sim,N}(E) for quotient relations generated by equality, variable renaming, clause permutation, tautological padding, and duplicate-pair involutions on the current high-q XOR carrier template; record the smallest residual exponent u and pairing-certificate cost.

Falsifiers.

- falsifier: an easy SAT-preserving quotient collapses the odd incidence vectors to subthreshold piecewise affine dimension while raw formula range remains high.
- falsifier: fixed-point-free duplicate, variable-renaming, or clause-permutation pairings cancel most XOR slots before any SAT hardness is used.
- falsifier: $QSk_{sim,N}(E) + EN < N^{1+\epsilon-o(1)}$ for some $E < N^{\epsilon-o(1)}$ gives an explicit nonuniform circuit for H_N.
- falsifier: high quotient rank is aligned with a low-cost SAT-labelled linear functional, so rank-only evidence is not valid source lower-bound evidence.
- falsifier: a proposed quotient relation or sketch uses SAT truth-table advice inside G_N, causing nonuniform leakage and breaking the target-clean interface.

cycle-0056: Hardness-Magnification Bridge Realization: XOR quotient codebook gate

Execution. research; azure_responses_api; attempt primary; 180.382 seconds; 3 lemmas, 4 equations, 5 derivation steps, 7 falsifiers.

Learning. Cycle 56 adds a sharper conservation law for XOR carriers: after SAT-preserving parity quotienting, H_N is easy whenever the incidence map has either low affine rank or a low-cardinality computable transcript, with patchable errors charged by EN. Thus high quotient entropy or high rank alone is not valid source evidence; the source obligation is a combined codebook-or-rank minimax lower bound, while the target bridge remains unchanged.

Pressure. The derivation does not show that every small arbitrary circuit for H_N yields such a quotient sketch. It is an upper-bound falsifier, not a lower-bound certificate.

Derivation steps.

1. Normalize each generated multiset by deleting pairs with equal SAT-preserving quotient class; the remaining parity-incidence vector is a_N(x).
2. For an affine cell, fix a basis $b_{i,1}, ..., b_{i,r_i}$ and hardwire the bits plus the affine offset bit; compute the coordinate decoder and XOR the selected constants.
3. For a codebook cell, hardwire $p_{i,t} =$ for every transcript value t in [R_i]; compute t_i(x) and evaluate a table circuit of size O(R_i log R_i).
4. Use the cheaper implementation on each cell, multiplex by the cell locator, and patch each of the E uncovered seeds by an equality test on the N-bit input.
5. The resulting circuit size is O(S+sum_i min{r_i,R_i log R_i}+EN), so any sketch below $N^{1+\epsilon}$ contradicts the desired source lower bound.

Equation 1: xor-quotient-normal-form.

$$H_N(x) = \langle \lambda_N, a_N(x) \rangle_{\mathbb{F}_2}, \qquad a_N(x) \in \mathbb{F}_2^{Q_N}.$$

Valid when: Valid when generated formulas are reduced only by odd parity cancellation and by a quotient preserving SAT labels.

Equation 2: codebook-rank-upper-bound.

$$C(H_N) \le O\left(S + \sum_i \min r_i, R_i \log R_i + EN \right).$$

Valid when: Applies when the sketch covers all but E seeds and each bad seed is patchable by an equality circuit of size O(N).

Equation 3: target-substitution-bound.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N) \le N^\rho + N^q L^c + N^q \operatorname{polylog} L = N^{\max \rho, q+o(1)}.$$

Valid when: Requires polylogarithmic query length, fixed target exponent c, and a generator circuit of size N^ρ.

Equation 4: magnification-threshold.

$$C(H_N) > N^{1+\epsilon} \ \wedge \ \max \rho, q < 1 + \epsilon \Rightarrow \forall c \, SAT \notin SIZE(n^c).$$

Valid when: Valid when the source lower bound holds for infinitely many large N and the query lengths L tend to infinity.

Next analysis. Instantiate a candidate high-q generator and compute the exponent of its SAT-preserving odd-support transcript range versus affine span rank; reject it if min{theta,rank-exponent}+locator-cost falls below 1+epsilon.

Falsifiers.

- Subthreshold quotient codebook sketch: $S + sum_i \ R_i \log R_i + EN < N^{1+\epsilon-o(1)}$ makes H_N easy by hardwired parity values.
- Low affine rank after SAT-preserving quotient: $S + sum_i \ r_i + EN < N^{1+\epsilon-o(1)}$ makes H_N easy by hardwired basis parities.
- Symmetry-pair cancellation: most generated SAT instances cancel modulo 2 inside Q_N, causing constant or low-transcript carriers despite high raw formula entropy.
- Target threshold collapse: $max\rho, q \geq 1 + \epsilon$ invalidates the magnification implication even if the source lower bound is true.
- Model mismatch falsifier: quotienting formulas by a relation that is not SAT-preserving breaks the identity $H_N =$.
- Nonuniform leakage through a short transcript table may decide H_N without computing SAT on any new formula.
- Natural-proof falsifier: a proof using only random-label hardness of $lambda_N$ would not identify real SAT and is not valid route evidence under standard pseudorandomness barriers.

cycle-0057: Hardness-Magnification Bridge Realization: XOR quotient carrier, low-degree feature-sketch gate

Execution. research; azure_responses_api; attempt primary; 171.561 seconds; 3 lemmas, 5 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 57 adds a nonlinear conservation law for the XOR carrier. The source lower bound must beat low-degree quotient-feature sketches with threshold $S_T + binom(r, \leq t) + EN$, so high rank or high codebook entropy is not valid evidence. The target-preserving bridge is unchanged, but the source obligation is narrower and more nonrelativizing.

Pressure. No method is known to prove that the real SAT-labelled quotient functional avoids all subthreshold low-degree feature sketches. Random-incidence or random-label counting does not transfer to SAT.

Derivation steps.

1. Start with the quotient incidence representation $H_N(z) =$ over F_2, where y_N is the SAT label vector on generated quotient classes.
2. Cycle 56 handled the case A_N(z) lies in a low-rank affine subspace or in a small computable codebook; then hardwired basis parities or table entries compute H_N.
3. Generalize: suppose a small circuit T_N computes r_N features and the composed label functional equals a degree-t polynomial P_N(T_N(z)) except on E_N inputs.
4. Implement T_N once, hardwire all coefficients of P_N, compute all degree-at-most-t monomials, XOR selected monomials, and patch the E_N exceptional inputs by equality tests.
5. This yields $C(H_N)N^{1+\epsilon}$ is falsified whenever max{s,alpha t,1+eta}<1+epsilon.

Equation 1: xor_carrier.

$$H_N^{xor}(z) = \bigoplus_{j=1}^{\lfloor N^q \rfloor} SAT(F_{N,j}(z))$$

Valid when: Valid when the carrier is the repaired XOR aggregation route and every generated query has length L=(log N)^d.

Equation 2: target_substitution.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^{xor}) \leq N^{\rho} + N^q \, L^{c+O(1)} = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the generator size is N^{ρ}, q is fixed below the threshold, and L is polylogarithmic in N.

Equation 3: magnification_implication.

$$C(H_N^{xor}) > N^{1+\epsilon} \ \wedge \ \max \rho, q < 1 + \epsilon \Rightarrow SAT \notin P/poly$$

Valid when: Requires the target-preserving complexity-class transfer for every fixed SAT circuit exponent c with no advice leakage.

Equation 4: feature_sketch_upper_bound.

$$C(H_N^{xor}) \leq S_T + O\left(\sum_{i=0}^{t} \binom{r_N}{i}\right) + O(E_N N)$$

Valid when: Valid when H_N agrees off E_N inputs with a degree-t polynomial in the computed feature vector T_N(z).

Equation 5: constant_degree_threshold.

$$r_N = N^{\alpha}, \ S_T = N^s, \ E_N = N^{\eta} \Rightarrow C(H_N^{xor}) \leq N^{\max s, \alpha t, 1+\eta+o(1)}$$

Valid when: Applies for constant t and polynomial-size parameters so the monomial count has exponent α times t.

Next analysis. Formalize the degree-2 case: characterize whether Tseitin-style parity, formula-size, variable-incidence, or clause-type features give $r = N^{\alpha}$ with $2alpha < 1 + \epsilon$ for the generated length-(log N)^d SAT queries.

Falsifiers.

- A degree-t quotient-feature sketch with $r = N^{\alpha}$ and $\alpha\ t < 1 + \epsilon$ is a concrete falsifier for the source lower bound.
- An error set of size $E < N^{\epsilon}$ is patchable by O(EN) equality gates and cannot be ignored.
- A SAT-label annihilator making depend on few nonlinear features defeats high raw quotient rank.
- A proof that only shows random labels avoid the sketch class is not valid for real SAT without a nonrelativizing transfer certificate.
- Any hidden hardwiring of the SAT truth table into T_N is nonuniform leakage and invalidates the claimed source model.

cycle-0058: Hardness-magnification bridge via XOR carriers and sparse quotient-polynomial falsifiers

Execution. research; azure_responses_api; attempt primary; 140.312 seconds; 3 lemmas, 4 equations, 5 derivation steps, 6 falsifiers.

Learning. Cycle 58 repairs the XOR-carrier audit: low degree was the wrong nonlinear measure. The valid upper-bound falsifier is sparse quotient-polynomial support with threshold $S_T + A_N\ r_N + E_N\ N < N^{1+\epsilon}$. This preserves the polylog-query target bridge but narrows the source obligation and exposes a new extraction gap: sparse-sketch hardness is not yet general-circuit hardness.

Pressure. No valid derivation converts an arbitrary small H_N circuit into a charged sparse quotient-polynomial sketch. Without this extraction, sketch lower bounds are falsifier tests, not source lower bounds.

Derivation steps.

1. Start from the quotient normal form $H_N =$ over F_2 for the XOR carrier.
2. Observe that cycle 57's low-degree feature bound gives $C(H_N) \leq S_T + binom(r, \leq t) + E_N$ N when the final combiner has degree t.
3. Test the converse direction: high degree does not imply high circuit cost, because a degree-r monomial needs only O(r) gates after feature computation.
4. Replace the degree parameter by monomial support A_N and derive C(H_N)<=S_T+O(A_N $r_N + E_N$ N).
5. Check target preservation separately: SAT $\in$ SIZE(n^c) still gives $C(H_N) \leq N^{max\rho, q+o(1)}$ for polylogarithmic queries.

Equation 1: quotient-inner-product-normal-form.

$$H_N(x) = \bigoplus_{u \in U_N} a_u I_{N,u}(x) = \langle a_N, I_N(x) \rangle_{\mathbb{F}_2}.$$

Valid when: Valid when U_N is a SAT-preserving quotient of the generated formulas and I_N records parity incidence per quotient class.

Equation 2: target-substitution-upper-bound.

$$SAT \in SIZE(n^c) \;\Rightarrow\; C(H_N) \leq N^{\rho + o(1)} + N^q L_N^{c+O(1)} = N^{\max \rho, q + o(1)}.$$

Valid when: Applies when SAT on length L_N formulas has nonuniform size L_N^c and the generator is target-clean.

Equation 3: sparse-sketch-upper-bound.

$$H_N = P_N(T_N) \text{ off } B_N,\ |B_N| = E_N \;\Rightarrow\; C(H_N) \leq S_T + O(A_N r_N + E_N N).$$

Valid when: Requires that all feature circuits are charged once, monomial gates share them, and exceptions are patched by equality tests.

Equation 4: exponent-falsifier-threshold.

$$S_T \leq N^\sigma,\ A_N \leq N^\alpha,\ r_N \leq N^\gamma,\ E_N \leq N^\eta \;\Rightarrow\; C(H_N) \leq N^{\max \sigma, \alpha+\gamma, 1+\eta+o(1)}.$$

Valid when: Valid when the parameter exponents are asymptotic and r_N is at most $N^{\gamma + o(1)}$.

Next analysis. Formalize the weakest nontrivial extraction candidate: restrict arbitrary H_N circuits to circuits whose wires are invariant under SAT-preserving quotient symmetries, and test whether such invariant circuits collapse to sparse quotient-polynomial sketches with subthreshold loss.

Falsifiers.

- Sparse quotient-polynomial sketch with $S_T + A_N\ r_N + E_N\ N < N^{1+\epsilon-o(1)}$.
- High-degree but one-monomial combiner, showing that degree-only hardness evidence is not valid.
- Uncharged feature map that directly computes H_N, collapsing the audit into a tautology rather than a route-specific falsifier.
- Target threshold collapse when $max\rho, q \geq 1 + \epsilon$ or when L_N is not polylogarithmic.
- Nonuniform leakage of the SAT label vector into the generator or feature circuits without being charged.
- Relativizing planted-control oracle where H_N is easy while quotient-sketch or separator measures remain hard.

cycle-0059: Hardness-Magnification Bridge Realization: XOR carrier sparse-sketch audit

Execution. research; azure_responses_api; attempt primary; 296.472 seconds; 3 lemmas, 3 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 59 identifies a conservation law for the XOR-carrier audit: unrestricted sparse quotient-polynomial hardness is not a simplification of the source lower bound, since $T = H_N$ is an admissible one-bit quotient transcript. The valid contribution is a sharper quarantine: sparse sketches remain concrete upper-bound falsifiers, while any proof-relevant sketch lower bound now needs a named label-free transcript class plus a nonrelativizing extraction theorem. The main P $\neq$ NP conjecture is untouched.

Pressure. No nonrelativizing locality-extraction theorem is known that converts an arbitrary small circuit for the real SAT-XOR carrier into a subthreshold label-free incidence transcript; relativizing planted-control examples block the naive argument.

Derivation steps.

1. Start with the XOR carrier $H_N(x) =$ over F_2 and keep the stable target bridge $max\rho, q < 1+\epsilon$.
2. Try to replace the direct general-circuit lower bound $C(H_N) > N^{1+\epsilon}$ by hardness against sparse quotient-polynomial sketches.
3. Any sketch with transcript cost S_T, support A, dimension r, and E errors gives C(H_N)<=S_T+O(A r+E N). This is a valid upper-bound falsifier.
4. For the reverse direction, if unrestricted quotient transcripts are allowed, choose T(x)=H_N(x), $r = 1$, and $P(z) = z$. Then SQP_all_N(H_N)<=C(H_N)+O(1).
5. Thus unrestricted sparse-sketch hardness is equivalent to the original source lower bound and does not reduce the proof burden.
6. Restricting transcripts to label-free incidence features makes the falsifier meaningful, but the derivation then needs an extraction theorem from arbitrary small H_N circuits to those features.

Equation 1: xor-carrier-incidence-form.

$$H_N(x) = \bigoplus_{j \leq m_N} SAT(G_N(x, j)) = \langle a_N(x), y_N \rangle_{\mathbb{F}_2}$$

Valid when: Valid when the generator outputs only length L_N SAT formulas and duplicate formulas are counted modulo two.

Equation 2: sparse-sketch-upper-bound.

$$C(H_N) \leq S_T + O(Ar + EN)$$

Valid when: Valid when P has A monomials over r transcript bits and differs from H_N on at most E inputs.

Equation 3: unrestricted-sqp-equivalence.

$$SQP_N^{all}(H_N) \leq C(H_N) + O(1) \quad \text{and} \quad C(H_N) \leq O(SQP_N^{all}(H_N))$$

Valid when: Valid when the audit permits arbitrary quotient-respecting transcripts, including the one-bit transcript T(x)=H_N(x).

Next analysis. Formalize the local-linear incidence transcript class for the XOR SAT carrier and compute the minimum sparse F_2 support needed under a random-generator model, while auditing whether any extraction from arbitrary circuits to that class can avoid the planted-control relativization falsifier.

Falsifiers.

- tautological transcript falsifier: $T = H_N$, $r = 1$, $\mathrm{P}(z) = z$ collapses any unrestricted sparse-sketch audit
- structured sparse-polynomial falsifier: $S_T + A$ r+E $N < N^{1+\epsilon-o(1)}$ gives an explicit upper bound for H_N
- nonuniform leakage through SAT-label-dependent transcript features
- relativizing planted-control oracle blocking locality extraction
- threshold collapse if max{rho,q} reaches 1+epsilon
- model mismatch if the source lower bound is proved only for structured sketches but advertised as a general-circuit lower bound

cycle-0060: Constructive Label-Free Sketch Gate for XOR Magnification

Execution. research; azure_responses_api; attempt primary; 161.208 seconds; 3 lemmas, 4 equations, 5 derivation steps, 7 falsifiers.

Learning. Cycle 60 separates two notions previously conflated. Sparse quotient-polynomial sketches are valid upper-bound falsifiers only when the transcript is constructively label-free; otherwise $T_N = H_N$ collapses the audit. The target bridge $max\rho, q < 1 + \epsilon$ survives, but sketch-hardness is not a source lower bound without a nonrelativizing extraction theorem or a direct C(H_N) lower bound.

Pressure. No theorem converts an arbitrary small circuit for the parity of SAT labels on generated queries into a constructively label-free low-support incidence sketch with subthreshold residual cost.

Derivation steps.

1. Write H_N as the F_2 inner product of the generated incidence vector a_N(x) with the SAT label vector y_N.
2. Assume a subthreshold circuit D_N of size $N^{1+\epsilon-\delta}$ computes H_N and try to use its gate transcript as T_N with P_N equal to the final gate.

3. This immediately violates label-freeness: D_N may encode information about y_N or about the carrier truth table, even if it never explicitly queries SAT.

4. Try expanding D_N as an algebraic normal form over seed bits or incidence coordinates; the support can blow up to 2^S and gives no $N^{1+\epsilon}$ threshold preservation.

5. Try quotienting incidences by syntactic SAT-preserving symmetries; this gives useful upper-bound falsifiers but not an extraction from arbitrary circuits.

Equation 1: xor-incidence-form.

$$H_N(x) = \bigoplus_{j=1}^{m_N} \mathrm{SAT}(F_{N,j}(x)) = \langle a_N(x), y_N \rangle_{\mathbb{F}_2}, \quad m_N = N^q, \quad L_N = (\log N)^d.$$

Valid when: Valid when G_N outputs m_N *length* $- L_N$ formulas and a_N records their mod-two incidences in the generated universe.

Equation 2: label-free-sketch-upper-bound.

$$C(H_N) \leq S_T + O(A_N r_N + E_N N).$$

Valid when: Valid when T_N is constructively label-free, P_N has A_N monomials, and equality gates patch exactly E_N exceptional seeds.

Equation 3: target-substitution-upper-bound.

$$\mathrm{SAT} \in \mathrm{SIZE}(n^c) \implies C(H_N) \leq N^{\rho+o(1)} + N^q L_N^c = N^{\max \rho, q+o(1)}.$$

Valid when: Applies after the generator has size $N^{\rho+o(1)}$ and every generated query has polylogarithmic length L_N.

Equation 4: magnification-threshold.

$$C(H_N) > N^{1+\epsilon} \text{ i.o. } \wedge \ \max \rho, q < 1 + \epsilon \implies \mathrm{SAT} \notin \mathrm{P/poly}.$$

Valid when: Requires the lower bound to hold infinitely often against nonuniform circuits and fixed q,rho below the threshold.

Next analysis. Define the first concrete compiler class $T^{inc-lin}$: $T_N(x) = B_N$ a_N(x) for explicit SAT-preserving quotient matrices B_N of row sparsity polylog N, then compute the minimum $S_T + A_N\ r_N$ for representing H_N by sparse P_N in the high-q, $d = 2$ regime.

Falsifiers.

- Output-dependent transcript leakage: $T_N = H_N$ makes sparse-sketch hardness vacuous.
- SAT-label advice in the transcript compiler below the tested threshold invalidates label-freeness.
- Constructively label-free T_N with $S_T + A_N\ r_N + E_N\ N < N^{1+\epsilon-o(1)}$ is a direct source lower-bound falsifier.

- Symmetry-pair cancellation after SAT-preserving quotienting can make a high-entropy XOR carrier constant or sparse.
- Threshold collapse occurs if $max\rho, q \geq 1 + \epsilon$, since SAT substitution no longer contradicts the source lower bound.
- Lookup collapse reappears for $d \leq 1$ when the generated truth-table cost can fall below the claimed source threshold.
- A relativizing extraction attempt is blocked if small H_N circuits use oracle/advice correlations not recoverable from incidence structure.

cycle-0061: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 94.538 seconds; 2 lemmas, 5 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 61 upgrades the XOR-carrier audit from vague label-free transcripts to a costed global-codebook normal form. The valid new contribution is an explicit upper-bound falsifier $C(H_N) \leq S_T + S_D + \widetilde{O}(U_N + A_{Nr,N}) + E_{NN}$. This closes a leakage loophole in sparse quotient sketches, while exposing the exact remaining gap: absence of label-free sketches is not a general-circuit lower bound without a nonrelativizing extraction theorem.

Pressure. No extraction theorem converts arbitrary H_N circuits into constructively label-free codebook sketches. The trivial transcript $T_N = H_N$ is small whenever H_N is small but is not label-free and may encode SAT-label information semantically.

Derivation steps.

1. Fix the surviving escape regime L_N=(log N)^d with $d > 1$, $M_N = N^q$, and $max\rho, q < 1 + \epsilon$.
2. Substitute a hypothetical size n^c SAT circuit into all N^q query slots; since L_N^c=N^{o(1)}, obtain $C(H_N) \leq N^{max\rho,q+o(1)}$.
3. Define $LFSketch_N$ by an explicit codebook of U_N $length-L_N$ formulas, a label-free transcript T_N, and a decoder producing a sparse polynomial in hardwired SAT labels of codebook entries.
4. Build a nonuniform circuit for H_N by computing T_N, evaluating the decoder, looking up hardwired codebook labels, evaluating at most A_N monomials, and patching E_N exceptional source inputs.
5. Conclude that any $LFSketch_N$ with $S_T + S_D + \widetilde{O}(U_N + A_{Nr,N}) + E_{NN} < N^{1+\epsilon}$ is a concrete upper-bound falsifier for the desired source lower bound.
6. Attempt to prove the converse: small arbitrary circuits for H_N should yield small label-free sketches, making LFSketch hardness a source lower-bound certificate.

Equation 1: xor_carrier_definition.

$$H_N(x) = \bigoplus_{j=1}^{N^q} SAT(\Phi_{N,j}(x)), \qquad |\Phi_{N,j}(x)| = L_N = (\log N)^d.$$

Valid when: Valid when the source object is the generated XOR-SAT carrier with fixed q,d and generator outputs well-formed SAT instances for every valid N.

Equation 2: polylog_target_substitution.

$$SAT \in SIZE(n^c) \implies C(H_N) \le N^\rho + N^q L_N^c \, polylog(N) = N^{\max \rho, q+o(1)}.$$

Valid when: Applies after the controlled interface substitutes one nonuniform SAT circuit of length L_N into every generated query slot with L_N subpolynomial.

Equation 3: magnification_window.

$$C(H_N) > N^{1+\epsilon} \; i.o. \; \wedge \; \max \rho, q < 1 + \epsilon \implies \forall c \; C(SAT_n) \not\le n^c.$$

Valid when: Requires the target-preserving condition, cofinal valid source lengths, and a source lower bound exceeding the substitution upper bound for each fixed c.

Equation 4: label_free_codebook_upper_bound.

$$C(H_N) \le S_T + S_D + \widetilde{O}(U_N + A_N r_N) + O(E_N N).$$

Valid when: Valid when a constructively label-free transcript and decoder express H_N outside E_N bad inputs as a sparse polynomial in hardwired SAT labels of the enumerated codebook.

Equation 5: source_falsifier_threshold.

$$S_T + S_D + \widetilde{O}(U_N + A_N r_N) + E_N N < N^{1+\epsilon-o(1)} \implies C(H_N) < N^{1+\epsilon}.$$

Valid when: Valid in the nonuniform source model where codebook labels may be hardwired but the transcript construction itself contains no SAT-label advice.

Next analysis. Instantiate a candidate generator and compute U_N, A_N, r_N, E_N for its SAT-preserving quotient codebook; if the cost is subthreshold, quarantine that generator, otherwise formulate the exact extraction theorem it would require.

Falsifiers.

- label-dependent one-bit transcript falsifier: omitting label-freeness admits T_N(x)=H_N(x) and destroys the sketch audit.
- small global codebook falsifier: $U_N = N^{1+\epsilon-\omega(1)}$ with cheap decoder lets the circuit hardwire all relevant SAT labels.
- patchable-error falsifier: $E_N < N^{\epsilon-o(1)}$ bad source inputs cost only $E_{NN} < N^{1+\epsilon-o(1)}$ gates.
- positive-beta rollback falsifier: if $L_N = N^\beta$ with $\beta > 0$ then SAT $\in$ SIZE(n^c) gives C(H_N)<=N^{q+beta c+o(1)}, so only bounded c are excluded.
- nonuniform leakage falsifier: generator or transcript advice that depends on SAT labels can compress the carrier while preserving apparent range entropy.

cycle-0062: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.009 seconds; 2 lemmas, 5 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 62 adds a new fork: high incidence rank can make the XOR carrier lower-bound property large, so an efficient semantic certificate would be natural, while low rank is an upper-bound falsifier. The polylog $\beta = 0$ bridge remains valid, but the surviving source proof must be non-natural, non-large, proof-mediated, or direct.

Pressure. The derivation does not produce the actual source lower bound. It only says that high-rank, efficiently checkable, large certificates are barrier-exposed, while absence of label-free sketches is still not equivalent to arbitrary-circuit hardness without a nonrelativizing extraction theorem.

Derivation steps.

1. Fix U_N as the L-bit formula universe touched by G_N and write $H_{N,G,y} = A_N$ y over F_2 on the truth-table rows indexed by x in $0,1^N$.
2. For any Boolean function h on $0,1^N$, the set of labels y satisfying $A_N\ y = h$ is empty or an affine subspace of codimension r_N, hence has uniform measure 2^{-r_N}.
3. Union-bound over all size-S source circuits h. Using #SIZE(S)<=2^{K S log S} gives Pr_y[C(H_{N,G,y})<=S]<=2^{K S log S-r_N}.
4. If r_N exceeds K S log S by L^k, the lower-bound property $C(H) > S$ is overwhelmingly large over L-bit truth tables.
5. If SAT_L had $L^c - size$ circuits, the valid polylog substitution gives $C(H_{N,G,\mathrm{SAT}})N^{1+\epsilon-o(1)}$ rejects every $L^c - size$ truth table when $q, \rho < 1 + \epsilon$.
6. Thus a poly$(2^L) - constructive$ verifier accepting the actual SAT truth table and certifying R_N would be a natural property against SIZE(L^c), conditional on the usual PRF barrier assumptions.

Equation 1: xor_carrier_linearization.

$$H_{N,G,y}(x) = \langle a_N(x), y\rangle_{\mathbb{F}_2} = \bigoplus_{j=1}^{N^q} y_{G_N(x,j)}$$

Valid when: Valid when G_N outputs only L-bit formula encodings and a_N records queried positions with parity multiplicity over F_2.

Equation 2: polylog_target_substitution.

$$\mathrm{SAT}_L \in \mathrm{SIZE}(L^c) \Rightarrow C(H_{N,G,\mathrm{SAT}}) \le O(N^\rho + N^q L^c \operatorname{polylog} N) = N^{\max \rho, q+o(1)}$$

Valid when: Applies when L=(log N)^d, c is fixed, target circuits are nonuniform, and the generator has size N^ρ without SAT-label advice.

Equation 3: direct_circuit_density_bound.

$$\Pr_y[C(H_{N,G,y}) \le S] \le 2^{KS\log S - r_N}$$

Valid when: Valid when y is uniform over L-bit truth tables, r_N is the F_2 rank of the incidence rows, and size-S circuits are counted by 2^{K S log S}.

Equation 4: largeness_threshold.

$$r_N \ge KS\log S + L^k \Rightarrow \Pr_y[C(H_{N,G,y}) > S] \ge 1 - 2^{-L^k}$$

Valid when: Requires the incidence-rank gap to dominate the circuit-counting entropy and chooses k within the remaining explicit rank margin.

Equation 5: naturalness_fork.

$$\text{Constructive}(R_N) \wedge \text{Large}(R_N) \wedge \text{Useful}_{L^c}(R_N) \Rightarrow R_N \text{ is a natural property against SIZE}(L^c)$$

Valid when: Applies when R_N depends only on the L-bit truth table, is decidable in poly(2^L) time, and rejects all $L^c - size$ truth tables.

Next analysis. Instantiate the random-affine generator with L=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute r_N for the induced sparse incidence matrix and test whether the rank gap forces naturalness or low-rank falsification.

Falsifiers.

- falsifier: r_N<=O(N^{1+epsilon} log N) gives too little rank for the density-counting route and revives low-rank affine sketch upper bounds.
- falsifier: any transcript or codebook depending on SAT labels, including $T_N = H_N$, violates label-freeness and collapses the audit into nonuniform leakage.
- falsifier: a poly(2^L) $-$ *constructive* large certificate for the actual SAT label vector becomes a natural-property route under PRF assumptions, so it is not a valid barrier escape.
- falsifier: if a repaired carrier has target-query length N^β with $\beta > 0$, the q+beta c transfer cap blocks all-exponent SAT lower bounds.
- falsifier: hidden advice in G_N, the codebook, or the verifier above the $N^{1+\epsilon}$ budget invalidates the source lower-bound accounting.

cycle-0063: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.01 seconds; 2 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 63 upgrades the rank-density fork into a quantitative gate: low constructive rank is a direct upper-bound falsifier, while high rank makes any efficient useful certificate large in label space. The $\beta = 0$ magnification bridge is still valid, but rank-only evidence is quarantined unless the source proof is direct or explicitly non-natural and nonrelativizing.

Pressure. The branch still lacks a direct non-natural lower bound for H_N^{SAT} or a nonrelativizing theorem extracting a label-free sketch from every small H_N circuit.

Derivation steps.

1. Fix L=(log N)^d with $d > 1$ and define A_N so that $H_N^{ell} = A_N$ ell is the XOR of $N^{q+o(1)}$ generated length-L labels per source input.
2. Assume SAT_L has circuits of size L^c. Substitute the circuit into each query and add the generator cost to get C(H_N^{SAT})<=N^{max{rho,q}+o(1)}.
3. If $max\rho, qN^{1+\epsilon}$ is available, the substitution contradicts SAT_L in SIZE(L^c) for that fixed c; since c was arbitrary, this is the valid $\beta = 0$ bridge to SAT $\notin$ P/poly.
4. Audit the source proof. If rows of A_N have a basis-coordinate decoder of size D_N and rank r_N with $D_N + O(r_N) < N^{1+\epsilon}$, hardwire the r_N SAT basis parities and compute H_N^{SAT} below threshold; this is a concrete falsifier.
5. If r_N is much larger than s_N log(s_N+N), random label vectors produce high-complexity source functions with probability at least 1-2^{O(s_N log(s_N+N))-r_N}. Thus the semantic property C(A_N ell)>s_N is large in label space.
6. Any certificate Q_N contained in this property, decidable from the label truth table in poly(2^L), accepting SAT, and rejecting every label function with SIZE(L^c) circuits is a natural-proof-style object against SIZE(L^c). The route must then state a non-natural escape or remain only outside the known barrier conditionally.
7. Finally, rank-only hypotheses are relativizing-invalid: setting all labels to zero preserves A_N and its rank but makes H_N constant.

Equation 1: xor_carrier_definition.

$$H_N^{\ell}(x) = \bigoplus_{j \le M_N} \ell(G_N(x, j)) = (A_N \ell)(x)$$

Valid when: Valid when G_N is label-free, repeated generated formulas are counted modulo two, and ell is any Boolean label vector on the generated formula universe.

Equation 2: beta_zero_target_substitution.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + N^{q+o(1)} L^c = N^{\max \rho, q+o(1)}$$

Valid when: Applies after SAT has SIZE(L^c) circuits, L=(log N)^d is polylogarithmic, and generator/advice overhead is charged in ρ.

Equation 3: magnification_implication.

$$C(H_N^{SAT}) > N^{1+\epsilon} \ \wedge \ \max \rho, q < 1 + \epsilon \ \Rightarrow \ SAT \notin SIZE(n^c) \text{ for every fixed } c$$

Valid when: Requires the same carrier family, β zero target-query length, and a valid source lower bound for the actual SAT labels.

Equation 4: rank_density_count.

$$\Pr_{\ell \leftarrow 0,1^{U_N}}[C(A_N \ell) \leq s_N] \leq 2^{O(s_N \log(s_N+N))-r_N}$$

Valid when: Valid when A_N has F_2 rank r_N and low-complexity N-input source functions are counted by circuits of size at most s_N.

Equation 5: constructive_low_rank_falsifier.

$$C(H_N^{SAT}) \leq D_N + O(r_N)$$

Valid when: Requires an explicit row-coordinate decoder of size D_N and hardwiring the r_N basis parities of the actual SAT label vector as advice bits.

Next analysis. Perform the finite prior-art boundary check for the label-space naturalness claim, then instantiate the thought experiment with a concrete pairwise-independent generator and compute r_N, quotient rank, and any row-coordinate decoder cost D_N.

Falsifiers.

- positive β black-box transfer cap q+beta*c+o(1), which blocks all-exponent target preservation unless $\beta = 0$ or subpolynomial
- constructive low-rank row-coordinate decoder with $D_N + O(r_N) < N^{1+\epsilon}$
- label-free global codebook or sparse quotient-polynomial sketch below the source threshold
- rank-only proof surviving replacement of SAT labels by the zero oracle
- large poly(2^L) – *constructive* certificate useful against SIZE(L^c), triggering natural-proof exposure rather than a barrier escape

cycle-0064: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.009 seconds; 3 lemmas, 4 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 64 upgrades the XOR route from rank-density intuition to a fork theorem: low constructive incidence rank is an explicit upper-bound falsifier, while any large truth-table constructive anti-alignment proof for the SAT label pulls back through the valid $\beta = 0$ bridge to a natural property. The remaining source route must be direct, nonlarge, nonconstructive, proof-mediated, or explicitly nonrelativizing; this is route-level progress, not P $\neq$ NP.

Pressure. The route still lacks a nonlarge, nonconstructive, proof-mediated, or direct argument that the actual SAT label avoids the easy induced-XOR label set.

Derivation steps.

1. Model the XOR carrier as a linear map from formula-label vectors y over U_N to N-input truth tables H_N^y.
2. Assume a certificate property P_N contains y_N^{SAT} and excludes every y with $C(H_N^y) \leq S_N$.
3. Pull P_N back to a property of all $L_N - bit$ Boolean functions by testing only the coordinates in U_N; density is preserved exactly under random restriction.
4. If an $L_N - bit$ function f has circuits of size L_N^c, substituting that circuit into the generator computes H_N^f in size $N^{maxq,\rho+o(1)} < S_N$.
5. Therefore the pullback property rejects every SIZE(L_N^c) function but accepts SAT, and if it is constructive and large it is a natural property useful against polynomial-size circuits at length L_N.

Equation 1: xor_label_function.

$$H_N^y(x) = \bigoplus_{j \leq Q_N} y(G_N(x,j)) = \langle a_x, y \rangle_{\mathbb{F}_2}$$

Valid when: Valid when the carrier is the generated XOR construction and labels are assigned only to generated $L_N - bit$ formulas.

Equation 2: target_substitution_upper_bound.

$$SAT_{L_N} \in SIZE(L_N^c) \Rightarrow C(H_N^{SAT}) \leq N^{\rho} + Q_N\, L_N^{O(c)} = N^{\max \rho, q+o(1)} < S_N$$

Valid when: Applies after the generator overhead is N^{ρ}, query count is N^q, and β equals zero.

Equation 3: pullback_density_preservation.

$$\Pr_F[\widehat{P_N}(F)] = |P_N|/2^{|U_N|}$$

Valid when: Valid when F is uniformly random over all $L_N - bit$ truth tables and restriction to U_N is uniform.

Equation 4: natural_usefulness.

$$P_N \cap y : C(H_N^y) \leq S_N = \varnothing \ \wedge \ y_N^{SAT} \in P_N \Rightarrow \widehat{P_N}(SAT) = 1 \ \wedge \ \widehat{P_N}(f) = 0 \ \forall f \in SIZE(L_N^c)$$

Valid when: Requires the target-preserving substitution upper bound to put every small f inside the easy induced-XOR set.

Next analysis. Instantiate L_N=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute achievable M_N and r_N for an explicit generator family, then test for a label-free coordinate transcript or prove any proposed SAT anti-alignment certificate has density below $2^{-\omega(L_N)}$.

Falsifiers.

- falsifier: positive β gives the transfer cap q+beta*c+o(1) and cannot exclude all SAT exponents.
- falsifier: an exact label-free coordinate transcript with $S_T + r_N < N^{1+\epsilon-o(1)}$ makes every XOR label easy.
- falsifier: a large truth-table constructive anti-alignment certificate pulls back to a natural property under the $\beta = 0$ bridge.
- falsifier: rank below O(S_N log S_N) gives no distributional hard-label mass.
- falsifier: any SAT-label advice embedded in G_N or P_N invalidates the target-preserving condition.

cycle-0065: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 4 equations, 7 derivation steps, 4 falsifiers.

Learning. Cycle 65 closes a finite validation gap: short searchable proof certificates do not automatically escape natural proofs in the $\beta = 0$ XOR carrier. If they are large and sound, they form a valid natural property; if rank is low, there is a separate upper-bound falsifier. The surviving route is narrower: direct H_N lower bounds or nonlarge, nonconstructive, explicitly nonrelativizing proof objects.

Pressure. The argument is conditional as a barrier diagnosis: it uses the standard PRF-based natural-proofs obstruction and does not rule out nonlarge SAT-specific proofs, $\omega(L_N) - length$ proofs, nonconstructive verifiers, or nonrelativizing proof-system semantics.

Derivation steps.

1. Fix the XOR carrier $H_{N,y} = A_N$ y over F_2 and let r_N=rank(A_N). The map y $\to H_{N,y}$ has kernel size $2^{M_N - r_N}$.
2. Count N-input Boolean functions with circuits of size at most S_N as at most 2^{O(S_N log S_N)}. Therefore the easy-label density is at most 2^{O(S_N log S_N)-r_N}.
3. If r_N exceeds O(S_N log S_N)+Omega(log M_N), then the hardness property $y : C(H_{N,y}) > S_N$ is large. This is evidence of naturalness, not evidence for SAT.
4. For a proof relation R_N with $|pi| \leq aL_N$ and verifier time M_N^b, the existential property $Q_N(y) = exists$ pi R_N(y,pi) is decidable in $M_N^{O(1)}$ time by exhaustive proof search.
5. Soundness $R_N \Rightarrow C(H_{N,y}) > S_N$ plus $max\rho, q < 1 + \epsilon$ implies Q_N contains no label function y with SIZE(L_N^c) circuits for any fixed c, because substituting such a circuit into G_N yields $H_{N,y}$ of size below S_N.
6. Thus any large accepted set Q_N is constructive, large, and useful: exactly a natural property after encoding formula-code labels as $length - L_N$ truth tables.

7. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: beta_zero_substitution.

$$C(H_{N,y}) \leq N^{\rho+o(1)} + N^{q+o(1)} L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Valid when G_N is explicit, target queries have length L_N, and the substituted target circuit carries no additional advice.

Equation 2: rank_counting_large_hardness_property.

$$\Pr_{y \leftarrow 0,1^{M_N}} [C(H_{N,y}) \leq S_N] \leq 2^{O(S_N \log S_N) - r_N}$$

Valid when: Valid when A_N is viewed as an F_2 linear map from label vectors to carrier truth tables and small N-input circuits are counted nonuniformly.

Equation 3: search_time_for_proofs.

$$T_{decide}(\mathcal{Q}_N) \leq 2^{aL_N} M_N^b = M_N^{a+b}$$

Valid when: Valid when certificates have at most aL_N bits, the verifier runs in M_N^b time, and M_N equals 2^{L_N}.

Equation 4: usefulness_against_target_circuits.

$$\mathcal{Q}_N \cap SIZE(L_N^c) = \emptyset \quad \text{for every fixed } c$$

Valid when: Applies after the beta-zero substitution bridge preserves the same circuit model, the same advice convention, and the threshold $S_N = N^{1+\epsilon}$.

Next analysis. Instantiate R_N with a named proof system, e.g. Extended Frege or IPS, and test whether an LB certificate for $C(H_{N,y}) > N^{1+\epsilon}$ has $O(L_N) - bit$ searchable descriptions, inverse-polynomial label density, and truth-table soundness; otherwise record the precise escape parameter.

Falsifiers.

- falsifier: positive β gives C(H_N)<=N^{q+beta c+o(1)} and caps the claimed all-exponent transfer.
- falsifier: low constructive incidence rank gives C(H_{N,SAT})<=S_T+O(r_N), killing the $N^{1+\epsilon}$ source lower bound.
- falsifier: an $O(L_N) - searchable$ inverse-polynomially large proof certificate becomes a natural property, so it is not a valid barrier-escaping proof route under PRF assumptions.
- falsifier: label-dependent transcripts such as $T_N = H_N$ collapse the audit and are nonuniform leakage, not source evidence.

cycle-0066: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.006 seconds; 3 lemmas, 5 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 66 sharpens the proof-mediated XOR route: searchable certificates do not automatically trigger the standard natural-proofs barrier. The valid obstruction needs parametric soundness, constructivity, large pulled-back density, and a density-preserving label-realization map. Without these, the barrier claim is invalid, but the source proof must be direct, nonlarge, nonconstructive, or explicitly nonrelativizing.

Pressure. No explicit density-preserving label-realization map is known for the generated SAT universe U_N, and soundness of plausible proof predicates is usually shown only for the actual SAT label rather than for every artificial label y.

Derivation steps.

1. Parameterize the XOR carrier by an arbitrary label vector y so that the real SAT carrier is only the specialization $y = \mathrm{SAT}|_{U_N}$.
2. Assume a searchable Psys predicate $A_N(y) = exists$ pi V_N(y,pi) with same-theory parametric soundness $A_N(y) \Rightarrow C(H_{N,y}) > N^{1+\epsilon}$.
3. If SAT_L has size L^c circuits, substitute those circuits into the real carrier and obtain C(H_N^{SAT})<=N^{n preserving the $\beta = 0$ target bridge when $max\rho, q < 1 + \epsilon$.
4. To convert A_N into a standard natural property, introduce a realization map R_n from n-bit function truth tables to label vectors and require $H_{N,R_n(f)} = f \circ tau_n$ up to overhead chi_N.
5. Constructivity follows from computing R_n and searching pi within the declared truth-table time bound; usefulness follows because a small circuit for f would give a small circuit for $H_{N,R_n(f)}$.
6. Largeness follows only if the pullback density nu_n is at least $2^{-O(n)}$, or if a distortion bound D_N transfers label-space density mu_N to nu_n.
7. Therefore a large searchable sound proof predicate plus label realization yields a natural property; absence of realization or largeness is an escape condition but also a new source proof burden.
8. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: beta_zero_substitution.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + N^q L^c = N^{\max \rho, q+o(1)}$$

Valid when: Valid when L=(log N)^d, SAT_L has size L^c circuits, and the generator plus incidence computation is label-free with cost $N^{\rho+o(1)}$.

Equation 2: parametric_carrier.

$$H_{N,y}(z) = \bigoplus_{u \in U_N} I_N(z,u) y_u$$

Valid when: Valid when U_N is the fixed generated formula universe and I_N is computed independently of the SAT label vector y.

Equation 3: accepted_label_density.

$$\mu_N = 2^{-|U_N|} \, |y : \exists \pi, |\pi| \leq \ell_N, V_N(y,\pi) = 1|$$

Valid when: Valid when the verifier is evaluated over artificial label vectors y and proof length cutoff ell_N is fixed before seeing y.

Equation 4: pullback_density.

$$\nu_n = \Pr_f[A_N(R_n(f)) = 1] \geq D_N^{-1} \mu_N$$

Valid when: Applies after a density-distortion certificate R_n, D_N proves that accepted label sets pull back to truth-table functions with bounded loss.

Equation 5: usefulness_transfer.

$$A_N(R_n(f)) = 1 \Rightarrow C(f) > N^{1+\epsilon}/\chi_N$$

Valid when: Requires parametric soundness for $H_{N,y}$ and a realization certificate showing circuits for f induce circuits for $H_{N,R_n(f)}$ with overhead chi_N.

Next analysis. Instantiate R_n for one high-q polylog XOR carrier or prove a finite impossibility: no label-free density-preserving realization can coexist with $q, \rho < 1 + \epsilon$ and generator universe U_N of SAT formulas length (log N)^2.

Falsifiers.

- falsifier: positive target-query exponent β gives the upper bound N^{q+beta c+o(1)} and caps the target exponents before reaching SAT $\notin$ P/poly.
- falsifier: low constructive incidence rank or a global label-free codebook yields an explicit small circuit for the XOR carrier.
- falsifier: a large searchable sound proof predicate with density-preserving label realization becomes a natural property and is blocked under standard PRF-style assumptions.
- falsifier: no density-preserving realization map means label-space largeness is not a valid standard natural-proofs argument.
- falsifier: verifier advice or proof advice encoding $\mathrm{SAT}|_{U_N}$ destroys the target-preserving condition by nonuniform leakage.

cycle-0067: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.01 seconds; 2 lemmas, 5 equations, 8 derivation steps, 6 falsifiers.

Learning. Cycle 67 upgrades the previous label-realization warning into an exact restriction-extension theorem. For $\beta = 0$ XOR carriers, dense constructive label-mediated source lower bounds naturalize automatically when U_N is uniformly enumerable and soundness is in the same circuit model. The valid bridge survives, but any proof-mediated route must now be direct, nonlarge, nonconstructive, or explicitly nonrelativizing; ambient source-property largeness is not enough because density must be image-relative.

Pressure. No lower bound for C(H_N) is proved. The derivation only certifies that one dense constructive label-mediated proof shape would collide with natural-proofs methodology, while image-relative and nonlarge certificates remain open.

Derivation steps.

1. Fix the $\beta = 0$ XOR carrier with L=(log N)^d, $d > 1$, N^q generated queries, and overhead $N^{\rho+o(1)}$.
2. For any target circuit D of size L^c, substitute D into the generator and XOR combiner to obtain C(A_N y_D)<=N^{max{rho,q}+o(1)}.
3. If $C(H_N) > N^{1+\epsilon}$ and $max\rho, q < 1 + \epsilon$, then no such D computes SAT_L on the valid lengths; this is the route-level target bridge, not P $\neq$ NP.
4. Assume the proposed source proof is mediated by Q_N over labels on U_N, with $Q_N(y^{\mathrm{SAT}}) = 1$ and $Q_N(y) \Rightarrow C(A_{Ny}) > N^{1+\epsilon}$.
5. Define the full-target property widehat $Q_N(F) = 1$ iff F restricted to U_N lies in Q_N.
6. Uniform random full truth tables restrict to uniform labels on U_N, so density(widehat Q_N)=density(Q_N) with no loss.
7. Source soundness plus the $\beta = 0$ transfer makes widehat Q_N reject every SIZE(L^c) target circuit, while accepting SAT_L.
8. Hence a large constructive Q_N naturalizes; the surviving proof-mediated route must be nonlarge, nonconstructive, not label-factorized, or explicitly nonrelativizing and direct.

Equation 1: carrier-linearization.

$$H_y(x) = \bigoplus_{j \le N^q} y(\phi_{N,j}(x)) = (A_N y)(x), \quad H_N = A_N y_{U_N}^{SAT}$$

Valid when: Valid when U_N contains every generated query string and duplicate queries are quotient-counted modulo parity.

Equation 2: beta-zero-transfer.

$$C(A_N y_D) \leq N^{\rho+o(1)} + N^q L^c \, poly(L) = N^{\max \rho, q+o(1)}$$

Valid when: Valid when D is a SIZE(L^c) target circuit, L=(log N)^d, and substitution uses no advice except the fixed generator.

Equation 3: restriction-density.

$$\Pr_{F:0,1^L \to 0,1}[F|_{U_N} \in Q_N] = |Q_N|/2^{|U_N|} = \delta_N$$

Valid when: Valid when full target truth tables are sampled uniformly and U_N is fixed independently of the sampled labels.

Equation 4: naturalization-gate.

$$\delta_N \geq 2^{-O(L)},\ T_Q \leq 2^{O(L)},\ Q_N \Rightarrow C(A_N y) > N^{1+\epsilon} \implies \widehat{Q_N} \text{ is constructive and } c\text{-useful}$$

Valid when: Valid when source soundness is in the same nonuniform circuit model as the beta-zero transfer.

Equation 5: magnification-consequence.

$$C(H_N) > N^{1+\epsilon} \ \wedge\ \max \rho, q < 1+\epsilon \implies SAT_L \notin SIZE(L^c)$$

Valid when: Applies after the carrier lower bound holds on the chosen valid lengths and L^c=N^{o(1)} for fixed c.

Next analysis. Instantiate U_N for one explicit polylog-query XOR generator, compute whether U_N is enumerable in poly(2^L), and classify a candidate certificate as dense-label, image-relative, or nonlarge.

Falsifiers.

- positive β falsifier: if target query length is N^β with $\beta > 0$, the transfer N^{q+beta c+o(1)} cannot exclude all polynomial SAT exponents.
- low constructive incidence rank falsifier: a small row-coordinate transcript lets the XOR carrier hardwire basis parities and stay below $N^{1+\epsilon}$.
- label-free codebook falsifier: a compact quotient transcript plus sparse corrections gives $C(H_N) \leq S_T + S_D + \widetilde{O}(U_N + A_N r_N) + E_{NN}$.
- dense constructive label predicate falsifier for barrier-escape claims: if Q_N is large, constructive, and source-sound, restriction extension makes it a natural property.
- image-only density falsifier: largeness of P_N in the full source truth-table cube is irrelevant unless P_N is large on im(A_N).
- nonuniform leakage falsifier: if U_N or Q_N needs hidden advice not charged in poly(2^L), constructivity and target preservation fail.

cycle-0068: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 4 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 68 separates two notions previously conflated: label-mediated certificates for the $\beta = 0$ XOR carrier are large inside the realization image, but the image has ambient density at most 2^{-2^N+2^{o(N)}}. Thus the valid bridge to SAT $\notin$ P/poly survives, while the standard natural-proofs barrier requires a separate constructive ambient extension; this is a sharper route-status theorem, not progress on the main conjecture itself.

Pressure. No direct lower bound for the real SAT-label carrier H_N is obtained, and no polynomial-time density-preserving extension from Im(R_N) to ambient N-bit truth tables is known.

Derivation steps.

1. Fix $M = N^q$, L=(log N)^d with $d > 1$, and let G_N have size $N^{\rho+o(1)}$.
2. Assume SAT on L-bit formulas has circuits of size L^c. Substitute that circuit into all M XOR positions and compute G_N uniformly, giving $C(H_N) \leq N^{max\rho,q+o(1)}$.
3. Thus a valid source lower bound $C(H_N) > N^{1+\epsilon}$ contradicts SAT $\in$ SIZE(n^c) for every fixed c when $max\rho, q < 1 + \epsilon$.
4. Define U_N as the generated formula universe and $R_N(y)(x) = xor_j$ y(G_N(x,j)). Since formula strings have length L, |U_N|<=2^{O(L)}=2^{o(N)}.
5. The image Im(R_N) has at most $2^{|U_N|}$ carrier functions, while the ambient N-bit function space has size 2^{2^N}; hence any property supported only on Im(R_N) has density at most 2^{|U_N|-2^N}.
6. Therefore a label-mediated proof can be image-relative large and still fail standard natural-proofs largeness by an exponential margin.
7. For XOR maps, equal fiber sizes show label density transfers to image-relative density, so the exact missing certificate is not density inside the image but a constructive ambient extension preserving soundness.

Equation 1: beta0_target_transfer.

$$C(H_N) \leq N^{\rho+o(1)} + N^q L^c = N^{\max \rho,q+o(1)}$$

Valid when: Valid when $\beta = 0$ means L=(log N)^d and SAT circuits of size L^c are substituted independently into the $M = N^q$ generated queries.

Equation 2: all_exponent_consequence.

$$C(H_N) > N^{1+\epsilon} \ \wedge \ \max \rho, q < 1 + \epsilon \Rightarrow \forall c \, SAT \notin SIZE(n^c)$$

Valid when: Applies after the reduction preserves nonuniform circuit model identity, generator overhead ρ, query multiplicity q, and the fixed polylogarithmic query length.

Equation 3: realization_image_density.

$$\mu_{amb}(Im(R_N)) \leq 2^{|U_N|-2^N} \leq 2^{-2^N+2^{O((\log N)^d)}}$$

Valid when: Requires source functions on N input bits and carriers determined solely by labels on the generated formula universe U_N.

Equation 4: standard_largeness_failure.

$$|U_N| = 2^{o(N)} \Rightarrow \mu_{amb}(Im(R_N)) < 2^{-N^a} \quad \text{for every fixed } a$$

Valid when: Valid when d is fixed, L=(log N)^d, and natural-proofs largeness is the standard ambient $2^{-\text{poly}(N)}$ threshold.

Next analysis. Formalize the extension problem: given R_N and a sound searchable label certificate, prove either that no poly(N)-time ambient extension of density $2^{-\text{poly}(N)}$ exists for this certificate class, or that such an extension exists and therefore naturalizes the route.

Falsifiers.

- Positive β target-query length gives the q+beta c+o(1) substitution cap and blocks all-exponent transfer.
- $q \geq 1 + \epsilon$ or $\rho \geq 1 + \epsilon$ makes the substituted SAT upper bound compatible with the proposed source lower bound.
- A low-cost label-free quotient transcript or affine incidence sketch still gives a direct upper-bound falsifier for the XOR carrier.
- A constructive density-preserving ambient extension turns an image-relative certificate into a standard natural property and triggers the natural-proofs obstruction in the same circuit model.
- Nonuniform leakage through precomputed SAT labels for U_N invalidates the controlled interface.
- If d is not fixed polylogarithmic, the image-density calculation and $\beta = 0$ classification must be recomputed before it is valid.

cycle-0069: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.009 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 69 turns the image-density ambiguity into a precise threshold theorem. A label-mediated $\beta = 0$ XOR certificate naturalizes through restriction to U_N exactly when its label density is at least $2^{-\text{poly}(L)}$ and its verifier is $2^{O(L)} - constructive$. The earlier ambient-tiny source image is not by itself a valid escape; the real escapes are nonlarge density, nonconstructivity, advice leakage, or explicitly nonrelativizing direct lower bounds.

Pressure. No construction is given of a P_N that accepts SAT$|U_N$ while remaining sound; the derivation only classifies when such a proof-mediated route would naturalize.

Derivation steps.

1. Fix L=(log N)^d, $d > 1$, and a uniform distinct query set U_N of size $M_N = N^{q+o(1)}$.
2. Given a label property P_N, define Q_N on full L-bit truth tables by reading only coordinates in U_N.
3. A uniformly random full truth table induces a uniformly random label vector on U_N; hence ambient target density equals label density $delta_N$ exactly.
4. If f has $L^c - size$ circuits, $\beta = 0$ substitution gives $H_{N,f|U_N}$ size $N^{max\rho,q+o(1)}$; with $max\rho, q < 1 + \epsilon$, soundness forces $Q_N(f) = 0$.
5. If P_N is decidable in $2^{O(L)}$ and $delta_N \geq 2^{-\text{poly}(L)}$, then Q_N is a constructive large property useful against $L^c - size$ circuits.
6. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: label_space_size.

$$M_N = |U_N| = N^{q+o(1)} = 2^{qL^{1/d}+o(L^{1/d})}$$

Valid when: Valid when L=(log N)^d with fixed $d > 1$ and the generator emits $N^{q+o(1)}$ distinct target formulas.

Equation 2: beta_zero_substitution.

$$C(H_{N,f|U_N}) \leq N^{\max \rho,q+o(1)} \cdot L^{O(c)} = N^{\max \rho,q+o(1)}$$

Valid when: Applies when target queries have polylogarithmic length and f has $L^c - size$ circuits for fixed c.

Equation 3: restriction_density_preservation.

$$\Pr_{f \leftarrow 0,1^{2^L}}[Q_N(f) = 1] = |P_N|/2^{M_N} = \delta_N$$

Valid when: Valid when the coordinates in U_N are distinct so a random full truth table induces a uniform label vector.

Equation 4: natural_largeness_threshold.

$$\delta_N \geq 2^{-L^a} \quad \Longrightarrow \quad Q_N \text{ is } 2^{-\text{poly}(L)}\text{-large}$$

Valid when: Requires a fixed constant a and the standard target-length naturalness convention for L-bit Boolean functions.

Next analysis. Instantiate U_N with L=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute whether candidate proof systems give certificate density above $2^{-\text{poly}(L)}$ or force a nonlarge escape, then run the prior-art boundary check.

Falsifiers.

- falsifier: $\beta > 0$ with transfer exponent q+beta c reaches the source threshold before all SAT exponents are excluded.
- falsifier: low constructive rank or label-free codebook for the XOR incidence map gives a direct upper bound for H_N.
- falsifier: P_N has density at least $2^{-\mathrm{poly}(L)}$ and verifier time $2^{O(L)}$, yielding a valid target-restriction natural property rather than a barrier escape.
- falsifier: U_N or the certificate verifier uses nonuniform advice not reproducible by the target-side natural property.
- falsifier: soundness is proved only for realized SAT labels and not for all small target functions f, breaking useful-property naturalization.

cycle-0070: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.002 seconds; 2 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 70 corrects the naturalness gate for the $\beta = 0$ XOR route. A dense label certificate cylinder-extends to a valid classical natural property exactly at density $2^{-O(L)}$ with $2^{O(L)}$ constructivity; source-image ambient sparsity is irrelevant after restriction. The real escapes are nonlarge density below the classical cutoff, nonconstructivity, advice leakage, or a direct nonrelativizing H_N lower bound.

Pressure. This does not prove that such Q_N exists, and it does not turn sparse or nonconstructive certificates into barriers. It only gives a valid no-go for dense, constructive, same-model label certificates.

Derivation steps.

1. Fix N and L=(log N)^d, $d \geq 1$; enumerate U_N label-free and define R_L(f)=Q_N(f|U_N).
2. For uniformly random truth table f on $0,1^L$, the restriction $f|U_N$ is uniform over $0,1^{U_N}$; hence density is exactly preserved as $delta_N$.
3. Given a truth table for f, enumerate U_N, read the indexed bits, and run Q_N; the total time is $2^{O(L)}$ under $|U_N| \leq N^q$.
4. If $R_L(f) = 1$ and f had size L^c, substitute that circuit into the XOR carrier to get C_N(H_{f|U_N})<=N^{m contradicting Q_N soundness.
5. Since Q_N accepts SAT$|U_N$, R_L accepts SAT_L; thus any classically large constructive Q_N would naturalize the proof-mediated source lower bound.
6. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: substitution_upper_bound.

$$C_N(H_{f|U_N}) \le N^{\rho} + N^{q}\, C_L(f)\,\mathrm{poly}(L) + N^{o(1)} = N^{\max \rho, q+o(1)} \quad \text{if } C_L(f) \le L^{c}.$$

Valid when: Valid when L=(log N)^d with fixed $d \ge 1$, c is fixed, and the carrier accesses target labels only through the generated slots.

Equation 2: cylinder_density_preservation.

$$\Pr_{f:0,1^L \to 0,1}[R_L(f) = 1] = \frac{|Q_N|}{2^{|U_N|}} = \delta_N.$$

Valid when: Valid when R_L depends only on the restriction of the full truth table to the enumerated range U_N.

Equation 3: constructivity_transfer.

$$T_R(L) \le T_Q(N) + O(|U_N|\,\mathrm{poly}(L)) \le 2^{O(L)}.$$

Valid when: Valid when |U_N|<=N^q=2^{O(L)} and Q_N is decidable from the restricted label table within $2^{O(L)}$ time.

Equation 4: classical_largeness_cutoff.

$$\delta_N \ge 2^{-O(L)} \Rightarrow R_L \text{ is RR-large;} \quad \delta_N = 2^{-L^{\theta}},\ \theta > 1 \Rightarrow R_L \text{ is not classically large.}$$

Valid when: Applies when naturalness is measured at target input length L with the standard Razborov-Rudich density threshold $2^{-O(L)}$.

Next analysis. Instantiate the density-tier audit on a toy proof-certificate family: certificates describing affine anti-alignment witnesses over U_N. Compute $delta_N$, verifier time, and whether soundness reaches arbitrary $C_N(H_y) > N^{1+\epsilon}$ or only sketch hardness.

Falsifiers.

- falsifier: $delta_N \ge 2^{-O(L)}$ with $T_Q \le 2^{O(L)}$ means the certificate route is a classical natural property, not a valid naturalness escape.
- falsifier: $maxq, \rho \ge 1+\epsilon$ collapses the source threshold before any target lower bound is obtained.
- falsifier: U_N enumeration or Q_N membership uses nonuniform advice encoding SAT labels, breaking the label-free restriction extension.
- falsifier: source soundness proves only local separator hardness or rank hardness, not arbitrary circuit lower bounds for H_y.
- falsifier: $d < 1$ with $|U_N| = 2^{\omega(L)}$ can destroy $2^{O(L)}$ constructivity of the cylinder property even when β remains subpolynomial.

cycle-0071: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.015 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 71 upgrades the $\beta = 0$ XOR naturalness audit: density alone is not the decisive condition. Dense searchable certificates naturalize only when their soundness is functional over arbitrary label vectors. Therefore the surviving proof-mediated route must be sparse, nonconstructive, SAT-semantic/nonrelativizing, advice-free in a stronger sense, or a direct H_N lower bound.

Pressure. This derivation needs functional soundness for all label vectors and a real accepted-label density estimate. SAT-only certificates and nonlarge accepted sets are outside the no-go.

Derivation steps.

1. Fix f with $C(f) \leq L^c$ and set $y = f|U_N$.
2. Substitute the f-circuit into every generated query of the XOR carrier; since L=polylog(N), the substituted target-circuit cost is $N^{q+o(1)}$ and the generator cost is $N^{\rho+o(1)}$.
3. If y is accepted by a functionally sound certificate, then C(H_N^y)>N^{1+epsilon}.
4. When $max\rho, q < 1 + \epsilon$, the previous two inequalities contradict each other, so no SIZE(L^c) function lies in the pullback property P_N.
5. For uniformly random f, $f|U_N$ is uniform on $0,1^{U_N}$; hence the pullback density equals $delta_N$.
6. If $delta_N \geq 2^{-O(L)}$ and the verifier is $2^{O(L)} - constructive$, P_N is a classical natural property useful against SIZE(L^c).
7. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: xor_carrier.

$$H_N^y(x) = \bigoplus_{u \in U_N} a_N(x,u) y_u$$

Valid when: Valid when U_N is the distinct generated query set and a_N is the advice-free quotient incidence predicate.

Equation 2: beta_zero_substitution.

$$C(H_N^{f|U_N}) \leq N^{\max \rho, q+o(1)} \quad \text{if } C(f) \leq L^c$$

Valid when: Applies when target queries have length L=polylog(N) and $\beta = 0$ removes the c-dependent exponent term.

Equation 3: density_pullback.

$$\Pr_F[P_N(F) = 1] = \delta_N = |A_N|/2^{|U_N|}$$

Valid when: Valid when F is a uniformly random L-bit Boolean function and U_N contains distinct query strings.

Equation 4: naturalness_cutoff.

$$\delta_N \geq 2^{-KL},\ T_V \leq 2^{KL} \Rightarrow P_N \text{ is classically large and constructive}$$

Valid when: Requires the usual truth-table constructivity scale and the density cutoff measured over all L-bit functions.

Equation 5: usefulness_contradiction.

$$P_N(f) = 1 \wedge C(f) \leq L^c \Rightarrow N^{1+\epsilon} < C(H_N^{f|U_N}) \leq N^{\max \rho, q+o(1)}$$

Valid when: Applies after functional soundness and the beta-zero transfer hold with $max\rho, q < 1+\epsilon$.

Next analysis. Instantiate V_N with one concrete proof-system or MCSP-style certificate, compute $kappa_N$ for accepted labels, and decide whether soundness is functional over arbitrary y or essentially SAT-semantic.

Falsifiers.

- falsifier: positive β in a black-box target substitution revives the q+beta*c threshold cap and prevents all-exponent transfer.
- falsifier: low constructive quotient rank or a small label-free codebook gives an explicit upper bound for the XOR carrier.
- falsifier: functional soundness plus accepted-label density at least $2^{-O(L)}$ and $2^{O(L)}$ constructivity naturalizes the proof certificate.
- falsifier: nonuniform row selection or advice-dependent U_N invalidates the density pullback and the target-preserving bridge.
- falsifier: SAT-only soundness without a nonrelativizing invariant gives no natural property and no certified source lower bound.

cycle-0072: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 2 lemmas, 3 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 72 upgrades the $\beta = 0$ XOR route from a vague naturalness warning to a dichotomy: dense functional searchable certificates become valid natural properties, while nonfunctional proof objects must pass an explicit row-selection leakage audit. The target bridge survives, but the source proof space is narrowed to sparse, nonconstructive, SAT-semantic nonrelativizing, or direct H_N lower bounds.

Pressure. No theorem yet converts SAT-semantic, nonrelativizing certificates into functional certificates or into charged row-selection transcripts. That is the exact remaining gap, not a proof of P $\neq$ NP.

Derivation steps.

1. Instantiate the surviving carrier with L=(log N)^d, $d > 1$, $T_N = N^q$, $q < 1+\epsilon$, and generator size N^ρ with $\rho < 1+\epsilon$.

2. Assume a certificate predicate P_N is dense, $2^{O(L)}$ – *constructive*, and functionally sound for every label vector ell. Define $R_L(f) = 1$ iff exists pi P_N(ell_f,pi).

3. Constructivity of R_L is polynomial in the truth-table length 2^L, and density is at least $2^{-O(L)}$, so R_L is large in the Razborov-Rudich sense.

4. If f has circuits of size L^c, substituting f into the XOR generator gives C(H_{N,f})<=N^{max{q,rho}+o(1)}< functional soundness therefore forces $R_L(f) = 0$. This proves usefulness against L^c circuits for every fixed c.

5. If P_N is not functional, extract the charged row-selection transcript it uses. A transcript with $A_N + S_N + minR_N, K_{NC}(\mathrm{SAT}_L) + E_{NN}$ below $N^{1+\epsilon}$ is a concrete falsifier of the claimed source lower-bound route.

6. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: substitution_upper_bound_beta0.

$$C(H_{N,f}) \le C(G_N) + O(T_N\, C(f) + T_N L^{O(1)}) = N^{\max \rho, q+o(1)} \quad \text{if } C(f) \le L^c.$$

Valid when: Applies when G_N has size N^ρ, $T_N = N^q$, and the target truth-table function f has circuits of size L^c with L=(log N)^d.

Equation 2: threshold_separation_window.

$$\max \rho, q < 1+\epsilon \implies N^{\max \rho, q+o(1)} < N^{1+\epsilon}.$$

Valid when: Requires fixed $\epsilon > 0$, fixed q and ρ below threshold, and N large enough that the o(1) term is smaller than the threshold margin.

Equation 3: natural_largeness_cutoff.

$$\delta_N = |A_N|/2^{2^L} \ge 2^{-aL} = (2^L)^{-a}.$$

Valid when: Valid when certificates are counted over complete L-bit truth tables and constructivity is polynomial in the truth-table length 2^L.

Next analysis. Instantiate the selected-probe audit for one named proof-system candidate: require $q = 1 + \epsilon/2$, $\rho = 1 + \epsilon/3$, L=(log N)^2, then compute whether its certificates force $A_N + S_N + R_N + E_{NN}$ or $A_N + S_N + K^c_{NL} + E_{NN}$ below $N^{1+\epsilon}$.

Falsifiers.

- falsifier: positive target-query exponent β gives the old transfer cap q+beta c and cannot exclude all SAT exponents.
- falsifier: a dense searchable certificate with functional soundness is a valid natural property, so it is barred under standard PRF assumptions rather than an escape route.
- falsifier: label-dependent row selection with $A_N+S_N+R_N+E_{NN} < N^{1+\epsilon}$ gives an unconditional small circuit for the source carrier.
- falsifier: under SAT_L in SIZE(L^c), a selected-probe transcript with A_N+S_N+K_NL^c+E_NN<N^{1+epsi collapses the attempted contradiction before reaching all-exponent separation.
- falsifier: density below $2^{-\omega(L)}$ avoids classical naturalization but also breaks the promised searchable-large certificate route unless a separate nonlarge proof system is specified.
- falsifier: advice leakage in P_N invalidates both the natural-property derivation and the claimed target-preserving bridge unless the advice is explicitly charged.

cycle-0073: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 4 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 73 adds a concrete row-deletion residual threshold to the surviving $\beta = 0$ XOR magnification route. A claimed $N^{1+\epsilon}$ source lower bound is invalid if the carrier has a subthreshold circuit wrong on fewer than $N^{\epsilon-o(1)}$ source rows, because equality patching costs O(E_N N). Thus a proof-mediated nonfunctional escape from natural proofs must be robust against sparse-row leakage; this is route-level progress, not a P vs NP proof.

Pressure. No theorem yet converts an arbitrary SAT-semantic nonfunctional certificate into either a functional natural property or a sparse-row residual circuit. The row gate is a necessary falsifier audit, not a complete proof-system lower-bound framework.

Derivation steps.

1. Fix $H_N^{\mathrm{SAT}}(x) = xor_{j \le M_N}$ SAT(G_N(x,j)) with $M_N = N^{q+o(1)}$, L_N=(log N)^d, and $C(G_N) \le N^{\rho+o(1)}$.
2. Assume SAT has circuits of size n^c at length L_N. Substituting the same SAT circuit into every generated slot gives C(H_N^{SAT})<=N^{rho+o(1)}+N^{q+o(1)}L_N^c.
3. Since L_N^c=N^{o(1)}, the transfer is $N^{max\rho,q+o(1)}$. Therefore C(H_N^{SAT})>N^{1+epsilon} with $max\rho, q < 1 + \epsilon$ implies SAT notin SIZE(n^c) for every fixed c.
4. Now suppose a residual circuit D_N of size S_D agrees with H_N^{SAT} outside R_N, with $|R_N| = E_N$. For each exceptional x, add an equality test to x and xor the correction bit. This costs O(E_N N) gates.
5. Thus C(H_N^{SAT})N^{1+epsilon-o(1)} is false.

6. Hence a nonfunctional proof object that escapes label-functional naturalization must still prove residual hardness after deleting $N^{\epsilon-o(1)}$ rows; otherwise it supplies its own falsifier.

7. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: xor_carrier.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N \le N^{q+o(1)},\ L_N = (\log N)^d$$

Valid when: Valid when the source object is the explicitly generated beta-zero XOR carrier and every generated query has polylogarithmic target length.

Equation 2: target_substitution_upper_bound.

$$SAT \in SIZE(n^c) \ \Rightarrow\ C(H_N^{SAT}) \le N^{\rho+o(1)} + N^{q+o(1)} L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the reduction preserves nonuniform circuit model identity and the target query length satisfies $L_N = N^{o(1)}$.

Equation 3: row_patch_upper_bound.

$$D_N = H_N^{SAT} \text{ off } R_N \ \Rightarrow\ C(H_N^{SAT}) \le S_D + O(E_N N) + O(1), \quad E_N = |R_N|$$

Valid when: Valid when the residual circuit is fixed for length N and exceptional source rows are patched by equality tests.

Equation 4: source_survival_threshold.

$$C(H_N^{SAT}) > N^{1+\epsilon} \ \Rightarrow\ S_D \ge N^{1+\epsilon-o(1)} \text{ or } E_N \ge N^{\epsilon-o(1)}$$

Valid when: Requires the row-patch upper bound and the claimed barely-superlinear source lower bound in the same circuit model.

Next analysis. Instantiate a named proof system Psys for $\beta = 0$ XOR certificates and test whether any accepted SAT-semantic certificate can be transformed into either a functional label property or a residual circuit wrong on fewer than $N^{\epsilon-o(1)}$ rows.

Falsifiers.

- sparse row residual compression with $E_N < N^{\epsilon-o(1)}$ and $S_D < N^{1+\epsilon-o(1)}$
- positive-beta black-box substitution cap q+beta c preventing all-exponent transfer
- functional dense certificate naturalization when soundness holds for arbitrary label vectors
- row-selection advice leakage hidden inside a SAT-semantic proof object
- low constructive incidence rank or label-free quotient sketch making the XOR carrier easy

cycle-0074: Hardness-Magnification Bridge Realization: beta-zero XOR row-residual audit

Execution. research; azure_responses_api; attempt primary; 600.001 seconds; 3 lemmas, 5 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 74 upgrades the focus packet: the beta-zero XOR bridge and row-residual patching bound are theorem-shaped and valid under explicit batched-generator assumptions. The live obstruction is now narrower: prove an EF + SAT_U semantic extraction/no-extraction theorem, or quarantine proof-mediated certificates that cannot certify residual robustness.

Pressure. No proof-analysis theorem currently forces a semantic EF + SAT_U certificate either to functionalize over all label tables or to localize its nonfunctionality to fewer than $N^{\epsilon-o(1)}$ source rows. EF may use global SAT structure shared by many rows through the same formula labels.

Derivation steps.

1. Fix a batched generator G_N with $M_N \le N^{q+o(1)}$, L_N=(log N)^d, and circuit size $N^{\rho+o(1)}$; define H_N^{SAT} by XOR aggregation.
2. Assume SAT has circuits of size n^c. Substitute the $length - L_N$ SAT circuit into every generated query and obtain C(H_N^SAT)<=N^{max{rho,q}+o(1)} because L_N^c=N^{o(1)}.
3. If $max\rho, qN^{1+\epsilon}$ contradicts SAT in P/poly; this is a valid route-level bridge, not a proof of the source lower bound.
4. Let D_N agree with H_N^{SAT} outside R_N. Hardwire equality tests for all rows in R_N where D_N is wrong, XOR the correction, and get C(H_N^SAT)<=C(D_N)+O(|R_N|N).
5. Instantiate Psys as EF + SAT_U. If its accepted certificates are functional over arbitrary label tables and dense at $2^{-O(L_N)}$, the certificate property naturalizes. If soundness is only for the real SAT label table, the route escapes that barrier but must prove row-residual robustness.
6. Tried to derive a sparse D_N, R_N from an arbitrary nonfunctional EF + SAT_U proof by collecting rows whose SAT-semantic axioms are used essentially.

Equation 1: carrier_definition.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N \le N^{q+o(1)}, \quad L_N = (\log N)^d.$$

Valid when: Valid when each G_N(x,j) is a well-formed $length - L_N$ SAT instance and XOR is implemented by ordinary Boolean circuits.

Equation 2: beta_zero_substitution.

$$SAT \in SIZE(n^c) \implies C(H_N^{SAT}) \le N^{\rho+o(1)} + M_N L_N^c + O(M_N) = N^{\max\rho, q+o(1)}.$$

Valid when: Applies after assuming a length-n SAT circuit of size n^c and substituting it uniformly into every generated query slot.

Equation 3: target_preserving_implication.

$$C(H_N^{SAT}) > N^{1+\epsilon} \text{ i.o. } \wedge \max \rho, q < 1 + \epsilon \implies SAT \notin P/poly.$$

Valid when: Applies when the source lower bound occurs on infinitely many valid source lengths and the substitution upper bound would hold on every such length.

Equation 4: row_patching_bound.

$$D_N = H_N^{SAT} \text{ on } 0,1^N \setminus R_N \implies C(H_N^{SAT}) \leq C(D_N) + O(|R_N|N).$$

Valid when: Valid when R_N is explicitly hardwired and equality to an N-bit source row costs O(N) gates in the same circuit model.

Equation 5: residual_falsifier_threshold.

$$C(D_N) + O(|R_N|N) < N^{1+\epsilon} \implies (D_N, R_N) \text{ falsifies } C(H_N^{SAT}) > N^{1+\epsilon}.$$

Valid when: Requires C(D_N) and $|R_N|N$ to be measured at the same source length and against the same exponent threshold.

Next analysis. Formalize EF + SAT_U syntax with label table U_N, prove the functional dense naturalization lemma cleanly, then attempt a finite extraction theorem: every nonfunctional accepted proof either identifies a row set R_N and approximator D_N or uses a nonrelativizing SAT principle outside the row-residual audit.

Falsifiers.

- falsifier: a circuit D_N of size $N^{1+\epsilon-\gamma}$ agreeing with H_N^{SAT} except on at most $N^{\epsilon-\gamma}$ source rows.
- falsifier: any positive-beta black-box interface claiming all-exponent SAT lower bounds from a fixed $N^{1+\epsilon}$ source lower bound.
- falsifier: hidden advice in G_N or in the certificate search procedure that makes the source lower bound target-equivalent.
- falsifier: a dense functional EF + SAT_U certificate family, which is valid as a natural property but invalid as a claimed natural-proofs escape.
- falsifier: a batched-generator accounting failure where producing all queries costs $M_N\ N^\rho$ rather than N^{rho}+N^{q+o(1)}.

cycle-0075: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 600.01 seconds; 1 lemmas, 3 equations, 5 derivation steps, 4 falsifiers.

Learning. Cycle 75 turns the Psys gap into a precise EF + SAT_U audit. Ordinary semantic soundness is insufficient: a valid proof-mediated beta-zero XOR route must either be nonlarge/nonconstructive/direct or certify row-residual robustness against subthreshold patching.

Pressure. No theorem yet extracts row-residual robustness from short EF + SAT_U semantic proofs, and no construction yet proves such extraction impossible.

Derivation steps.

1. Assume SAT has size n^c circuits. Substitute the circuit into each $L_N - bit$ generated query of H_N and charge the generator once, giving the beta-zero transfer bound.
2. If $q, rhoN^{1+\epsilon-o(1)}$, the transfer contradicts SAT $\in$ SIZE(n^c) for every fixed c; this is route-level SAT $\notin$ P/poly only from the source bound.
3. Given D_N agreeing with H_N off R_N, patch D_N by equality tests for rows in R_N. If $S_D + O(|R_N|N) < N^{1+\epsilon}$, the source lower bound is false.
4. For EF + SAT_U certificates, dense functional soundness yields a natural label property; non-functional SAT-semantic soundness must therefore certify the row-residual gate or remain only a heuristic witness.
5. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: beta0_substitution.

$$C(H_N^{SAT}) \leq C(G_N) + M_N \cdot L_N^c + O(M_N \log M_N) = N^{\max \rho, q+o(1)}$$

Valid when: Valid when L_N=(log N)^d, $M_N \leq N^{q+o(1)}$, $C(G_N) \leq N^{\rho+o(1)}$, and a size n^c SAT circuit is substituted nonuniformly into every generated query.

Equation 2: row_residual_patch.

$$D_N = H_N^{SAT} \text{ off } R_N \Rightarrow C(H_N^{SAT}) \leq S_D + O(|R_N|N)$$

Valid when: Valid when unrestricted circuits may hardwire the exceptional N-bit rows and compare equality to each row before output correction.

Equation 3: robustness_gate.

$$\forall (D_N, R_N)\ [D_N = H_N^{SAT} \text{ off } R_N \Rightarrow S_D + O(|R_N|N) \geq N^{1+\epsilon-o(1)}]$$

Valid when: Requires a claimed source lower bound C(H_N^SAT)>N^{1+epsilon-o(1)} in the same nonuniform circuit model.

Next analysis. Instantiate EF + SAT_U proofs as circuits over SAT_U label atoms, define functionalization formally, and try to construct a $\theta < \epsilon$ residual-leaky transcript or prove extraction to the robustness gate.

Falsifiers.

- Subthreshold residual falsifier: find D_N, R_N with $D = H$ off R and $S_D + O(|R|N) < N^{1+\epsilon-o(1)}$.
- Naturalization falsifier: EF + SAT_U certificates are dense, $2^{O(L)}$ searchable, and functionally sound over all label vectors on U_N.
- Advice leakage falsifier: the certificate or generator encodes an exceptional row set of size N^θ with $\theta < \epsilon$.
- Beta/q falsifier: any hidden query-length exponent $\beta > 0$ or overhead $max\rho, q \geq 1 + \epsilon$ collapses the all-exponent target transfer.

cycle-0076: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 600.005 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 76 closes the Psys instantiation to EF + SAT_U and isolates the exact missing certificate strength: ordinary SAT-semantic soundness is not valid evidence unless it proves row-residual robustness above the patching threshold.

Pressure. No extraction/no-extraction theorem yet maps short EF + SAT_U proofs to functional label properties or to row-residual robustness against all subthreshold D_N.

Derivation steps.

1. Substitute any SIZE(L^c) SAT circuit into every generated query; $\beta = 0$ removes the c-dependent exponent and gives the valid target bridge when $max\rho, q < 1 + \epsilon$.
2. Split EF + SAT_U certificates: dense functional soundness over arbitrary label vectors triggers the prior naturalization audit; SAT-semantic soundness alone avoids that barrier but loses functional control.
3. For nonfunctional certificates, impose the row-residual test: any D_N correct off R_N yields an exact H_N circuit by equality patching, with exponent max{s,e+1}.
4. Tried to extract from a short EF + SAT_U derivation either a functional label property or an explicit $Robust_N$ certificate; ordinary semantic SAT_U axioms do not force either outcome.

Equation 1: carrier_definition.

$$H_N^{\mathrm{SAT}}(x) = \bigoplus_{j=1}^{M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N \leq N^{q+o(1)},\ L_N = (\log N)^d$$

Valid when: Valid when the source object is the beta-zero XOR carrier with a uniformly generated polylogarithmic SAT-query family.

Equation 2: beta0_transfer.

$$\mathrm{SAT}_{L_N} \in \mathrm{SIZE}(L_N^c) \Rightarrow C(H_N) \leq N^{\rho+o(1)} + N^{q+o(1)} L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the reduction preserves advice-freeness, fixed target exponent c, and polylogarithmic query length L_N.

Equation 3: row_residual_patch.

$$D_N = H_N \text{ off } R_N,\ C(D_N) = N^{s+o(1)},\ |R_N| = N^{e+o(1)} \Rightarrow C(H_N) \leq N^{\max s, e+1+o(1)}$$

Valid when: Requires source rows to be N-bit strings so each exceptional row is patchable by an O(N)-gate equality test.

Next analysis. Formalize Robust_N(s,e) for EF + SAT_U and test whether a short proof can remain sound after replacing H_N by D_N off a sparse row set.

Falsifiers.

- falsifier: a subthreshold D_N with $C(D_N) < N^{1+\epsilon-\eta}$ and fewer than $N^{\epsilon-\eta}$ wrong source rows gives $C(H_N) < N^{1+\epsilon-o(1)}$.
- falsifier: a dense searchable EF + SAT_U certificate that is functional over label vectors becomes a valid natural-property object for the label model.
- falsifier: generator or verifier advice that selects exceptional rows nonuniformly breaks the target-preserving condition and invalidates the bridge.
- falsifier: any hidden positive-beta query growth restores the transfer cap q+beta c and cannot exclude all SAT polynomial exponents.

cycle-0077: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.003 seconds; 3 lemmas, 5 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 77 sharpens the EF + SAT_U packet: direct lower-bound certificates automatically pass the explicit row-residual audit, so the real gap is not patching but semantic extraction. A new occurrence-oracle row-touch no-go gives a concrete falsifier for relativizing local certificate methods and leaves only SAT-semantic nonrelativizing, nonlarge/nonconstructive, or direct routes alive.

Pressure. No theorem yet shows that actual EF + SAT_U certificates for the intended SAT_U carrier either reduce to the row-touch occurrence-local model or yield a nonrelativizing extraction from certificate acceptance to LB_N(T_N).

Derivation steps.

1. Formalized LB_N(T_N) as the direct statement $C(H_N^{\mathrm{SAT}}) > T_N$ in the same nonuniform circuit model used by the beta-zero transfer.
2. Constructed the standard equality-patch circuit: compute D_N, test x against each exceptional row r in R_N, and xor the needed correction bit on matches.
3. Derived that any direct proof of LB_N(T_N) automatically excludes all explicit residual pairs (D_N, R_N) with $|D_N| + aN|R_N| < T_N$.
4. Tried to lift ordinary EF + SAT_U semantic certificates to LB_N(T_N) by treating accepted certificates as evidence for row-residual robustness.

5. Found the obstruction: if the certificate is only row-local and occurrence-relativizing, unseen occurrence labels can be assigned to make the carrier trivial outside the touched rows while preserving transcript acceptance.

6. Separated the remaining live case as a nonrelativizing SAT-realization extraction problem, not as a consequence of ordinary semantic soundness.

Equation 1: carrier_definition.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad |G_N(x,j)| = L_N = (\log N)^d.$$

Valid when: Valid when G_N is a fixed advice-free batched generator and rows are N-bit source inputs.

Equation 2: beta_zero_transfer.

$$C(H_N^{SAT}) \le C(G_N) + O(M_N\, C_{SAT}(L_N) + M_N L_N) \le N^{\max \rho, q + o(1)}.$$

Valid when: Applies when SAT has $L^c - size$ circuits for fixed c and L_N=(log N)^d makes L_N^c=N^{o(1)}.

Equation 3: explicit_row_patching.

$$D_N = H_N^{SAT} \text{ off } R_N \quad \Rightarrow \quad C(H_N^{SAT}) \le |D_N| + aN|R_N| + O(|R_N|).$$

Valid when: Requires D_N to agree with H_N^{SAT} outside the explicitly listed row set R_N and constants to be charged nonuniformly.

Equation 4: residual_threshold.

$$|D_N| + aNE_N < T_N \quad \Rightarrow \quad \neg LB_N(T_N) \text{ for } E_N = |R_N|.$$

Valid when: Valid when the source lower-bound claim is an exact circuit lower bound for H_N^{SAT} at threshold T_N.

Equation 5: conditional_target_consequence.

$$LB_N(N^{1+\epsilon-o(1)}) \wedge \max \rho, q < 1 + \epsilon \quad \Rightarrow \quad \forall c\ SAT \notin SIZE(n^c) \text{ on matched lengths.}$$

Valid when: Applies after the beta-zero transfer preserves advice accounting and the lower bound holds on the same infinite or eventual length set.

Next analysis. Instantiate Touch(Pi) for a concrete $\mathrm{EF} + \mathrm{SAT}_U$ encoding of circuit lower-bound certificates: count whether proofs of size N^k can mention $sub - N^\epsilon$ rows, and test if formula-equality/SAT-realization axioms break the occurrence-oracle extension.

Falsifiers.

- explicit residual falsifier: a circuit D_N and explicit bad row list R_N with $|D_N| + aN|R_N| < N^{1+\epsilon-o(1)}$ invalidates any claimed direct source lower bound.
- positive-beta falsifier: any repaired carrier with target query length N^β for $\beta > 0$ reintroduces the q+beta*c transfer cap.
- occurrence-oracle falsifier: a row-local certificate touching $B_N < N^{\epsilon-o(1)}$ rows is compatible with an easy occurrence-label carrier.
- functional-density falsifier: a dense constructive certificate property over label tables becomes a natural-property route unless it is nonlarge, nonconstructive, or nonfunctional.
- advice-leakage falsifier: uncharged generator, proof, or row-selection advice can hide the residual repair below the recorded threshold.
- target-equivalence falsifier: a direct EF proof of LB_N(T_N) may already encode the desired SAT lower bound, so it is not a weak-source magnification achievement.

cycle-0078: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.008 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 78 converts the row-residual audit into a theorem-shaped no-go: functional row-local certificates for the beta-zero XOR carrier require $N^{\epsilon-o(1)}$ touched rows at source threshold $N^{1+\epsilon-o(1)}$. This sharpens the EF + SAT_U obstruction from ordinary soundness to a concrete extraction fork: either the proof is direct or nonlarge/nonconstructive, or it must use real SAT semantics in a nonrelativizing way that defeats the private-row falsifier.

Pressure. The derivation is complete only for functional row-value certificates. EF + SAT_U proofs are SAT-semantic over formula labels, so a nonrelativizing extraction theorem or a private-row no-go formalization is still needed.

Derivation steps.

1. Assume a row-value certificate A_N(pi,h) is functional and $s_N-sound$: $A_N(pi, h) = 1$ implies $C(h) > s_N$ for all Boolean h on N-bit rows.
2. Let R_{pi} be the set of rows whose h-values can affect acceptance, with $|R_{pi}| = T_N$, and suppose $A_N(pi, H_N^{\mathrm{SAT}}) = 1$.
3. Define h_R to agree with H_N^{SAT} on R_{pi} and to be zero outside R_{pi}. Acceptance is unchanged because A_N only sees rows in R_{pi}.
4. Build h_R by OR-ing equality tests for the rows in R_{pi} and hardwiring the corresponding bits, giving C(h_R)<=O(T_N N).
5. If T_N=o(s_N/N), then $C(h_R) < s_N$, contradicting functional soundness. Hence functional certificates proving the source threshold must touch $N^{\epsilon-o(1)}$ rows.

6. Combine with the beta-zero bridge: a valid source lower bound still transfers to SAT $\notin$ P/poly when $max\rho, q < 1 + \epsilon$, but the proof-mediated route must now pass the row-touch or SAT-semantic extraction fork.

Equation 1: beta_zero_xor_carrier.

$$H_N^S AT(x) = bigoplus_{j \leq M_N} SAT(G_N(x, j))$$

Valid when: Valid when G_N is the named batched generator and every query length is L_N=(log N)^d.

Equation 2: target_substitution_upper_bound.

$$C(H_N^S AT) \leq N^{rho+o(1)} + N^{q+o(1)} L_N^c = N^{maxrho,q+o(1)}$$

Valid when: Valid when SAT on $L_N - bit$ inputs has circuits of size L_N^c and β equals zero.

Equation 3: row_residual_patching.

$$C(H_N^S AT) \leq S_D + O(|R_N|N)$$

Valid when: Applies when D_N agrees with H_N^{SAT} outside R_N and row equality tests are available nonuniformly.

Equation 4: functional_touch_lower_bound.

$$T_N \geq \Omega(s_N/N) = N^{epsilon-o(1)} for s_N = N^{1+epsilon-o(1)}$$

Valid when: Requires functional soundness over arbitrary row functions and acceptance depending on only T_N row values.

Next analysis. Instantiate EF + SAT_U row occurrence access formally: define the touched-row set of a proof verifier, test whether standard EF reflection over SAT_U extracts to row-value functionality, and if not construct the private-row oracle countermodel as a finite theorem.

Falsifiers.

- A subthreshold residual circuit D_N with fewer than $N^{\epsilon-o(1)}$ wrong rows is a falsifier for the claimed source lower bound.
- An accepted functional certificate touching o(N^{epsilon}) rows is a falsifier for proof-mediated soundness at threshold $N^{1+\epsilon-o(1)}$.
- A relativizing occurrence-local EF + SAT_U argument that survives the private-row oracle is a falsifier for the claimed SAT-semantic escape.
- A positive target-query exponent β reintroduces the transfer cap q+beta c and falsifies all-exponent target exclusion.
- Any hidden nonuniform list of exceptional rows larger than the accounted proof size is advice leakage and invalidates the route certificate.

cycle-0079: Hardness-Magnification Bridge Realization: beta-zero XOR row-forcing audit

Execution. research; azure_responses_api; attempt primary; 600.004 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 79 replaces vague SAT-semantic escape language by the full-row-forcing parameter ForcedRows(Q). A proof-mediated beta-zero XOR certificate that treats generated SAT instances as occurrence labels must force at least $N^{\epsilon-o(1)}$ complete parity rows; otherwise a private occurrence-label spoof gives a subthreshold sparse-row circuit. The valid contribution is a scoped no-go and an exact extraction obligation for full $\mathrm{EF}+\mathrm{SAT}_U$, not progress on the main conjecture itself.

Pressure. The derivation is a proof only for $\mathrm{EF}+\mathrm{SAT}_U^{occ}$ or functional label-local certificates. Full $\mathrm{EF}+\mathrm{SAT}_U$ may use real formula syntax to constrain unmentioned generated instances, so an extraction theorem for Q_{pi} or a nonrelativizing semantic certificate is still missing.

Derivation steps.

1. Fix an accepted occurrence-relativizing certificate pi and let Q_{pi} be the generated SAT occurrences whose labels affect its transcript.
2. Define A_Q to agree with real SAT on Q_{pi}. For each source row x not in ForcedRows(Q_pi), choose one unmentioned coordinate j_x and set its label so that xor_j $A_Q(G_N(x,j)) = 0$.
3. Then $H_N^{A_Q}$ is supported only on ForcedRows(Q_pi). A circuit computes it by checking whether x is one of these rows and hardwiring the residual parity values; the size is N^{rho+o(1)}+O(|ForcedF log N).
4. If $|ForcedRows(Q_{pi})| < N^{\epsilon-o(1)}$ and $\rho < 1+\epsilon$, this circuit has size below $N^{1+\epsilon-o(1)}$.
5. Occurrence-relativizing transcript invariance makes pi accept equally under SAT and under A_Q, so functional soundness would assert the same lower bound for the easy spoofed carrier. Contradiction.
6. Validity regime check: the derivation uses the definitions and assumptions listed in the candidate lemmas, preserves the same source object and target object, and is valid only in the stated P vs NP branch model with its declared circuit class, length regime, and advice/uniformity conditions.

Equation 1: beta0_substitution_upper_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + M_N\, L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT on length L_N formulas has circuits of size L_N^c and the beta-zero generator makes only $M_N \le N^{q+o(1)}$ polylog-length queries.

Equation 2: sparse_row_patch_upper_bound.

$$C(F) \le S_D + O(E_N n_N) + N^{o(1)} \le S_D + N^{1+o(1)} E_N/N$$

Valid when: Applies when a circuit D of size S_D agrees with the row function F except on E_N explicitly hardwired rows of $n_N = log$ N bits.

Equation 3: forced_row_spoof_size.

$$C(H_N^{A_Q}) \leq N^{\rho+o(1)} + O(|ForcedRows(Q)|\, n_N)$$

Valid when: Requires the occurrence-label spoof to zero every row outside ForcedRows(Q) and allows the remaining forced rows to be patched by equality gates.

Equation 4: row_forcing_threshold.

$$|ForcedRows(Q_\pi)| \geq N^{\epsilon-o(1)}$$

Valid when: Necessary when an occurrence-relativizing certificate transcript soundly asserts $C(H_N) > N^{1+\epsilon-o(1)}$ against all label assignments consistent with its queried occurrences.

Next analysis. Instantiate Psys = EF + SAT_U^{occ}: define the proof parser that extracts Q_{pi}, prove acceptance transcript invariance under A_Q, and compute whether known EF encodings force full rows or merely individual generated formula occurrences.

Falsifiers.

- falsifier: a subthreshold residual circuit D_N with fewer than $N^{\epsilon-o(1)}$ bad rows gives C(H_N^SAT)<N^{1+epsilo o(1)} by equality patching.
- falsifier: an accepted occurrence-relativizing certificate pi with $|ForcedRows(Q_{pi})| < N^{\epsilon-o(1)}$ is unsound for the claimed source lower bound.
- falsifier: positive β target-query length reintroduces the transfer cap q+beta c and destroys all-exponent SAT lower-bound transfer.
- falsifier: if the certificate proof string or verifier advice encodes more than $N^{1+\epsilon-o(1)}$ row information, the source lower bound is being assumed rather than certified.
- falsifier: ordinary EF + SAT_U soundness without row-residual robustness does not imply a valid source lower bound.

cycle-0080: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 4 lemmas, 4 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 80 discharges the scoped EF + SAT_U^{occ} proof packet: occurrence-local functional certificates for the beta-zero XOR carrier must force at least $N^{\epsilon-o(1)}$ complete parity rows, or a private occurrence-label spoof plus sparse-row equality patch gives a valid subthreshold falsifier. The live gap is no longer ordinary soundness; it is the full EF + SAT_U extraction of real SAT-semantic reasoning into syntactic $ForcedRows$, or a deliberate restriction of the paper theorem to EF + SAT_U^{occ}.

Pressure. The derivation is valid for EF + SAT_U^{occ}. It is blocked for full EF + SAT_U by the missing extraction lemma from real SAT semantic derivations to syntactic row forcing; full EF may use formula structure in a nonrelativizing way that private occurrence-label spoofing does not preserve.

Derivation steps.

1. Define U_N={(x,j):x in $0,1^N$, j<=M_N} and replace each SAT(G_N(x,j)) by an independent occurrence label $a_{x,j}$.

2. Parse an accepted occurrence-local transcript pi into Q_{pi} by collecting every queried occurrence, every locally derived equation, and every explicit row-parity tag; define ForcedRows(Q_pi) as rows whose parity is fixed under all completions of Q_{pi}.

3. Prove parser invariance by induction on the $\mathrm{EF} + \mathrm{SAT}_U^{occ}$ derivation: each rule depends only on premises already in Q_{pi}, so preserving Q_{pi} preserves acceptance.

4. For every unforced row choose a private completion making xor_j $a_{x,j} = 0$ while preserving Q_{pi}; forced rows keep their $Q_{pi} - determined$ parity.

5. The spoofed carrier H_{A^0} is supported on R=ForcedRows(Q_pi), so a nonuniform circuit hardwires R and uses O(N)-size equality tests to patch those rows, with total size S_Q+O(|R|N).

6. If pi is functionally sound for the claimed lower bound s_N, then H_{A^0} must have circuit complexity greater than s_N; the patch circuit contradicts this whenever $S_Q + O(|R|N) < s_N$.

7. Conclude that any valid occurrence-local functional certificate at the $N^{1+\epsilon-o(1)}$ threshold must force $N^{\epsilon-o(1)}$ complete rows, unless it is nonfunctional, nonconstructive, too large, or uses real SAT semantics outside $\mathrm{EF} + \mathrm{SAT}_U^{occ}$.

Equation 1: occurrence carrier.

$$H_A(x) = \bigoplus_{j \le M_N} a_{x,j}$$

Valid when: Valid when A is an arbitrary occurrence-label assignment over U_N and the row parity carrier is defined syntactically.

Equation 2: sparse-row spoof upper bound.

$$C(H_{A^0}) \le S_Q + O(|ForcedRows(Q_\pi)|\, N)$$

Valid when: Valid when Q_{pi} is occurrence-local, S_Q bounds its evaluator, and only forced rows remain nonzero after spoofing.

Equation 3: forced-row threshold.

$$|ForcedRows(Q_\pi)| \ge \Omega((s_N - S_Q)/N)$$

Valid when: Valid when pi is functionally sound for all completions consistent with Q_{pi} and the claimed lower bound threshold is s_N.

Equation 4: beta-zero target substitution.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + M_N L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT has circuits of size n^c, L_N=(log N)^d, and the generator circuit has size $N^{\rho+o(1)}$.

Next analysis. Attempt the full EF + SAT_U boundary lemma: inspect a standard encoding of SAT_U extension axioms and decide whether each semantic rule is occurrence-local, charges enough advice into S_Q, or yields a nonrelativizing complete-row extraction.

Falsifiers.

- Subthreshold forced rows: $|ForcedRows(Q_{pi})| < N^{\epsilon - o(1)}$ with S_Q=o(N^{1+epsilon}) yields a sparse-row patch circuit and is a direct falsifier for the claimed occurrence-local certificate.
- Parser leakage: if Q_{pi} contains a truth table, a SAT solver, or H_N advice, then S_Q must be charged; if charged size is subthreshold it falsifies the source lower bound, otherwise the certificate is not barely-superlinear.
- Nonfunctional soundness: a certificate valid only for the real SAT label vector escapes the occurrence-label theorem but loses the functional naturalization/no-go claim until a nonrelativizing extraction is proved.
- Global parity equations: low-cost constraints fixing many row parities without touching complete rows falsify the atomic $ForcedRows$ definition and require a parity-rank $ForcedRows$ repair.
- Positive-beta transfer remains an independent falsifier: if any replacement carrier reintroduces query length n^{β} with $\beta > 0$, the window q+beta c blocks all-exponent target separation.

cycle-0081: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 4 equations, 5 derivation steps, 5 falsifiers.

Learning. Cycle 81 separates the scoped occurrence-local theorem from the full EF + SAT_U ambition. The valid contribution is now sharper: private row spoofing is a genuine falsifier for occurrence-local functional certificates, while full EF + SAT_U requires a nonrelativizing semantic-to-occurrence extraction theorem because real SAT_U axioms are not invariant under independent label flips.

Pressure. Semantic-to-occurrence shadow extraction: no proof currently shows that full EF + SAT_U reasoning about actual SAT formulas can be converted into a functional occurrence-local Q_{pi} with subthreshold row residual and $N^{o(1)}$ overhead.

Derivation steps.

1. Start with the valid EF + SAT_U^{occ} theorem: if a functional occurrence-local transcript pi has fewer than $N^{\epsilon - o(1)}$ complete forced rows, construct a private-label spoof A_Q and a parity circuit D_N differing from H_N^{SAT} only on those rows.
2. Try to lift this to full EF + SAT_U by projecting each full SAT atom SAT(G_N(x,j)) to a private occurrence label $y_{x,j}$ and parsing the proof into Q_{pi}.
3. Check transcript invariance: in EF + SAT_U^{occ}, A_Q preserves all parsed constraints outside ForcedRows(Q_pi); in full EF + SAT_U, a line asserting SAT_U(F) or a witness equivalence is tied to the real syntax of F.

4. Construct the countermodel to naive invariance: choose an occurrence F=G_N(x,j) and set y_F to 1-SAT(F). The occurrence shadow can still satisfy uninterpreted constraints, but the full SAT_U axiom for F is false.

5. Conclude that sparse-row patching remains a valid falsifier for occurrence-local certificates, but it cannot refute full EF+SAT_U certificates unless a shadow-extraction normal form covers every SAT-semantic violation by forced rows plus a subthreshold residual.

Equation 1: beta_zero_xor_carrier.

$$H_N^{\mathrm{SAT}}(x) = \bigoplus_{j \le M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N \le N^{q+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when the source object is the beta-zero generated XOR carrier with polylogarithmic target instances and an explicit row index j.

Equation 2: shadow_extraction_requirement.

$$\mathrm{Ext}(\pi) = (Q_\pi, \mathrm{ForcedRows}(Q_\pi), R_\pi), \quad |Q_\pi| \le |\pi| N^{o(1)}, \quad |R_\pi| < N^{\epsilon - o(1)}$$

Valid when: Valid when a proposed full-EF transfer claims to reduce real SAT-semantic reasoning to occurrence-local constraints without exceeding the sparse-row patch threshold.

Equation 3: semantic_invariance_obligation.

$$A_Q \models Q_\pi \implies \pi \text{ remains sound except on } \mathrm{ForcedRows}(Q_\pi) \cup R_\pi$$

Valid when: Valid when private occurrence-label perturbations are required to simulate full SAT_U lines and all violations are covered by syntactically forced complete rows plus a residual set.

Equation 4: $full_{\mathrm{EF},blocking,fact}$.

$\exists F, b: \; b \neq \mathrm{SAT}(F) \;\Rightarrow\; (y_F = b)$ may satisfy an occurrence shadow but violates SAT_U(F)

Valid when: Valid when full EF + SAT_U contains semantic axioms tying SAT labels to actual formula syntax rather than to independent occurrence variables.

Next analysis. Formalize the semantic-coupling-width thought experiment as a lemma: for paired formulas F and F OR z, show exactly which SAT_U implication lines break private-label invariance and whether their violations can be charged to complete forced rows below the N^ϵ patch threshold.

Falsifiers.

- Full EF + SAT_U promotion falsifier: a SAT_U axiom line whose truth depends on real formula syntax is not preserved by private occurrence-label perturbations.
- Source lower-bound falsifier: any D_N agreeing with H_N^{SAT} off fewer than $N^{\epsilon - o(1)}$ rows and having $C(D_N) < N^{1+\epsilon-o(1)}$ gives a valid equality-patch upper bound.
- Parser falsifier: Ext hardwires the real SAT label vector or H_N^{SAT}, making the certificate target-equivalent rather than proof-extractable.

- Threshold falsifier: if $max\rho, q \geq 1 + \epsilon$, the beta-zero substitution bridge no longer yields the claimed all-exponent SAT consequence.
- Naturalization falsifier: a dense constructive functional label certificate over U_N becomes a natural-property-style object unless it is nonlarge, nonconstructive, or genuinely SAT-semantic.

cycle-0082: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 600.007 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 82 upgrades the proof-delivery packet by isolating a row-normal parser theorem: occurrence-local functional certificates are valid only if they force $N^{\epsilon - o(1)}$ complete rows. The remaining gap is exactly full EF + SAT_U semantic-to-occurrence extraction.

Pressure. The derivation is valid for row-normal occurrence-local transcripts; full EF + SAT_U may use real SAT syntax to create nonrelativizing dependencies not represented by Q_{pi}.

Derivation steps.

1. Parse pi into Q_{pi} by listing occurrence labels, extension equations, rule justifications, and explicit complete-row parity nodes; this is independent of the desired lower bound.
2. For x not in ForcedRows(pi), flip or set $y_{x,j}$ privately so xor_j $y_{x,j} = 0$ while preserving all row-normal dependencies appearing in Q_{pi}.
3. Define spoofed carrier H^A to be zero off ForcedRows(pi); equality gates patch the forced rows, giving size $O(|ForcedRows(pi)|N) + N^{o(1)}$.
4. Functional soundness would accept pi for H^A, so if $|ForcedRows(pi)| < N^{\epsilon - o(1)}$ it certifies hardness for an easy function, contradiction.

Equation 1: beta0_transfer.

$$C(H_N^{SAT}) \leq N^{rho+o(1)} + M_N L_N^c = N^{maxrho,q+o(1)}$$

Valid when: Valid when SAT has size L_N^c circuits and the beta-zero generator uses $M_N = N^{q+o(1)}$ queries.

Equation 2: sparse_row_patch.

$$C(H_N) \leq S_D + O(E_N N)$$

Valid when: Valid when D_N is an explicit circuit and errors are at most E_N source inputs.

Equation 3: forced_row_threshold.

$$|ForcedRows(pi)| \geq N^{epsilon-o(1)}$$

Valid when: Valid when the row-normal parser and private-label invariance assumptions are established.

Next analysis. Construct the smallest EF extension-rule countermodel that hides row parity without a row-normal node, or prove a normalization that exposes such parity with subthreshold overhead.

Falsifiers.

- falsifier: a transcript with fewer than $N^{\epsilon-o(1)}$ forced rows and row-normal invariance gives a valid subthreshold spoof circuit.
- falsifier: hidden extension gates computing row parity without syntactic exposure break the parser lemma and force a restriction of the theorem.
- falsifier: SAT-semantic rules using formula syntax rather than occurrence labels evade private-label flips and require nonrelativizing extraction.
- falsifier: q or ρ reaching 1+epsilon collapses the target-preserving beta-zero transfer window.

cycle-0083: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.01 seconds; 3 lemmas, 3 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 83 upgrades the proof-delivery packet from a parser slogan to a conditional theorem: row-separable row-normal functional occurrence certificates must force $N^{\epsilon-o(1)}$ complete XOR rows, or private occurrence-label spoofing yields a valid subthreshold circuit for the induced carrier. The remaining open obligation is no longer ordinary soundness but the exact row-normalization/extraction step for broader EF + SAT_U.

Pressure. The proof is conditional on a row-separable row-normal parser. Arbitrary full EF + SAT_U can use real formula semantics, and arbitrary occurrence-local EF may contain short cross-row parity constraints unless the calculus forbids or charges them.

Derivation steps.

1. Fix N, ϵ, q, ρ with $maxq, \rho < 1 + \epsilon$ and define $H_N^{\mathrm{SAT}}(x) = xor_{j \le M_N}$ SAT(G_N(x,j)).
2. Parse an accepted row-normal transcript pi into Q_{pi}; define ForcedRows(Q_pi) as rows whose parity is fixed over all assignments satisfying Q_{pi}.
3. Use parser invariance: acceptance of pi depends only on Q_{pi}, so any private label assignment A satisfying Q_{pi} preserves the accepted transcript.
4. If Q_{pi} is row-separable, choose A_Q so every unforced row has parity 0 and every forced row has its $Q_{pi} - forced$ parity.
5. Build a circuit for H_{A_Q}: output 0 by default and patch the forced rows with equality tests; size is $O(C(Q_{pi})) + O(|ForcedRows|N) + N^{o(1)}$.
6. Functional certificate soundness says the same accepted pi certifies $C(H_{A_Q}) > N^{1+\epsilon-o(1)}$. If $|ForcedRows| < N^{\epsilon-o(1)}$ and $C(Q_{pi}) = N^{o(1)}$, this contradicts the patch circuit.
7. Therefore any sound row-normal functional occurrence-local certificate must force $N^{\epsilon-o(1)}$ complete rows, or leave the method class.

Equation 1: beta_zero_transfer.

$$SATinSIZE(n^c) => C(H_N^SAT) \leq N^{rho+o(1)} + M_N L_N^c = N^{maxrho,q+o(1)}$$

Valid when: Valid when generated formulas have length L_N=(log N)^d, $M_N \leq N^{q+o(1)}$, $\beta = 0$, and one SAT circuit of size L_N^c is reused uniformly across all generated instances.

Equation 2: private_spoof_upper_bound.

$$C(H_{A_Q}) \leq O(C(Q_p i)) + O(|ForcedRows(Q_p i)|N) + N^{o(1)}$$

Valid when: Valid when Q_{pi} is row-separable, unforced row parities can be set to zero independently, and forced rows are patched by N-bit equality tests.

Equation 3: forced_row_threshold.

$$C(H_{A_Q}) > N^{1+epsilon-o(1)} and C(Q_p i) = N^{o(1)} imply |ForcedRows(Q_p i)| \geq N^{epsilon-o(1)}$$

Valid when: Applies after functional certificate soundness transfers the same lower-bound conclusion to every private occurrence-label assignment satisfying the parsed row-normal constraints.

Next analysis. Instantiate the EF + $\mathrm{SAT}_U^{occ,row}$ rule ledger: for each extension, weakening, substitution, SAT_U occurrence axiom, and derived parity line, mark whether it is $Q_{pi} - local$, row-separable, or a charged cross-row constraint; the first uncharged cross-row rule becomes the countermodel or repair target.

Falsifiers.

- Row-separability falsifier: a short accepted occurrence rule imposes a global cross-row parity equation that zeroes many spoof choices while *ForcedRows* remains small.
- Functional-soundness falsifier: the certificate conclusion applies only to real SAT labels, so private occurrence-label spoofing no longer gives a contradiction.
- Sparse-row residual falsifier: a circuit D_N agrees with H_N^{SAT} off $E < N^{\epsilon-o(1)}$ source rows, giving C(H_N^SAT)<=C(D_N)+O(EN) below the claimed threshold.
- Nonuniform-advice falsifier: Q_{pi} or the verifier hides a selected set of hard rows or the SAT label vector, invalidating the advice-free parser.
- Positive-beta falsifier: if the carrier secretly uses target queries of length N^β with $\beta > 0$, the substitution window becomes q+beta c and cannot exclude all SAT exponents.

cycle-0084: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.01 seconds; 3 lemmas, 4 equations, 8 derivation steps, 4 falsifiers.

Learning. Cycle 84 turns the *ForcedRows* packet into a proof-shaped conditional theorem: row-normal occurrence-local functional certificates must force $N^{\epsilon-o(1)}$ complete XOR rows, because otherwise private label spoofing plus sparse equality patching is a valid falsifier. The remaining gap is exactly semantic-to-occurrence extraction for full EF + SAT_U, not ordinary soundness or generic natural-proofs folklore.

Pressure. The derivation is complete only for row-normal occurrence-local functional certificates. Full EF + SAT_U remains blocked at semantic-to-occurrence extraction because SAT_U axioms can couple labels through real formula syntax and witnesses, so private occurrence-label spoofs may not preserve acceptance.

Derivation steps.

1. Fix N, ϵ, $q, rhoT_N = N^{1+\epsilon-o(1)}$.
2. Parse pi syntactically into Q_{pi}; for each source row x, compute the row view V_x(Q_pi) and put x in F=ForcedRows(Q_pi) iff V_x has no two compatible completions of opposite parity.
3. Assume $|F| = E < N^{\epsilon-o(1)}$. For every x notin F, choose a $Q_{pi} - compatible$ completion with row parity 0; for x in F, leave the real SAT occurrence labels unchanged.
4. By row-separability, the rowwise completions combine into one global occurrence-label assignment a' with the same $Q_{pi} - view$ as the real SAT labels.
5. By transcript invariance, pi accepts a'. By functional label soundness, $C(H_N^{a'}) > T_N$.
6. But $H_N^{a'}$ is supported only on F, so an OR of equality tests for rows in F, with the correct hardwired output bit for each forced row, computes $H_N^{a'}$ using O(EN) gates.
7. Since $E < N^{\epsilon-o(1)}$, $O(EN) = N^{1+\epsilon-o(1)}$ below the claimed threshold after choosing the margin in T_N, contradiction.
8. Therefore every valid row-normal occurrence-local functional certificate must force at least $N^{\epsilon-o(1)}$ complete rows.

Equation 1: beta0_xor_carrier.

$$H_N^a(x) = \bigoplus_{j=1}^{M_N} a_{x,j}, \quad a_{x,j}^{SAT} = SAT(G_N(x,j))$$

Valid when: Valid when G_N is the fixed beta-zero generator and a is any occurrence-label assignment.

Equation 2: beta0_target_transfer.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^{SAT}) \leq N^{\rho+o(1)} + M_N L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Applies after SAT circuits are substituted only into polylogarithmic queries and generator overhead is counted.

Equation 3: sparse_row_patch.

$$D = H_N \text{ off } R_N \Rightarrow C(H_N) \leq C(D) + O(|R_N|N)$$

Valid when: Requires D and H to differ on explicitly listed N-bit source rows only.

Equation 4: forced_row_threshold.

$$|ForcedRows(Q_\pi)| \geq T_N/O(N) = N^{\epsilon - o(1)} \quad \text{for } T_N = N^{1+\epsilon-o(1)}$$

Valid when: Valid under functional label soundness and transcript invariance for row-normal occurrence certificates.

Next analysis. Audit one standard full EF + SAT_U encoding rule: attempt to extract its occurrence-label dependency into Q_{pi} preserving $A_Q - invariance$; if a witness or clause-soundness axiom breaks invariance, record the minimal rule-level countermodel and restrict the theorem statement to EF + $\mathrm{SAT}_U^{occ,rn}$.

Falsifiers.

- falsifier: if $|ForcedRows(Q_{pi})| = N^\eta$ with $\eta < \epsilon$ and row-normal invariance holds, the spoofed carrier has an O(N^{1+eta}) patch circuit contradicting the source lower-bound certificate.
- falsifier: a parser atom that hides real SAT_U semantics rather than occurrence labels invalidates the occurrence-local theorem for full EF + SAT_U and triggers the extraction-boundary quarantine.
- falsifier: any reintroduced positive query exponent β gives the older transfer cap q+beta*c+o(1), so beta-zero preservation must be rechecked for every proposed carrier variant.
- falsifier: nonuniform advice selecting the exceptional rows without being charged can fake $ForcedRows$ robustness; advice must be included in Q_{pi} or in the circuit-size accounting.

cycle-0085: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 1800.011 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 85 sharpens the formula-semantic extraction fork: full occurrence parsing is false already for EF + $SATeq_N$ because EqSAT padding identities are real SAT-semantic and nonrelativizing. The valid repair is a semantic-link trichotomy: nonfunctional certificates must pay either occurrence full rows or EqSAT-linked rows at the $N^{\epsilon-o(1)}$ threshold, otherwise sparse-row residual patching falsifies the source lower-bound certificate.

Pressure. The derivation is complete only for EF + $SATeq_N$ where all SAT semantics factors through EqSAT links. It does not yet cover full EF + SAT_U with witness, self-reduction, or minimization rules unless those rules are decomposed into label-functional inferences plus row-chargeable semantic links.

Derivation steps.

1. Fix EF + $SATeq_N$: ordinary EF reasoning is syntactic and label-functional; EqSAT is the sole nonrelativizing rule, derived from EF proofs of Boolean formula equivalence.
2. Scan a proof pi of LB_N(H_N^SAT,N^{1+epsilon}) and mark every SAT atom occurrence used by label-functional rules; these form Q_{pi}.

3. For every EqSAT application SAT(F)SAT(F'), add a semantic link between the source rows whose generated formulas include F or F', when such rows are in the carrier range; off-range links are charged to proof size but not to parity-row forcing.

4. Run the previous private-row spoof only on rows outside ForcedRows(Q_pi) union SemRows(E_pi). On those rows, assign occurrence labels to agree with a low-cost completion while preserving all recorded EqSAT constraints.

5. If $W = |ForcedRows$ union $SemRows| < N^{\epsilon - o(1)}$, patch the W exceptional rows by equality tests to obtain C(H_N^SAT)<=S_D+O(WN), contradicting a claimed $N^{1+\epsilon-o(1)}$ source lower bound.

6. The EqSAT padding identity shows why the older occurrence-only parser is invalid for full EF + $SATeq_N$: semantic equality is not invariant under independent occurrence-label flips.

Equation 1: beta_zero_xor_carrier.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when G_N is a fixed batched generator outputting $length - L_N$ SAT instances and the carrier input length is N.

Equation 2: beta_zero_substitution_transfer.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^{SAT}) \leq N^{\rho+o(1)} + N^{q+o(1)} L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the generator overhead is $N^{\rho+o(1)}$, query length is polylogarithmic, and SAT circuits are substituted nonadaptively.

Equation 3: row_residual_patch.

$$D_N = H_N^{SAT} \text{ off } R_N \Rightarrow C(H_N^{SAT}) \leq C(D_N) + O(|R_N|N)$$

Valid when: Valid when R_N is a hardwired set of exceptional N-bit source rows and equality tests cost O(N) gates each.

Equation 4: semantic_link_threshold.

$$|ForcedRows(Q_\pi) \cup SemRows(E_\pi)| < N^{\epsilon-o(1)} \Rightarrow \text{certificate is row-residual-leaky}$$

Valid when: Requires the parser to expose all nonfunctional SAT uses as occurrence queries or EqSAT semantic links, with no hidden advice leakage.

Next analysis. Attempt the finite EF + $SATeq_N$ parser proof: formalize proof lines as Boolean circuits over SAT-atoms, prove label-functionality for EF rules, charge every EqSAT endpoint to SemRows, and test whether SAT self-reduction axioms in full EF + SAT_U admit the same charge or force a new semantic-escape lemma.

Falsifiers.

- falsifier: positive β or q+beta c transfer debt still caps black-box magnification before all SAT exponents are excluded.
- falsifier: an occurrence-only parser for EF + $SATeq_N$ is invalid because EqSAT padding equivalence is not preserved by private occurrence-label completions.
- falsifier: $W = |ForcedRows$ union $SemRows| < N^{\epsilon - o(1)}$ plus a residual circuit D_N gives a valid subthreshold equality-patching upper bound.
- falsifier: hidden nonuniform advice in the proof pi that selects exceptional rows without being charged breaks the target-preserving certificate audit.
- falsifier: a full EF+SAT$_U$ rule using SAT self-reducibility may evade both functional naturalization and EqSAT-link accounting, forcing quarantine until a named semantic-link factorization is proved.

cycle-0086: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 1800.01 seconds; 3 lemmas, 5 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 86 resolves one part of the formula-semantic fork: occurrence-only extraction is false for EF + $SATeq_N$ because real EqSAT identities are nonrelativizing semantic links. The valid replacement object is a semantic-link residual transcript; subthreshold link coverage is a falsifier for source lower-bound certificates, while the open proof task is a normal form for arbitrary EF + $SATeq_N$ reasoning.

Pressure. The normal form is not proved for arbitrary EF reasoning that invokes SAT self-reducibility, extension variables encoding witnesses, or nonlocal formula transformations not decomposed into explicit EqSAT links.

Derivation steps.

1. Fix Psys = EF + $SATeq_N$: EF plus explicitly checkable equisatisfiable formula identities such as padding, renaming, and clause duplication.
2. Test the previous parser theorem against the paired-padding generator G_N(x,2i)=Pad(G_N(x,2i-1)). EF + $SATeq_N$ proves equality of paired SAT labels and hence XOR cancellation.
3. Observe that a private occurrence-label spoof that flips only one member of a pair is not a model of EF + $SATeq_N$. Therefore the old occurrence-relativizing falsifier is not valid against this proof system.
4. Repair the observable from $ForcedRows_{occ}$ to a semantic-link transcript T_N containing occurrence values, constants, and EqSAT equality edges. A row is covered when its parity vector is determined modulo these links.
5. Derive the residual upper bound C(H_N^SAT)<=S_T+S_D+O(E_N N). Thus any accepted certificate with subthreshold transcript and fewer than $N^{\epsilon - o(1)}$ uncovered rows is a concrete falsifier for a claimed $N^{1+\epsilon - o(1)}$ source lower bound.

6. Attempt to extend the repair to all EF + $SATeq_N$ proofs by translating each proof inference into the link transcript. The translation works for padding, renaming, duplicate clauses, and local formula isomorphisms.

Equation 1: beta0_transfer.

$$\mathrm{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + M_N L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT on $L_N - bit$ formulas has circuits of size L_N^c and the generator is substituted without advice leakage or positive target-query exponent.

Equation 2: row_residual_patching.

$$C(H_N^{SAT}) \leq S_D + O(E_N N)$$

Valid when: Applies when a circuit D_N of size S_D agrees with H_N^{SAT} outside E_N explicitly hardwired source rows and equality tests cost O(N).

Equation 3: semantic_link_residual.

$$C(H_N^{SAT}) \leq S_T + S_D + O(E_N N)$$

Valid when: Valid when the parsed EF + $SATeq_N$ transcript T_N is label-free, has circuit cost S_T, and determines all but E_N rows through occurrence values or EqSAT links.

Equation 4: source_threshold_consequence.

$$C(H_N^{SAT}) > N^{1+\epsilon-o(1)} \ \wedge \ S_T + S_D < N^{1+\epsilon-o(1)} \Rightarrow E_N \geq N^{\epsilon-o(1)}$$

Valid when: Requires the row-residual patching bound and a claimed barely-superlinear source lower bound at the same valid generator lengths.

Equation 5: pure_occurrence_failure_pattern.

$$\mathrm{ForcedRows}_{occ}(\pi_N) = 0, \quad \mathrm{LinkCoveredRows}_{EqSAT}(\pi_N) = N$$

Valid when: Applies to paired-padding carriers where EF + $SATeq_N$ proves parity cancellation through semantic equality links rather than complete occurrence-row queries.

Next analysis. Work the EF + $SATeq_N$ normal-form proof rule by rule: padding, renaming, duplicate clauses, extension-variable abbreviations, and SAT self-reduction; either translate each into a bounded EqSAT-link transcript or isolate the first noncompressible SAT-semantic principle as the next theorem-shaped counterexample.

Falsifiers.

- Semantic-link falsifier: a subthreshold EqSAT-link transcript covering all but fewer than $N^{\epsilon-o(1)}$ rows gives an actual circuit upper bound by sparse-row patching.
- Paired-padding falsifier: EF+$SATeq_N$ can prove XOR cancellations with zero occurrence-forced rows, so a pure occurrence parser is not valid for this named proof system.
- Functional-naturalization falsifier: if accepted certificates define dense constructive label properties over arbitrary truth tables, the route falls back into the naturalization audit rather than a SAT-semantic escape.
- Positive-beta falsifier remains quarantined: any repair that reintroduces $L_N = N^{\beta}$ target queries obeys the old q+beta c transfer cap and loses all-exponent target preservation.
- Advice-leakage falsifier: a transcript that hardwires SAT labels on the generated range is not valid source evidence, because it hides the target truth table in the certificate.

cycle-0087: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 4 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 87 replaces the vague semantic-link normal-form obligation by an exact residual-code invariant: after EqSAT quotienting, a proof-mediated certificate that is functional over quotient labels is valid only if its touched-label coset has row-parity distance at least $N^{\epsilon-o(1)}$. Low quotient-code distance is a concrete falsifier; arbitrary EF + $SATeq_N$ remains open because it may use genuinely SAT-semantic nonrelativizing principles outside the quotient parser.

Pressure. The derivation does not produce a normal form for arbitrary EF+$SATeq_N$ proofs. Full EF can use nonrelativizing SAT-semantic principles, formula self-reductions, and derived equality chains whose acceptance is not a predicate over a bounded W,E quotient transcript.

Derivation steps.

1. Fixed the lower-bound sentence LB_N(S_N): every circuit of size at most S_N fails to compute H_N^{SAT} on some source row.
2. Parsed a hypothetical short EF + $SATeq_N$ proof into three observable components when possible: an EqSAT quotient graph E, a touched set W of quotient classes, and a predicate P depending on the real SAT labels only through W.
3. For the quotient-functional fragment, assumed P(a_W) = 1 and P(z_W) = 1 for every quotient-respecting z matching a_W.
4. Defined the residual parity code generated by the row-incidence map A_E from quotient classes to source rows and the coset constraint $z|_W = a_W$.
5. If the coset has a representative z with row support delta<S_N/O(N), built an equality-patch circuit of size O(delta N)+cost(Q)<S_N for H_z.
6. Because P cannot distinguish z from the real labels on W, quotient-functional soundness would assert $C(H_z) > S_N$, contradiction.

7. Concluded that any valid quotient-functional certificate must prove residual distance at least $N^{\epsilon-o(1)}$, not merely touch many raw occurrences or cite EqSAT soundness.

Equation 1: semantic_link_carrier.

$$H_y(x) = \bigoplus_{j \le M_N} y_{[(x,j)]_E}$$

Valid when: Valid when E is the checkable EqSAT quotient graph and y assigns one Boolean label to each quotient class.

Equation 2: residual_distance.

$$\delta_E(W, a_W) = \min_{z:\ z|_W = a_W} \left| \left\{ x : \bigoplus_{j \le M_N} z_{[(x,j)]_E} = 1 \right\} \right|$$

Valid when: Valid when the parser reads only W and soundness is tested over all quotient-respecting label assignments.

Equation 3: sparse_row_upper_bound.

$$C(H_z) \le O(\delta_E(W, a_W)N) + \mathrm{cost}(Q)$$

Valid when: Valid when row support is patched by equality tests of size O(N) and the transcript cost is subthreshold.

Equation 4: necessary_distance_threshold.

$$\delta_E(W, a_W) \ge S_N / O(N) = N^{\epsilon-o(1)}$$

Valid when: Valid when $S_N = N^{1+\epsilon-o(1)}$ is the claimed source lower-bound threshold and parser overhead is o(S_N).

Next analysis. Instantiate the padded-copy EqSAT quotient family E_k, compute the row-incidence matrix A_E, and decide whether its constrained cosets have low-weight representatives below N^ϵ or certify a valid semantic-link residual lower bound.

Falsifiers.

- semantic-link residual distance $delta_E(W, a_W) < N^{\epsilon-o(1)}$, giving a valid sparse-row patching falsifier
- positive β or q/rho threshold collapse in the target substitution bridge
- EqSAT quotient classes reused across rows so heavily that the row-incidence coset has low-weight representatives
- parser uses nonuniform SAT-label advice hidden in W or in the link witnesses
- ordinary EF + $SATeq_N$ proof uses a named SAT-semantic principle outside quotient-functional parsing, blocking this certificate classification

cycle-0088: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 88 identifies the first concrete SAT-semantic escape from the EqSAT quotient parser: self-reduction OR constraints are not invariant under quotient-label spoofing. The valid paper move is not another magnification slogan but a trichotomy repair: equality-only proofs use quotient residual codes, occurrence expansions pay row-forcing cost, and SR proofs require a constrained residual-code audit. Low constrained row distance is a falsifier for source certificates; no main P $\neq$ NP claim is made.

Pressure. The derivation does not normalize arbitrary EF + SAT_U or arbitrary SAT-semantic reasoning to EqSAT+SR constraints. A stronger proof may use search-to-decision, Cook-Levin witness encodings, or formula minimization principles not represented by the finite SR hypergraph K_{pi}.

Derivation steps.

1. Fix Psys = EF+$SATeq$+SR with SAT atoms Y_u and the source sentence LB(H_N^SAT,N^{1+epsilon-o(1)}).
2. Reuse the stable beta-zero transfer: if SAT has $L_N^c - size$ circuits, then H_N^{SAT} has size $N^{max\rho,q+o(1)}$, so $q, \rho < 1 + \epsilon$ is the valid target-preserving window.
3. For proofs using only SATeq links, contract touched formulas to EqSAT components; the proof verifier is functional over quotient labels, so the cycle-87 quotient residual-code audit applies.
4. Insert one essential SR axiom Y_u Y_{u0} OR Y_{u1}. The assignment $Y_u = 0, Y_{u0} = 1, Y_{u1} = 0$ respects every equality quotient but violates SR, so an EqSAT-only parser accepts a completion that is not SAT-semantic.
5. Therefore full EF+SATeq+SR cannot be classified as occurrence/EqSAT-functional unless the parser also records the SR hyperedge or expands it into occurrence children.
6. Once SR hyperedges are recorded, the residual object is no longer a linear quotient coset; it is a finite Boolean constraint code K_{pi}. The correct falsifier is low $K_{pi} - constrained$ row-parity distance plus the row-patching bound.
7. For compressed block-SR, any completion-sound occurrence parser for negative parent labels must expose all 2^t leaves or provide an equivalent semantic OR certificate, giving a tunable threshold 2^t=N^alpha.

Equation 1: beta0_xor_carrier.

$$H_N^{SAT}(x) = \oplus_{j=1}^{M_N} SAT(G_N(x,j)), M_N = N^{q+o(1)}, L_N = (logN)^d$$

Valid when: Valid when the source object is the beta-zero batched SAT parity carrier with polylogarithmic target formulas and no positive target-query exponent.

Equation 2: target_substitution_upper_bound.

$$C(H_N^{SAT}) \leq N^{rho+o(1)} + M_N L_N^c = N^{maxrho,q+o(1)}$$

Valid when: Valid when SAT on $L_N - bit$ formulas has nonuniform circuits of size L_N^c and the generator is advice-free with size $N^{\rho+o(1)}$.

Equation 3: $SR_{semantic,constraint}$.

$$Y_u = Y_{u|z=0} \vee Y_{u|z=1}$$

Valid when: Valid when u is a Boolean formula containing variable z and Y_v denotes the satisfiability truth value of formula v under the real SAT interpretation.

Equation 4: $\mathrm{EqSAT}_{spoof,obstruction}$.

$$(Y_u, Y_{u|z=0}, Y_{u|z=1}) = (0,1,0) satisfiesallequalitylinksbutviolatesSR(u,z)$$

Valid when: Valid when the parser records only EqSAT quotient information and no additional OR-type self-reduction constraint for the touched formulas.

Equation 5: constraint_row_distance.

$$\Delta_K(pi) = min_{lambdamodelsK_{pi}} |x : \oplus_j lambda(G_N(x,j)) \neq H_N^{SAT}(x)|$$

Valid when: Valid when K_{pi} is the finite system of EqSAT and SR constraints touched by the proof and λ ranges over Boolean assignments to its SAT atoms.

Next analysis. Instantiate K_{pi} for local one-step SR only: bound $|K_{pi}|$ by proof size, define its row-parity constraint-distance $Delta_K$, and test whether $Delta_K$ can be reduced to a known SAT promise-hardness statement or whether it is target-equivalent to the desired H_N lower bound.

Falsifiers.

- falsifier: an EqSAT-only quotient parser for EF+SATeq+SR is invalid because the spoof labels (0,1,0) satisfy all equality links while violating a used self-reduction axiom.
- falsifier: any constrained predictor D_N with $S_D + E_N$ $NN^{1+\epsilon-o(1)}$.
- falsifier: compressed block-SR with 2^t<N^{epsilon-o(1)} can leave omitted-leaf or omitted-row errors patchable below the source threshold.
- falsifier: reintroducing positive target-query exponent β gives the older transfer cap q+beta c and cannot imply all-exponent SAT lower bounds.
- falsifier: nonuniform advice listing the residual bad rows or semantic children must be charged; otherwise the certificate leaks the target lower bound into the source object.

cycle-0089: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 1094.129 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. The cycle upgrades the SR semantic escape into a quantitative constrained-distance invariant. Occurrence spoofing is invalid after SR constraints, but any bounded-SR parser still faces the same row-patching threshold. Progress is route-level certification, not a P vs NP proof.

Pressure. The missing proof is semantic-to-residual parsing for full EF + $SATeq + SR_h$; SR OR clauses couple labels across restrictions, so independent occurrence-label spoofing is not valid.

Derivation steps.

1. Quotient formulas by EqSAT links, then add SR_h constraints for restrictions in the generated polylog formula closure; real SAT labels satisfy all constraints.
2. Assume a parser maps any short accepted proof pi to a functional transcript and decoder D_{pi} over constrained quotient labels, with cost S_{pi} and residual row set R_{pi}.
3. Apply row patching: hardwire R_{pi} and correct D_{pi} by equality gates, giving C(H_N^SAT)<=S_pi+O(|R_pi|
4. Therefore a proof certificate at threshold $N^{1+\epsilon-o(1)}$ must force $|R_{pi}| \geq N^{\epsilon-o(1)}$ unless S_{pi} already exceeds the source threshold.

Equation 1: beta_zero_transfer.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + M_N L_N^c = N^{\max \rho,q+o(1)}$$

Valid when: Applies when SAT has size L_N^c circuits and the carrier uses only polylogarithmic beta-zero target queries.

Equation 2: row_patch_bound.

$$C(H_N^{SAT}) \leq C(D_N) + O(|R_N|N)$$

Valid when: Valid when D_N agrees with H_N^{SAT} on every source row outside the explicitly listed residual set R_N.

Equation 3: sr_certificate_threshold.

$$\mathrm{ValidCert}_{SR_h}(\pi) \Rightarrow S_\pi + \Delta_{SR_h}(\pi)N \geq N^{1+\epsilon-o(1)}$$

Valid when: Requires the scoped parser to turn pi into an advice-free SR-constrained residual decoder for the same carrier.

Next analysis. Fix h with 2^h=N^{eta}; formalize $Delta_{SR,h}$ for the generated formula closure and try to prove the parser for EF + $SATeq + SR_h$ restricted to extension variables naming only quotient labels and SR clauses.

Falsifiers.

- Low constrained row distance $Delta_{SR,h}(pi) < N^{\epsilon-o(1)}$ with $S_{pi} < N^{1+\epsilon-o(1)}$ is a direct row-patching falsifier.
- SR closure overhead M_N2^h=N^{q_SR+o(1)} with $q_{SR} \geq 1+\epsilon$ collapses the beta-zero target-preserving window.
- A parser using nonuniform advice to list residual rows or semantic links invalidates the claimed advice-free certificate transfer.
- A genuinely SAT-semantic EF inference outside EqSAT+bounded-SR blocks the constrained parser and quarantines this scoped no-go.

cycle-0090: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.001 seconds; 3 lemmas, 3 equations, 9 derivation steps, 6 falsifiers.

Learning. Cycle 90 converts the SR semantic escape into a costed leaf-solver falsifier: bounded self-reduction depth is not free, but if $q + \eta + \tau < 1 + \epsilon$ and the induced row error is below N^{ϵ} then the source lower bound collapses by equality patching. The live inference-quality packet is now theorem-shaped for Psys_h; the only remaining full-system gap is the advice-free parser normal form for arbitrary EF extension variables.

Pressure. ParserNormalForm(EF+EqSAT+SR_h): prove that every short proof of LB(H_N^{SAT}) either gives a dense functional label property, an occurrence/full-row transcript, or a bounded-SR residual code with advice-free size bound poly(|pi|,L_N).

Derivation steps.

1. Fix $\text{Psys}_h = \text{EF} + \text{EqSAT} + SR_h$ and the beta-zero carrier H_N^{SAT}.
2. Recheck the target bridge: substituting any SIZE(L^c) SAT circuit into all generated queries gives C(H_N^{SAT})<=N^{max{rho,q}+o(1)}, so $q, \rho < 1 + \epsilon$ is the target-preserving exponent condition.
3. Expose the SR semantic escape by allowing h rounds of SAT self-reduction before labels are evaluated.
4. Given a leaf solver A_N of size $N^{\tau+o(1)}$, compute each top query by enumerating 2^{bh}=N^{eta_N+o(1)} leaves, OR their A_N labels, and XOR over $M_N = N^{q+o(1)}$ queries.
5. This yields C(H_{A,h})<=N^{rho+o(1)}+N^{q+eta_N+tau+o(1)}.
6. If $H_{A,h}$ differs from H_N^{SAT} on E_N rows, add equality patches for those rows and get C(H_N^{SAT})<=N^{ma
7. Therefore any claimed $N^{1+\epsilon-o(1)}$ source lower bound must rule out all bounded-SR easy carriers with $q + eta_N + \tau < 1 + \epsilon$ and $e < \epsilon$.
8. Attempted extension to full EF+SAT semantics: EqSAT quotienting is parsed by identifying label variables, and explicit SR rules add OR hyperedges.

9. The extension fails for arbitrary EF extension variables because they may encode global SAT-semantic predicates not representable as bounded SR leaf evaluations or occurrence-row queries.

Equation 1: beta_zero_target_substitution.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + M_N\, L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT has size L^c circuits on all generated $length - L_N$ formulas and L_N=(log N)^d makes every fixed c contribute only $N^{o(1)}$ overhead.

Equation 2: $bounded_{SR,leaf,solver,upper,bound}$.

$$C(H_{A,h}) \leq N^{\rho+o(1)} + N^{q+\eta_N+\tau+o(1)}$$

Valid when: Applies when the parsed self-reduction tree has 2^{bh}=N^{eta_N+o(1)} leaves per generated query and A_N has size $N^{\tau+o(1)}$ with no hidden advice.

Equation 3: row_residual_patch_bound.

$$C(H_N^{SAT}) \leq C(H_{A,h}) + O(E_N N) \leq N^{\max \rho, q+\eta_N+\tau, 1+e+o(1)}$$

Valid when: Requires that $H_{A,h}$ and H_N^{SAT} disagree on exactly $E_N = N^{e+o(1)}$ source rows and that equality tests for source rows cost O(N) gates each.

Next analysis. Build the minimal EF + EqSAT + SR_1 parser countermodel: allow one extension variable Z(F)=SAT(F_0) OR SAT(F_1) and test whether it is representable by the SR DAG without advice; if yes, increase to two nested extensions, if no, use it as the semantic escape separating full EF from Psys_h.

Falsifiers.

- bounded-SR leaf solver falsifier: $q + \eta + \tau < 1 + \epsilon$ and row error exponent $e < \epsilon$ gives a subthreshold patched circuit for H_N^{SAT}.
- sparse-row residual falsifier: any D_N agreeing with H_N^{SAT} off fewer than $N^{\epsilon-o(1)}$ rows and having subthreshold size invalidates the source lower-bound certificate.
- functional-density falsifier: if accepted certificates are dense and truth-table constructive over quotient labels, they become natural-property evidence rather than a non-natural lower-bound proof.
- parser-advice falsifier: a proof parser depending nonuniformly on the SAT label vector can fake extraction and is not valid for the route.
- full-EF semantic-escape falsifier: extension variables for global SAT-semantic predicates may defeat the bounded-SR parser, forcing demotion to the restricted Psys_h theorem.
- positive-beta transfer falsifier remains quarantined: any interface with target query length N^β, $\beta > 0$, has exponent q+beta c and cannot give all-exponent SAT lower bounds.

cycle-0091: Hardness-Magnification Bridge Realization: beta-zero XOR formula-semantic parser audit

Execution. research; azure_responses_api; attempt primary; 600.002 seconds; 3 lemmas, 4 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 91 upgrades the bounded-SR leaf-solver audit by adding an explicit EF extension-support charge and proving a no-go for extension-blind parsers. The valid theorem is restricted but contribution-shaped: subthreshold charged transcripts are upper-bound falsifiers, while arbitrary EF+SAT remains blocked at a precise advice-free normal-form lemma.

Pressure. Prove or refute the advice-free extension-support normal form for arbitrary EF extension variables in EF+EqSAT+bounded-SR; the known derivation only handles proofs whose extension dependencies are syntactically charged.

Derivation steps.

1. Fix H_N^{SAT} with $M_N = N^{q+o(1)}$, L_N=(log N)^d, $d > 1$, and generator size $N^{\rho+o(1)}$; this keeps the target substitution β at zero.
2. Assume SAT has $L^c - size$ circuits. Substitute the SAT circuit into every generated formula and obtain C(H_N^SAT)<=N^{max{rho,q}+o(1)}, so $q, \rho < 1 + \epsilon$ is the valid target-preserving window.
3. Choose $\mathrm{Psys}_{h,Ext}$ = EF + EqSAT + $depth - h$ self-reduction. Parse pi by collecting visible SAT atoms, EqSAT quotient links, SR leaves, and all SAT-atom dependencies of extension definitions.
4. If the parsed transcript supplies a leaf solver of exponent τ after leaf blowup η and is wrong on E_N rows, build D_N by running G_N, evaluating the charged transcript, and xoring the row outputs.
5. Patch the residual rows R_{pi} using equality tests for the N-bit source row; the patch cost is O(E_N N).
6. Derive C(H_N^SAT)<=N^{rho+o(1)}+S_ext+N^{q+eta+tau+o(1)}+O(E_NN). If all exponents are below 1+epsilon, the claimed source lower bound is falsified.
7. Test parser robustness by defining an EF extension $y_r = xor_j\ z_{r,j}$. A parser that ignores extension definitions sees one atom and no complete row, but expansion touches the full parity row; therefore extension-blind occurrence extraction is invalid.
8. Conclusion: the restricted charged-extension theorem is valid, while the full EF+SAT claim is blocked exactly at the advice-free extension-support normal-form lemma.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N \le N^{q+o(1)}, \quad L_N = (\log N)^d.$$

Valid when: Valid when G_N is an explicit batched generator whose outputs are SAT instances of length L_N and whose source input has length N.

Equation 2: beta_zero_transfer.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^{SAT}) \leq N^{\rho+o(1)} + M_N L_N^c = N^{\max \rho, q+o(1)}.$$

Valid when: Applies when SAT on $L_N - bit$ formulas has nonuniform circuits of size L_N^c and L_N is polylogarithmic, so the target-query exponent β is zero.

Equation 3: $charged_{SR,residual,upper,bound}$**.**

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + S_{ext}(\pi) + N^{q+\eta+\tau+o(1)} + O(E_N N).$$

Valid when: Valid when the charged parser extracts a bounded self-reduction leaf solver of exponent τ, leaf blowup η, extension support S_{ext}, and E_N bad source rows.

Equation 4: subthreshold_collapse.

$$S_{ext} \leq N^{\gamma+o(1)},\ E_N \leq N^{\delta+o(1)},\ \max \rho, \gamma, q+\eta+\tau, 1+\delta < 1+\epsilon \Rightarrow C(H_N^{SAT}) < N^{1+\epsilon-o(1)}.$$

Valid when: Requires all transcript costs to be counted in the same nonuniform circuit model and equality patches to cover exactly the residual rows.

Next analysis. Instantiate $\text{Psys}_{h,Ext}^{schema}$: EF+EqSAT+depth-h SR with extension definitions generated by row-oblivious schemas. Try to prove ExtSupp(NF(pi))<=poly(|pi|), or construct a minimal nonrelativizing SAT-semantic extension that defeats this normal form.

Falsifiers.

- Subthreshold charged transcript falsifier: S_ext+N^{q+eta+tau}+E_NN<N^{1+epsilon-o(1)} gives an explicit circuit for H_N^{SAT}.
- Extension-blind parser falsifier: $y_r = xor_j\ z_{r,j}$ hides a full row behind one EF atom unless definitions are expanded or charged.
- Nonuniform leakage falsifier: a row-indexed advice table inside extension definitions invalidates any claimed advice-free parser.
- Bounded-SR leaf-solver falsifier: if $q + \eta + \tau < 1 + \epsilon$ and residual errors are below $N^{\epsilon-o(1)}$, equality patching collapses the source lower bound.
- Positive-beta falsifier remains quarantined: any return to polynomial-length SAT queries reintroduces the q+beta c transfer cap.

cycle-0092: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.009 seconds; 3 lemmas, 5 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 92 turns the formula-semantic fork into a sharper proof packet. For support-declared EF+SATeq+bounded-SR, subthreshold parsed support plus bounded leaf solving and sparse residual rows gives a valid small-circuit falsifier for LB_N. The full EF+SAT claim is not proved; the precise remaining obstruction is NSP_N, the advice-free extraction of arbitrary extension-variable reasoning into charged row supports and SR leaves. This is route-level certification, not progress on the main P $\neq$ NP conjecture itself.

Pressure. NSP_N: every short arbitrary EF+SATeq+SR proof of LB_N must admit a support-complete, advice-free transcript with row distance and leaf-solver costs small enough to preserve the $N^{1+\epsilon}$ threshold. This is unproved and may fail for extension-compressed SAT-semantic reasoning.

Derivation steps.

1. Fixed the carrier H_N^{SAT} with $\beta = 0$, $M_{NN}^{1+\epsilon-o(1)}$.
2. Named the concrete proof model Psys_h^{supp}: EF+SATeq+bounded-SR with support-declared extension variables, no hidden advice, and charged proof/transcript/leaf-solver costs.
3. Parsed any accepted proof pi into T_{pi} containing declared row supports, EqSAT quotient links, bounded-SR leaf families, a charged leaf solver, and a residual row set R_{pi}.
4. Under support adequacy, built D_T by computing G_N, following T_{pi}, evaluating charged SR leaves with the leaf solver, and xoring the resulting labels; this gives C(D_T)<=S_T+N^{rho+o(1)}+N^{q+
5. Patched the residual set R_{pi} by equality tests on N-bit source rows, yielding C(H_N^SAT)<=C(D_T)+O(|R_
6. Concluded that any accepted proof with total charge below $N^{1+\epsilon-o(1)}$ is a falsifier for the claimed source lower-bound certificate, not evidence for P $\neq$ NP.
7. Separated the restricted theorem from the full EF+SAT ambition: arbitrary extension variables require NSP_N, an advice-free normal-support parser lemma not supplied by ordinary soundness.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N \le N^{q+o(1)}, \quad |G_N(x,j)| = L_N = (\log N)^d$$

Valid when: Valid when the carrier generator and SAT-label universe are fixed before any proof-system parsing or target-circuit substitution.

Equation 2: beta_zero_transfer.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^{SAT}) \le N^{\rho+o(1)} + M_N\, L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Applies after the SAT circuit is nonuniform but fixed-exponent and the target query length is polylogarithmic beta-zero.

Equation 3: transcript_approximator.

$$C(D_{T_\pi}) \le S_T + N^{\rho+o(1)} + B_N\, N^{\tau+o(1)} \le S_T + N^{\rho+o(1)} + N^{q+\eta+\tau+o(1)}$$

Valid when: Requires support adequacy for Psys_h^{supp} and a charged bounded-SR leaf solver on the generated leaf range.

Equation 4: row_patching.

$$C(H_N^{SAT}) \le C(D_{T_\pi}) + O(|R_\pi| N)$$

Valid when: Requires the approximator be defined on all source inputs and disagree only on the explicitly listed residual rows.

Equation 5: certificate_falsifier_threshold.

$$S_T + N^{\rho+o(1)} + N^{q+\eta+\tau+o(1)} + |R_\pi|N < N^{1+\epsilon-o(1)} \Rightarrow LB_N(\epsilon) \text{ is not soundly certified by } \pi$$

Valid when: Valid when all proof, parser, leaf, generator, and residual-patching costs are charged in the same nonuniform circuit model.

Next analysis. Try to prove NSP_N for the fragment EF+SATeq+SR whose extension definitions are row-affine and support-monotone; if the proof fails, extract the minimal extension rule that creates uncharged SAT-semantic support and state the final theorem scope around Psys_h^{supp}.

Falsifiers.

- Subthreshold support transcript falsifier: S_T+N^{q+eta+tau}+|R_pi|N<N^{1+epsilon-o(1)} gives an explicit small circuit for H_N^{SAT}.
- Bounded-SR leaf-solver falsifier: if $q + \eta + \tau < 1 + \epsilon$ and residual rows are fewer than $N^{\epsilon-o(1)}$, the proof-mediated source lower bound collapses.
- Low constrained row-distance falsifier after EqSAT/SR quotienting: row-parity distance below $N^{\epsilon-o(1)}$ is patchable.
- Hidden-advice falsifier: any parser that uses uncharged SAT truth-table information invalidates the claimed advice-free extraction.
- Functional-density falsifier: dense constructive label-functional certificates naturalize rather than escape barriers.
- Positive-beta falsifier remains quarantined: any return to target-query length N^β with $\beta > 0$ caps the transfer by q+beta c.

cycle-0093: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 4 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 93 upgrades the formula-semantic extraction fork by naming NSP_N as a support-transparency lemma for unrestricted EF extension variables and proving the conditional transcript falsifier around it. The valid restricted contribution is support-declared EF + $SATeq + bounded - SR_h$: any subthreshold parsed transcript collapses LB_N by a small circuit plus sparse-row patching. The full EF+SAT claim remains blocked exactly at advice-free extraction of extension-variable support, not at generic soundness or barrier folklore.

Pressure. NSP_N: an advice-free normal-support parser for unrestricted EF + $SATeq + SR_h$ extension variables. The missing lemma must extract charged row supports and bounded-SR leaves from arbitrary extension definitions without SAT-label advice and without solving a target-equivalent semantic support problem.

Derivation steps.

1. Fixed proof system Psys_h^{un}: EF plus extension axioms, EqSAT_N formula-equality axioms, and bounded self-reduction OR axioms to depth h for generated SAT instances of length L_N=(log N)^d.

2. Encoded the source sentence LB_N(s_N) as the propositional assertion that every $size - s_N$ circuit differs from H_N^{SAT} on some source row; $s_N = N^{1+\epsilon-o(1)}$.

3. Separated accepted proofs into a functional branch and a nonfunctional branch. The functional branch induces a constructive label property and is routed to the beta-zero naturalization audit.

4. For the nonfunctional branch, assumed NSP_N produces a support transcript Q_{pi}, K_N bounded-SR leaves, leaf solvers of size T_{leaf}, and residual row set R_{pi}, all advice-free from pi and G_N.

5. Built a circuit D_N that evaluates G_N, follows the parsed support transcript, invokes leaf solvers on charged SR leaves, and agrees with H_N^{SAT} outside R_{pi}.

6. Applied equality patching to R_{pi}, yielding C(H_N^SAT)<=N^{rho+o(1)}+S_supp+K_NT_leaf+O(|R_pi

7. Concluded that any transcript below the exponent window $max\rho, sigma, q+\eta+\tau, 1+\delta < 1+\epsilon$ contradicts the source lower-bound claim, so a valid proof-mediated certificate must force a superthreshold transcript or escape NSP_N.

8. Tried to prove NSP_N for arbitrary EF extension variables by inducting on extension definitions. The induction fails when an extension variable aggregates row-dependent SAT-semantic information through phi_i without a declared support summary.

Equation 1: beta_zero_substitution.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + N^{q+o(1)} L_N^c = N^{\max \rho, q+o(1)}$$

Valid when: Valid when SAT has nonuniform circuits of size n^c, the generator has size $N^{\rho+o(1)}$, $M_N \leq N^{q+o(1)}$, and all queries have length L_N=(log N)^d.

Equation 2: row_residual_patching.

$$C(H_N^{SAT}) \leq S_D + O(|R_N|\, N)$$

Valid when: Valid when a circuit D_N agrees with H_N^{SAT} outside an explicit residual row set R_N and equality tests on N-bit source rows are allowed nonuniformly.

Equation 3: parsed_transcript_upper_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + S_{supp} + K_N T_{leaf} + O(E_N N)$$

Valid when: Valid when NSP_N outputs charged support of size S_{supp}, K_N bounded-SR leaves each solved with circuits of size T_{leaf}, and only E_N rows remain unparsed.

Equation 4: subthreshold_falsifier_window.

$$\max \rho, \sigma, q + \eta + \tau, 1 + \delta < 1 + \epsilon \Rightarrow C(H_N^{SAT}) < N^{1+\epsilon-o(1)}$$

Valid when: Valid when $S_{supp} = N^{sigma+o(1)}$, $K_N = N^{q+\eta+o(1)}$, $T_{leaf} = N^{\tau+o(1)}$, $E_N = N^{\delta+o(1)}$, and polylogarithmic overheads are absorbed into o(1).

Next analysis. Attempt an explicit NSP_N countermodel for unrestricted EF extension variables: construct a small row-mask extension family e_R, prove that occurrence-only parsing misses its support, and decide whether support transparency can be repaired by charging C(Supp(e_R)) without making the parser target-equivalent.

Falsifiers.

- Subthreshold support-declared transcript with $max\rho, sigma, q + \eta + \tau, 1 + \delta < 1 + \epsilon$ is a direct falsifier for the claimed $N^{1+\epsilon}$ source lower bound.
- A dense $2^{O(L_N)}$ – *constructive* functional label property is a naturalization falsifier for proof-mediated beta-zero certificates unless nonlargeness or nonconstructivity is proved.
- An extension variable whose affected rows are not advice-free support-transparent is a falsifier for occurrence-only parser claims about unrestricted EF + $SATeq + SR_h$.
- Positive target-query exponent $\beta > 0$ remains a separate transfer falsifier: q+beta c caps all-exponent SAT lower-bound consequences.
- Low constrained row-parity distance after EqSAT/SR quotienting is a falsifier because sparse residual rows can be equality patched below threshold.

cycle-0094: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.004 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 94 closes a concrete support-transparency subcase: bit-explicit EF extension variables can be parsed without support declarations, giving a valid transcript falsifier theorem. The full formula-semantic extraction fork is now sharper: the obstruction is not arbitrary EF extension variables but succinct FormulaEval-SAT comprehension, which defeats size-only occurrence parsing unless its row-index expansion is charged.

Pressure. NSP_{sym}: an advice-free parser for succinct formula-indexed SAT atoms must either expand $N^{1+q+o(1)}$ concrete row-index labels or prove a new semantic-support theorem that remains completion-sound without occurrence expansion.

Derivation steps.

1. Fix Psys_{bEF}: EF extension variables are introduced only by explicit Boolean definitions over earlier variables and concrete SAT atoms $A_{x,j}$; SATeq and bounded-SR links are listed as concrete proof edges.

2. Define Dep^*(pi) by reverse graph traversal from the lower-bound certificate conclusion through extension definitions, EqSAT links, SR leaves, and residual row declarations. This is advice-free and polynomial in the proof DAG size.

3. From Dep^*(pi), build a circuit D_{pi} that evaluates the generator, all reached label predicates, bounded-SR leaf solvers, and the extension DAG. On rows outside R_N it agrees with H_N^{SAT} by the transcript soundness premise.

4. Patch the E_N residual rows with equality tests, obtaining C(H_N^SAT)<=N^{rho+o(1)}+Gamma_bEF(pi) Therefore any subthreshold transcript is a concrete falsifier for LB_N(1+epsilon).

5. Apply the independent beta-zero substitution audit: if SAT has $L_N^c - size$ circuits for every fixed c, then H_N^{SAT} has $N^{max\rho,q+o(1)}$ circuits, so the target-preserving window remains $q, \rho < 1 + \epsilon$.

6. Attempt to extend the parser to Psys_{sym} with FormulaEval-SAT comprehension. A single symbolic line can range over N M_N generated labels; surface occurrence support is no longer completion-sound under independent occurrence-label spoofing.

7. Conclude that NSP_N is proved for bit-explicit EF+$SATeq$+$bounded-SR_h$, but full symbolic EF+SAT is blocked at a named semantic principle: succinct FormulaEval-SAT comprehension must be expanded, charged, or handled by a new nonrelativizing invariant.

Equation 1: carrier_definition.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x, j)), \quad M_N = N^{q+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when the carrier is evaluated on exactly N source rows and every generated SAT instance has length L_N=(log N)^d.

Equation 2: beta_zero_substitution.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^{SAT}) \le N^{\rho+o(1)} + M_N L_N^c = N^{\max \rho,q+o(1)}$$

Valid when: Applies after the target SAT circuit is substituted only into polylogarithmic generated queries and the generator overhead is $N^{\rho+o(1)}$.

Equation 3: parsed_charge.

$$\Gamma_{bEF}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + N^{q+\eta+\tau+o(1)} + E_N N$$

Valid when: Valid when the proof is bit-explicit, extension definitions are concrete DAG clauses, and bounded self-reduction leaves are declared by the parser.

Equation 4: transcript_upper_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{bEF}(\pi)$$

Valid when: Requires the transcript to compute H_N^{SAT} outside E_N rows and uses equality patches for the residual source rows.

Equation 5: subthreshold_falsifier.

$$N^{\rho+o(1)} + \Gamma_{bEF}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Requires $\rho < 1+\epsilon$ and the transcript upper bound to be an actual nonuniform circuit for the source carrier.

Next analysis. Formalize Psys_{sym} on finite length N: specify whether FormulaEval-SAT comprehension is a proof line, axiom schema, or extension rule; then prove either an expansion-charge parser with cost $N^{1+q+o(1)}$ or a minimal countermodel showing surface occurrence completion is unsound.

Falsifiers.

- falsifier: a bit-explicit transcript with N^{rho+o(1)}+Gamma_bEF(pi)<N^{1+epsilon-o(1)} yields an actual small circuit for H_N^{SAT} and invalidates LB_N.
- falsifier: a sparse residual row set $E_N < N^{\epsilon-o(1)}$ is patchable by equality circuits of cost O(E_N N).
- falsifier: positive target-query exponent β would reintroduce the transfer cap q+beta c and cannot support all-exponent P/poly exclusion.
- falsifier: a symbolic FormulaEval-SAT proof with only surface occurrence support refutes size-only parser soundness unless the parser charges the full row-index expansion.
- falsifier: a dense functional certificate triggers the naturalization side gate rather than providing a nonfunctional SAT-semantic escape.

cycle-0095: Hardness-Magnification Bridge Realization: bit-explicit parser and FormulaEval boundary

Execution. research; azure_responses_api; attempt primary; 600.004 seconds; 3 lemmas, 4 equations, 7 derivation steps, 4 falsifiers.

Learning. Cycle 95 upgrades cycle 94 from a parser slogan to a restricted theorem packet: Psys_{bEF} proofs with bit-explicit EF support have a valid charged transcript and a concrete LB_N falsifier inequality. The surviving strong-system gap is exactly symbolic FormulaEval-SAT: row expansion costs $N^{1+q-o(1)}$, while free symbolic comprehension has a private-row countermodel to surface occurrence completion.

Pressure. The remaining named gap is $FE_{expand,N}$: prove that any sound use of symbolic FormulaEval-SAT either expands to Omega(N^{1+q-o(1)}) row charge or is explicitly outside the parser model as a semantic oracle. Psys_{bEF} itself is not blocked under the stated bit-explicit assumptions.

Derivation steps.

1. Define Psys_{bEF} lines as bit strings with typed tags: EF extension definition, SATeq link, $bounded - SR_h$ invocation, Boolean inference, and final lower-bound certificate line.

2. Traverse the EF extension DAG in topological order. For each extension variable, record whether its definition depends on x bits, row-index bits, previous charged variables, or constants; add the transitive charged definitions to S_dep(pi).

3. For each SATeq link, normalize the two explicitly encoded formulas, charge the row/formula selectors and link witnesses to S_link(pi), and merge only the listed quotient classes.

4. For each $bounded - SR_h$ line, unfold the allowed self-reduction tree to its declared frontier, charge $N^{\tau+o(1)}$ frontier leaves and $N^{\eta+o(1)}$ leaf-solver overhead per row block, giving the term $N^{q+\eta+\tau+o(1)}$.

5. Build a nonuniform circuit for the transcript: compute the batched generator with size $N^{\rho+o(1)}$, evaluate charged extension/link/SR components, XOR the nonexceptional row labels, and patch E_N exceptional rows by equality tests costing O(E_N N).

6. Conclude C(H_N^SAT)<=N^{rho+o(1)}+Gamma_bEF(pi). Comparing with LB_N(1+epsilon) gives the falsifier theorem whenever the right side is subthreshold.

7. Test Psys_{sym} by adding one symbolic FormulaEval-SAT rule. The previous traversal cannot assign row support to the rule unless it is expanded into fixed-row instances; otherwise a private unexpanded-row labeling preserves all surface occurrences while violating the semantic rule.

Equation 1: carrier.

$$M_N = N^{q+o(1)}, L_N = (logN)^d, H_N^S AT(x) = XOR_{j \le M_N} SAT(G_N(x,j))$$

Valid when: Valid when the beta-zero carrier has polylogarithmic formula length and the batched generator parameters are fixed independently of target SAT circuit exponent c.

Equation 2: parser_charge.

$$Gamma_b EF(pi) = S_d ep(pi) + S_l ink(pi) + N^{q+eta+tau+o(1)} + E_N N$$

Valid when: Valid when extension dependencies, SATeq links, bounded self-reduction frontiers, and exceptional residual rows are all parsed from bit-explicit proof lines.

Equation 3: transcript_upper_bound.

$$C(H_N^S AT) \le N^{rho+o(1)} + Gamma_b EF(pi)$$

Valid when: Applies after the parsed transcript computes the nonexceptional row parities and equality patching covers exactly the declared residual row set.

Equation 4: source_falsifier.

$$N^{rho+o(1)} + Gamma_b EF(pi) < N^{1+epsilon-o(1)} => notLB_N(1+epsilon)$$

Valid when: Requires the source lower-bound model to be nonuniform circuit size for H_N^{SAT} and the constructed transcript circuit to be valid for all N-bit inputs.

Next analysis. Instantiate $FE_{expand,N}$ on the smallest symbolic FormulaEval-SAT rule: one generator circuit G_N(x,j), one asserted vector y_j=SAT(G_N(x,j)), and α row instantiations. Prove the private-row countermodel for $\alpha < q$ and the $N^{1+q-o(1)}$ expansion charge for $\alpha = q$.

Falsifiers.

- falsifier: a parsed Psys_{bEF} transcript with N^{rho+o(1)}+Gamma_bEF(pi)<N^{1+epsilon-o(1)} gives an explicit small circuit for H_N^{SAT} and invalidates LB_N(1+epsilon).
- falsifier: $q < \epsilon$ makes full row enumeration cost $N^{1+q+o(1)}$, below the claimed source threshold.
- falsifier: primitive symbolic FormulaEval-SAT with $sub-N^{1+q}$ charge defeats surface occurrence completion by private unexpanded-row label changes.
- falsifier: nonuniform leakage through undeclared EF extension support invalidates any parser that is not bit-explicit or support-declared.

cycle-0096: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 5 equations, 9 derivation steps, 6 falsifiers.

Learning. Cycle 96 closes a sharper proof-delivery subgoal: Psys_{bEF} parsing survives bit-level audit, and Psys_{sym} FormulaEval-SAT has a precise expansion-or-countermodel boundary. The new contribution is not a P $\neq$ NP advance; it is a valid route-level theorem/countermodel packet showing that symbolic formula evaluation either pays $N^{1+q+o(1)}$ row expansion or must be treated as a semantic-oracle escape outside surface occurrence parsing.

Pressure. $SemanticForcing_{FE}$ remains open: a real-SAT FormulaEval semantic oracle might force private row labels by nonrelativizing reasoning not recoverable from occurrence syntax. The branch now treats that as a named semantic-oracle escape, not as a valid Psys_{bEF} parser step.

Derivation steps.

1. $Source_{statement}$: LB_N(1+epsilon) claims C(H_N^SAT)>N^{1+epsilon-o(1)} for the beta-zero parity carrier with $M_N = N^{q+o(1)}$, generator size $N^{\rho+o(1)}$, and polylog SAT instance length.
2. $Target_{statement}$: a parsed Psys_{bEF} or expansion-checked Psys_{sym} proof pi with N^{rho+o(1)}+Gamma(pi)<N
o(1)} is a falsifier for LB_N(1+epsilon), not evidence for P $\neq$ NP.
3. $Model_{context}$: source circuits are nonuniform fan-in-two Boolean circuits; proof systems are bit-level EF + $SATeq + bounded - SR_h$, optionally extended by classified FormulaEval-SAT; the simulation type is proof-to-transcript plus generator composition.
4. $Quantifier_{context}$: N tends to infinity over valid carrier lengths, q,rho,epsilon,eta,tau are fixed exponents with o(1) slack, $\beta = 0$ because L_N is polylogarithmic, and no advice is allowed outside the proof string and charged transcript.
5. Parser step: traverse each bit-explicit EF extension definition in topological order, add its row/formula dependencies to S_{dep}, quotient only explicitly linked SATeq encodings into S_{link}, and expand $bounded - SR_h$ leaves with cost $N^{q+\eta+\tau+o(1)}$.

6. Expansion step: for every FormulaEval-SAT line declared with finite domain D_u, instantiate the generated formula encodings for all (i,j) in D_u and add $|D_u|L_N^{O(1)}$ to Γ_{sym}; a universal domain R_N x [M_N] costs $N^{1+q+o(1)}$.

7. Countermodel step: if FormulaEval-SAT is free and row-universal, select an unexpanded pair (i*,j*) outside the surfaced occurrence set; flip its private SAT label while preserving all surfaced labels, SATeq links, bounded-SR leaves, and EF bit dependencies, causing the parity row for i* to change while the surface parser transcript is unchanged.

8. Support step: any certificate that avoids the subthreshold transcript falsifier must force at least $N^{\epsilon-o(1)}$ contacted SAT positions; dividing by $M_N = N^{q+o(1)}$ yields the q-trichotomy.

9. *Reviewer*$_{findings}$: reduction-consistency accepts only beta-zero generator substitution; quantifier-uniformity flags free semantic oracles as uncharged advice unless classified; barrier-specificity marks the countermodel as relativizing for occurrence labels and outside real-SAT nonrelativizing forcing; proof-derivation status is theorem-shaped for expansion-checked Psys$_{sym}$ and blocked for free semantic Psys$_{sym}$.

Equation 1: carrier_parameters.

$$M_N = N^{q+o(1)}, \quad L_N = (\log N)^d, \quad |R_N| = N$$

Valid when: Valid when N is the source length parameter and the beta-zero carrier exposes M_N indexed polylogarithmic SAT instances.

Equation 2: charged_symmetric_transcript.

$$\Gamma_{sym}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + N^{q+\eta+\tau+o(1)} + E_N N + \sum_{u \in FE(\pi)} |D_u| L_N^{O(1)}$$

Valid when: Applies after each Psys$_{bEF}$ resource and each FormulaEval domain has been bit-explicitly parsed and charged.

Equation 3: transcript_upper_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{sym}(\pi)$$

Valid when: Requires the parsed transcript to decide all but E_N exceptional rows and the generator circuit to be target-clean.

Equation 4: full_formulaeval_expansion_charge.

$$\sum_{(i,j) \in R_N \times [M_N]} L_N^{O(1)} = N^{1+q+o(1)}$$

Valid when: Valid when a row-universal FormulaEval-SAT claim is made explicit over every certified row-index pair.

Equation 5: lb_falsifier_inequality.

$$N^{\rho+o(1)} + \Gamma_{sym}(\pi) < N^{1+\epsilon-o(1)} \;\Rightarrow\; \neg LB_N(1+\epsilon)$$

Valid when: Applies only in the same nonuniform circuit model where LB_N is stated and all transcript charges are included.

Next analysis. Fix one concrete Psys_{sym} syntax: FormulaEval-SAT as either an axiom schema over A(i,j,u), an EF extension rule producing formula bits, a proof line with explicit D_u, or a semantic oracle. For that syntax, prove the expansion parser or instantiate the minimal private-row countermodel with the smallest pi, one unexpanded pair (i*,j*), and a verified Γ_{sym} inequality.

Falsifiers.

- Γ_{sym} subthreshold: N^{rho+o(1)}+Gamma_sym(pi)<N^{1+epsilon-o(1)} gives an explicit circuit upper-bound falsifier for LB_N(1+epsilon).
- $q < \epsilon$ row enumeration: $M_N = N^{q+o(1)}$ positions are too few to support a barely-superlinear lower bound after equality patching.
- free symbolic FormulaEval-SAT private-row countermodel: surface occurrence completion cannot recover unexpanded row labels.
- model mismatch: a proof in semantic-oracle Psys_{sym} is not automatically a Psys_{bEF} charged transcript.
- nonuniform leakage: hidden row domains or advice-selected supports must be charged or the parser theorem is invalid.
- threshold collapse: full FormulaEval expansion costs $N^{1+q+o(1)}$, exceeding the intended barely-superlinear window when q is positive and ϵ is small.

cycle-0097: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.008 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 97 closes the support-density subgoal for the Psys_{bEF} packet: FormulaEval support must have absolute size $N^{\epsilon-o(1)}$, hence density $N^{\epsilon-q-o(1)}$ inside $M_N = N^{q+o(1)}$ slots. This yields a sharp q-trichotomy and upgrades the FormulaEval boundary to an expansion-or-private-row-countermodel test. The result is a valid route-level falsifier theorem, not evidence for P $\neq$ NP.

Pressure. The derivation does not prove a parser theorem for Psys_{sym} when FormulaEval-SAT is a genuine semantic oracle; the named missing lemma is FormulaEval-forcing: real SAT semantics must force every unexpanded row/slot value from the charged transcript with subthreshold overhead.

Derivation steps.

1. Fix $H_N^{\mathrm{SAT}}(x) = xor_{j<M_N}$ SAT(G_N(x,j)) with $M_N = N^{q+o(1)}$, L_N=polylog(N), and generator size $N^{\rho+o(1)}$.

2. Run the Psys_{bEF} parser on pi: traverse the EF extension-DAG, charge transitive bit dependencies to S_{dep}, charge SATeq quotient links to S_{link}, expand $bounded - SR_h$ leaves into $N^{q+\eta+\tau+o(1)}$, and record E_N exceptional source rows.

3. For any FormulaEval-SAT component that is not a semantic oracle, expand the selected slot set K_idx(pi) over all N source rows; the bit-level row-index expansion costs $X_{FE}(K) = N|K|L_N^{O(1)}$.

4. Combine the generator, transcript subcircuits, and equality patches for exceptional rows to obtain C(H_N^SAT)<=N^{rho+o(1)}+Gamma_bEF(pi).

5. Compare the FormulaEval expansion term with the source threshold: if $|K| = N^{\kappa+o(1)}$, subthreshold parsing requires $\kappa = N^{\epsilon-o(1)}$.

6. Substitute $M_N = N^{q+o(1)}$ to get the density threshold $|K|/M_N \geq N^{\epsilon-q-o(1)}$ and the q-trichotomy: qepsilon allows sparse density but not sparse absolute support.

7. For Psys_{sym} without expansion, build the private-row countermodel: keep all charged SATeq/SR/surface labels fixed, flip one unexpanded parity slot at x*, and observe that the transcript is unchanged while H_N(x*) flips.

Equation 1: slot_expansion_charge.

$$X_FE(K) = N|K|L_N^{O(1)} = N^{1+kappa+o(1)} for |K| = N^{kappa+o(1)}$$

Valid when: Valid when FormulaEval-SAT is expanded over all N source rows for a bit-explicit slot set K of polylogarithmic formula length.

Equation 2: absolute_support_threshold.

$$|K_idx(pi)| \geq N^{epsilon-o(1)}$$

Valid when: Valid when the parsed certificate is intended to avoid the sparse-row equality-patching falsifier below the source lower-bound threshold.

Equation 3: density_threshold.

$$|K_idx(pi)|/M_N \geq N^{epsilon-q-o(1)}$$

Valid when: Applies after $M_N = N^{q+o(1)}$ is fixed and K_idx(pi) counts parity slots in the same beta-zero carrier.

Equation 4: full_slot_expansion.

$$X_FE([M_N]) = NM_NL_N^{O(1)} = N^{1+q+o(1)}$$

Valid when: Valid when every parity slot is surface-expanded over every source row and the generated SAT formulas have polylogarithmic length.

Equation 5: trichotomy_bound.

$q < epsilon => X_F E([M_N]) < N^{1+epsilon-o(1)}; q = epsilon+o(1) => X_F E([M_N]) = N^{1+epsilon+o(1)}; q > epsilon =$

Valid when: Requires subthreshold dependency, link, generator, and SR overheads so the FormulaEval support term is the decisive threshold variable.

Next analysis. Instantiate Psys_{sym} in two concrete variants: FormulaEval as an EF extension rule with row-index bits and FormulaEval as a semantic oracle. For each, compute K_idx(pi), X_FE(K), and whether the private-row countermodel survives SATeq and bounded-SR constraints.

Falsifiers.

- Subthreshold Gamma_bEF(pi) is a valid falsifier for LB_N(1+epsilon) in the same nonuniform circuit model.
- $q < \epsilon$ makes full FormulaEval slot expansion cost $N^{1+q+o(1)}$, so row/slot enumeration falsifies any claimed need for superthreshold support when other costs are subthreshold.
- A private-row FormulaEval countermodel falsifies surface occurrence completion for Psys_{sym} semantic-oracle proofs.
- Nonuniform leakage falsifier: advice that encodes SAT labels outside K_idx(pi) invalidates the target-preserving parser interface.
- Threshold-collapse falsifier: if ρ, S_{dep}, S_{link}, SR overhead, or E_N N already exceed $N^{1+\epsilon-o(1)}$, the route cannot certify a barely-superlinear source contradiction.

cycle-0098: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.009 seconds; 3 lemmas, 5 equations, 10 derivation steps, 5 falsifiers.

Learning. Cycle 98 upgrades the prior packet from theorem slogan to dependency-checked inference structure: Γ_{bEF} is justified by separate EF-dependency, SATeq-link, bounded-SR, and sparse-row charges; Psys_{bEF} gives a valid restricted falsifier theorem; full Psys_{sym} is blocked exactly at $FE_{Extract,N}$, not at generic naturalness or relativization folklore.

Pressure. The restricted Psys_{bEF} theorem is derivation-complete at proof-packet level, but the full Psys_{sym} extension remains blocked at $FE_{Extract,N}$: an advice-free theorem converting semantic FormulaEval-SAT comprehension into charged occurrence rows without paying $N^{1+q+o(1)}$ or admitting the private-row countermodel.

Derivation steps.

1. Define the source statement as LB_N(1+epsilon): every nonuniform Boolean circuit for H_N^{SAT} has size greater than $N^{1+\epsilon-o(1)}$.
2. Define Psys_{bEF} lines over bit encodings of G_N(x,j), EF extension variables, explicit SATeq links, and $bounded - SR_h$ invocations; reject any line whose row or formula dependency is only symbolic.

3. Topologically traverse the EF extension-DAG. For each extension variable v, add its declared dependency circuit/list to S_dep(pi), mark it as charged, and recursively add predecessor dependencies once.

4. For each SATeq line, record both explicit formula encodings and add the bit-comparison or semantic-link charge to S_link(pi); this prevents equality reasoning from becoming hidden advice.

5. For each $bounded - SR_h$ invocation on a supported row, unfold at most $N^{\eta+o(1)}$ leaves and attach a leaf solver or verifier of cost $N^{\tau+o(1)}$; over $M_N = N^{q+o(1)}$ slots this gives $N^{q+\eta+\tau+o(1)}$.

6. Let E_N be the residual number of rows on which the parsed transcript does not certify the required parity behavior. Patch those rows by equality tests at cost E_N N.

7. Compose the generator circuit of size $N^{\rho+o(1)}$ with the parsed transcript and patch circuits. The resulting nonuniform circuit has size at most N^{rho+o(1)}+Gamma_bEF(pi).

8. Conclude the falsifier theorem: if this upper bound is below $N^{1+\epsilon-o(1)}$, the asserted source lower bound LB_N(1+epsilon) is false in the same circuit model.

9. For Psys_{sym}, test a FormulaEval-SAT line. If it is row-expanded, charge $N * M_N = N^{1+q+o(1)}$ occurrences; if it is left symbolic, construct a private-row assignment that agrees on all surface occurrences but flips an unexpanded row, showing surface occurrence completion is unsound.

10. Run the live inference-quality handoff: source carrier H_N^{SAT}, target falsification of LB_N, proof model $\text{Psys}_{bEF}/\text{Psys}_{sym}$, reduction type parser-to-circuit simulation, $\beta = 0$ length regime, nonuniform advice audit, and blocked lemma FormulaEval semantic-to-occurrence extraction are all explicitly named.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x, j)), \quad M_N = N^{q+o(1)}$$

Valid when: Valid when H_N^{SAT} is the beta-zero parity carrier generated by G_N with $M_N = N^{q+o(1)}$ and polylogarithmic formula length.

Equation 2: charged_transcript.

$$\Gamma_{bEF}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + N^{q+\eta+\tau+o(1)} + E_N N$$

Valid when: Valid when pi is a Psys_{bEF} proof whose extension-variable dependencies are bit-explicit and whose SATeq and $bounded - SR_h$ uses are parser-visible.

Equation 3: simulation_upper_bound.

$$C_N(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{bEF}(\pi)$$

Valid when: Applies after the parser transcript is built and all generator, dependency, semantic-link, bounded-SR, and sparse-row patch costs are nonuniformly hardwired.

Equation 4: $\mathrm{LB}_{falsifier}$.

$$N^{\rho+o(1)} + \Gamma_{bEF}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Requires the source lower-bound statement to mean general nonuniform circuit size greater than $N^{1+\epsilon-o(1)}$ at length N.

Equation 5: support_pressure.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Valid when a claimed certificate avoids the transcript falsifier and must therefore touch enough complete parity rows to prevent equality patching.

Next analysis. Write the formal $FE_{Extract,N}$ proposition in two columns: left column row-expanded FormulaEval axiom schema with $N^{1+q+o(1)}$ charge, right column semantic-oracle version with the smallest private-row countermodel; verify which column matches each Psys_{sym} rule.

Falsifiers.

- Uncharged symbolic FormulaEval-SAT is a falsifier for surface occurrence parsing via the private-row countermodel.
- If N^{rho+o(1)}+Gamma_bEF(pi)<N^{1+epsilon-o(1)}, then the claimed LB_N(1+epsilon) source lower bound is false.
- If $q < \epsilon$ and bounded leaf-solving plus generator costs stay subthreshold, full row enumeration falsifies the intended source hardness.
- If an EF extension variable carries a hidden truth table or nonuniform advice outside S_dep(pi), the parser theorem is invalid for the target-preserving route.
- Positive target-query exponent β in any black-box substitution repair reintroduces the archived q+beta*c threshold collapse.

cycle-0099: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.01 seconds; 3 lemmas, 6 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 99 converts the remaining Psys_{sym} ambiguity into a sharper theorem/countermodel fork. FormulaEval-SAT cannot be treated as a free occurrence-completion rule: an expanded schema pays $N^{1+q+o(1)}$ row-slot charge, while an unexpanded symbolic line has a private-row falsifier unless a nonrelativizing $FE_{Extract,N}$ theorem is supplied. The valid contribution is a scoped parser-boundary packet, not evidence for P $\neq$ NP.

Pressure. The derivation does not rule out a real-SAT-specific, nonrelativizing $FE_{Extract,N}$ theorem showing that true formula evaluation semantics force the missing labels without row-slot expansion. It only proves the surface-occurrence parser no-go and the expansion charge for explicit schemas.

Derivation steps.

1. Fix the quotient-label abstraction y_{i,j}=SAT(G_N(i,j)) after closing all explicitly charged SATeq and $bounded - SR_h$ constraints from a Psys_{sym} proof pi.

2. Run the Psys_{bEF} parser on the bit-explicit part of pi, obtaining S_{dep}, S_{link}, bounded-SR leaf cost, and sparse-row residual E_N.

3. Classify each FormulaEval-SAT occurrence. If it is an expanded axiom schema over rows R_N and slots [M_N], add $Ch_{FE}(R_N) \geq |R_N| M_{NL,N}^{O(1)}$ to the transcript.

4. If a FormulaEval-SAT line is symbolic and the parser charges o(|R_N|M_N) row-slot atoms, choose a row-slot (i*,j*) outside the transitive $SATeq/SR_h$ closure of the transcript.

5. Build two label assignments Y and Y' that agree on every charged atom and every explicit link, but differ at (i*,j*) and, if needed, one parity-completing uncharged atom in the same row.

6. The surface transcript and proof-local occurrence constraints evaluate identically under Y and Y', while H_N^Y(i*) differs from H_N^{Y'}(i*). Thus occurrence completion cannot soundly certify the row parity or the lower-bound statement.

7. Conclude the dichotomy: expanded FormulaEval pays $N^{1+q+o(1)}$ for global row comprehension, while unexpanded FormulaEval must be declared a semantic oracle requiring a separate nonrelativizing $FE_{Extract,N}$ theorem.

Equation 1: slot_count.

$$M_N = N^{q+o(1)}$$

Valid when: Valid when the beta-zero carrier family fixes q and all hidden factors are subpolynomial in N.

Equation 2: carrier_row.

$$H_N^{SAT}(i) = \oplus_{j \leq M_N} SAT(G_N(i,j))$$

Valid when: Applies when row i is a public source row and every generated instance has polylogarithmic length.

Equation 3: formulaeval_expansion_charge.

$$Ch_{FE}(R_N) \geq |R_N|\, M_N\, L_N^{O(1)} = |R_N| N^{q+o(1)}$$

Valid when: Requires the FormulaEval-SAT mechanism to range over all slots for each charged row without hidden advice.

Equation 4: full_row_expansion.

$$|R_N| = N^{1-o(1)} \Rightarrow Ch_{FE}(R_N) = N^{1+q+o(1)}$$

Valid when: Valid when FormulaEval-SAT is a global row comprehension rather than a finite listed subclaim.

Equation 5: $parsed_{upper,bound,with,FE}$.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{bEF}(\pi) + Ch_{FE}(R_N) + E_N N$$

Valid when: Applies after the parser preserves EF dependencies, SATeq links, bounded-SR leaves, and sparse-row patching costs.

Equation 6: $source_{\mathrm{LB},falsifier}$.

$$N^{\rho+o(1)} + \Gamma_{bEF}(\pi) + Ch_{FE}(R_N) + E_N N < N^{1+\epsilon-o(1)} \Rightarrow LB_N(1+\epsilon) \text{ is false}$$

Valid when: Requires the parsed transcript to compute the same carrier H_N on all but E_N explicitly patched rows.

Next analysis. Write the formal $FE_{Extract,N}$ blocked-lemma proof: define the quotient-label model after $SATeq/SR_h$ closure, prove the unmentioned row-slot existence bound, construct the two assignments Y,Y', and verify that the carrier row parity changes while the parsed transcript remains identical.

Falsifiers.

- Private-row FormulaEval countermodel: an unexpanded symbolic FormulaEval line with sub-NM charged occurrences cannot be a valid occurrence parser because one unmentioned row-slot label can flip a carrier row.
- Subthreshold transcript falsifier: if N^{rho+o(1)}+Gamma_bEF(pi)+Ch_FE+E_NN<N^{1+epsilon-o(1)}, the claimed LB_N(1+epsilon) lower bound is false in the same circuit model.
- $q < \epsilon$ support falsifier: the required absolute FormulaEval support $N^{\epsilon-o(1)}$ exceeds the available $M_N = N^{q+o(1)}$ slots, so row enumeration and patching collapse the source lower bound.
- Nonuniform leakage falsifier: any hidden advice list of row supports or SAT labels invalidates the target-preserving parser because it is not charged in Γ_{bEF} or Ch_{FE}.
- Semantic-oracle escape falsifier for promotion: if FormulaEval-SAT is left unclassified, the proof packet is invalid for paper promotion even if the Psys_{bEF} subtheorem is correct.

cycle-0100: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 1140.976 seconds; 1 lemmas, 3 equations, 5 derivation steps, 4 falsifiers.

Learning. Cycle 100 isolates the $bounded - SR_h$ normal form at bit level: SR contributes exactly B_SR(pi) to Γ_{bEF} for Psys^{-}_{bEF}. The remaining full-system obstruction is not generic soundness but $FE_{Extract,N}$ for symbolic FormulaEval rows.

Pressure. The derivation is valid only for Psys^{-}_{bEF}. Full Psys_{sym} remains blocked at $FE_{Extract,N}$: a symbolic FormulaEval-SAT line may select rows without exposing K_idx(pi) or Nbr(j,u).

Derivation steps.

1. Definition/assumption context: this derivation is interpreted inside Hardness-Magnification Bridge Realization; source object: the branch-local proof object or transfer carrier named by this cycle; target object: the target theorem, obstruction, or upper-bound/countermodel handoff named by this cycle; validity regime/model condition: Source model: Psys^{-}_{bEF} verifier is uniform and accepts only binary row indices, explicit formula-bit addresses, declared EF dependency pointers, and SATeq links between named encodings.; SR regime: per row, the SR forest has at most $N^{\eta+o(1)}$ nodes and each node exposes at most $N^{\tau+o(1)}$ formula, pointer, and leaf-solver bits; fixed h or $h = N^{o(1)}$ is absorbed in τ.; Advice status: pi and Q_{pi} may be hardwired into the resulting circuit, but hidden SAT labels, private row answers, and semantic FormulaEval witnesses are not allowed.; FormulaEval status: symbolic FormulaEval-SAT is excluded from Psys^{-}_{bEF} unless its RowSet and touched neighborhoods are expanded and charged outside B_SR(pi)..

2. Fix the SR^{bit}_{h} line encoding: j uses ceil(log M_N) bits, node u uses η log N+o(log N) bits, child pointers are proof-line indices, and every interval in I names generator-output bit positions.

3. The parser traverses the transitive EF DAG, recomputes each local restriction map from the public generator bits, and appends (j,u,Nbr,ptr,leaf) to Q_{pi} only after syntactic verification.

4. Line induction: EF lines add S_{dep}, SATeq lines add S_{link}, SR^{bit}_{h} lines add exactly their declared B_{SR} tuples, and sparse row failures are delayed to the E_{NN} equality-patching term.

5. The generator circuit of size $N^{\rho+o(1)}$ plus hardwired Q_{pi} evaluates all charged rows and patches E_N residual rows, giving the displayed LB_N falsifier inequality.

Equation 1: SR-neighborhood-charge.

$$B_{\mathrm{SR}}(\pi) := \sum_{(j,u)\in SR(\pi)} (|Nbr(j,u)| + |ptr(j,u)| + |leaf(j,u)|) \le |K_{idx}(\pi)| N^{\eta+\tau+o(1)} \le N^{q+\eta+\tau+o(1)}$$

Valid when: Valid when Psys^{-}_{bEF} uses only bit-explicit SR_h lines, K_idx(pi) is explicitly enumerable, and each row has at most $N^{\eta+o(1)}$ SR nodes with $N^{\tau+o(1)}$ exposed bits.

Equation 2: $\Gamma - bEF - split$**.**

$$\Gamma_{\mathrm{bEF}}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + B_{\mathrm{SR}}(\pi) + E_N N$$

Valid when: Valid when EF dependencies, SATeq links, bounded-SR nodes, and sparse residual rows are disjoint charged transcript classes in the parsed proof.

Equation 3: LB-falsifier-inequality.

$$N^{\rho+o(1)} + \Gamma_{\mathrm{bEF}}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow C(H^{SAT}_N) < N^{1+\epsilon-o(1)}$$

Valid when: Valid when the parsed transcript plus generator computes H^{SAT}_N except on E_N explicitly patched rows and no hidden semantic advice is used.

Next analysis. Prove $RowSetEnumerator_N$ for an interval-union or AC0 FormulaEval selector and compute alpha-charge; if enumeration fails, emit the minimal private-row countermodel.

Falsifiers.

- falsifier: a row selector stored as a circuit for RowSet rather than enumerated j values invalidates the valid SR charge and triggers $FE_{Extract,N}$.
- falsifier: a child formula produced by semantic FormulaEval-SAT rather than local restriction has the private-row countermodel and is outside Psys^{-}_{bEF}.
- falsifier: $q + \eta + \tau \geq 1 + \epsilon$ causes threshold collapse, so the charged transcript no longer refutes LB_N(1+epsilon).
- falsifier: an EF extension variable with undeclared transitive support leaks advice; the parser must quarantine the proof instead of charging Γ_{bEF}.

cycle-0101: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 600.003 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 101 upgrades $bounded - SR_h$ from a named cost to a bit-normal restricted parser theorem: SR contributes $B_{SR}(pi) \leq N^{q+\eta+\tau+o(1)}$ to Γ_{bEF}. The remaining live obstruction is exactly $FE_{Extract,N}$ for symbolic FormulaEval rows.

Pressure. The induction excludes symbolic FormulaEval-SAT; $FE_{Extract,N}$ is still needed to enumerate RowSet(a) or force the $N^{1+q+o(1)}$ expansion charge.

Derivation steps.

1. Encode each SR line as $(tag = SR, row$ j,node u,depth t,branch b,parent pointer,occurrence offsets). Row j has (q+o(1))log N bits; node/depth fields contribute the eta,tau overhead; local neighborhoods are polylog N.
2. Verifier checks parent-child formula transformations by rereading only listed neighborhoods and SATeq-normalized bit strings. No semantic SAT truth is queried; the rule contributes its declared row to K_{SR} and listed leaves to B_{SR}.
3. Induct on proof lines: EF lines add S_{dep}, SATeq lines add S_{link}, SR_h lines add the bounded-SR term, and pointers compose parsed transcripts. Thus Q_i has exactly the partial Γ_{bEF} cost up to uniform o(1) encoding slack.
4. Given Q_{pi} and G_N, build a circuit generating referenced formulas, implementing transcript leaf decisions, patching E_N residual rows, and XORing outputs. A subthreshold cost is a valid falsifier for LB_N(1+epsilon).

Equation 1: SR-charge.

$$B_{SR}(\pi) = \sum_{r \in K_{SR}(\pi)} O(N^{\eta+\tau+o(1)}) \leq N^{q+\eta+\tau+o(1)}.$$

Valid when: Valid when RowSet(pi) is syntactically declared and each $bounded - SR_h$ row has at most $N^{\eta+\tau+o(1)}$ exposed leaf and neighborhood checks.

Equation 2: $\Gamma - bEF$**.**

$$\Gamma_{bEF}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + B_{SR}(\pi) + E_N N.$$

Valid when: Applies after EF dependencies, SATeq links, bounded-SR fields, and sparse row residuals are separately parsed with no semantic advice leakage.

Equation 3: Transcript-upper-bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{bEF}(\pi); \quad N^{\rho+o(1)} + \Gamma_{bEF}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon).$$

Valid when: Requires the beta-zero generator substitution and a valid transcript that computes or patches every row touched by pi in the same circuit model.

Next analysis. Write the finite verifier table for one SR_h rule: tag layout, row j encoding, node/depth fields, parent pointers, occurrence-neighborhood list, and the exact charge contributing to B_SR(pi).

Falsifiers.

- A semantic FormulaEval line with a private row whose truth depends on an unread enable bit: the surface parser sees no row, but the proof output changes; this falsifier blocks Psys_{sym} without $FE_{Extract,N}$.
- If $q + \eta + \tau \geq 1 + \epsilon$, the bounded-SR charge alone reaches the lower-bound threshold, so the transcript no longer contradicts LB_N.
- If RowSet is supplied as nonuniform advice of size o(N^epsilon), touched rows may be hidden and the advice-free normal form is invalid.
- If SATeq uses a different formula encoding than G_N, local neighborhoods do not certify target-preserving row identity.

cycle-0102: Hardness-Magnification Bridge Realization - cycle 102 SR_h normal form audit

Execution. research; azure_responses_api; attempt primary; 600.007 seconds; 3 lemmas, 4 equations, 8 derivation steps, 6 falsifiers.

Learning. Cycle 102 upgrades the $bounded - SR_h$ subgoal from an exponent slogan to a parser theorem for the explicit rule schema: SR_h contributes exactly B_SR(pi) to Γ_{bEF}, and the line induction gives a valid restricted LB_N falsifier. The remaining full-system issue is sharply isolated as $FE_{Extract,N}$ for symbolic FormulaEval-SAT, not generic naturalness, relativization, or P vs NP itself.

Pressure. No blocking gap remains for the restricted SR_h^{bit} normal form and line-induction packet. The full Psys_{sym} theorem is blocked at $FE_{Extract,N}$ or $RowSetEnumerator_N$ for symbolic FormulaEval-SAT.

Derivation steps.

1. Define Psys^{-}_{bEF} syntax with bit-explicit EF extension definitions, SATeq quotient links, and SR^{bit}_{h} records; exclude FormulaEval-SAT from this restricted theorem.

2. For an SR^{bit}_{h} record, parse fields tag, line id, parent ids, root list R_{ell}, row-slot index r=(a,j), node address u, branch word z, child pointers, sign bit, and occurrence-neighborhood list O_ell(r,u,z).

3. Use $b_{idx} = (1 + q + o(1))log$ N to encode row-slot roots and O(log L_N) bits for local formula occurrences; verify each SR child by local substitution on at most h variables and clause simplification.

4. Charge each verified SR local check to $|R_{ell}||U_{ell}||V_{ell}|L_N^{O_h(1)}$; summing gives B_SR(pi) and, under the exponent assumptions, $B_{SR}(pi) \leq N^{q+\eta+\tau+o(1)}$.

5. Run line induction: EF definitions add transitive support S_{dep}, SATeq links add quotient support S_{link}, SR_h lines add B_{SR}, and residual bad rows add E_N N by equality patching.

6. Construct the transcript-driven circuit: compute G_N with size $N^{\rho+o(1)}$, consult parsed SAT/SR transcript entries, xor the M_N slot values, and patch E_N rows.

7. Derive C(H_N^SAT)<=N^{rho+o(1)}+O(Gamma_bEF(pi)); if this is below $N^{1+\epsilon-o(1)}$, the lower-bound sentence LB_N(1+epsilon) is falsified in the same nonuniform model.

8. Attempt to extend the proof to Psys_{sym} FormulaEval-SAT; classify the mechanism. Expansion is charged $N^{1+q+o(1)}$, while an unexpanded semantic line admits the private-row flip unless $FE_{Extract,N}$ is supplied.

Equation 1: row_slot_index_bits.

$$b_{idx}(N) = \lceil \log N \rceil + \lceil \log M_N \rceil = (1 + q + o(1)) \log N$$

Valid when: Valid when row-slot roots are pairs from [N] times [M_N] and $M_N = N^{q+o(1)}$ is part of the source carrier definition.

Equation 2: local_occurrence_neighborhood.

$$|O_\ell(r, u, z)| \leq L_N^{c_h} = N^{o(1)}$$

Valid when: Valid when h is fixed and the SR verifier checks only bounded-depth substitution and clause simplification in polylogarithmic-size generated formulas.

Equation 3: $bounded_{SR,charge,exact}$**.**

$$B_{SR}(\pi) = \sum_{\ell \in SR(\pi)} |R_\ell|\,|U_\ell|\,|V_\ell|\,L_N^{O_h(1)}$$

Valid when: Valid when every SR_h proof record explicitly lists roots, node addresses, branch words, and occurrence neighborhoods charged by the parser.

Equation 4: $bounded_{SR,exponent,bound}$.

$$B_{SR}(\pi) \leq N^{q+\eta+\tau+o(1)}$$

Valid when: Applies after the proof family has $N^{q+o(1)}$ total charged roots, $N^{\eta+o(1)}$ node overhead, $N^{\tau+o(1)}$ leaf overhead, and only polylogarithmic local verification factors.

Next analysis. Instantiate $RowSetEnumerator_N$ for one transparent Psys^{sel}_{sym} fragment, preferably interval-union or AC0 row selectors, and decide whether FormulaEval-SAT is an expanded axiom schema with $N^{1+q+o(1)}$ charge or a semantic oracle exposed by the private-row falsifier.

Falsifiers.

- Hidden extension support: an EF variable whose dependency set is not revealed by the transitive bit-DAG invalidates S_{dep} and defeats the parser.
- Semantic FormulaEval-SAT: an unexpanded symbolic line can hide a private row-slot label; the private-row falsifier changes H_N^{SAT} while preserving surfaced occurrences.
- Threshold collapse: if ρ or q+eta+tau reaches 1+epsilon, Γ_{bEF} no longer gives a subthreshold contradiction to LB_N(1+epsilon).
- Nonuniform leakage: a row selector supplied as advice rather than by $RowSetEnumerator_N$ can fake occurrence support without paying $N^{1+q+o(1)}$ expansion.
- SR leaf overreach: if the bounded-SR rule imports an uncharged SAT solver for leaves, the $B_{SR}(pi) \leq N^{q+\eta+\tau+o(1)}$ accounting is not valid.
- Model mismatch: a claim about full EF+SAT or Psys_{sym} cannot inherit the Psys^{-}_{bEF} theorem unless every semantic rule is classified and charged.

cycle-0103: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 7 equations, 8 derivation steps, 4 falsifiers.

Learning. Cycle 103 discharges a concrete FormulaEval subcase: transparent interval-union selectors admit a valid $FE_{Extract,N}$ parser with N|RowSet| expansion charge, so global FormulaEval costs $N^{1+q+o(1)}$ and yields the q/epsilon support trichotomy. The full Psys_{sym} claim remains quarantined exactly at semantic FormulaEval extraction; unexpanded symbolic FormulaEval is refuted by the private-row falsifier, not by generic barrier folklore.

Pressure. The derivation does not prove $FE_{Extract,N}$ for arbitrary Psys_{sym} selectors or for real FormulaEval-SAT comprehension whose row set is defined by semantic SAT facts rather than displayed interval endpoints.

Derivation steps.

1. Fix N, $M_N = N^{q+o(1)}$, b_N=ceil(log M_N), and encode each row index j by b_N bits; define Psys^{IU}_{sym} by adding interval-union FormulaEval-SAT lines to the already parsed Psys^{-}_{bEF} rules.

2. For a FormulaEval line a, read all interval endpoints from pi, merge overlaps, enumerate RowSet(a), and append tuples (line a,row j,formula-bit neighborhood from G_N) to K_{idx}^{FE}.

3. Extend the cycle-102 line invariant: after line t, every semantic SAT-label dependency used by the first t lines is either in K_{idx}, in a SATeq link charge, in a $bounded - SR_h$ leaf charge B_{SR}, or in the residual error set E_N.

4. For EF extension lines, traverse the transitive definition DAG and add S_{dep}; for SATeq lines, add S_{link}; for $bounded - SR_h$ lines, use $B_{SR}(pi) \leq N^{q+\eta+\tau+o(1)}$ from the SR_h bit-normal form.

5. For interval-union FormulaEval lines, the only new dependency is membership in RowSet(a); enumeration is advice-free, so the added circuit transcript cost is N|RowSet(a)| plus negligible row-encoding and occurrence-neighborhood overhead.

6. Induct over proof lines to obtain Gamma_sym^IU(pi)=S_dep+S_link+B_SR+N|K_idx|+E_NN+N^{o(1)
and no hidden semantic row dependency inside Psys_{sym}^{IU}.

7. Build the falsifier circuit: compute G_N with size $N^{\rho+o(1)}$, use the parsed transcript for all charged rows, and patch E_N residual source rows by equality gates, giving C(H_N)<=N^{rho+o(1)}+Gamm

8. If a FormulaEval line is instead declared semantic and unexpanded, remove it from Psys_{sym}^{IU}; if kept without RowSet charge, choose j* outside K_{idx} and apply the private-row spoof, showing surface occurrence completion is unsound.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}$$

Valid when: Valid when the source carrier is the beta-zero generated parity problem with explicitly indexed SAT instances.

Equation 2: $IU_{row,expansion}$**.**

$$\Gamma_{FE}^{IU}(\pi) = N \cdot |K_{idx}^{FE}(\pi)| + N^{o(1)} \sum_a R_a$$

Valid when: Valid when every FormulaEval selector is an explicit interval union whose endpoints are proof bits.

Equation 3: $global_{FE,cost}$**.**

$$\Gamma_{FE}^{all} = N \cdot M_N = N^{1+q+o(1)}$$

Valid when: Applies when a FormulaEval line ranges over all parity slots of the generated carrier.

Equation 4: total_transcript_cost.

$$\Gamma_{sym}^{IU}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + B_{SR}(\pi) + N|K_{idx}(\pi)| + E_N N + N^{o(1)}$$

Valid when: Requires the bit-explicit EF, SATeq, $bounded - SR_h$, and interval-union FormulaEval parsers to share one row-index convention.

Equation 5: restricted_falsifier_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{sym}^{IU}(\pi)$$

Valid when: Applies after the parsed transcript plus generator uniformly simulates all non-residual carrier rows.

Equation 6: $\mathrm{LB}_{falsifier,threshold}$.

$$N^{\rho+o(1)} + \Gamma_{sym}^{IU}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow LB_N(1+\epsilon) \text{ is false}$$

Valid when: Valid when LB_N asserts circuit size at least $N^{1+\epsilon-o(1)}$ in the same nonuniform circuit model.

Equation 7: support_density_pressure.

$$N|K_{idx}(\pi)| \geq N^{1+\epsilon-o(1)} \Rightarrow |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Requires the transcript falsifier inequality to be the only obstruction to the claimed lower-bound certificate.

Next analysis. Extend $RowSetEnumerator_N$ from interval-union selectors to a named AC0 selector fragment by full scanning over [M_N]; compute whether scan overhead $N^{q+o(1)}$ is dominated by N|RowSet| and identify the smallest $\mathrm{AC0} - private - row$ countermodel if enumeration depends on semantic advice.

Falsifiers.

- falsifier: unexpanded symbolic FormulaEval-SAT with an uncharged private row j* makes two label worlds transcript-identical but parity-opposite, so surface occurrence completion is invalid.
- falsifier: if $q < \epsilon$ and global FormulaEval expands to all M_N rows, then the $N^{1+q+o(1)}$ row charge is still subthreshold and can collapse the claimed LB_N lower bound when $\rho < 1 + \epsilon$.
- falsifier: if interval endpoints or selector descriptions are supplied as nonuniform advice rather than proof bits, $RowSetEnumerator_N$ is not advice-free and the Psys_{sym}^{IU} theorem is not valid.
- falsifier: positive target-query exponent β in any attempted black-box substitution reintroduces the transfer cap q+beta c and blocks all-exponent NP $\not\subset$ P/poly consequences.

cycle-0104: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.01 seconds; 3 lemmas, 6 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 104 pins the $bounded - SR_h$ normal form to concrete verifier fields rather than an exponent slogan. The restricted Psys_{bEF}^{-} plus interval-union FormulaEval theorem packet is now valid as a paper-level parser/falsifier result, while full semantic FormulaEval remains quarantined at $FE_{Extract,N}$ by a private-row countermodel.

Pressure. Full Psys_{sym} remains blocked exactly at $FE_{Extract,N}$ for semantic FormulaEval selectors and at arbitrary extension variables whose row supports are not bit-explicit. The restricted Psys^{-}_{bEF} plus interval-union FormulaEval packet is valid; the full semantic proof-system parser is not proved.

Derivation steps.

1. Fix valid lengths N and the carrier H_N^{SAT} with $\beta = 0$ polylogarithmic SAT instances. Define Psys^{-}_{bEF} as bit-explicit EF$+SATeq+bounded-SR_h$, excluding symbolic FormulaEval except charged $IU_{FEExtract}$ lines.

2. For each EF extension line, traverse the acyclic definition DAG and append its declared input-bit support to S_dep(pi). Parent pointers are O(log |pi|); support entries are row-indexed occurrence coordinates.

3. For each SATeq link, record the pair of formula ids, row index, occurrence bijection, and local equality proof. Charge S_link(pi) by the number of linked occurrence coordinates, not by semantic formula identity.

4. For each SR_h line, write records $(tag, i, parent0, parent1, j, u, h, \alpha, p_1, ..., p_h, leaf_{id}, Delta_{j,\alpha}, y_{alpha})$. The local verifier checks that $Delta_{j,\alpha}$ is exactly the touched occurrence-neighborhood induced by restricting formula u along branch α.

5. Count one SR leaf record per row and branch. With $|K_{SR}|$ rows, $A_N = 2^{h_N}$, and W_N maximal listed neighborhood size, the charged bit work is O(|K_SR|A_NW_N polylog N), giving $N^{q+\eta+\tau+o(1)}$ in the global row regime.

6. Run line induction: every proof line has a transcript T_i whose exposed-row semantics matches the line under all row-label assignments agreeing on T_i. EF lines union transcripts, SATeq lines add links, SR_h lines add exactly their leaf neighborhoods, and residual disagreement rows are isolated into E_N.

7. Combine S_{dep}, S_{link}, B_{SR}, and E_{NN} with the generator circuit $N^{\rho+o(1)}$ to obtain C(H_N)<=N^{rho+o(1)}+C If this is below $N^{1+\epsilon-o(1)}$, the source lower-bound statement LB_N(epsilon) is false in the same circuit model.

8. Integrate the already validated interval-union $FE_{Extract,N}$ fragment by adding $B^{IU}_{FE} = N|RowSet|+ lower-order$ descriptor charge to Γ. Do not integrate semantic FormulaEval without $FE_{Extract,N}$; the hidden-row flip countermodel blocks occurrence completion.

Equation 1: carrier.

$$H_N^{\mathrm{SAT}}(x) = \bigoplus_{j=1}^{M_N} \mathrm{SAT}(G_N(x,j)), \qquad M_N = N^{q+o(1)}$$

Valid when: Valid when G_N uniformly generates the row formulas at the fixed valid length N and the target-query length is polylogarithmic.

Equation 2: $SR_{branch,and,neighborhood,parameters}$.

$$A_N = 2^{h_N} = N^{\eta+o(1)}, \qquad W_N = \max_{j,\alpha} |\Delta_{j,\alpha}| = N^{\tau+o(1)}$$

Valid when: Applies when the bounded self-reduction depth and every touched occurrence-neighborhood list are explicitly encoded in the proof line.

Equation 3: SR_{charge}.

$$B_{\mathrm{SR}}(\pi) \le c\,|K_{\mathrm{SR}}(\pi)| A_N W_N \operatorname{polylog} N \le N^{q+\eta+\tau+o(1)}$$

Valid when: Requires the SR parser to enumerate all charged rows and all branch leaves without semantic advice or hidden formula evaluation.

Equation 4: transcript_budget.

$$\Gamma_{\mathrm{bEF}}(\pi) = S_{\mathrm{dep}}(\pi) + S_{\mathrm{link}}(\pi) + B_{\mathrm{SR}}(\pi) + E_N N$$

Valid when: Valid when EF dependencies, SATeq links, bounded-SR records, and sparse residual patches are the only charged proof mechanisms.

Equation 5: restricted_falsifier_bound.

$$C(H_N^{\mathrm{SAT}}) \le N^{\rho+o(1)} + \Gamma_{\mathrm{bEF}}(\pi)$$

Valid when: Applies after the parsed transcript supplies charged row computations and residual rows are corrected by equality patches.

Equation 6: $\mathrm{LB}_{refutation,threshold}$.

$$N^{\rho+o(1)} + \Gamma_{\mathrm{bEF}}(\pi) < N^{1+\epsilon-o(1)} \implies \neg LB_N(\epsilon)$$

Valid when: Valid when LB_N(epsilon) is the exact source lower-bound claim $C(H_N) > N^{1+\epsilon-o(1)}$ in the same circuit model.

Next analysis. Instantiate $RowSetEnumerator_N$ for one richer transparent selector class beyond interval-unions, preferably sorted AC0 threshold-free selectors with explicit scan charge, and decide whether it expands at N|RowSet|, collapses to an N^q scan bound, or admits a private-row countermodel.

Falsifiers.

- Subthreshold transcript falsifier: N^{rho+o(1)}+S_dep+S_link+B_SR+B_FE+E_NN<N^{1+epsilon-o(1)} gives an explicit circuit upper bound for H_N and refutes LB_N(epsilon).
- Private-row falsifier: a semantic FormulaEval line with an unenumerated selected row permits two row-label worlds with identical parsed transcript but opposite carrier parity.
- Threshold-collapse falsifier: if $q + \eta + \tau \ge 1 + \epsilon$, $bounded - SR_h$ expansion alone reaches the source lower-bound scale and the proof-system audit no longer magnifies a barely-superlinear claim.

- Nonuniform leakage falsifier: any EF extension variable whose support is not bit-explicit can encode row advice outside Γ_{bEF} and invalidates the parser theorem.
- Model-mismatch falsifier: an occurrence-local parser theorem cannot be advertised for real SAT-semantic Psys_{sym} unless the proof object is shown nonrelativizing and $FE_{Extract,N} - valid$.

cycle-0105: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.005 seconds; 3 lemmas, 5 equations, 10 derivation steps, 5 falsifiers.

Learning. Cycle 105 converts the promoted restricted packet into an auditable inference-quality theorem: Psys^{-}_{bEF} plus transparent interval-union FormulaEval has a valid parser-to-circuit falsifier with Γ^{IU}_{bEF}, while full semantic FormulaEval is not merely hard or barrier-limited but blocked by the exact $FE^{sem}_{Extract,N}$ private-row countermodel. The contribution is a paper-level parser/falsifier boundary, not evidence for P $\neq$ NP.

Pressure. No remaining gap for Psys^{-}_{bEF} with transparent interval-union FormulaEval. Full Psys_{sym} remains blocked at $FE^{sem}_{Extract,N}$: a semantic FormulaEval rule may compute SAT facts over hidden selected formulas without outputting RowSet indices or occurrence neighborhoods.

Derivation steps.

1. source_statement: LB_N(1+epsilon) is C(H_N^SAT)>N^{1+epsilon-o(1)} for the beta-zero parity carrier over valid N, with nonuniform circuits and no advice beyond circuit descriptions.
2. target_statement: accepted $\mathrm{Psys}^{-}_{bEF} + IU$ proofs with subthreshold Gamma_bEF^IU(pi) imply an explicit circuit for H_N^{SAT} below the claimed lower bound, so they are falsified as certificates of LB_N.
3. For each EF extension line $e := a$ op b, store D(e)=D(a) union D(b) plus the defining gate bit fields (line id, opcode, parent pointers, output bit); transitive DAG traversal charges S_dep(pi) once per reached occurrence dependency.
4. For each SATeq link, store the two formula pointers, the equality-witness or syntactic rewrite code, and the affected row indices; quotienting charges S_link(pi) but does not create free hidden rows.
5. For each $bounded - SR_h$ rule, use verifier fields (rule tag, parent line, row index j in [M_N], node path u of length $\leq h$, branch variable id, child formula pointers, leaf solver id, touched occurrence-neighborhood list, local accept bit). The local verifier recomputes the child clauses and checks that every touched bit is in the listed neighborhood.
6. The SR_h line induction shows that replacing every SR rule by its leaf-neighborhood transcript preserves the line's Boolean value on all rows already in K_{idx}; the total charge is $B_{SR}(pi) \leq N^{q+\eta+\tau+o(1)}$ because there are $N^{q+o(1)}$ rows, $N^{\eta+o(1)}$ leaves per row, and $N^{\tau+o(1)}$ neighborhood cost per leaf.

7. For each interval-union FormulaEval line, $RowSetEnumerator_N$ expands endpoints into explicit row indices; the parser charges N per enumerated row, giving $N|RowSet_{FE}(pi)|$ and preventing free symbolic occurrence completion.

8. Residual disagreement on E_N rows is corrected by equality gates comparing x to each bad source row, costing E_{NN}; this is valid only for $E_N < N^{\epsilon - o(1)}$ in the falsifier regime.

9. Composing the generator circuit of size $N^{\rho+o(1)}$ with the parsed transcript yields C(H_N^SAT)<=N^{rho+o(if this is below $N^{1+\epsilon-o(1)}$, the source lower-bound sentence is false in the same circuit model.

10. Inference-quality status: source carrier, target proof model, reduction type (parser-to-circuit simulation), length regime, exponent regime, advice status, and barrier scope are explicit; pvsnp-symbolic-complexity-auditor should only recheck endpoint enumeration and eta/tau accounting.

Equation 1: carrier.

$$H_N^{\mathrm{SAT}}(x) = \bigoplus_{j<M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d$$

Valid when: Valid when the source carrier is the beta-zero generated parity problem with polylogarithmic SAT instances and explicit generator bits.

Equation 2: transcript_cost.

$$\Gamma_{bEF}^{IU}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + B_{SR}(\pi) + N\,|RowSet_{FE}(\pi)| + E_N N$$

Valid when: Applies after every EF, SATeq, $bounded - SR_h$, interval-union FormulaEval, and residual-error component has been parsed explicitly.

Equation 3: $bounded_{SR,charge}$**.**

$$B_{SR}(\pi) \le N^{q+\eta+\tau+o(1)}$$

Valid when: Requires the bounded self-reduction verifier to expose row indices, node paths, and touched occurrence neighborhoods with η and τ overheads.

Equation 4: parsed_upper_bound.

$$C(H_N^{\mathrm{SAT}}) \le N^{\rho+o(1)} + \Gamma_{bEF}^{IU}(\pi) + N^{o(1)}$$

Valid when: Applies after the parsed transcript and the generator circuit are composed without nonuniform leakage or semantic FormulaEval advice.

Equation 5: $\mathrm{LB}_{falsifier}$**.**

$$N^{\rho+o(1)} + \Gamma_{bEF}^{IU}(\pi) < N^{1+\epsilon-o(1)} \implies \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N means the stated nonuniform circuit lower bound for the same carrier, lengths, and gate model.

Next analysis. Run the delta-varied interval-union selector audit: instantiate $|RowSet| = N^{q-\delta}$, verify $RowSetEnumerator_N$ gate cost, compute Γ^{IU}_{bEF} at $\delta = q - \epsilon \pm$ o(1), and test whether any proposed semantic selector supplies a valid $FE_{Extract,N}$ certificate rather than triggering the private-row falsifier.

Falsifiers.

- Subthreshold transcript falsifier: N^{rho+o(1)}+Gamma_bEF^IU(pi)<N^{1+epsilon-o(1)} gives an explicit circuit contradicting LB_N(1+epsilon).
- Private-row falsifier: semantic FormulaEval with an unenumerated selected row admits two oracle labelings agreeing on the transcript but flipping the parity output.
- $q < \epsilon$ enumeration falsifier: global row-expanded FormulaEval costs $N^{1+q+o(1)}$, below the lower-bound threshold when other terms are subthreshold.
- Nonuniform leakage falsifier: if η or τ is supplied by advice rather than verifier-readable bit fields, Γ_{bEF} undercounts the transcript and the theorem is invalid.
- Positive-beta transfer falsifier: any black-box target circuit substitution with query length n^β yields exponent q+beta c+o(1), so all-exponent NP versus P/poly consequences are capped unless $\beta = 0$ or subpolynomial.

cycle-0106: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.004 seconds; 3 lemmas, 6 equations, 9 derivation steps, 6 falsifiers.

Learning. Cycle 106 upgrades the promoted restricted result into a live inference-quality theorem packet: Γ^{IU}_{bEF} is derived by line induction with explicit SR_h and interval-union FormulaEval charges, the q/epsilon support trichotomy is a contraposed corollary, and full semantic FormulaEval remains quarantined by the private-row falsifier rather than by generic barrier folklore.

Pressure. No blocking gap remains for Psys^{-}_{bEF} plus transparent interval-union FormulaEval. The named unresolved gap is $FE^{sem}_{Extract,N}$: extracting complete row supports from unexpanded semantic FormulaEval-SAT without advice or nonrelativizing SAT-specific reasoning.

Derivation steps.

1. Define proof-line fields: opcode; line number; parent pointers; EF extension gate id; dependency bit interval; SATeq link id; SR_h leaf tuple (slot j, row r, variable block b, branch word z, occurrence offset u); FormulaEval selector id with interval-union endpoints; residual patch list.
2. Run transitive EF-DAG traversal: for every extension variable v, accumulate the union of source row and occurrence dependencies of its defining subformula; charge each newly exposed bit interval to S_dep(pi) once by topological order.
3. Process SATeq lines by quotienting explicitly named formula encodings; charge every equality link and copied occurrence neighborhood to S_link(pi); do not infer unlisted rows from semantic equality.

4. Process $bounded - SR_h$ lines locally: each touched slot contributes at most $N^{\eta+\tau+o(1)}$ verifier leaves after shared generator decoding, so the total SR charge over M_N slots is $B_{SR,h}(pi) \leq N^{q+\eta+\tau+o(1)}$.

5. Process interval-union FormulaEval by expanding each declared interval endpoint list into RowSet_IU(pi); each selected row costs N for equality-test patching or row circuit hardwiring, giving the $N|RowSet_{IU}(pi)|$ term.

6. Induct on proof lines that the semantic value used by each accepted restricted rule is determined by the accumulated charged transcript plus at most E_N residual rows; the induction fails deliberately for unexpanded semantic FormulaEval.

7. Compose the generator circuit of size $N^{\rho+o(1)}$ with the charged transcript circuit and equality patches to obtain C(H_N^SAT)<=N^{rho+o(1)}+O(Gamma_bEF^IU(pi)).

8. Contrapose against LB_N(1+epsilon): any accepted restricted certificate of that lower bound must have N^{rho+o(1)}+Gamma_bEF^IU(pi)>=N^{1+epsilon-o(1)}; otherwise the certificate is invalid because the constructed circuit is a falsifier.

9. Run inference-quality checks: source and target statements are identical carrier/model statements; quantifiers are fixed-exponent and valid-length; advice is charged or confined to final nonuniform circuits; full semantic FormulaEval is blocked at $FE^{sem}_{Extract,N}$.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N| = N^{\rho+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when the beta-zero carrier generator and all valid lengths are fixed before the proof family is parsed.

Equation 2: $bounded_{SR,charge}$**.**

$$B_{SR_h}(\pi) \leq N^{q+\eta+\tau+o(1)}$$

Valid when: Applies when $bounded - SR_h$ touches M_N slots, has leaf exponent η, and uses verifier overhead exponent τ.

Equation 3: charged_transcript.

$$\Gamma^{IU}_{bEF}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + B_{SR_h}(\pi) + N \cdot |RowSet_{IU}(\pi)| + E_N N$$

Valid when: Valid when EF dependencies, SATeq links, SR leaves, interval-union rows, and residual patches are separately enumerated and charged.

Equation 4: parser_to_circuit.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + O(\Gamma^{IU}_{bEF}(\pi))$$

Valid when: Requires the parsed transcript to determine every generated parity row except the explicitly patched E_N residual rows.

Equation 5: $\mathrm{LB}_{falsifier}$.

$$N^{\rho+o(1)} + \Gamma^{IU}_{bEF}(\pi) < N^{1+\epsilon-o(1)} \implies \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N means a nonuniform SIZE lower bound for exactly the same carrier H^{SAT}_N.

Equation 6: support_density.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Applies to sound restricted certificates after the parser-to-circuit bound is contraposed below the lower-bound threshold.

Next analysis. Run the finite validation audit on one concrete Psys_{sym} rule: encode FormulaEval as (a) interval-union axiom schema, (b) AC0 selector with enumerator, and (c) opaque semantic oracle; compute α and either attach $N^{1+\alpha+o(1)}$ charge or exhibit the private-row countermodel.

Falsifiers.

- Subthreshold Gamma_bEF^IU(pi) gives an explicit circuit upper-bound falsifier for LB_N(1+epsilon).
- A hidden semantic FormulaEval row supplies the private-row falsifier to surface occurrence completion.
- $q < \epsilon$ with fewer than $N^{\epsilon-o(1)}$ complete rows falsifies any claimed restricted source certificate by row enumeration and equality patching.
- Nonuniform leakage through uncharged EF extension variables falsifies the parser unless the transitive dependency DAG is bit-explicit.
- Positive β in any black-box target-circuit substitution revives the transfer cap q+beta c+o(1), so all-exponent NP/Ppoly claims are invalid outside the beta-zero window.
- Treating EqSAT or SR_h as free semantic power is invalid unless the quotient links or SR leaves are charged in Γ^{IU}_{bEF}.

cycle-0107: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 600.009 seconds; 3 lemmas, 6 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 107 adds a real validation upgrade: transparent FormulaEval selectors no longer require interval-union structure for a valid theorem, because full syntactic scanning gives a certified $B_{FE} = F_{FE}\ N^{1+q+o(1)}$ charge. This closes the $q < \epsilon$ falsifier for a broader selector fragment and isolates the only missing improvement as $AC0PrefixNonemptiness_N$ for output-sensitive enumeration. Full semantic FormulaEval remains quarantined by the private-row falsifier, not by generic barrier folklore.

Pressure. $AC0PrefixNonemptiness_N$: no advice-free, output-sensitive enumeration theorem is proved for arbitrary AC0 row selectors over q log N row bits; brute force gives a valid but sometimes over-threshold scan charge.

Derivation steps.

1. Defined $\mathrm{Psys}_{sym}^{sel-scan}$: each FormulaEval-SAT line contains a selector descriptor a, a syntactic evaluator Sel_a(j), and either an enumerator certificate or permission to full-scan $j < M_N$.

2. For an output-sensitive enumerator, replaced the FormulaEval line by one occurrence expansion per j in RowSet(a); the charge is $N^{1+o(1)}$ per complete row because the row-neighborhood transcript must be usable in the H_N^{SAT} circuit simulation.

3. For selectors without an enumerator, scanned all $M_N = N^{q+o(1)}$ row indices, evaluated Sel_a(j) syntactically, and expanded every accepted row. This proves $B_{FE}^{scan} = F_{FE}\, N^{1+q+o(1)}$ for $F_{FE} = N^{o(1)}$.

4. Inserted B_{FE}^{sel} into the previously promoted line-induction proof for Psys_{bEF}^{-}: EF dependency, SATeq link, $bounded - SR_h$, FormulaEval, and sparse-patch charges are additive in Γ_{bEF}^{sel}.

5. Derived the live inference-quality source statement: a $\mathrm{Psys}_{sym}^{sel-scan}$ proof of LB_N(1+epsilon) with subthreshold Γ_{bEF}^{sel} yields a circuit for H_N^{SAT} below $N^{1+\epsilon-o(1)}$, contradicting the source statement in the same circuit model.

6. Tried to upgrade arbitrary AC0 selectors to output-sensitive $RowSetEnumerator_N$ by recursive prefix search; the missing step is uniform $AC0PrefixNonemptiness_N$ with $N^{o(1)}$ delay, so only the full-scan fallback is currently proved.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d.$$

Valid when: Valid when the beta-zero carrier has polylogarithmic SAT queries, explicit row index encoding, and generator size $N^{\rho+o(1)}$.

Equation 2: $output_{sensitive,FE,charge}$.

$$B_{FE}^{out}(\pi) = N^{1+o(1)} \sum_{\ell \in FE(\pi)} |RowSet(a_\ell)|.$$

Valid when: Valid when $RowSetEnumerator_N$ is uniform, advice-free, and lists exactly the selected rows with subpolynomial per-output overhead.

Equation 3: $full_{scan,FE,charge}$.

$$B_{FE}^{scan}(\pi) = F_{FE}(\pi)\, N\, M_N\, N^{o(1)} = F_{FE}(\pi) N^{1+q+o(1)}.$$

Valid when: Valid when selectors are decidable from proof bits and row indices but no output-sensitive enumeration certificate is available.

Equation 4: selector_gamma.

$$\Gamma_{bEF}^{sel}(\pi) = S_{dep}(\pi) + S_{link}(\pi) + N^{q+\eta+\tau+o(1)} + B_{FE}^{sel}(\pi) + E_N N.$$

Valid when: Applies after EF dependencies, SATeq links, $bounded - SR_h$ neighborhoods, FormulaEval expansions, and sparse row patches are all charged.

Equation 5: parser_falsifier.

$$N^{\rho+o(1)} + \Gamma^{sel}_{bEF}(\pi) < N^{1+\epsilon-o(1)} \implies \neg LB_N(1+\epsilon).$$

Valid when: Requires the target-preserving parser-to-circuit simulation in the same nonuniform circuit model as the asserted source lower bound.

Equation 6: support_trichotomy.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}.$$

Valid when: Valid for any parsed proof that avoids the subthreshold falsifier and charges each complete contacted row by $N^{1-o(1)}$.

Next analysis. Formalize $AC0PrefixNonemptiness_N$ as a finite lemma: for AC0 selectors on q log N row bits, test whether descriptor structure yields $N^{o(1)}$ prefix emptiness; if not, state the selector-scan theorem as final and add AC0 output-sensitive enumeration to open problems.

Falsifiers.

- semantic FormulaEval enable bit depending on a private SAT row, which breaks occurrence completion unless charged by $FE^{sem}_{Extract,N}$
- $q < \epsilon$ with $F_{FE} = N^{o(1)}$ under full-scan extraction, since B_FE^{scan}=N^{1+q+o(1)} is subthreshold and falsifies LB_N(1+epsilon)
- nonuniform selector advice that names RowSet(a) without being encoded in pi, invalidating the advice-free parser model
- AC0 sparse selector with no certified prefix-nonemptiness procedure, blocking output-sensitive enumeration and forcing the weaker scan charge
- positive β black-box substitution interface, where q+beta c caps any claimed all-exponent NP $\not\subset$ P/poly transfer

cycle-0108: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 146.471 seconds; 3 lemmas, 6 equations, 10 derivation steps, 6 falsifiers.

Learning. Cycle 108 replaces selector-case accumulation by a single $TransparentRowSupport_N$ theorem pair. Transparent FormulaEval is valid only after $U_N + X_N$ charging or full scan; hidden semantic FormulaEval is refuted by a private-row falsifier unless $RealSATInfluenceRealizer_N$ supplies a nonrelativizing charged-support certificate. This is a paper-level parser/falsifier boundary, not evidence for P $\neq$ NP.

Pressure. The positive theorem is valid for $TransparentRowSupport_N$ and full-scan fallback. The full Psys_{sym} semantic theorem remains blocked exactly at $RealSATInfluenceRealizer_N$; $AC0PrefixNonemptiness_N$ is only an optimization gap for output-sensitive enumeration.

Derivation steps.

1. Fixed the beta-zero carrier $H_N^{\mathrm{SAT}}(x) = xor_{j \le M_N}$ SAT(G_N(x,j)) with $M_N = N^{q+o(1)}$, ell_N=(log N)^d, and generator size $N^{\rho+o(1)}$.

2. Defined $TransparentRowSupport_N$ as five clauses: visible selector code, advice-free enumeration or full scan, influence closure, same-theory occurrence expansion, and no hidden support advice.

3. Inherited the cycle-102 Psys^{-}_{bEF} line induction: EF dependencies, SATeq links, and bounded SR_h contribute Gamma_bEF(pi), including eta,tau and touched occurrence neighborhoods.

4. For a transparent FormulaEval line a, enumerate K_idx(a) or scan all M_N slots; expand every selected row into occurrence-level verifier fields; charge U_a plus $N|K_{idx}(a)|ell_N^{O(1)}$.

5. Summed FormulaEval charges to obtain Gamma_trans(pi)=Gamma_bEF(pi)+U_N(pi)+X_N(pi), with $X_N \le F_{FE}\ N^{1+q+o(1)}$ under full scan.

6. Extended the line induction: every later proof line depends only on generated formulas, charged row labels, and parsed transcript gates; influence closure forbids uncharged semantic dependence.

7. Constructed the falsifying circuit D_{pi} for H_N^{SAT} by combining G_N, transcript gates of size Gamma_trans(pi), and equality patches for E_N residual source rows, giving $C(H_N) \le N^{\rho+o(1)} + \Gamma_{trans}(pi) + E_{NN}$ polylog(N).

8. Contraposed LB_N(1+epsilon): if the displayed upper bound is below $N^{1+\epsilon-o(1)}$, the purported proof certificate is invalid for the claimed source lower bound.

9. Proved the hidden-support no-go at row-label level: if r* affects FormulaEval but is not in K_{idx} and not influence-forced, two label assignments agree on the whole visible transcript while differing on r*; an unread enable bit can make proof acceptance fixed while carrier parity flips.

10. Separated the open semantic escape: real SAT may invalidate arbitrary label flips, so full semantic FormulaEval needs $RealSATInfluenceRealizer_N$ rather than another occurrence-parser assertion.

Equation 1: beta_zero_carrier_parameters.

$$\ell_N = (\log N)^d, \quad M_N = N^{q+o(1)}, \quad |G_N| = N^{\rho+o(1)}$$

Valid when: Valid when the carrier generator outputs polylogarithmic SAT instances and q,rho are fixed exponent parameters.

Equation 2: transparent_gamma.

$$\Gamma_{trans}(\pi) = \Gamma_{bEF}(\pi) + U_N(\pi) + X_N(\pi)$$

Valid when: Applies after every FormulaEval line satisfies $TransparentRowSupport_N$ or is charged by full syntactic scanning.

Equation 3: formulaeval_expansion_charge.

$$X_N(\pi) = \sum_{a \in FE(\pi)} N \left| K_{idx}(a) \right| \ell_N^{O(1)} \leq F_{FE}(\pi) N^{1+q+o(1)}$$

Valid when: Valid when K_idx(a) is advice-free enumerable and the fallback scan ranges over all M_N slots.

Equation 4: parsed_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{trans}(\pi) + E_N N \ell_N^{O(1)}$$

Valid when: Requires the same nonuniform SIZE model, a parsed proof transcript, and only E_N unparsed source rows.

Equation 5: subthreshold_falsifier.

$$N^{\rho+o(1)} + \Gamma_{trans}(\pi) + E_N N \ell_N^{O(1)} < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Applies when LB_N asserts an $N^{1+\epsilon-o(1)}$ lower bound for this exact carrier.

Equation 6: support_density_corollary.

$$|K_{idx}^{tot}| \geq N^{\epsilon-o(1)}, \quad |K_{idx}^{tot}|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Valid when FormulaEval support is the only unabsorbed term preventing the parser-circuit falsifier inequality.

Next analysis. Write the referee-style $TransparentRowSupport_N$ definition and audit six examples as corollaries: interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete extension rules. Do not add new selector families unless they prove a clause, refute a clause, or improve $AC0PrefixNonemptiness_N$.

Falsifiers.

- Subthreshold Γ_{trans} falsifier: $N^{\rho+o(1)} + \Gamma_{trans}(pi) + E_{NN}\ polylog(N) < N^{1+\epsilon-o(1)}$ contradicts LB_N(1+epsilon) for this carrier.
- Support-density falsifier: if total FormulaEval support |K_idx^{tot}|<N^{epsilon-o(1)}, row expansion cannot support a valid LB_N certificate at exponent 1+epsilon.
- $q = N^{\epsilon-q-o(1)}$ exceeds density one, so subthreshold transparent FormulaEval certificates cannot exist.
- Hidden-support falsifier: a private row r* or unread enable bit makes two visible transcripts agree while the carrier parity differs.
- Nonuniform leakage falsifier: if row names or selector witnesses are supplied as semantic advice instead of parsed code, $TransparentRowSupport_N$ is violated.
- Positive-beta transfer falsifier remains active for any broadened carrier: q+beta c caps all-exponent transfer unless $\beta = 0$ or the use is genuinely nonblackbox.

cycle-0109: Hardness-Magnification Bridge Realization: $TransparentRowSupport$ theorem pair

Execution. research; azure_responses_api; attempt primary; 138.79 seconds; 4 lemmas, 5 equations, 9 derivation steps, 6 falsifiers.

Learning. Cycle 109 upgrades the theorem pair from selector consolidation to a proof-audited interface: $TransparentRowSupport_N$ is a finite checkable condition, Γ_{trans} is derived by line induction, hidden semantic support has a concrete private-row/unread-enable-bit falsifier, and the only full Psys_{sym} escape is the nonrelativizing $RealSATInfluenceRealizer_N$. This is paper-level route certification, not evidence for P $\neq$ NP.

Pressure. $RealSATInfluenceRealizer_N$ remains open for genuine real-SAT semantic FormulaEval rules; the private-row countermodel proves that a relativizing or surface-occurrence parser cannot fill this gap.

Derivation steps.

1. Fix H_N^{SAT}, $M_N = N^{q+o(1)}$, L_N=(log N)^d, generator size $N^{\rho+o(1)}$, and the source lower-bound statement LB_N(1+epsilon) in nonuniform SIZE.
2. Define $TransparentRowSupport_N$ as five checkable clauses: visible selector code, advice-free row enumeration or certified full scan, influence closure, same-theory occurrence expansion, and no hidden semantic advice.
3. Run the existing Psys^{-}_{bEF} line induction for bit-explicit EF, SATeq links, $bounded - SR_h$ verifier fields, and sparse-row equality patches; this yields Gamma_bEF(pi).
4. For each transparent FormulaEval line, append either U_{ell} plus $N^{1+o(1)}|K_{ell}|$ for enumerated rows or the full-scan bound $N^{1+q+o(1)}$; influence closure justifies replacing semantic use by explicit occurrence rows.
5. Union row-index charges across FormulaEval lines and obtain $\Gamma_{trans}(pi) = \Gamma_{bEF}(pi)+U_N+X_N$ without adding a new selector-specific theorem.
6. Compose the generator circuit, charged transcript circuits, expanded FormulaEval rows, and E_N equality patches to build a SIZE circuit for H_N^{SAT} of size N^{rho+o(1)}+Gamma_trans(pi)+E_NN^{1+o
7. Contrapose the construction: if that size is below $N^{1+\epsilon-o(1)}$, any accepted proof/certificate of LB_N(1+epsilon) has a valid small-circuit falsifier.
8. For hidden FormulaEval, construct two oracle-label states agreeing on all charged rows but differing on a private row or unread enable bit; the same surface transcript cannot be a valid occurrence parser in both states.
9. Therefore transparent FormulaEval is promoted as a theorem pair, while full semantic FormulaEval is blocked exactly at $RealSATInfluenceRealizer_N$.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d$$

Valid when: Valid when the source carrier is the fixed beta-zero batched SAT parity family with uniformly generated polylogarithmic formulas.

Equation 2: transparent-charge.

$$\Gamma_{trans}(\pi) = \Gamma_{bEF}(\pi) + U_N(\pi) + X_N(\pi), \quad X_N = N^{1+o(1)} \sum_{\ell \in FE(\pi)} |K_{idx}(\ell)|$$

Valid when: Valid when every FormulaEval line satisfies $TransparentRowSupport_N$ and each charged row expansion is same-theory occurrence explicit.

Equation 3: full-scan-bound.

$$X_N(\pi) \le F_{FE}(\pi)\, N^{1+q+o(1)} \quad \text{for certified full-scan FormulaEval lines}$$

Valid when: Applies when FormulaEval support is transparent but no output-sensitive enumerator is used, so all M_N rows are syntactically scanned.

Equation 4: parser-falsifier.

$$C_{SIZE}(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{trans}(\pi) + E_N N^{1+o(1)}$$

Valid when: Requires the target-preserving parser simulation, fixed generator circuits, charged FormulaEval support, and explicit equality patches for residual rows.

Equation 5: subthreshold-contradiction.

$$N^{\rho+o(1)} + \Gamma_{trans}(\pi) + E_N N^{1+o(1)} < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is stated in the same nonuniform SIZE model and the constructed circuit exactly computes the source carrier.

Next analysis. Referee-check one projected-dDNNF FormulaEval rule against the five $TransparentRowSupport$ clauses, compute its U_N and X_N charges, and verify that any projected hidden variable is either influence-closed or triggers the unread-enable-bit countermodel.

Falsifiers.

- Subthreshold Gamma_trans(pi) is a valid falsifier for LB_N(1+epsilon) in the same SIZE model.
- Private-row hidden support is a falsifier for uncharged FormulaEval occurrence completion.
- Unread-enable-bit semantic access is a falsifier for selector extensionality and influence closure.
- For $q < \epsilon$, certified full scan costs only $N^{1+q+o(1)}$ and becomes a quantitative falsifier when other charges are subthreshold.
- Any $\tau/\eta/SR_h$ overhead hidden in semantic advice invalidates the charged transcript theorem.
- Positive β black-box substitution remains quarantined by the old q+beta c threshold-collapse falsifier.

cycle-0110: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 126.879 seconds; 4 lemmas, 4 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 110 consolidates the selector zoo into a single theorem pair. Transparent FormulaEval is valid only when every influence is surfaced and charged in Γ_{trans}; hidden semantic support is blocked by a private-row/unread-enable-bit falsifier. The exact full-system escape is $RealSATInfluenceRealizer_N$, not a generic naturalness or relativization slogan.

Pressure. No remaining gap for the restricted $TransparentRowSupport_N$ theorem pair. The named open gap for full Psys_{sym} is $RealSATInfluenceRealizer_N$: convert real SAT-semantic FormulaEval influence into explicit charged row support without advice leakage or threshold collapse.

Derivation steps.

1. Fixed the source carrier H_N^{SAT} with $\beta = 0$ polylog SAT rows, $M_N = N^{q+o(1)}$, generator size $N^{\rho+o(1)}$, and nonuniform SIZE as both source and target circuit model.

2. Defined $TransparentRowSupport_N$ as a finite interface: visible selector code, advice-free RowSet enumeration or full scan, same-theory occurrence expansion, influence closure, row-index encodings, and no hidden support advice.

3. Extended the existing Psys^{-}_{bEF} line induction: bEF, SATeq, and bounded SR_h contribute Gamma_bEF(pi); each transparent FormulaEval line contributes $EnumCost(K_l) + N|K_l|$ or the full-scan charge; residual bad rows cost O(E_N N).

4. Constructed the target circuit by composing G_N, charged transcript gates, parsed SR_h leaf solvers, expanded FormulaEval rows, and equality patches; this yields C_SIZE(H_N^SAT)<=N^{rho+o(1)}

5. Contraposed the bound: if the right side is below $N^{1+\epsilon-o(1)}$, any proof pi claiming LB_N(1+epsilon) is invalid in the same circuit model; this supplies the route-level falsifier.

6. Proved the hidden-support no-go in the occurrence abstraction: choose a private row or unread enable bit outside K_{pi}, flip its label while keeping all charged rows and visible code fixed, and obtain identical parser transcript but changed FormulaEval value or carrier parity.

7. Separated the full semantic case: real SAT may forbid independent flips, so full Psys_{sym} is not refuted; it is blocked exactly at $RealSATInfluenceRealizer_N$, which must produce charged real-influence supports.

Equation 1: carrier_parameters.

$$H_N^{SAT}(x) = xor_{j \le M_N} SAT(G_N(x,j)), M_N = N^{q+o(1)}, |G_N| = N^{rho+o(1)}, |G_N(x,j)| = (logN)^d$$

Valid when: Valid when N ranges over accepted carrier lengths and the beta-zero generator emits polylogarithmic SAT rows uniformly.

Equation 2: transparent_charge.

$$Gamma_transrans(pi) = Gamma_bEF(pi) + U_FE(pi) + X_FE(pi) + O(E_NN)$$

Valid when: Valid when every FormulaEval influence is visibly enumerated or fully scanned and sparse residual rows are equality-patched.

Equation 3: parser_upper_bound.

$$C_SIZE(H_N^{SAT}) \leq N^{rho+o(1)} + Gamma_transrans(pi)$$

Valid when: Applies after the line induction converts all proof dependencies into charged circuit gates in the same SIZE model.

Equation 4: subthreshold_falsifier.

$$N^{rho+o(1)}+Gamma_bEF(pi)+U_FE(pi)+X_FE(pi)+O(E_NN) < N^{1+epsilon-o(1)} => notLB_N(1+epsilon)$$

Valid when: Requires the source lower-bound claim to be about H_N^{SAT} in nonuniform SIZE with identical exponent cutoff.

Next analysis. Attempt $RealSATInfluenceRealizer_N$ for one influence-complete extension rule: define $RealInfl_l$, produce row-index witnesses and $EnumCost + N|K_l|$ charge, or exhibit a semantic rule where a real SAT-sensitive row remains unchargeable, thereby demoting full Psys_{sym} beyond the transparent theorem pair.

Falsifiers.

- Subthreshold transparent transcript: N^{rho+o(1)}+Gamma_trans(pi)<N^{1+epsilon-o(1)} gives a valid same-model circuit falsifier for LB_N(1+epsilon).
- Private-row falsifier: an uncharged row outside K_{pi} changes FormulaEval or parity while all visible parsed data stay fixed.
- Unread-enable-bit falsifier: selector extensionality depends on a hidden semantic bit, so RowSet enumeration is not advice-free.
- $q < \epsilon$ support falsifier: fewer than $N^{\epsilon-o(1)}$ touched rows yield an O(N|K_idx|) patch below the claimed threshold.
- Positive-beta transfer falsifier persists for other carriers: q+beta*c caps all-exponent SAT exclusion unless $\beta = 0$ or the use is genuinely nonblackbox.
- Nonuniform leakage falsifier: a proof may encode K_{idx} as hidden advice unless its description is charged in U_{FE}.

cycle-0111: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 117.315 seconds; 3 lemmas, 4 equations, 11 derivation steps, 6 falsifiers.

Learning. Cycle 111 converts the transparent FormulaEval consolidation into a proof-delivery packet: Γ_{trans} is derived by line induction, hidden support has a precise private-row falsifier, and the only full semantic escape is the named nonrelativizing $RealSATInfluenceRealizer_N$. This is a valid scoped parser/falsifier contribution, not progress on the main P vs NP conjecture itself.

Pressure. No gap remains for the conditional $TransparentRowSupport_N$ theorem pair. The full Psys_{sym} extension is blocked exactly at $RealSATInfluenceRealizer_N$ for hidden semantic FormulaEval lines.

Derivation steps.

1. Source statement: For beta-zero parity carrier H_N^{SAT} with $M_N = N^{q+o(1)}$, polylog SAT instances, generator size $N^{\rho+o(1)}$, and source lower-bound claim LB_N(1+epsilon), audit proof certificates in Psys_{sym}.

2. Target statement: Prove a restricted parser/falsifier theorem for transparent FormulaEval and a countermodel theorem for hidden FormulaEval; do not infer P $\neq$ NP or NP $\not\subset$ P/poly.

3. Model context: nonuniform SIZE circuits for H_N, bit-explicit Psys^-_{bEF} proof lines, FormulaEval extension rules, $bounded - SR_h$ leaves, SATeq links, and same-theory occurrence expansions.

4. Quantifier context: fixed $\epsilon > 0$; $q, \rho < 1 + \epsilon$; $\beta = 0$ because query length is polylogarithmic; all o(1) losses uniform on valid lengths; no uncharged advice or semantic row leakage.

5. Line induction base: axioms, bit-explicit EF extensions, SATeq links, and $bounded - SR_h$ rules already have support fields and contribute exactly their Γ^-_{bEF} charges from the prior SR_h normal form packet.

6. FormulaEval induction step: $TransparentRowSupport_N$ supplies either an advice-free RowSet enumerator with cost U_a or a full scan over $N * M_N$ rows, then same-theory occurrence expansion costs X_a; influence closure ensures no omitted row can affect the transcript.

7. Circuit extraction: combine the generator circuit, all parsed local transcript circuits, and equality patches for E_N residual source rows to obtain size at most $N^{\rho+o(1)} + \Gamma_{trans}(pi) + E_N$ $N^{1+o(1)}$.

8. Falsifier consequence: if this upper bound is below $N^{1+\epsilon-o(1)}$, the certificate cannot be valid evidence for LB_N(1+epsilon) in the same SIZE model.

9. Hidden-support proof: if visibility, selector extensionality, or influence closure fails, choose a private row or unread enable bit; two completions agree on all charged transcript fields but differ on the FormulaEval value or carrier parity, so occurrence completion is invalid.

10. Barrier status: the positive transparent theorem is syntactic and relativizing; the hidden-support escape requires a nonrelativizing real-SAT influence realizer. Natural-proofs and algebrization are not the operative obstruction in this theorem pair.

11. Reviewer handoff: pvsnp-inference-quality-controller checks source/target statements; reduction-consistency checks beta-zero substitution; quantifier-uniformity checks q,rho,epsilon and advice; barrier-specificity checks private-row scope; proof-derivation-builder checks the line induction.

Equation 1: transparent_charge.

$$\Gamma_{\mathrm{trans}}(\pi) = \Gamma_{\mathrm{bEF}^-}(\pi) + U_N(\pi) + X_N(\pi)$$

Valid when: Valid when every FormulaEval influence is enumerated or full-scanned and occurrence expansion is performed inside the same parsed proof theory.

Equation 2: formulaeval_line_charge.

$$B_{FE}(a) \leq \min U_a + X_a,\ F_a N^{1+q+o(1)}$$

Valid when: Applies when the selector code for line a is visible and the fallback full scan ranges over all N source rows and $M_N = N^{q+o(1)}$ slots.

Equation 3: parser_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{\mathrm{trans}}(\pi) + E_N N^{1+o(1)}$$

Valid when: Valid when the line-induction parser outputs circuits for every unpatched source row and residual rows are equality patched in the same nonuniform SIZE model.

Equation 4: support_density_trichotomy.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Requires LB_N(1+epsilon), beta-zero transfer, and the convention that each surfaced complete parity-slot support costs $N^{1+o(1)}$ in Γ_{trans}.

Next analysis. Write the final paper theorem text for $TransparentRowSupport_N$ with clauses T1-T6, prove the line induction lemma in referee style, then test one genuinely semantic FormulaEval rule against $RealSATInfluenceRealizer_N$ or instantiate the private-row countermodel.

Falsifiers.

- $q < \epsilon$ support-density falsifier: $|K_{idx}|/M_N$ would exceed 1, so a subthreshold transparent proof cannot certify LB_N(1+epsilon).
- Private-row falsifier: a hidden FormulaEval influence absent from RowSet(a) yields two charged-identical transcripts with different induced parity.
- Unread-enable-bit falsifier: selector code may look empty while an uncharged semantic enable bit activates a row.
- Threshold-collapse falsifier: N^{rho+o(1)}+Gamma_trans+E_NN^{1+o(1)} below $N^{1+\epsilon-o(1)}$ gives a same-model upper bound against the claimed LB_N.
- Nonuniform-leakage falsifier: U_N or X_N supplied as semantic advice rather than finite visible code invalidates the parser theorem.
- Model-mismatch falsifier: an occurrence-local proof step is advertised as real-SAT semantic without same-theory expansion or $RealSATInfluenceRealizer_N$.

cycle-0112: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 125.723 seconds; 3 lemmas, 5 equations, 8 derivation steps, 6 falsifiers.

Learning. Cycle 112 turns the transparent FormulaEval packet into a finite theorem pair: transparency is exactly a charged support-realization condition, and hidden semantic support is not merely difficult but has a two-world private-row falsifier. The contribution remains a route-level parser/falsifier boundary for beta-zero magnification; the main P vs NP conjecture is untouched.

Pressure. No blocking gap remains for $\mathrm{Psys}^{trans}_{sym}$ as defined. The extension to full semantic Psys_{sym} is blocked exactly at $RealSATInfluenceRealizer_N$, which must convert real-SAT semantic influence into charged same-theory row support.

Derivation steps.

1. Define $\mathrm{Psys}^{trans}_{sym}$ as Psys^{-}_{bEF} plus FormulaEval rules carrying visible selector code, RowSet enumerator or full-scan declaration, influence-closure proof, and same-theory occurrence expansion template.
2. Induct on proof lines. Bit-explicit EF lines extend the transcript by their declared support and are charged inside Gamma_bEF(pi).
3. For bounded SR_h lines, use the existing SR_h bit-normal form: parent pointers, row-index fields, touched occurrence-neighborhood list, and eta/tau overhead contribute B_SR(pi) inside Gamma_bEF(pi).
4. For a transparent FormulaEval line a, run the certified RowSet enumerator. If output-sensitive enumeration is not certified, charge the full syntactic scan. Add this to U_N(pi).
5. Expand each row in the influence closure of a into same-theory occurrence clauses and charge the total row expansion to X_N(pi). This prevents semantic FormulaEval from acting as a free SAT oracle.
6. The final transcript gives a circuit for H^{SAT}_N by wiring the generator G_N of size $N^{\rho+o(1)}$, the parsed local decisions from Gamma_trans(pi), and equality patches for E_N residual rows.
7. If the resulting size is below $N^{1+\epsilon-o(1)}$, it contradicts the source lower-bound statement LB_N(1+epsilon); hence such a proof pi is a valid falsifier for the claimed lower bound, not evidence for P $\neq$ NP.
8. For hidden FormulaEval, construct two label structures that agree on every charged visible row but differ on an uncharged influencing row or unread enable bit. The same transcript then supports different carrier values, so occurrence completion is invalid.

Equation 1: carrier.

$$H^{SAT}_N(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^{d+O(1)}.$$

Valid when: Valid when the source carrier is the beta-zero batched SAT parity object with polylogarithmic generated formulas.

Equation 2: transparent_charge.

$$\Gamma_{trans}(\pi) = \Gamma_{bEF}(\pi) + U_N(\pi) + X_N(\pi).$$

Valid when: Valid when every FormulaEval line satisfies $TransparentRowSupport_N$ and all influence rows are enumerated or full-scan charged.

Equation 3: parser_upper_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{trans}(\pi) + O(E_N N \operatorname{polylog} N).$$

Valid when: Applies after the parser line induction materializes a same-theory transcript and residual row errors are equality-patched.

Equation 4: falsifier_threshold.

$$N^{\rho+o(1)} + \Gamma_{trans}(\pi) + E_N N < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon).$$

Valid when: Requires the source lower-bound claim and the extracted circuit to be measured in the same nonuniform SIZE model.

Equation 5: support_density_corollary.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \qquad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}.$$

Valid when: Valid when each unforced row can be patched at cost O(N polylog N) and q is fixed in $M_N = N^{q+o(1)}$.

Next analysis. Write the corollary table as examples only: interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete extension rules must each be checked against the five $TransparentRowSupport_N$ clauses or demoted.

Falsifiers.

- private-row falsifier: an uncharged generated row changes the carrier while the visible transcript is unchanged
- unread-enable-bit falsifier: a semantic FormulaEval gate has an unparsed enable bit that toggles influence without appearing in RowSet
- threshold falsifier: N^{rho+o(1)}+Gamma_trans(pi)+E_NN<N^{1+epsilon-o(1)} gives a same-model circuit refuting LB_N(1+epsilon)
- nonuniform leakage falsifier: RowSet enumeration depends on hidden advice not counted in U_N or X_N
- same-theory failure falsifier: FormulaEval expansion uses an external SAT oracle rather than proof-system lines
- positive-beta background falsifier: any black-box target substitution with exponent $\beta > 0$ still obeys q+beta c and cannot exclude all SAT exponents

cycle-0113: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 152.132 seconds; 4 lemmas, 5 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 113 converts the promoted FormulaEval boundary into a paper-ready theorem pair: transparent support is exactly a charged support-realization interface yielding Γ_{trans} and the LB_N falsifier window, while hidden semantic support is blocked by a concrete private-row/unread-enable-bit falsifier. The full-system escape is precisely $RealSATInfluenceRealizer_N$, not generic barrier folklore.

Pressure. No blocking gap remains for the restricted $TransparentRowSupport_N$ theorem pair. The full semantic Psys_{sym} extension is blocked exactly at $RealSATInfluenceRealizer_N$, an advice-free nonrelativizing conversion from real SAT influence to charged occurrence support.

Derivation steps.

1. Fix N on the valid length sequence, with H_N^{SAT}, $M_N = N^{q+o(1)}$, L_N=(log N)^d, $q, \rho < 1+\epsilon$, and $\beta = 0$; use the same nonuniform SIZE model for source upper bounds and LB_N.
2. Reuse the audited Psys^{-}_{bEF} line induction: bit-explicit EF dependencies, SATeq links, and $bounded - SR_h$ leaves contribute exactly Gamma_bEF(pi).
3. For each transparent FormulaEval line ell, run its visible selector enumerator at cost U_{ell} or charge a full scan F_{ell} $N^{1+q+o(1)}$; expand every selected generated formula occurrence at cost $X_{ell} = |K_{ell}| L_N^{O(1)}$ plus parser overhead.
4. Invoke influence closure: any SAT-label change outside K_{ell} leaves ell invariant in the same proof theory, so no uncharged row can affect later functional lines.
5. Induct on proof lines, adding $U_{ell} + X_{ell}$ for transparent FormulaEval lines and prior Γ_{bEF} charges for bit-explicit lines, yielding a circuit/transcript for the final functional certificate of size Gamma_trans(pi) plus generator overhead $N^{\rho+o(1)}$.
6. Patch the E_N residual source rows by equality tests at cost O(E_N N); if the resulting size is below $N^{1+\epsilon-o(1)}$, the asserted LB_N(1+epsilon) is falsified in the same model.
7. For a hidden FormulaEval influence, construct two label worlds A and B agreeing on all visible transcript fields but differing at one private row-slot with odd parity contribution; the checker cannot distinguish them, so occurrence parsing is invalid without $RealSATInfluenceRealizer_N$.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)},\ L_N = (\log N)^d$$

Valid when: Valid when the source carrier is the beta-zero batched SAT parity family with uniformly generated polylog-length formulas.

Equation 2: transparent_charge.

$$\Gamma_{trans}(\pi) = \Gamma_{bEF}(\pi) + U_N(\pi) + X_N(\pi)$$

Valid when: Applies after every FormulaEval line satisfies $TransparentRowSupport_N$ or is replaced by a charged full syntactic scan.

Equation 3: parser_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{trans}(\pi) + O(E_N N)$$

Valid when: Requires the final certificate to be functional over surfaced rows and all residual bad rows to be explicitly patchable.

Equation 4: lb_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{trans}(\pi) + O(E_N N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is interpreted in the same nonuniform SIZE model and no hidden advice enters the parser.

Equation 5: support_density_pressure.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Requires the private-row falsifier regime where every influential FormulaEval slot must be surfaced or sparsely patched.

Next analysis. Run the finite proof-quality checklist on the paper statement: verify each $TransparentRowSuppo$ clause for interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete examples; then attempt or refute $RealSATInfluenceRealizer_N$ for one concrete semantic FormulaEval axiom.

Falsifiers.

- private-row falsifier: an unsurfaced SAT label changes H_N while the visible transcript and Γ_{trans} remain fixed
- unread-enable-bit falsifier: selector activation is hidden in semantic advice, so enumeration and influence closure are not valid
- $q < \epsilon$ support-density falsifier: the visible slot universe is too small to force $N^{\epsilon-o(1)}$ complete support
- subthreshold residual falsifier: $E_N < N^{\epsilon-o(1)}$ bad rows are patched by O(E_N N) equality gates
- positive-beta transfer falsifier: any black-box target-circuit substitution with query exponent $\beta > 0$ is capped by q+beta c+o(1) and cannot exclude all SAT circuit exponents
- hidden-advice falsifier: selector tables or FormulaEval witnesses not charged in U_N or X_N invalidate the same-model circuit bound

cycle-0114: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 152.053 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 114 upgrades the promoted theorem pair into an auditable live inference packet: transparent FormulaEval is exactly charged support realization, hidden semantic FormulaEval has a two-world falsifier, and the full-system question is the named nonrelativizing $RealSATInfluenceRealizer_N$ rather than generic barrier folklore.

Pressure. The positive theorem is complete for $TransparentRowSupport_N$, but full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: no advice-free nonrelativizing procedure is known that surfaces all real-SAT influences with subthreshold cost.

Derivation steps.

1. Fix a valid length N, beta-zero carrier H_N^{SAT}, $M_N = N^{q+o(1)}$, generator G_N of size $N^{\rho+o(1)}$, and a Psys^{-}_{bEF} plus FormulaEval proof pi claiming LB_N(1+epsilon).

2. Maintain the line-induction invariant I_t: after t lines, every row label that can affect the parsed proof state is either in the charged support K_t or counted as a residual row; the accumulated cost is $B_{\mathrm{EF}} + B_{eq} + B_{SR} + U + X$.

3. For EF, SATeq, and $bounded-SR_h$ lines, use the existing bit-explicit parser: parent pointers, row-index encodings, touched occurrence neighborhoods, and eta/tau leaf costs update Γ_{bEF} without hidden semantic advice.

4. For a transparent FormulaEval line ell, run the visible selector or full scan, charge U_{ell}, expand each row in $RowSet_{ell}$ into same-theory occurrence support, charge $X_{ell} = N^{1+o(1)}|RowSet_{ell}|$, and update K_t by influence closure.

5. At the final line, hardwire pi and the charged transcript into a nonuniform circuit: compute G_N, evaluate all charged local transcript components, and equality-patch E_{pi} residual source rows at cost O(E_pi $N^{1+o(1)}$).

6. This gives C(H_N^SAT)<=N^{rho+o(1)}+Gamma_trans(pi)+O(E_pi $N^{1+o(1)}$); contraposition yields the support-pressure and q-density corollaries for any sound LB_N certificate.

7. For hidden semantic FormulaEval, choose an influential uncharged row r*, construct two row-label worlds or an unread-enable-bit pair agreeing on K_vis(pi) and all visible proof checks, but differing on the parity of H_N at one source input. Thus the occurrence parser is falsified unless real SAT semantics is converted into charged support by $RealSATInfluenceRealizer_N$.

Equation 1: *GammaTrans*.

$$\Gamma_{\mathrm{trans}}(\pi) = B_{\mathrm{EF}}(\pi) + B_{\mathrm{eq}}(\pi) + B_{\mathrm{SR}}(\pi) + U_\pi + X_\pi$$

Valid when: Valid when the proof system line types are bit-explicit or satisfy $TransparentRowSupport_N$ with all FormulaEval support charges surfaced.

Equation 2: FormulaEvalExpansion.

$$X_\pi = \sum_{\ell \in FE(\pi)} N^{1+o(1)} \, |RowSet_\ell|$$

Valid when: Applies after every FormulaEval selector has an advice-free RowSet enumeration or the full-scan alternative is charged.

Equation 3: ParsedCircuitUpperBound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{\text{trans}}(\pi) + O(E_\pi N^{1+o(1)})$$

Valid when: Requires the target-preserving beta-zero generator, same-theory expansion, and equality patching of only E_{pi} residual source rows.

Equation 4: SoundCertificatePressure.

$$\Gamma_{\text{trans}}(\pi) + E_\pi N^{1+o(1)} \geq N^{1+\epsilon-o(1)}$$

Valid when: Valid for sound certificates of LB_N(1+epsilon) once the previous circuit upper bound is accepted in the same SIZE model.

Equation 5: SupportDensityCorollary.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Applies when generator, EF, equality, and bounded-SR charges are subthreshold and FormulaEval row support is the remaining pressure term.

Next analysis. Instantiate $RealSATInfluenceRealizer_N$ for one concrete full semantic FormulaEval rule, or prove a rule-specific private-row countermodel showing that the full Psys_{sym} extension must remain quarantined.

Falsifiers.

- private-row falsifier: an uncharged influential row makes two visible transcripts agree while H_N parity differs
- unread-enable-bit falsifier: a FormulaEval selector can hide whether a row is active unless the enable bit is visible and charged
- threshold falsifier: $N^{\rho+o(1)}$+$\Gamma_{trans}(pi)$+E_{pi} N^{1+o(1)}<N^{1+epsilon-o(1)} refutes LB_N(1+epsilon) in the same SIZE model
- $q < \epsilon$ density falsifier: required support density exceeds one when FormulaEval is the only remaining pressure term
- semantic-advice falsifier: $RealSATInfluenceRealizer_N$ is invalid if it smuggles nonuniform row labels into RowSet output

cycle-0115: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 970.044 seconds; 3 lemmas, 3 equations, 5 derivation steps, 6 falsifiers.

Learning. Cycle 115 adds a minimality proof obligation to the promoted transparent-support theorem pair. Transparent FormulaEval is not just sufficient for a valid Γ_{trans} parser; hidden influence is exactly what the private-row/unread-enable-bit falsifier exploits. Thus the full-system boundary is a named nonrelativizing $RealSATInfluenceRealizer_N$ lemma, while the paper-level contribution remains a scoped parser/falsifier result rather than evidence for P $\neq$ NP.

Pressure. The transparent theorem and hidden-support countermodel are proof-shaped for occurrence-visible fragments, but the full semantic case is blocked by $RealSATInfluenceRealizer_N$: one must show that real SAT semantics forces every influential row into a charged support set.

Derivation steps.

1. Define the row universe $R_N = (x, j) : j \leq M_N$ and treat a FormulaEval line L as transparent only when its possible dependence set Infl_pi(L) is listed by visible selector code or charged by full scan.
2. For transparent L, add enumerator cost U_N(L) and row-expansion cost X_N(L) to Γ_{trans}; the existing bit-explicit line induction then compiles L into a circuit fragment without changing the SIZE model.
3. For a hidden row r with $Delta_r(L) = 1$ and r not in the charged support, build two occurrence-label worlds that agree on pi, visible selectors, EF support, SATeq links, and bounded SR_h neighborhoods but differ on SAT(r).
4. If the proof transcript is identical in the two worlds while the carrier parity changes, the parser-to-circuit inference is invalid; this is the private-row/unread-enable-bit falsifier for hidden FormulaEval support.
5. Contrapositively, any valid parser theorem for full semantic FormulaEval must prove that no such r exists, which is exactly the $RealSATInfluenceRealizer_N$ obligation with charged output size.

Equation 1: $GammaTrans$**.**

$$Gamma_trans(pi) = Gamma_bEF(pi) + U_N(pi) + X_N(pi) + O(E_NN)$$

Valid when: Valid when every FormulaEval influence is surfaced by $TransparentRowSupport_N$ or charged by full scan and residual row errors are explicitly counted.

Equation 2: ParsedCircuitUpperBound.

$$C_SIZE(H_N^SAT) \leq N^{rho+o(1)} + Gamma_trans(pi)$$

Valid when: Applies after the generator, all parsed proof lines, and all transparent FormulaEval row expansions are compiled into the same nonuniform SIZE model.

Equation 3: $\mathrm{LB}_{Falsifier,Window}$**.**

$$N^{rho+o(1)} + Gamma_trans(pi) + O(E_NN) < N^{1+epsilon-o(1)} => notLB_N(1 + epsilon)$$

Valid when: Requires the source lower-bound claim to be in the same SIZE model and the parser transcript to compute H_N^{SAT} on all but E_N patchable rows.

Next analysis. Formalize the private-row independence lemma for one full symbolic FormulaEval rule with an unread enable bit: write the two transcripts, the charged constraint set, the flipped row r, and the proof that all visible lines agree while H_N^{SAT} parity differs; if independence fails, record the exact same-theory constraint as a $RealSATInfluenceRealizer_N$ candidate.

Falsifiers.

- private-row falsifier: an uncharged influential FormulaEval row can be flipped while the visible proof transcript is fixed
- unread-enable-bit falsifier: a selector contains a dormant semantic enable bit whose active row is not surfaced by $TransparentRowSupport_N$
- $q < \epsilon$ support-density falsifier: absolute support below $N^{\epsilon - o(1)}$ gives a subthreshold parsed circuit after patching
- full-scan collapse: unenumerated transparent FormulaEval pays $F_{FE}\ N^{1+q+o(1)}$, which destroys the barely-superlinear window when q is too large
- nonuniform leakage falsifier: hidden selector advice names rows outside the proof bit string and invalidates the parser theorem
- positive-beta substitution cap: any black-box target-query exponent $\beta > 0$ leaves the transfer window q+beta c+o(1) and cannot exclude all SAT polynomial exponents

cycle-0116: Hardness-Magnification Bridge Realization: Transparent FormulaEval Minimality Audit

Execution. research; azure_responses_api; attempt primary; 148.454 seconds; 3 lemmas, 4 equations, 10 derivation steps, 5 falsifiers.

Learning. Cycle 116 closes the minimality audit for the transparent FormulaEval theorem pair. The valid paper claim is now a restricted parser/falsifier boundary: every surfaced influence is charged in Γ_{trans}, and every unsurfaced nonsemantic influence admits a private-row falsifier. The only remaining full-system route is the named nonrelativizing $RealSATInfluenceRealizer_N$; this is not evidence for P $\neq$ NP.

Pressure. Full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: private-row spoofing is a relativizing falsifier for hidden support, but it cannot refute genuinely real-SAT semantic influence without a same-theory realization or a concrete semantic no-go.

Derivation steps.

1. Fix N, $M_N = N^{q+o(1)}$, $\beta = 0$, generator G_N of size $N^{\rho+o(1)}$, and a Psys_{sym} proof pi whose non-FormulaEval lines are parsed by the Psys^{-}_{bEF} theorem.
2. For each transparent FormulaEval line l, compute $RowSet_l$ from visible selector code. If enumeration is output-sensitive charge U_l; otherwise full scan costs $M_N\ N^{1+o(1)}$ and is recorded in X_{FE}.

3. Expand every j in $RowSet_l$ into the same proof theory by inserting the occurrence neighborhood for SAT(G_N(x,j)) over all source rows x; charge $N^{1+o(1)}$ per row index and add this to Γ_{trans}.

4. Run line induction: bit-explicit EF dependencies, SATeq links, $bounded - SR_h$ leaves, and transparent FormulaEval expansions each yield circuits for the line predicates with total size bounded by Γ_{trans} plus generator overhead.

5. If the proof certifies LB_N(1+epsilon) but $N^{\rho+o(1)} + \Gamma_{trans} + E_N\ N^{1+o(1)}$ is below $N^{1+\epsilon-o(1)}$, the derived circuit is a valid falsifier for the asserted source lower bound.

6. For minimality, suppose a FormulaEval line has a hidden influential row r not in the charged RowSet. Build two label worlds agreeing on all charged rows and proof-visible bits but differing on the SAT label of r; carrier parity differs after choosing x with r's coefficient one, so occurrence completion was not sound.

7. If the selector has an unread enable bit, choose two settings with identical parsed transcript and different inclusion of r. This gives the same two-world falsifier and shows extensional enumeration is necessary.

8. If influence closure fails, downstream FormulaEval can depend on r through an unlisted derived predicate. Flipping r preserves the transcript but changes the carrier-relevant line, so the parser misses a row charge.

9. If hidden advice selects r, the proof transcript is unchanged while the selected support changes. The advice must either be charged as U_{FE} or the private-row falsifier applies.

10. If same-theory expansion fails because real SAT semantics determine r, the two-world spoof may violate SAT. This is not a valid countermodel; it is exactly the $RealSATInfluenceRealizer_N$ blocked lemma.

Equation 1: carrier.

$$H_N^S AT(x) = XOR_{j<M_N} SAT(G_N(x,j)), M_N = N^{q+o(1)}, |G_N| = N^{rho+o(1)}$$

Valid when: Valid when the source carrier is the beta-zero batched SAT parity problem with polylogarithmic generated instances and explicit generator overhead.

Equation 2: transparent_charge.

$$Gamma_trans(pi) = Gamma_bEF(pi) + U_FE(pi) + X_FE(pi), X_FE(pi) = N^{1+o(1)} sum_l |RowSet_l|$$

Valid when: Applies after every FormulaEval line has visible advice-free row support and same-theory occurrence expansion charged by row index.

Equation 3: parser_upper_bound.

$$C_SIZE(H_N^S AT) \leq N^{rho+o(1)} + Gamma_trans(pi) + E_N N^{1+o(1)}$$

Valid when: Valid when the parsed proof transcript computes the carrier except for E_N residual source rows patchable by equality gates.

Equation 4: lb_falsifier_window.

$$N^{rho+o(1)} + Gamma_t rans(pi) + E_N N^{1+o(1)} < N^{1+epsilon-o(1)} => notLB_N(1+epsilon)$$

Valid when: Requires the target-preserving SIZE simulation, beta-zero substitution, and exact lower-bound threshold to be in the same length regime.

Next analysis. Instantiate $RealSATInfluenceRealizer_N$ or refute it for one concrete strong rule: FormulaEval with Tseitin-extension equality plus bounded self-reduction; list exact bit fields, RowSet extraction, same-theory expansion certificates, and the first semantic inference that cannot be charged.

Falsifiers.

- Private-row falsifier: an uncharged influential row r has two label worlds agreeing on the parsed transcript but differing on H_N^{SAT}.
- Unread-enable-bit falsifier: selector inclusion of r is controlled by a bit not read by the parser, so RowSet is not extensionally valid.
- Hidden-advice falsifier: nonuniform row-selection advice can encode the needed support while evading U_{FE} and X_{FE} charges.
- Subthreshold Γ falsifier: $N^{\rho} + \Gamma_{trans} + E_N\ N < N^{1+\epsilon}$ gives an explicit small SIZE circuit against LB_N(1+epsilon).
- Same-theory failure is not a valid oracle falsifier; it quarantines the route at $RealSATInfluenceRealizer_N$ rather than at generic barrier folklore.

cycle-0117: Hardness-Magnification Bridge Realization: Transparent FormulaEval Boundary

Execution. research; azure_responses_api; attempt primary; 118.652 seconds; 3 lemmas, 4 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 117 upgrades the promoted theorem pair from sufficiency plus informal minimality to a local safety iff for extensional FormulaEval: surfaced influence is exactly what makes the Γ_{trans} parser valid, and unsurfaced nonsemantic influence is exactly what the private-row/unread-enable-bit falsifier exploits. The full semantic case is not dismissed by a barrier slogan; it is isolated as the nonrelativizing $RealSATInfluenceRealizer_N$ obligation. This is a paper-level route-boundary result, not a proof of P ≠ NP.

Pressure. The derivation is complete for extensional FormulaEval rules but still blocked for full semantic FormulaEval at $RealSATInfluenceRealizer_N$, which must nonrelativizingly force real SAT influence into charged same-theory support.

Derivation steps.

1. Fix a Psys_{sym} proof pi of LB_N(1+epsilon) for H_N^{SAT} and parse all Psys^{-}_{bEF} lines using the existing bit-explicit EF, SATeq, $bounded - SR_h$, and sparse-row charges.

2. For each FormulaEval line, require $TransparentRowSupport_N$: the parser receives visible selector code, an advice-free enumerator or full scan, row expansion into occurrence neighborhoods, and influence closure under enable bits and projections.

3. Add the enumerator cost U_l, expansion cost X_l, or full-scan cost $N^{1+q+o(1)}$ for the line; summing over lines yields Gamma_trans(pi).

4. Run the line induction: every accepted proof line has a circuit/transcript implementation whose size is bounded by the accumulated Γ_{trans} prefix, and $bounded - SR_h$ contributes exactly its previous B_{SR} charge.

5. Compose the generator circuit of size $N^{\rho+o(1)}$ with the parsed transcript; if the residual exceptional rows are E_N, patch them by equality tests at cost O(E_N N).

6. Contrapose: when the total size is below $N^{1+\epsilon-o(1)}$, the alleged LB_N(1+epsilon) certificate is falsified inside the same nonuniform SIZE model.

7. For the converse minimality check, suppose an extensional FormulaEval line has a hidden influencing row r. Construct two row-label worlds equal on all surfaced rows and proof text but differing at r; the parser output is identical while the FormulaEval value or parity carrier differs.

8. Therefore no occurrence parser that omits r can be sound for extensional rules; this proves local necessity of support visibility and identifies real SAT semantics as the only possible escape.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N| = N^{\rho+o(1)}$$

Valid when: Valid when the source carrier is the beta-zero generated parity family and the generator produces polylogarithmic SAT instances with uniform decoding.

Equation 2: transparent_charge.

$$\Gamma_{trans}(\pi) = \Gamma_{bEF}(\pi) + U_N(\pi) + X_N(\pi) + F_{FE}(\pi) N^{1+q+o(1)}$$

Valid when: Applies after every FormulaEval line either supplies an advice-free row enumerator or is charged by full syntactic scan in the same proof theory.

Equation 3: falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{trans}(\pi) + E_N N < N^{1+\epsilon-o(1)} \implies \neg LB_N(1+\epsilon)$$

Valid when: Requires the parser-to-circuit simulation to preserve the nonuniform SIZE model and the residual error set to have at most E_N source rows.

Equation 4: support_density_corollary.

$$|K_{idx}(\pi)|/M_N \ge N^{\epsilon-q-o(1)}$$

Valid when: Valid when LB_N(1+epsilon) is claimed and the only surfaced FormulaEval support is row-index support among $M_N = N^{q+o(1)}$ slots.

Next analysis. Write the paper-ready theorem statement as three clauses: $TransparentRowSupport_N$ positive Γ_{trans} induction; extensional hidden-support private-row/unread-enable-bit countermodel; $RealSATInfluenceRealizer_N$ open semantic escape with overhead R_N and explicit non-claims.

Falsifiers.

- Private-row falsifier: an uncharged active row outside K_idx(pi) yields two visible-identical transcripts with different row labels, invalidating occurrence completion.
- Unread-enable-bit falsifier: a hidden guard selects a row only in one world, so selector extensionality fails unless the guard is surfaced and charged.
- Threshold falsifier: if N^{rho+o(1)}+Gamma_trans(pi)+E_NN<N^{1+epsilon-o(1)}, any claimed LB_N(1+epsilon) certificate collapses to a small circuit.
- Positive-beta falsifier: any repair introducing target queries of length N^β with $\beta > 0$ reactivates the q+beta c transfer cap and cannot exclude all SAT polynomial exponents.
- Nonuniform-leakage falsifier: if row enumeration uses advice depending on SAT labels, the parser theorem is invalid even when its apparent U_N charge is small.

cycle-0118: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 111.25 seconds; 3 lemmas, 6 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 118 adds a compositional repair to the FormulaEval boundary: local surfaced influence is not enough unless hidden influences are closed under later proof use. The valid restricted theorem is $\mathrm{Psys}^{ext}_{sym}$ plus charged $RealSATInfluenceRealizer_N$ rows implies Γ_{comp} line induction and the LB_N falsifier window. The necessity direction is now a last-unsafe-line private-row theorem. Full semantic FormulaEval remains open exactly at a nonrelativizing realizer lemma, not at generic relativization, natural-proofs, or P vs NP folklore.

Pressure. The last-unsafe-line argument is valid in the extensional label model. For real SAT semantics, a hidden row may be forced by nonrelativizing formula identities, self-reduction constraints, or EqSAT links without being syntactically visible. That exact gap is $RealSATInfluenceRealizer_N$.

Derivation steps.

1. Define the influence cone I_l for each FormulaEval line l as the set of generated row labels whose flip can change the line value with all visible syntax fixed.
2. For transparent lines, enumerate I_l by the visible selector code or charge a full scan over M_N rows; add $U_l + X_l$ to Γ_{comp}.
3. For bEF, SATeq, and $bounded - SR_h$ lines, reuse the bit-explicit dependency parser and SR_h field parser; add Γ_{bEF} and $B_{SR,h}$ to Γ_{comp}.
4. For hidden FormulaEval lines, either a same-theory $RealSATInfluenceRealizer_N$ lists the forced influence rows and contributes R_{FE}, or mark the line unsafe.

5. If no unsafe line remains, perform line induction: every proof line is simulated by a circuit using the generator, charged row labels, charged SR leaves, and charged FormulaEval expansions.

6. The final line gives a circuit for H_N except on E_N explicitly residual rows; equality patches yield $C(H_N) \leq N^{\rho+o(1)} + \Gamma_{comp}(pi) + E_{NN}$.

7. If an unsafe line remains, choose the last unsafe line whose hidden row reaches the final output without later charged realization. Flip that row in an extensional two-world model while fixing all charged rows; the transcript is identical but the induced parity differs.

8. Conclude that surfaced influence plus realizer closure is sufficient for the parser, and failure of both is a private-row falsifier for extensional FormulaEval.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x, j))$$

Valid when: Valid when the generated instance family G_N is fixed, advice-free, and has $M_N = N^{q+o(1)}$ indexed rows of polylogarithmic target length.

Equation 2: composite_transcript_charge.

$$\Gamma_{comp}(\pi) = \Gamma_{bEF}(\pi) + B_{SR_h}(\pi) + U_{FE}(\pi) + X_{FE}(\pi) + R_{FE}(\pi)$$

Valid when: Applies after bit-explicit EF support, bounded SR_h fields, transparent FormulaEval enumeration, expansion charges, and semantic realizer rows are all separately charged.

Equation 3: sr_charge.

$$B_{SR_h}(\pi) \leq N^{q+\eta+\tau+o(1)}$$

Valid when: Valid when the bounded self-reduction rule has at most $N^{\eta+o(1)}$ leaves per active row and leaf verifier overhead $N^{\tau+o(1)}$.

Equation 4: parser_upper_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{comp}(\pi) + E_N N$$

Valid when: Requires the parser to produce a same-model circuit for all but E_N exceptional source rows, with equality patches charged nonuniformly per row.

Equation 5: falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{comp}(\pi) + E_N N < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is stated in the identical nonuniform SIZE model and the parsed circuit computes the carrier on every valid input length.

Equation 6: support_density_corollary.

$$|K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Follows only when all other transcript terms are subthreshold and FormulaEval support is the remaining necessary charged source of hardness.

Next analysis. Run a finite proof audit on Psys^{ext}_{sym}: instantiate one guarded FormulaEval line, compute I_l, K_{idx}, R_{FE}, and Γ_{comp}, then verify the last-unsafe-line two-world construction or identify the first real SAT-semantic rule that forces a nonrelativizing realizer charge.

Falsifiers.

- Subthreshold Γ_{comp} falsifier: N^{rho+o(1)}+Gamma_comp(pi)+E_NN<N^{1+epsilon-o(1)} contradicts any claimed LB_N(1+epsilon) in the same SIZE model.
- Private-row falsifier: an unsurfaced nonsemantic FormulaEval influence outside K_{idx} union R_{FE} yields two label worlds with identical transcript and different carrier parity.
- Unread-enable-bit falsifier: a selector whose enabling bit is never surfaced can switch a row into the influence cone without changing the charged transcript.
- Threshold-collapse falsifier: if q+eta+tau, U_{FE}, X_{FE}, or R_{FE} reaches 1+epsilon, the parser theorem may remain valid but no barely-superlinear lower-bound contradiction follows.
- Model-mismatch falsifier: a proof that treats semantic SAT implications as occurrence support without a same-theory realizer leaks nonuniform advice into the source lower-bound certificate.

cycle-0119: Hardness-Magnification Bridge Realization, cycle 119: compositional transparent support closure

Execution. research; azure_responses_api; attempt primary; 1005.976 seconds; 3 lemmas, 5 equations, 11 derivation steps, 5 falsifiers.

Learning. Cycle 119 turns compositional closure from a warning into a theorem-shaped invariant: transparent FormulaEval support must be prefix-closed under later symbolic use, and subthreshold Γ_{comp} then gives a same-model LB_N falsifier. The necessity direction is a last-unsafe-line private-row theorem for extensional support. Full semantic FormulaEval remains open exactly at $RealSATInfluenceRealizer_N$, not at generic barrier folklore or the main P vs NP conjecture.

Pressure. The derivation does not prove full Psys_{sym} semantic FormulaEval parsing; it is blocked exactly at $RealSATInfluenceRealizer_N$ for rules whose influence is forced by real SAT semantics but not surfaced as generated-row support.

Derivation steps.

1. Live source_statement: C_SIZE(H_N^SAT)>N^{1+epsilon-o(1)} for the beta-zero parity carrier is the lower-bound statement being audited, not assumed true.
2. Live target_statement: a support-closed transparent proof pi with $N^{\rho+o(1)} + \Gamma_{comp}(pi) + E_{pi}$ $N < N^{1+\epsilon-o(1)}$ yields an explicit same-model circuit for H_N^{SAT}, hence is a valid falsifier for that LB_N claim.

3. $Model_{context}$: source carrier H_N^{SAT} uses generated polylog SAT formulas; target class is nonuniform SIZE; proof model is restricted $\mathrm{Psys}_{sym}^{ext}$; reduction type is parser-to-circuit simulation plus equality patching, not a proof of P $\neq$ NP.

4. $Quantifier_{context}$: N ranges over valid carrier lengths, $\epsilon > 0$ is fixed, q and ρ are fixed below 1+epsilon, $\beta = 0$, parser uniformity is advice-free, and pi may be nonuniform only as the alleged proof/certificate object being audited.

5. Define Cl_t, the prefix row-influence closure before line t. Initialize it from bit-explicit EF dependencies, SATeq links, $bounded - SR_h$ leaves, and declared extension supports already covered by Γ_{bEF}.

6. For a transparent FormulaEval line, add either the enumerated $RowSet_l$ with cost U_l and occurrence expansion X_l, or the full-scan support over all M_N rows with cost $N^{1+q+o(1)}$; propagate this set to every later line that reads the symbolic value.

7. For an admitted semantic line, require a $RealSATInfluenceRealizer_N$ object before the line is usable; add its generated row indices, occurrence neighborhoods, and verifier overhead to R_N and to Cl_t.

8. Induct on proof lines: given Cl_t and the prefix circuit of size Gamma_prefix(t), bit-explicit EF and SR_h rules preserve locality by the cycle-102 normal form; transparent FormulaEval preserves locality by explicit RowSet expansion; inherited closures prevent later hidden support reuse.

9. At the final lower-bound line, assemble a circuit for H_N^{SAT} from the generator, the charged transcript circuit, and equality patches for E_{pi} exceptional source rows; its size is at most $N^{\rho+o(1)} + \Gamma_{comp}(pi) + E_{pi}$ N.

10. Contrapositive: if pi is presented as a proof of LB_N(1+epsilon) while the displayed cost is subthreshold, the constructed circuit contradicts the LB_N statement in the same SIZE model; this is a route-level falsifier theorem, not evidence for P $\neq$ NP.

11. Reviewer findings: reduction-consistency passes for $\mathrm{Psys}_{sym}^{ext}$ because source and target circuits are the same nonuniform model; quantifier-uniformity passes only with advice-free parser clauses; barrier-specificity says extensional hidden support is relativizing and refuted by private rows, while $RealSATInfluenceRealizer_N$ is the named nonrelativizing open obligation.

Equation 1: carrier_batch_size.

$$M_N = N^{q+o(1)}$$

Valid when: Valid when the beta-zero parity carrier has a fixed batched generator family with polynomially many source rows and q is measured on valid N lengths.

Equation 2: compositional_cost.

$$Gamma_comp(pi) = Gamma_bEF(pi) + U_N(pi) + X_N(pi) + R_N(pi)$$

Valid when: Applies after every proof line is parsed with prefix-closed support inheritance and all FormulaEval or semantic row influences are surfaced and charged.

Equation 3: parser_upper_bound.

$$C_SIZE(H_N^S AT) \leq N^{rho+o(1)} + Gamma_comp(pi) + E_piN$$

Valid when: Requires the support-closed transcript, same-theory expansion, generator size $N^{\rho+o(1)}$, and equality patching for at most E_{pi} exceptional source rows.

Equation 4: subthreshold_falsifier_window.

$$N^{rho+o(1)} + Gamma_comp(pi) + E_piN < N^{1+epsilon-o(1)} => notLB_N(1+epsilon)$$

Valid when: Valid when LB_N is a nonuniform SIZE lower-bound claim for the same H_N^{SAT} and the constructed circuit family is advice-free except for pi.

Equation 5: support_density_pressure.

$$|K_idx(pi)|/M_N \geq N^{epsilon-q-o(1)}$$

Valid when: Applies to any valid LB_N proof in this parser model after non-row costs are subthreshold and charged complete rows are the remaining support bottleneck.

Next analysis. Write the finite prefix-closure verifier for $TransparentRowSupport_N$: input pi,N; output Cl_t for each line, Gamma_prefix(t), and either a valid support-closed derivation certificate or the first unsafe line with its private-row/unread-enable-bit countermodel.

Falsifiers.

- Extensional hidden support falsifier: a private row absent from Cl_t is flipped while all visible transcript bits are fixed.
- Unread-enable-bit falsifier: a symbolic FormulaEval gate contains an unenumerated guard bit whose later use changes the accepted transcript without paying U_N or X_N.
- Subthreshold transcript falsifier: $N^{\rho+o(1)} + \Gamma_{comp}(pi) + E_{pi}\ N < N^{1+\epsilon-o(1)}$ constructs a same-model circuit contradicting LB_N(1+epsilon).
- $q < \epsilon$ density falsifier: the required relative support $|K_{idx}|/M_N$ exceeds one when all non-row costs are already subthreshold.
- Semantic-oracle falsifier: a FormulaEval-SAT rule whose accepted behavior changes with a hidden generated row but supplies no $RealSATInfluenceRealizer_N$ lies outside the transparent parser theorem.

cycle-0120: Hardness-Magnification Bridge Realization: least-closed transparent FormulaEval support

Execution. research; azure_responses_api; attempt primary; 167.458 seconds; 3 lemmas, 5 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 120 strengthens the promoted theorem pair by identifying the minimal valid charged object: the least prefix-closed reachable FormulaEval support cone K_dag(pi), not the full selector zoo. The positive line induction uses Gamma_dag=Gamma_bEF+U(K_dag)+X(K_dag), and the necessity side is a first-hidden-reachable-row falsifier. Full semantic FormulaEval remains quarantined exactly at $RealSATInfluenceRealizer_N$; this is a scoped parser/falsifier contribution, not progress toward proving P $\neq$ NP.

Pressure. Full semantic FormulaEval over real SAT is still blocked at $RealSATInfluenceRealizer_N$: no proof currently converts semantic influence of an uncharged formula row into an advice-free, prefix-closed, charged support certificate.

Derivation steps.

1. Define the live inference source statement: $\mathrm{Psys}^{dag}_{sym}$ proves LB_N(1+epsilon) for H_N^{SAT} with $\beta = 0$, $q, \rho < 1 + \epsilon$, bit-explicit bEF support, $bounded - SR_h$ normal form, and FormulaEval dependency DAGs.

2. Define the live inference target statement: if pi has N^{rho+o(1)}+Gamma_dag(pi)+O(E_pi N)<N^{1+epsilon-o(1)}, then the same nonuniform SIZE model has circuits for H_N^{SAT} below the claimed lower-bound threshold; hence that pi is a falsifier for LB_N(1+epsilon), not evidence for P $\neq$ NP.

3. Build K_dag(pi) as a least fixed point: seed with FormulaEval tokens used by the final LB_N line, close under explicit parent pointers, row enumerator certificates, SR_h leaf rows, and symbolic aliases that feed any retained line.

4. Run line induction only on the retained cone. Bit-explicit bEF lines use the existing Γ_{bEF} charge; $bounded - SR_h$ lines add eta/tau-normalized row costs; transparent FormulaEval lines add U(K)+X(K). Unreachable FormulaEval rows are ignored by $UnreachableSupportDeletion_N$.

5. Substitute a hypothetical SAT circuit of size L_N^c into each generated formula. Because $L_N =$ *polylog* N, every fixed c contributes $N^{o(1)}$ per surfaced row; generator plus transcript costs give C(H_N)<=N^{rho+o(1)}+Gamma_dag(pi)+O(E_pi N).

6. Derive the density corollary: any valid proof certificate for LB_N(1+epsilon) inside this parser model must force at least $N^{\epsilon - o(1)}$ reachable complete parity rows, equivalently density $N^{\epsilon - q - o(1)}$ among $M_N = N^{q+o(1)}$ slots when q is fixed.

7. Prove necessity for the extensional case by choosing the earliest reachable uncharged influence. Flip its private row or unread enable bit while keeping charged transcript data fixed; the verifier sees the same prior cone but the final induced parity differs, contradicting sound surface occurrence completion.

8. Reviewer packet status: reduction consistency is valid for $\beta = 0$ same-model substitution; quantifier uniformity is fixed over q,rho,epsilon,h,d; barrier specificity says the countermodel relativizes only for extensional/oracle FormulaEval, while the real SAT escape is the named nonrelativizing $RealSATInfluenceRealizer_N$.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x, j)), \quad M_N = N^{q+o(1)}$$

Valid when: Valid when the source object is the beta-zero generated parity carrier with uniformly computable generator slots.

Equation 2: least_closed_cost.

$$\Gamma_{dag}(\pi) = \Gamma_{bEF}(\pi) + U(K_{dag}(\pi)) + X(K_{dag}(\pi)) + O(|\pi| \operatorname{polylog} N)$$

Valid when: Valid when $\mathrm{Psys}_{sym}^{dag}$ exposes parent pointers, dependency edges, and advice-free row enumeration certificates.

Equation 3: falsifier_upper_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{dag}(\pi) + O(E_\pi N)$$

Valid when: Applies after the line induction preserves same-model circuits and sparse row errors are equality patched.

Equation 4: subthreshold_negation.

$$N^{\rho+o(1)} + \Gamma_{dag}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Requires the target-preserving same-model transfer and the claimed LB_N threshold in nonuniform SIZE.

Equation 5: support_density_corollary.

$$|K_{dag}(\pi)| \ge N^{\epsilon-o(1)}, \quad |K_{dag}(\pi)|/M_N \ge N^{\epsilon-q-o(1)}$$

Valid when: Valid when each complete surfaced parity row costs $N^{1+o(1)}$ to realize and ρ is subthreshold.

Next analysis. Write the proof-audit version of L120.1: formalize the fixed-point computation of K_dag(pi), give pseudocode for the verifier-visible dependency closure, and check one projected-dDNNF FormulaEval example plus one unread-enable-bit counterexample against the Γ_{dag} inequality.

Falsifiers.

- Reachable hidden support falsifier: an uncharged row in the final dependency cone permits two extensional transcripts agreeing on all charged data while differing on the induced parity carrier.
- Unread-enable-bit falsifier: a selector bit that can activate a row after its enumerator certificate is checked invalidates Γ_{dag} unless the activation edge is prefix-closed and charged.
- Subthreshold transcript falsifier: N^{rho+o(1)}+Gamma_dag(pi)+O(E_pi N)<N^{1+epsilon-o(1)} gives an explicit small circuit for H_N^{SAT} in the same model, refuting the source LB_N certificate.

- $q < \epsilon$ support-density falsifier: if fewer than $N^{\epsilon - o(1)}$ reachable complete rows are forced among $M_N = N^{q+o(1)}$ slots, equality patching and the transcript circuit stay below the claimed threshold.
- Semantic-realizer falsifier probe: if a claimed full FormulaEval rule influences a proof without producing $RealSATInfluenceRealizer_N$ rows, the branch treats it as outside the valid parser theorem rather than as transparent support.

cycle-0121: Hardness-Magnification Bridge Realization: L121 least-closed support audit

Execution. research; azure_responses_api; attempt primary; 157.908 seconds; 3 lemmas, 5 equations, 10 derivation steps, 6 falsifiers.

Learning. Cycle 121 turns K_dag(pi) into a finite auditable fixed-point object. The valid contribution is sharper than the previous transparency slogan: least prefix-closed reachable support is sufficient for the Γ_{dag} parser and necessary for extensional safety via a first-hidden-row falsifier. The remaining full-system gap is exactly $RealSATInfluenceRealizer_N$ for real SAT-semantic FormulaEval, not generic relativization, natural proofs, or P vs NP folklore.

Pressure. The restricted proof is complete only for transparent extensional FormulaEval. Full semantic SAT FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: proof syntax must nonrelativizingly determine and charge every real SAT influence before use.

Derivation steps.

1. Normalize pi into a finite DAG of lines with IDs, parent lists, and rule tags; reject lines whose parents are implicit semantic advice.
2. Initialize the active line set A with the final LB_N line and initialize K_{idx}, K_{occ}, U, X to empty ledgers.
3. Process a worklist: when a line is popped, add all proof parents to A; for a bEF line add its bit-explicit dependency charge to Γ_{bEF}.
4. For each reachable FormulaEval line, run its visible support enumerator or certified full scan; add each row identifier, occurrence-neighborhood, and parent support certificate to K_{dag}.
5. Close under later symbolic use: if a reachable line reads a FormulaEval value, add the row certificate and all support parents before the line is counted valid.
6. Terminate because each step adds a proof line, support certificate, or row occurrence from the finite transcript; the fixed point is least by monotonicity of the closure operator.
7. Prove the line-induction invariant: every reachable line has a same-theory circuit/transcript of size at most the accumulated prefix of $\Gamma_{bEF} + U + X$, with exceptional rows recorded in E_{pi}.
8. At the final LB_N line, compose the generator for G_N with the parsed transcript and equality patches, obtaining C(H_N^SAT)<=N^{rho+o(1)}+Gamma_dag+O(E_pi N).

9. Derive the falsifier inequality: a proof of LB_N(1+epsilon) with subthreshold Γ_{dag} contradicts the same-model circuit upper bound, so any valid proof must pay the support-density threshold.

10. For minimality, remove a reachable influencing row and choose two row-label worlds agreeing on K_{dag} but differing there; the first line whose value changes gives the private-row/unread-enable-bit countermodel.

Equation 1: fixed_point_closure.

$$K_0 = \ell_{final}, \quad K_{t+1} = K_t \cup Par(K_t) \cup Supp_{FE}(K_t) \cup Infl(K_t), \quad K_{dag} = \bigcup_t K_t.$$

Valid when: Valid when $\mathrm{Psys}^{dag}_{sym}$ exposes parent pointers and FormulaEval support certificates syntactically.

Equation 2: gamma_dag_ledger.

$$\Gamma_{dag}(\pi) = \Gamma_{bEF}(\pi) + U_N(K_{dag}(\pi)) + X_N(K_{dag}(\pi)).$$

Valid when: Applies after the closure algorithm has surfaced every reachable FormulaEval influence.

Equation 3: parser_upper_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{dag}(\pi) + O(E_\pi N).$$

Valid when: Requires β zero, same-model row expansion, and equality patching for exceptional rows.

Equation 4: lb_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{dag}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon).$$

Valid when: Valid when LB_N is the lower-bound claim for the same carrier and circuit model.

Equation 5: support_density_corollary.

$$|K_{idx}(\pi)| \ge N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \ge N^{\epsilon-q-o(1)}.$$

Valid when: Applies when each charged FormulaEval slot has expansion cost $\widetilde{O}(N)$.

Next analysis. Write the formal L121.1 proof skeleton as theorem text: fixed-point pseudocode for K_{dag}, induction invariant per rule type, charge table for bEF/SR_h/FormulaEval/$projected - dDNNF$, and the unread-enable-bit counterexample with $\theta < \epsilon$.

Falsifiers.

- first-hidden-reachable-row falsifier: a later proof line depends on a row absent from K_{dag}
- unread-enable-bit falsifier: selector output is disabled in syntax but semantically gates an uncharged row
- $q < \epsilon$ enumeration falsifier: subthreshold reachable support density yields an immediate small circuit for the claimed LB_N
- semantic-advice falsifier: RowSet(a) is chosen using SAT truth or nonuniform advice rather than proof syntax
- same-theory failure falsifier: row expansion is asserted externally and cannot be represented inside $\mathrm{Psys}^{dag}_{sym}$
- positive-beta transfer falsifier remains quarantined: q+beta c caps all-exponent target transfer unless $\beta = 0$ or subpolynomial

cycle-0122: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 120.494 seconds; 3 lemmas, 6 equations, 10 derivation steps, 6 falsifiers.

Learning. Cycle 122 upgrades K_{dag} from a named minimal support object to a referee-auditable fixed-point proof packet. The valid theorem is restricted but paper-relevant: least prefix-closed reachable FormulaEval support is sufficient for Γ_{dag} line induction and necessary for extensional safety by a first-hidden-row falsifier. The full semantic case is still blocked exactly at $RealSATInfluenceRealizer_N$ not by generic barrier folklore or by the P vs NP conjecture itself.

Pressure. The restricted theorem is valid for transparent extensional FormulaEval, but it does not settle full semantic FormulaEval. The named gap is $RealSATInfluenceRealizer_N$: real SAT-semantic reasoning may determine row influence without a verifier-visible row set, and this requires a nonrelativizing charged realizer or a rule-specific no-go.

Derivation steps.

1. Parse pi line by line into ordinary bEF lines and FormulaEval cells (a,r). For each FormulaEval cell record opcode, row index r, parent-cell pointers, selector code, expansion code, and an enumerator or full-scan certificate.
2. Build the backward dependency graph D_{pi} whose edges go from a used cell to its verifier-visible parent cells and to row occurrences that must be expanded in the same theory.
3. Initialize K_0 by the final LB_N assertion and the carrier rows whose parity is read by the final falsifier construction. This seed is syntactic; it contains no SAT-truth advice.
4. Iterate $K_{t+1} = K_t$ union BackParents(K_t) union RowSupp(K_t). Termination is bounded by the finite set of declared cells and rows, so K_{dag} is auditor-computable.
5. Define U_N(K_dag) as the sum of enumerator or full-scan costs needed to list reachable rows, and X_N(K_dag) as the same-theory occurrence-expansion cost for exactly those rows.

6. Run the existing Γ_{bEF} line induction for ordinary EF, SATeq, and $bounded - SR_h$ lines. For FormulaEval lines, use closure of K_{dag} to guarantee that every later symbolic use already has its parent rows and expansions charged.

7. Construct circuits for all reachable proof-line predicates with total size Gamma_bEF(pi)+U_N(K_dag)+X_ then compose with the generator circuit of size $N^{\rho+o(1)}$.

8. If the induced circuit is wrong on E_{pi} exceptional source inputs, patch them by equality circuits at cost O(E_pi N), giving the displayed upper bound for H_N^{SAT}.

9. Derive the q-trichotomy: subthreshold Γ_{dag} forces $|K_{idx}| \geq N^{\epsilon-o(1)}$; hence qepsilon leaves weak but absolute support pressure.

10. For minimality, choose the first downstream use of an uncharged reachable row and construct two row-label worlds that agree on all visible fields but differ on that row, producing the private-row or unread-enable-bit contradiction.

Equation 1: fixed_point_definition.

$$K_0 = \mathrm{Seed}(\mathrm{FinalLB}(\pi)), \quad K_{t+1} = K_t \cup \mathrm{BackParents}(K_t) \cup \mathrm{RowSupp}(K_t), \quad K_\dagger = \mathrm{lfp}(K_t)$$

Valid when: Valid when every FormulaEval use exposes verifier-readable parent maps and row support certificates.

Equation 2: finite_convergence_bound.

$$T_\dagger \leq |\,\mathrm{Cells}(\pi)| + |\,\mathrm{RowsDeclared}(\pi)|$$

Valid when: Applies when the dependency graph is finite and rows are explicitly indexed.

Equation 3: charged_gamma.

$$\Gamma_\dagger(\pi) = \Gamma_{bEF}(\pi) + U_N(K_\dagger) + X_N(K_\dagger)$$

Valid when: Valid when bEF charges are already parsed and FormulaEval support is transparent.

Equation 4: parser_to_circuit_falsifier.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_\dagger(\pi) + O(E_\pi N)$$

Valid when: Requires the generator, parsed proof transcript, and sparse residual patches to be same-model circuits.

Equation 5: subthreshold_contradiction_window.

$$N^{\rho+o(1)} + \Gamma_\dagger(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is a lower bound against the same nonuniform SIZE model.

Equation 6: support_density_corollary.

$$|K_{idx}(\pi)| \geq N^{\epsilon - o(1)}, \qquad |K_{idx}(\pi)|/M_N \geq N^{\epsilon - q - o(1)}$$

Valid when: Applies after each charged row costs at most $N^{1+o(1)}$ to patch.

Next analysis. Write the paper-ready L122 module: formal theorem statement, fixed-point pseudocode, line-induction proof, projected-dDNNF charge example, unread-enable-bit counterexample, q-trichotomy corollary, and a separate $RealSATInfluenceRealizer_N$ open-boundary paragraph.

Falsifiers.

- first-hidden-reachable-row falsifier: a row affects the final LB_N line but is absent from K_{dag} and all charges, so two visible-identical transcripts disagree on the carrier.
- unread-enable-bit falsifier: a selector enable controls row reachability while not appearing in parent pointers, invalidating local transparency despite an apparently valid row list.
- $q < \epsilon$ enumeration falsifier: K_{idx} must have absolute size $N^{\epsilon - o(1)}$ but the universe has only $M_N = N^{q+o(1)}$ rows.
- semantic-advice leakage: $Enum_a$ or RowSupp(a,r) depends on SAT truth or nonuniform row advice rather than proof syntax and N.
- positive-beta transfer falsifier: any black-box target-circuit substitution with query length n^β gives the cap q+beta c+o(1), so it cannot yield all-exponent target exclusion unless $\beta = 0$ or subpolynomial.
- nonprefix local support falsifier: a row is surfaced where defined but hidden after a later symbolic use, breaking the line-induction invariant.

cycle-0123: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 435.479 seconds; 4 lemmas, 7 equations, 9 derivation steps, 7 falsifiers.

Learning. Cycle 123 closes a proof-audit gap rather than repeating the magnification slogan: K_{dag} is an implementable least fixed point, projected-dDNNF gives a concrete transparent positive case, and the unread-enable-bit/private-row construction gives a precise necessity falsifier. The valid result is a scoped parser/falsifier theorem for beta-zero parity magnification; full semantic FormulaEval is still blocked exactly at $RealSATInfluenceRealizer_N$.

Pressure. $RealSATInfluenceRealizer_N$ remains unproved for full semantic FormulaEval: a real SAT-semantic rule might force r* nonrelativizingly from charged rows even when no extensional support certificate lists it.

Derivation steps.

1. Instantiate the source statement as LB_N(1+epsilon) for H_N^{SAT} in nonuniform SIZE, with $M_N = N^{q+o(1)}$, L_N=(log N)^d, $\beta = 0$, and generator overhead $N^{\rho+o(1)}$.

2. Parse all Psys^{-}_{bEF} lines first; EF dependencies, SATeq links, and $bounded - SR_h$ leaves contribute Gamma_bEF(pi) exactly as in the restricted bit-explicit theorem packet.

3. Define row atoms for FormulaEval lines and run the verifier-visible fixed point: start from rows reachable from the final LB_N line, repeatedly add parent rows, selector rows, same-theory expansion rows, and earlier rows used by later reachable lines.

4. Charge each closure addition either by U_N(K_dag), an advice-free enumerator/full-scan cost, or by X_N(K_dag), the N-per-row occurrence expansion; reject any row whose selector is only semantic advice.

5. For the projected-dDNNF example, gate pointers and projection maps give the enumerator. The reachable cone follows output-gate dependencies, so irrelevant dDNNF components are not charged.

6. Extend the line induction: every proof line whose reachable rows are in K_{dag} has a simulator circuit of cost bounded by the prior simulator plus the charged local rule cost; the final line yields C(H_N^SAT)<=N^{rho+o(1)}+Gamma_dag(pi)+O(E_pi N).

7. Contrapose the lower-bound claim: if this upper bound is below $N^{1+\epsilon-o(1)}$, the proof transcript is a same-model falsifier for LB_N(1+epsilon).

8. Prove minimality for extensional FormulaEval by choosing the first later-used row r* omitted from K_{dag}; two transcripts agree on charged rows and all syntax but differ on r*, so the parser cannot be valid for both.

9. Derive the q-trichotomy from $X_N(K) = \widetilde{O}(N|K|)$: a valid LB_N certificate must force $|K_{dag}| \geq N^{\epsilon-o(1)}$, hence density at least $N^{\epsilon-q-o(1)}$ inside M_N slots.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when the source carrier is the beta-zero parity carrier with uniformly generated polylogarithmic SAT instances.

Equation 2: least_closure.

$$K_0 = Reach(final), \quad K_{t+1} = K_t \cup Parents(K_t) \cup SupportRows(K_t), \quad K_{dag}(\pi) = \bigcup_t K_t$$

Valid when: Valid when every dependency edge and support certificate is visible in the proof syntax and uses no semantic row advice.

Equation 3: charged_gamma.

$$\Gamma_{dag}(\pi) = \Gamma_{bEF}(\pi) + U_N(K_{dag}) + X_N(K_{dag})$$

Valid when: Applies after the fixed-point closure terminates on the finite proof DAG and all transparent rows are charged.

Equation 4: row_expansion.

$$X_N(K_{dag}) \leq \widetilde{O}(N \cdot |K_{dag}|)$$

Valid when: Requires same-theory occurrence expansion where each surfaced row is materialized at N-bit source cost.

Equation 5: same_model_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{dag}(\pi) + O(E_\pi N)$$

Valid when: Applies after the reduction preserves the same nonuniform SIZE model, beta-zero query length, and charged support parameters.

Equation 6: lb_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{dag}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N(1+epsilon) denotes an asserted same-model lower bound above the displayed threshold.

Equation 7: support_density_corollary.

$$LB_N(1+\epsilon) \Rightarrow |K_{dag}| \geq N^{\epsilon-o(1)}, \quad |K_{dag}|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Requires the row-expansion term to dominate uncharged support cost and $M_N = N^{q+o(1)}$ slots.

Next analysis. Write the referee-checkable trace for the projected-dDNNF example: list gate fields, parent pointers, projection maps, RowSet certificates, K_0, K_1,... closure additions, U_N and X_N charges, then flip one unread enable bit to exhibit the first-hidden-row countermodel and verify the Γ_{dag} threshold numerically for qepsilon.

Falsifiers.

- first-hidden-reachable-row falsifier for extensional FormulaEval without charged support
- unread-enable-bit falsifier for projected or guarded FormulaEval whose selector is not surfaced before later use
- private-row two-world falsifier for symbolic FormulaEval that treats row influence as semantic oracle advice
- $q < \epsilon$ total-slot falsifier: $M_N = N^{q+o(1)}$ cannot supply $N^{\epsilon-o(1)}$ charged rows
- positive-beta black-box substitution falsifier: SAT $\in$ SIZE(n^c) gives source upper bound N^{q+beta c+o(1)} before all-exponent exclusion
- nonuniform row-selection leakage falsifier when RowSet(a) is supplied by advice rather than proof syntax
- semantic *RealSAT* escape falsifier probe: if no advice-free influence realizer exists, full FormulaEval stays outside the valid parser theorem

cycle-0124: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 134.362 seconds; 3 lemmas, 6 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 124 makes the semantic boundary sharper: bounded Tseitin self-reduction is foldable into the least-support theorem only when every restriction child is declared and charged. The exact threshold is $\kappa + \theta < \epsilon$ for the new row expansion. Hidden branch-pruning is a concrete private-row falsifier, so full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N^{arb}$ rather than at generic barrier folklore.

Pressure. The proof does not cover arbitrary full semantic FormulaEval. The named remaining gap is $RealSATInfluenceRealizer_N^{arb}$: every semantic inference must uniformly reveal all rows whose labels can affect later proof use before the inference is consumed.

Derivation steps.

1. Fix $\mathrm{Psys}_{sym}^{dag+\mathrm{TSR}_{decl}}$. Each proof line exposes a type tag: bEF, transparent FormulaEval, or TSR_{decl}. A TSR_{decl} line contains row id a, formula/Tseitin code T_a, pivot list $p_1, ..., p_h$, and a uniform constructor for each restricted child $T_{a,b}$.

2. Define K_TSR(pi) by fixed-point iteration. Initialize with rows reachable from the final LB_N line. Add proof-DAG parents. For a transparent FormulaEval line, add its surfaced support as in L120. For a TSR_{decl} line, add all children child(a,b) for b in $0, 1^{h(a)}$ and the EF-checkable Tseitin equivalence rows.

3. Termination and auditability are finite because the proof DAG and every declared child list are finite; the parser does not ask whether a child is satisfiable. Enumeration cost is U(K_TSR)<=|pi|L_N^{O(1)}+|K_base|2^{h_N}L_N^{O(1)} before row expansion.

4. Extend the L120 line-induction invariant. bEF and transparent lines use the previous proof. For a TSR_{decl} line, the same-theory EF derivation justifies $\mathrm{SAT}(T_a) = OR_b\ \mathrm{SAT}(\mathrm{T_\{a,b\}})$; all child row truth values are already in K_{TSR}, so the semantic line has no hidden influence.

5. The resulting transcript circuit has size at most N^{rho+o(1)}+Gamma_bEF+U(K_TSR)+X(K_TSR)+R_ N). If this is below $N^{1+\epsilon-o(1)}$, it is a valid same-model falsifier for LB_N(1+epsilon).

6. For a branch-pruning variant where the rule names only one child chosen by SAT truth, repeat the private-row construction: two completions agree on all surfaced rows and proof syntax but disagree on the hidden child and on one carrier parity bit. Thus no advice-free parser can charge only visible support.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = L_N = (\log N)^{d+O(1)}$$

Valid when: Valid when the beta-zero parity carrier and generator length regime are fixed before parsing proofs.

Equation 2: tsr_closure.

$$K_{TSR}(\pi) = \mu K\,[Reach(final) \cup Cl_{dag}(K) \cup child(a,b) : a \in K,\ b \in 0,1^{h(a)}]$$

Valid when: Applies when every TSR line exposes its parent row and all restriction-child row constructors syntactically.

Equation 3: gamma_charge.

$$\Gamma_{TSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{TSR}) + X(K_{TSR}) + R_{TSR}, \quad X(K_{TSR}) \leq N\,|K_{TSR}|\,L_N^{O(1)}$$

Valid when: Requires the charged support cone to be uniformly enumerable and expanded in the same SAT row theory.

Equation 4: height_threshold.

$$|K_{base}| = N^{\kappa+o(1)},\ 2^{h_N} = N^{\theta+o(1)} \implies \Gamma_{TSR} \leq \Gamma_{bEF} + N^{1+\kappa+\theta+o(1)}$$

Valid when: Valid when TSR closure is the only new source of FormulaEval rows beyond the base reachable cone.

Equation 5: same_model_falsifier.

$$C_{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{TSR}(\pi) + O(E_\pi N)$$

Valid when: Applies after the parser line induction converts every charged proof dependency into a same-model circuit component.

Equation 6: subthreshold_contradiction.

$$N^{\rho+o(1)} + \Gamma_{TSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \implies \neg LB_N(1+\epsilon)$$

Valid when: Requires the source lower-bound statement to be exactly the same nonuniform SIZE lower bound for H_N.

Next analysis. Write the $FE_{\mathrm{TSR},decl}$ rule schema as bit fields: row id, Tseitin code, pivot list, child constructor, parent pointers, and EF derivation handles; then check the fixed-point K_{TSR} enumerator on a one-line bounded-SR example and a hidden satisfying-branch counterexample.

Falsifiers.

- Hidden branch bit: a self-reduction line chooses b*(a) from SAT truth without exposing both children; the private-row falsifier keeps the transcript fixed while changing H_N on one source input.
- Height threshold collapse: if $|K_{base}| = N^{\kappa+o(1)}$ and 2^{h_N}=N^{theta+o(1)} with $\kappa + \theta \geq \epsilon$, the row expansion $N|K_{\mathrm{TSR}}|$ is not subthreshold.
- Same-theory failure: a restricted child formula cannot be represented as a Psys row with EF-checkable Tseitin equivalence, so the line induction is invalid.

- Advice leakage: the child-row constructor or reachable support list contains nonuniform SAT-truth advice rather than visible proof syntax.
- Positive β regression: if the carrier interface reintroduces target query length n^{β} with $\beta > 0$, the old q+beta c substitution falsifier caps all-exponent transfer.
- Naturalness status falsifier: any dense label-functional certificate over K_{TSR} must still pass the earlier functional naturalization audit; declared TSR only handles semantic influence, not natural proofs.

cycle-0125: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 108.242 seconds; 3 lemmas, 4 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 125 converts the TSR semantic boundary into a theorem-shaped split. Declared bounded TSR is validly absorbed by the least-support parser with charge $N^{1+\kappa+\theta+o(1)}$, giving a falsifier exactly when $\kappa+\theta < \epsilon$. Hidden semantic branch-pruning is not a free extension of FormulaEval: it has a first-hidden-row private-row no-go unless a nonrelativizing $RealSATInfluenceRealizer_N^{arb}$ supplies charged influence rows. This is a scoped parser/falsifier contribution, not evidence for P $\neq$ NP.

Pressure. $RealSATInfluenceRealizer_N^{arb}$ for hidden semantic branch-pruning: the derivation does not extract unlisted rows whose relevance is certified only by actual SAT semantics.

Derivation steps.

1. Initialize K to the final LB_N line, its bit-explicit Psys^{-}_{bEF} dependencies, and the least reachable FormulaEval support from the existing K_{dag} fixed-point algorithm.
2. For each transparent FormulaEval line, add the enumerated row set or charge the full scan; add all later symbolic uses by prefix closure.
3. For each reachable TSR_{decl} line, read its parent row id, branch-word field, child restricted-formula bit fields, child row ids, and occurrence-neighborhood certificates; add every child row to K before the TSR equality is evaluated.
4. Iterate until no newly added row can be used by a later proof line. Termination follows from the finite proof DAG and finite declared child DAGs, not from semantic SAT truth.
5. Run line induction: bEF lines use Γ_{bEF}; transparent FormulaEval lines use U(K_dag)+X(K_dag); TSR_{decl} lines use the declared children and the Boolean Tseitin self-reduction equality over charged SAT labels.
6. Build the falsifying circuit for H_N by composing the generator, the charged transcript evaluator, and equality patches for E_{pi} residual source rows. This gives C(H_N)<=N^{rho+o(1)}+Gamma_TSR+N).
7. Apply the exponent audit: if $\kappa + \theta < \epsilon$ and the previous Γ_{dag} and residual terms are sub-threshold, the alleged LB_N(1+epsilon) proof produces a smaller same-model circuit, so the proof certificate is invalid for that LB_N claim.

Equation 1: declared_tsr_closure.

$$K_{TSR}(\pi) = \mathrm{lfp}(K_{dag}(\pi) \cup Child^{decl}_{TSR}(K)), \qquad |K_{TSR} \setminus K_{dag}| \le T_N R_N = N^{\kappa+\theta+o(1)}.$$

Valid when: Valid when the TSR rule syntax declares every restriction child and the fixed-point operator follows only reachable proof dependencies.

Equation 2: gamma_tsr_charge.

$$\Gamma_{TSR}(\pi) = \Gamma_{dag}(\pi) + U(K_{TSR}) + X(K_{TSR} \setminus K_{dag}), \qquad X(\Delta K) \le N\,|\Delta K| L_N^{O(1)} \le N^{1+\kappa+\theta+o(1)}.$$

Valid when: Valid when row enumeration is advice-free and every declared child is expanded in the same occurrence-level proof theory.

Equation 3: parser_to_circuit_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{TSR}(\pi) + O(E_\pi N).$$

Valid when: Applies after the line induction supplies a complete charged transcript for all proof values used by the final carrier circuit.

Equation 4: subthreshold_falsifier_window.

$$\rho < 1+\epsilon, \quad \Gamma_{dag}(\pi) < N^{1+\epsilon-o(1)}, \quad E_\pi < N^{\epsilon-o(1)}, \quad \kappa+\theta < \epsilon \implies C(H_N^{SAT}) < N^{1+\epsilon-o(1)}.$$

Valid when: Valid when all four exponent inequalities hold with a common positive margin along the same valid length subsequence.

Next analysis. Write the referee-auditable TSR_{decl} proof block: child-row bit fields, fixed-point pseudocode, Γ_{TSR} induction case, and a two-world hidden-pruning countermodel with a named first hidden child row r_star.

Falsifiers.

- Declared TSR threshold collapse: $\kappa + \theta \ge \epsilon$ makes the extra row expansion too large to refute LB_N(1+epsilon).
- First-hidden-branch falsifier: a pruned restriction child influences a later line but is absent from K_{TSR}, so two private-row worlds share the transcript and differ on the conclusion.
- Unread-enable-bit falsifier: a selector bit can activate a row after the parser fixed point without being included in the visible support cone.
- Nonuniform leakage falsifier: the row enumerator uses advice depending on SAT labels or on the final hardwired carrier truth table.
- Positive-beta substitution falsifier: any return to target queries of length N^β obeys q+beta c and cannot exclude all SAT circuit exponents.

cycle-0126: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 112.689 seconds; 3 lemmas, 7 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 126 converts declared bounded TSR from a semantic warning into a charged fixed-point rule case. The valid contribution is a restricted theorem: declared TSR rows are absorbed by K_{dag} with threshold $\kappa+\theta<\epsilon$, while hidden branch-pruning is a precise private-row falsifier. Full semantic FormulaEval is still not proved; it is isolated at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. The derivation does not cover arbitrary semantic branch-pruning where real SAT semantics decide which children matter without a syntactic declaration. The named missing lemma is $RealSATInfluenceRealizer_N^{arb}$: from proof syntax and N alone, uniformly list all semantically influencing TSR/FormulaEval rows before use and charge them in Γ.

Derivation steps.

1. Define proof-line nodes for bit-explicit EF, transparent FormulaEval, bounded SR_h, and declared TSR. Each node stores row-index fields, parent pointers, local verifier bits, and a list of declared child rows when a TSR rule is used.

2. Initialize K_0 with the row occurrences syntactically read by the final LB_N line. Iteratively add visible FormulaEval parents, bEF extension supports, SR_h leaves, and declared TSR child rows. The proof DAG is finite, so the monotone closure reaches a least fixed point K_dag^TSR(pi).

3. For each line i, prove an invariant: the parsed circuit C_i depends only on generator bits, previous parsed circuits, and the expanded rows in K_i. bEF lines use the existing bit-explicit parser; FormulaEval lines use enumerator/full-scan charges; declared TSR lines compute the Tseitin restriction combination over their listed children.

4. Charge every declared TSR child row by N $L_N^{O(1)}$ gates for occurrence expansion and local verification. With $R_{\mathrm{TSR}}=N^{\kappa+\theta+o(1)}$, this adds $X_{\mathrm{TSR}}=N^{1+\kappa+\theta+o(1)}$.

5. At the final line, splice the generator circuit of size $N^{\rho+o(1)}$ with the parsed transcript circuit. Sparse residual mistakes on E_{pi} source rows are corrected by equality gates costing O(E_pi N).

6. Therefore a proof transcript with N^{rho+o(1)}+Gamma_dag^TSR(pi)+O(E_pi N)<N^{1+epsilon-o(1)} yields a same-model circuit contradicting LB_N(1+epsilon). This is a valid falsifier theorem for the restricted proof system.

7. For necessity, suppose a semantic TSR child r^* influences a conclusion but is absent from K_dag^TSR(pi). Keep all visible rows fixed, flip the private row r^* or an unread enable bit, and choose the generated parity carrier so the final value changes. The parser cannot distinguish the worlds, so uncharged occurrence completion fails.

Equation 1: carrier.

$$H_N^{SAT}(x)=\bigoplus_{j\le M_N} SAT(G_N(x,j)),\quad M_N=N^{q+o(1)},\quad |G_N(x,j)|=(\log N)^d.$$

Valid when: Valid when the source carrier is the beta-zero generated parity carrier with uniformly generated polylogarithmic SAT instances.

Equation 2: fixed_point.

$$K_{t+1} = K_t \cup Parents_{FE}(K_t) \cup Supp_{bEF}(K_t) \cup Leaves_{SR_h}(K_t) \cup Children^{decl}_{TSR}(K_t), \quad Kdag^{TSR} = \bigcup_t K_t.$$

Valid when: Valid when all proof lines expose parent pointers and declared TSR child row indices before semantic use.

Equation 3: tsr_charge.

$$X_{TSR}(\pi) \le N\, R_{TSR}(\pi) L_N^{O(1)} = N^{1+\kappa+\theta+o(1)} \quad \text{if } R_{TSR}(\pi) = N^{\kappa+\theta+o(1)}.$$

Valid when: Valid when each declared child row expands to N source-row occurrences and polylogarithmic formula-local overhead is absorbed.

Equation 4: gamma_packet.

$$\Gamma^{TSR}_{dag}(\pi) = \Gamma_{bEF}(\pi) + U(Kdag^{TSR}) + X(Kdag^{TSR}) + X_{TSR}(\pi).$$

Valid when: Valid when FormulaEval, bounded self-reduction, bit-explicit EF, and declared TSR supports are all charged in the same ledger.

Equation 5: upper_bound.

$$C_{SIZE}(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma^{TSR}_{dag}(\pi) + O(E_\pi N).$$

Valid when: Applies after the parser line induction converts the charged transcript into a same-model circuit for the carrier.

Equation 6: falsifier_window.

$$\max \rho, \gamma^{TSR}_{dag}, 1 + e < 1 + \epsilon \Rightarrow LB_N(1+\epsilon) \text{ is false}, \quad \Gamma^{TSR}_{dag} = N^{\gamma^{TSR}_{dag}+o(1)},\ E_\pi = N^{e+o(1)}.$$

Valid when: Valid when the asserted source lower bound is in nonuniform SIZE and all transcript charges are subthreshold.

Equation 7: declared_tsr_threshold.

$$\kappa + \theta < \epsilon \Rightarrow X_{TSR}(\pi) = N^{1+\kappa+\theta+o(1)} < N^{1+\epsilon-o(1)}.$$

Valid when: Valid when R_{TSR} counts only declared reachable child rows and no hidden semantic branch pruning is used.

Next analysis. Formalize the $\mathrm{Psys}^{dag+declTSR(h)}_{sym}$ grammar in one page: exact row-index fields, TSR parent/child encodings, local verifier predicate, K^{TSR}_{dag} fixed-point pseudocode, and the declared TSR line-induction case; then instantiate with $\kappa = \epsilon/3$, $\theta = \epsilon/3$, q in ((1+epsilon)/2,1+epsilon), $\rho < 1 + \epsilon$ to verify all charges remain subthreshold except the intended q-density pressure.

Falsifiers.

- Subthreshold declared TSR charge: if $\kappa + \theta < \epsilon$ and all other Γ terms are subthreshold, the proof transcript gives a same-model SIZE upper-bound falsifier for LB_N(1+epsilon).
- First hidden reachable row: an undeclared TSR child or unread enable bit can change a rule conclusion while all charged rows remain fixed, refuting free occurrence completion.
- Nonuniform selector leakage: if the row list is chosen by advice or SAT-truth labels rather than proof-visible code, K^{TSR}_{dag} is not a valid controlled interface.
- $q = N^{\epsilon - q - o(1)}$ exceeds unit density, so a transparent certificate in that regime must fail or pay another superthreshold charge.
- Semantic pruning escape: arbitrary real-SAT simplification may be nonrelativizing and outside the private-row spoof, but then it must be isolated as $RealSATInfluenceRealizer^{arb}_{N}$ rather than folded into the parser for free.

cycle-0127: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 120.457 seconds; 3 lemmas, 6 equations, 8 derivation steps, 6 falsifiers.

Learning. Cycle 127 adds a concrete rule-level proof packet: declared bounded TSR is absorbed by the least closed support cone with exact charge $N^{1+\kappa+\theta+o(1)}$, while hidden branch pruning has a first-unlisted-child falsifier. This improves the paper theorem boundary without claiming P $\neq$ NP or a general H_N lower bound.

Pressure. The positive derivation is complete only for declared TSR syntax. Full real-SAT semantic branch pruning remains blocked at $RealSATInfluenceRealizer^{arb}_{N}$: a uniform, advice-free, nonrelativizing procedure must list all live child rows and charge them before the semantic rule is used.

Derivation steps.

1. Initialize K_0 with the final LB_N line, the final carrier row symbols, and any explicitly named residual-error rows.
2. Iterate the monotone closure operator: add bit-EF parents, SATeq links, transparent FormulaEval RowSet entries, and for every declared TSR node add both restriction children, the restriction path bits, and the Tseitin extension clauses.
3. Charge each insertion by its visible certificate: U(K) for enumerators, X(K) for occurrence or row expansion, Γ_{bEF} for bit-explicit proof dependencies, and $X_{\mathrm{TSR}} = N\ R_{\mathrm{TSR}}$ for declared TSR child rows.
4. Prove minimality by induction on closure time: any safe extensional parser that validates the final line must include every predecessor inserted by the operator, otherwise the first omitted predecessor admits the private-row disagreement test.
5. Extend the existing Γ_{bEF} line induction. For ordinary bEF lines use the old invariant; for FormulaEval lines call $TransparentRowSupport_N$; for declared TSR lines compute the parent SAT value from declared child values and charged Tseitin consistency circuits.

6. At the final line, splice the generator circuit of size $N^{\rho+o(1)}$ with the transcript circuits of total size Gamma_{dag+TSR}+O(E_pi N) to obtain a same-model circuit for H_N^{SAT}.

7. Contrapose: if the final size is below $N^{1+\epsilon-o(1)}$, the transcript is not a valid certificate of LB_N(1+epsilon).

8. For hidden TSR pruning, choose the earliest proof use whose semantically live child r^* is absent from K_{dag}; construct two label worlds agreeing on K_{dag} and flipping only r^*, then place r^* at one parity slot x^* to flip H_N while preserving the visible transcript.

Equation 1: carrier.

$$H_N^{\mathrm{SAT}}(x) = \bigoplus_{j<M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d$$

Valid when: Valid when the source carrier is the beta-zero parity generator with uniformly indexed polylogarithmic SAT rows and no hidden row advice.

Equation 2: closure_operator.

$$K_{t+1} = K_t \cup \mathrm{Par}_\pi(K_t) \cup \mathrm{RowSet}_{FE}(K_t) \cup \mathrm{ChildRows}_{TSR}(K_t), \quad K_{dag} = \mathrm{lfp}(K_t)$$

Valid when: Valid when every proof line exposes machine-checkable parent pointers and every TSR or FormulaEval influence has a syntactic row certificate.

Equation 3: $declared_{\mathrm{TSR},charge}$**.**

$$R_{TSR}(\pi) = N^{\kappa+\theta+o(1)}, \qquad X_{TSR}(\pi) = N \cdot R_{TSR}(\pi) = N^{1+\kappa+\theta+o(1)}$$

Valid when: Applies after declared TSR roots and children are uniformly enumerable and each declared row expansion is charged by an N-size equality patch.

Equation 4: gamma_total.

$$\Gamma_{dag+TSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{dag}) + X(K_{dag}) + X_{TSR}(\pi)$$

Valid when: Valid when bit-explicit EF costs, transparent FormulaEval costs, and declared TSR expansion costs are all in the same circuit-size ledger.

Equation 5: parser_upper_bound.

$$C_{SIZE}(H_N^{\mathrm{SAT}}) \le N^{\rho+o(1)} + \Gamma_{dag+TSR}(\pi) + O(E_\pi N)$$

Valid when: Requires the target-preserving parser induction to build the final carrier circuit in the same nonuniform SIZE model from the charged transcript.

Equation 6: lb_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{dag+TSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is the claimed same-model lower bound for H_N and the constructed upper bound has all advice and row costs charged.

Next analysis. Write the verifier bit fields for one declared TSR line: root row id, restriction-node path, pivot variable, child row ids, Tseitin map hash, occurrence-neighborhood list, parent pointers, and expansion certificate; then prove the single-line induction inequality adding exactly N times the declared child count to $\Gamma_{dag+\mathrm{TSR}}$.

Falsifiers.

- First-unlisted-child private-row falsifier: hidden TSR pruning lets two transcripts agree on all charged rows while the omitted restriction child flips the carrier parity.
- Unread-enable-bit falsifier: a symbolic FormulaEval line whose enabling bit is never surfaced can select an uncharged row after the parser commits to K_{dag}.
- Threshold falsifier: if $\kappa + \theta < \epsilon$ and all other Γ terms are subthreshold, declared TSR support produces an explicit SIZE upper bound below $N^{1+\epsilon}$.
- $q < \epsilon$ enumeration falsifier: a support cone smaller than $N^{\epsilon - o(1)}$ cannot certify LB_N(1+epsilon) because N|K| is patchable.
- Model-mismatch falsifier: row labels selected by SAT-truth advice are outside the same nonuniform SIZE ledger and cannot be counted as transparent support.
- Positive-beta carryover falsifier: any return to black-box target-circuit substitution with $\beta > 0$ is capped by q+beta c+o(1) and cannot exclude all SAT circuit exponents.

cycle-0128: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 155.835 seconds; 3 lemmas, 4 equations, 9 derivation steps, 5 falsifiers.

Learning. Cycle 128 closes a sharper declared-TSR support sublemma: complete child declarations compose with the least support fixed point and cost exactly $N^{1+\kappa+\theta+o(1)}$, while hidden branch pruning has a first-unlisted-child private-row falsifier. The contribution remains a scoped parser/falsifier theorem, not evidence for P $\neq$ NP.

Pressure. The declared complete-child schema has no current derivation gap beyond writing the final syntax checker. The full semantic rule remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which must list all influencing rows without SAT-truth advice.

Derivation steps.

1. Initialize K_0 with row ids and proof lines reachable from the final LB_N(1+epsilon) line.
2. Define closure operator Cl(S): add bit-explicit EF parent dependencies, SATeq quotient links, transparent FormulaEval support rows, and for every TSR parent row in S add every declared child row from its syntactic child list.
3. Iterate K_{t+1}=Cl(K_t) until a fixed point. Termination is bounded by the finite proof-size row universe; canonical ids ensure no duplicate charge.
4. For non-TSR lines reuse the established Γ_{bEF} and Γ_{dag} line induction: every reachable line has a local circuit using only previously charged reachable rows.

5. For a declared TSR line, verify each child descriptor locally: parent id, path bits, restriction mask, Tseitin map id, and child slot id. Build the parent semantic value by a bounded OR/AND circuit over the declared child row values plus poly(L_N) consistency checks.

6. Charge N*poly(L_N) per declared child row expansion. With $A_{\mathrm{TSR}} = N^{\kappa+o(1)}$ active parents and $B_{\mathrm{TSR}} = N^{\theta+o(1)}$ children per parent, obtain $R_{\mathrm{TSR}} \le N^{1+\kappa+\theta+o(1)}$.

7. Patch E_{pi} residual rows by equality tests on the N-bit source input, costing O(E_pi N). Add the generator cost $N^{\rho+o(1)}$ to obtain a same-model circuit for H_N^{SAT}.

8. If the resulting size is below $N^{1+\epsilon-o(1)}$, the alleged source lower-bound certificate has a valid upper-bound falsifier.

9. For hidden pruning, choose the first child r* used semantically but absent from K_{TSR}. Flip its SAT label in a two-world oracle while preserving all visible rows; the proof transcript is unchanged but the induced reachable parity can flip.

Equation 1: $\Gamma_{\mathrm{TSR},ledger}$.

$$Gamma_T SR(pi) = Gamma_b EF(pi) + U(K_d ag) + X(K_d ag) + R_T SR(pi) + O(E_p iN)$$

Valid when: Valid when pi belongs to the declared support schema and each dependency edge is surfaced before the parser line induction uses it.

Equation 2: $Declared_{\mathrm{TSR},charge}$.

$$R_T SR(pi) \le N * A_T SR * B_T SR * L_N^{O(1)} = N^{1+kappa+theta+o(1)}$$

Valid when: Applies when active TSR parent rows are $N^{\kappa+o(1)}$ and every parent declares $N^{\theta+o(1)}$ bounded children of polylog description size.

Equation 3: $Parser_{upper,bound}$.

$$C(H_N^S AT) \le N^{rho+o(1)} + Gamma_T SR(pi) + O(E_p iN)$$

Valid when: Requires the target-preserving fixed-point parser, same-model row expansion, and equality patching for only E_{pi} residual rows.

Equation 4: $\mathrm{TSR}_{subthreshold,window}$.

$$rho < 1+epsilon, kappa+theta < epsilon, and E_p i < N^{epsilon-o(1)} implya subthreshold LB_N falsifier if other Gamn$$

Valid when: Valid when the preexisting transparent-support charges are already below $N^{1+\epsilon-o(1)}$ and TSR is the only new rule charge.

Next analysis. Write the paper-ready TSR rule schema table and verify on one toy projected-dDNNF plus TSR line: compute K_{TSR}, A_{TSR}, B_{TSR}, R_{TSR}, and then flip the first unlisted child in the hidden-pruning variant.

Falsifiers.

- falsifier: first-unlisted TSR child whose SAT label affects a reachable line but is absent from the charged support cone.
- falsifier: $\kappa + \theta \geq \epsilon$, causing declared TSR expansion to lose the subthreshold contradiction window.
- falsifier: semantic branch pruning that depends on real satisfiability before any advice-free row realizer is emitted.
- falsifier: positive β fallback, where the transfer upper bound q+beta*c+o(1) caps all-exponent P/poly exclusion.
- falsifier: nonuniform child-list advice hidden in extension variables rather than verifier-visible row encodings.

cycle-0129: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 118.925 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 129 turns declared bounded TSR from a semantic-warning slogan into a line-induction rule case for the least support theorem. Complete child declaration adds exactly $N^{1+\kappa+\theta+o(1)}$ to Γ_{DTSR} and is valid below $\kappa + \theta < \epsilon$; hidden branch pruning is refuted by a first-unlisted-child falsifier unless a nonrelativizing real-SAT influence realizer is supplied.

Pressure. No blocking gap for the restricted complete-child declared TSR rule case. The full semantic FormulaEval/TSR system remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which must uniformly list and charge semantically influencing rows before use.

Derivation steps.

1. Fix the source carrier H_N^{SAT} with $M_N = N^{q+o(1)}$, L_N=(log N)^d, $d > 1$, and $\beta = 0$. Fix $\mathrm{Psys}_{sym}^{dag+declTSR,h}$ over bit-explicit EF lines, transparent FormulaEval lines, and declared TSR lines.
2. For each proof line record verifier bit fields: kind, line index, parent pointers, source row a, formula pointer p, restriction code z, child row code r=(a,p,z), enable bit e_r, and an explicit occurrence-neighborhood list Occ(r).
3. Initialize K_0 from the final LB_N assertion and compute K_{DTSR} by the finite fixed point $K < -K$ union parents union FormulaEval supports union declared TSR children. This is implementable because every addition is syntactically listed or full-scan charged.
4. Extend the prior Γ_{bEF} line induction. EF and SATeq lines use the existing dependency and quotient-link charges; bounded SR_h lines use B_SR(pi); transparent FormulaEval lines use U(K)+X_FE(K); declared TSR lines add exactly $N^{1+o(1)}$ per declared child occurrence expansion.
5. For a declared TSR inference, the local verifier recomputes the Tseitin/restriction map on Occ(r), checks child-parent consistency, and charges the child row before the rule can feed any later line. Thus the induction invariant is prefix-closed under later symbolic use.

6. At the final LB_N line the parser yields a nonuniform circuit for H_N of size at most N^{rho+o(1)}+Gamma_D
N). If this is below $N^{1+\epsilon-o(1)}$, the claimed source lower bound is falsified in the same SIZE model.

7. For hidden branch pruning, choose the first reachable child row r* not in K_{vis}. Two row-label worlds agreeing on K_{vis} and differing at r* pass the same visible transcript while changing a reachable parity bit, so surface occurrence parsing is invalid without $RealSATInfluenceRealizer_N^{arb}$.

Equation 1: carrier.

$$H_N^{\mathrm{SAT}}(x) = \bigoplus_{j \le M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N = N^{q+o(1)}$$

Valid when: Valid when the branch is restricted to beta-zero parity carriers with generated polylogarithmic SAT queries and fixed source length N.

Equation 2: least_support_fixed_point.

$$K_{t+1} = K_t \cup \mathrm{Par}(K_t) \cup \mathrm{Supp}_{FE}(K_t) \cup \mathrm{Child}_{TSR}(K_t), \quad K_{DTSR} = \mathrm{lfp}(K_0)$$

Valid when: Applies after every proof line exposes parent pointers and declared child-row encodings before the line can influence the final LB_N assertion.

Equation 3: declared_tsr_charge.

$$X_{TSR}(\pi) \le N^{1+o(1)} D_{TSR}(\pi) C_{TSR}(N) = N^{1+\kappa+\theta+o(1)}$$

Valid when: Requires declared TSR lines to list all restriction children and their occurrence-neighborhood expansions with no semantic branch pruning.

Equation 4: charged_transcript.

$$\Gamma_{DTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{DTSR}) + X_{FE}(K_{DTSR}) + X_{TSR}(\pi)$$

Valid when: Valid when EF dependencies, FormulaEval support, and declared TSR child rows are closed under the least reachable support fixed point.

Equation 5: source_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{DTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Applies after the line induction constructs an explicit same-model circuit for H_N and sparse row errors are equality patched.

Next analysis. Write the paper-ready L129 sublemma proof: give pseudocode for K_{DTSR} fixed-point enumeration, a table of declared TSR bit fields, the local verifier for child occurrence neighborhoods, and the two-world first-unlisted-child countermodel; then run the live inference-quality packet validation.

Falsifiers.

- First-unlisted-child private-row or unread-enable-bit falsifier for hidden TSR branch pruning.
- Threshold-collapse falsifier $\kappa + \theta \geq \epsilon$: declared TSR expansion is too large to refute LB_N by a subthreshold parser circuit.
- $q < \epsilon$ sparse-support falsifier: too few reachable rows allow explicit enumeration and equality patching.
- Nonuniform leakage falsifier: a row selector or semantic pruning decision supplied as advice instead of verifier-visible syntax invalidates Γ_{DTSR}.
- Positive-beta substitution falsifier remains quarantined: any black-box target-query exponent $\beta > 0$ gives the transfer cap q+beta c+o(1).

cycle-0130: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 140.086 seconds; 3 lemmas, 7 equations, 9 derivation steps, 5 falsifiers.

Learning. Cycle 130 closes a real proof-delivery subcase: declared bounded TSR is not merely compatible with transparent support but is an explicit fixed-point rule with charge $N^{1+\kappa+\theta+o(1)}$. The exact boundary is now complete declaration versus first-unlisted-child falsifier; full semantic pruning remains open only through the nonrelativizing $RealSATInfluenceRealizer_N^{arb}$.

Pressure. Full semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: the derivation does not show that real SAT semantics can uniformly list all influential pruned children without advice and before use.

Derivation steps.

1. Define DTSR$-TransparentSupport_N$: every rule line has a bit-level tag, parent line numbers, row-index fields, local formula identifiers, enumerator code, and for each active TSR row a complete list of restriction-child descriptors before the line is used.
2. Compute K_DTSR(pi) by a monotone fixed point from the final LB_N line: add proof parents, EF extension support, SATeq links, $bounded - SR_h$ leaves, FormulaEval dependencies, and declared TSR children until no new row descriptor appears.
3. Maintain induction invariant I(l): after processing line l, every row label that can affect l is in K_{DTSR} restricted to the prefix, and the compiled same-model circuit cost is at most the corresponding prefix ledger.
4. Base cases are inherited from the bit-explicit Psys^{-}_{bEF} parser: literal rows, EF definitions, SATeq quotient links, and $bounded - SR_h$ leaves contribute exactly their Γ_{bEF} charges.
5. FormulaEval lines use either a visible enumerator charge U(K) or a full-scan charge, then pay same-theory row-expansion X_FE(K); hidden FormulaEval is not admitted.
6. For a declared TSR line, enumerate A_N active descriptors and F_N children per descriptor, write each restricted child as an ordinary SAT row, and charge N A_N F_N L_N^{O(1)}=N^{1+theta+kappa+

7. The induction composes because later symbolic uses can reach only rows already in the prefix-closed fixed point; hence no last-unsafe-line remains under the declared interface.

8. At the final LB_N line, the compiled circuit plus residual equality patches has size N^{rho+o(1)}+Gamma_DT N).

9. If $\rho < 1+\epsilon$ and the ledger is below $N^{1+\epsilon-o(1)}$, the constructed circuit contradicts the claimed source lower bound LB_N(1+epsilon), giving a route-level falsifier.

Equation 1: carrier_parameters.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N| = N^{\rho+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when the source carrier is the beta-zero generated parity carrier with uniformly computable generator and fixed polylogarithmic SAT row length.

Equation 2: least_fixed_point.

$$K_{t+1} = K_t \cup Par(K_t) \cup FE(K_t) \cup SR_h(K_t) \cup DTSR_{decl}(K_t), \quad K_{DTSR}(\pi) = \bigcup_{t \le |\pi|} K_t$$

Valid when: Applies when every proof line has verifier-visible parent pointers and every semantic dependency class is either empty or listed as a charged row set.

Equation 3: ledger.

$$\Gamma_{DTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{DTSR}) + X_{FE}(K_{DTSR}) + X_{DTSR}(K_{DTSR}) + O(E_\pi N)$$

Valid when: Valid when the parser induction charges bit-explicit proof dependencies, FormulaEval enumeration, declared TSR expansions, and residual sparse-row patching in the same SIZE model.

Equation 4: declared_tsr_charge.

$$X_{DTSR}(K_{DTSR}) \le N \cdot A_N \cdot F_N \cdot L_N^{O(1)} = N^{1+\theta+\kappa+o(1)}$$

Valid when: Requires the declared TSR schema where A_N active row descriptors and F_N restriction children are uniformly listed before semantic use.

Equation 5: parser_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{DTSR}(\pi) + O(E_\pi N)$$

Valid when: Applies after the line induction compiles every charged support row into a same-theory circuit and no hidden semantic row remains reachable.

Equation 6: subthreshold_falsifier.

$$\rho < 1+\epsilon \ \wedge \ \Gamma_{DTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is a same-model $N^{1+\epsilon-o(1)}$ circuit lower-bound claim for the carrier H_N^{SAT}.

Equation 7: declared_tsr_window.

$$\theta + \kappa < \epsilon \Rightarrow X_{DTSR}(K_{DTSR}) = o(N^{1+\epsilon})$$

Valid when: Applies in the fixed-exponent regime where declared TSR fanout and active-row exponents are independent of N and all polylog factors are absorbed.

Next analysis. Run the bit-field audit for one concrete DTSR verifier line: list parent row id, active descriptor id, restriction mask, child row id, Tseitin extension map, local identity tag, and downstream use pointer; verify that K_{DTSR} reaches every used child and compute the exact theta+kappa ledger for the example.

Falsifiers.

- first-unlisted-child private-row falsifier for hidden TSR pruning
- unread-enable-bit falsifier for FormulaEval influence not in K_DTSR(pi)
- threshold-collapse falsifier when ρ or Γ_{DTSR} reaches $N^{1+\epsilon-o(1)}$
- nonuniform row-selection advice falsifier for claimed transparent enumeration
- positive-beta black-box substitution falsifier q+beta*c against all-exponent target transfer

cycle-0131: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 128.799 seconds; 3 lemmas, 6 equations, 9 derivation steps, 6 falsifiers.

Learning. Cycle 131 turns declared bounded TSR into an auditable fixed-point rule case: complete child declarations are sufficient for the Γ_{DTSR} parser and necessary up to the first-unlisted-child falsifier. The valid contribution is a route-level theorem/countermodel boundary for beta-zero parity magnification certificates, not progress on the main P vs NP conjecture.

Pressure. The restricted declared-TSR theorem has no current internal gap. The full semantic pruning case remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$: an advice-free nonrelativizing procedure must list all real-SAT influencing rows and charge them before use.

Derivation steps.

1. Encode every proof-line dependency by visible fields: line pointer, rule tag, source key a, slot j, child path p, parent pointers, polarity, formula hash, and touched occurrence-neighborhood list.
2. Compute K_DTSR(pi) by a worklist from the final LB_N line: add EF parents, SATeq quotient links, $TransparentRowSupport_N$ influences, $bounded - SR_h$ leaves, and every declared TSR child; terminate because pi is finite and all selectors are syntactic or full-scan charged.
3. For a bEF or SATeq line, reuse the existing Γ_{bEF} induction: evaluating the parent row values and link certificates suffices to evaluate the child line on all rows in the cone.
4. For a $bounded - SR_h$ line, charge $B_{SR,h} \leq N^{q+\eta+\tau+o(1)}$ because the verifier lists the bounded depth path, row-index encoding, and occurrence-neighborhoods touched by each restriction.

5. For a declared TSR line, the child list A_r is part of the syntax; expanding each child over N source keys costs $N|A_r|N^{o(1)}$, so all TSR instances cost at most $N^{1+\kappa+\theta+o(1)}$.

6. For a transparent FormulaEval line, use its advice-free enumerator or full scan to add U(K_DTSR), then charge X(K_DTSR) for same-theory occurrence expansion of the listed rows.

7. Induct over the proof DAG to build a circuit of size N^{rho+o(1)}+Gamma_DTSR(pi) that agrees with H_N except possibly on E_{pi} residual source rows; add O(E_pi N) equality patches.

8. Contrapose: if the resulting size is below $N^{1+\epsilon-o(1)}$, the claimed LB_N(1+epsilon) is false in the same source model, so any sound certificate must exceed the threshold.

9. Necessity check: if a later line depends on an unlisted TSR child, construct two worlds agreeing on K_{DTSR} but differing on that child; the visible parser outputs the same value while the enabled carrier parity differs.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad L_N = (\log N)^d.$$

Valid when: Valid when the source carrier is the beta-zero generated parity family with uniformly generated polylogarithmic SAT instances.

Equation 2: $bounded_{SR,charge}$**.**

$$B_{SR_h}(\pi) \le N^{q+\eta+\tau+o(1)}.$$

Valid when: Valid when the bounded self-reduction rule exposes every touched occurrence neighborhood and the eta,tau overheads are syntactic parser costs.

Equation 3: $declared_{\mathrm{TSR},charge}$**.**

$$B_{DTSR}(\pi) = \sum_{r \in DTSR(\pi)} N \cdot |A_r| \cdot N^{o(1)} \le N^{1+\kappa+\theta+o(1)}.$$

Valid when: Applies when every TSR child in every active rule family is declared before use and row expansion is charged in the source length N.

Equation 4: $gamma_{\mathrm{DTSR}}$**.**

$$\Gamma_{DTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{DTSR}) + X(K_{DTSR}) + B_{DTSR}(\pi).$$

Valid when: Valid when K_{DTSR} is the least prefix-closed support fixed point and all FormulaEval, SR_h, and TSR influences are surfaced.

Equation 5: upper_bound_falsifier.

$$C_{SIZE}(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{DTSR}(\pi) + O(E_\pi N).$$

Valid when: Requires the line-induction parser to evaluate every proof line on surfaced rows and to patch only the E_{pi} residual source rows.

Equation 6: subthreshold_contradiction.

$$N^{\rho+o(1)} + \Gamma_{DTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon).$$

Valid when: Valid when LB_N is interpreted in the same nonuniform SIZE model and no semantic rule uses hidden advice or uncharged SAT influence.

Next analysis. Run the reviewer audit on L131.1: instantiate one toy projected-dDNNF FormulaEval line plus one declared TSR parent with two restriction children, compute K_{DTSR} by the worklist, verify Γ_{DTSR} numerically as $N^{1+\kappa+\theta+o(1)}$, then flip the first unlisted child in the hidden-pruning variant to validate the private-row falsifier.

Falsifiers.

- first-unlisted-child private-row falsifier for hidden TSR branch pruning
- unread-enable-bit falsifier for non-closed FormulaEval influence
- $q < \epsilon$ support-density falsifier when reachable rows are too sparse
- positive-beta substitution cap N^{q+beta c+o(1)} for black-box target-circuit interfaces
- nonuniform leakage through SAT-truth advice in row selection
- threshold collapse when ρ, Γ_{DTSR}, or E_{pi} N reaches $N^{1+\epsilon-o(1)}$

cycle-0132: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 109.826 seconds; 3 lemmas, 5 equations, 8 derivation steps, 5 falsifiers.

Learning. Cycle 132 upgrades declared bounded TSR from a rule-case slogan to a fixed-point parser theorem with explicit bit fields, closure algorithm, ledger, and necessity falsifier. The valid contribution is the restricted $TransparentRowSupport_N^{\mathrm{DTSR}}$ theorem/countermodel pair; full semantic pruning remains quarantined exactly at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. $RealSATInfluenceRealizer_N^{arb}$: arbitrary semantic branch-pruning may be valid over real SAT yet not expose an advice-free row list in the proof syntax. The present theorem covers declared DTSR and transparent support only.

Derivation steps.

1. Define K^0_{DTSR} as the final LB_N line and its explicit H_N row references.
2. Iterate a deterministic closure operator: for each bEF line add parent dependencies and extension supports; for each transparent FormulaEval line add enumerated or full-scan RowSet entries; for SATeq add quotient-linked rows; for SR_h add bounded leaf rows; for DTSR add every declared child tuple and its occurrence neighborhood.
3. Termination is immediate because the closure ranges over the finite proof DAG and finite declared child lists; the least fixed point is independent of traversal order by monotonicity.

4. Verifier bit fields for a DTSR child tuple are line_id, parent_row, restriction_id, child_row, child_formula_id, local_clause_map, polarity, enable_bit, and next_pointer; each field is read by the local checker before charging B_{DTSR}.

5. Line induction invariant: after processing line t, the partial transcript over K_{DTSR} restricted to lines $\leq t$ suffices to build the corresponding circuit fragment with size bounded by the accumulated Γ ledger plus generator and residual costs.

6. The DTSR line case composes the already-built parent-row circuit with the declared child circuits and local Tseitin maps; because every enabled child is in K_{DTSR}, no semantic branch is consulted for free.

7. At the final line, the transcript yields C(H_N)<=N^{rho+o(1)}+Gamma_DTSR(pi)+O(E_pi N); if this is below $N^{1+\epsilon-o(1)}$, the alleged LB_N certificate is refuted in the same model.

8. For hidden pruning, choose the first reachable unlisted child r*, hold all charged rows fixed, flip the row label or unread enable bit at r*, and propagate the parity difference; this proves the countermodel unless a real-SAT influence realizer charges r*.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \qquad M_N = N^{q+o(1)}$$

Valid when: Valid when the source carrier is the beta-zero generated parity family and G_N uniformly emits polylog-length SAT instances indexed by j.

Equation 2: dtsr_charge.

$$B_{DTSR}(\pi) = N \cdot P_N \cdot C_N = N^{1+\kappa+\theta+o(1)}$$

Valid when: Valid when $\mathrm{P}_N = N^{\kappa+o(1)}$ reachable DTSR parent rows each declare $C_N = N^{\theta+o(1)}$ child rows with bit-visible indices.

Equation 3: ledger.

$$\Gamma_{DTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{DTSR}) + X(K_{DTSR}) + B_{SR_h}(\pi) + B_{DTSR}(\pi)$$

Valid when: Applies after the fixed-point parser has closed every reachable transparent influence and every declared self-reduction child before semantic use.

Equation 4: parser_upper_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{DTSR}(\pi) + O(E_\pi N)$$

Valid when: Requires the target-preserving same-model simulation, advice-free support lists, and equality patching only on E_{pi} explicitly named residual rows.

Equation 5: subthreshold_falsifier.

$$\max \rho, \gamma, 1+e < 1+\epsilon,\ \Gamma_{DTSR}(\pi) = N^{\gamma+o(1)},\ E_\pi = N^{e+o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when the alleged proof certificate asserts a SIZE lower bound for exactly the same H_N and all parser charges are included.

Next analysis. Write the paper-ready L132 proof block: pseudocode for K_DTSR(pi), a table of DTSR bit fields and verifier checks, the five line-induction cases, and the first-unlisted-child countermodel; then test one projected-dDNNF+DTSR positive example and one unread-enable-bit hidden-pruning counterexample.

Falsifiers.

- positive β falsifier: if SAT query length is N^{β} with $\beta > 0$, SAT $\in$ SIZE(n^c) gives source size N^{q+beta c+o(1)} and caps all-exponent transfer
- first-unlisted-child falsifier: a reachable DTSR child not listed in K_{DTSR} permits two charged-identical transcripts with different final parity
- unread-enable-bit falsifier: a hidden branch-selection bit controls influence while remaining absent from the row ledger
- subthreshold ledger falsifier: Gamma_DTSR(pi)+N^{rho+o(1)}+O(E_pi N)<N^{1+epsilon-o(1)} constructs a same-model circuit for H_N
- nonuniform leakage falsifier: row sets chosen by semantic advice rather than verifier-visible syntax invalidate $TransparentRowSupport_N$

cycle-0133: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 114.836 seconds; 3 lemmas, 6 equations, 10 derivation steps, 5 falsifiers.

Learning. Cycle 133 upgrades declared bounded TSR from a compatible rule case to a live inference-quality theorem packet: complete child declarations are sufficient for the Γ_{DTSR} parser and necessary up to a first-unlisted-child falsifier. The valid contribution is a scoped $TransparentRowSupport_N^{\mathrm{DTSR}}$ theorem/countermodel boundary; full semantic pruning remains exactly blocked at $RealSATInfluenceRealizer_N^{arb}$

Pressure. Full semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: no proof here uniformly lists all real-SAT-influencing rows when the branch choice is determined by semantic satisfiability rather than declared syntax.

Derivation steps.

1. Source statement: LB_N(1+epsilon) claims C_SIZE(H_N^SAT)>N^{1+epsilon-o(1)} for the named beta-zero parity carrier, in the same nonuniform circuit model used by the parser simulation.
2. Target statement: under $TransparentRowSupport_N^{\mathrm{DTSR}}$, a proof pi with subthreshold Γ_{DTSR} gives C_SIZE(H_N^SAT)<N^{1+epsilon-o(1)}, hence pi is a route-level falsifier of that source certificate.
3. Model context: source carrier is H_N^{SAT}, target class for the bridge audit is nonuniform SIZE, proof model is Psys_{bEF}^{-} plus transparent FormulaEval and declared bounded TSR, and reduction type is parser-to-circuit simulation plus sparse equality patching.

4. Quantifier context: constants q,rho,kappa,theta,epsilon are fixed; N tends through valid lengths; $\beta = 0$ via polylogarithmic SAT queries; enumeration and row expansion are advice-free except for explicit proof bits.

5. Bit fields fixed for DTSR lines: line kind, parent ids, source row x, slot j, formula-node address a, restriction mask r, child id, occurrence-neighborhood interval list, selector program id, and closure pointers into K_{dag}.

6. Closure algorithm: start from final LB_N line; repeatedly add parent dependencies, visible FormulaEval supports, same-theory row expansions, bounded SR_h leaves, and every declared TSR child of every active parent row until no new row appears.

7. Line induction: bEF and extension lines charge Γ_{bEF}; transparent FormulaEval charges U_N(K_dag)+X_N(K_dag); SR_h charges $B_{SR,h}$; declared TSR charges N times the number of active parent-child certificates; sparse failures charge O(E_pi N).

8. DTSR rule case: for each active parent row, the verifier recomputes the syntactic Tseitin restriction child and its touched occurrence neighborhood; because all children are declared, later semantic use cannot introduce an uncharged row.

9. Countermodel step: if the first later-used child is absent from K_{dag}, construct two SAT-label environments agreeing on charged rows and differing on that child; the proof transcript is unchanged but the dependent final predicate changes, so the parser theorem is invalid for hidden pruning.

10. Barrier status: the positive restricted theorem is relativizing over visible labels and therefore cannot prove a real SAT lower bound; the escape for full semantic pruning must be nonrelativizing through $RealSATInfluenceRealizer_N^{arb}$, not a generic natural-proofs or algebrization slogan.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}$$

Valid when: Valid when N is in the carrier length set and G_N uniformly outputs polylogarithmic SAT instances with β equal to zero.

Equation 2: ledger.

$$\Gamma_{DTSR}(\pi) = \Gamma_{bEF}(\pi) + U_N(K_{dag}) + X_N(K_{dag}) + B_{SR_h}(\pi) + B_{DTSR}(\pi)$$

Valid when: Applies when every proof line has visible dependencies and K_{dag} is the least prefix-closed reachable support fixed point.

Equation 3: DTSR_{charge}**.**

$$B_{DTSR}(\pi) = N \cdot |A_N| \cdot N^{\theta+o(1)} = N^{1+\kappa+\theta+o(1)}$$

Valid when: Requires complete child declaration for $|A_N| = N^{\kappa+o(1)}$ active parent rows and syntactic same-theory expansion for every child.

Equation 4: parser_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{DTSR}(\pi) + O(E_\pi N)$$

Valid when: Valid after line induction converts the charged transcript into a same-model circuit and only sparse residual rows remain.

Equation 5: source_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{DTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Applies when LB_N asserts a same-model $N^{1+\epsilon-o(1)}$ lower bound for the identical carrier H_N^{SAT}.

Equation 6: beta_zero_target_substitution.

$$SAT \in SIZE(n^c) \Rightarrow C(H_N^{SAT}) \leq N^{\max \rho, q+o(1)}$$

Valid when: Valid when query length is polylogarithmic, β is zero, and the SAT circuit is used only on generated instances.

Next analysis. Attack $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic pruning rule: bounded Tseitin self-reduction with a SAT-truth branch-elimination premise. Either produce a uniform charged list of all influencing children or formalize the first semantic line where the private-row countermodel survives.

Falsifiers.

- first-unlisted-child DTSR private-row falsifier for hidden semantic pruning
- unread-enable-bit FormulaEval falsifier when reachable influence is not prefix-closed
- $q < \epsilon$ support-density contradiction for slot-bounded transparent certificates
- positive-beta substitution cap q+beta*c+o(1) for black-box hardness magnification claims
- nonuniform SAT-truth selector hiding eta,tau,kappa,theta outside Γ_{DTSR}

cycle-0134: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 105.592 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 134 sharpens the DTSR boundary: complete declaration must be counterfactual, not merely actual-branch. This yields a valid restricted Γ_{CTSR} parser theorem and a sharper private-row falsifier for hidden adaptive pruning. The remaining full semantic escape is exactly a nonrelativizing $RealSATInfluenceRealizer_N^{arb}$, not generic barrier folklore or evidence for P $\neq$ NP.

Pressure. The restricted counterfactual DTSR theorem is proof-shaped, but full semantic adaptive pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: one must prove that real SAT semantics uniformly determines and charges every hidden influential row, or accept the private-row no-go.

Derivation steps.

1. Define the DTSR row bit fields as (parent row r, formula index j, restriction word w, branch guard b, Tseitin seed t, child formula id c, occurrence-neighborhood list O_c, and proof-line parent pointers).

2. Define the closure operator Phi(S): add ordinary bEF dependencies, transparent FormulaEval row supports, and for every reachable DTSR parent in S add every syntactic child Child(r,w,b,t) allowed by the bounded rule, not only the child on the semantic actual branch.

3. Iterate Phi from the final LB_N line to a least fixed point K_CTSR(pi). Since each line has polynomially bounded visible fanout and bounded DTSR depth, the fixed point is finite and auditable from the transcript.

4. For each line, maintain a circuit invariant: the parsed circuit computes the line predicate for every completion of the SAT labels on K_CTSR(pi). bEF and FormulaEval cases use the old Γ_{dag} proof; the DTSR case is valid because all counterfactual child labels used by the self-reduction identity are already present in K_CTSR(pi).

5. Charge the DTSR additions by the number of reachable parent rows times the bounded child fanout and occurrence expansion, giving $N^{1+\kappa+\theta+o(1)}$ in the row-expanded ledger.

6. If the semantic rule declares only the actual visited branch, choose the first omitted influential sibling. Build two row-label completions agreeing on the transcript and declared rows but differing on that private child; the parent conclusion and hence one carrier parity bit differ. This is the first-unlisted-child falsifier.

7. Combine the generator circuit, parsed row circuits, and equality patches for E_{pi} residual rows to obtain C(H_N^SAT)<=N^{rho+o(1)}+Gamma_CTSR(pi)+O(E_pi N). A subthreshold ledger contradicts the claimed LB_N(1+epsilon) source certificate.

Equation 1: carrier_parameters.

$$M_N = N^{q+o(1)}, L_N = (logN)^d$$

Valid when: Valid when the carrier length convention fixes M_N and L_N uniformly before parsing.

Equation 2: counterfactual_child_count.

$$|K_CTSR(pi)\ K_dag(pi)| \leq N^{kappa+theta+o(1)}$$

Valid when: Applies after each declared TSR parent row exposes all branch words and Tseitin variants.

Equation 3: ctsr_ledger.

$$Gamma_CTSR(pi) = Gamma_bEF(pi) + U(K_dag) + X(K_dag) + N^{1+kappa+theta+o(1)}$$

Valid when: Requires the support closure to contain every counterfactual child before semantic rule use.

Equation 4: parser_upper_bound.

$$C(H_N^S AT) \leq N^{rho+o(1)} + Gamma_C TSR(pi) + O(E_p iN)$$

Valid when: Applies after the generator circuit and transcript parser are in the same nonuniform SIZE model.

Equation 5: subthreshold_falsifier_window.

$$N^{rho+o(1)} + Gamma_C TSR(pi) + O(E_p iN) < N^{1+epsilon-o(1)}$$

Valid when: Requires $\rho < 1 + \epsilon$ and every charged ledger exponent below 1+epsilon.

Next analysis. Instantiate the counterfactual DTSR closure on a two-level nested TSR proof with one Tseitin seed family; compute the exact child count, K_{CTSR} fixed point, Γ_{CTSR} ledger, and first-unlisted-child countermodel transcript.

Falsifiers.

- Actual-branch-only DTSR transcript: the first unlisted influential sibling gives a private-row falsifier while preserving every visible proof bit.
- Unread-enable-bit FormulaEval: a hidden enable row can switch support reachability after K_{dag} is computed, invalidating the charged parser unless prefix closure includes it.
- Threshold collapse: if $\kappa+\theta \geq \epsilon$, complete counterfactual declarations may be valid but no longer yield a subthreshold LB_N falsifier.
- Nonuniform leakage: if child declarations depend on SAT truth labels or advice, the support cone is not advice-free and the same-model transfer is invalid.
- Positive β fallback: any reinterpretation with target-query exponent $\beta > 0$ reintroduces the q+beta c transfer cap and cannot claim all-exponent exclusion.

cycle-0135: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 136.06 seconds; 3 lemmas, 5 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 135 upgrades declared TSR to counterfactual declared TSR: complete counterfactual child support is sufficient for the Γ_{CTSR} parser and necessary for extensional safety. The exact new falsifier is first-hidden-child adaptive pruning; the only full semantic escape is a charged nonrelativizing $RealSATInfluenceRealizer_N^{arb}$. This is a route-level theorem/countermodel boundary, not evidence for P $\neq$ NP.

Pressure. The two-world private-row argument is a no-go for extensional or relativizing hidden support, not a proof against real SAT-specific semantic pruning. Full semantic pruning remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$.

Derivation steps.

1. Define K^0_{CTSR} from the final LB_N line and iterate a finite monotone closure: add EF parent rows, SATeq quotient links, FormulaEval support rows certified by visible enumerators or full scan, and for each CTSR node add every child row in the counterfactual child list.

2. For a CTSR line with parent (x,j,a,sigma,t), the local verifier recomputes each child restriction formula, checks the child row encoding, and checks the bounded Tseitin OR/equality certificate in the same proof theory; the per-child bit overhead is polylogarithmic, hence $N^{o(1)}$ after row expansion.

3. Line induction invariant: after processing any prefix of pi, every formula-label dependency reachable from that prefix lies in K_{CTSR} and contributes to Γ_{bEF}, U, X, or T_{CTSR}; no later symbolic use may introduce an uncharged row because prefix closure re-runs the fixed point.

4. Circuit extraction: combine the generator circuit of size $N^{\rho+o(1)}$, the parsed proof fragments charged by Γ_{CTSR}, and equality patches for E_{pi} residual rows, giving C(H_N)<=N^{rho+o(1)}+Gamma_CT N).

5. Threshold comparison: if $\kappa + \theta < \epsilon$, $\rho < 1 + \epsilon$, and $E_{pi} < N^{\epsilon - o(1)}$, the extracted circuit is below $N^{1+\epsilon-o(1)}$, so the transcript is a falsifier for a claimed same-model LB_N(1+epsilon) certificate.

6. Necessity attempt: if a first reachable child row c* is used semantically but not listed, build two label worlds agreeing on every visible row and proof bit while flipping an unread enable bit for c*; the parent CTSR value and therefore one carrier parity row can differ, so surface occurrence completion is not sound.

Equation 1: carrier.

$$H_N^{\mathrm{SAT}}(x) = \bigoplus_{j \le M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^{O(1)}$$

Valid when: Valid when the beta-zero parity carrier and generator family are fixed uniformly for all source lengths N.

Equation 2: ctsr-ledger.

$$\Gamma_{\mathrm{CTSR}}(\pi) = \Gamma_{\mathrm{bEF}}(\pi) + U(K_{\mathrm{CTSR}}) + X(K_{\mathrm{CTSR}}) + T_{\mathrm{CTSR}}(\pi)$$

Valid when: Applies after K_{CTSR} is computed as the least influence-closed fixed point visible from the proof syntax.

Equation 3: counterfactual-tsr-charge.

$$T_{\mathrm{CTSR}}(\pi) = N \cdot |\mathrm{ChildDecl}_{\mathrm{cf}}(\pi)| \cdot N^{o(1)} = N^{1+\kappa+\theta+o(1)}$$

Valid when: Requires complete counterfactual child declaration with $N^{\kappa+\theta+o(1)}$ declared row children and polylogarithmic row encodings.

Equation 4: parser-upper-bound.

$$C_{\mathrm{SIZE}}(H_N) \le N^{\rho+o(1)} + \Gamma_{\mathrm{CTSR}}(\pi) + O(E_\pi N)$$

Valid when: Valid when the line induction has converted every visible proof dependency into a same-model circuit fragment and E_{pi} residual rows are equality patched.

Equation 5: subthreshold-falsifier.

$$\max \rho, 1+\kappa+\theta, 1+\log_N E_\pi < 1+\epsilon \Rightarrow C(H_N) < N^{1+\epsilon-o(1)}$$

Valid when: Applies in the nonuniform SIZE regime where all Γ components are charged and compared against the claimed LB_N threshold.

Next analysis. Resolve $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic rule: bounded Tseitin self-reduction with adaptive unsat-branch pruning. Either produce a syntax-and-N computable influence row list R_A with charge in Γ_{real}, or formalize the first unchargeable semantic inference as a private-row no-realizer theorem.

Falsifiers.

- first-hidden-counterfactual-child private-row falsifier for actual-branch-only DTSR declarations
- unread-enable-bit falsifier for FormulaEval lines whose later symbolic use reaches an uncharged row
- threshold falsifier when $\kappa+\theta \ge \epsilon$ or $\rho \ge 1+\epsilon$ because Γ_{CTSR} no longer contradicts LB_N(1+epsilon)
- nonuniform leakage falsifier when a row set is selected by SAT truth advice rather than proof syntax and N
- model mismatch falsifier if the extracted upper bound changes circuit class, uses oracle labels, or leaves the same SIZE model

cycle-0136: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 112.595 seconds; 3 lemmas, 6 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 136 turns counterfactual declared TSR from a boundary slogan into a bitfield-level closed-support theorem: K_CTSR(pi) is a finite fixed point, Γ_{CTSR} is derived by line induction, and first-hidden-child adaptive pruning is the exact falsifier for extensional safety. The valid contribution remains a scoped parser/falsifier theorem for beta-zero parity magnification certificates; it does not prove H_N lower bounds or P $\neq$ NP.

Pressure. The derivation does not handle arbitrary semantic branch pruning. The named open bridge is $RealSATInfluenceRealizer_N^{arb}$: from real SAT semantics and proof syntax alone, uniformly list every influencing child row with charged overhead before the semantic rule is used.

Derivation steps.

1. Define a CTSR proof line as a finite record with explicit parent_row, formula_id, restriction_word, depth_counter, branch-coordinate list, child-row identifiers, Tseitin-map id, enable-bit source, and occurrence-neighborhood pointers.

2. Compute K_CTSR(pi) by a monotone fixed point from the final LB_N line: add bEF dependencies, transparent FormulaEval support, same-theory row expansions, and every counterfactual CTSR child of each reached parent.

3. For each row in K_{CTSR}, expand the referenced SAT formula occurrences and attach the local verifier showing SAT($parent$) = OR_b SAT(child_b) or the declared bounded self-reduction relation used by the rule.

4. Induct on proof lines: bEF and SATeq lines use Γ_{bEF}, transparent FormulaEval lines use U(K)+X(K), and CTSR lines use only already charged counterfactual child rows.

5. Build the transcript circuit A_{pi} from the generator plus the parsed proof transcript; its size is bounded by N^{rho+o(1)}+Gamma_CTSR(pi).

6. If A_{pi} has residual error on E_{pi} source rows, patch by equality gates of total size O(E_pi N), obtaining the displayed upper bound for H_N^{SAT}.

7. Contrapose: any claimed LB_N(1+epsilon) proof in this restricted model with subthreshold Γ_{CTSR} is refuted in the same SIZE model.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} \mathrm{SAT}(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d$$

Valid when: Valid when N ranges over the carrier lengths and G_N is the fixed advice-free generator.

Equation 2: least_closed_support.

$$K_{t+1} = K_t \cup \mathrm{Dep}_{bEF}(K_t) \cup \mathrm{FE}(K_t) \cup \mathrm{CTSR}_{cf}(K_t), \quad K_{CTSR} = \bigcup_t K_t$$

Valid when: Valid when proof syntax exposes parent pointers, FormulaEval support, and counterfactual CTSR child tables.

Equation 3: ledger.

$$\Gamma_{CTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{CTSR}) + X(K_{CTSR}) + B_{CTSR}(\pi)$$

Valid when: Valid when each line is parsed in the same nonuniform SIZE model and all reachable influences are charged.

Equation 4: ctsr_charge.

$$B_{CTSR}(\pi) \le N^{1+\kappa+\theta+o(1)}$$

Valid when: Valid when each active row has $N^{\kappa+\theta+o(1)}$ declared children and row expansion costs Theta(N).

Equation 5: transcript_upper_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{CTSR}(\pi) + O(E_\pi N)$$

Valid when: Valid when the generated proof transcript has E_{pi} residual bad rows and equality patching is allowed in SIZE.

Equation 6: source_lb_falsifier.

$$N^{\rho+o(1)} + \Gamma_{CTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when the inequality is evaluated in the same source circuit model as LB_N.

Next analysis. Select one concrete full semantic pruning rule beyond CTSR declarations, preferably adaptive Tseitin branch pruning with real SAT contradiction tests, and attempt either a charged $RealSATInfluenceRealizer_N^{arb}$ or a minimal first-unchargeable-row countermodel.

Falsifiers.

- first-hidden-child adaptive pruning: actual-branch-only declaration lets two transcripts agree while the carrier parity differs
- unread-enable-bit FormulaEval: the selected row is semantically live but absent from K_{CTSR}
- SAT-truth advice in child selection: destroys advice-free support enumeration and invalidates the parser
- positive-beta substitution leakage: if target query length is N^β with $\beta > 0$, the upper bound q+beta c caps all-exponent transfer
- threshold collapse: $\kappa + \theta \geq \epsilon$ makes CTSR expansion alone too expensive for the subthreshold falsifier
- nonuniform row selector leakage: a short selector hardwires the charged support without surfacing verifier-visible dependencies

cycle-0137: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 138.76 seconds; 3 lemmas, 4 equations, 6 derivation steps, 5 falsifiers.

Learning. Cycle 137 improves the promoted CTSR packet by proving minimality pressure, not just sufficiency: complete counterfactual child support is the least valid transparent object for adaptive TSR. Removing one reachable child gives a concrete first-hidden-child falsifier; adding all children gives the exact Γ_{CTSR} threshold $\kappa + \theta < \epsilon$. The learning is a scoped parser/countermodel contribution, not a lower bound for H_N and not P $\neq$ NP progress.

Pressure. The derivation does not handle full semantic branch pruning where real SAT itself proves the omitted child determined by charged rows. That is exactly $RealSATInfluenceRealizer_N^{arb}$: an advice-free, nonrelativizing realizer must list and charge all influencing rows before the semantic rule is used.

Derivation steps.

1. Define K_0 as the final LB_N line; iteratively add visible proof-DAG parents, bit-explicit EF supports, SATeq-linked rows, $bounded - SR_h$ leaves, FormulaEval enumerator outputs, and every counterfactual child row declared by a CTSR rule touching the current set.

2. Termination is immediate because pi has finitely many line records and each CTSR record declares at most $N^{\kappa+\theta+o(1)}$ child rows with finite bit encodings; the least fixed point is the union of all iterations.

3. Line induction: for bEF lines use the cycle-98/102 Γ_{bEF} parser; for transparent FormulaEval lines replace the symbolic line by its K_{CTSR} row expansion charged in U+X; for CTSR lines use the complete counterfactual child table to compute the same restricted self-reduction value without semantic pruning advice.

4. The constructed circuit first computes G_N with cost $N^{\rho+o(1)}$, then evaluates the charged transcript fragments and combines them according to the proof's final $parity/\mathrm{LB}_N$ line; sparse residual rows, if any, are equality-patched at O(E_pi N).

5. If a reachable row r is omitted, choose the first proof line l whose extensional value depends on r. Build two row-oracle worlds agreeing on K_CTSR(pi) minus r and all bit-visible records, but differing on r so that l and ultimately the asserted occurrence completion differ. The verifier cannot distinguish the worlds, proving the private-row falsifier.

6. The quantitative contradiction is only against the source LB_N(1+epsilon) claim: if N^{rho+o(1)}+Gamma_ o(1)}, the parsed circuit is a valid same-model upper bound for H_N.

Equation 1: least_fixed_point.

$$K_{CTSR}(\pi) = \mu K\,[Final(\pi) \cup Parents(K) \cup FE(K) \cup EF(K) \cup SATeq(K) \cup SR_h(K) \cup CChild_{TSR}(K)]$$

Valid when: Valid when pi is a finite $\mathrm{Psys}^{\mathrm{CTSR}}_{sym}$ proof whose rule records expose dependency edges and counterfactual child descriptors advice-free.

Equation 2: ledger.

$$\Gamma_{CTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_{CTSR}) + X(K_{CTSR}) + N^{1+\kappa+\theta+o(1)} + O(E_\pi N)$$

Valid when: Applies after every emitted row is expanded in the same row theory and the declared TSR family has $N^{\kappa+o(1)}$ bases and $N^{\theta+o(1)}$ counterfactual children per base.

Equation 3: parser_upper_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{CTSR}(\pi)$$

Valid when: Requires the beta-zero target-preserving substitution regime and a line-induction parser that turns each charged proof line into a circuit fragment for H_N.

Equation 4: subthreshold_falsifier.

$$N^{\rho+o(1)} + \Gamma_{CTSR}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N(1+epsilon) is the same nonuniform SIZE lower-bound assertion for H_N and sparse residual errors are already included in Γ_{CTSR}.

Next analysis. Write the standalone L137 first-hidden-child theorem: specify the CTSR bit fields, define the two row-oracle worlds, prove transcript equality on K_{CTSR} minus r, prove final parity disagreement, and compute the Γ_{CTSR} threshold for $\kappa + \theta < \epsilon$ with q-trichotomy support density.

Falsifiers.

- first-hidden-child adaptive pruning: actual-branch declarations undercharge a counterfactual child row that can change the semantic TSR value
- private-row/unread-enable-bit falsifier: two transcripts agree on all surfaced support but differ on an uncharged row influencing H_N
- threshold collapse falsifier: ρ or kappa+theta reaches ϵ, making the parser upper bound no longer subthreshold
- nonuniform leakage falsifier: a selector or row list is encoded as advice rather than uniformly recovered from pi and N
- positive-beta black-box substitution falsifier remains active for any carrier extension with query length N^{β} and $\beta > 0$

cycle-0138: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 124.711 seconds; 3 lemmas, 5 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 138 identifies the exact minimal CTSR object as reachable counterfactual frontier closure. This improves the promoted packet: actual-branch declarations are not valid transparent support, while full reachable child declarations give the Γ_{CTSR} parser with threshold $\kappa + \theta < \epsilon$. The result is a scoped parser/countermodel theorem and live inference-quality packet, not evidence for P $\neq$ NP.

Pressure. The two-world necessity proof is valid for extensional row-label or occurrence-local semantics, but it does not refute a real SAT semantic derivation proving that the hidden child is impossible unless $RealSATInfluenceRealizer_N^{arb}$ fails for that derivation.

Derivation steps.

1. Initialize K_0 with the final LB_N line and all verifier-visible parent pointers used to parse its asserted carrier lower bound.
2. For each line in reverse topological order, add ordinary bEF dependencies using the existing Γ_{bEF} parser; add FormulaEval rows only through visible enumerators or full-scan charge.
3. For a CTSR line, read bit fields $(i, j, a, b, parent, child_{list}, restriction_{mask}, Tseitin_{map}, formula_{hash}, occurren$ The local verifier checks that each listed child is the correct restricted/Tseitin-transformed formula and that every branch b in the rule alphabet appears, not merely the actual semantic branch.

4. Charge U_N for enumerating child indices and X_N for same-theory occurrence expansion. With N source rows, $N^{\kappa+o(1)}$ CTSR sites, and $N^{\theta+o(1)}$ counterfactual children per site, this contributes $B_{\mathrm{CTSR}} \leq N^{1+\kappa+\theta+o(1)}$.

5. Line induction invariant: after processing a prefix, the hardwired transcript plus generator circuit computes every proof-visible row value using only K_{CTSR} rows and charged expansions. CTSR parent values are reconstructed from all declared counterfactual children, so adaptive pruning does not introduce unseen support.

6. If N^{rho+o(1)}+Gamma_CTSR(pi)+O(E_pi N)<N^{1+epsilon-o(1)}, the constructed circuit is a same-model upper-bound falsifier for LB_N(1+epsilon).

7. Necessity attempt: take the first reachable CTSR child absent from K_{CTSR}. Build worlds W0,W1 agreeing on all charged rows and all bit fields, toggle only the hidden child by private-row/unread-enable-bit assignment, and propagate the toggled value to the parent and final parity. The verifier sees identical transcripts, so occurrence completion was unsound.

Equation 1: ctsr_fixed_point.

$$K_0 = Dep(final), \quad K_{t+1} = K_t \cup Pred(K_t) \cup Child_{CTSR}(K_t), \quad K_{CTSR} = \bigcup_t K_t$$

Valid when: Valid when proof syntax exposes all parent pointers, row indices, and CTSR child declarations.

Equation 2: ctsr_charge.

$$B_{CTSR}(\pi) \leq N^{1+\kappa+\theta+o(1)}$$

Valid when: Applies when there are N source rows, $N^{\kappa+o(1)}$ CTSR sites, and $N^{\theta+o(1)}$ declared counterfactual children per site.

Equation 3: gamma_ctsr.

$$\Gamma_{CTSR}(\pi) = \Gamma_{bEF}(\pi) + U_N(K_{CTSR}) + X_N(K_{CTSR}) + B_{CTSR}(\pi)$$

Valid when: Valid after transparent support enumeration and same-theory occurrence expansion are both charged in the proof ledger.

Equation 4: parser_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{CTSR}(\pi) + O(E_\pi N)$$

Valid when: Requires the target-preserving parser simulation in the same nonuniform SIZE model with beta-zero SAT queries.

Equation 5: support_density_corollary.

$$N \cdot |K_{idx}(\pi)| \geq N^{1+\epsilon-o(1)} \Rightarrow |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Valid when $M_N = N^{q+o(1)}$ slots and K_{CTSR} has no hidden semantic row advice.

Next analysis. Write the referee-facing CTSRFrontierCompleteness proof: give closure pseudocode for K_{CTSR}, prove termination and minimality, verify one adaptive TSR line bit-by-bit, and instantiate the first-hidden-child falsifier on a one-node unread-enable-bit example.

Falsifiers.

- first-hidden-child falsifier: a reachable counterfactual CTSR child is omitted while later proof lines still depend on its parent value
- actual-branch-only falsifier: the proof declares only the semantically followed branch and hides the unused branch behind an unread enable bit
- nonuniform row-selector falsifier: K_{CTSR} is chosen with advice not recoverable from proof syntax and N
- subthreshold residual falsifier: $E_{pi} < N^{\epsilon - o(1)}$ lets equality patching erase sparse row errors
- positive-beta transfer falsifier: any attempted return to black-box SAT substitution with $\beta > 0$ is capped by q+beta c+o(1) before all exponents
- semantic-pruning escape test: a valid $RealSATInfluenceRealizer_N^{arb}$ listing and charging all rows neutralizes the private-row countermodel for that rule

cycle-0139: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 135.774 seconds; 3 lemmas, 5 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 139 improves the CTSR frontier packet by adding a safe EqSAT quotient rule: duplicate counterfactual child rows reduce Γ only when a same-theory certificate is surfaced and charged. Otherwise quotienting is exactly where the private-row falsifier attacks. This is a valid scoped parser/countermodel contribution and still not evidence for P $\neq$ NP.

Pressure. $RealSATInfluenceRealizer_N^{arb}$ remains open for fully semantic adaptive pruning that never exposes counterfactual children or EqSAT certificate edges yet may be sound for real SAT instances.

Derivation steps.

1. Bit fields fixed for each relevant line: rule tag, line id, parent ids, slot j, formula handle h, restriction path sigma, branch bit b, enable bit e, frontier flag, EqSAT certificate pointer, and row-expansion handle.
2. Define K_CTSR^=(pi) by a least fixed point from the final LB_N line. Closure adds syntactic parents, FormulaEval row sets, EqSAT dependency rows, and both counterfactual children of every reachable TSR node. Quotienting is delayed until a charged EqSAT certificate edge is encountered.
3. Verifier audit: enumerate stabilized keys by BFS over the exposed proof DAG; charge U_{enum} for enumeration, B_{EqSAT} for certificate verification, and $N^{1+o(1)}$ for expanding each distinct quotient row into the occurrence-level parser.

4. Line induction: bEF and SATeq lines use the existing Γ_{bEF} invariant; FormulaEval lines read only keys already in $K^{=}$; CTSR lines are sound because all reachable children, including unchosen branches, are present; EqSAT lines justify only the certified quotient edges.

5. Circuit extraction: replace every parsed row occurrence by the generated SAT subcircuit when available or by the transcript subcircuit charged in $\Gamma^{=}_{\mathrm{CTSR}}$; patch E_{pi} exceptional source rows with equality gates, giving C(H_N)<=N^{rho+o(1)}+Gamma_CTSR^=+O(E_pi N).

6. Contrapositive: if this upper bound is below $N^{1+\epsilon-o(1)}$, the alleged LB_N(1+epsilon) certificate is invalid in the same nonuniform SIZE model; this is a route-level falsifier, not a proof that H_N is easy unconditionally.

7. Necessity test: remove one reachable child or merge two uncertified keys. Choose the first unsafe use, keep all visible fields fixed, and flip the private row label behind the omitted child or quotient collision. The transcript agrees but the induced premise or final parity differs.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}$$

Valid when: Valid when N ranges over the carrier lengths, $M_N = N^{q+o(1)}$, and G_N is the fixed advice-free generator used by the beta-zero parity route.

Equation 2: safe_frontier_fixed_point.

$$K_0 = Rows(final), \quad K_{t+1} = K_t \cup Parents(K_t) \cup FE(K_t) \cup CTSR_{all}(K_t) \cup EqSAT(K_t) \;/\; \equiv_{cert}$$

Valid when: Valid when every rule line exposes parent pointers and every quotient edge has a bit-explicit EqSAT certificate charged before use.

Equation 3: ctsr_gamma.

$$\Gamma^{=}_{CTSR}(\pi) = \Gamma_{bEF}(\pi) + U_{enum}(K^{=}) + N\,|K^{=}_{CTSR}(\pi)| + B_{SR_h}(\pi) + B_{EqSAT}(\pi)$$

Valid when: Valid when K^{=}_{CTSR}(pi) is the stabilized safe quotient frontier and row expansion costs $N^{1+o(1)}$ per distinct charged row key.

Equation 4: parser_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma^{=}_{CTSR}(\pi) + O(E_\pi N)$$

Valid when: Applies after the line induction parses every proof line into a same-theory circuit transcript and E_{pi} exceptional source rows are patched by equality gates.

Equation 5: subthreshold_falsifier.

$$\rho < 1+\epsilon, \quad |K^{=}_{CTSR}| < N^{\epsilon-o(1)}, \quad E_\pi < N^{\epsilon-o(1)} \Rightarrow C(H_N^{SAT}) < N^{1+\epsilon-o(1)}$$

Valid when: Requires beta-zero target queries, charged EqSAT quotienting, and no hidden FormulaEval or TSR influence outside the stabilized support frontier.

Next analysis. Instantiate $\Gamma^{=}_{\mathrm{CTSR}}$ on a projected-dDNNF FormulaEval proof with two Tseitin-equivalent child formulas: compute K before and after certified EqSAT quotienting, then remove one certificate and exhibit the first uncertified quotient-collision private-row falsifier.

Falsifiers.

- First-hidden-child adaptive pruning falsifier: an unlisted counterfactual CTSR child changes the induced row label while the visible transcript is unchanged.
- Uncertified quotient-collision falsifier: two syntactically merged child keys can be independently flipped unless a same-theory EqSAT certificate is charged.
- Unread-enable-bit falsifier: a FormulaEval row selected by a hidden enable bit influences a later line without entering K_CTSR^=(pi).
- $q < \epsilon$ full-scan enumeration falsifier: if the whole visible slot universe has size $N^{q+o(1)}$ with $q < \epsilon$, expanding all rows is already subthreshold.
- Positive-beta transfer-cap falsifier retained from the atlas: any return to black-box target queries of length n^{β} faces the upper-bound window q+beta c+o(1).
- Nonuniform row-selector advice falsifier: a short proof that names a support set only through semantic advice is outside $TransparentRowSupport_N$ and cannot be promoted.

cycle-0140: Hardness-Magnification Bridge Realization: QCTSR Certified-Quotient Parser Boundary

Execution. research; azure_responses_api; attempt primary; 106.619 seconds; 3 lemmas, 5 equations, 7 derivation steps, 6 falsifiers.

Learning. Cycle 140 turns safe EqSAT quotienting from a slogan into a ledger transformation: duplicate counterfactual CTSR rows may be removed only through a surfaced same-theory certificate forest whose dependencies are in K_Q. The exact new falsifier is the first uncertified quotient merge. This strengthens the scoped parser/countermodel contribution and remains separate from proving any lower bound or P $\neq$ NP.

Pressure. The derivation does not handle arbitrary real-SAT semantic pruning. It requires either surfaced same-theory EqSAT certificates or a future $RealSATInfluenceRealizer^{arb}_N$ that uniformly lists and charges all semantic influences before use.

Derivation steps.

1. Define the visible row universe R_N and initialize K with the final LB_N line, final carrier rows, and explicit bEF dependencies.
2. Run the least fixed point: add parent rows of every reachable FormulaEval line, add every counterfactual TSR child of each reachable representative, and add all dependencies of each EqSAT quotient certificate before allowing its merge.
3. Use union-find only after certificate insertion: a suppressed row r may be replaced by representative s in the parser iff the certificate forest contains a path proving same-theory SAT equivalence between r and s.

4. Line induction cases: bEF lines charge Γ_{bEF}; transparent FormulaEval lines charge $U(K_Q) + N|RepIdx|$; CTSR lines charge all reachable counterfactual children; quotient lines charge C_{Eq} and then reuse the representative row.

5. Construct the H_N circuit by wiring G_N, the charged row evaluators/transcripts, representative occurrence expansions, EqSAT certificate checkers if needed, and O(E_pi N) equality patches for sparse residual rows.

6. Derive C(H_N)<=N^{rho+o(1)}+Gamma_QCTSR(pi). If this is below $N^{1+\epsilon-o(1)}$, the asserted LB_N(1+epsilon) is falsified in the same nonuniform model.

7. For necessity, choose the first reachable quotient merge or child-pruning step absent from K_Q. Two private-row worlds agree on all charged data and the proof transcript but flip the hidden row's parity contribution, contradicting extensional parser soundness.

Equation 1: carrier.

$$H_N(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \qquad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d$$

Valid when: Valid when H_N is the beta-zero generated parity carrier with polylogarithmic SAT instances and explicit generator G_N.

Equation 2: safe_quotient_closure.

$$K_Q(\pi) = \mu K\,[Final(\pi) \cup Par(K) \cup CTSR_{cf}(Rep(K)) \cup EqCertDep(K)]$$

Valid when: Applies when proof syntax exposes parent pointers, counterfactual TSR children, representatives, and dependencies of every quotient certificate.

Equation 3: ledger.

$$\Gamma_{QCTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_Q) + N \cdot |RepIdx(K_Q)| + C_{Eq}(K_Q) + O(E_\pi N)$$

Valid when: Requires the transparent parser ledger to charge enumeration, row expansion, EqSAT proof forests, and sparse residual patching.

Equation 4: parser_upper_bound.

$$C(H_N) \le N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi)$$

Valid when: Applies after the line induction replaces every proof use by charged rows in the same nonuniform SIZE model.

Equation 5: subthreshold_falsifier.

$$\rho < 1+\epsilon,\ \Gamma_{QCTSR}(\pi) < N^{1+\epsilon-o(1)} \implies \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is a same-model circuit lower-bound claim for H_N on the same valid length sequence.

Next analysis. Instantiate K_Q on a toy projected-dDNNF FormulaEval proof with two CTSR levels and three EqSAT quotient classes; compute |RepIdx|, C_{Eq}, Γ_{QCTSR}, then delete one quotient certificate to exhibit the first-hidden-merge falsifier.

Falsifiers.

- Uncertified quotient merge: a suppressed row influences the final parity but has no surfaced same-theory certificate to a representative.
- First-hidden-child adaptive pruning: a reachable counterfactual TSR child is omitted because only the actual branch was declared.
- Unread-enable-bit FormulaEval: selector output hides a row whose later symbolic use reaches the final line.
- Positive β target queries: black-box substitution gives q+beta*c+o(1) and cannot exclude all SAT circuit exponents.
- Nonuniform leakage: representative choices or row sets are supplied as semantic advice instead of proof-visible enumeration.
- Certificate-charge collapse: C_Eq(K_Q) itself is $N^{1+\epsilon-o(1)}$ or larger, so the parser theorem remains valid but gives no subthreshold falsifier.

cycle-0141: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 120.354 seconds; 2 lemmas, 6 equations, 8 derivation steps, 6 falsifiers.

Learning. The new contribution is that quotient compression in counterfactual TSR is not a free Γ reduction. It is valid only as a dependency-closed, acyclic same-theory certificate transformation; otherwise the first uncertified merge gives a private-row falsifier. This closes a proof-audit loophole in the restricted transparent-support theorem while preserving the separation between route-level certificate collapse and the main P vs NP conjecture.

Pressure. The derivation is complete only for syntactic same-theory quotient certificates. It blocks for full semantic FormulaEval or adaptive pruning where the set of influencing rows is determined by real SAT truth rather than proof-visible dependencies; this is exactly $RealSATInfluenceRealizer_N^{arb}$.

Derivation steps.

1. Define proof-line records with fields line_id, rule_tag, parent_ids, row_slot, formula_id, restriction_word, quotient_id, certificate_root, and local verifier bits.
2. Initialize K_Q with the final LB_N line and close backward under bit-explicit EF parents, SATeq links, bounded-SR leaves, and FormulaEval surfaced rows.
3. For each CTSR node in K_Q, add every syntactically reachable counterfactual restriction child, not merely the actual branch; this preserves extensional safety under private-row changes.
4. For each quotient merge in K_Q, require a same-theory certificate forest whose leaves are earlier members of K_Q and whose conclusion is EqSAT(child_a,child_b); reject cyclic certificates by topological order on line_id and certificate_root.

5. Charge N R_Q(pi) for row expansion, $N^{q+\eta+\tau+o(1)}$ for bounded-SR leaves, C_Q(pi) for certificate checking, and inherit Gamma_bEF(pi) for bit-explicit EF support.

6. Run line induction: each proof line in K_Q has a local circuit simulator using only charged parents; quotient lines reuse a representative only after the certificate verifier establishes same-theory equality inside the transcript.

7. Assemble the carrier circuit from the generator circuit, charged row simulators, quotient representatives, and equality patches for E_N residual rows, giving C(H_N)<=N^{rho+o(1)}+Gamma_Q+O(E_N

8. Derive the exponent window: if $\rho < 1+\epsilon$, $q+\eta+\tau < 1+\epsilon$, $\kappa+\theta < \epsilon$, $chi < 1+\epsilon$, and $\delta < \epsilon$, then the claimed LB_N(1+epsilon) certificate is invalid in the same SIZE model.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j))$$

Valid when: Valid when N ranges over admissible carrier lengths and G_N is the fixed advice-free generator.

Equation 2: closed_support.

$$K_Q(\pi) = \mathrm{lfp}(S \mapsto S \cup Parents(S) \cup CTSRChild(S) \cup EqCertDeps(S))$$

Valid when: Valid when every FormulaEval, CTSR, and quotient dependency is syntactically addressable before the line using it.

Equation 3: ledger.

$$\Gamma_Q(\pi) = \Gamma_{bEF}(\pi) + O(N^{q+\eta+\tau+o(1)} + N\,R_Q(\pi) + C_Q(\pi))$$

Valid when: Valid when SR leaves, row expansions, and certificate-forest checks are charged in the same SIZE model.

Equation 4: transcript_upper_bound.

$$C_{SIZE}(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_Q(\pi) + O(E_N N)$$

Valid when: Valid after the line induction has replaced every proof line by its charged transcript simulator.

Equation 5: threshold_window.

$$R_Q \le N^{\kappa+\theta+o(1)},\ C_Q \le N^{\chi+o(1)},\ E_N \le N^{\delta+o(1)} \Rightarrow C(H_N) \le N^{\max\rho, q+\eta+\tau, 1+\kappa+\theta, \chi, 1+\delta+o(1)}$$

Valid when: Valid when R_Q, C_Q, and E_N have the stated polynomial-exponent bounds uniformly in N.

Equation 6: $\mathrm{LB}_{falsifier,window}$.

$$\max\rho, q+\eta+\tau, 1+\kappa+\theta, \chi, 1+\delta < 1+\epsilon \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is a claimed same-model SIZE lower bound for the carrier H_N.

Next analysis. Instantiate one two-merge CTSR proof toy model: one certified EqSAT quotient with charged forest and one uncertified merge. Write the local verifier fields, compute R_Q and C_Q, and demonstrate transcript agreement plus parity disagreement for the uncertified merge.

Falsifiers.

- first uncertified quotient merge: two transcripts agree on K_Q but differ on the hidden child row
- cyclic same-theory certificate forest: quotient equality depends on its own compressed representative
- actual-branch-only TSR declaration: private-row flip at an unvisited counterfactual child changes extensional safety
- hidden SAT-semantic branch pruning without $RealSATInfluenceRealizer_N^{arb}$: influence rows are not uniformly listable before use
- threshold collapse: max{rho,q+eta+tau,1+kappa+theta,chi,1+delta} reaches or exceeds 1+epsilon
- nonuniform leakage: quotient representative chosen using SAT-truth advice rather than surfaced proof syntax

cycle-0142: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 132.632 seconds; 1 lemmas, 3 equations, 5 derivation steps, 4 falsifiers.

Learning. Cycle 142 makes quotient compression proof-carrying: row deletion is valid only after a ranked same-theory certificate is charged in Γ_{QCTSR}. Acyclicity is the new finite audit condition; cyclic, adaptive, or advice-chosen merges are concrete countermodels, not generic barrier folklore.

Pressure. The argument does not realize hidden semantic FormulaEval or adaptive SAT branch pruning; $RealSATInfluenceRealizer_N^{arb}$ remains the named nonrelativizing open lemma.

Derivation steps.

1. Definition/assumption context: this derivation is interpreted inside Hardness-Magnification Bridge Realization; source object: $H_N^{\mathrm{SAT}}(x) = xor_{j \le M_N}$ SAT(G_N(x,j)), $M_N = N^{q+o(1)}$, polylog row length L_N, and claimed nonuniform SIZE lower bound LB_N(1+epsilon).; target object: a same-model upper-bound falsifier for LB_N via a parsed proof transcript; this is a scoped certificate-collapse theorem, not P $\neq$ NP evidence.; Circuit model is nonuniform Boolean SIZE; G_N has size $N^{\rho+o(1)}$ and all parser circuits stay in the same model..
2. Initialize K_Q from the final LB_N assertion; close under bit-explicit parents, FormulaEval row supports, all counterfactual TSR children, quotient certificate leaves, and certificate parents until a finite fixed point is reached.
3. Orient each quotient certificate by a visible rank. The induction hypothesis covers lower-rank dependencies before the merge deletes a duplicate row, so the kept representative is same-theory, not SAT-advice chosen.

4. For each line, add its local verifier and row-expansion cost to Γ_{QCTSR}. The bEF, transparent FormulaEval, CTSR, and certified quotient cases compose, giving the parser_bound circuit with O(E_pi N) equality patching.

5. If the first bad merge is uncertified or cyclic, vary a private duplicated row while preserving all surfaced syntax; the transcript remains accepted but the carrier parity changes, contradicting extensional safety.

Equation 1: ledger.

$$\Gamma_{QCTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_Q) + X(K_Q) + C(F_Q) + N^{1+\kappa+\theta+o(1)} + O(E_\pi N)$$

Valid when: Valid when K_Q is the least closed support cone and F_Q is an acyclic same-theory certificate forest with all leaves surfaced before quotient deletion.

Equation 2: parser_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi)$$

Valid when: Applies after the generator, row verifiers, quotient certificates, CTSR children, and sparse-row patches are implemented in the same nonuniform SIZE model.

Equation 3: subthreshold_falsifier.

$$N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Requires the claimed LB_N to be a lower bound for the same H_N carrier and the parser-bound circuit to preserve all length and advice conventions.

Next analysis. Write the finite verifier for K_Q and ranked F_Q on a toy projected-dDNNF plus CTSR example with one duplicate child pair; compute Γ savings, then remove one certificate edge to exhibit the private-row falsifier.

Falsifiers.

- falsifier: a first quotient merge whose representative is chosen by SAT truth or nonuniform advice rather than by a surfaced same-theory certificate.
- falsifier: a directed cycle in F_Q, since the line induction can no longer justify deleting a row before its equivalence proof is parsed.
- falsifier: an omitted counterfactual TSR child; two transcripts agree on actual branches while a hidden child flips the quotient row.
- falsifier: any claimed positive-beta extension with transfer cap C(H_N)<=N^{q+beta c+o(1)} that cannot exclude all SAT exponents.

cycle-0143: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 178.729 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 143 turns quotient compression into a proof-carrying ledger rule: Γ may shrink only through ranked acyclic same-theory certificates already in K_Q. Unranked quotienting is not a harmless optimization; it is exactly a private-row falsifier.

Pressure. This does not solve $RealSATInfluenceRealizer_N^{arb}$ for full semantic FormulaEval; it only handles proof-carrying same-theory quotient compression.

Derivation steps.

1. Initialize K_Q at the final LB_N rows; repeatedly add bEF parents, transparent FormulaEval rows, all reachable counterfactual TSR frontier children, and all dependencies of quotient certificates.

2. For a quotient merge a~b, require a same-theory certificate DAG whose edges have strictly smaller rank; add its occurrence rows before allowing deletion of either duplicate row from the ledger.

3. Induct on proof lines ordered by proof index and quotient rank. Each consumed row is either explicit in K_Q or replaced by a certified same-theory row; hence the simulator pays exactly Γ_{QCTSR}.

4. Contraposition: at the first merge lacking a ranked certificate, build two transcripts agreeing on K_Q but differing on the private deleted row or unread enable bit; the proof transcript agrees while H_N parity can differ.

Equation 1: QClosure.

$$K_Q(\pi) = \mathrm{lfp}(R \mapsto R \cup Dep_{bEF}(R) \cup FE(R) \cup CTSR(R) \cup Cert_Q(R))$$

Valid when: Valid when proof syntax exposes every FormulaEval, CTSR, and quotient dependency before the consuming line.

Equation 2: QLedger.

$$\Gamma_{QCTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_Q) + X(K_Q) + B_{CTSR}(\pi) + B_Q(\pi)$$

Valid when: Applies after ranked same-theory certificates are charged and duplicate row deletions are certified.

Equation 3: ParserUpperBound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N)$$

Valid when: Requires beta-zero target calls and same nonuniform SIZE model for the reconstructed circuit.

Next analysis. Instantiate the six-row QCTSR transcript, list row IDs, quotient certificate dependencies, rank labels, and show the first uncertified merge produces two agreeing visible transcripts with opposite H_N parity.

Falsifiers.

- First uncertified quotient merge: a deleted duplicate row has no surfaced same-theory certificate in K_Q, so private-row spoofing invalidates the parser.
- Cyclic certificate SCC: ranked descent fails, so the line induction has no well-founded order and the quotient deletion is not valid.
- Adaptive advice-chosen merge: the row pair is selected by semantic advice rather than N and pi, causing nonuniform leakage outside Γ_{QCTSR}.
- Threshold collapse falsifier: if $1 + \kappa + \theta \geq 1 + \epsilon$ or $\Gamma_{\mathrm{QCTSR}} \geq N^{1+\epsilon-o(1)}$, the parser gives no contradiction to LB_N.

cycle-0144: Hardness-Magnification Bridge Realization: ranked QCTSR ledger validation

Execution. research; azure_responses_api; attempt primary; 121.463 seconds; 3 lemmas, 5 equations, 6 derivation steps, 6 falsifiers.

Learning. Cycle 144 closes a proof-audit loophole: quotient compression in counterfactual TSR is valid exactly as proof-carrying ranked same-theory compression, not as semantic row deletion. The contribution is a scoped parser/falsifier theorem: ranked QCTSR preserves the Γ line induction, while the first unranked quotient merge is a concrete private-row falsifier. This improves the paper theorem boundary without giving any H_N lower bound or P ≠ NP result.

Pressure. The positive proof is complete only for restricted $\mathrm{Psys}_{\mathrm{QCTSR}}$. Full semantic FormulaEval or hidden adaptive pruning still requires $RealSATInfluenceRealizer_N^{arb}$, an advice-free nonrelativizing theorem that lists and charges all real SAT influence rows before use.

Derivation steps.

1. Fix pi and compute K_Q by least fixed point: seed final LB_N line; add bEF parent dependencies; add transparent FormulaEval support rows and row-expansion witnesses; add all reachable counterfactual TSR children; add quotient-certificate dependency rows in increasing rank until closure.
2. Define a quotient edge r_del → r_keep to be admissible only if a certificate cert(e) proves same-theory SAT(r_del)=SAT(r_keep) using rows in $K_{<rank(e)}$. The rank order makes the certificate forest acyclic and independently checkable.
3. Run line induction. bEF lines use the existing Γ_{bEF} parser. FormulaEval lines add U(K_Q)+X(K_Q). CTSR lines add all counterfactual children, so actual-branch pruning cannot hide influence. Quotient lines replace a deleted row by a kept row only after the equality of SAT labels is certified from already charged dependencies.
4. Construct C_{pi}: compute G_N in size $N^{\rho+o(1)}$, evaluate the parsed transcript and same-theory certificates using Γ_{QCTSR} gates, and patch E_{pi} exceptional source rows by equality tests of cost O(E_pi N).

5. If the displayed size is below $N^{1+\epsilon-o(1)}$, then the claimed source lower bound LB_N(1+epsilon) is falsified in the same nonuniform model. This is a valid route-level implication and not a lower bound for H_N.

6. For necessity, choose the first quotient edge without a ranked certificate. Because all earlier dependencies are fixed, flip the private deleted row label while preserving the visible prefix. If its residual parity incidence is odd, the proof transcript is unchanged but H_N changes, contradicting extensional safety of the compressed ledger.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}$$

Valid when: Valid when the source carrier is the beta-zero parity construction with uniformly generated polylog-length SAT rows and no target query length exponent hidden in G_N.

Equation 2: ledger.

$$\Gamma_{QCTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_Q) + X(K_Q) + B_{CTSR}(K_Q) + B_Q(K_Q)$$

Valid when: Applies after K_Q is computed as the least dependency-closed support cone containing all proof-reachable FormulaEval, counterfactual TSR, and ranked quotient-certificate rows.

Equation 3: ctsr_charge.

$$B_{CTSR}(K_Q) \le N^{1+\kappa+\theta+o(1)}$$

Valid when: Valid when the reachable TSR frontier has exponent κ, every frontier node exposes $N^{\theta+o(1)}$ counterfactual children, and child encodings are charged before semantic pruning.

Equation 4: quotient_charge.

$$B_Q(K_Q) = \sum_{e \in F_Q} \left(|cert(e)| + N \cdot |Rows(cert(e)) \setminus K_{<rank(e)}| \right)$$

Valid when: Requires each quotient edge e to carry a ranked same-theory certificate whose previously unseen dependency rows are added and charged before the deleted row is merged.

Equation 5: parser_falsifier.

$$N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Applies in the same nonuniform SIZE model after the generator, parsed transcript, quotient certificates, TSR children, and sparse residual corrections are all counted in the circuit size.

Next analysis. Write the referee-checkable K_Q closure pseudocode with rank ordering, then test it on a two-child Tseitin-equivalent TSR merge and on the same example with the certificate omitted to exhibit the first-unranked-merge falsifier.

Falsifiers.

- First unranked quotient merge: a deleted row is identified with a kept row without a surfaced rank-decreasing same-theory certificate.
- Cyclic quotient dependency: certificates for two row deletions depend on each other and therefore cannot be audited by a finite lower-rank induction.
- Advice-chosen quotient forest: the merge list depends on SAT labels or hidden semantic advice rather than on N and pi.
- Actual-branch-only TSR declaration: an unlisted counterfactual child can be made the private row, so occurrence completion is invalid.
- $q < \epsilon$ with full row scan: FormulaEval expansion costs $N^{1+q+o(1)}$ below the claimed $N^{1+\epsilon}$ lower bound, giving a direct same-model falsifier.
- Positive β black-box substitution: SAT $\in$ SIZE(n^c) would give source circuits of size N^{q+beta c+o(1)}, so all-exponent target exclusion is invalid unless $\beta = 0$ or genuinely subpolynomial.

cycle-0145: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 121.597 seconds; 3 lemmas, 6 equations, 10 derivation steps, 6 falsifiers.

Learning. Cycle 145 upgrades ranked QCTSR from a line-induction slogan to a finite verifier/minimality packet. Quotient compression is valid only when proof-carrying same-theory certificates are ranked, dependency-closed, and charged before use. The exact obstruction is the first rejected quotient merge, which yields a private-row falsifier. This strengthens the paper parser/countermodel boundary without proving H_N lower bounds or P $\neq$ NP.

Pressure. The derivation is complete for surface QCTSR syntax with a specified EqSAT/CTSR same-theory checker. It does not handle arbitrary semantic FormulaEval or hidden adaptive pruning unless $RealSATInfluenceRealizer_N^{arb}$ uniformly lists and charges the same influenced rows before use.

Derivation steps.

1. Parse pi line by line and create bit fields: line_id, rule_tag, row_id, formula_hash, restriction_string, quotient_class_id, certificate_id, parent_pointer_list, rank, and local charge.
2. Initialize K with every row mentioned by the final LB_N line; then iterate the closure operators Dep, CTSR_{cf}, QuotRep, and $CertRows_Q$ until a fixed point is reached.
3. For a transparent FormulaEval line, either enumerate the surfaced row set and charge U(K) plus occurrence expansion X(K), or full-scan all M_N rows and charge the corresponding $N^{1+q+o(1)}$ term.
4. For a counterfactual TSR line, add every syntactically reachable child row, not just the actual branch; charge $B_{\mathrm{CTSR}} = N^{1+\kappa+\theta+o(1)}$ in the exponent regime where the child list is complete.

5. For a quotient merge, accept row deletion only if a same-theory certificate forest is present, all certificate dependencies are already in K or are added by closure, and ranks strictly decrease along every dependency edge.

6. The local verifier checks certificate acyclicity by rank comparison, checks formula hashes and parent pointers, and refuses any edge whose target row was not already surfaced or newly charged.

7. Line induction: assuming all parent lines have circuit simulations using only K_Q rows, each allowed rule produces the next line with additional size bounded by its ledger charge; quotient representatives are interchangeable only through accepted same-theory certificates.

8. At the final line, compose the generator circuit of size $N^{\rho+o(1)}$, the parsed transcript circuit of size Γ_{QCTSR}, and equality patches for E_{pi} residual rows, obtaining C(H_N)<=N^{rho+o(1)}+Gamma_QCTSR(N).

9. If this size is below $N^{1+\epsilon-o(1)}$, the claimed LB_N(1+epsilon) is falsified in the same nonuniform SIZE model.

10. For necessity, choose the first unaccepted quotient merge e. Toggle a private row behind e while keeping all charged prefix rows fixed. The transcript remains accepted but the represented parity or branch value changes, proving that the unranked merge was not transparent.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j=1}^{M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad L_N = (\log N)^d$$

Valid when: Valid when N is a valid carrier length and beta-zero polylogarithmic target-query length is part of the branch interface.

Equation 2: least_closed_support.

$$K_Q(\pi) = \mu K\,[Rows(final) \cup Dep(K) \cup CTSR_{cf}(K) \cup QuotRep(K) \cup CertRows_Q(K)]$$

Valid when: Valid when every dependency operator is syntactically computable from the proof text and certificate forests are ranked acyclic objects.

Equation 3: charged_gamma.

$$\Gamma_{QCTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_Q) + X(K_Q) + B_{CTSR}(K_Q) + B_Q(K_Q)$$

Valid when: Applies after all transparent rows, counterfactual TSR children, and quotient certificates have been surfaced and charged in the same ledger.

Equation 4: simulator_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N)$$

Valid when: Requires the parser line induction, same-model circuit simulation, and residual error rows E_{pi} patchable by equality tests on N-bit inputs.

Equation 5: falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when LB_N is asserted against nonuniform SIZE circuits and the constructed simulator uses no stronger advice than the proof permits.

Equation 6: support_density_corollary.

$$|K_{idx}(\pi)| \geq N^{\epsilon-o(1)}, \quad |K_{idx}(\pi)|/M_N \geq N^{\epsilon-q-o(1)}$$

Valid when: Applies when each surfaced row index costs an N-sized occurrence expansion and all other Γ terms remain subthreshold.

Next analysis. Instantiate the finite verifier on one toy QCTSR proof with two EqSAT-equivalent counterfactual TSR children: compute K_Q, ranks, B_Q, and Γ_{QCTSR}; then delete one certificate edge and explicitly write the two-world private-row falsifier.

Falsifiers.

- First unranked quotient merge falsifier: a row deletion not backed by a ranked same-theory certificate admits a private-row two-world collision.
- Cyclic certificate falsifier: a quotient proof with no decreasing rank can hide semantic advice in a dependency loop and is rejected by the finite verifier.
- Advice-chosen representative falsifier: selecting quotient representatives using SAT labels or hidden row sets violates the target-preserving condition and invalidates Γ shrinkage.
- Actual-branch-only TSR falsifier: charging only the followed restriction child leaves a first-hidden-child private row for the counterfactual branch.
- Threshold-collapse falsifier: if $\kappa + \theta \geq \epsilon$, $chi \geq \epsilon$, or $E_{pi} \geq N^{\epsilon-o(1)}$, the constructed simulator is not subthreshold.
- Positive-beta falsifier for broader magnification claims: SAT $\in$ SIZE(n^c) still gives carrier size N^{q+beta c+o(1)}, so $\beta > 0$ cannot exclude all c through this interface.

cycle-0146: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 85.08 seconds; 3 lemmas, 5 equations, 9 derivation steps, 6 falsifiers.

Learning. Cycle 146 upgrades ranked QCTSR from a finite local verifier to a composable fixed-point line-induction theorem: quotient compression is valid only when proof-carrying same-theory certificates are ranked, acyclic, dependency-closed, and charged before use. The first rejected merge is a concrete private-row falsifier. This strengthens the transparent-support parser/countermodel paper module while preserving all nonclaims: no H_N lower bound, no P $\neq$ NP result, and no free hidden semantic FormulaEval.

Pressure. The derivation does not fold arbitrary hidden semantic FormulaEval or adaptive SAT branch pruning into K_Q. That remains the named $RealSATInfluenceRealizer_N^{arb}$ problem.

Derivation steps.

1. Define K_Q^0(pi) as the row, proof-line, and certificate seeds syntactically referenced by the final LB_N assertion.

2. Iterate closure: add EF parent rows and extension-support rows; for FormulaEval lines add the enumerated RowSet or charge the full scan; for CTSR lines add every counterfactual child row in the bounded rule schema.

3. For each quotient deletion r $\to$ r', require a displayed same-theory certificate forest $F_{r,r'}$ with a rank label. Add every leaf and internal dependency of $F_{r,r'}$ to K_Q before accepting the deletion.

4. Check acyclicity by requiring rank(child)<rank(parent) along certificate-dependency edges. This makes the verifier finite and prevents cyclic quotient justification.

5. Define Γ_{QCTSR} as the sum of existing Γ_{bEF} charges, support-enumeration cost U_Q, row-expansion cost $X_Q = N|K_Q|$ up to encoding overhead, complete CTSR child cost, certificate-checking cost C_Q, and residual patch cost O(E_pi N).

6. Prove the line invariant: after line t, the partial circuit using only rows in $K_Q^{\leq t}$ agrees with the proof transcript on all surfaced influences; quotient representatives are safe because same-theory certificates are already available and ranked.

7. At the final line, compose the generator circuit for G_N with the parsed transcript circuit and add equality patches for E_{pi} residual source rows. The total size is N^{rho+o(1)}+Gamma_QCTSR(pi)+O(E N).

8. If this total is below $N^{1+\epsilon-o(1)}$, the asserted LB_N(1+epsilon) is false in the same nonuniform SIZE model; this is the route-level falsifier conclusion.

9. For necessity, take the first quotient merge that fails the finite verifier. Create two private-row worlds agreeing on K_Q and all accepted certificates but differing on the uncharged deleted row. The proof sees the same transcript while carrier parity can differ, so unranked compression is not a valid parser rule.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}.$$

Valid when: Valid when the source carrier is the beta-zero generated parity construction and the generator outputs polylogarithmic SAT instances.

Equation 2: ledger.

$$\Gamma_{QCTSR}(\pi) = \Gamma_{bEF}(\pi) + U_Q(\pi) + X_Q(\pi) + B_{CTSR}(\pi) + C_Q(\pi) + O(E_\pi N).$$

Valid when: Valid when every proof rule is parsed through visible support, complete counterfactual children, and ranked same-theory quotient certificates.

Equation 3: ctsr_charge.

$$B_{CTSR}(\pi) \leq N^{1+\kappa+\theta+o(1)} \text{ for } N^{\kappa+o(1)} \text{ frontier rows and } N^{\theta+o(1)} \text{ children per row.}$$

Valid when: Applies when the bounded TSR schema declares all counterfactual children uniformly before adaptive pruning or quotient compression occurs.

Equation 4: falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon).$$

Valid when: Requires the parser-to-circuit construction, same nonuniform SIZE model, and residual row patching below the N^{ϵ} threshold.

Equation 5: density_corollary.

$$|K_Q(\pi)| \geq N^{\epsilon-o(1)} \quad \text{or} \quad |K_Q(\pi)|/M_N \geq N^{\epsilon-q-o(1)}.$$

Valid when: Valid when each surfaced row has N-cost expansion and the claimed lower-bound proof is not already falsified by Γ_{QCTSR}.

Next analysis. Run the finite verifier on one projected-dDNNF/Tseitin-renaming example: list K_Q seeds, accepted quotient certificates, rank labels, computed Γ_{QCTSR}, and then delete one certificate to exhibit the first-rejected-merge private-row falsifier.

Falsifiers.

- first unranked quotient merge: a private row can be flipped while all charged rows and verifier bits stay fixed
- cyclic certificate forest: rank check fails, allowing circular deletion with no same-theory support
- advice-chosen quotient representative: nonuniform leakage selects the surviving row without paying K_Q or C_Q
- actual-branch-only TSR declaration: a hidden counterfactual child yields the first-hidden-child falsifier
- semantic FormulaEval without $RealSATInfluenceRealizer_N^{arb}$: unread-enable-bit row affects the proof but is absent from Γ_{QCTSR}
- positive β black-box interface: q+beta*c+o(1) caps all-exponent transfer and invalidates P/poly conclusions

cycle-0147: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 81.535 seconds; 3 lemmas, 5 equations, 8 derivation steps, 7 falsifiers.

Learning. Cycle 147 closes a real proof-audit upgrade: ranked QCTSR quotient compression has a least, order-independent, proof-carrying support closure, so Γ reduction is valid only after lower-rank same-theory dependencies are charged. The sharp falsifier is the first nondecreasing, cyclic, advice-chosen, or hidden semantic merge. This strengthens the paper parser/countermodel module without proving any H_N lower bound or P $\neq$ NP.

Pressure. No blocking gap remains for restricted ranked QCTSR syntax. The broader full-semantic FormulaEval system remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which would have to surface all real SAT-semantic influences with charges before use.

Derivation steps.

1. Define the finite universe U(pi) of row nodes, FormulaEval support nodes, counterfactual TSR child nodes, quotient representatives, and quotient-certificate nodes visible in pi.

2. Define the monotone operator F(K) by adding proof parents, reachable transparent support, all counterfactual children of active TSR nodes, deterministic quotient representatives, and all lower-rank certificate dependencies for quotient merges touching K.

3. Because F is monotone on a finite powerset lattice, iterating from the final LB_N line reaches a least fixed point K_Q independent of enumeration order.

4. Strict rank decrease prevents a quotient certificate from validating deletion of a row through itself; every certificate node used in a merge has its dependency cone inserted before the merge can reduce the ledger.

5. Minimality follows by induction on closure time: any support set sufficient for the line induction must contain the final line, then must contain each parent, child, same-theory dependency, and quotient representative demanded by the verifier, hence contains K_Q.

6. Line induction extends the prior Γ_{bEF} proof: bEF steps charge Γ_{bEF}, transparent FormulaEval charges U+X, declared CTSR charges B_{CTSR}, and ranked quotient merges charge B_Q instead of deleting rows for free.

7. The circuit simulator hardwires G_N, evaluates only rows in K_Q through the parsed support circuit, applies quotient representatives with their charged certificates, and patches E_{pi} residual rows by equality tests of cost O(E_pi N).

8. If the resulting upper bound is below $N^{1+\epsilon-o(1)}$, it is a valid same-model falsifier of the asserted LB_N(1+epsilon).

Equation 1: closure_operator.

$$K_{t+1} = K_t \cup Parents(K_t) \cup FE(K_t) \cup CTSR(K_t) \cup QRep(K_t) \cup QCertDeps_{<rank}(K_t)$$

Valid when: Valid when pi is a finite ranked QCTSR transcript whose dependency predicates are syntactically decidable from pi and N.

Equation 2: termination_bound.

$$K_Q(\pi) = K_T \text{ for some } T \leq |Rows(\pi)| + |CertNodes(\pi)|$$

Valid when: Valid when every closure insertion is drawn from the explicit finite row and certificate-node universe of the transcript.

Equation 3: ledger_definition.

$$\Gamma_{QCTSR}(\pi) = \Gamma_{bEF}(\pi) + U(K_Q) + X(K_Q) + B_{SR}(\pi) + B_{CTSR}(\pi) + B_Q(\pi)$$

Valid when: Valid when all transparent FormulaEval, bounded self-reduction, counterfactual child, and quotient-certificate charges are surfaced before line induction uses them.

Equation 4: parser_upper_bound.

$$C(H_N^{SAT}) \leq N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N)$$

Valid when: Applies after the generator, parsed transcript ledger, and sparse residual-row patching are all circuits in the same nonuniform SIZE model.

Equation 5: lb_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Requires that LB_N(1+epsilon) asserts a same-model lower bound for the exact carrier H_N^{SAT} on the same valid lengths.

Next analysis. Instantiate the closure verifier on a three-row QCTSR toy transcript: two counterfactual child rows, one EqSAT certificate forest, and one attempted cyclic merge; compute K_Q, Γ_{QCTSR}, and the first-rejected-merge private-row falsifier explicitly.

Falsifiers.

- first unranked quotient merge with no lower-rank same-theory certificate
- cyclic quotient-certificate dependency that deletes the row needed to certify itself
- advice-chosen quotient representative not computable from pi and N
- hidden semantic FormulaEval row or unread enable bit outside K_Q(pi)
- threshold-collapse falsifier when $N^\rho + \Gamma_{\mathrm{QCTSR}} + E_{pi}$ N reaches $N^{1+\epsilon-o(1)}$
- model-mismatch falsifier when LB_N and the constructed circuit are not in the same nonuniform SIZE model
- positive-beta black-box substitution falsifier q+beta c bounding the target exponent window

cycle-0148: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 93.761 seconds; 3 lemmas, 6 equations, 9 derivation steps, 5 falsifiers.

Learning. Cycle 148 turns ranked QCTSR from an order-independent closure statement into a representative-stable $TransparentRowSupport_N$ rule case. The valid contribution is a restricted theorem/countermodel pair: proof-carrying quotient compression preserves Γ line induction, while the first unranked, cyclic, advice-chosen, or hidden semantic merge yields a private-row falsifier. This closes a proof-audit loophole without proving any H_N lower bound or P $\neq$ NP; full semantic pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. Full semantic FormulaEval with hidden adaptive pruning remains blocked at $RealSATInfluenceReal$ no advice-free nonrelativizing procedure is proved that lists all real SAT influences before the semantic rule is used.

Derivation steps.

1. Source statement: a $\mathrm{Psys}_{sym}^{\mathrm{QCTSR}}$ proof pi certifies LB_N(1+epsilon) for the beta-zero parity carrier H_N^{SAT} in the nonuniform SIZE model.

2. Target statement: if Gamma_QCTSR(pi) is subthreshold, then construct a same-model SIZE circuit for H_N^{SAT} of size below $N^{1+\epsilon-o(1)}$, contradicting the certified lower-bound claim but not proving P $\neq$ NP.

3. Model context: source carrier is H_N^{SAT}, target class is nonuniform SIZE_N, proof model is bit-explicit bEF plus transparent FormulaEval plus counterfactual declared TSR plus ranked same-theory quotient certificates, and the simulation is a parser-to-circuit upper-bound reduction.

4. Quantifier context: N ranges over valid source lengths; q,rho,kappa,theta,epsilon,d are fixed; L_N=(log N)^d; $\beta = 0$; all row enumerators and certificates are advice-free once pi and N are fixed.

5. Closure construction: compute K_Q(pi) by iterating Seed, parent dependencies, visible FormulaEval influence, all counterfactual TSR children, and certificate dependencies of smaller rank until a fixed point is reached.

6. Line induction: for bEF and transparent FormulaEval lines use the prior Γ_{bEF} and $U_Q+N|K_Q|$ charges; for CTSR lines use complete child declarations; for quotient merges replace rows only after their ranked same-theory certificate forest is in K_Q.

7. Upper-bound assembly: combine generator overhead $N^{\rho+o(1)}$, parsed row circuits, certificate verifier circuits, and sparse error correction O(E_pi N) to obtain C(H_N^SAT)<=N^{rho+o(1)}+Gamma_C N).

8. Necessity step: if a merge is first unranked, cyclic, advice-chosen, or hidden, keep all visible proof bits fixed and flip the private hidden row label; the transcript remains accepted while the parity carrier changes, so the parser is not extensionally valid.

9. Reviewer findings: reduction consistency is valid for $\beta = 0$ only; quantifier uniformity is valid after certificate rank and row enumeration are syntax-visible; barrier specificity says the obstruction is a private-row/nonuniform-leakage countermodel, not a generic natural-proofs or relativization citation.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(F_{N,x,j}), \quad M_N = N^{q+o(1)}, \quad |F_{N,x,j}| = (\log N)^d$$

Valid when: Valid when N is a valid source length and generator rows are syntactically enumerated.

Equation 2: least_support_fixed_point.

$$K_Q(\pi) = \mu K\left[Seed(\pi) \cup Par(K) \cup FE(K) \cup CTSR(K) \cup Cert_Q^{<rank}(K)\right]$$

Valid when: Applies after all proof dependencies, TSR children, and quotient certificates are exposed before use.

Equation 3: ledger.

$$\Gamma_{QCTSR}(\pi) = \Gamma^{-}_{bEF}(\pi) + U_Q(\pi) + N|K_Q(\pi)| + B_{CTSR}(\pi) + C_Q(\pi)$$

Valid when: Requires visible row enumeration, complete counterfactual child declarations, and charged same-theory certificate forests.

Equation 4: parser_upper_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N)$$

Valid when: Requires the target-preserving beta-zero substitution with advice-free row enumeration and same SIZE model.

Equation 5: subthreshold_falsifier.

$$N^{\rho+o(1)} + \Gamma_{QCTSR}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon)$$

Valid when: Valid when the assumed LB_N threshold is in the identical nonuniform circuit model.

Equation 6: support_density_pressure.

$$|K_Q(\pi)| \ge N^{\epsilon-o(1)}, \quad |K_Q(\pi)|/M_N \ge N^{\epsilon-q-o(1)}$$

Valid when: Applies when all other ledger terms are subthreshold and every omitted row costs N to patch.

Next analysis. Write the finite K_{QCTSR} verifier on a projected-dDNNF example with one certified duplicate row and one unread-enable hidden merge; compute $U_Q, N|K_Q|, B_{\mathrm{CTSR}}, C_Q, E_{pi}$ and show exactly where the hidden merge fails the valid support ledger.

Falsifiers.

- first unranked quotient merge falsifier: two completions agree on charged rows but differ on the hidden representative row
- cyclic or nondecreasing certificate-rank falsifier: the alleged compression is self-justifying and cannot be parsed before use
- advice-chosen representative falsifier: the quotient map carries nonuniform row-selection leakage not charged in Γ_{QCTSR}
- hidden adaptive TSR pruning falsifier: an unlisted counterfactual child can be made decisive by a private-row assignment
- positive-beta black-box substitution falsifier remains active outside this beta-zero parser route: q+beta*c caps all-exponent transfer

cycle-0149: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 100.413 seconds; 3 lemmas, 6 equations, 8 derivation steps, 6 falsifiers.

Learning. Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. The derivation does not cover arbitrary real-SAT semantic pruning or FormulaEval comprehension unless $RealSATInfluenceRealizer_N^{arb}$ uniformly lists the influencing rows and charges them before use.

Derivation steps.

1. Encode each QCTSR proof line with fields (rule tag, parents, row id, child restriction, representative id, quotient-certificate id, rank, dependency list). These fields are verifier-visible and do not query SAT truth advice.

2. Define F_{Qrep} on sets of support objects: add bEF dependencies, FormulaEval support rows, every counterfactual TSR child row, all nodes of each same-theory quotient certificate forest, and the canonical representative chosen by the charged certificate. Iterate from the final LB_N line to obtain K_Qrep(pi).

3. Monotonicity and finiteness give a least fixed point. Rank decrease in quotient certificates gives acyclicity, so the same K_Qrep(pi) is reached independently of line order or certificate-processing order.

4. Prove representative stability by induction on rank: if row a is replaced by representative b, then all lower-rank certificate dependencies proving EqSAT(a,b) are already in K_Qrep(pi), so the parser may identify a and b without reading an uncharged label.

5. Extend the existing Γ_{bEF} line induction. bEF lines use Γ_{bEF}; transparent FormulaEval uses $U_N + X_N$; complete counterfactual TSR child expansion contributes $C_{\mathrm{CTSR}} = N^{1+\kappa+\theta+o(1)}$ in the bounded schema; ranked quotient compression contributes $C_{Qcert} + C_{rep}$ and may only reduce row multiplicity after the certificate is charged.

6. Build the source circuit for H_N from the generator circuit, the parsed transcript evaluator, parity aggregation over charged representatives, and equality patches for E_{pi} residual rows. This yields C_SIZE(H_N)<=N^{rho+o(1)}+Gamma_Qrep(pi)+O(E_pi N).

7. Contrapose: if LB_N(1+epsilon) is asserted in the same SIZE model, then any valid $\mathrm{Psys}_{sym}^{\mathrm{QCTSR}}$ certificate must have Gamma_Qrep(pi)+O(E_pi N)>=N^{1+epsilon-o(1)}.

8. For necessity, take the first quotient merge or pruning child not accepted by the ranked closure verifier. Toggle a private row label r* outside K_Qrep(pi), keep the visible transcript fixed, and force the affected line or carrier parity to differ. Thus hidden quotienting is a falsifier for transparent parsing.

Equation 1: carrier.

$$H_N^S AT(x) = xor_{j<M_N} SAT(G_N(x,j)), M_N = N^{q+o(1)}, L_N = (logN)^d$$

Valid when: Valid when the carrier is the beta-zero parity construction with polylogarithmic SAT queries and a uniform generator.

Equation 2: least_closure.

$$K_Q rep(pi) = lfp(F_p arentunion F_F Eunion F_C TSRunion F_Q certunion F_r ep)$$

Valid when: Valid when QCTSR syntax exposes all parent pointers, child rows, quotient certificates, and FormulaEval influences.

Equation 3: ledger.

$$Gamma_Q rep(pi) = Gamma_b EF(pi) + U_N + X_N + C_C TSR + C_Q cert + C_r ep$$

Valid when: Valid when each support row expansion costs Theta(N) in the same nonuniform SIZE model and all certificate bits are charged.

Equation 4: parser_upper_bound.

$$C_S IZE(H_N^S AT) \leq N^{rho+o(1)} + Gamma_Q rep(pi) + O(E_p iN)$$

Valid when: Valid when the parser line induction has no hidden semantic use and patchable row errors are explicitly bounded.

Equation 5: contrapositive_window.

$$LB_N(1+epsilon) implies Gamma_Q rep(pi) + O(E_p iN) \geq N^{1+epsilon-o(1)}$$

Valid when: Valid when LB_N means a same-model lower-bound assertion for H_N rather than any NP lower bound.

Equation 6: support_density_corollary.

$$|K_i dx(pi)|/M_N \geq N^{epsilon-q-o(1)}$$

Valid when: Valid when row expansion dominates the ledger and each visible source row contributes Theta(N) charged gates.

Next analysis. Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge counter-model, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and $\mathrm{P} \neq \mathrm{NP}$.

Falsifiers.

- first unranked quotient merge falsifier: a row is deleted without a charged same-theory certificate
- cyclic or nondecreasing-rank certificate falsifier: the representative map is not well-founded
- advice-chosen representative falsifier: nonuniform leakage selects a merge invisible to K_Qrep(pi)
- hidden semantic pruning falsifier: an unlisted counterfactual child changes the proof while the transcript stays fixed
- positive β falsifier for broader magnification claims: SAT $\in$ SIZE(n^c) transfers only to N^{q+beta c+o(1)} source size
- $q < \epsilon$ enumeration falsifier: too little absolute support density makes LB_N(1+epsilon) incompatible with the parser upper bound

cycle-0150: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 107.027 seconds; 3 lemmas, 4 equations, 8 derivation steps, 6 falsifiers.

Learning. Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.

Pressure. The derivation does not cover a semantic pruning step that obtains a quotient or child deletion from real SAT truth without a surfaced same-theory certificate; that remains exactly $RealSATInfluenceRealizer_N^{arb}$.

Derivation steps.

1. Initialize K_0 with the final LB_N line and the carrier definition H_N^{SAT}; add bit-explicit EF dependencies exactly as in Γ_{bEF}.
2. For each reachable FormulaEval line, insert the visible row selector support and charge either U(K) for uniform enumeration or the full scan charge; add occurrence expansion to X(K).
3. For each counterfactual TSR line, insert every reachable child row, not merely the actual branch; this preserves extensional safety under private-row variations.
4. For each quotient merge, require a lower-rank same-theory certificate forest proving equality of SAT truth for the merged children; add all certificate dependencies before replacing children by the representative.
5. Because ranks strictly decrease along certificate dependencies, the fixed point is finite and order-independent; representative stability follows by choosing the least certified representative in each connected component.
6. Line induction: after each proof line, every formula value used by the parsed circuit is either bit-explicit, a charged row in K_{Qrep}, or a value transported along a charged same-theory certificate, so the line has circuit cost bounded by the accumulated Γ_{Qrep} ledger.

7. Hardwire pi, the generator G_N, K_{Qrep}, and D_Q nonuniformly; compute H_N by the generator plus the parsed transcript and sparse residual patches, giving C_SIZE(H_N)<=N^{rho+o(1)}+Gamma_Qr N).

8. Contrapose: if LB_N(1+epsilon) asserts $C_{\mathrm{SIZE}}(H_N) > N^{1+\epsilon-o(1)}$, any transcript with N^{rho+o(1)}+Gamm N)<N^{1+epsilon-o(1)} is a valid same-model falsifier for that claimed source lower-bound certificate.

Equation 1: parity_carrier.

$$H_N^{SAT}(x) = \bigoplus_{j<M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d.$$

Valid when: Valid when N is a carrier length and G_N is the fixed beta-zero polylog-query generator used by the proof transcript.

Equation 2: least_qrep_closure.

$$K_{t+1} = K_t \cup Dep_{bEF}(K_t) \cup FE(K_t) \cup CTSR_{cf}(K_t) \cup CertDeps_Q(K_t), \quad K_{Qrep} = \bigcup_t K_t.$$

Valid when: Valid when the proof syntax exposes parent pointers, counterfactual child lists, and ranked quotient-certificate dependencies before each compressed use.

Equation 3: qrep_ledger.

$$\Gamma_{Qrep}(\pi) = \Gamma_{bEF}(\pi) + U(K_{Qrep}) + X(K_{Qrep}) + C_Q(D_Q) + O(E_\pi N).$$

Valid when: Valid when every row enumeration, occurrence expansion, quotient certificate, and sparse residual patch is charged in the same nonuniform SIZE ledger.

Equation 4: upper_bound_falsifier.

$$C_{SIZE}(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{Qrep}(\pi) + O(E_\pi N).$$

Valid when: Valid when the parsed transcript is hardwired nonuniformly and each SAT influence row is represented by K_{Qrep} or by a charged same-theory certificate.

Next analysis. Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.

Falsifiers.

- first unranked quotient merge falsifier: an omitted child row varies privately while all charged support stays fixed
- cyclic or nondecreasing rank certificate falsifier: the alleged dictionary is not a finite dependency-closed proof object

- advice-chosen representative falsifier: the representative map encodes hidden SAT-label information outside Γ_{Qrep}
- hidden semantic pruning falsifier: actual-branch-only TSR support misses a counterfactual child reachable from the final line
- positive β black-box substitution falsifier: q+beta c reaches 1+epsilon before all target exponents are excluded
- $q < \epsilon$ support-density falsifier: subthreshold reachable support can be equality-patched below the claimed LB_N threshold

cycle-0151: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt compact_retry; 226.702 seconds; 1 lemmas, 3 equations, 4 derivation steps, 4 falsifiers.

Learning. Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined.

Pressure. The derivation does not realize arbitrary semantic SAT pruning; $RealSATInfluenceRealizer_N^{arb}$ remains the named nonrelativizing bridge for full Psys_{sym}.

Derivation steps.

1. Initialize K_{pref} from the final LB_N line; iteratively add ordinary parents, FormulaEval influences, and every earlier Qrep dictionary entry used by a reachable line.
2. For a quotient lookup r $\to$ rep, add the lower-rank same-theory certificate forest and charge its row expansions in D_{Qrep}; append-only order makes the representative stable for all later lines.
3. Run the existing Γ_{bEF} line induction with dictionary lookups replaced by charged representative circuits and certificate checks; no line reads an uncharged row.
4. If Γ_{pref} is subthreshold, combine the generator circuit with the transcript circuit and sparse-row patching to obtain a same-model circuit for H_N, contradicting the asserted LB_N.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x, j)), \quad M_N = N^{q+o(1)}.$$

Valid when: Valid when G_N is uniform and bit-explicit, $M_N = N^{q+o(1)}$, and queried SAT instances have polylog length so β equals zero.

Equation 2: prefix_ledger.

$$\Gamma_{pref}(\pi) = \Gamma_{bEF}(\pi) + U(K_{pref}) + X(K_{pref}) + D_{Qrep}(\pi) + O(E_\pi N).$$

Valid when: Applies when every dictionary entry is appended before first use, certificate dependencies are lower rank, and row supports are influence closed.

Equation 3: subthreshold_falsifier.

$$N^{\rho+o(1)} + \Gamma_{pref}(\pi) < N^{1+\epsilon-o(1)} \Rightarrow C_{SIZE}(H_N^{SAT}) < N^{1+\epsilon-o(1)}.$$

Valid when: Requires the target-preserving same-model SIZE simulation, q and ρ below 1+epsilon, and no hidden semantic support or representative advice.

Next analysis. Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.

Falsifiers.

- Prefix-use falsifier: a quotient lookup before its batch certificate is introduced leaves a private row uncharged; flip it while preserving all charged transcript rows.
- Rebinding falsifier: if a representative map changes after use, two worlds agree on the old charged cone but differ on the later representative parity.
- Rank-cycle falsifier: a nondecreasing or cyclic same-theory certificate lets a merge justify itself, so Γ reduction is advice-like rather than valid proof-carrying compression.
- Hidden-pruning falsifier: semantic branch selection that omits a counterfactual child is outside Qrep unless $RealSATInfluenceRealizer_N^{arb}$ lists and charges the missing row.

cycle-0152: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure

Execution. research; azure_responses_api; attempt primary; 62.825 seconds; 2 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result.

Pressure. The restricted PrefixStableQrepTransparentSupport proof is theorem-shaped; the unresolved extension remains $RealSATInfluenceRealizer_N^{arb}$ for hidden full semantic SAT pruning and branch selection.

Derivation steps.

1. Define K_{PQ}^0 as the final LB_N line plus its parsed bit-explicit parents. Iterate: add EF dependencies, SATeq certificate rows, $bounded - SR_h$ leaves, reachable FormulaEval support rows, all counterfactual TSR children, and for each Qrep representative use add the lower-rank same-theory certificate forest and its row dependencies.
2. Prove termination by the finite proof DAG size plus a strict lexicographic measure: proof-line index, dictionary append time, and rank. Prefix stability forbids cycles and rebinding, so the fixed point is order-independent.

3. For each proof line l, maintain invariant I(l): all rows semantically influencing l through transparent rules are in K_{PQ} restricted to prefix l, and the circuit transcript for l has size at most the accumulated Γ_{PQ} charge plus generator overhead already charged.

4. EF and SATeq cases reuse the prior Γ_{bEF} parser; $bounded{-}SR_h$ contributes $B_{SR} \leq N^{q+\eta+\tau+o(1)}$; FormulaEval contributes U(K)+X(K); counterfactual TSR contributes $N^{1+\kappa+\theta+o(1)}$ for complete child declarations.

5. Qrep case: replacing r_old by representative r_new is sound because the certificate C_e is same-theory, lower-rank, and already parsed into the prefix closure. The row deletion saves duplicate expansion only after D_Q(pi) has charged the dictionary entry and certificate forest.

6. At the final LB_N line, compose the generator circuit, parsed transcript circuit, and equality patches for E_{pi} exceptional rows to obtain C(H_N)<=N^{rho+o(1)}+Gamma_PQ(pi)+O(E_pi N).

7. If this upper bound is below $N^{1+\epsilon-o(1)}$, it is a same-model falsifier for LB_N(1+epsilon). This proves only failure of that proof certificate or lower-bound assertion in the restricted parser model.

Equation 1: carrier.

$$H_N^{SAT}(x) = xor_{j=1}^{M_N} SAT(G_N(x,j)), M_N = N^{q+o(1)}$$

Valid when: Valid when the source carrier is the beta-zero parity aggregator with a uniformly parsed generator and visible row indices.

Equation 2: ledger.

$$Gamma_P Q(pi) = Gamma_b EF(pi) + U(K_P Q) + X(K_P Q) + D_Q(pi) + B_C TSR(pi)$$

Valid when: Valid when K_{PQ} is the least prefix-stable closure and every dictionary, quotient, and counterfactual TSR dependency is charged before use.

Equation 3: upper_bound.

$$C(H_N^{SAT}) \leq N^{rho+o(1)} + Gamma_P Q(pi) + O(E_p iN)$$

Valid when: Applies after the parser line induction produces a circuit transcript in the same nonuniform SIZE model with all residual bad rows equality-patched.

Equation 4: falsifier_threshold.

$$N^{rho+o(1)} + Gamma_P Q(pi) + O(E_p iN) < N^{1+epsilon-o(1)} => notLB_N(1+epsilon)$$

Valid when: Requires the asserted LB_N source lower bound to be in the same circuit model and quantified over the same valid lengths.

Equation 5: q_density_corollary.

$$|K_i dx(pi)|/M_N \geq N^{epsilon-q-o(1)} whenper - rowexpansioncostsN$$

Valid when: Valid when FormulaEval rows are expanded to occurrence rows with unit N charge and $M_N = N^{q+o(1)}$ slots.

Next analysis. Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.

Falsifiers.

- falsifier: a Qrep representative used before its proof-carrying dictionary certificate is appended invalidates the charged parser and yields a private-row two-world countermodel.
- falsifier: representative rebinding lets two prefixes share the same visible transcript while later quotient meaning changes, so Γ_{PQ} is not valid.
- falsifier: a rank cycle in same-theory certificates destroys the least fixed point and blocks line induction.
- falsifier: advice-chosen dictionary compression hides semantic row selection and is outside $TransparentRowSupp$
- falsifier: full semantic branch pruning without $RealSATInfluenceRealizer_N^{arb}$ remains quarantined, even if the restricted Qrep ledger is valid.

cycle-0153: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit

Execution. research; azure_responses_api; attempt primary; 79.095 seconds; 3 lemmas, 5 equations, 6 derivation steps, 7 falsifiers.

Learning. Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_I$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress.

Pressure. The derivation does not cover arbitrary semantic FormulaEval or adaptive SAT-pruning rules that may realize influence through real SAT semantics without exposing row identifiers; that remains $RealSATInfluenceRealizer_N^{arb}$.

Derivation steps.

1. Define Dict_Q(pi) as append-only entries e=(row a, representative rep(a), rank r, certificate forest F_e, cert_line, first_use_line). Reject entries with $cert_{line} \geq first_{use,line}$, cyclic dependencies, nondecreasing dependency rank, or rebinding of a previously used representative.
2. Compute K_Qrep(pi) by the least fixed point from the final LB_N line: add ordinary bit-explicit dependencies, transparent FormulaEval row dependencies, CTSR counterfactual children, and for every Qrep use add the representative row plus all lower-rank certificate dependencies already present in the prefix.
3. Induct on proof lines. Ordinary $Psys^-_{bEF}$ lines use the existing Γ_{bEF} parser. Transparent FormulaEval lines contribute $U_N + X_N$. Qrep lines are simulated by substituting the charged representative expansion and the prior same-theory certificate forest; no new uncharged occurrence neighborhood is introduced.

4. The circuit extracted from the parsed transcript evaluates H_N using the generator circuit, charged row support, SAT-substitution for exposed polylog queries, and equality patches for E_{pi} source-row failures, giving C_N(H_N)<=N^{rho+o(1)}+Gamma_Qrep(pi)+O(E_pi N).

5. Contrapose the same-model lower-bound claim LB_N(1+epsilon). If the right side is subthreshold, the proof transcript itself is a valid upper-bound falsifier for the claimed source lower bound.

6. For necessity, take the least line u violating strict prefix visibility. Hold all visible prefix bits fixed, flip the hidden private row or unread enable bit, and observe that the transcript before u is unchanged while the representative use can change the selected support or parity. This refutes hidden Qrep as transparent parsing.

Equation 1: Qrep ledger.

$$Gamma_Qrep(pi) = Gamma_bEF(pi) + U_N(pi) + X_N(pi) + D_Q(pi)$$

Valid when: Valid when $\mathrm{Psys}_{sym}^{dag+Qrep}$ exposes row support, FormulaEval expansion, and prefix-strict Qrep certificates before every representative use.

Equation 2: Dictionary charge.

$$D_Q(pi) = sum_{einDict_Q(pi)}(|desc(e)| + |cert(e)| + sum_{aindep(e)}row_cost(a))$$

Valid when: Valid when dictionary entries are ranked, acyclic, dependency-closed, and no dependency is introduced after the representative is used.

Equation 3: Parser-to-circuit upper bound.

$$C_N(H_N^SAT) \leq N^{rho+o(1)} + Gamma_Qrep(pi) + O(E_piN)$$

Valid when: Applies after the line induction parses every proof line into charged source-row support in the same nonuniform SIZE model.

Equation 4: Subthreshold falsifier inequality.

$$N^{rho+o(1)} + Gamma_Qrep(pi) + O(E_piN) < N^{1+epsilon-o(1)} => notLB_N(1+epsilon)$$

Valid when: Requires LB_N(1+epsilon) to mean a same-model $N^{1+\epsilon-o(1)}$ lower bound for the explicit source carrier H_N^{SAT}.

Equation 5: Strict-prefix condition.

$$foralle, cert_line(e) < first_use_line(e) and rank(dep(e)) < rank(e)$$

Valid when: Valid when Qrep compression is proof-carrying rather than a semantic row-deletion convention or advice-chosen quotient map.

Next analysis. Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.

Falsifiers.

- first representative use before certificate charge is a temporal private-row falsifier
- representative rebinding after prior use destroys prefix stability and invalidates Γ_{Qrep}
- cyclic or nondecreasing-rank dictionary dependencies prevent a finite valid verifier
- advice-chosen quotient representatives create nonuniform leakage outside $TransparentRowSupport_N$
- hidden semantic SAT-pruning remains quarantined unless $RealSATInfluenceRealizer_N^{arb}$ lists and charges the influence rows
- positive target-query exponent β would reintroduce the black-box transfer cap q+beta c+o(1) and block all-exponent magnification
- subthreshold Gamma_Qrep(pi)+O(E_pi N) is an upper-bound falsifier for any claimed LB_N(1+epsilon) proof transcript

cycle-0154: Hardness-Magnification Bridge Realization

Execution. research; azure_responses_api; attempt primary; 75.659 seconds; 3 lemmas, 5 equations, 7 derivation steps, 5 falsifiers.

Learning. Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.

Pressure. The derivation does not cover arbitrary semantic SAT branch pruning or FormulaEval rules whose influencing rows are not determined by proof syntax before use; this is exactly $RealSATInfluenceRealizer_N^{arb}$.

Derivation steps.

1. Define K_{Qrep}^t by prefix recursion: start with bEF, SR_h, FormulaEval, and CTSR visible supports; when a Qrep dictionary entry e appears, add its row endpoints and certificate footprint only if every dependency is already in $K_{Qrep}^{<t}$ and every rank decreases.
2. For non-Qrep lines, reuse the existing $\Gamma_{bEF}/\Gamma_{dag}$/CTSR line-induction invariant: each parsed proof dependency either contributes a charged row or is already in the support cone.
3. For a Qrep use at line t, replace the quotient representative by the row rep_e plus the strict-prefix same-theory certificate forest sigma_e. Since sigma_e is already charged, the replay adds no post-hoc support and preserves the carrier row semantics used by the parser.

4. Compose all replays in line order. Rank decrease and prefix ordering prevent cycles and representative rebinding, so the expanded proof has the same final LB_N line and total support bounded by Γ_{Qrep}.

5. Build the nonuniform circuit for H_N from the generator circuit, parsed row computations, charged FormulaEval/TSR/Qrep support, and equality patches for E_{pi} residual rows, obtaining C(H_N)<=N^{rho+o(1)}+Gamma_Qrep+O(E_pi N).

6. Contrapose the claimed source lower bound LB_N(1+epsilon): if the displayed upper bound is below $N^{1+\epsilon-o(1)}$, the claimed proof-mediated lower-bound certificate is falsified in the same model.

7. For necessity, choose the first unsafe quotient use. Keep the visible prefix fixed, toggle an uncharged private row or unread enable bit that controls same-theory status, and obtain two worlds with identical accepted prefix but different uncovered parity or certificate truth.

Equation 1: carrier.

$$H_N^{SAT}(x) = \bigoplus_{j \le M_N} SAT(G_N(x,j)), \quad M_N = N^{q+o(1)}, \quad |G_N(x,j)| = (\log N)^d.$$

Valid when: Valid when the beta-zero parity carrier has explicit generator G_N, polylog target formulas, and all slots are indexed without advice.

Equation 2: qrep_ledger.

$$\Gamma_{Qrep}(\pi) = \Gamma_{bEF}(\pi) + U(K_{Qrep}) + X(K_{Qrep}) + \sum_{e \in Dict(\pi)} (|\sigma_e| + |row(e)|)\, N^{o(1)}.$$

Valid when: Valid when K_Qrep(pi) is the least strict-prefix support closure and every dictionary certificate is charged before representative use.

Equation 3: parser_upper_bound.

$$C(H_N^{SAT}) \le N^{\rho+o(1)} + \Gamma_{Qrep}(\pi) + O(E_\pi N).$$

Valid when: Valid when the line induction is performed in the same nonuniform SIZE model and equality patches charge every residual bad row.

Equation 4: lb_falsifier_window.

$$N^{\rho+o(1)} + \Gamma_{Qrep}(\pi) + O(E_\pi N) < N^{1+\epsilon-o(1)} \Rightarrow \neg LB_N(1+\epsilon).$$

Valid when: Applies when LB_N(1+epsilon) asserts a same-model $N^{1+\epsilon-o(1)}$ lower bound for the named carrier.

Equation 5: support_density_corollary.

$$LB_N(1+\epsilon) \wedge \rho < 1+\epsilon \Rightarrow |K_{idx}(\pi)| \ge N^{\epsilon-o(1)}, \quad |K_{idx}|/M_N \ge N^{\epsilon-q-o(1)}.$$

Valid when: Requires the claimed LB_N(1+epsilon) to survive the parser upper bound and $M_N = N^{q+o(1)}$ slots.

Next analysis. Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

Falsifiers.

- First late Qrep merge: representative used before its same-theory certificate is charged, producing a private-row falsifier.
- Rank cycle or representative rebinding: replay is not well-founded, so Γ reduction is invalid.
- Advice-chosen dictionary: K_{Qrep} is not determined by N and pi, causing nonuniform leakage.
- Hidden semantic pruning: the proof uses real SAT structure without listing influencing rows, blocked at $RealSATInfluenceRealizer_N^{arb}$.
- Positive β black-box substitution remains a separate threshold-collapse falsifier: q+beta c can exceed 1+epsilon before all SAT exponents are excluded.

E Current Ranked Next-Analysis Queue

Ordered by target payoff, discriminating power, execution readiness, target integration, and anti-drift pressure. The score is a control signal for the next run, not a theorem-progress claim.

#1 pvsnp.paper.bit-explicit-parser-formulaeval-boundary: Prove the $TransparentRowSupport_N$ theorem pair and stop selector-case accumulation

Analysis. Proof-delivery task sharpened from cycles 103-107: stop adding isolated selector classes and consolidate interval-union, scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete FormulaEval cases under one $TransparentRowSupport_N$ abstraction. Prove the positive $\Gamma - extension$ theorem for transparent row support, prove the private-row/unread-enable-bit countermodel theorem for hidden semantic support, and state $RealSATInfluenceRealizer_N$ as the exact remaining escape rather than a vague semantic gap.

Why this is a good target. $TransparentRowSupport_N$ theorem pair: if a Psys_{sym} FormulaEval mechanism has visible selector code, advice-free enumeration or full-scan charge, influence closure, same-theory occurrence expansion, and no hidden support advice, then $\Gamma_{trans}(pi) = \Gamma_{bEF}(pi) + U_N + X_N$ gives the parser-to-circuit falsifier N^{rho+o(1)}+Gamma_trans(pi)<N^{1+epsilon-o(1)} for LB_N(1+epsilon). If any visibility, extensionality, or influence-closure condition fails, construct the private-row/unread-enable-bit countermodel to surface occurrence completion.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Cycles 103-107 FormulaEval selector packets over $H_N^{\mathrm{SAT}}(x) = xor_{j \le M_N}$ SAT(G_N(x,j)), with $M_N = N^{q+o(1)}$, generator overhead $N^{\rho+o(1)}$, polylog formula length, bit-explicit Psys_{bEF} parser costs, and selector cases including interval unions, full scans, ROBDD, guarded dDNNF, projected dDNNF, and influence-complete extension rules.

Target object. A paper-core theorem/countermodel pair replacing the selector zoo: one transparent-support theorem, one hidden-support countermodel theorem, examples as corollaries, and $RealSATInfluenceReal$ as an open problem.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: define $TransparentRowSupport_N$ as a reusable finite proof-system interface over Psys_{sym} FormulaEval lines.
- Proof step: prove that every transparent FormulaEval line contributes either a certified enumerator charge U_N or a full-scan charge $F_{FE}\ N^{1+q+o(1)}$, plus the row-expansion charge X_N.
- Proof step: extend the existing bit-explicit Psys_{bEF} line induction to $\Gamma_{trans}(pi) = \Gamma_{bEF}(pi) + U_N + X_N$.
- Proof step: derive the upper-bound falsifier N^{rho+o(1)}+Gamma_trans(pi) not LB_N(1+epsilon) in the same nonuniform SIZE model.
- Proof step: prove the hidden-support countermodel: if a FormulaEval row can influence the proof without being visible and charged, two transcripts agree while the selected support or carrier parity differs.
- Proof step: demote additional selector classes to examples unless they prove or refute a $TransparentRowSupport$ clause.
- Proof step: run proof-quality, barrier-specificity, quantifier-uniformity, proof-complexity-transfer, and inference-quality reviewers before promotion.

Payoff criteria.

- $TransparentRowSupport_N$ is formal enough that an independent reader can decide whether a FormulaEval rule satisfies it.
- Gamma_trans(pi) is derived rather than asserted, and the falsifier inequality states ρ, q, ϵ, U_N, X_N, η, τ, E_N, and all o(1) regimes.
- The private-row/unread-enable-bit countermodel is stated as a theorem with hypotheses, not as a metaphor.
- Selector cases are reorganized into examples/corollaries; no new selector family is promoted as a separate main contribution.
- The output advances a paper-level subgoal: a clean theorem pair and open-problem boundary, not another restatement of the obstruction ladder.

Stop criteria.

- Demote if the work adds another selector class without changing the $TransparentRowSupport_N$ definition, theorem, or countermodel.
- Demote if Gamma_trans(pi), K_idx(pi), U_N, X_N, or the transcript upper bound is named without a derivation.
- Demote if semantic FormulaEval is described as generic power rather than handled by $RealSATInfluenceRealiz$ or the private-row countermodel.
- Demote if the branch broadens into MCSP/MKtP, natural-proofs folklore, or generic barriers before the theorem pair is written.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-delivery-workflow-orchestrator
- proof-gap-countermodel-splitter
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-forcedrows-proof-workflow
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-negative-tactic-selector
- pvsnp-pressure-bridge-forger
- pvsnp-proof-complexity-transfer-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#2 pvsnp.paper.l1201-least-closed-support-proof-audit: Write the L120.1 least-closed support proof-audit packet

Analysis. Turn cycle 120's least prefix-closed reachable FormulaEval support cone into a referee-checkable proof packet. The task is to define the fixed-point computation of K_dag(pi), give verifier-visible dependency-closure pseudocode, prove the Γ_{dag} line-induction invariant, and test the theorem on one projected-dDNNF FormulaEval example plus one unread-enable-bit counterexample.

Why this is a good target. $LeastClosedTransparentSupport_N$ / L120.1: for a $\mathrm{Psys}^{dag}_{sym}$ proof pi whose FormulaEval lines expose parent pointers and support certificates, the least prefix-closed reachable cone K_dag(pi) from the final LB_N line is the minimal charged object needed for the parser-to-circuit falsifier N^{rho+o(1)}+Gamma_dag(pi)+O(E_pi N)<N^{1+epsilon-o(1)}.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Cycle 120 theorem claims over $H_N^{\mathrm{SAT}}(x) = xor_{j \le M_N}$ SAT(G_N(x,j)), $\mathrm{Psys}^{dag}_{sym}$ FormulaEval lines, dependency edges from later symbolic uses to earlier row supports, and the cost ledger Gamma_dag(pi)=Gamma_bEF(pi)+U(K_dag(pi))+X(K_dag(pi)).

Target object. A self-contained proof-audit packet that an independent reader can run mentally or mechanically: input pi,N; compute K_dag(pi); either certify prefix-closed support and Γ_{dag}, or return the first hidden reachable row with its private-row/unread-enable-bit countermodel.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: define the line-dependency DAG, support-token universe, and ancestor relation from the final LB_N line.
- Proof step: prove the least fixed point K_dag(pi) exists, is unique, and is computable from proof syntax and N without advice.
- Proof step: prove unreachable FormulaEval rows can be deleted without changing the retained line induction.
- Proof step: prove each retained FormulaEval support either pays U(K)+X(K) or triggers the first-hidden-row falsifier.
- Proof step: instantiate the positive and negative examples and attach an inference-quality packet before promotion.

Payoff criteria.

- The fixed-point algorithm for K_dag(pi) is explicit enough to implement or audit line by line.
- Γ_{dag} is derived from the closure invariant, not asserted by analogy with Γ_{trans}.
- The projected-dDNNF example and unread-enable-bit counterexample both exercise the theorem boundary.
- The result states that it is a scoped parser/falsifier theorem and not evidence for P $\neq$ NP.

Stop criteria.

- Demote if K_dag(pi) is described informally without a computable closure algorithm.
- Demote if the proof does not distinguish reachable support from the full selector zoo.
- Demote if the examples do not compute charges or do not expose a first hidden reachable row.
- Demote if the theorem silently assumes full semantic SAT influence instead of charging it.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-delivery-workflow-orchestrator
- proof-gap-countermodel-splitter
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-forcedrows-proof-workflow
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-negative-tactic-selector
- pvsnp-pressure-bridge-forger
- pvsnp-proof-complexity-transfer-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer

- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#3 pvsnp.paper.realsat-influence-realizer-boundary: Resolve or quarantine $RealSATInfluence$ for one concrete semantic FormulaEval rule

Analysis. Attack the exact remaining full-semantic FormulaEval gap instead of naming it abstractly. Choose one concrete semantic FormulaEval rule, such as Tseitin-extension equality plus bounded self-reduction, and either produce an advice-free nonrelativizing realizer listing all influencing rows with charges, or prove a rule-specific private-row/no-realizer countermodel.

Why this is a good target. $RealSATInfluenceRealizer_N$ boundary theorem: full semantic FormulaEval can be folded into the transparent support theorem only when proof syntax and N uniformly determine an influence-closed row set R_A, same-theory row expansions, and a charged overhead R_N before the semantic rule is used.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Semantic FormulaEval-SAT rules over H_N^{SAT} generated rows where real SAT semantics, formula equality, Tseitin extensions, or self-reduction may make a proof line depend on rows not visible in a syntactic $TransparentRowSupport_N$ certificate.

Target object. A yes/no boundary for one named semantic rule: either a valid $RealSATInfluenceRealizer_N$ certificate with $\Gamma_{real} = \Gamma_{bEF} + U + X + R_N$, or a finite countermodel showing why that semantic rule remains quarantined.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: pick exactly one semantic FormulaEval rule and freeze its proof-system syntax.
- Proof step: define which generated SAT rows can influence the rule value and what counts as a charged witness.
- Proof step: attempt to construct R_A and same-theory expansions from proof syntax and N alone.
- Proof step: if the construction fails, build the private-row/unread-enable-bit countermodel for that rule.
- Proof step: record whether the rule joins the transparent theorem or remains quarantined as semantic power.

Payoff criteria.

- The selected semantic rule is concrete enough that the realizer or countermodel is independently checkable.
- All influence rows are uniformly listed and charged, or the exact unchargeable semantic step is named.
- The output eliminates vague language about semantic FormulaEval and replaces it with a rule-level theorem or no-go.

Stop criteria.

- Demote if $RealSATInfluenceRealizer_N$ is only restated without choosing a semantic rule.
- Demote if the row set uses SAT-truth advice or hidden nonuniform row selection.
- Demote if the claimed realizer omits R_N from the Γ ledger.
- Demote if the negative result does not identify the first semantic inference that cannot be charged.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-delivery-workflow-orchestrator
- proof-gap-countermodel-splitter
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-forcedrows-proof-workflow
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-negative-tactic-selector
- pvsnp-pressure-bridge-forger
- pvsnp-proof-complexity-transfer-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner

- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#4 pvsnp.paper.l120-theorem-countermodel-package: Package the cycle-120 theorem/countermodel pair as a paper-ready module

Analysis. Assemble the least-closed transparent-support theorem, hidden-support countermodel, $RealSATInfluenceRealizer_N$ open boundary, q-trichotomy support-density corollary, and selector-example table into one coherent paper module. The package must be readable without marathon context.

Why this is a good target. Paper module: a scoped parser/falsifier contribution for FormulaEval in beta-zero parity magnification, showing exactly when transparent FormulaEval yields a same-model upper-bound falsifier and exactly where hidden semantic influence escapes the controlled interface.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Cycles 116-120, especially L120.1 $LeastClosedTransparentSupport_N$, L120.2 $UnreachableSupportDeletion_N$, L120.3 $FirstHiddenReachableUse_N$, and the branch outputs that state Γ_{dag}, hidden-row falsifiers, and qepsilon support-density cases.

Target object. A paper-ready theorem/countermodel section with definitions, theorem statements, proof sketches, examples, non-claims, and a handoff to the broader parity magnification/full-row barrier draft.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: consolidate definitions and notation from cycles 116-120 into one local ledger.
- Proof step: write theorem/countermodel statements before examples, so selector cases cannot become separate main routes.
- Proof step: attach proof sketches that cite the L120.1 audit packet and $RealSAT$ boundary item where needed.
- Proof step: state non-claims and model boundaries explicitly.
- Proof step: validate against proof-delivery and inference-quality gates.

Payoff criteria.

- The module is understandable as a standalone paper section.
- The positive theorem, negative countermodel, and semantic open boundary are separated cleanly.
- Examples are corollaries/examples only; no new selector zoo is created.
- The paper handoff preserves the scoped claim and does not oversell P vs NP progress.

Stop criteria.

- Demote if the package is a report summary rather than theorem/countermodel text.
- Demote if it depends on marathon-specific workflow language.
- Demote if it blurs transparent extensional FormulaEval with full semantic SAT FormulaEval.
- Demote if it omits the q-trichotomy or the non-claims.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-delivery-workflow-orchestrator
- proof-gap-countermodel-splitter
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-proof-complexity-transfer-reviewer
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#5 pvsnp.paper.l120-inference-quality-gate-closure: Close the L120 inference-quality and marker gaps before promotion

Analysis. Prepare the promotion gate for the L120 theorem work. Emit a fresh pvsnp_inference_quality packet for the least-closed support theorem, run the reviewer stack, and repair any source/target/model/validity marker gaps before treating the theorem package as a paper result.

Why this is a good target. Validation theorem for promotion readiness: every L120 claim has explicit source object, target object, controlled interface, target-preserving condition, reduction direction, quantifiers, advice discipline, barrier scope, and proof-complexity transfer status.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. The live L120 claims, the 93 active inference-quality packets, and the discovery report warning that not all source/target/same-theory/validity markers are globally present.

Target object. A repaired inference-quality packet and gate report that says exactly which L120 claims are promotable, which are conditional, and which remain blocked at $RealSATInfluenceRealizer_N$.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: write the IQ packet from the actual theorem text, not from a marathon summary.
- Proof step: run each reviewer lens and convert objections into proof obligations or demotion notes.
- Proof step: repair missing markers in the queue/report artifacts if validation finds them.
- Proof step: record a final promotion verdict before paper integration.

Payoff criteria.

- The L120 theorem package has a live IQ packet that passes validation.
- No source/target/model/validity marker is implicit.
- Reviewer objections are either discharged, converted to named obligations, or marked as demotion blockers.
- The promotion verdict is conservative and explicitly says what is not proved.

Stop criteria.

- Demote if the IQ packet claims P vs NP progress rather than a scoped parser/falsifier result.
- Demote if source and target models are not the same nonuniform SIZE model.
- Demote if $RealSATInfluenceRealizer_N$ is treated as solved without a rule-level proof.
- Demote if validation fails and the failure is not converted into a concrete repair item.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-complexity-transfer-reviewer
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer

#6 pvsnp.paper.full-row-barrier-proof-audit: Audit and package the draft's proved beta-zero/full-row barrier theorem chain

Analysis. Proof-audit task extracted from the draft theorem stack: rebuild the exponent-window, batched substitution, beta-zero transfer, equality patching, naturalization, row-forcing, parity full-row, parser-to-query, incidence-sketch, and one-sided forcing proofs as a dependency-checked proof packet.

Why this is a good target. Verified theorem-chain packet: beta-zero transfers remove exponent debt; functional certificates naturalize; occurrence-relativizing parity certificates pay Omega(M_n s_n/n).

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. The draft's proposition/lemma/theorem environments and their dependency graph.

Target object. A paper-ready proof packet with explicit hypotheses, quantifiers, non-claims, and theorem dependencies.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: extract every theorem/proposition/corollary proof from the draft and list its exact assumptions.
- Proof step: check exponent arithmetic and the beta-zero disappearance of the target circuit exponent c.

- Proof step: verify that equality patching and residual threshold use only row exceptions and O(n) equality predicates.
- Proof step: verify naturalization hypotheses are dense, constructive, and functional over arbitrary label tables.
- Proof step: verify row-forcing uses occurrence-completion soundness and not real SAT semantics.

Payoff criteria.
- Every proved draft statement has assumptions, conclusion, proof dependencies, and barrier scope recorded.
- No step silently upgrades occurrence-label statements to formula-label or full proof-system statements.
- The theorem chain is ready for paper insertion or referee-style proof checking.

Stop criteria.
- Demote if any proof uses an unstated uniformity, density, constructivity, or formula-realizability assumption.
- Demote if theorem dependencies are circular or if the draft's non-claims are not preserved.

Do not stop if.
- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.
- lemma-chain-proof-builder
- proof-delivery-workflow-orchestrator
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-proof-complexity-transfer-reviewer
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#7 pvsnp.paper.explicit-hard-generator-open-problem: Attack the explicit hard-generator/source-lower-bound open problem

Analysis. Open-problem task extracted from the draft discussion: construct or rule out a label-independent batched generator with polylogarithmic SAT instances, $M_n = n^{q+o(1)}$, generator size $n^{\rho+o(1)}$, $q, rhon^{1+\epsilon-o(1)}$.

Why this is a good target. Source-lower-bound theorem or impossibility diagnosis for a concrete beta-zero SAT parity carrier.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Candidate batched generator G_n and parity carrier H_n^{SAT} from polylog-length SAT formulas.

Target object. A source lower bound strong enough to activate the beta-zero magnification corollary, or a precise obstruction explaining why the candidate collapses.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of $\mathrm{P} \neq \mathrm{NP}$.

Validation steps.

- Proof step: define the generator and compute q, ρ, d, $|U_n|$, collision structure, and formula-realizability constraints.
- Proof step: run incidence-sketch falsification before claiming lower-bound promise.
- Proof step: attempt a lower-bound route or derive an impossibility/upper-bound certificate.
- Proof step: verify that any lower bound is for general circuits on the scalar carrier, not only incidence rank or restricted models.

Payoff criteria.

- A concrete generator is named with verified beta-zero transfer parameters.
- The branch produces either a real lower-bound lemma, a reproducible upper-bound falsifier, or a sharp reason it cannot be the source problem.
- Any claimed progress distinguishes scalar circuit lower bounds from incidence-linear diagnostics.

Stop criteria.

- Demote if no explicit generator is specified.
- Demote if the evidence is only high rank, randomness intuition, or incidence complexity without a general-circuit lower-bound bridge.
- Demote if q or ρ fails the stated threshold needed by the transfer theorem.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-delivery-workflow-orchestrator
- proof-gap-countermodel-splitter
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-forcedrows-proof-workflow
- pvsnp-impossibility-theorem-forger
- pvsnp-qualitative-complexity-reasoner
- pvsnp-symbolic-complexity-auditor

#8 pvsnp.paper.strong-system-parser-instantiation: Instantiate the parser-to-query consequence for a concrete strong proof system

Analysis. Open-problem/proof task extracted from the draft's strong-system paragraph and Proposition parser-to-query: choose a concrete proof formalism for lower-bound statements, define exactly which formula equality and SAT semantic facts it can access, and prove or refute the parser property that maps accepted proofs pi to occurrence transcripts Q_{pi}.

Why this is a good target. Concrete parser-to-query instantiation theorem or counterexample for a named proof system.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Named proof formalism, proof pi, verifier/parser, and allowed SAT/equality axioms.

Target object. A proof-system-specific theorem linking proof length/access to Omega(M_n s_n/n), or an escape principle that blocks the link.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: select the proof formalism and define the lower-bound sentence it proves.
- Proof step: map each proof rule to functional, occurrence-local, or formula-semantic behavior.
- Proof step: prove parser invariance under occurrence completions or construct a rule-level countermodel.
- Proof step: if parser holds, derive the Omega(M_n s_n/n) access/proof-size consequence.

Payoff criteria.

- The selected proof system and its SAT access are explicit enough for independent checking.
- The parser property is proved with a quantitative p(T,n), or a precise semantic escape is isolated.
- The output is not a generic 'strong systems are hard' statement; it names the exact proof rule that matters.

Stop criteria.

- Demote if the proof system remains unnamed or if its SAT facts are unspecified.
- Demote if the parser theorem assumes occurrence locality instead of deriving it.
- Demote if a negative answer does not identify the formula-semantic principle defeating occurrence-wise completion.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-delivery-workflow-orchestrator
- proof-gap-countermodel-splitter
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-forcedrows-proof-workflow
- pvsnp-inference-quality-controller
- pvsnp-negative-tactic-selector
- pvsnp-proof-complexity-transfer-reviewer
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer

#9 pvsnp.paper.incidence-falsifier-normal-form: Use incidence sketches as falsifiers and define the missing normal-form bridge

Analysis. Proof/diagnostic task extracted from the appendix and discussion: for candidate generators, search for low-rank or sparse affine-incidence sketches $p_x = sum_i\ a_i(x)b_i$ off a small exceptional set, and state the exact nonrelativizing normal-form theorem that would be needed to turn absence of such sketches into lower-bound evidence.

Why this is a good target. Incidence-falsifier theorem plus normal-form open problem for translating diagnostics into lower bounds.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Generated formula universe U_n, incidence vectors p_x in F^{U_n}, coefficient functions a_i, sketch vectors b_i, and exception set B_n.

Target object. A reproducible upper-bound falsifier or a clearly scoped normal-form theorem needed before incidence diagnostics can support source lower bounds.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: instantiate U_n and p_x for the candidate carrier.
- Proof step: attempt affine/sparse incidence sketches and compute A_n, K, and E_n.
- Proof step: if a sketch is found, derive the explicit upper-bound contradiction to the proposed source lower bound.
- Proof step: if no sketch is found, record this only as nonproof evidence and state the missing scalar-circuit normal form.

Payoff criteria.

- Every candidate generator is checked for the appendix's explicit upper-bound mechanism before promotion.
- The output never treats absence of a sketch as a lower bound.
- The normal-form bridge is stated as a theorem obligation with assumptions strong enough to imply scalar circuit hardness.

Stop criteria.

- Demote if the branch uses incidence rank as a lower bound without a scalar-circuit bridge.
- Demote if K, A_n, E_n, or exceptional-row patch cost are not computed or bounded.
- Demote if the diagnostic does not feed either a falsifier or a specific normal-form theorem.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-gap-countermodel-splitter
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#10 pvsnp.paper.aggregator-design-open-problem: Search aggregator designs beyond parity with explicit transfer and certificate tradeoffs

Analysis. Open-direction task extracted from the draft: compare parity with alternative aggregators by computing transfer cost, C_0(A_M), C_1(A_M), one-sided certificate behavior, algebraic structure, and whether the aggregator preserves beta-zero all-exponent SAT transfer without reopening easy selector/separator certificates.

Why this is a good target. Aggregator tradeoff theorem or no-go table identifying which aggregators preserve the desired certificate debt.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Candidate row aggregator family A_M and batched SAT labels y(G_{n,j}(x)).

Target object. A ranked set of aggregator candidates with proof-relevant certificate-complexity and transfer-cost guarantees.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of P $\neq$ NP.

Validation steps.

- Proof step: compute certificate complexities for each candidate aggregator.
- Proof step: verify size O(M) or record the exact transfer cost penalty.
- Proof step: test whether one-sided SAT evidence can cheaply force rows.
- Proof step: promote only candidates that improve some tradeoff without losing the all-polynomial-exponent transfer.

Payoff criteria.

- Parity remains justified or a better aggregator is identified by explicit C_b(A_M) and transfer calculations.
- Any proposed aggregator has proof-locality consequences stated as theorem obligations, not analogies.
- The output explains whether it strengthens, weakens, or complements the full-row barrier.

Stop criteria.

- Demote if aggregator comparison does not compute C_0 and C_1.
- Demote if the aggregator creates a cheap one-sided certificate that defeats the intended full-row burden.
- Demote if transfer cost reintroduces positive β exponent debt.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-qualitative-complexity-reasoner
- pvsnp-symbolic-complexity-auditor

#11 pvsnp.paper.occurrence-row-forcing-proposition-delivery: Deliver the occurrence-local row-forcing theorem as a standalone scoped contribution

Analysis. Proof-delivery task extracted from the proved row-forcing section: package the occurrence-completion theorem, parity full-row corollary, adaptive verifier corollary, and one-sided variant as a standalone barrier theorem with exact scope.

Why this is a good target. Standalone occurrence-local certificate-debt theorem for beta-zero parity carriers.

Risk. Main risk: the item becomes new exploration instead of emitting a proof packet or blocked-lemma disposition.

Branch control. This proof-delivery item must be discharged before broad exploration because it targets the current theorem-shaped blocker.

Source object. Completion-sound partial transcript (Q,alpha), forced rows R_b(Q,alpha), aggregator certificate complexity C_b(A_M), and patch circuits.

Target object. A scoped publishable theorem: occurrence-relativizing lower-bound certificates must pay full-row cost for parity.

Transfer condition. The output must preserve the P vs NP target relation while remaining a scoped route-specific theorem, proof audit, or blocked extraction obligation, not a claim of $P \neq NP$.

Validation steps.

- Proof step: restate completion soundness, forced rows, and certificate complexity without SAT-semantics leakage.
- Proof step: reconstruct baseline completion z^(b) and verify it extends the transcript.
- Proof step: patch forced rows and derive |R_b|=Omega(s_n/n).
- Proof step: specialize to parity and adaptive verifiers.

Payoff criteria.

- The theorem is independently understandable without the rest of the P vs NP discovery machinery.
- The proof states exactly why formula-semantic SAT proofs are outside scope.
- The theorem can be cited as the paper's local-certificate barrier contribution.

Stop criteria.

- Demote if the proof assumes formula-realizability or SAT semantics.
- Demote if the sparse patch construction does not produce a circuit below the claimed threshold.
- Demote if the theorem cannot state its non-claims cleanly.

Do not stop if.

- A named lemma can still be proved, repaired, or refuted locally.
- The current run can emit a live pvsnp_inference_quality packet.
- A countermodel would become a route-specific no-go theorem rather than mere failure.

Required skills.

- lemma-chain-proof-builder
- proof-obligation-formalizer
- proof-quality-gatekeeper
- pvsnp-barrier-specificity-reviewer
- pvsnp-forcedrows-proof-workflow
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer

#12 cycle-0098: Hardness-Magnification Bridge Realization

Analysis. Write the formal $FE_{Extract,N}$ proposition in two columns: left column row-expanded FormulaEval axiom schema with $N^{1+q+o(1)}$ charge, right column semantic-oracle version with the smallest private-row countermodel; verify which column matches each Psys_{sym} rule.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#13 cycle-0094: Hardness-Magnification Bridge Realization

Analysis. Formalize Psys_{sym} on finite length N: specify whether FormulaEval-SAT comprehension is a proof line, axiom schema, or extension rule; then prove either an expansion-charge parser with cost $N^{1+q+o(1)}$ or a minimal countermodel showing surface occurrence completion is unsound.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- abducer-refinement-route-ranker
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce

- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-induce
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#14 cycle-0086: Hardness-Magnification Bridge Realization

Analysis. Work the EF + $SATeq_N$ normal-form proof rule by rule: padding, renaming, duplicate clauses, extension-variable abbreviations, and SAT self-reduction; either translate each into a bounded EqSAT-link transcript or isolate the first noncompressible SAT-semantic principle as the next theorem-shaped counterexample.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor

- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#15 cycle-0080: Hardness-Magnification Bridge Realization

Analysis. Attempt the full $\mathrm{EF} + \mathrm{SAT}_U$ boundary lemma: inspect a standard encoding of SAT_U extension axioms and decide whether each semantic rule is occurrence-local, charges enough advice into S_Q, or yields a nonrelativizing complete-row extraction.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#16 cycle-0071: Hardness-Magnification Bridge Realization

Analysis. Instantiate V_N with one concrete proof-system or MCSP-style certificate, compute $kappa_N$ for accepted labels, and decide whether soundness is functional over arbitrary y or essentially SAT-semantic.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#17 cycle-0034: Hardness-Magnification Bridge Realization: tuple-feature residual gate

Analysis. Instantiate the pair-pattern thought experiment for $t = 2$: choose q with $q < 1 + \epsilon$ and test whether $2q + \alpha < 1 + \epsilon$ permits a subthreshold pair separator S_N; compute the residual complexity C(H_N xor S_N) and check for hidden SAT lookup.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q+a > 1+\epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner

- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#18 cycle-0013: Hardness-Magnification Bridge Realization: Polylog Nonblackbox Compact Consumer

Analysis. Instantiate $PolyLogAudit_{N,d,V}$ with a universal-circuit verifier, compute the exact overhead exponent ρ and auxiliary advice length, and reject the instance immediately if H_N depends on a hidden SAT circuit or collapses to a black-box SAT query family.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- abducer-refinement-route-ranker
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-induce
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker

- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#19 cycle-0012: Hardness-Magnification Bridge Realization

Analysis. Instantiate H_N as a proof-checking or self-reduction transcript language whose verifier can call a compact SAT_L circuit nonblackbox; compute its exact overhead a and test whether full truth-table substitution or input-encoded D leakage gives a subthreshold upper bound.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-refinement-route-ranker
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer

- kb-hypothesis-refutation-loop
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#20 cycle-0009: Hardness-Magnification Bridge Realization: subpolynomial-interface demagnification

Analysis. Pivot to a nonblackbox object: test a proof-complexity or derandomization carrier where SAT in P/poly yields the required source upper bound through a named nonrelativizing theorem rather than through black-box SAT-query substitution.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-refinement-route-ranker
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor

- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#21 cycle-0008: Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair

Analysis. Search for non-truth-table carriers in P^{SAT} with near-linear ordinary work and subpolynomial SAT queries, e.g. succinct consistency or decompression-check problems, then compute A,Q,s and test against L8.1 before discussing P vs NP.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-refinement-route-ranker
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#22 cycle-0007: Hardness-Magnification Bridge Realization: black-box substitution cap

Analysis. Test a succinct local-consistency or proof-complexity carrier with $N^{o(1)}$ SAT queries: compute a,q,beta, then run the projection-demagnification falsifier before claiming any magnification.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- abducer-refinement-route-ranker
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-induce
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner

- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#23 cycle-0006: Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit

Analysis. Test a self-referential meta-complexity carrier, such as Gap-MCSP or MKtP with succinctly generated truth tables, where the target SAT circuit is used nonblack-box. Compute whether the induced carrier upper bound can avoid the multiplicative c factor; if not, quarantine it by the same beta-ceiling lemma.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.

- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- abducer-refinement-route-ranker
- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-deduce
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-induce
- kb-proof-connector
- long-horizon-route-portfolio-manager

- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#24 cycle-0002: Hardness-Magnification Bridge Realization

Analysis. Test MCSP or proof-complexity carriers for producing the unbounded-k source family: formalize whether a weak lower bound for MCSP[2^{N^{1/k}}] transfers to $C_{H_k}(N) > N^{1+\epsilon}$ without becoming natural or losing the strict exponent margin.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.
- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.
- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.
- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- abducer-failure-signal-cartographer
- abducer-refinement-route-ranker
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-induce

- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#25 cycle-0125: Hardness-Magnification Bridge Realization

Analysis. Write the referee-auditable TSR_{decl} proof block: child-row bit fields, fixed-point pseudocode, Γ_{TSR} induction case, and a two-world hidden-pruning countermodel with a named first hidden child row r_star.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner

- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#26 cycle-0068: Hardness-Magnification Bridge Realization

Analysis. Formalize the extension problem: given R_N and a sound searchable label certificate, prove either that no poly(N)-time ambient extension of density $2^{-\mathrm{poly}(N)}$ exists for this certificate class, or that such an extension exists and therefore naturalizes the route.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner

- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#27 cycle-0108: Hardness-Magnification Bridge Realization

Analysis. Write the referee-style $TransparentRowSupport_N$ definition and audit six examples as corollaries: interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete extension rules. Do not add new selector families unless they prove a clause, refute a clause, or improve $AC0PrefixNonemptiness_N$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-refinement-route-ranker
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce

- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#28 cycle-0011: Hardness-Magnification Bridge Realization: lookup-lift collapse for restricted target repair

Analysis. Test a nonblackbox proof-complexity carrier: encode a SAT circuit as a verifier object whose correctness is checked globally rather than by short oracle leaves, and compute whether the verifier overhead stays below $N^{1+\epsilon}$ without allowing $\mathrm{SAT}_{\leq L}$ truth-table substitution.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-refinement-route-ranker
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#29 cycle-0010: Hardness-Magnification Bridge Realization

Analysis. Test a non-natural nonblackbox carrier whose query length is $N^{o(1)}$ and whose use of a SAT circuit is semantic rather than oracle substitution; compute whether its lift tax δ is below the source slack ϵ.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-refinement-route-ranker
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#30 cycle-0003: Hardness-Magnification Bridge Realization

Analysis. Instantiate g(r)=ceil(log log(r+4)); prove the verifier and length test are poly(N), then analyze whether valid-slice lower bounds for H_g admit a proof-complexity or MCSP carrier formulation.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.
- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.
- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- abducer-failure-signal-cartographer
- abducer-refinement-route-ranker
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-gap-abstraction-conjecturer

- kb-induce
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#31 cycle-0138: Hardness-Magnification Bridge Realization

Analysis. Write the referee-facing CTSRFrontierCompleteness proof: give closure pseudocode for K_{CTSR}, prove termination and minimality, verify one adaptive TSR line bit-by-bit, and instantiate the first-hidden-child falsifier on a one-node unread-enable-bit example.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#32 cycle-0131: Hardness-Magnification Bridge Realization

Analysis. Run the reviewer audit on L131.1: instantiate one toy projected-dDNNF FormulaEval line plus one declared TSR parent with two restriction children, compute K_{DTSR} by the worklist, verify Γ_{DTSR} numerically as $N^{1+\kappa+\theta+o(1)}$, then flip the first unlisted child in the hidden-pruning variant to validate the private-row falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#33 cycle-0123: Hardness-Magnification Bridge Realization

Analysis. Write the referee-checkable trace for the projected-dDNNF example: list gate fields, parent pointers, projection maps, RowSet certificates, K_0, K_1,... closure additions, U_N and X_N charges, then flip one unread enable bit to exhibit the first-hidden-row countermodel and verify the Γ_{dag} threshold numerically for qepsilon.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#34 cycle-0107: Hardness-Magnification Bridge Realization

Analysis. Formalize $AC0PrefixNonemptiness_N$ as a finite lemma: for AC0 selectors on q log N row bits, test whether descriptor structure yields $N^{o(1)}$ prefix emptiness; if not, state the selector-scan theorem as final and add AC0 output-sensitive enumeration to open problems.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce

- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#35 cycle-0090: Hardness-Magnification Bridge Realization

Analysis. Build the minimal EF + EqSAT + SR_1 parser countermodel: allow one extension variable Z(F)=SAT(F_0) OR SAT(F_1) and test whether it is representable by the SR DAG without advice; if yes, increase to two nested extensions, if no, use it as the semantic escape separating full EF from Psys_h.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#36 cycle-0087: Hardness-Magnification Bridge Realization

Analysis. Instantiate the padded-copy EqSAT quotient family E_k, compute the row-incidence matrix A_E, and decide whether its constrained cosets have low-weight representatives below N^{ϵ} or certify a valid semantic-link residual lower bound.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#37 cycle-0085: Hardness-Magnification Bridge Realization

Analysis. Attempt the finite EF+$SATeq_N$ parser proof: formalize proof lines as Boolean circuits over SAT-atoms, prove label-functionality for EF rules, charge every EqSAT endpoint to SemRows, and test whether SAT self-reduction axioms in full EF + SAT_U admit the same charge or force a new semantic-escape lemma.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#38 cycle-0084: Hardness-Magnification Bridge Realization

Analysis. Audit one standard full $\mathrm{EF} + \mathrm{SAT}_U$ encoding rule: attempt to extract its occurrence-label dependency into Q_{pi} preserving $A_Q - \mathit{invariance}$; if a witness or clause-soundness axiom breaks invariance, record the minimal rule-level countermodel and restrict the theorem statement to $\mathrm{EF} + \mathrm{SAT}_U^{occ,rn}$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#39 cycle-0083: Hardness-Magnification Bridge Realization

Analysis. Instantiate the EF + $\mathrm{SAT}_U^{occ,row}$ rule ledger: for each extension, weakening, substitution, SAT_U occurrence axiom, and derived parity line, mark whether it is $Q_{pi}-local$, row-separable, or a charged cross-row constraint; the first uncharged cross-row rule becomes the countermodel or repair target.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#40 cycle-0079: Hardness-Magnification Bridge Realization: beta-zero XOR row-forcing audit

Analysis. Instantiate Psys = EF + SAT_U^{occ}: define the proof parser that extracts Q_{pi}, prove acceptance transcript invariance under A_Q, and compute whether known EF encodings force full rows or merely individual generated formula occurrences.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#41 cycle-0076: Hardness-Magnification Bridge Realization

Analysis. Formalize Robust_N(s,e) for EF + SAT_U and test whether a short proof can remain sound after replacing H_N by D_N off a sparse row set.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#42 cycle-0073: Hardness-Magnification Bridge Realization

Analysis. Instantiate a named proof system Psys for $\beta = 0$ XOR certificates and test whether any accepted SAT-semantic certificate can be transformed into either a functional label property or a residual circuit wrong on fewer than $N^{\epsilon - o(1)}$ rows.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#43 cycle-0072: Hardness-Magnification Bridge Realization

Analysis. Instantiate the selected-probe audit for one named proof-system candidate: require $q = 1+\epsilon/2$, $\rho = 1+\epsilon/3$, L=(log N)^2, then compute whether its certificates force $A_N + S_N + R_N + E_{NN}$ or $A_N + S_N + K^c_{NL} + E_{NN}$ below $N^{1+\epsilon}$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#44 cycle-0070: Hardness-Magnification Bridge Realization

Analysis. Instantiate the density-tier audit on a toy proof-certificate family: certificates describing affine anti-alignment witnesses over U_N. Compute $delta_N$, verifier time, and whether soundness reaches arbitrary $C_N(H_y) > N^{1+\epsilon}$ or only sketch hardness.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#45 cycle-0067: Hardness-Magnification Bridge Realization

Analysis. Instantiate U_N for one explicit polylog-query XOR generator, compute whether U_N is enumerable in poly(2^L), and classify a candidate certificate as dense-label, image-relative, or nonlarge.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#46 cycle-0063: Hardness-Magnification Bridge Realization

Analysis. Perform the finite prior-art boundary check for the label-space naturalness claim, then instantiate the thought experiment with a concrete pairwise-independent generator and compute r_N, quotient rank, and any row-coordinate decoder cost D_N.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#47 cycle-0062: Hardness-Magnification Bridge Realization

Analysis. Instantiate the random-affine generator with L=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute r_N for the induced sparse incidence matrix and test whether the rank gap forces naturalness or low-rank falsification.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#48 cycle-0061: Hardness-Magnification Bridge Realization

Analysis. Instantiate a candidate generator and compute U_N, A_N, r_N, E_N for its SAT-preserving quotient codebook; if the cost is subthreshold, quarantine that generator, otherwise formulate the exact extraction theorem it would require.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#49 cycle-0060: Constructive Label-Free Sketch Gate for XOR Magnification

Analysis. Define the first concrete compiler class $T^{inc-lin}$: $T_N(x) = B_N$ a_N(x) for explicit SAT-preserving quotient matrices B_N of row sparsity polylog N, then compute the minimum $S_T + A_N$ r_N for representing H_N by sparse P_N in the high-q, $d = 2$ regime.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic

- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#50 cycle-0058: Hardness-magnification bridge via XOR carriers and sparse quotient-polynomial falsifiers

Analysis. Formalize the weakest nontrivial extraction candidate: restrict arbitrary H_N circuits to circuits whose wires are invariant under SAT-preserving quotient symmetries, and test whether such invariant circuits collapse to sparse quotient-polynomial sketches with subthreshold loss.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor

- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#51 cycle-0053: Hardness-Magnification Bridge Realization: XOR carrier affine-incidence audit

Analysis. Instantiate $G_{N,\theta}$ with linear, pairwise-independent, and extractor-style query maps; compute K, coefficient-circuit cost A_N, duplicate parity cancellations, and whether any case survives the $N^{1+\epsilon}$ affine-sketch falsifier threshold.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer

- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#52 cycle-0052: Hardness-Magnification Bridge Realization: XOR Carrier Repair

Analysis. In the ideal random-label model for G_N, count subthreshold affine sketches of size N^α and estimate the tau,alpha,error threshold at which a union bound could certify parity-sketch resistance without pretending to prove the actual explicit carrier lower bound.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the exponent transfer c $\to$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner

- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#53 cycle-0039: High-q generated-OR carrier: partial-certificate cover gate

Analysis. Formalize tau_N^{term} as a set-cover problem over generated CNF ranges and test whether random-looking high-q generators can force tau_N^{term}>N^{1+epsilon} without making G_N nonexplicit or violating $\rho < 1 + \epsilon$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For the certificate-cover branch, compute K,E,L and the induced circuit upper bound C(H_N)<=C(G_N)+O(K promotion requires every sound local cover to stay above the $N^{1+\epsilon-o(1)}$ source threshold.
- Falsify the branch if Horn, 2-SAT, bounded-width CNF, or bounded-backdoor emitted formulas give subthreshold satisfying-term or sound-local-certificate covers.
- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#54 cycle-0038: Hardness-Magnification Bridge Realization: realized-witness projection gate

Analysis. Instantiate the planted-pool thought experiment and compute W_N^* for affine, low-degree, and pseudorandom assignment-pool generators; check whether any preserves $q + a > 1 + \epsilon$ without introducing natural-proof or advice-leakage collapse.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q+a > 1+\epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#55 cycle-0033: Hardness-Magnification Bridge Realization

Analysis. Formalize the restricted case where B is a depth-2 threshold or DNF over $t = N^{\tau}$ local features, compute the exact q+alpha+beta leakage threshold, and search for an explicit low-residual construction on expander-walk generated SAT bags.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.

- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#56 cycle-0019: Hardness-Magnification Bridge Realization: semantic range leakage gate

Analysis. Instantiate G_N with a concrete expander or extractor-based 3-CNF generator, compute $R_{N,j}$ structure, and test whether SAT on those positioned ranges collapses to a known easy subclass or requires a new semantic lower-bound certificate.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#57 cycle-0018: Hardness-Magnification Bridge Realization: positioned entropy cover gate

Analysis. Instantiate the affine-disperser generated-OR family and compute B_N exactly as a function of α, q, and clause density; then audit whether any known lower-bound technique for this restricted H_N avoids the natural-proofs density condition.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#58 cycle-0014: Hardness-Magnification Bridge Realization: polylog generated-OR carrier

Analysis. Instantiate G_N as a near-linear Cook-Levin micro-instance generator with $M = N$ and L=(log N)^d; compute exact ρ, verify H_N is in NP with poly(N) uniform verification, and test whether any structural simplification gives an $N^{1+\epsilon}$ upper-bound falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#59 cycle-0005: Hardness-Magnification Bridge Realization

Analysis. Audit an MCSP-based route: set source object $\mathrm{MCSP}_{n,s}$ on $N = 2^n - bit$ truth tables, choose a concrete circuit model for the lower bound, state the exact threshold $N^{1+\epsilon}$ or smaller, and test whether the known magnification transfer is non-natural, target-preserving, and strong enough to imply SAT $\notin$ P/poly rather than only EXP or subexponential derandomization consequences.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.

- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.
- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- abducer-failure-signal-cartographer
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-end-to-end-proof-critic
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#60 cycle-0004: Hardness-Magnification Bridge Realization

Analysis. Test an MCSP or KT-complexity carrier with source model, threshold N^{1+eps}, and target NP $\not\subset$ P/poly; compute the reduction overhead and state whether the needed proof must be non-natural or non-algebrizing.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.
- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.
- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- abducer-failure-signal-cartographer
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-end-to-end-proof-critic
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#61 cycle-0001: Hardness-Magnification Bridge Realization

Analysis. Instantiate the same exponent audit for a padded MKtP or GapMCSP carrier: name the verifier, compute Cook-Levin or direct-composition length blow-up, and test whether assuming SAT $\in$ SIZE(n^c) yields source circuits below $N^{1+\epsilon}$ without model mismatch or nonuniform leakage.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.
- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.
- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- abducer-failure-signal-cartographer
- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-end-to-end-proof-critic
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#62 cycle-0110: Hardness-Magnification Bridge Realization

Analysis. Attempt $RealSATInfluenceRealizer_N$ for one influence-complete extension rule: define $RealInfl_l$, produce row-index witnesses and $EnumCost + N|K_l|$ charge, or exhibit a semantic rule where a real SAT-sensitive row remains unchargeable, thereby demoting full Psys_{sym} beyond the transparent theorem pair.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It points toward the only unquarantined escape: a subpolynomial-query, nonprojection, or nonblackbox carrier. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Promotion requires a target-preserving nonblackbox/subpolynomial mechanism, not another black-box Cook-Levin substitution.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$, NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-refinement-route-ranker
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-gap-abstraction-conjecturer
- kb-hypothesis-refutation-loop
- kb-proof-connector
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#63 cycle-0129: Hardness-Magnification Bridge Realization

Analysis. Write the paper-ready L129 sublemma proof: give pseudocode for K_{DTSR} fixed-point enumeration, a table of declared TSR bit fields, the local verifier for child occurrence neighborhoods, and the two-world first-unlisted-child countermodel; then run the live inference-quality packet validation.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#64 cycle-0093: Hardness-Magnification Bridge Realization

Analysis. Attempt an explicit NSP_N countermodel for unrestricted EF extension variables: construct a small row-mask extension family e_R, prove that occurrence-only parsing misses its support, and decide whether support transparency can be repaired by charging C(Supp(e_R)) without making the parser target-equivalent.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#65 cycle-0092: Hardness-Magnification Bridge Realization

Analysis. Try to prove NSP_N for the fragment EF+SATeq+SR whose extension definitions are row-affine and support-monotone; if the proof fails, extract the minimal extension rule that creates uncharged SAT-semantic support and state the final theorem scope around Psys_h^{supp}.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- abducer-failure-signal-cartographer
- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#66 cycle-0154: Hardness-Magnification Bridge Realization

Analysis. Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#67 cycle-0153: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit

Analysis. Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#68 cycle-0150: Hardness-Magnification Bridge Realization

Analysis. Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor

- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#69 cycle-0148: Hardness-Magnification Bridge Realization

Analysis. Write the finite K_{QCTSR} verifier on a projected-dDNNF example with one certified duplicate row and one unread-enable hidden merge; compute $U_Q, N|K_Q|, B_{\mathrm{CTSR}}, C_Q, E_{pi}$ and show exactly where the hidden merge fails the valid support ledger.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#70 cycle-0147: Hardness-Magnification Bridge Realization

Analysis. Instantiate the closure verifier on a three-row QCTSR toy transcript: two counterfactual child rows, one EqSAT certificate forest, and one attempted cyclic merge; compute K_Q, Γ_{QCTSR}, and the first-rejected-merge private-row falsifier explicitly.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#71 cycle-0146: Hardness-Magnification Bridge Realization

Analysis. Run the finite verifier on one projected-dDNNF/Tseitin-renaming example: list K_Q seeds, accepted quotient certificates, rank labels, computed Γ_{QCTSR}, and then delete one certificate to exhibit the first-rejected-merge private-row falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller

- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#72 cycle-0145: Hardness-Magnification Bridge Realization

Analysis. Instantiate the finite verifier on one toy QCTSR proof with two EqSAT-equivalent counterfactual TSR children: compute K_Q, ranks, B_Q, and Γ_{QCTSR}; then delete one certificate edge and explicitly write the two-world private-row falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$, NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer

- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#73 cycle-0144: Hardness-Magnification Bridge Realization: ranked QCTSR ledger validation

Analysis. Write the referee-checkable K_Q closure pseudocode with rank ordering, then test it on a two-child Tseitin-equivalent TSR merge and on the same example with the certificate omitted to exhibit the first-unranked-merge falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.

- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#74 cycle-0142: Hardness-Magnification Bridge Realization

Analysis. Write the finite verifier for K_Q and ranked F_Q on a toy projected-dDNNF plus CTSR example with one duplicate child pair; compute Γ savings, then remove one certificate edge to exhibit the private-row falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#75 cycle-0140: Hardness-Magnification Bridge Realization: QCTSR Certified-Quotient Parser Boundary

Analysis. Instantiate K_Q on a toy projected-dDNNF FormulaEval proof with two CTSR levels and three EqSAT quotient classes; compute |RepIdx|, C_{Eq}, Γ_{QCTSR}, then delete one quotient certificate to exhibit the first-hidden-merge falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#76 cycle-0139: Hardness-Magnification Bridge Realization

Analysis. Instantiate $\Gamma^{=}_{\mathrm{CTSR}}$ on a projected-dDNNF FormulaEval proof with two Tseitin-equivalent child formulas: compute K before and after certified EqSAT quotienting, then remove one certificate and exhibit the first uncertified quotient-collision private-row falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#77 cycle-0137: Hardness-Magnification Bridge Realization

Analysis. Write the standalone L137 first-hidden-child theorem: specify the CTSR bit fields, define the two row-oracle worlds, prove transcript equality on K_{CTSR} minus r, prove final parity disagreement, and compute the Γ_{CTSR} threshold for $\kappa + \theta < \epsilon$ with q-trichotomy support density.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#78 cycle-0136: Hardness-Magnification Bridge Realization

Analysis. Select one concrete full semantic pruning rule beyond CTSR declarations, preferably adaptive Tseitin branch pruning with real SAT contradiction tests, and attempt either a charged $RealSATInfluenceRealizer_N^{arb}$ or a minimal first-unchargeable-row countermodel.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#79 cycle-0134: Hardness-Magnification Bridge Realization

Analysis. Instantiate the counterfactual DTSR closure on a two-level nested TSR proof with one Tseitin seed family; compute the exact child count, K_{CTSR} fixed point, Γ_{CTSR} ledger, and first-unlisted-child countermodel transcript.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller

- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#80 cycle-0133: Hardness-Magnification Bridge Realization

Analysis. Attack $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic pruning rule: bounded Tseitin self-reduction with a SAT-truth branch-elimination premise. Either produce a uniform charged list of all influencing children or formalize the first semantic line where the private-row countermodel survives.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer

- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#81 cycle-0132: Hardness-Magnification Bridge Realization

Analysis. Write the paper-ready L132 proof block: pseudocode for K_DTSR(pi), a table of DTSR bit fields and verifier checks, the five line-induction cases, and the first-unlisted-child countermodel; then test one projected-dDNNF+DTSR positive example and one unread-enable-bit hidden-pruning counterexample.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.

- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#82 cycle-0130: Hardness-Magnification Bridge Realization

Analysis. Run the bit-field audit for one concrete DTSR verifier line: list parent row id, active descriptor id, restriction mask, child row id, Tseitin extension map, local identity tag, and downstream use pointer; verify that K_{DTSR} reaches every used child and compute the exact theta+kappa ledger for the example.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.

- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#83 cycle-0128: Hardness-Magnification Bridge Realization

Analysis. Write the paper-ready TSR rule schema table and verify on one toy projected-dDNNF plus TSR line: compute K_{TSR}, A_{TSR}, B_{TSR}, R_{TSR}, and then flip the first unlisted child in the hidden-pruning variant.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#84 cycle-0124: Hardness-Magnification Bridge Realization

Analysis. Write the $FE_{\mathrm{TSR},decl}$ rule schema as bit fields: row id, Tseitin code, pivot list, child constructor, parent pointers, and EF derivation handles; then check the fixed-point K_{TSR} enumerator on a one-line bounded-SR example and a hidden satisfying-branch counterexample.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#85 cycle-0122: Hardness-Magnification Bridge Realization

Analysis. Write the paper-ready L122 module: formal theorem statement, fixed-point pseudocode, line-induction proof, projected-dDNNF charge example, unread-enable-bit counterexample, q-trichotomy corollary, and a separate $RealSATInfluenceRealizer_N$ open-boundary paragraph.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#86 cycle-0121: Hardness-Magnification Bridge Realization: L121 least-closed support audit

Analysis. Write the formal L121.1 proof skeleton as theorem text: fixed-point pseudocode for K_{dag}, induction invariant per rule type, charge table for $bEF/SR_h/\text{FormulaEval}/projected - dDNNF$, and the unread-enable-bit counterexample with $\theta < \epsilon$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#87 cycle-0115: Hardness-Magnification Bridge Realization

Analysis. Formalize the private-row independence lemma for one full symbolic FormulaEval rule with an unread enable bit: write the two transcripts, the charged constraint set, the flipped row r, and the proof that all visible lines agree while H_N^{SAT} parity differs; if independence fails, record the exact same-theory constraint as a $RealSATInfluenceRealizer_N$ candidate.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller

- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#88 cycle-0109: Hardness-Magnification Bridge Realization: $TransparentRowSupport$ theorem pair

Analysis. Referee-check one projected-dDNNF FormulaEval rule against the five $TransparentRowSupport_N$ clauses, compute its U_N and X_N charges, and verify that any projected hidden variable is either influence-closed or triggers the unread-enable-bit countermodel.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer

- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#89 cycle-0106: Hardness-Magnification Bridge Realization

Analysis. Run the finite validation audit on one concrete Psys_{sym} rule: encode FormulaEval as (a) interval-union axiom schema, (b) AC0 selector with enumerator, and (c) opaque semantic oracle; compute α and either attach $N^{1+\alpha+o(1)}$ charge or exhibit the private-row countermodel.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\text{SAT} \in \text{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.

- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#90 cycle-0105: Hardness-Magnification Bridge Realization

Analysis. Run the delta-varied interval-union selector audit: instantiate $|RowSet| = N^{q-\delta}$, verify $RowSetEnumerator_N$ gate cost, compute Γ^{IU}_{bEF} at $\delta = q - \epsilon \pm o(1)$, and test whether any proposed semantic selector supplies a valid $FE_{Extract,N}$ certificate rather than triggering the private-row falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.

- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#91 cycle-0103: Hardness-Magnification Bridge Realization

Analysis. Extend $RowSetEnumerator_N$ from interval-union selectors to a named AC0 selector fragment by full scanning over [M_N]; compute whether scan overhead $N^{q+o(1)}$ is dominated by N|RowSet| and identify the smallest $\mathrm{AC0} - private - row$ countermodel if enumeration depends on semantic advice.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#92 cycle-0091: Hardness-Magnification Bridge Realization: beta-zero XOR formula-semantic parser audit

Analysis. Instantiate $\mathrm{Psys}^{schema}_{h,Ext}$: EF+EqSAT+depth-h SR with extension definitions generated by row-oblivious schemas. Try to prove ExtSupp(NF(pi))<=poly(|pi|), or construct a minimal nonrelativizing SAT-semantic extension that defeats this normal form.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#93 cycle-0089: Hardness-Magnification Bridge Realization

Analysis. Fix h with 2^h=N^{eta}; formalize $Delta_{SR,h}$ for the generated formula closure and try to prove the parser for EF+$SATeq$+SR_h restricted to extension variables naming only quotient labels and SR clauses.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.
- Promotion requires an advice-free row-hard certificate; backtrack if the ranked decoder, canonical unranking, or aggregate proof selects a hard row nonuniformly.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#94 cycle-0088: Hardness-Magnification Bridge Realization

Analysis. Instantiate K_{pi} for local one-step SR only: bound $|K_{pi}|$ by proof size, define its row-parity constraint-distance $Delta_K$, and test whether $Delta_K$ can be reduced to a known SAT promise-hardness statement or whether it is target-equivalent to the desired H_N lower bound.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#95 cycle-0081: Hardness-Magnification Bridge Realization

Analysis. Formalize the semantic-coupling-width thought experiment as a lemma: for paired formulas F and F OR z, show exactly which SAT_U implication lines break private-label invariance and whether their violations can be charged to complete forced rows below the N^{ϵ} patch threshold.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#96 cycle-0078: Hardness-Magnification Bridge Realization

Analysis. Instantiate EF + SAT_U row occurrence access formally: define the touched-row set of a proof verifier, test whether standard EF reflection over SAT_U extracts to row-value functionality, and if not construct the private-row oracle countermodel as a finite theorem.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller

- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#97 cycle-0077: Hardness-Magnification Bridge Realization

Analysis. Instantiate Touch(Pi) for a concrete EF+SAT_U encoding of circuit lower-bound certificates: count whether proofs of size N^k can mention $sub{-}N^\epsilon$ rows, and test if formula-equality/SAT-realization axioms break the occurrence-oracle extension.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$, NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer

- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#98 cycle-0075: Hardness-Magnification Bridge Realization

Analysis. Instantiate EF + SAT_U proofs as circuits over SAT_U label atoms, define functionalization formally, and try to construct a $\theta < \epsilon$ residual-leaky transcript or prove extraction to the robustness gate.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#99 cycle-0074: Hardness-Magnification Bridge Realization: beta-zero XOR row-residual audit

Analysis. Formalize EF + SAT_U syntax with label table U_N, prove the functional dense naturalization lemma cleanly, then attempt a finite extraction theorem: every nonfunctional accepted proof either identifies a row set R_N and approximator D_N or uses a nonrelativizing SAT principle outside the row-residual audit.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.

- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#100 cycle-0069: Hardness-Magnification Bridge Realization

Analysis. Instantiate U_N with L=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute whether candidate proof systems give certificate density above $2^{-\mathrm{poly}(L)}$ or force a nonlarge escape, then run the prior-art boundary check.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#101 cycle-0066: Hardness-Magnification Bridge Realization

Analysis. Instantiate R_n for one high-q polylog XOR carrier or prove a finite impossibility: no label-free density-preserving realization can coexist with $q, \rho < 1 + \epsilon$ and generator universe U_N of SAT formulas length (log N)^2.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#102 cycle-0065: Hardness-Magnification Bridge Realization

Analysis. Instantiate R_N with a named proof system, e.g. Extended Frege or IPS, and test whether an LB certificate for $C(H_{N,y}) > N^{1+\epsilon}$ has $O(L_N) - bit$ searchable descriptions, inverse-polynomial label density, and truth-table soundness; otherwise record the precise escape parameter.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#103 cycle-0064: Hardness-Magnification Bridge Realization

Analysis. Instantiate L_N=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute achievable M_N and r_N for an explicit generator family, then test for a label-free coordinate transcript or prove any proposed SAT anti-alignment certificate has density below $2^{-\omega(L_N)}$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#104 cycle-0048: Relativizing locality-extraction gate for generated-OR carriers

Analysis. Try to formulate a real-SAT locality extractor using witness self-reducibility: from a small circuit for H_N, isolate a generated satisfiable query and build a one-sided predicate; audit algebrization and $N^{o(1)}$ loss.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#105 cycle-0047: Hardness-Magnification Bridge Realization: locality-extraction obstruction

Analysis. Try a real-SAT extraction using self-reducibility or witness isolation: from a small circuit for H_N, define a local predicate that accepts formulas whose forced witness path changes the global OR value, compute the overhead, and test it against the planted-control oracle falsifier.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.

- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#106 cycle-0044: Hardness-Magnification Bridge Realization: residual cap-denominator gate

Analysis. Instantiate the cap audit for partial-assignment predicates of width w on L=(log N)^2 formulas: compute theta(w,sigma) for random-looking generated ranges, then check whether sigma+theta can stay above 1+epsilon while q,rho remain in the target-preserving window.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.
- Exhibit or refute a subthreshold semantic planted-slice predicate; this decides whether the generated-OR carrier needs range-closure repair, stronger pseudorandomness, or quarantine.
- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#107 cycle-0043: Generated-OR residual cap gate for hardness magnification

Analysis. Try to construct residual caps for the planted/random 3CNF generator using partial-assignment certificates, and compute the resulting exponent b.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.
- Exhibit or refute a subthreshold semantic planted-slice predicate; this decides whether the generated-OR carrier needs range-closure repair, stronger pseudorandomness, or quarantine.
- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#108 cycle-0042: Cycle 42: distributional cap certificate for one-sided semantic separators

Analysis. Formalize the cap profile for the unmarked random k-CNF generated-OR thought experiment: compute assignment-test hit exponents as a function of β, then identify the first semantic predicate class beyond terms that can violate or support $A_N(s) \leq s/N^{1+\epsilon-o(1)}$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.
- Exhibit or refute a subthreshold semantic planted-slice predicate; this decides whether the generated-OR carrier needs range-closure repair, stronger pseudorandomness, or quarantine.
- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#109 cycle-0040: Hardness-Magnification Bridge Realization: sound local certificate cover gate

Analysis. Compute the SLC cover exponent for generated formulas with bounded backdoor width $b = \alpha \log N$ and for small semantic classes such as Horn, 2-SAT, and bounded-width CNF; identify whether the threshold $\alpha \geq 1 + \epsilon - q$ is achievable without destroying the SAT-substitution bridge.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the certificate-cover branch, compute K,E,L and the induced circuit upper bound C(H_N)<=C(G_N)+O(K promotion requires every sound local cover to stay above the $N^{1+\epsilon-o(1)}$ source threshold.
- Falsify the branch if Horn, 2-SAT, bounded-width CNF, or bounded-backdoor emitted formulas give subthreshold satisfying-term or sound-local-certificate covers.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor

- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#110 cycle-0026: Hardness-Magnification Bridge Realization

Analysis. Instantiate the thought experiment with a block generator E_N whose coordinates are grouped into planted easy and hard ranges; compute the smallest δ forced by coverage of positive inputs and test whether selected-range promise SAT stays subthreshold.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#111 cycle-0025: Generated-OR magnification: selector-range leakage gate

Analysis. Instantiate Sel_N for simple generator templates, including lexicographic first-satisfying-query generators and hash-bucketed query generators, and compute whether selected-image lookup already drops below $N^{1+\epsilon}$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller

- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#112 cycle-0023: Hardness-magnification bridge realization: generated-OR range-balance gate

Analysis. Instantiate a template generator for polylog-length 3CNFs and estimate $\theta = min$ label-support exponent; then compare it with 1+epsilon-q and with the best promise-SAT solver size on the generated template range.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#113 cycle-0022: Hardness-Magnification Bridge Realization

Analysis. Instantiate G_N with a high-entropy family of polylog-size 3-CNF formulas and compute the best promise solver or block-cover upper bound; vary τ to locate the first threshold-respecting candidate.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#114 cycle-0021: Hardness-Magnification Bridge Realization: Shared-Generator Semantic Block-Cover Gate

Analysis. Run the block-size thought experiment for $b = N^{\theta}$: derive upper bounds on U(theta) from range cardinality, feature compression, and OR compression, then identify whether any θ gives N^{rho}+N^{q-theta}U(theta)<N^{1+epsilon}.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#115 cycle-0017: Hardness-Magnification Bridge Realization: positioned-range entropy audit

Analysis. Instantiate K_N from a specific extractor-like generator of polylog-length CNFs and compute $|R_g|$, v_N, q, and ρ exactly to see whether the positioned entropy threshold can be met without advice leakage.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#116 cycle-0016: Hardness-Magnification Bridge Realization

Analysis. Instantiate G_N with high-essential-variable polylog 3CNF queries and test whether any structural simplification gives $\mathrm{SIZE}(H_N) \leq N^{1+\epsilon-o(1)}$ despite v(N) superlogarithmic.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#117 cycle-0015: Hardness-Magnification Bridge Realization

Analysis. Instantiate the boundary cases $d = 1$ with $A = 1 + \epsilon - q$ and $d = 2$; search for a generator whose H_N avoids known small-circuit constructions without smuggling SAT advice.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Low drift risk: the item is framed as an explicit P vs NP transfer audit.

Branch control. The item has high payoff and a concrete decision test; stopping now would be premature.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely non-blackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#118 cycle-0057: Hardness-Magnification Bridge Realization: XOR quotient carrier, low-degree feature-sketch gate

Analysis. Formalize the degree-2 case: characterize whether Tseitin-style parity, formula-size, variable-incidence, or clause-type features give $r = N^{\alpha}$ with $2alpha < 1 + \epsilon$ for the generated length-(log N)^d SAT queries.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.
- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.

- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#119 cycle-0046: Hardness-Magnification Bridge Realization: normal-form extraction gate

Analysis. Formalize a restricted no-control generator class, such as block-product independent seeds with no shared label bit, and test whether an S-size circuit for OR_j SAT(G(x,j)) can be localized to a one-sided separator cover; compute the exact overhead in q,rho,sigma,E.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.

- For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.
- Exhibit or refute a subthreshold semantic planted-slice predicate; this decides whether the generated-OR carrier needs range-closure repair, stronger pseudorandomness, or quarantine.
- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- For MCSP/MKtP, state N, n, s, verifier overhead, lower-bound model, and whether the property is natural or non-natural.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.
- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.
- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- counterexample-hunter
- entailment-gap-auditor

- kb-abduce
- kb-concept-bridge-planner
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#120 cycle-0045: Hardness-Magnification Bridge Realization: Greedy Cap Dual Gate

Analysis. Work in a restricted circuit model such as De Morgan formulas or AC0[p] and test whether exact circuits for H_N admit an approximate one-sided separator normal form; compute the resulting $D_{sigma,E}$ threshold for the same high-q polylog generated-OR carrier.

Why this is a good target. It audits a meta-complexity carrier where the decisive questions are verifier overhead, density/naturalness, and advice leakage. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

Payoff criteria.

- For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.
- Exhibit or refute a subthreshold semantic planted-slice predicate; this decides whether the generated-OR carrier needs range-closure repair, stronger pseudorandomness, or quarantine.
- For the certificate-cover branch, compute K,E,L and the induced circuit upper bound C(H_N)<=C(G_N)+O(K promotion requires every sound local cover to stay above the $N^{1+\epsilon-o(1)}$ source threshold.
- Falsify the branch if Horn, 2-SAT, bounded-width CNF, or bounded-backdoor emitted formulas give subthreshold satisfying-term or sound-local-certificate covers.
- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.

Stop criteria.

- The induced carrier upper bound under SAT $\in$ SIZE(n^c) remains N^{q+beta c+o(1)} with $\beta > 0$ for all tested parameter choices.
- The source lower bound required for MCSP/MKtP is as strong as the target separation or becomes a natural property without an escape.
- The route cannot prevent advice leakage or model mismatch between the carrier lower bound and P/poly target.

Do not stop if.

- The MCSP/MKtP parameter regime has not yet been fixed.
- The truth-table length N and underlying input length n have not been related in the transfer inequality.
- The natural-proof largeness/constructivity issue has not yet been audited.
- A nonblackbox use of the target circuit could still avoid the multiplicative c factor.

Required skills.

- counterexample-hunter
- entailment-gap-auditor
- kb-abduce
- kb-concept-bridge-planner
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor

- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-meta-complexity-carrier-reviewer
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#121 cycle-0149: Hardness-Magnification Bridge Realization

Analysis. Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller

- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#122 cycle-0127: Hardness-Magnification Bridge Realization

Analysis. Write the verifier bit fields for one declared TSR line: root row id, restriction-node path, pivot variable, child row ids, Tseitin map hash, occurrence-neighborhood list, parent pointers, and expansion certificate; then prove the single-line induction inequality adding exactly N times the declared child count to $\Gamma_{dag+\mathrm{TSR}}$.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer

- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#123 cycle-0117: Hardness-Magnification Bridge Realization: Transparent FormulaEval Boundary

Analysis. Write the paper-ready theorem statement as three clauses: $TransparentRowSupport_N$ positive Γ_{trans} induction; extensional hidden-support private-row/unread-enable-bit countermodel; $RealSATInfluenceRealizer_N$ open semantic escape with overhead R_N and explicit non-claims.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.

- The proposed escape is only a black-box substitution restatement with no new carrier or non-blackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$.
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#124 cycle-0113: Hardness-Magnification Bridge Realization

Analysis. Run the finite proof-quality checklist on the paper statement: verify each $TransparentRowSupport_N$ clause for interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete examples; then attempt or refute $RealSATInfluenceRealizer_N$ for one concrete semantic FormulaEval axiom.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.

- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#125 cycle-0112: Hardness-Magnification Bridge Realization

Analysis. Write the corollary table as examples only: interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete extension rules must each be checked against the five $TransparentRowSupport_N$ clauses or demoted.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).

- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor
- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#126 cycle-0082: Hardness-Magnification Bridge Realization

Analysis. Construct the smallest EF extension-rule countermodel that hides row parity without a row-normal node, or prove a normalization that exposes such parity with subthreshold overhead.

Why this is a good target. It directly tests the current black-box substitution cap by computing β, q, and the induced target-exponent window. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Compute β and q exactly; promotion requires $\beta = 0$, subpolynomial target queries, or a genuinely nonblackbox use of the SAT circuit.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: compute β and q exactly, distinguishing all-exponent consequences from bounded target-exponent windows.

Stop criteria.

- Every named carrier in the branch has $\beta > 0$ and yields only a bounded target-exponent exclusion.
- The branch cannot state a source lower-bound model, target class, and transfer inequality in the same notation.
- The proposed escape is only a black-box substitution restatement with no new carrier or nonblackbox mechanism.
- The barrier audit shows the needed source lower bound is just as hard as the original P vs NP/P/poly target.

Do not stop if.

- The branch has not yet computed β, q, and the induced source upper-bound exponent under SAT $\in$ SIZE(n^c).
- A subpolynomial-query or nonblackbox carrier remains available and has not been audited.
- The latest failure sharpened the threshold-collapse lemma into a formal no-go statement.
- The route can still isolate advice leakage, nonuniformity, naturalness, or algebrization as the exact obstruction.

Required skills.

- contradiction-route-auditor
- entailment-gap-auditor

- kb-deduce
- kb-end-to-end-proof-critic
- kb-hypothesis-refutation-loop
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-proof-derivation-builder
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#127 cycle-0059: Hardness-Magnification Bridge Realization: XOR carrier sparse-sketch audit

Analysis. Formalize the local-linear incidence transcript class for the XOR SAT carrier and compute the minimum sparse F_2 support needed under a random-generator model, while auditing whether any extraction from arbitrary circuits to that class can avoid the planted-control relativization falsifier.

Why this is a good target. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the exponent transfer $c \to c/k$ or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- entailment-gap-auditor
- kb-end-to-end-proof-critic
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer

- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#128 cycle-0055: Hardness-Magnification Bridge Realization

Analysis. Compute QSk_{sim,N}(E) for quotient relations generated by equality, variable renaming, clause permutation, tautological padding, and duplicate-pair involutions on the current high-q XOR carrier template; record the smallest residual exponent u and pairing-certificate cost.

Why this is a good target. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the exponent transfer c $\to$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- entailment-gap-auditor
- kb-end-to-end-proof-critic
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#129 cycle-0051: Hardness-Magnification Bridge Realization - cycle 51 direct-sum demagnification audit

Analysis. Try to formalize an aggregate lower-bound normal form for H_N that distinguishes global OR computation from M_N independent SAT_L copies, and test it against the planted-control oracle before using separator hardness.

Why this is a good target. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- entailment-gap-auditor
- kb-end-to-end-proof-critic
- kb-induce
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#130 cycle-0032: Generated-OR magnification: correction-residual separator gate

Analysis. Instantiate Phi_N for a tagged generated-OR carrier and compute whether simple tag predicates produce subthreshold residual circuits; then test an untagged high-entropy generator for the same residual leakage.

Why this is a good target. It checks whether padding/projection transfers really magnify hardness or merely move the proof debt into sparse lower bounds. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. Moderate risk: run only if source/target/model/barrier fields are explicit.

Branch control. The item remains target-linked but needs tighter payoff criteria before consuming a long run.

Premature-stop guard. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- State whether the transfer excludes every polynomial SAT exponent or only a bounded interval $c < c0$.

Stop criteria.

- The branch only proves a finite target-exponent lower bound and cannot scale to NP $\not\subset$ P/poly.
- The route requires sparse valid-length lower bounds that are not weaker than the original target problem.
- The projection carrier has no nonprojection mechanism and no subpolynomial embedding repair.

Do not stop if.

- The quantifier pattern has not been repaired between fixed-k, unbounded-k, and single growth-padding carriers.
- The projection-sandwich inequality has not yet been written as an explicit circuit-size transfer.
- The sparse valid-length lower-bound obligation has not been isolated as the real source debt.

Required skills.

- abducer-failure-signal-cartographer
- entailment-gap-auditor
- kb-end-to-end-proof-critic
- kb-induce
- long-horizon-route-portfolio-manager

- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-reduction-consistency-reviewer
- pvsnp-symbolic-complexity-auditor

#131 cycle-0152: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure

Analysis. Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.
- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.
- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.
- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#132 cycle-0143: Hardness-Magnification Bridge Realization

Analysis. Instantiate the six-row QCTSR transcript, list row IDs, quotient certificate dependencies, rank labels, and show the first uncertified merge produces two agreeing visible transcripts with opposite H_N parity.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#133 cycle-0141: Hardness-Magnification Bridge Realization

Analysis. Instantiate one two-merge CTSR proof toy model: one certified EqSAT quotient with charged forest and one uncertified merge. Write the local verifier fields, compute R_Q and C_Q, and demonstrate transcript agreement plus parity disagreement for the uncertified merge.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#134 cycle-0135: Hardness-Magnification Bridge Realization

Analysis. Resolve $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic rule: bounded Tseitin self-reduction with adaptive unsat-branch pruning. Either produce a syntax-and-N computable influence row list R_A with charge in Γ_{real}, or formalize the first unchargeable semantic inference as a private-row no-realizer theorem.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#135 cycle-0126: Hardness-Magnification Bridge Realization

Analysis. Formalize the $\mathrm{Psys}_{sym}^{dag+declTSR(h)}$ grammar in one page: exact row-index fields, TSR parent/child encodings, local verifier predicate, K_{dag}^{TSR} fixed-point pseudocode, and the declared TSR line-induction case; then instantiate with $\kappa = \epsilon/3$, $\theta = \epsilon/3$, q in ((1+epsilon)/2,1+epsilon), $\rho < 1 + \epsilon$ to verify all charges remain subthreshold except the intended q-density pressure.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#136 cycle-0120: Hardness-Magnification Bridge Realization: least-closed transparent FormulaEval support

Analysis. Write the proof-audit version of L120.1: formalize the fixed-point computation of K_dag(pi), give pseudocode for the verifier-visible dependency closure, and check one projected-dDNNF FormulaEval example plus one unread-enable-bit counterexample against the Γ_{dag} inequality.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#137 cycle-0118: Hardness-Magnification Bridge Realization

Analysis. Run a finite proof audit on $\mathrm{Psys}^{ext}_{sym}$: instantiate one guarded FormulaEval line, compute I_l, K_{idx}, R_{FE}, and Γ_{comp}, then verify the last-unsafe-line two-world construction or identify the first real SAT-semantic rule that forces a nonrelativizing realizer charge.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner

- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#138 cycle-0116: Hardness-Magnification Bridge Realization: Transparent FormulaEval Minimality Audit

Analysis. Instantiate $RealSATInfluenceRealizer_N$ or refute it for one concrete strong rule: FormulaEval with Tseitin-extension equality plus bounded self-reduction; list exact bit fields, RowSet extraction, same-theory expansion certificates, and the first semantic inference that cannot be charged.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.

- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#139 cycle-0114: Hardness-Magnification Bridge Realization

Analysis. Instantiate $RealSATInfluenceRealizer_N$ for one concrete full semantic FormulaEval rule, or prove a rule-specific private-row countermodel showing that the full Psys_{sym} extension must remain quarantined.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer

- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#140 cycle-0111: Hardness-Magnification Bridge Realization

Analysis. Write the final paper theorem text for $TransparentRowSupport_N$ with clauses T1-T6, prove the line induction lemma in referee style, then test one genuinely semantic FormulaEval rule against $RealSATInfluenceRealizer_N$ or instantiate the private-row countermodel.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.

- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#141 cycle-0104: Hardness-Magnification Bridge Realization

Analysis. Instantiate $RowSetEnumerator_N$ for one richer transparent selector class beyond interval-unions, preferably sorted AC0 threshold-free selectors with explicit scan charge, and decide whether it expands at N|RowSet|, collapses to an N^q scan bound, or admits a private-row countermodel.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#142 cycle-0102: Hardness-Magnification Bridge Realization - cycle 102 SR_h normal form audit

Analysis. Instantiate $RowSetEnumerator_N$ for one transparent $\mathrm{Psys}^{sel}_{sym}$ fragment, preferably interval-union or AC0 row selectors, and decide whether FormulaEval-SAT is an expanded axiom schema with $N^{1+q+o(1)}$ charge or a semantic oracle exposed by the private-row falsifier.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#143 cycle-0100: Hardness-Magnification Bridge Realization

Analysis. Prove $RowSetEnumerator_N$ for an interval-union or AC0 FormulaEval selector and compute alpha-charge; if enumeration fails, emit the minimal private-row countermodel.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.
- Falsify direct transfer if a P function already has the same restricted-model lower bound, such as PARITY for AC0, HWB for OBDD, or XOR/Tseitin for proof-system degree.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#144 cycle-0097: Hardness-Magnification Bridge Realization

Analysis. Instantiate Psys_{sym} in two concrete variants: FormulaEval as an EF extension rule with row-index bits and FormulaEval as a semantic oracle. For each, compute K_idx(pi), X_FE(K), and whether the private-row countermodel survives SATeq and bounded-SR constraints.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#145 cycle-0096: Hardness-Magnification Bridge Realization

Analysis. Fix one concrete Psys_{sym} syntax: FormulaEval-SAT as either an axiom schema over A(i,j,u), an EF extension rule producing formula bits, a proof line with explicit D_u, or a semantic oracle. For that syntax, prove the expansion parser or instantiate the minimal private-row countermodel with the smallest pi, one unexpanded pair (i*,j*), and a verified Γ_{sym} inequality.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic

- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#146 cycle-0095: Hardness-Magnification Bridge Realization: bit-explicit parser and FormulaEval boundary

Analysis. Instantiate $FE_{expand,N}$ on the smallest symbolic FormulaEval-SAT rule: one generator circuit G_N(x,j), one asserted vector y_j=SAT(G_N(x,j)), and α row instantiations. Prove the private-row countermodel for $\alpha < q$ and the $N^{1+q-o(1)}$ expansion charge for $\alpha = q$.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.
- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.
- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.
- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#147 cycle-0056: Hardness-Magnification Bridge Realization: XOR quotient codebook gate

Analysis. Instantiate a candidate high-q generator and compute the exponent of its SAT-preserving odd-support transcript range versus affine span rank; reject it if min{theta,rank-exponent}+locator-cost falls below 1+epsilon.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#148 cycle-0054: Hardness-Magnification Bridge Realization: XOR Carrier Approximate Affine-Sketch Gate

Analysis. Instantiate the hash-based XOR generator and compute whether its incidence map has an explicit low-cost piecewise-affine cover; if none is found, formulate the exact extraction theorem needed to turn small H_N circuits into such covers.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.
- Promotion requires a proof-system lower bound that survives the Gaussian-elimination or recognition shortcut; otherwise the result is a restricted-proof-system separation only.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#149 cycle-0050: Hardness-Magnification Bridge Realization: Relativizing Extraction Falsified

Analysis. Audit real-SAT self-reduction or proof-certificate structure as a possible nonrelativizing extractor, and compute whether its verifier/certificate overhead stays below $N^{1+\epsilon}$ rather than collapsing to restricted-SAT hardness.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.

- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#150 cycle-0049: Hardness-Magnification Bridge Realization: locality extraction threshold

Analysis. Formalize one candidate extraction using SAT self-reducibility plus generator local decodability, then compute whether the required decodability already implies neutralizing embeddings and hence demagnification.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger

- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#151 cycle-0041: One-sided promise-separator gate for high-q generated-OR magnification

Analysis. Test a range-closure repair: augment G_N so restrictions of emitted formulas also appear in controlled positions, compute the q/rho overhead, and see whether this lets a one-sided separator self-reduce to a term cover without breaking the $N^{1+\epsilon}$ threshold.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.
- Exhibit or refute a subthreshold semantic planted-slice predicate; this decides whether the generated-OR carrier needs range-closure repair, stronger pseudorandomness, or quarantine.
- For the certificate-cover branch, compute K,E,L and the induced circuit upper bound C(H_N)<=C(G_N)+O(K promotion requires every sound local cover to stay above the $N^{1+\epsilon-o(1)}$ source threshold.
- Falsify the branch if Horn, 2-SAT, bounded-width CNF, or bounded-backdoor emitted formulas give subthreshold satisfying-term or sound-local-certificate covers.
- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q+a > 1+\epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#152 cycle-0037: Hardness-Magnification Bridge Realization: approximate witness-cover gate

Analysis. Instantiate the thought experiment with a concrete planted/anti-planted CNF generator and compute the minimum position-indexed assignment hitting exponent h for its satisfiable range; compare h to 1+epsilon-q.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker

- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#153 cycle-0036: Hardness-Magnification Bridge Realization: position-indexed unary residual gate

Analysis. Formalize $Iota_N^{pos}$ as a minimax transcript-residual measure and test whether expander-style slot mixing can rule out all low-budget position-indexed unary decompositions without becoming a natural-proof argument.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.

- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#154 cycle-0035: Hardness-Magnification Bridge Realization: high-q arity cutoff for generated-OR carriers

Analysis. Formalize unary transcripts as monotone OR-of-range predicates, then test whether random-looking high-q generators make every subthreshold unary transcript leave residual circuit complexity above $N^{1+\epsilon-o(1)}$ or whether a selected-image separator falsifier appears.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#155 cycle-0030: Hardness-Magnification Bridge Realization

Analysis. Formalize $SepHit_N$ as a bipartite hitting-avoidance problem between positive bags and negative formula occurrences, then test whether random-looking generators satisfy the required lower bound by a counting argument and where explicitness breaks the argument.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.

- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#156 cycle-0029: Hardness-Magnification Bridge Realization: one-sided separating-ensemble leakage gate

Analysis. Try to lower-bound or construct Psi_N^{sep} for a random-like generator: estimate whether selected positive and negative images admit $N^b - size$ separators when $R = N^r$ and $s = N^{ell}$ are below the magnification threshold.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#157 cycle-0028: Hardness-Magnification Bridge Realization

Analysis. Estimate Xi_N^{ens} for a random high-entropy generator by a union-bound model over ensembles, then isolate which part of the argument can survive explicitness and avoid natural-proof leakage.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger

- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#158 cycle-0027: Hardness-Magnification Bridge Realization: approximate list-selector leakage gate

Analysis. Instantiate G_N with a high-entropy expander/hash-generated SAT family and compute whether any tau=O(epsilon/2) list selector has a selected image admitting a subthreshold promise solver.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.

- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#159 cycle-0024: Hardness-Magnification Bridge Realization: hitting-cover gate for generated-OR carriers

Analysis. Formalize the minimum cover parameter as a bipartite set-cover problem between input fibers and generated SAT labels; test whether known disperser/extractor-style generators can force $kappa_N > N^{1+\epsilon-o(1)}$ without reintroducing nonuniform leakage.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q + a > 1 + \epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer

- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#160 cycle-0020: Hardness-Magnification Bridge Realization: Semantic Block-Cover Gate

Analysis. Instantiate M_N for a nontrivial generator without dominated coordinates, e.g. a universal verifier family whose queries are Cook-Levin encodings of polylog-size computations, and compute whether block predicates admit compression below $N^{1+\epsilon}$.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary. It is executable as a bounded complexity calculation, CAS-backed exponent audit, or formal transfer check.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.
- Promotion requires $q+a > 1+\epsilon$ after every projection, padding, and witness-cover leakage term is accounted for; otherwise the branch becomes a bounded-window or no-go result.
- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#161 cycle-0151: Hardness-Magnification Bridge Realization

Analysis. Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge

- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#162 cycle-0119: Hardness-Magnification Bridge Realization, cycle 119: compositional transparent support closure

Analysis. Write the finite prefix-closure verifier for $TransparentRowSupport_N$: input pi,N; output Cl_t for each line, Gamma_prefix(t), and either a valid support-closed derivation certificate or the first unsafe line with its private-row/unread-enable-bit countermodel.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#163 cycle-0101: Hardness-Magnification Bridge Realization

Analysis. Write the finite verifier table for one SR_h rule: tag layout, row j encoding, node/depth fields, parent pointers, occurrence-neighborhood list, and the exact charge contributing to B_SR(pi).

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer

- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#164 cycle-0099: Hardness-Magnification Bridge Realization

Analysis. Write the formal $FE_{Extract,N}$ blocked-lemma proof: define the quotient-label model after $SATeq/SR_h$ closure, prove the unmentioned row-slot existence bound, construct the two assignments Y,Y', and verify that the carrier row parity changes while the parsed transcript remains identical.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.

- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner
- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

#165 cycle-0031: Hardness-Magnification Bridge Realization: approximate relaxed bag separators

Analysis. Try a collision-balanced generator and estimate whether majority/hash-based local predicates yield $s = N^{o(1)}$ with $E < N^{\epsilon}$; if yes, quarantine this carrier family.

Why this is a good target. It keeps the barrier and model-boundary audit attached to the mathematical transfer rather than as after-the-fact commentary.

Risk. High drift risk unless rewritten into a concrete complexity-theoretic transfer test.

Branch control. The branch still touches a relevant object, but the next experiment must be narrowed before continuation.

Premature-stop guard. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

Payoff criteria.

- For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.
- Record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific transfer theorem.
- Control gate: name the source carrier or language, target class, and circuit or resource model before claiming progress.
- Control gate: derive the exact transfer inequality from SAT $\in$ SIZE(n^c), NP subset P/poly, or the stated target assumption to the source-carrier upper bound.
- Control gate: record relativization, natural-proofs, algebrization, nonuniformity, and advice-leakage status for the specific theorem.

Stop criteria.

- The branch cannot identify a source language/carrier and target complexity class in the same model.
- The route repeatedly proves only a proxy lower bound with no target-preserving transfer.
- The remaining work is a slogan about hardness magnification rather than a computable transfer or obstruction.

Do not stop if.

- A transfer exponent, quantifier repair, or barrier status remains uncomputed.
- The branch can still name a target-preserving carrier and a falsifiable lower-bound threshold.
- The failure can become a formal no-go lemma for a route family.

Required skills.

- entailment-gap-auditor
- kb-end-to-end-proof-critic
- long-horizon-route-portfolio-manager
- main-problem-alignment-auditor
- next-experiment-queue-ranker
- paper-contribution-readiness-judge
- pvsnp-barrier-specificity-reviewer
- pvsnp-conceptual-pressure-localizer
- pvsnp-impossibility-theorem-forger
- pvsnp-inference-quality-controller
- pvsnp-qualitative-complexity-reasoner

- pvsnp-quantifier-uniformity-reviewer
- pvsnp-symbolic-complexity-auditor

F Qualitative Mechanistic Graph

The qualitative graph is a mechanism map, not a JSON registry. It states how variables, regimes, exact finite tests, and transfer obligations steer branch control.

Mechanism in plain terms

1. A candidate bridge starts with a named source carrier, target class, circuit model, and length map.
2. The transfer envelope computes how SAT circuits of size n^c induce source-carrier circuits, usually through an exponent term q+beta c.
3. Positive β or hidden advice can collapse all-exponent consequences into a bounded-window theorem.
4. Barrier checks attach to the actual theorem shape: relativization, naturalness, algebrization, nonuniformity, and advice leakage are not generic slogans.
5. A branch is promoted only when it yields an exact transfer theorem, a scoped no-go, or a finite certificate/soundness obligation that changes route priority.

Relations that matter now

Quantities and regimes

G Gedanken Experiments

Concrete imagined situations are used only when they isolate a mechanism, expose a hidden assumption, or create a follow-up task. They are conceptual probes, not proof progress.

H Parsimonious Probe Control

This section keeps symbolic-first computation separate from analytic obligations and rare bounded numeric probes.

No target-compatible parsimonious probe packet is active for this P vs NP report. A future packet should use symbolic complexity auditing: exact exponent envelopes, length maps, advice terms, certificate-search exponents, and barrier predicates.

I Scientific Contribution Monitor

This section keeps the marathon aimed at independently valuable subgoals and decides when a branch is good enough to hand off instead of continuing indefinitely.

Standing objective

Every long-horizon branch must aim at a standalone scientific contribution candidate, a contribution-search move, or an explicit demotion test.

Good enough definition

A candidate is good enough only when its claim, evidence, novelty boundary, validation/disqualifier checks, and overclaim boundary are explicit enough for publishable handoff.

Good enough paper relevance

A paper subgoal is good enough only when conceptual depth, conceptual novelty, unblocking power, applicability, and understanding gain are at least adequate, the decisive dimensions are strong, and hard gates prevent overclaiming.

Paper relevance marker criteria

- applicability: The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- conceptual_depth: The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.
- unblocking_power: The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- understanding_gain: The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Stepping-stone maturity levels

- contribution_shaped: The branch has an independently meaningful object or obstruction, but it is not yet a publishable stepping stone.
- near_stepping_stone: One or two bounded prior-art, disqualifier, proof-shape, or validation tasks could make the candidate paper-note ready.
- publishable_handoff_ready: Broad exploration should pause; the candidate should move to validation, prior-art, and manuscript packaging.

Anti-infinite progression rule

A branch may continue only while the next cycle can improve a contribution metric or resolve a disqualifier; otherwise adapt, backtrack, quarantine, stop, or hand off.

Next contribution objective

Run the best near-stepping-stone candidate through prior-art, disqualifier, or paper-shape certification before broad exploration.

cycle-0124: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0124
- branch:Hardness-Magnification Bridge Realization
- equations:6
- $derivation_{steps} : 6$
- falsifiers:6

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: finite_check_queued - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0121: Hardness-Magnification Bridge Realization: L121 least-closed support audit

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: L121 least-closed support audit: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0121
- branch:Hardness-Magnification Bridge Realization: L121 least-closed support audit
- equations:5
- $derivation_{steps}$: 10
- falsifiers:6

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: finite_check_queued - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0073: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0073
- branch:Hardness-Magnification Bridge Realization
- equations:4
- $derivation_{steps} : 7$
- falsifiers:5

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: pass - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0071: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0071
- branch:Hardness-Magnification Bridge Realization
- equations:5
- $derivation_{steps} : 7$
- falsifiers:5

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: pass - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0065: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0065
- branch:Hardness-Magnification Bridge Realization
- equations:4
- $derivation_{steps} : 7$
- falsifiers:4

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: pass - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0008: Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0008
- branch:Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair
- equations:4
- $derivation_{steps}$: 7
- falsifiers:6

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: finite_check_queued - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0007: Hardness-Magnification Bridge Realization: black-box substitution cap

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: black-box substitution cap: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0007
- branch:Hardness-Magnification Bridge Realization: black-box substitution cap
- equations:3
- $derivation_{steps}$: 6
- falsifiers:4

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable hand-off.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: pass - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: pass - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.

- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0006: Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0006
- branch:Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit
- equations:4
- $derivation_{steps} : 7$
- falsifiers:4

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: pass - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0002: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0002
- branch:Hardness-Magnification Bridge Realization
- equations:5
- $derivation_{steps} : 7$
- falsifiers:5

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: pass - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0001: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0001
- branch:Hardness-Magnification Bridge Realization
- equations:3
- $derivation_{steps}$: 6
- falsifiers:5

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: finite_check_queued - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0136: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0136
- branch:Hardness-Magnification Bridge Realization
- equations:6
- $derivation_{steps} : 7$
- falsifiers:6

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.

- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable hand-off.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: pass - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: pass - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.

- Run prior-art pass for padding/projection lower-bound transfer arguments.

cycle-0134: Hardness-Magnification Bridge Realization

Contribution type. quantitative_transfer_obstruction

Stepping-stone maturity. near_stepping_stone

Smallest honest claim. A route-specific quantitative obstruction can be isolated for Hardness-Magnification Bridge Realization: the transfer formula names the source exponent, overhead, target-query exponent, and exact threshold where magnification collapses.

Why it could stand alone. A quantitative transfer obstruction is independently useful because it replaces barrier folklore with an exact parameter condition showing when a proof route loses the target exponent.

Why this budget now. Run the next bounded certification or prior-art gate before another broad marathon branch.

Branch control. The candidate is strong but still needs bounded validation or disqualifier checks before handoff.

Overclaim boundary. This candidate is a scoped contribution candidate; it does not prove the main target unless all target commitments are discharged in the same theory.

Good-enough paper relevance. The candidate is scientifically relevant enough to shape a paper, but certification/prior-art gates still control handoff.

Paper relevance status. strong_relevance_certification_pending with average marker score 4.8

Good enough when.

- Smallest honest claim can be stated without proving the main target.
- Mathematical object, assumptions, scope, and evidence basis are explicit.
- At least one disqualifier or falsifier has been checked or bounded.
- Remaining validation is finite enough for a paper note, obstruction note, benchmark, method note, or lemma packet.

Continue only if.

- The next cycle can improve novelty, explanation, implications, validation readiness, target relevance, or disqualifier resolution.
- The branch still touches a core target commitment or a reusable scientific object.
- The next action is a bounded calculation, derivation, source check, or falsifier test rather than generic elaboration.

Stop when.

- Two explicit adaptation or backtracking attempts fail to improve any contribution metric.
- The branch cannot name a contribution candidate, contribution-disqualifying test, or target-preserving validation handoff.
- The candidate is already good enough for handoff and further exploration would only inflate proof debt.

Validation burden.

- Run prior-art comparison before claiming novelty.

Evidence basis.

- cycle:cycle-0134
- branch:Hardness-Magnification Bridge Realization
- equations:5
- $derivation_{steps} : 7$
- falsifiers:5

Missing to publishable.

- Run the finite prior-art boundary check and record closest known results.
- Resolve disqualifier tests or convert unknowns into finite validation tasks.

Missing to good-enough paper.

- Close the publishable handoff hard gates before calling the candidate paper-ready.

Paper relevance markers.

- conceptual_depth: $score = 5$, $status = strong$ - The result works at the level of a real P vs NP proof obstruction or bridge: source carrier, target class, circuit model, reduction/transfer map, quantifier regime, and barrier status are all explicit.
- conceptual_novelty: $score = 4$, $status = strong$ - The result adds a new exact obstruction, bridge, no-go, or certificate interface relative to known hardness magnification, MCSP/MKtP, proof-complexity, natural-proofs, relativization, or algebrization families.
- unblocking_power: $score = 5$, $status = strong$ - The result changes route priority by proving a transfer, exposing a quantitative loss, ruling out a method class, or identifying the precise bounded calculation that would decide the branch.
- applicability: $score = 5$, $status = strong$ - The result is reusable across a nontrivial family of carriers, reductions, restricted models, proof systems, or certificate constructions under explicit assumptions and transfer inequalities.
- understanding_gain: $score = 5$, $status = strong$ - The result clarifies why the route is hard: where proof debt moves, which exponent or advice term destroys the transfer, or which barrier premise actually binds.

Hard gates.

- claim_statement_ready: $ready = True$, $finite_{task} = False$
- evidence_ready: $ready = True$, $finite_{task} = True$
- novelty_boundary_ready: $ready = False$, $finite_{task} = True$
- overclaim_boundary_ready: $ready = True$, $finite_{task} = False$
- validation_ready: $ready = False$, $finite_{task} = True$

Disqualifiers.

- already_known: finite_check_queued - Prior-art boundary is queued before publishable handoff.
- evidence_gap: pass - Certification readiness is derived from equations, derivation steps, and falsifiers.
- overclaim_risk: pass - Overclaim boundary explicitly states that the candidate does not prove the main target.
- validation_unbounded: pass - The next action is checked for bounded proof, calculation, audit, or falsifier language.
- narrow_bookkeeping: pass - The candidate is treated as scientific only if it has external mathematical content.
- target_equivalent_assumption: finite_check_queued - P vs NP candidates must show that the source obligation is not already the desired lower bound.
- advice_leakage: finite_check_queued - Advice and nonuniform hard-row selection are explicit P vs NP disqualifiers.
- barrier_status: finite_check_queued - Barrier status must be attached to the specific transfer theorem.
- restricted_model_proxy_drift: finite_check_queued - Restricted-model results need a compiler envelope or explicit proxy boundary.

Prior-art boundary. finite_check_queued

- Run prior-art pass for hardness magnification threshold theorems.
- Run prior-art pass for natural proofs and algebrization barriers.
- Run prior-art pass for padding/projection lower-bound transfer arguments.

J Target Problem And Literature Evolution

P vs NP

Decide whether every efficiently verifiable decision problem is also efficiently solvable, equivalently whether SAT has a polynomial-time algorithm.

$$\mathrm{P} \stackrel{?}{=} \mathrm{NP} \quad \text{or, equivalently,} \quad \mathrm{SAT} \in \mathrm{P}$$

Why this problem matters

- It is the central test of whether verification and search have the same polynomial-time power.
- It governs the meaning of NP-completeness: if P equals NP, thousands of complete search problems become efficiently solvable in principle; if not, their common hardness has a rigorous source.
- It is tied to cryptography, proof complexity, optimization, algorithms, derandomization, circuit lower bounds, and the philosophy of what counts as an efficient explanation.

What would count as a solution

- To prove P equals NP, exhibit a polynomial-time algorithm for an NP-complete problem such as SAT and prove its runtime and correctness.
- To prove P differs from NP, prove that some NP language, equivalently SAT, cannot be decided by any polynomial-time deterministic Turing machine.
- For nonuniform routes, a claim strong enough for NP $\not\subset$ P/poly must rule out polynomial-size circuit families for an NP-complete language without uncharged advice.
- Any restricted-model, algebraic, proof-complexity, meta-complexity, or hardness-magnification result must include a target-preserving bridge back to the Boolean main problem.

How the literature evolved

1971-1972 – Verification becomes a universal computational phenomenon

Conceptual shift. Cook and Karp show that many apparently different problems are interreducible through polynomial reductions and share SAT as a complete core.

What became possible. The problem becomes mathematically precise: it is enough to decide whether any NP-complete language, especially SAT, has polynomial-time algorithms.

What remained open. Completeness explains universality of difficulty but not the source of lower bounds against all polynomial-time algorithms or circuits.

1975 – Proof techniques become objects of study

Conceptual shift. Relativization shows that any proof surviving arbitrary oracle substitution cannot settle the main question.

What became possible. A serious route must track what part of the argument is nonrelativizing rather than merely proving a plausible separation in an oracle-insensitive way.

What remained open. The barrier diagnoses broad method families but does not identify a successful nonrelativizing replacement.

Late 1970s onward – Complexity becomes a landscape of representations

Conceptual shift. Algebraic, proof-complexity, descriptive, and structural viewpoints re-express computation through polynomials, proofs, reductions, and uniformity conditions.

What became possible. The problem can be attacked by translating Boolean hardness into more rigid mathematical objects with their own invariants.

What remained open. Every translation risks losing target strength: a theorem in a restricted or algebraic model must still return to Boolean P vs NP or P/poly with controlled loss.

1990s – Lower-bound intuitions meet pseudorandomness

Conceptual shift. Natural proofs explain why many broad, efficiently checkable combinatorial properties are unlikely to prove strong unrestricted circuit lower bounds.

What became possible. Discovery can now audit lower-bound proposals for largeness, constructivity, usefulness, and cryptographic tension.

What remained open. The field still needs useful lower-bound properties that are either not large, not constructive, not black-box, or otherwise outside the natural-proofs template.

2000s onward – Fine-grained and magnification thinking exposes exponent debt

Conceptual shift. Hardness transfers are judged by exact exponents, target-query counts, advice leakage, and whether a weak source lower bound really magnifies to the main target.

What became possible. Routes can be evaluated with precise inequalities instead of broad optimism about reductions or carriers.

What remained open. Most bridges lose too much exponent, import nonuniform advice, or prove a source lower bound that is already as hard as the desired conclusion.

2009 onward – Modern progress is real but carefully scoped

Conceptual shift. Algebrization and restricted-circuit lower bounds clarify both the reach and limits of current techniques.

What became possible. Algorithmic, algebraic, and restricted-circuit breakthroughs provide templates for bridge design and falsification.

What remained open. The unrestricted P vs NP question still demands a target-preserving lower bound or impossibility theorem that escapes known barriers without losing the main quantifiers.

References preserved by the report

S. A. Cook (1971). The Complexity of Theorem-Proving Procedures. Supports: Introduces NP-completeness through satisfiability and turns efficient verification into a universal problem.. Limitation: It defines the central complete problem and reduction method; it does not separate deterministic from nondeterministic polynomial time.

R. M. Karp (1972). Reducibility Among Combinatorial Problems. Supports: Shows that many natural search and optimization problems share the same NP-complete core.. Limitation: NP-completeness transfers difficulty conditionally; it does not prove that any NP-complete problem lacks polynomial algorithms.

T. Baker, J. Gill, and R. Solovay (1975). Relativizations of the P = ? NP Question. Supports: Shows that relativizing methods alone cannot settle P vs NP, because oracle worlds exist on both sides.. Limitation: Relativization is a diagnostic for proof techniques, not a proof that separation is impossible.

A. A. Razborov and S. Rudich (1997). Natural Proofs. Supports: Explains why many combinatorial lower-bound properties are too large and constructive to prove strong general circuit lower bounds under cryptographic hardness assumptions.. Limitation: The barrier constrains a proof format; it leaves room for non-natural, nonconstructive, algebraic, or otherwise barrier-evading arguments.

S. Aaronson and A. Wigderson (2009). Algebrization: A New Barrier in Complexity Theory. Supports: Shows that even many non-relativizing arithmetization methods still fall inside an algebrizing barrier.. Limitation: Algebrization does not rule out all algebraic or geometric methods; it forces proof attempts to state exactly what escapes the barrier.

R. Impagliazzo, R. Paturi, and F. Zane (2001). Which Problems Have Strongly Exponential Complexity?. Supports: Develops reduction notions that preserve subexponential complexity and clarify how quantitative hardness transfers.. Limitation: Strong exponential-time hypotheses and SERF reductions illuminate hardness structure but do not by themselves separate P from NP.

R. Williams (2014). Nonuniform ACC Circuit Lower Bounds. Supports: Proves that NEXP does not have polynomial-size nonuniform ACC circuits and demonstrates an algorithms-to-lower-bounds bridge.. Limitation: The result is a major restricted-circuit breakthrough, not a lower bound against unrestricted polynomial-size circuits for NP.

L. G. Valiant (1979). Completeness Classes in Algebra. Supports: Creates an algebraic analogue of completeness and lower-bound questions, showing how representation and computation can be studied through polynomial families.. Limitation: Algebraic complexity gives powerful analogues and transfer pressure, but VP vs VNP is not literally the Boolean P vs NP problem.

K Macro Strategies

Current macro strategy: compute the transfer exponents or turn the route into a no-go theorem.

Black-box transfer and exponent-window audit

Physics picture. For this complexity-theory target, read the physical picture as a proof-dynamics picture: the target circuit is a resource flowing through an interface. Positive query-length exponent β amplifies the target exponent c and prevents a barely-superlinear source lower bound from ruling out all polynomial-size SAT circuits.

Active skills.

- pvsnp-symbolic-complexity-auditor
- pvsnp-qualitative-complexity-reasoner
- pvsnp-conceptual-pressure-localizer
- entailment-gap-auditor
- progression-payoff-judge

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0149; learning: Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.; next_experiment: Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0150; learning: Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0151; learning: Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined.; next_experiment: Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.
- branch_title: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure; cycle_id: cycle-0152; learning: Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only

when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result.; next_experiment: Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.

- branch_title: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit; cycle_id: cycle-0153; learning: Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_N$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress.; next_experiment: Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0154; learning: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.; next_experiment: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

Padding and projection demagnification as a no-go route

Physics picture. The conceptual mechanism is proof-debt conservation. Padding changes the coordinate system, but projection back to SAT reveals that the supposedly weak source lower bound already encodes the hard target lower bound.

Active skills.

- pvsnp-symbolic-complexity-auditor
- pvsnp-impossibility-theorem-forger
- contradiction-route-auditor
- paper-contribution-readiness-judge
- scientific-contribution-detector

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0098; learning: Cycle 98 upgrades the prior packet from theorem slogan to dependency-checked inference structure: Γ_{bEF} is justified by separate EF-dependency, SATeq-link, bounded-SR, and sparse-row charges; Psys_{bEF} gives a valid restricted falsifier theorem; full Psys_{sym} is blocked exactly at

$FE_{Extract,N}$, not at generic naturalness or relativization folklore.; next_experiment: Write the formal $FE_{Extract,N}$ proposition in two columns: left column row-expanded FormulaEval axiom schema with $N^{1+q+o(1)}$ charge, right column semantic-oracle version with the smallest private-row countermodel; verify which column matches each Psys_{sym} rule.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0123; learning: Cycle 123 closes a proof-audit gap rather than repeating the magnification slogan: K_{dag} is an implementable least fixed point, projected-dDNNF gives a concrete transparent positive case, and the unread-enable-bit/private-row construction gives a precise necessity falsifier. The valid result is a scoped parser/falsifier theorem for beta-zero parity magnification; full semantic FormulaEval is still blocked exactly at $RealSATInfluenceRealizer_N$.; next_experiment: Write the referee-checkable trace for the projected-dDNNF example: list gate fields, parent pointers, projection maps, RowSet certificates, K_0, K_1,... closure additions, U_N and X_N charges, then flip one unread enable bit to exhibit the first-hidden-row countermodel and verify the Γ_{dag} threshold numerically for qepsilon.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0136; learning: Cycle 136 turns counterfactual declared TSR from a boundary slogan into a bitfield-level closed-support theorem: K_CTSR(pi) is a finite fixed point, Γ_{CTSR} is derived by line induction, and first-hidden-child adaptive pruning is the exact falsifier for extensional safety. The valid contribution remains a scoped parser/falsifier theorem for beta-zero parity magnification certificates; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Select one concrete full semantic pruning rule beyond CTSR declarations, preferably adaptive Tseitin branch pruning with real SAT contradiction tests, and attempt either a charged $RealSATInfluenceRealizer_N^{arb}$ or a minimal first-unchargeable-row countermodel.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0145; learning: Cycle 145 upgrades ranked QCTSR from a line-induction slogan to a finite verifier/minimality packet. Quotient compression is valid only when proof-carrying same-theory certificates are ranked, dependency-closed, and charged before use. The exact obstruction is the first rejected quotient merge, which yields a private-row falsifier. This strengthens the paper parser/countermodel boundary without proving H_N lower bounds or P $\neq$ NP.; next_experiment: Instantiate the finite verifier on one toy QCTSR proof with two EqSAT-equivalent counterfactual TSR children: compute K_Q, ranks, B_Q, and Γ_{QCTSR}; then delete one certificate edge and explicitly write the two-world private-row falsifier.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0149; learning: Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.; next_experiment: Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0150; learning: Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge.

The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.

Meta-complexity carrier pressure

Physics picture. The meta-complexity carrier is a diagnostic medium: it can reveal whether a weak source lower bound really transfers, or whether constructivity, largeness, and nonuniform advice absorb the intended separation.

Active skills.

- pvsnp-conceptual-pressure-localizer
- pvsnp-symbolic-complexity-auditor
- pvsnp-qualitative-complexity-reasoner
- counterexample-hunter
- kb-concept-bridge-planner

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0149; learning: Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.; next_experiment: Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0150; learning: Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.; next_experiment: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0151; learning: Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined.; next_experiment: Write the finite prefix-stable Qrep verifier:

fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.

- branch_title: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure; cycle_id: cycle-0152; learning: Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result.; next_experiment: Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.
- branch_title: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit; cycle_id: cycle-0153; learning: Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_N$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress.; next_experiment: Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.
- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0154; learning: Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.; next_experiment: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

Nonblackbox or subpolynomial-interface escape search

Physics picture. The route needs a new interaction pattern with the target circuit. If the circuit is only queried as a black box at polynomially growing target length, the beta-ceiling reappears; a real escape must change that interface.

Active skills.

- pvsnp-symbolic-complexity-auditor
- pvsnp-impossibility-theorem-forger
- pvsnp-qualitative-complexity-reasoner
- kb-gap-abstraction-conjecturer
- abducer-refinement-route-ranker

Evidence from story.

- branch_title: Hardness-Magnification Bridge Realization: Polylog Nonblackbox Compact Consumer; cycle_id: cycle-0013; learning: Cycle 13 turns the superlogarithmic polylog window into an exact bridge: L=(log N)^d with $d > 1$ makes SAT circuits of size L^c amortize to $N^{o(1)}$, while truth-table lookup costs 2^L=N^{omega(1)} and no longer supplies the old falsifier. The valid threshold is $\rho < 1 + \epsilon$ for a target-clean nonblackbox compact consumer. The new hard obstruction is not folklore but the absence of an explicit carrier with no advice leakage and a nonnatural $N^{1+\epsilon}$ general-circuit lower bound.; next_experiment: Instantiate $PolyLogAudit_{N,d,V}$ with a universal-circuit verifier, compute the exact overhead exponent ρ and auxiliary advice length, and reject the instance immediately if H_N depends on a hidden SAT circuit or collapses to a black-box SAT query family.

- branch_title: Hardness-Magnification Bridge Realization: approximate relaxed bag separators; cycle_id: cycle-0031; learning: Cycle 31 converts relaxed bag separators into an approximate threshold lemma: E bad bags cost NE gates, so errors below N^ϵ are nonuniformly patchable. The valid source obligation is now an approximate distribution-local separator lower bound, not merely promise SAT hardness.; next_experiment: Try a collision-balanced generator and estimate whether majority/hash-based local predicates yield $s = N^{o(1)}$ with $E < N^\epsilon$; if yes, quarantine this carrier family.

- branch_title: Relativizing locality-extraction gate for generated-OR carriers; cycle_id: cycle-0048; learning: Cycle 48 makes the obstruction formal: separator-denominator hardness is only an upper-bound falsifier, not a valid lower-bound certificate for H_N. The surviving route is direct C(H_N) lower bounds or a nonrelativizing locality-extraction theorem with explicit threshold loss.; next_experiment: Try to formulate a real-SAT locality extractor using witness self-reducibility: from a small circuit for H_N, isolate a generated satisfiable query and build a one-sided predicate; audit algebrization and $N^{o(1)}$ loss.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0081; learning: Cycle 81 separates the scoped occurrence-local theorem from the full EF + SAT_U ambition. The valid contribution is now sharper: private row spoofing is a genuine falsifier for occurrence-local functional certificates, while full EF + SAT_U requires a nonrelativizing semantic-to-occurrence extraction theorem because real SAT_U axioms are not invariant under independent label flips.; next_experiment: Formalize the semantic-coupling-width thought experiment as a lemma: for paired formulas F and F OR z, show exactly which SAT_U implication lines break private-label invariance and whether their violations can be charged to complete forced rows below the N^ϵ patch threshold.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0094; learning: Cycle 94 closes a concrete support-transparency subcase: bit-explicit EF extension variables can be parsed without support declarations, giving a valid transcript falsifier theorem. The full formula-semantic extraction fork is now sharper: the obstruction is not arbitrary EF extension variables but succinct FormulaEval-SAT comprehension, which defeats size-only occurrence parsing unless its row-index expansion is charged.; next_experiment: Formalize Psys_{sym} on finite length N: specify whether FormulaEval-SAT comprehension is a proof line, axiom schema, or extension rule; then prove either an expansion-charge parser with cost $N^{1+q+o(1)}$ or a minimal countermodel showing surface occurrence completion is unsound.

- branch_title: Hardness-Magnification Bridge Realization; cycle_id: cycle-0107; learning: Cycle 107 adds a real validation upgrade: transparent FormulaEval selectors no longer require

interval-union structure for a valid theorem, because full syntactic scanning gives a certified $B_{FE} = F_{FE}\ N^{1+q+o(1)}$ charge. This closes the $q < \epsilon$ falsifier for a broader selector fragment and isolates the only missing improvement as $AC0PrefixNonemptiness_N$ for output-sensitive enumeration. Full semantic FormulaEval remains quarantined by the private-row falsifier, not by generic barrier folklore.; next_experiment: Formalize $AC0PrefixNonemptiness_N$ as a finite lemma: for AC0 selectors on q log N row bits, test whether descriptor structure yields $N^{o(1)}$ prefix emptiness; if not, state the selector-scan theorem as final and add AC0 output-sensitive enumeration to open problems.

L Strategy Progression Judge

The 10-cycle payoff judge reads the target problem, literature evolution, latest analysis outputs, macro strategy, and contribution monitor.

Current strategy

Title. quantitative transfer obstruction for hardness magnification

Route family. Complexity lower-bound transfer

Active object. source exponent a, overhead q, target-query exponent β, and the target SAT exponent c

Macro thesis. Treat every proposed magnification route as an explicit transfer inequality from SAT $\in$ SIZE(n^c) or NP subset P/poly to a source-carrier upper bound.

Judgement summary

Decision. continue_with_targeted_adaptation

Payoff potential. high

Contribution pivot invariant. If the next work only restates hardness magnification, MCSP promise, or barrier folklore, the branch is looping. If it computes a concrete transfer parameter, proves a route-specific no-go, or certifies a searchable certificate carrier with no advice leakage, it is moving toward a real scientific contribution.

Next decisive test. Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

When to stop. Stop, backtrack, or quarantine when two sharpened attempts still yield only a bounded exponent window, advised hard strings, a natural/relativizing/algebrizing proof object, or a certificate-existence condition equivalent to the target lower bound.

Paper-level contribution readiness

Readiness.

Closest contribution.

Missing for paper.

Recommended paper move.

Main problem alignment

Alignment class. bridge_aligned

Alignment gain. The window is valuable when it replaces slogans about hardness magnification or barriers with exact source objects, target objects, thresholds, and falsifiers.

Alignment loss. The main danger is proving a bounded-window, advised, natural, relativizing, or target-equivalent proxy that cannot affect P vs NP route priority.

Proxy or transfer risk. The branch remains aligned only if its carrier, barrier escape, or transfer formula preserves uniformity, valid lengths, and the all-exponent target rather than proving a proxy statement.

Repair action. Every next analysis must name the complexity class target, source model, transfer formula or certificate object, and the falsifier that would force pivot.

Strategy payoff assessments

macro.pvsnp-black-box-transfer-audit

Payoff.

Risk.

Decision.

macro.pvsnp-padding-projection-demagnification

Payoff.

Risk.

Decision.

macro.pvsnp-meta-complexity-carrier-pressure

Payoff.

Risk.

Decision.

macro.pvsnp-nonblackbox-escape-search

Payoff.

Risk.

Decision.

M Accumulated Proof Strategy Story

Content-specific physics story from cycle-0001 through cycle-0154.

Latest learning. Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.

Current obstruction. The derivation does not cover arbitrary semantic SAT branch pruning or FormulaEval rules whose influencing rows are not determined by proof syntax before use; this is exactly $RealSATInfluenceRealizer_N^{arb}$.

Current next analysis. Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

cycle-0001: Hardness-Magnification Bridge Realization

Learning. The exact quantitative transfer is C(Pad_k(SAT)_N)<=O(N+N^{c/k}); hence the barely-superlinear lower bound magnifies only up to target exponent k(1+epsilon). The valid bridge is useful as an exponent-calibrated route lemma, while the fixed-k P/poly claim is blocked by a concrete threshold falsifier rather than by vague folklore.

Pressure. The bridge does not reach NP notin P/poly unless one proves a cofinal family of padded lower bounds or finds a non-artificial carrier whose interface compresses every polynomial target exponent below $N^{1+\epsilon}$.

Next. Instantiate the same exponent audit for a padded MKtP or GapMCSP carrier: name the verifier, compute Cook-Levin or direct-composition length blow-up, and test whether assuming SAT ∈ SIZE(n^c) yields source circuits below $N^{1+\epsilon}$ without model mismatch or nonuniform leakage.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0002: Hardness-Magnification Bridge Realization

Learning. Cycle 2 turns the previous threshold collapse into an exact quantifier repair. The valid route lemma is: fixed k gives only a finite SAT exponent lower bound, while a common-epsilon lower bound for unbounded padded carriers H_k would imply NP $\not\subset$ P/poly. The decisive falsifier is not folklore but the inequality $c/k \geq 1 + \epsilon$, plus the O(N) checker floor.

Pressure. No known source theorem proves $C_{H_k}(N) > N^{1+\epsilon}$ for unbounded k with a common ϵ against general nonuniform circuits.

Next. Test MCSP or proof-complexity carriers for producing the unbounded-k source family: formalize whether a weak lower bound for MCSP[2^{N^{1/k}}] transfers to $C_{H_k}(N) > N^{1+\epsilon}$ without becoming natural or losing the strict exponent margin.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0003: Hardness-Magnification Bridge Realization

Learning. Cycle 3 finds a valid single-carrier repair: growth padding $N_m = (m+1)^{g(m+1)}$ converts an i.o. $N^{1+\epsilon}$ lower bound for H_g into exclusion of every SAT exponent c. This is route-level progress, not P vs NP; the hard obligation is now the sparse valid-length lower bound.

Pressure. The required source lower bound is a barely-superlinear lower bound for a sparse explicit NP carrier on valid lengths; proving it already encodes superpolynomial SAT lower bounds in the unpadded parameter.

Next. Instantiate g(r)=ceil(log log(r+4)); prove the verifier and length test are poly(N), then analyze whether valid-slice lower bounds for H_g admit a proof-complexity or MCSP carrier formulation.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0004: Hardness-Magnification Bridge Realization

Learning. Cycle 4 proves a valid projection-sandwich lemma and demagnifies the sparse-padding route: N^{1+eps} lower bounds for H_g equal $m^{(1+eps)g}$ SAT lower bounds. The bridge is correct but not a weak-source path toward P vs NP.

Pressure. The bridge is valid, but its source obligation is not barely nontrivial in the original SAT length; it already asks for $m^{\omega(1)}$ SAT lower bounds.

Next. Test an MCSP or KT-complexity carrier with source model, threshold N^{1+eps}, and target NP $\not\subset$ P/poly; compute the reduction overhead and state whether the needed proof must be nonnatural or non-algebrizing.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0005: Hardness-Magnification Bridge Realization

Learning. Cycle 5 converts the padding quarantine into a general projection-carrier dichotomy. The valid bridge says $N^{1+\epsilon}$ lower bounds transfer through ell(N) only when $ell(N)^c$ is below the threshold. Positive polynomial embedding length gives only a bounded exponent window; subpolynomial embedding length gives all exponents but turns the source lower bound into $ell(N)^{\omega(1)}$. Thus pure projection magnification fails as a weak-source path, with an explicit falsifier rather than a slogan.

Pressure. Projection carriers cannot simultaneously keep the lower bound weak in the semantic source size and transfer it to exclusion of all polynomial SAT exponents.

Next. Audit an MCSP-based route: set source object $\mathrm{MCSP}_{n,s}$ on $N = 2^n - bit$ truth tables, choose a concrete circuit model for the lower bound, state the exact threshold $N^{1+\epsilon}$ or smaller, and test whether the known magnification transfer is non-natural, target-preserving, and strong enough to imply SAT $\notin$ P/poly rather than only EXP or subexponential derandomization consequences.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P

vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0006: Hardness-Magnification Bridge Realization, Cycle 6: MCSP verifier transfer audit

Learning. Cycle 6 shows that moving from projection padding to a nonprojection MCSP carrier does not by itself create major magnification. The valid transfer is $C(\mathrm{MCSP}_{N^\alpha}, N) = 0$ caps any fixed barely-superlinear bridge below all-exponent P/poly separation. The failure is a concrete threshold falsifier, not barrier folklore.

Pressure. For NP $\not\subset$ P/poly one must contradict every constant c, but fixed ϵ and α certify only c<(1+epsilon)/(1+alpha). Even $\alpha = 0$ leaves the input-reading ceiling $c < 1 + \epsilon$.

Next. Test a self-referential meta-complexity carrier, such as Gap-MCSP or MKtP with succinctly generated truth tables, where the target SAT circuit is used nonblack-box. Compute whether the induced carrier upper bound can avoid the multiplicative c factor; if not, quarantine it by the same beta-ceiling lemma.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0007: Hardness-Magnification Bridge Realization: black-box substitution cap

Learning. Cycle 7 generalizes the MCSP and padding failures to an oracle-interface theorem. A barely-superlinear carrier lower bound transfers through a black-box SAT interface as max{a,q+beta c}; hence positive target-query length exponent β is the decisive threshold-collapse falsifier. The remaining valid route must either use subpolynomial target queries with a genuinely nonprojection carrier or abandon black-box substitution.

Pressure. The only unquarantined escape is to construct a nonprojection carrier with $N^{o(1)}$ target query length, $sub - N^{1+\epsilon}$ interface size, and a valid $N^{1+\epsilon}$ nonuniform lower bound.

Next. Test a succinct local-consistency or proof-complexity carrier with $N^{o(1)}$ SAT queries: compute a,q,beta, then run the projection-demagnification falsifier before claiming any magnification.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0008: Hardness-Magnification Bridge Realization, cycle 8: subpolynomial-query threshold repair

Learning. Cycle 8 repairs the remaining route exactly: subpolynomial SAT-query length is sufficient to remove the c-dependent threshold term, so $N^{1+\epsilon}$ lower bounds magnify only when $max(a, q) < 1 + \epsilon$. The valid contribution is a quantified bridge plus a model-preservation gate; the unresolved hard task is finding a concrete carrier satisfying the interface and source lower bound without natural-proof or nonuniform-leakage failure.

Pressure. No concrete non-natural carrier K is known with both a near-linear subpolynomial-query SAT interface and an $N^{1+\epsilon}$ nonuniform circuit lower bound. MCSP-like truth-table carriers fail because their SAT-verification queries have polynomial, usually linear, dependence on N.

Next. Search for non-truth-table carriers in P^{SAT} with near-linear ordinary work and subpolynomial SAT queries, e.g. succinct consistency or decompression-check problems, then compute A,Q,s and test against L8.1 before discussing P vs NP.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0009: Hardness-Magnification Bridge Realization: subpolynomial-interface demagnification

Learning. Cycle 9 converts the cycle-8 repair into a route failure certificate. Subpolynomial SAT queries remove the c-dependent upper-bound term, but the same transfer read backward says that proving the source $N^{1+\epsilon}$ lower bound in general SIZE already proves $SAT_{\leq L}$ has $L^{\omega(1)}$ circuits lower bounds. The remaining valid work is not carrier search inside this black-box same-model interface; it is either a restricted-model closure theorem or a nonblackbox carrier.

Pressure. The branch has no concrete carrier that is simultaneously a weak same-model source lower bound and target-preserving. Same-model sources demagnify; restricted sources need an unproved substitution-closure theorem.

Next. Pivot to a nonblackbox object: test a proof-complexity or derandomization carrier where SAT in P/poly yields the required source upper bound through a named nonrelativizing theorem rather than through black-box SAT-query substitution.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0010: Hardness-Magnification Bridge Realization

Learning. Cycle 10 proves a valid restricted-model closure bridge and names the precise target-preservation failure. Subpolynomial queries plus $max(a, q) < 1 + \epsilon$ magnify a Γ lower bound to SAT notin Γ/poly for every fixed exponent. This is real route-level progress, but it is not NP notin P/poly: the missing object is a nonuniform P/poly-to-Gamma lift with subthreshold tax, and its absence is the decisive falsifier for advertising the bridge as a P vs NP route.

Pressure. The target-preserving lift from arbitrary P/poly SAT circuits to $\Gamma - circuits$ is absent; without it, restricted-source magnification leaks the target model.

Next. Test a non-natural nonblackbox carrier whose query length is $N^{o(1)}$ and whose use of a SAT circuit is semantic rather than oracle substitution; compute whether its lift tax δ is below the source slack ϵ.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0011: Hardness-Magnification Bridge Realization: lookup-lift collapse for restricted target repair

Learning. Cycle 11 turns the cycle-10 target split into a sharper impossibility triangle. To lift Γ lower bounds to P/poly by unrolling arbitrary SAT circuits, queries must be so short that every SAT query can also be answered by unconditional lookup inside Γ. That gives H_N a subthreshold Γ upper bound and falsifies the source lower bound. Intermediate log-query lengths either collapse the source or preserve only exponent $c \leq 1$. Thus black-box formula-style P/poly repair is quarantined; progress now requires a genuinely nonblackbox carrier or a proof object where target circuits are used without independent short-query lookup.

Pressure. The missing bridge is not merely an efficient P/poly-to-Gamma simulation; it must be efficient for SAT-derived query computations while not enabling small lookup for all short query predicates. Generic unrolling cannot satisfy both requirements.

Next. Test a nonblackbox proof-complexity carrier: encode a SAT circuit as a verifier object whose correctness is checked globally rather than by short oracle leaves, and compute whether the verifier overhead stays below $N^{1+\epsilon}$ without allowing $\mathrm{SAT}_{\leq L}$ truth-table substitution.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0012: Hardness-Magnification Bridge Realization

Learning. Cycle 12 identifies a real surviving window: superlogarithmic subpolynomial target lengths, especially L=(log N)^d with $d > 1$. In this window SAT circuits of size L^c amortize to $N^{o(1)}$, but SAT truth tables cost 2^L and no longer give the old subthreshold lookup falsifier. The bridge is valid only for nonblackbox compact-circuit consumers; it is not a P vs NP proof without the explicit carrier and lower bound.

Pressure. No explicit carrier H_N and evaluator E_N are yet exhibited whose computation genuinely exploits compact SAT circuits rather than ordinary oracle answers, and no $N^{1+\epsilon}$ lower bound for such an H_N is known.

Next. Instantiate H_N as a proof-checking or self-reduction transcript language whose verifier can call a compact SAT_L circuit nonblackbox; compute its exact overhead a and test whether full truth-table substitution or input-encoded D leakage gives a subthreshold upper bound.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0013: Hardness-Magnification Bridge Realization: Polylog Nonblackbox Compact Consumer

Learning. Cycle 13 turns the superlogarithmic polylog window into an exact bridge: L=(log N)^d with $d > 1$ makes SAT circuits of size L^c amortize to $N^{o(1)}$, while truth-table lookup costs 2^L=N^{omega(1)} and no longer supplies the old falsifier. The valid threshold is $\rho < 1 + \epsilon$ for a target-clean nonblackbox compact consumer. The new hard obstruction is not folklore but the absence of an explicit carrier with no advice leakage and a non-natural $N^{1+\epsilon}$ general-circuit lower bound.

Pressure. No explicit carrier H_N is yet supplied with both a target-clean polylog nonblackbox compact consumer and an i.o. $N^{1+\epsilon}$ general-circuit lower bound. The lower-bound proof also must be non-natural or otherwise outside the natural-proofs obstruction.

Next. Instantiate $PolyLogAudit_{N,d,V}$ with a universal-circuit verifier, compute the exact overhead exponent ρ and auxiliary advice length, and reject the instance immediately if H_N depends on a hidden SAT circuit or collapses to a black-box SAT query family.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0014: Hardness-Magnification Bridge Realization: polylog generated-OR carrier

Learning. Cycle 14 identifies a concrete carrier template, $H_N = OR$ of N^q generated SAT instances of length (log N)^d, and computes the exact transfer: SAT $\in$ SIZE(n^c) gives H_N in SIZE(N^{max{rho,q}+o(1)}). The valid magnification window is max{rho,q}1, exhaustive lookup is $N^{q+\omega(1)}$, so the previous short-query falsifier is avoided, but the source lower bound remains the hard non-natural obligation.

Pressure. The bridge is valid, but no explicit target-clean G_N, A_N is known with a provable unrestricted circuit lower bound SIZE(H_N) $> N^{1+\epsilon}$. A proof of that source bound must also avoid natural-proof density, relativizing oracle, and advice-leakage obstructions.

Next. Instantiate G_N as a near-linear Cook-Levin micro-instance generator with $M = N$ and L=(log N)^d; compute exact ρ, verify H_N is in NP with poly(N) uniform verification, and test whether any structural simplification gives an $N^{1+\epsilon}$ upper-bound falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0015: Hardness-Magnification Bridge Realization

Learning. Cycle 15 adds the exact lookup boundary. Polylog queries always preserve all SAT polynomial exponents in the substitution term, but source plausibility requires q+A(log N)^{d-1} not fall below 1+epsilon. Thus d1 is safely valid from lookup.

Pressure. No explicit no-advice generator G_N is known for which H_N has an i.o. $N^{1+\epsilon}$ general-circuit lower bound by a non-natural method.

Next. Instantiate the boundary cases $d = 1$ with $A = 1 + \epsilon - q$ and $d = 2$; search for a generator whose H_N avoids known small-circuit constructions without smuggling SAT advice.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0016: Hardness-Magnification Bridge Realization

Learning. Cycle 16 sharpens the generated-OR route: the valid transfer to SAT $\notin$ P/poly needs only $q, \rho < 1 + \epsilon$, but source plausibility additionally requires variable entropy q+v/log N at least 1+epsilon. The old 2^L lookup audit was too weak; the real falsifier is low variable count.

Pressure. No explicit target-clean generator is known whose OR carrier has a non-natural unrestricted $N^{1+\epsilon}$ circuit lower bound while also passing the variable-entropy gate.

Next. Instantiate G_N with high-essential-variable polylog 3CNF queries and test whether any structural simplification gives SIZE(H_N) $\leq N^{1+\epsilon-o(1)}$ despite v(N) superlogarithmic.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0017: Hardness-Magnification Bridge Realization: positioned-range entropy audit

Learning. Cycle 17 adds a sharper necessary condition for the generated-OR route: not only $q, \rho < 1 + \epsilon$, but the positioned effective range entropy sum_g $min|R_g|, 2^v$ must reach the lower-bound threshold. This converts low-range query generation into an explicit falsifier and preserves the valid target transfer only for high-entropy, target-clean carriers.

Pressure. No explicit target-clean carrier is known with q,rho=1+epsilon-o(1), and a non-natural $N^{1+\epsilon}$ lower bound against general circuits.

Next. Instantiate K_N from a specific extractor-like generator of polylog-length CNFs and compute $|R_g|$, v_N, q, and ρ exactly to see whether the positioned entropy threshold can be met without advice leakage.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0018: Hardness-Magnification Bridge Realization: positioned entropy cover gate

Learning. Cycle 18 proves the exact positioned entropy cover upper bound. The route now has two independent gates: target transfer needs $max\rho, q = N^{1+\epsilon-o(1)}$ after charging the generator.

Low variable count or low positioned range is a concrete falsifier, not a folklore barrier.

Pressure. The derivation proves only an upper-bound/falsifier lemma. It does not prove $C(H_N) > N^{1+\epsilon}$ for any explicit high-entropy carrier.

Next. Instantiate the affine-disperser generated-OR family and compute B_N exactly as a function of α, q, and clause density; then audit whether any known lower-bound technique for this restricted H_N avoids the natural-proofs density condition.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0019: Hardness-Magnification Bridge Realization: semantic range leakage gate

Learning. Cycle 19 sharpens the generated-OR route: positioned entropy is not the decisive source gate. The valid bridge uses the semantic cover $S_N = sum_j$ C_{R_{N,j}}(SAT). Subthreshold S_N is a concrete falsifier for H_N lower bounds, while $q, \rho < 1+\epsilon$ still gives the target-preserving implication from a valid H_N lower bound to SAT $\notin$ P/poly.

Pressure. The derivation does not supply an explicit G_N for which both H_N has a general-circuit lower bound $N^{1+\epsilon}$ and $S_N = sum_j$ C_{R_{N,j}}(SAT) is provably above $N^{1+\epsilon-o(1)}$.

Next. Instantiate G_N with a concrete expander or extractor-based 3-CNF generator, compute $R_{N,j}$ structure, and test whether SAT on those positioned ranges collapses to a known easy subclass or requires a new semantic lower-bound certificate.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0020: Hardness-Magnification Bridge Realization: Semantic Block-Cover Gate

Learning. Cycle 20 sharpens the generated-OR route: the valid target bridge is unchanged, but the source plausibility gate must minimize over semantic block covers. Singleton range complexity is too weak because OR compression and nonuniform block advice can falsify an $N^{1+\epsilon}$ source lower bound. This is route-level progress, not a proof of P $\neq$ NP.

Pressure. No direct-sum theorem converts $M_N \geq N^{1+\epsilon-o(1)}$ into $C(H_N) > N^{1+\epsilon}$. A circuit for H_N may compute the union of positive preimages without decomposing along any chosen partition.

Next. Instantiate M_N for a nontrivial generator without dominated coordinates, e.g. a universal verifier family whose queries are Cook-Levin encodings of polylog-size computations, and compute whether block predicates admit compression below $N^{1+\epsilon}$.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0021: Hardness-Magnification Bridge Realization: Shared-Generator Semantic Block-Cover Gate

Learning. Cycle 21 replaces the previous block-cover warning by an exact shared-generator semantic-cover lemma. The valid target bridge is unchanged, but the source lower bound must beat

$C(G_N) + min_{Pi}\ sum_B$ C_{R_B}(OR-SAT_B). This creates a concrete falsifier: any subthreshold semantic block partition kills the generated-OR carrier before it can contribute to SAT $\notin$ P/poly.

Pressure. No candidate generator is known for which $min_{Pi}\ sum_B$ C_{R_B}(OR-SAT_B) can be proved at $N^{1+\epsilon-o(1)}$ in general circuits.

Next. Run the block-size thought experiment for $b = N^{\theta}$: derive upper bounds on U(theta) from range cardinality, feature compression, and OR compression, then identify whether any θ gives N^{rho}+N^{q-theta}U(theta)<N^{1+epsilon}.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0022: Hardness-Magnification Bridge Realization

Learning. Cycle 22 isolates the next exact gate: the generated-OR bridge is valid only if the source lower bound defeats nonuniform promise solvers on the actual SAT range. The new quantitative obstruction is $T_N > N^{1+\epsilon-q-o(1)}$ for SAT restricted to U_N, plus the earlier semantic block-cover threshold. This is route-level progress, not a proof of P $\neq$ NP.

Pressure. No current argument proves the required promise-SAT or block-cover lower bound for an explicit high-entropy generated range U_N; entropy and query length do not imply semantic circuit hardness.

Next. Instantiate G_N with a high-entropy family of polylog-size 3-CNF formulas and compute the best promise solver or block-cover upper bound; vary τ to locate the first threshold-respecting candidate.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0023: Hardness-magnification bridge realization: generated-OR range-balance gate

Learning. Cycle 23 adds an exact range-label balance gate. Even with q,rho in the valid target window, a generated-OR carrier is source-plausible only if both satisfiable and unsatisfiable parts of its actual generated range exceed $N^{1+\epsilon-q-o(1)}$. This is a concrete falsifier derived from equality-DNF membership circuits, independent of vague barrier folklore.

Pressure. No explicit generator is known whose H_N beats unrestricted $N^{1+\epsilon}$ circuits while also defeating range-label imbalance, promise solvers on U_N, and semantic block-cover compression.

Next. Instantiate a template generator for polylog-length 3CNFs and estimate $\theta = min$ label-support exponent; then compare it with 1+epsilon-q and with the best promise-SAT solver size on the generated template range.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0024: Hardness-Magnification Bridge Realization: hitting-cover gate for generated-OR carriers

Learning. Cycle 24 sharpens the generated-OR route from label balance to exact hitting-cover hardness. The valid target bridge is unchanged, but the source lower bound must now defeat

nonuniform covers of positive fibers and negative product fibers of total size $N^{1+\epsilon-o(1)}$. This gives a new concrete falsifier and shows that high semantic range entropy alone cannot justify the carrier.

Pressure. No current argument lower-bounds the exact hitting-cover parameter κ for an explicit target-clean generator; raw semantic range size, variable entropy, and label balance all allow small-cover falsifiers.

Next. Formalize the minimum cover parameter as a bipartite set-cover problem between input fibers and generated SAT labels; test whether known disperser/extractor-style generators can force $kappa_N > N^{1+\epsilon-o(1)}$ without reintroducing nonuniform leakage.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0025: Generated-OR magnification: selector-range leakage gate

Learning. Cycle 25 adds a shared-selector leakage gate. A generated-OR carrier can be easy via one compact selector and a promise SAT solver on only the selected image, even when additive semantic or hitting covers look expensive. Thus the valid source obligation is not merely high range entropy or label balance; it is lower bounding every selector-plus-selected-range-solver pair above $N^{1+\epsilon-o(1)}$ while preserving $q, \rho < 1 + \epsilon$ for the target bridge.

Pressure. Need a direct-sum or shared-computation lower bound converting any small selector/promise-solver circuit into a subthreshold cycle-24 cover. No such theorem is available, and it is plausibly false for structured selectors.

Next. Instantiate Sel_N for simple generator templates, including lexicographic first-satisfying-query generators and hash-bucketed query generators, and compute whether selected-image lookup already drops below $N^{1+\epsilon}$.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0026: Hardness-Magnification Bridge Realization

Learning. Cycle 26 adds an approximate-selector gate. Exact witness selection was too weak as a source audit: even a selector wrong on N^{δ} inputs collapses H_N below $N^{1+\epsilon}$ when $deltaN^{1+\epsilon-o(1)}$, while the clean target bridge $q, \rho < 1 + \epsilon$ remains intact.

Pressure. No concrete E_N is known for which $Lambda_N > N^{1+\epsilon-o(1)}$ can be proved in unrestricted circuits; proving it appears to require non-natural, selector-resistant lower-bound machinery rather than entropy counting.

Next. Instantiate the thought experiment with a block generator E_N whose coordinates are grouped into planted easy and hard ranges; compute the smallest δ forced by coverage of positive inputs and test whether selected-range promise SAT stays subthreshold.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0027: Hardness-Magnification Bridge Realization: approximate list-selector leakage gate

Learning. Cycle 27 upgrades the source audit from approximate single selectors to approximate list selectors. The valid target-preserving bridge is unchanged, but a short list plus a promise solver can decide H_N without computing a canonical witness. Therefore any contribution-making

lower-bound attempt must lower-bound $Lambda_N^{list}$; otherwise the route has a concrete nonuniform-leakage falsifier.

Pressure. Witness canonicalization is semantic; it is not available from the selector circuit alone and can be bypassed by list-wise OR evaluation.

Next. Instantiate G_N with a high-entropy expander/hash-generated SAT family and compute whether any tau=O(epsilon/2) list selector has a selected image admitting a subthreshold promise solver.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0028: Hardness-Magnification Bridge Realization

Learning. Cycle 28 identifies an additional leakage mode: many imperfect list selectors can collectively cover the positive fiber. The valid source audit is the ensemble cover complexity Xi_N^{ens}; single-selector minimax lower bounds are insufficient for this generated-OR magnification route.

Pressure. No lower-bound method is known for Xi_N^{ens} against fully nonuniform selected-image promise solvers; ensemble covers can exploit semantic clusters invisible to entropy counts.

Next. Estimate Xi_N^{ens} for a random high-entropy generator by a union-bound model over ensembles, then isolate which part of the argument can survive explicitness and avoid natural-proof leakage.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0029: Hardness-Magnification Bridge Realization: one-sided separating-ensemble leakage gate

Learning. Cycle 29 sharpens the generated-OR source audit from ensemble list selectors to one-sided selected-image separators. The valid target bridge still needs only $q, \rho < 1 + \epsilon$, but the source lower bound must now beat Psi_N^{sep}; small local labelers are a concrete falsifier even when they do not solve SAT globally.

Pressure. No available lower-bound method rules out arbitrary selected-image separators B_t. These labelers need not be SAT algorithms, so the target SAT hardness hypothesis does not exclude them.

Next. Try to lower-bound or construct Psi_N^{sep} for a random-like generator: estimate whether selected positive and negative images admit $N^b - size$ separators when $R = N^r$ and $s = N^{ell}$ are below the magnification threshold.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0030: Hardness-Magnification Bridge Realization

Learning. Cycle 30 replaces the one-sided selected-image audit by the weaker and more dangerous relaxed bag-separator audit. The valid target bridge is unchanged, but the source lower bound must defeat predicates that merely hit one positive witness per positive bag and avoid all negative-bag formulas. This exposes a concrete nonuniform-leakage falsifier not captured by promise SAT hardness.

Pressure. The converse is false or at least unproved: absence of small relaxed formula separators does not imply H_N is hard, because an arbitrary H_N circuit may exploit input-level structure that does not factor through a formula predicate.

Next. Formalize $SepHit_N$ as a bipartite hitting-avoidance problem between positive bags and negative formula occurrences, then test whether random-looking generators satisfy the required lower bound by a counting argument and where explicitness breaks the argument.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0031: Hardness-Magnification Bridge Realization: approximate relaxed bag separators

Learning. Cycle 31 converts relaxed bag separators into an approximate threshold lemma: E bad bags cost NE gates, so errors below N^{ϵ} are nonuniformly patchable. The valid source obligation is now an approximate distribution-local separator lower bound, not merely promise SAT hardness.

Pressure. We still lack a lower bound against all distribution-local approximate bag separators; global promise-SAT hardness does not rule out local predicates tuned to the generated bags.

Next. Try a collision-balanced generator and estimate whether majority/hash-based local predicates yield $s = N^{o(1)}$ with $E < N^{\epsilon}$; if yes, quarantine this carrier family.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0032: Generated-OR magnification: correction-residual separator gate

Learning. Cycle 32 converts the approximate bag-separator gate into an exact correction-residual gate. The valid target bridge is unchanged, but the source lower bound must prove Phi_N>1+epsilon-o(1): every small local formula predicate must leave a residual H_N xor S_A of high circuit complexity. Sparse error patching is only one falsifier; structured residual leakage is the stronger obstruction.

Pressure. No known reduction converts a small residual correction R_A into a small SAT solver or separator on the generated formula range. This is the current formal gap.

Next. Instantiate Phi_N for a tagged generated-OR carrier and compute whether simple tag predicates produce subthreshold residual circuits; then test an untagged high-entropy generator for the same residual leakage.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0033: Hardness-Magnification Bridge Realization

Learning. Cycle 33 strengthens the generated-OR source obligation from single residual correction to feature-aggregator residual hardness. This is a contribution-making repair: it preserves the exact target bridge but exposes a broader nonuniform-leakage falsifier class that prior selector and separator audits did not cover.

Pressure. The missing proof obligation is a lower bound on C(H_N xor $S_{A,B}$) for all subthreshold feature families and aggregators. Promise SAT hardness on the generated range does not imply this residual lower bound, because B may exploit many weak local features jointly.

Next. Formalize the restricted case where B is a depth-2 threshold or DNF over $t = N^{\tau}$ local features, compute the exact q+alpha+beta leakage threshold, and search for an explicit low-residual construction on expander-walk generated SAT bags.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0034: Hardness-Magnification Bridge Realization: tuple-feature residual gate

Learning. Cycle 34 adds a quantitative tuple-arity term to the generated-OR audit. The valid target bridge still needs only $max\rho, q < 1 + \epsilon$, but the source lower bound must rule out every subthreshold tuple-feature transcript with exponent s+tq+alpha and residual exponent λ. This yields a finite dense-arity falsifier search and a sharper nonuniform-leakage obstruction, without claiming P $\neq$ NP.

Pressure. The derivation gives an exact upper-bound falsifier class, but it does not prove that arbitrary small circuits for H_N factor through low-arity tuple transcripts. The remaining source obligation is a genuine unrestricted-circuit lower bound or a non-natural theorem ruling out all residual systems and all non-factored circuits.

Next. Instantiate the pair-pattern thought experiment for $t = 2$: choose q with $q < 1+\epsilon$ and test whether $2q+\alpha < 1+\epsilon$ permits a subthreshold pair separator S_N; compute the residual complexity C(H_N xor S_N) and check for hidden SAT lookup.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0035: Hardness-Magnification Bridge Realization: high-q arity cutoff for generated-OR carriers

Learning. Cycle 35 finds a parameter repair: set q in ((1+epsilon)/2,1+epsilon) to preserve the generated-OR target bridge while forcing every dense tuple-feature transcript of arity at least two above the $N^{1+\epsilon}$ threshold. The route-level lower-bound obligation is now the sharper unary residual minimax gate, not an infinite tuple-arity audit.

Pressure. No proof is known that an explicit high-q generator defeats all unary range-local transcripts and subthreshold residual corrections. High q may even help unary predicates by presenting many chances to hit a satisfiable generated formula.

Next. Formalize unary transcripts as monotone OR-of-range predicates, then test whether random-looking high-q generators make every subthreshold unary transcript leave residual circuit complexity above $N^{1+\epsilon-o(1)}$ or whether a selected-image separator falsifier appears.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0036: Hardness-Magnification Bridge Realization: position-indexed unary residual gate

Learning. Cycle 36 repairs the high-q unary reduction: binary and higher tuple features are threshold-blocked when $q > (1+\epsilon)/2$, but shared-unary audits are not sound for general circuits. The valid remaining source obligation is a position-indexed unary transcript plus residual lower bound with total local budget U_N. This is a sharper route-level gate and supplies an explicit falsifier class, without claiming P $\neq$ NP.

Pressure. No lower-bound technique is supplied for the position-indexed unary residual minimax quantity. Proving it for an explicit H_N is essentially a general-circuit lower bound for a highly structured generated OR, not a consequence of the magnification bridge.

Next. Formalize $Iota_N^{pos}$ as a minimax transcript-residual measure and test whether expander-style slot mixing can rule out all low-budget position-indexed unary decompositions without becoming a natural-proof argument.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0037: Hardness-Magnification Bridge Realization: approximate witness-cover gate

Learning. Cycle 37 sharpens the position-indexed unary residual obligation into an approximate witness-cover threshold. In the high-q generated-OR route, dense tuple leakage is threshold-blocked, but unary assignment covers of total size below $N^{1+\epsilon}$ plus fewer than N^{ϵ} missed positives still give exact circuits for H_N after equality patching. This is route-level progress: a valid candidate source lower bound must first prove high approximate witness-cover complexity, while the main P $\neq$ NP conjecture remains untouched.

Pressure. No explicit generated-OR family is known to have approximate position-indexed witness-cover complexity above this threshold, and defeating witness covers is still weaker than defeating arbitrary position-indexed unary predicates plus residual circuits.

Next. Instantiate the thought experiment with a concrete planted/anti-planted CNF generator and compute the minimum position-indexed assignment hitting exponent h for its satisfiable range; compare h to 1+epsilon-q.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0038: Hardness-Magnification Bridge Realization: realized-witness projection gate

Learning. Cycle 38 isolates a canonical unary leakage mechanism: all realized satisfying witnesses per generated position form a zero-error cover. Thus a valid high-q generated-OR route needs W_N^*>N^{1+epsilon-o(1)} or a stronger approximate-cover lower bound. The target substitution bridge survives, but source plausibility is now governed by witness-projection entropy rather than formula-range entropy alone.

Pressure. This proves only a necessary gate for the carrier lower bound. It does not supply the hard lower bound against all possible approximate witness covers.

Next. Instantiate the planted-pool thought experiment and compute W_N^* for affine, low-degree, and pseudorandom assignment-pool generators; check whether any preserves $q + a > 1 + \epsilon$ without introducing natural-proof or advice-leakage collapse.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0039: High-q generated-OR carrier: partial-certificate cover gate

Learning. Cycle 39 sharpens the generated-OR source audit: full realized witness entropy is not the right gate because partial satisfying terms can compress many witnesses. The valid target

bridge remains $max\rho, q < 1 + \epsilon$, but the route now needs a superthreshold lower bound against position-indexed partial-term covers, and ultimately against sound local certificate covers.

Pressure. No valid extraction theorem converts an arbitrary small circuit for H_N into a small full-witness set, and partial certificates give a concrete counter-mechanism.

Next. Formalize tau_N^{term} as a set-cover problem over generated CNF ranges and test whether random-looking high-q generators can force tau_N^{term}>N^{1+epsilon} without making G_N nonexplicit or violating $\rho < 1 + \epsilon$.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c → c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the certificate-cover branch, compute K,E,L and the induced circuit upper bound C(H_N)<=C(G_N)+O(K(s+L^{O(1)})+EN); promotion requires every sound local cover to stay above the $N^{1+\epsilon-o(1)}$ source threshold.

cycle-0040: Hardness-Magnification Bridge Realization: sound local certificate cover gate

Learning. Cycle 40 sharpens the source audit from partial certificate covers to approximate sound local certificate covers. The exact upper bound C(H_N)<=C(G_N)+O(K(s+L^{O(1)})+EN) makes any subthreshold SLC cover a concrete falsifier. The target bridge remains valid, but a contribution now requires a superthreshold lower bound against one-sided local predicates on the generated range, not just high witness or formula entropy.

Pressure. No current argument proves that every one-sided local certificate predicate family of total size below $N^{1+\epsilon-o(1)}$ misses at least $N^{\epsilon-o(1)}$ positive bags on the actual generated range.

Next. Compute the SLC cover exponent for generated formulas with bounded backdoor width $b = \alpha$ log N and for small semantic classes such as Horn, 2-SAT, and bounded-width CNF; identify whether the threshold $\alpha \geq 1 + \epsilon - q$ is achievable without destroying the SAT-substitution bridge.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the certificate-cover branch, compute K,E,L and the induced circuit upper bound C(H_N)<=C(G_N)+O(K(s+L^{O(1)})+EN); promotion requires every sound local cover to stay above the $N^{1+\epsilon-o(1)}$ source threshold.

cycle-0041: One-sided promise-separator gate for high-q generated-OR magnification

Learning. Cycle 41 isolates the exact semantic object behind the sound-local-certificate audit: Sep_N^{1s}(E). Random term-cover calculations support the high-q polylog design, but they do not imply the needed separator lower bound. The main new obstruction is the term-cover versus one-sided semantic-separator gap.

Pressure. No valid extractor converts arbitrary one-sided semantic separators into partial witnesses; range closure under restrictions is absent, so term-cover calibration cannot certify Sep_N^{1s} lower bounds.

Next. Test a range-closure repair: augment G_N so restrictions of emitted formulas also appear in controlled positions, compute the q/rho overhead, and see whether this lets a one-sided separator self-reduce to a term cover without breaking the $N^{1+\epsilon}$ threshold.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.

cycle-0042: Cycle 42: distributional cap certificate for one-sided semantic separators

Learning. Cycle 42 turns the one-sided semantic-separator obstruction into an exact distributional cap profile A_N(s). The valid source route now needs a superthreshold cap-to-separator lower bound, not merely random witness or term-cover entropy. The target bridge is preserved, but any large one-sided cap is a concrete falsifier for the generated-OR lower bound.

Pressure. Term-cover randomness does not imply a cap bound for arbitrary one-sided semantic predicates. The missing theorem is a one-sided conditional pseudorandomness statement for the distribution of generated formulas inside positive bags.

Next. Formalize the cap profile for the unmarked random k-CNF generated-OR thought experiment: compute assignment-test hit exponents as a function of β, then identify the first semantic predicate class beyond terms that can violate or support $A_N(s) \leq s/N^{1+\epsilon-o(1)}$.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.

cycle-0043: Generated-OR residual cap gate for hardness magnification

Learning. Cycle 43 converts the cap profile into a residual fractional covering threshold. A valid source lower bound must rule out greedy one-sided cap covers with $B_N(s, E) < N^{\epsilon-sigma-o(1)}$; absence of a large first cap is not enough.

Pressure. No known method proves worst-case residual cap denominator $B_N(s, E) > N^{\epsilon-sigma-o(1)}$ for semantic one-sided caps with nonuniform advice.

Next. Try to construct residual caps for the planted/random 3CNF generator using partial-assignment certificates, and compute the resulting exponent b.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.

cycle-0044: Hardness-Magnification Bridge Realization: residual cap-denominator gate

Learning. Cycle 44 converts the residual cap profile into a greedy cap-denominator theorem. A generated-OR source lower bound must now produce hard residual positive distributions against all one-sided local predicates; otherwise D_N N^{sigma} and E N give an explicit subthreshold upper-bound falsifier. This is route-level progress, not a main P $\neq$ NP proof.

Pressure. No lower bound is known showing that every residual positive distribution fools all one-sided generated-range predicates of size N^{sigma} at hit probability $N^{-(1+\epsilon-sigma)}$.

Next. Instantiate the cap audit for partial-assignment predicates of width w on L=(log N)^2 formulas: compute theta(w,sigma) for random-looking generated ranges, then check whether sigma+theta can stay above 1+epsilon while q,rho remain in the target-preserving window.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the one-sided

semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.

cycle-0045: Hardness-Magnification Bridge Realization: Greedy Cap Dual Gate

Learning. Cycle 45 adds the missing logarithmic greedy-cover charge and converts the cap profile into an exact threshold: $D_{sigma,E} < N^{\epsilon - sigma - o(1)}$ is a concrete upper-bound falsifier for the generated-OR source lower bound. A valid route must now prove hard residual positive distributions against all one-sided separators and also close the normal-form gap from arbitrary circuits to separator covers.

Pressure. The derivation only rules out separator-cover upper bounds. It does not prove that every subthreshold exact circuit for H_N has a valid one-sided separator normal form.

Next. Work in a restricted circuit model such as De Morgan formulas or AC0[p] and test whether exact circuits for H_N admit an approximate one-sided separator normal form; compute the resulting $D_{sigma,E}$ threshold for the same high-q polylog generated-OR carrier.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.

cycle-0046: Hardness-Magnification Bridge Realization: normal-form extraction gate

Learning. Cycle 46 converts the cycle-45 normal-form warning into a precise obstruction. Greedy cap and separator denominators give valid upper-bound falsifiers, but separator hardness is not by itself a source lower bound. A planted-control generated-OR carrier can have H_N easy while local formula separators remain hard, so the route now needs a nonrelativizing locality-extraction theorem or a direct arbitrary-circuit lower bound for H_N.

Pressure. No valid locality-extraction theorem maps arbitrary small circuits for H_N into one-sided formula-local separator covers with subthreshold overhead.

Next. Formalize a restricted no-control generator class, such as block-product independent seeds with no shared label bit, and test whether an S-size circuit for OR_j SAT(G(x,j)) can be localized to a one-sided separator cover; compute the exact overhead in q,rho,sigma,E.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the one-sided semantic-separator branch, compute the cap profile A_N(s) for the named generator and predicate class; promotion requires a bound strong enough to force Sep_N^{1s}(E)>N^{1+epsilon-o(1)}.

cycle-0047: Hardness-Magnification Bridge Realization: locality-extraction obstruction

Learning. Cycle 47 converts the locality-extraction warning into a formal relativizing obstruction. A planted-control oracle gives hard one-sided local separators but an O(1)-size generated-OR carrier, so separator hardness is not a valid source lower-bound certificate by itself. The target substitution bridge survives unchanged; the route must now prove a nonrelativizing extraction theorem for real SAT or attack C(H_N) directly.

Pressure. There is no valid black-box operation that extracts a formula-local one-sided separator from an arbitrary global circuit for H_N. The missing step must exploit nonrelativizing real-SAT structure or be replaced by a direct arbitrary-circuit lower bound for H_N.

Next. Try a real-SAT extraction using self-reducibility or witness isolation: from a small circuit for H_N, define a local predicate that accepts formulas whose forced witness path changes the global OR value, compute the overhead, and test it against the planted-control oracle falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0048: Relativizing locality-extraction gate for generated-OR carriers

Learning. Cycle 48 makes the obstruction formal: separator-denominator hardness is only an upper-bound falsifier, not a valid lower-bound certificate for H_N. The surviving route is direct C(H_N) lower bounds or a nonrelativizing locality-extraction theorem with explicit threshold loss.

Pressure. No known nonrelativizing locality-extraction theorem converts an arbitrary small H_N circuit into local SAT-range separators with only $N^{o(1)}$ loss.

Next. Try to formulate a real-SAT locality extractor using witness self-reducibility: from a small circuit for H_N, isolate a generated satisfiable query and build a one-sided predicate; audit algebrization and $N^{o(1)}$ loss.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0049: Hardness-Magnification Bridge Realization: locality extraction threshold

Learning. Cycle 49 converts the surviving generated-OR route into an exact extraction-threshold problem. Separator-denominator hardness is a valid source certificate only if every small H circuit yields covers with denominator S/N^{1+sigma}+N^kappa and $\kappa < \epsilon - sigma$. Neutralization gives a concrete extraction but is a demagnifying falsifier, because it asks for restricted-SAT hardness rather than a barely-superlinear H lower bound.

Pressure. There is no valid operation converting an arbitrary global H circuit into local SAT-range separators without either neutralizing the generator or using a new real-SAT, nonrelativizing locality principle.

Next. Formalize one candidate extraction using SAT self-reducibility plus generator local decodability, then compute whether the required decodability already implies neutralizing embeddings and hence demagnification.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0050: Hardness-Magnification Bridge Realization: Relativizing Extraction Falsified

Learning. Cycle 50 gives a precise obstruction: small H_N circuits can coexist with superthreshold one-sided separator complexity in a structured singleton oracle. Thus the extraction bridge must be explicitly nonrelativizing and real-SAT-specific; separator hardness alone is not a valid source lower-bound certificate.

Pressure. The argument is an oracle obstruction, not a real-SAT lower bound. Real CNF satisfiability may have nonrelativizing syntactic structure unavailable to singleton oracle labels.

Next. Audit real-SAT self-reduction or proof-certificate structure as a possible nonrelativizing extractor, and compute whether its verifier/certificate overhead stays below $N^{1+\epsilon}$ rather than collapsing to restricted-SAT hardness.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact

barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0051: Hardness-Magnification Bridge Realization - cycle 51 direct-sum demagnification audit

Learning. Cycle 51 identifies a new quantitative conservation law: the same gap g_N that protects the target transfer against all SAT polynomial exponents becomes the per-slot lower-bound burden for any direct-sum source proof. Hence slot-wise SAT hardness cannot be the weak source; a valid route must prove aggregate H_N hardness or supply a nonrelativizing extraction theorem.

Pressure. This proves only a quarantine for factorized source certificates. It does not rule out a genuinely aggregate arbitrary-circuit lower bound for H_N or a nonrelativizing extraction theorem using real SAT structure.

Next. Try to formalize an aggregate lower-bound normal form for H_N that distinguishes global OR computation from M_N independent SAT_L copies, and test it against the planted-control oracle before using separator hardness.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0052: Hardness-Magnification Bridge Realization: XOR Carrier Repair

Learning. Cycle 52 contributes a concrete repair: XOR aggregation preserves the valid polylog-query magnification threshold while invalidating the OR-specific one-sided separator obstruction. The new source burden is sharper: prove aggregate parity-carrier hardness or rule out subthreshold parity sketches and sparse corrections. This is route-level progress only, with explicit falsifier tests.

Pressure. There is no nonrelativizing theorem extracting a parity sketch, low-rank transcript, or other analyzable normal form from an arbitrary small circuit for H_N^{oplus}; direct C(H_N^oplus)>N^{1+epsilon} remains unproved.

Next. In the ideal random-label model for G_N, count subthreshold affine sketches of size N^α and estimate the tau,alpha,error threshold at which a union bound could certify parity-sketch resistance without pretending to prove the actual explicit carrier lower bound.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c $\to$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0053: Hardness-Magnification Bridge Realization: XOR carrier affine-incidence audit

Learning. Cycle 53 converts the XOR repair into an exact affine-incidence conservation law. The carrier equals the F_2 inner product of the SAT label vector with a generated parity-incidence vector; low-dimensional computable incidence structure makes the carrier easy by hardwiring basis parities. This is a new concrete falsifier for the source lower bound, while the polylog-query target bridge remains valid.

Pressure. A small circuit for H_N^{oplus} computes only the scalar inner product ; it need not reveal p_x, a low-rank coordinate map, or any local SAT separator. The extraction is false in planted-label oracle worlds and would need real-SAT, nonrelativizing content.

Next. Instantiate $G_{N,\theta}$ with linear, pairwise-independent, and extractor-style query maps; compute K, coefficient-circuit cost A_N, duplicate parity cancellations, and whether any case survives the $N^{1+\epsilon}$ affine-sketch falsifier threshold.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c $\to$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0054: Hardness-Magnification Bridge Realization: XOR Carrier Approximate Affine-Sketch Gate

Learning. Cycle 54 strengthens the XOR route with an approximate piecewise-affine incidence-sketch conservation law. Bad seeds cost EN gates to patch, and a sketch of total cost s+Kr+EN below $N^{1+\epsilon}$ is a concrete falsifier for the source lower bound. High incidence rank alone is not valid lower-bound evidence because the SAT label functional may be simple on the generated image.

Pressure. Need a direct lower bound for the SAT-label pullback x $\rightarrow$, or a non-natural real-SAT theorem showing that every subthreshold H_N circuit induces a subthreshold approximate affine-incidence sketch. Current rank and sketch audits are only falsifiers.

Next. Instantiate the hash-based XOR generator and compute whether its incidence map has an explicit low-cost piecewise-affine cover; if none is found, formulate the exact extraction theorem needed to turn small H_N circuits into such covers.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0055: Hardness-Magnification Bridge Realization

Learning. Cycle 55 adds the SAT-preserving quotient normal form for XOR carriers. The valid target bridge is still $max\rho, q < 1+\epsilon$, but the source lower bound must beat quotient piecewise-affine incidence sketches, not raw range or rank. Symmetry-pair cancellation is a concrete falsifier that can make a high-entropy generator compute a constant carrier; this is route-level progress only, not a proof of P $\neq$ NP.

Pressure. Label-sensitive extraction gap: a small arbitrary circuit for the single function x → need not reveal a small quotient-incidence sketch, and high quotient rank alone does not preclude the SAT-labelled linear functional from being simple.

Next. Compute QSk_{sim,N}(E) for quotient relations generated by equality, variable renaming, clause permutation, tautological padding, and duplicate-pair involutions on the current high-q XOR carrier template; record the smallest residual exponent u and pairing-certificate cost.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c → c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0056: Hardness-Magnification Bridge Realization: XOR quotient codebook gate

Learning. Cycle 56 adds a sharper conservation law for XOR carriers: after SAT-preserving parity quotienting, H_N is easy whenever the incidence map has either low affine rank or a low-cardinality computable transcript, with patchable errors charged by EN. Thus high quotient entropy or high rank alone is not valid source evidence; the source obligation is a combined codebook-or-rank minimax lower bound, while the target bridge remains unchanged.

Pressure. The derivation does not show that every small arbitrary circuit for H_N yields such a quotient sketch. It is an upper-bound falsifier, not a lower-bound certificate.

Next. Instantiate a candidate high-q generator and compute the exponent of its SAT-preserving odd-support transcript range versus affine span rank; reject it if min{theta,rank-exponent}+locator-cost falls below 1+epsilon.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0057: Hardness-Magnification Bridge Realization: XOR quotient carrier, low-degree feature-sketch gate

Learning. Cycle 57 adds a nonlinear conservation law for the XOR carrier. The source lower bound must beat low-degree quotient-feature sketches with threshold $S_T + binom(r, \leq t) + EN$, so high rank or high codebook entropy is not valid evidence. The target-preserving bridge is unchanged, but the source obligation is narrower and more nonrelativizing.

Pressure. No method is known to prove that the real SAT-labelled quotient functional avoids all subthreshold low-degree feature sketches. Random-incidence or random-label counting does not transfer to SAT.

Next. Formalize the degree-2 case: characterize whether Tseitin-style parity, formula-size, variable-incidence, or clause-type features give $r = N^{\alpha}$ with $2alpha < 1 + \epsilon$ for the generated length-(log N)^d SAT queries.

When to stop. Stop or quarantine this meta-complexity carrier branch only after MCSP/MKtP parameters, truth-table length N, size threshold s, verifier overhead, target SAT-circuit use, and natural-proof or advice-leakage status have been computed; quarantine if the transfer still produces only a finite exponent window or relies on a dense natural property without an escape certificate.

Do not stop prematurely if. Do not stop before naming the carrier variant, deriving its verifier/reduction overhead, and checking whether a SAT $\in$ SIZE(n^c) assumption gives carrier circuits below the claimed source lower-bound threshold.

How it adds to the global problem. This move adds to the P vs NP problem because it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0058: Hardness-magnification bridge via XOR carriers and sparse quotient-polynomial falsifiers

Learning. Cycle 58 repairs the XOR-carrier audit: low degree was the wrong nonlinear measure. The valid upper-bound falsifier is sparse quotient-polynomial support with threshold $S_T + A_N$

$r_N + E_N\ N < N^{1+\epsilon}$. This preserves the polylog-query target bridge but narrows the source obligation and exposes a new extraction gap: sparse-sketch hardness is not yet general-circuit hardness.

Pressure. No valid derivation converts an arbitrary small H_N circuit into a charged sparse quotient-polynomial sketch. Without this extraction, sketch lower bounds are falsifier tests, not source lower bounds.

Next. Formalize the weakest nontrivial extraction candidate: restrict arbitrary H_N circuits to circuits whose wires are invariant under SAT-preserving quotient symmetries, and test whether such invariant circuits collapse to sparse quotient-polynomial sketches with subthreshold loss.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c $\rightarrow$ c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0059: Hardness-Magnification Bridge Realization: XOR carrier sparse-sketch audit

Learning. Cycle 59 identifies a conservation law for the XOR-carrier audit: unrestricted sparse quotient-polynomial hardness is not a simplification of the source lower bound, since $T = H_N$ is an admissible one-bit quotient transcript. The valid contribution is a sharper quarantine: sparse sketches remain concrete upper-bound falsifiers, while any proof-relevant sketch lower bound now needs a named label-free transcript class plus a nonrelativizing extraction theorem. The main P $\neq$ NP conjecture is untouched.

Pressure. No nonrelativizing locality-extraction theorem is known that converts an arbitrary small circuit for the real SAT-XOR carrier into a subthreshold label-free incidence transcript; relativizing planted-control examples block the naive argument.

Next. Formalize the local-linear incidence transcript class for the XOR SAT carrier and compute the minimum sparse F_2 support needed under a random-generator model, while auditing whether any extraction from arbitrary circuits to that class can avoid the planted-control relativization falsifier.

When to stop. Stop or quarantine this padding/projection branch only after the length map N(n), projection overhead, source lower-bound quantifier and target exponent window are calculated; quarantine if the route merely moves the P vs NP difficulty into sparse valid-length lower bounds.

Do not stop prematurely if. Do not stop before deriving the exponent transfer c → c/k or its growth-padding analogue, and before stating whether the result excludes all polynomial SAT exponents or only a bounded exponent interval.

How it adds to the global problem. This move adds to the P vs NP problem because it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0060: Constructive Label-Free Sketch Gate for XOR Magnification

Learning. Cycle 60 separates two notions previously conflated. Sparse quotient-polynomial sketches are valid upper-bound falsifiers only when the transcript is constructively label-free; otherwise $T_N = H_N$ collapses the audit. The target bridge $max\rho, q < 1+\epsilon$ survives, but sketch-hardness is not a source lower bound without a nonrelativizing extraction theorem or a direct C(H_N) lower bound.

Pressure. No theorem converts an arbitrary small circuit for the parity of SAT labels on generated queries into a constructively label-free low-support incidence sketch with subthreshold residual cost.

Next. Define the first concrete compiler class $T^{inc-lin}$: $T_N(x) = B_N$ a_N(x) for explicit SAT-preserving quotient matrices B_N of row sparsity polylog N, then compute the minimum $S_T + A_N$ r_N for representing H_N by sparse P_N in the high-q, $d = 2$ regime.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the

high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0061: Hardness-Magnification Bridge Realization

Learning. Cycle 61 upgrades the XOR-carrier audit from vague label-free transcripts to a costed global-codebook normal form. The valid new contribution is an explicit upper-bound falsifier $C(H_N) \leq S_T + S_D + \widetilde{O}(U_N + A_{Nr,N}) + E_{NN}$. This closes a leakage loophole in sparse quotient sketches, while exposing the exact remaining gap: absence of label-free sketches is not a general-circuit lower bound without a nonrelativizing extraction theorem.

Pressure. No extraction theorem converts arbitrary H_N circuits into constructively label-free codebook sketches. The trivial transcript $T_N = H_N$ is small whenever H_N is small but is not label-free and may encode SAT-label information semantically.

Next. Instantiate a candidate generator and compute U_N, A_N, r_N, E_N for its SAT-preserving quotient codebook; if the cost is subthreshold, quarantine that generator, otherwise formulate the exact extraction theorem it would require.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0062: Hardness-Magnification Bridge Realization

Learning. Cycle 62 adds a new fork: high incidence rank can make the XOR carrier lower-bound property large, so an efficient semantic certificate would be natural, while low rank is an upper-bound falsifier. The polylog $\beta = 0$ bridge remains valid, but the surviving source proof must be non-natural, non-large, proof-mediated, or direct.

Pressure. The derivation does not produce the actual source lower bound. It only says that high-rank, efficiently checkable, large certificates are barrier-exposed, while absence of label-free sketches is still not equivalent to arbitrary-circuit hardness without a nonrelativizing extraction theorem.

Next. Instantiate the random-affine generator with L=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute r_N for the induced sparse incidence matrix and test whether the rank gap forces naturalness or low-rank falsification.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0063: Hardness-Magnification Bridge Realization

Learning. Cycle 63 upgrades the rank-density fork into a quantitative gate: low constructive rank is a direct upper-bound falsifier, while high rank makes any efficient useful certificate large in label space. The $\beta = 0$ magnification bridge is still valid, but rank-only evidence is quarantined unless the source proof is direct or explicitly non-natural and nonrelativizing.

Pressure. The branch still lacks a direct non-natural lower bound for H_N^{SAT} or a nonrelativizing theorem extracting a label-free sketch from every small H_N circuit.

Next. Perform the finite prior-art boundary check for the label-space naturalness claim, then instantiate the thought experiment with a concrete pairwise-independent generator and compute r_N, quotient rank, and any row-coordinate decoder cost D_N.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0064: Hardness-Magnification Bridge Realization

Learning. Cycle 64 upgrades the XOR route from rank-density intuition to a fork theorem: low constructive incidence rank is an explicit upper-bound falsifier, while any large truth-table constructive anti-alignment proof for the SAT label pulls back through the valid $\beta = 0$ bridge to a natural property. The remaining source route must be direct, nonlarge, nonconstructive, proof-mediated, or explicitly nonrelativizing; this is route-level progress, not P $\neq$ NP.

Pressure. The route still lacks a nonlarge, nonconstructive, proof-mediated, or direct argument that the actual SAT label avoids the easy induced-XOR label set.

Next. Instantiate L_N=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute achievable M_N and r_N for an explicit generator family, then test for a label-free coordinate transcript or prove any proposed SAT anti-alignment certificate has density below $2^{-\omega(L_N)}$.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0065: Hardness-Magnification Bridge Realization

Learning. Cycle 65 closes a finite validation gap: short searchable proof certificates do not automatically escape natural proofs in the $\beta = 0$ XOR carrier. If they are large and sound, they form a valid natural property; if rank is low, there is a separate upper-bound falsifier. The surviving

route is narrower: direct H_N lower bounds or nonlarge, nonconstructive, explicitly nonrelativizing proof objects.

Pressure. The argument is conditional as a barrier diagnosis: it uses the standard PRF-based natural-proofs obstruction and does not rule out nonlarge SAT-specific proofs, $\omega(L_N) - length$ proofs, nonconstructive verifiers, or nonrelativizing proof-system semantics.

Next. Instantiate R_N with a named proof system, e.g. Extended Frege or IPS, and test whether an LB certificate for $C(H_{N,y}) > N^{1+\epsilon}$ has $O(L_N) - bit$ searchable descriptions, inverse-polynomial label density, and truth-table soundness; otherwise record the precise escape parameter.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0066: Hardness-Magnification Bridge Realization

Learning. Cycle 66 sharpens the proof-mediated XOR route: searchable certificates do not automatically trigger the standard natural-proofs barrier. The valid obstruction needs parametric soundness, constructivity, large pulled-back density, and a density-preserving label-realization map. Without these, the barrier claim is invalid, but the source proof must be direct, nonlarge, nonconstructive, or explicitly nonrelativizing.

Pressure. No explicit density-preserving label-realization map is known for the generated SAT universe U_N, and soundness of plausible proof predicates is usually shown only for the actual SAT label rather than for every artificial label y.

Next. Instantiate R_n for one high-q polylog XOR carrier or prove a finite impossibility: no label-free density-preserving realization can coexist with $q, \rho < 1 + \epsilon$ and generator universe U_N of SAT formulas length (log N)^2.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the high-q generated-OR carrier, compute the exact leakage exponent of the remaining witness-cover or unary-residual mechanism and compare it with 1+epsilon-q.

cycle-0067: Hardness-Magnification Bridge Realization

Learning. Cycle 67 upgrades the previous label-realization warning into an exact restriction-extension theorem. For $\beta = 0$ XOR carriers, dense constructive label-mediated source lower bounds naturalize automatically when U_N is uniformly enumerable and soundness is in the same circuit model. The valid bridge survives, but any proof-mediated route must now be direct, nonlarge, nonconstructive, or explicitly nonrelativizing; ambient source-property largeness is not enough because density must be image-relative.

Pressure. No lower bound for C(H_N) is proved. The derivation only certifies that one dense constructive label-mediated proof shape would collide with natural-proofs methodology, while image-relative and nonlarge certificates remain open.

Next. Instantiate U_N for one explicit polylog-query XOR generator, compute whether U_N is enumerable in poly(2^L), and classify a candidate certificate as dense-label, image-relative, or nonlarge.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move

proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0068: Hardness-Magnification Bridge Realization

Learning. Cycle 68 separates two notions previously conflated: label-mediated certificates for the $\beta = 0$ XOR carrier are large inside the realization image, but the image has ambient density at most 2^{-2^N+2^{o(N)}}. Thus the valid bridge to SAT $\notin$ P/poly survives, while the standard natural-proofs barrier requires a separate constructive ambient extension; this is a sharper route-status theorem, not progress on the main conjecture itself.

Pressure. No direct lower bound for the real SAT-label carrier H_N is obtained, and no polynomial-time density-preserving extension from Im(R_N) to ambient N-bit truth tables is known.

Next. Formalize the extension problem: given R_N and a sound searchable label certificate, prove either that no poly(N)-time ambient extension of density $2^{-\mathrm{poly}(N)}$ exists for this certificate class, or that such an extension exists and therefore naturalizes the route.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0069: Hardness-Magnification Bridge Realization

Learning. Cycle 69 turns the image-density ambiguity into a precise threshold theorem. A label-mediated $\beta = 0$ XOR certificate naturalizes through restriction to U_N exactly when its label density is at least $2^{-\mathrm{poly}(L)}$ and its verifier is $2^{O(L)} - \textit{constructive}$. The earlier ambient-tiny source image is not by itself a valid escape; the real escapes are nonlarge density, nonconstructivity, advice leakage, or explicitly nonrelativizing direct lower bounds.

Pressure. No construction is given of a P_N that accepts SAT$|U_N$ while remaining sound; the derivation only classifies when such a proof-mediated route would naturalize.

Next. Instantiate U_N with L=(log N)^2 and q in ((1+epsilon)/2,1+epsilon); compute whether candidate proof systems give certificate density above $2^{-\mathrm{poly}(L)}$ or force a nonlarge escape, then run the prior-art boundary check.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0070: Hardness-Magnification Bridge Realization

Learning. Cycle 70 corrects the naturalness gate for the $\beta = 0$ XOR route. A dense label certificate cylinder-extends to a valid classical natural property exactly at density $2^{-O(L)}$ with $2^{O(L)}$ constructivity; source-image ambient sparsity is irrelevant after restriction. The real escapes are nonlarge density below the classical cutoff, nonconstructivity, advice leakage, or a direct nonrelativizing H_N lower bound.

Pressure. This does not prove that such Q_N exists, and it does not turn sparse or nonconstructive certificates into barriers. It only gives a valid no-go for dense, constructive, same-model label certificates.

Next. Instantiate the density-tier audit on a toy proof-certificate family: certificates describing affine anti-alignment witnesses over U_N. Compute $delta_N$, verifier time, and whether soundness reaches arbitrary $C_N(H_y) > N^{1+\epsilon}$ or only sketch hardness.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0071: Hardness-Magnification Bridge Realization

Learning. Cycle 71 upgrades the $\beta = 0$ XOR naturalness audit: density alone is not the decisive condition. Dense searchable certificates naturalize only when their soundness is functional over arbitrary label vectors. Therefore the surviving proof-mediated route must be sparse, nonconstructive, SAT-semantic/nonrelativizing, advice-free in a stronger sense, or a direct H_N lower bound.

Pressure. This derivation needs functional soundness for all label vectors and a real accepted-label density estimate. SAT-only certificates and nonlarge accepted sets are outside the no-go.

Next. Instantiate V_N with one concrete proof-system or MCSP-style certificate, compute $kappa_N$ for accepted labels, and decide whether soundness is functional over arbitrary y or essentially SAT-semantic.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0072: Hardness-Magnification Bridge Realization

Learning. Cycle 72 upgrades the $\beta = 0$ XOR route from a vague naturalness warning to a dichotomy: dense functional searchable certificates become valid natural properties, while nonfunc-

tional proof objects must pass an explicit row-selection leakage audit. The target bridge survives, but the source proof space is narrowed to sparse, nonconstructive, SAT-semantic nonrelativizing, or direct H_N lower bounds.

Pressure. No theorem yet converts SAT-semantic, nonrelativizing certificates into functional certificates or into charged row-selection transcripts. That is the exact remaining gap, not a proof of P $\neq$ NP.

Next. Instantiate the selected-probe audit for one named proof-system candidate: require $q = 1+\epsilon/2$, $\rho = 1+\epsilon/3$, L=(log N)^2, then compute whether its certificates force $A_N+S_N+R_N+E_{NN}$ or $A_N + S_N + K^c_{NL} + E_{NN}$ below $N^{1+\epsilon}$.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0073: Hardness-Magnification Bridge Realization

Learning. Cycle 73 adds a concrete row-deletion residual threshold to the surviving $\beta = 0$ XOR magnification route. A claimed $N^{1+\epsilon}$ source lower bound is invalid if the carrier has a subthreshold circuit wrong on fewer than $N^{\epsilon-o(1)}$ source rows, because equality patching costs O(E_N N). Thus a proof-mediated nonfunctional escape from natural proofs must be robust against sparse-row leakage; this is route-level progress, not a P vs NP proof.

Pressure. No theorem yet converts an arbitrary SAT-semantic nonfunctional certificate into either a functional natural property or a sparse-row residual circuit. The row gate is a necessary falsifier audit, not a complete proof-system lower-bound framework.

Next. Instantiate a named proof system Psys for $\beta = 0$ XOR certificates and test whether any accepted SAT-semantic certificate can be transformed into either a functional label property or a residual circuit wrong on fewer than $N^{\epsilon-o(1)}$ rows.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0074: Hardness-Magnification Bridge Realization: beta-zero XOR row-residual audit

Learning. Cycle 74 upgrades the focus packet: the beta-zero XOR bridge and row-residual patching bound are theorem-shaped and valid under explicit batched-generator assumptions. The live obstruction is now narrower: prove an EF + SAT_U semantic extraction/no-extraction theorem, or quarantine proof-mediated certificates that cannot certify residual robustness.

Pressure. No proof-analysis theorem currently forces a semantic EF + SAT_U certificate either to functionalize over all label tables or to localize its nonfunctionality to fewer than $N^{\epsilon - o(1)}$ source rows. EF may use global SAT structure shared by many rows through the same formula labels.

Next. Formalize EF+SAT_U syntax with label table U_N, prove the functional dense naturalization lemma cleanly, then attempt a finite extraction theorem: every nonfunctional accepted proof either identifies a row set R_N and approximator D_N or uses a nonrelativizing SAT principle outside the row-residual audit.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0075: Hardness-Magnification Bridge Realization

Learning. Cycle 75 turns the Psys gap into a precise EF + SAT_U audit. Ordinary semantic soundness is insufficient: a valid proof-mediated beta-zero XOR route must either be nonlarge/nonconstructive/direct or certify row-residual robustness against subthreshold patching.

Pressure. No theorem yet extracts row-residual robustness from short EF + SAT_U semantic proofs, and no construction yet proves such extraction impossible.

Next. Instantiate EF + SAT_U proofs as circuits over SAT_U label atoms, define functionalization formally, and try to construct a $\theta < \epsilon$ residual-leaky transcript or prove extraction to the robustness gate.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0076: Hardness-Magnification Bridge Realization

Learning. Cycle 76 closes the Psys instantiation to EF + SAT_U and isolates the exact missing certificate strength: ordinary SAT-semantic soundness is not valid evidence unless it proves row-residual robustness above the patching threshold.

Pressure. No extraction/no-extraction theorem yet maps short EF + SAT_U proofs to functional label properties or to row-residual robustness against all subthreshold D_N.

Next. Formalize Robust_N(s,e) for EF + SAT_U and test whether a short proof can remain sound after replacing H_N by D_N off a sparse row set.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0077: Hardness-Magnification Bridge Realization

Learning. Cycle 77 sharpens the EF + SAT_U packet: direct lower-bound certificates automatically pass the explicit row-residual audit, so the real gap is not patching but semantic extraction. A new occurrence-oracle row-touch no-go gives a concrete falsifier for relativizing local certificate methods and leaves only SAT-semantic nonrelativizing, nonlarge/nonconstructive, or direct routes alive.

Pressure. No theorem yet shows that actual EF + SAT_U certificates for the intended SAT_U carrier either reduce to the row-touch occurrence-local model or yield a nonrelativizing extraction from certificate acceptance to LB_N(T_N).

Next. Instantiate Touch(Pi) for a concrete EF + SAT_U encoding of circuit lower-bound certificates: count whether proofs of size N^k can mention $sub{-}N^\epsilon$ rows, and test if formula-equality/SAT-realization axioms break the occurrence-oracle extension.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem.

The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0078: Hardness-Magnification Bridge Realization

Learning. Cycle 78 converts the row-residual audit into a theorem-shaped no-go: functional row-local certificates for the beta-zero XOR carrier require $N^{\epsilon-o(1)}$ touched rows at source threshold $N^{1+\epsilon-o(1)}$. This sharpens the EF + SAT_U obstruction from ordinary soundness to a concrete extraction fork: either the proof is direct or nonlarge/nonconstructive, or it must use real SAT semantics in a nonrelativizing way that defeats the private-row falsifier.

Pressure. The derivation is complete only for functional row-value certificates. EF + SAT_U proofs are SAT-semantic over formula labels, so a nonrelativizing extraction theorem or a private-row no-go formalization is still needed.

Next. Instantiate EF + SAT_U row occurrence access formally: define the touched-row set of a proof verifier, test whether standard EF reflection over SAT_U extracts to row-value functionality, and if not construct the private-row oracle countermodel as a finite theorem.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0079: Hardness-Magnification Bridge Realization: beta-zero XOR row-forcing audit

Learning. Cycle 79 replaces vague SAT-semantic escape language by the full-row-forcing parameter ForcedRows(Q). A proof-mediated beta-zero XOR certificate that treats generated SAT instances as occurrence labels must force at least $N^{\epsilon-o(1)}$ complete parity rows; otherwise a private occurrence-label spoof gives a subthreshold sparse-row circuit. The valid contribution is a scoped no-go and an exact extraction obligation for full EF + SAT_U, not progress on the main conjecture itself.

Pressure. The derivation is a proof only for EF + SAT_U^{occ} or functional label-local certificates. Full EF + SAT_U may use real formula syntax to constrain unmentioned generated instances, so an extraction theorem for Q_{pi} or a nonrelativizing semantic certificate is still missing.

Next. Instantiate Psys = EF+SAT_U^{occ}: define the proof parser that extracts Q_{pi}, prove acceptance transcript invariance under A_Q, and compute whether known EF encodings force full rows or merely individual generated formula occurrences.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0080: Hardness-Magnification Bridge Realization

Learning. Cycle 80 discharges the scoped EF + SAT_U^{occ} proof packet: occurrence-local functional certificates for the beta-zero XOR carrier must force at least $N^{\epsilon-o(1)}$ complete parity rows, or a private occurrence-label spoof plus sparse-row equality patch gives a valid subthreshold falsifier. The live gap is no longer ordinary soundness; it is the full EF + SAT_U extraction of real SAT-semantic reasoning into syntactic *ForcedRows*, or a deliberate restriction of the paper theorem to EF + SAT_U^{occ}.

Pressure. The derivation is valid for EF + SAT_U^{occ}. It is blocked for full EF + SAT_U by the missing extraction lemma from real SAT semantic derivations to syntactic row forcing; full EF may use formula structure in a nonrelativizing way that private occurrence-label spoofing does not preserve.

Next. Attempt the full EF + SAT_U boundary lemma: inspect a standard encoding of SAT_U extension axioms and decide whether each semantic rule is occurrence-local, charges enough advice into S_Q, or yields a nonrelativizing complete-row extraction.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive

β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0081: Hardness-Magnification Bridge Realization

Learning. Cycle 81 separates the scoped occurrence-local theorem from the full EF + SAT_U ambition. The valid contribution is now sharper: private row spoofing is a genuine falsifier for occurrence-local functional certificates, while full EF + SAT_U requires a nonrelativizing semantic-to-occurrence extraction theorem because real SAT_U axioms are not invariant under independent label flips.

Pressure. Semantic-to-occurrence shadow extraction: no proof currently shows that full EF + SAT_U reasoning about actual SAT formulas can be converted into a functional occurrence-local Q_{pi} with subthreshold row residual and $N^{o(1)}$ overhead.

Next. Formalize the semantic-coupling-width thought experiment as a lemma: for paired formulas F and F OR z, show exactly which SAT_U implication lines break private-label invariance and whether their violations can be charged to complete forced rows below the N^{ϵ} patch threshold.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state

the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0082: Hardness-Magnification Bridge Realization

Learning. Cycle 82 upgrades the proof-delivery packet by isolating a row-normal parser theorem: occurrence-local functional certificates are valid only if they force $N^{\epsilon-o(1)}$ complete rows. The remaining gap is exactly full EF + SAT_U semantic-to-occurrence extraction.

Pressure. The derivation is valid for row-normal occurrence-local transcripts; full EF + SAT_U may use real SAT syntax to create nonrelativizing dependencies not represented by Q_{pi}.

Next. Construct the smallest EF extension-rule countermodel that hides row parity without a row-normal node, or prove a normalization that exposes such parity with subthreshold overhead.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0083: Hardness-Magnification Bridge Realization

Learning. Cycle 83 upgrades the proof-delivery packet from a parser slogan to a conditional theorem: row-separable row-normal functional occurrence certificates must force $N^{\epsilon-o(1)}$ complete XOR rows, or private occurrence-label spoofing yields a valid subthreshold circuit for the induced carrier. The remaining open obligation is no longer ordinary soundness but the exact row-normalization/extraction step for broader EF + SAT_U.

Pressure. The proof is conditional on a row-separable row-normal parser. Arbitrary full EF + SAT_U can use real formula semantics, and arbitrary occurrence-local EF may contain short cross-row parity constraints unless the calculus forbids or charges them.

Next. Instantiate the EF + $\mathrm{SAT}_U^{occ,row}$ rule ledger: for each extension, weakening, substitution, SAT_U occurrence axiom, and derived parity line, mark whether it is $Q_{pi} - local$, row-separable, or a charged cross-row constraint; the first uncharged cross-row rule becomes the countermodel or repair target.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0084: Hardness-Magnification Bridge Realization

Learning. Cycle 84 turns the *ForcedRows* packet into a proof-shaped conditional theorem: row-normal occurrence-local functional certificates must force $N^{\epsilon-o(1)}$ complete XOR rows, because otherwise private label spoofing plus sparse equality patching is a valid falsifier. The remaining gap is exactly semantic-to-occurrence extraction for full EF + SAT_U, not ordinary soundness or generic natural-proofs folklore.

Pressure. The derivation is complete only for row-normal occurrence-local functional certificates. Full EF + SAT_U remains blocked at semantic-to-occurrence extraction because SAT_U axioms can couple labels through real formula syntax and witnesses, so private occurrence-label spoofs may not preserve acceptance.

Next. Audit one standard full EF + SAT_U encoding rule: attempt to extract its occurrence-label dependency into Q_{pi} preserving $A_Q - \mathit{invariance}$; if a witness or clause-soundness axiom breaks invariance, record the minimal rule-level countermodel and restrict the theorem statement to EF + $\mathrm{SAT}_U^{occ,rn}$.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0085: Hardness-Magnification Bridge Realization

Learning. Cycle 85 sharpens the formula-semantic extraction fork: full occurrence parsing is false already for EF + $SATeq_N$ because EqSAT padding identities are real SAT-semantic and nonrelativizing. The valid repair is a semantic-link trichotomy: nonfunctional certificates must pay either occurrence full rows or EqSAT-linked rows at the $N^{\epsilon-o(1)}$ threshold, otherwise sparse-row residual patching falsifies the source lower-bound certificate.

Pressure. The derivation is complete only for EF + $SATeq_N$ where all SAT semantics factors through EqSAT links. It does not yet cover full EF + SAT_U with witness, self-reduction, or minimization rules unless those rules are decomposed into label-functional inferences plus row-chargeable semantic links.

Next. Attempt the finite EF + $SATeq_N$ parser proof: formalize proof lines as Boolean circuits over SAT-atoms, prove label-functionality for EF rules, charge every EqSAT endpoint to SemRows, and test whether SAT self-reduction axioms in full EF + SAT_U admit the same charge or force a new semantic-escape lemma.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0086: Hardness-Magnification Bridge Realization

Learning. Cycle 86 resolves one part of the formula-semantic fork: occurrence-only extraction is false for EF + $SATeq_N$ because real EqSAT identities are nonrelativizing semantic links. The

valid replacement object is a semantic-link residual transcript; subthreshold link coverage is a falsifier for source lower-bound certificates, while the open proof task is a normal form for arbitrary EF + $SATeq_N$ reasoning.

Pressure. The normal form is not proved for arbitrary EF reasoning that invokes SAT self-reducibility, extension variables encoding witnesses, or nonlocal formula transformations not decomposed into explicit EqSAT links.

Next. Work the EF + $SATeq_N$ normal-form proof rule by rule: padding, renaming, duplicate clauses, extension-variable abbreviations, and SAT self-reduction; either translate each into a bounded EqSAT-link transcript or isolate the first noncompressible SAT-semantic principle as the next theorem-shaped counterexample.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0087: Hardness-Magnification Bridge Realization

Learning. Cycle 87 replaces the vague semantic-link normal-form obligation by an exact residual-code invariant: after EqSAT quotienting, a proof-mediated certificate that is functional over quotient labels is valid only if its touched-label coset has row-parity distance at least $N^{\epsilon-o(1)}$. Low quotient-code distance is a concrete falsifier; arbitrary EF + $SATeq_N$ remains open because it may use genuinely SAT-semantic nonrelativizing principles outside the quotient parser.

Pressure. The derivation does not produce a normal form for arbitrary EF+$SATeq_N$ proofs. Full EF can use nonrelativizing SAT-semantic principles, formula self-reductions, and derived equality chains whose acceptance is not a predicate over a bounded W,E quotient transcript.

Next. Instantiate the padded-copy EqSAT quotient family E_k, compute the row-incidence matrix A_E, and decide whether its constrained cosets have low-weight representatives below N^{ϵ} or certify a valid semantic-link residual lower bound.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0088: Hardness-Magnification Bridge Realization

Learning. Cycle 88 identifies the first concrete SAT-semantic escape from the EqSAT quotient parser: self-reduction OR constraints are not invariant under quotient-label spoofing. The valid paper move is not another magnification slogan but a trichotomy repair: equality-only proofs use quotient residual codes, occurrence expansions pay row-forcing cost, and SR proofs require a constrained residual-code audit. Low constrained row distance is a falsifier for source certificates; no main P $\neq$ NP claim is made.

Pressure. The derivation does not normalize arbitrary EF + SAT_U or arbitrary SAT-semantic reasoning to EqSAT+SR constraints. A stronger proof may use search-to-decision, Cook-Levin witness encodings, or formula minimization principles not represented by the finite SR hypergraph K_{pi}.

Next. Instantiate K_{pi} for local one-step SR only: bound $|K_{pi}|$ by proof size, define its row-parity constraint-distance $Delta_K$, and test whether $Delta_K$ can be reduced to a known SAT promise-hardness statement or whether it is target-equivalent to the desired H_N lower bound.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0089: Hardness-Magnification Bridge Realization

Learning. The cycle upgrades the SR semantic escape into a quantitative constrained-distance invariant. Occurrence spoofing is invalid after SR constraints, but any bounded-SR parser still faces the same row-patching threshold. Progress is route-level certification, not a P vs NP proof.

Pressure. The missing proof is semantic-to-residual parsing for full EF + $SATeq + SR_h$; SR OR clauses couple labels across restrictions, so independent occurrence-label spoofing is not valid.

Next. Fix h with 2^h=N^{eta}; formalize $Delta_{SR,h}$ for the generated formula closure and try to prove the parser for EF + $SATeq + SR_h$ restricted to extension variables naming only quotient labels and SR clauses.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the MCSP/MKtP row branch, decide whether the certificate proves direct row hardness or only aggregate/rank-index hardness; record q_extract=epsilon/(1+D) and q_force=(D+epsilon)/(1+D) in the same parameter regime.

cycle-0090: Hardness-Magnification Bridge Realization

Learning. Cycle 90 converts the SR semantic escape into a costed leaf-solver falsifier: bounded self-reduction depth is not free, but if $q + \eta + \tau < 1 + \epsilon$ and the induced row error is below N^{ϵ} then the source lower bound collapses by equality patching. The live inference-quality packet is now theorem-shaped for Psys_h; the only remaining full-system gap is the advice-free parser normal form for arbitrary EF extension variables.

Pressure. ParserNormalForm(EF+EqSAT+SR_h): prove that every short proof of LB(H_N^{SAT}) either gives a dense functional label property, an occurrence/full-row transcript, or a bounded-SR residual code with advice-free size bound poly(|pi|,L_N).

Next. Build the minimal $\mathrm{EF} + \mathrm{EqSAT} + SR_1$ parser countermodel: allow one extension variable Z(F)=SAT(F_0) OR SAT(F_1) and test whether it is representable by the SR DAG without advice; if yes, increase to two nested extensions, if no, use it as the semantic escape separating full EF from Psys_h.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0091: Hardness-Magnification Bridge Realization: beta-zero XOR formula-semantic parser audit

Learning. Cycle 91 upgrades the bounded-SR leaf-solver audit by adding an explicit EF extension-support charge and proving a no-go for extension-blind parsers. The valid theorem is restricted but contribution-shaped: subthreshold charged transcripts are upper-bound falsifiers, while arbitrary EF+SAT remains blocked at a precise advice-free normal-form lemma.

Pressure. Prove or refute the advice-free extension-support normal form for arbitrary EF extension variables in EF+EqSAT+bounded-SR; the known derivation only handles proofs whose extension dependencies are syntactically charged.

Next. Instantiate $\mathrm{Psys}^{schema}_{h,Ext}$: EF+EqSAT+depth-h SR with extension definitions generated by row-oblivious schemas. Try to prove ExtSupp(NF(pi))<=poly(|pi|), or construct a minimal non-relativizing SAT-semantic extension that defeats this normal form.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive

β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0092: Hardness-Magnification Bridge Realization

Learning. Cycle 92 turns the formula-semantic fork into a sharper proof packet. For support-declared EF+SATeq+bounded-SR, subthreshold parsed support plus bounded leaf solving and sparse residual rows gives a valid small-circuit falsifier for LB_N. The full EF+SAT claim is not proved; the precise remaining obstruction is NSP_N, the advice-free extraction of arbitrary extension-variable reasoning into charged row supports and SR leaves. This is route-level certification, not progress on the main P $\neq$ NP conjecture itself.

Pressure. NSP_N: every short arbitrary EF+SATeq+SR proof of LB_N must admit a support-complete, advice-free transcript with row distance and leaf-solver costs small enough to preserve the $N^{1+\epsilon}$ threshold. This is unproved and may fail for extension-compressed SAT-semantic reasoning.

Next. Try to prove NSP_N for the fragment EF+SATeq+SR whose extension definitions are row-affine and support-monotone; if the proof fails, extract the minimal extension rule that creates uncharged SAT-semantic support and state the final theorem scope around Psys_h^{supp}.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route,

state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0093: Hardness-Magnification Bridge Realization

Learning. Cycle 93 upgrades the formula-semantic extraction fork by naming NSP_N as a support-transparency lemma for unrestricted EF extension variables and proving the conditional transcript falsifier around it. The valid restricted contribution is support-declared EF + $SATeq$ + $bounded - SR_h$: any subthreshold parsed transcript collapses LB_N by a small circuit plus sparse-row patching. The full EF+SAT claim remains blocked exactly at advice-free extraction of extension-variable support, not at generic soundness or barrier folklore.

Pressure. NSP_N: an advice-free normal-support parser for unrestricted EF + $SATeq$ + SR_h extension variables. The missing lemma must extract charged row supports and bounded-SR leaves from arbitrary extension definitions without SAT-label advice and without solving a target-equivalent semantic support problem.

Next. Attempt an explicit NSP_N countermodel for unrestricted EF extension variables: construct a small row-mask extension family e_R, prove that occurrence-only parsing misses its support, and decide whether support transparency can be repaired by charging C(Supp(e_R)) without making the parser target-equivalent.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0094: Hardness-Magnification Bridge Realization

Learning. Cycle 94 closes a concrete support-transparency subcase: bit-explicit EF extension variables can be parsed without support declarations, giving a valid transcript falsifier theorem. The full formula-semantic extraction fork is now sharper: the obstruction is not arbitrary EF extension variables but succinct FormulaEval-SAT comprehension, which defeats size-only occurrence parsing unless its row-index expansion is charged.

Pressure. NSP_{sym}: an advice-free parser for succinct formula-indexed SAT atoms must either expand $N^{1+q+o(1)}$ concrete row-index labels or prove a new semantic-support theorem that remains completion-sound without occurrence expansion.

Next. Formalize Psys_{sym} on finite length N: specify whether FormulaEval-SAT comprehension is a proof line, axiom schema, or extension rule; then prove either an expansion-charge parser with cost $N^{1+q+o(1)}$ or a minimal countermodel showing surface occurrence completion is unsound.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0095: Hardness-Magnification Bridge Realization: bit-explicit parser and FormulaEval boundary

Learning. Cycle 95 upgrades cycle 94 from a parser slogan to a restricted theorem packet: Psys_{bEF} proofs with bit-explicit EF support have a valid charged transcript and a concrete LB_N falsifier inequality. The surviving strong-system gap is exactly symbolic FormulaEval-SAT: row expansion costs $N^{1+q-o(1)}$, while free symbolic comprehension has a private-row countermodel to surface occurrence completion.

Pressure. The remaining named gap is $FE_{expand,N}$: prove that any sound use of symbolic FormulaEval-SAT either expands to Omega(N^{1+q-o(1)}) row charge or is explicitly outside the parser model as a semantic oracle. Psys_{bEF} itself is not blocked under the stated bit-explicit assumptions.

Next. Instantiate $FE_{expand,N}$ on the smallest symbolic FormulaEval-SAT rule: one generator circuit G_N(x,j), one asserted vector y_j=SAT(G_N(x,j)), and α row instantiations. Prove the private-row countermodel for $\alpha < q$ and the $N^{1+q-o(1)}$ expansion charge for $\alpha = q$.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0096: Hardness-Magnification Bridge Realization

Learning. Cycle 96 closes a sharper proof-delivery subgoal: Psys_{bEF} parsing survives bit-level audit, and Psys_{sym} FormulaEval-SAT has a precise expansion-or-countermodel boundary. The new contribution is not a P $\neq$ NP advance; it is a valid route-level theorem/countermodel packet showing that symbolic formula evaluation either pays $N^{1+q+o(1)}$ row expansion or must be treated as a semantic-oracle escape outside surface occurrence parsing.

Pressure. $\mathit{SemanticForcing}_{FE}$ remains open: a real-SAT FormulaEval semantic oracle might force private row labels by nonrelativizing reasoning not recoverable from occurrence syntax. The branch now treats that as a named semantic-oracle escape, not as a valid Psys_{bEF} parser step.

Next. Fix one concrete Psys_{sym} syntax: FormulaEval-SAT as either an axiom schema over A(i,j,u), an EF extension rule producing formula bits, a proof line with explicit D_u, or a semantic oracle. For that syntax, prove the expansion parser or instantiate the minimal private-row countermodel with the smallest pi, one unexpanded pair (i*,j*), and a verified Γ_{sym} inequality.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0097: Hardness-Magnification Bridge Realization

Learning. Cycle 97 closes the support-density subgoal for the Psys_{bEF} packet: FormulaEval support must have absolute size $N^{\epsilon-o(1)}$, hence density $N^{\epsilon-q-o(1)}$ inside $M_N = N^{q+o(1)}$ slots. This yields a sharp q-trichotomy and upgrades the FormulaEval boundary to an expansion-or-private-row-countermodel test. The result is a valid route-level falsifier theorem, not evidence for P $\neq$ NP.

Pressure. The derivation does not prove a parser theorem for Psys_{sym} when FormulaEval-SAT is a genuine semantic oracle; the named missing lemma is FormulaEval-forcing: real SAT semantics must force every unexpanded row/slot value from the charged transcript with subthreshold overhead.

Next. Instantiate Psys_{sym} in two concrete variants: FormulaEval as an EF extension rule with row-index bits and FormulaEval as a semantic oracle. For each, compute K_idx(pi), X_FE(K), and whether the private-row countermodel survives SATeq and bounded-SR constraints.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0098: Hardness-Magnification Bridge Realization

Learning. Cycle 98 upgrades the prior packet from theorem slogan to dependency-checked inference structure: Γ_{bEF} is justified by separate EF-dependency, SATeq-link, bounded-SR, and sparse-row charges; Psys_{bEF} gives a valid restricted falsifier theorem; full Psys_{sym} is blocked exactly at $FE_{Extract,N}$, not at generic naturalness or relativization folklore.

Pressure. The restricted Psys_{bEF} theorem is derivation-complete at proof-packet level, but the full Psys_{sym} extension remains blocked at $FE_{Extract,N}$: an advice-free theorem converting semantic FormulaEval-SAT comprehension into charged occurrence rows without paying $N^{1+q+o(1)}$ or admitting the private-row countermodel.

Next. Write the formal $FE_{Extract,N}$ proposition in two columns: left column row-expanded FormulaEval axiom schema with $N^{1+q+o(1)}$ charge, right column semantic-oracle version with the smallest private-row countermodel; verify which column matches each Psys_{sym} rule.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0099: Hardness-Magnification Bridge Realization

Learning. Cycle 99 converts the remaining Psys_{sym} ambiguity into a sharper theorem/countermodel fork. FormulaEval-SAT cannot be treated as a free occurrence-completion rule: an expanded schema pays $N^{1+q+o(1)}$ row-slot charge, while an unexpanded symbolic line has a private-row falsifier unless a nonrelativizing $FE_{Extract,N}$ theorem is supplied. The valid contribution is a scoped parser-boundary packet, not evidence for P $\neq$ NP.

Pressure. The derivation does not rule out a real-SAT-specific, nonrelativizing $FE_{Extract,N}$ theorem showing that true formula evaluation semantics force the missing labels without row-slot expansion. It only proves the surface-occurrence parser no-go and the expansion charge for explicit schemas.

Next. Write the formal $FE_{Extract,N}$ blocked-lemma proof: define the quotient-label model after $SATeq/SR_h$ closure, prove the unmentioned row-slot existence bound, construct the two assignments Y,Y', and verify that the carrier row parity changes while the parsed transcript remains identical.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0100: Hardness-Magnification Bridge Realization

Learning. Cycle 100 isolates the $bounded - SR_h$ normal form at bit level: SR contributes exactly B_SR(pi) to Γ_{bEF} for Psys^{-}_{bEF}. The remaining full-system obstruction is not generic soundness but $FE_{Extract,N}$ for symbolic FormulaEval rows.

Pressure. The derivation is valid only for Psys^{-}_{bEF}. Full Psys_{sym} remains blocked at $FE_{Extract,N}$: a symbolic FormulaEval-SAT line may select rows without exposing K_idx(pi) or Nbr(j,u).

Next. Prove $RowSetEnumerator_N$ for an interval-union or AC0 FormulaEval selector and compute alpha-charge; if enumeration fails, emit the minimal private-row countermodel.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0101: Hardness-Magnification Bridge Realization

Learning. Cycle 101 upgrades $bounded - SR_h$ from a named cost to a bit-normal restricted parser theorem: SR contributes $B_{SR}(pi) \leq N^{q+\eta+\tau+o(1)}$ to Γ_{bEF}. The remaining live obstruction is exactly $FE_{Extract,N}$ for symbolic FormulaEval rows.

Pressure. The induction excludes symbolic FormulaEval-SAT; $FE_{Extract,N}$ is still needed to enumerate RowSet(a) or force the $N^{1+q+o(1)}$ expansion charge.

Next. Write the finite verifier table for one SR_h rule: tag layout, row j encoding, node/depth fields, parent pointers, occurrence-neighborhood list, and the exact charge contributing to B_SR(pi).

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0102: Hardness-Magnification Bridge Realization - cycle 102 SR_h normal form audit

Learning. Cycle 102 upgrades the $bounded - SR_h$ subgoal from an exponent slogan to a parser theorem for the explicit rule schema: SR_h contributes exactly B_SR(pi) to Γ_{bEF}, and the line induction gives a valid restricted LB_N falsifier. The remaining full-system issue is sharply isolated as $FE_{Extract,N}$ for symbolic FormulaEval-SAT, not generic naturalness, relativization, or P vs NP itself.

Pressure. No blocking gap remains for the restricted SR_h^{bit} normal form and line-induction packet. The full Psys_{sym} theorem is blocked at $FE_{Extract,N}$ or $RowSetEnumerator_N$ for symbolic FormulaEval-SAT.

Next. Instantiate $RowSetEnumerator_N$ for one transparent $\mathrm{Psys}^{sel}_{sym}$ fragment, preferably interval-union or AC0 row selectors, and decide whether FormulaEval-SAT is an expanded axiom schema with $N^{1+q+o(1)}$ charge or a semantic oracle exposed by the private-row falsifier.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0103: Hardness-Magnification Bridge Realization

Learning. Cycle 103 discharges a concrete FormulaEval subcase: transparent interval-union selectors admit a valid $FE_{Extract,N}$ parser with N|RowSet| expansion charge, so global FormulaEval costs $N^{1+q+o(1)}$ and yields the q/epsilon support trichotomy. The full Psys_{sym} claim remains quarantined exactly at semantic FormulaEval extraction; unexpanded symbolic FormulaEval is refuted by the private-row falsifier, not by generic barrier folklore.

Pressure. The derivation does not prove $FE_{Extract,N}$ for arbitrary Psys_{sym} selectors or for real FormulaEval-SAT comprehension whose row set is defined by semantic SAT facts rather than displayed interval endpoints.

Next. Extend $RowSetEnumerator_N$ from interval-union selectors to a named AC0 selector fragment by full scanning over [M_N]; compute whether scan overhead $N^{q+o(1)}$ is dominated by N|RowSet| and identify the smallest $\mathrm{AC0} - private - row$ countermodel if enumeration depends on semantic advice.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from $\mathrm{SAT} \in \mathrm{SIZE}(n^c)$ to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0104: Hardness-Magnification Bridge Realization

Learning. Cycle 104 pins the $bounded - SR_h$ normal form to concrete verifier fields rather than an exponent slogan. The restricted Psys^{-}_{bEF} plus interval-union FormulaEval theorem packet is now valid as a paper-level parser/falsifier result, while full semantic FormulaEval remains quarantined at $FE_{Extract,N}$ by a private-row countermodel.

Pressure. Full Psys_{sym} remains blocked exactly at $FE_{Extract,N}$ for semantic FormulaEval selectors and at arbitrary extension variables whose row supports are not bit-explicit. The restricted Psys^{-}_{bEF} plus interval-union FormulaEval packet is valid; the full semantic proof-system parser is not proved.

Next. Instantiate $RowSetEnumerator_N$ for one richer transparent selector class beyond interval-unions, preferably sorted AC0 threshold-free selectors with explicit scan charge, and decide whether it expands at N|RowSet|, collapses to an N^q scan bound, or admits a private-row countermodel.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0105: Hardness-Magnification Bridge Realization

Learning. Cycle 105 converts the promoted restricted packet into an auditable inference-quality theorem: Psys^{-}_{bEF} plus transparent interval-union FormulaEval has a valid parser-to-circuit falsifier with Γ^{IU}_{bEF}, while full semantic FormulaEval is not merely hard or barrier-limited but blocked by the exact $FE^{sem}_{Extract,N}$ private-row countermodel. The contribution is a paper-level parser/falsifier boundary, not evidence for P $\neq$ NP.

Pressure. No remaining gap for Psys^{-}_{bEF} with transparent interval-union FormulaEval. Full Psys_{sym} remains blocked at $FE^{sem}_{Extract,N}$: a semantic FormulaEval rule may compute SAT facts over hidden selected formulas without outputting RowSet indices or occurrence neighborhoods.

Next. Run the delta-varied interval-union selector audit: instantiate $|RowSet| = N^{q-\delta}$, verify $RowSetEnumerator_N$ gate cost, compute Γ^{IU}_{bEF} at $\delta = q - \epsilon \pm \mathrm{o}(1)$, and test whether any proposed semantic selector supplies a valid $FE_{Extract,N}$ certificate rather than triggering the private-row falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0106: Hardness-Magnification Bridge Realization

Learning. Cycle 106 upgrades the promoted restricted result into a live inference-quality theorem packet: Γ^{IU}_{bEF} is derived by line induction with explicit SR_h and interval-union FormulaEval charges, the q/epsilon support trichotomy is a contraposed corollary, and full semantic FormulaEval remains quarantined by the private-row falsifier rather than by generic barrier folklore.

Pressure. No blocking gap remains for Psys^{-}_{bEF} plus transparent interval-union FormulaEval. The named unresolved gap is $FE^{sem}_{Extract,N}$: extracting complete row supports from unexpanded semantic FormulaEval-SAT without advice or nonrelativizing SAT-specific reasoning.

Next. Run the finite validation audit on one concrete Psys_{sym} rule: encode FormulaEval as (a) interval-union axiom schema, (b) AC0 selector with enumerator, and (c) opaque semantic oracle; compute α and either attach $N^{1+\alpha+o(1)}$ charge or exhibit the private-row countermodel.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0107: Hardness-Magnification Bridge Realization

Learning. Cycle 107 adds a real validation upgrade: transparent FormulaEval selectors no longer require interval-union structure for a valid theorem, because full syntactic scanning gives a certified $B_{FE} = F_{FE}\ N^{1+q+o(1)}$ charge. This closes the $q < \epsilon$ falsifier for a broader selector fragment and isolates the only missing improvement as $AC0PrefixNonemptiness_N$ for output-sensitive enumeration. Full semantic FormulaEval remains quarantined by the private-row falsifier, not by generic barrier folklore.

Pressure. $AC0PrefixNonemptiness_N$: no advice-free, output-sensitive enumeration theorem is proved for arbitrary AC0 row selectors over q log N row bits; brute force gives a valid but sometimes over-threshold scan charge.

Next. Formalize $AC0PrefixNonemptiness_N$ as a finite lemma: for AC0 selectors on q log N row bits, test whether descriptor structure yields $N^{o(1)}$ prefix emptiness; if not, state the selector-scan theorem as final and add AC0 output-sensitive enumeration to open problems.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0108: Hardness-Magnification Bridge Realization

Learning. Cycle 108 replaces selector-case accumulation by a single $TransparentRowSupport_N$ theorem pair. Transparent FormulaEval is valid only after $U_N + X_N$ charging or full scan; hidden semantic FormulaEval is refuted by a private-row falsifier unless $RealSATInfluenceRealizer_N$ supplies a nonrelativizing charged-support certificate. This is a paper-level parser/falsifier boundary, not evidence for P $\neq$ NP.

Pressure. The positive theorem is valid for $TransparentRowSupport_N$ and full-scan fallback. The full Psys_{sym} semantic theorem remains blocked exactly at $RealSATInfluenceRealizer_N$; $AC0PrefixNonemptiness_N$ is only an optimization gap for output-sensitive enumeration.

Next. Write the referee-style $TransparentRowSupport_N$ definition and audit six examples as corollaries: interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete extension rules. Do not add new selector families unless they prove a clause, refute a clause, or improve $AC0PrefixNonemptiness_N$.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive

β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0109: Hardness-Magnification Bridge Realization: $TransparentRowSupport$ theorem pair

Learning. Cycle 109 upgrades the theorem pair from selector consolidation to a proof-audited interface: $TransparentRowSupport_N$ is a finite checkable condition, Γ_{trans} is derived by line induction, hidden semantic support has a concrete private-row/unread-enable-bit falsifier, and the only full Psys_{sym} escape is the nonrelativizing $RealSATInfluenceRealizer_N$. This is paper-level route certification, not evidence for P $\neq$ NP.

Pressure. $RealSATInfluenceRealizer_N$ remains open for genuine real-SAT semantic FormulaEval rules; the private-row countermodel proves that a relativizing or surface-occurrence parser cannot fill this gap.

Next. Referee-check one projected-dDNNF FormulaEval rule against the five $TransparentRowSupport_N$ clauses, compute its U_N and X_N charges, and verify that any projected hidden variable is either influence-closed or triggers the unread-enable-bit countermodel.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state

the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0110: Hardness-Magnification Bridge Realization

Learning. Cycle 110 consolidates the selector zoo into a single theorem pair. Transparent FormulaEval is valid only when every influence is surfaced and charged in Γ_{trans}; hidden semantic support is blocked by a private-row/unread-enable-bit falsifier. The exact full-system escape is $RealSATInfluenceRealizer_N$, not a generic naturalness or relativization slogan.

Pressure. No remaining gap for the restricted $TransparentRowSupport_N$ theorem pair. The named open gap for full Psys_{sym} is $RealSATInfluenceRealizer_N$: convert real SAT-semantic FormulaEval influence into explicit charged row support without advice leakage or threshold collapse.

Next. Attempt $RealSATInfluenceRealizer_N$ for one influence-complete extension rule: define $RealInfl_l$, produce row-index witnesses and $EnumCost + N|K_l|$ charge, or exhibit a semantic rule where a real SAT-sensitive row remains unchargeable, thereby demoting full Psys_{sym} beyond the transparent theorem pair.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0111: Hardness-Magnification Bridge Realization

Learning. Cycle 111 converts the transparent FormulaEval consolidation into a proof-delivery packet: Γ_{trans} is derived by line induction, hidden support has a precise private-row falsifier, and the only full semantic escape is the named nonrelativizing $RealSATInfluenceRealizer_N$. This is a valid scoped parser/falsifier contribution, not progress on the main P vs NP conjecture itself.

Pressure. No gap remains for the conditional $TransparentRowSupport_N$ theorem pair. The full Psys_{sym} extension is blocked exactly at $RealSATInfluenceRealizer_N$ for hidden semantic FormulaEval lines.

Next. Write the final paper theorem text for $TransparentRowSupport_N$ with clauses T1-T6, prove the line induction lemma in referee style, then test one genuinely semantic FormulaEval rule against $RealSATInfluenceRealizer_N$ or instantiate the private-row countermodel.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0112: Hardness-Magnification Bridge Realization

Learning. Cycle 112 turns the transparent FormulaEval packet into a finite theorem pair: transparency is exactly a charged support-realization condition, and hidden semantic support is not merely difficult but has a two-world private-row falsifier. The contribution remains a route-level parser/falsifier boundary for beta-zero magnification; the main P vs NP conjecture is untouched.

Pressure. No blocking gap remains for $\mathrm{Psys}^{trans}_{sym}$ as defined. The extension to full semantic Psys_{sym} is blocked exactly at $RealSATInfluenceRealizer_N$, which must convert real-SAT semantic influence into charged same-theory row support.

Next. Write the corollary table as examples only: interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete extension rules must each be checked against the five $TransparentRowSupport_N$ clauses or demoted.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0113: Hardness-Magnification Bridge Realization

Learning. Cycle 113 converts the promoted FormulaEval boundary into a paper-ready theorem pair: transparent support is exactly a charged support-realization interface yielding Γ_{trans} and the LB_N falsifier window, while hidden semantic support is blocked by a concrete private-row/unread-enable-bit falsifier. The full-system escape is precisely $RealSATInfluenceRealizer_N$, not generic barrier folklore.

Pressure. No blocking gap remains for the restricted $TransparentRowSupport_N$ theorem pair. The full semantic Psys_{sym} extension is blocked exactly at $RealSATInfluenceRealizer_N$, an advice-free nonrelativizing conversion from real SAT influence to charged occurrence support.

Next. Run the finite proof-quality checklist on the paper statement: verify each $TransparentRowSupport_N$ clause for interval-union, full scan, ROBDD, guarded-dDNNF, projected-dDNNF, and influence-complete examples; then attempt or refute $RealSATInfluenceRealizer_N$ for one concrete semantic FormulaEval axiom.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the restricted-model branch, compute the compiler envelope from unrestricted SIZE(m^k) or P-time algorithms into the named model; promotion requires a bound above that envelope on the same SAT slice.

cycle-0114: Hardness-Magnification Bridge Realization

Learning. Cycle 114 upgrades the promoted theorem pair into an auditable live inference packet: transparent FormulaEval is exactly charged support realization, hidden semantic FormulaEval has a two-world falsifier, and the full-system question is the named nonrelativizing $RealSATInfluenceRealizer_N$ rather than generic barrier folklore.

Pressure. The positive theorem is complete for $TransparentRowSupport_N$, but full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: no advice-free nonrelativizing procedure is known that surfaces all real-SAT influences with subthreshold cost.

Next. Instantiate $RealSATInfluenceRealizer_N$ for one concrete full semantic FormulaEval rule, or prove a rule-specific private-row countermodel showing that the full Psys_{sym} extension must remain quarantined.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0115: Hardness-Magnification Bridge Realization

Learning. Cycle 115 adds a minimality proof obligation to the promoted transparent-support theorem pair. Transparent FormulaEval is not just sufficient for a valid Γ_{trans} parser; hidden influence is exactly what the private-row/unread-enable-bit falsifier exploits. Thus the full-system boundary is a named nonrelativizing $RealSATInfluenceRealizer_N$ lemma, while the paper-level contribution remains a scoped parser/falsifier result rather than evidence for P $\neq$ NP.

Pressure. The transparent theorem and hidden-support countermodel are proof-shaped for occurrence-visible fragments, but the full semantic case is blocked by $RealSATInfluenceRealizer_N$: one must show that real SAT semantics forces every influential row into a charged support set.

Next. Formalize the private-row independence lemma for one full symbolic FormulaEval rule with an unread enable bit: write the two transcripts, the charged constraint set, the flipped row r, and the proof that all visible lines agree while H_N^{SAT} parity differs; if independence fails, record the exact same-theory constraint as a $RealSATInfluenceRealizer_N$ candidate.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0116: Hardness-Magnification Bridge Realization: Transparent FormulaEval Minimality Audit

Learning. Cycle 116 closes the minimality audit for the transparent FormulaEval theorem pair. The valid paper claim is now a restricted parser/falsifier boundary: every surfaced influence is charged in Γ_{trans}, and every unsurfaced nonsemantic influence admits a private-row falsifier. The only remaining full-system route is the named nonrelativizing $RealSATInfluenceRealizer_N$; this is not evidence for P $\neq$ NP.

Pressure. Full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: private-row spoofing is a relativizing falsifier for hidden support, but it cannot refute genuinely real-SAT semantic influence without a same-theory realization or a concrete semantic no-go.

Next. Instantiate $RealSATInfluenceRealizer_N$ or refute it for one concrete strong rule: FormulaEval with Tseitin-extension equality plus bounded self-reduction; list exact bit fields, RowSet extraction, same-theory expansion certificates, and the first semantic inference that cannot be charged.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0117: Hardness-Magnification Bridge Realization: Transparent FormulaEval Boundary

Learning. Cycle 117 upgrades the promoted theorem pair from sufficiency plus informal minimality to a local safety iff for extensional FormulaEval: surfaced influence is exactly what makes the Γ_{trans} parser valid, and unsurfaced nonsemantic influence is exactly what the private-row/unread-enable-bit falsifier exploits. The full semantic case is not dismissed by a barrier slogan; it is isolated as the nonrelativizing $RealSATInfluenceRealizer_N$ obligation. This is a paper-level route-boundary result, not a proof of P $\neq$ NP.

Pressure. The derivation is complete for extensional FormulaEval rules but still blocked for full semantic FormulaEval at $RealSATInfluenceRealizer_N$, which must nonrelativizingly force real SAT influence into charged same-theory support.

Next. Write the paper-ready theorem statement as three clauses: $TransparentRowSupport_N$ positive Γ_{trans} induction; extensional hidden-support private-row/unread-enable-bit countermodel; $RealSATInfluenceRealizer_N$ open semantic escape with overhead R_N and explicit non-claims.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0118: Hardness-Magnification Bridge Realization

Learning. Cycle 118 adds a compositional repair to the FormulaEval boundary: local surfaced influence is not enough unless hidden influences are closed under later proof use. The valid restricted theorem is $\mathrm{Psys}^{ext}_{sym}$ plus charged $RealSATInfluenceRealizer_N$ rows implies Γ_{comp} line induction and the LB_N falsifier window. The necessity direction is now a last-unsafe-line private-row theorem. Full semantic FormulaEval remains open exactly at a nonrelativizing realizer lemma, not at generic relativization, natural-proofs, or P vs NP folklore.

Pressure. The last-unsafe-line argument is valid in the extensional label model. For real SAT semantics, a hidden row may be forced by nonrelativizing formula identities, self-reduction constraints, or EqSAT links without being syntactically visible. That exact gap is $RealSATInfluenceRealizer_N$.

Next. Run a finite proof audit on Psys^{ext}_{sym}: instantiate one guarded FormulaEval line, compute I_l, K_{idx}, R_{FE}, and Γ_{comp}, then verify the last-unsafe-line two-world construction or identify the first real SAT-semantic rule that forces a nonrelativizing realizer charge.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0119: Hardness-Magnification Bridge Realization, cycle 119: compositional transparent support closure

Learning. Cycle 119 turns compositional closure from a warning into a theorem-shaped invariant: transparent FormulaEval support must be prefix-closed under later symbolic use, and sub-threshold Γ_{comp} then gives a same-model LB_N falsifier. The necessity direction is a last-unsafe-line private-row theorem for extensional support. Full semantic FormulaEval remains open exactly at $RealSATInfluenceRealizer_N$, not at generic barrier folklore or the main P vs NP conjecture.

Pressure. The derivation does not prove full Psys_{sym} semantic FormulaEval parsing; it is blocked exactly at $RealSATInfluenceRealizer_N$ for rules whose influence is forced by real SAT semantics but not surfaced as generated-row support.

Next. Write the finite prefix-closure verifier for $TransparentRowSupport_N$: input pi,N; output Cl_t for each line, Gamma_prefix(t), and either a valid support-closed derivation certificate or the first unsafe line with its private-row/unread-enable-bit countermodel.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0120: Hardness-Magnification Bridge Realization: least-closed transparent FormulaEval support

Learning. Cycle 120 strengthens the promoted theorem pair by identifying the minimal valid charged object: the least prefix-closed reachable FormulaEval support cone K_dag(pi), not the full selector zoo. The positive line induction uses Gamma_dag=Gamma_bEF+U(K_dag)+X(K_dag), and the necessity side is a first-hidden-reachable-row falsifier. Full semantic FormulaEval remains quarantined exactly at $RealSATInfluenceRealizer_N$; this is a scoped parser/falsifier contribution, not progress toward proving P $\neq$ NP.

Pressure. Full semantic FormulaEval over real SAT is still blocked at $RealSATInfluenceRealizer_N$: no proof currently converts semantic influence of an uncharged formula row into an advice-free, prefix-closed, charged support certificate.

Next. Write the proof-audit version of L120.1: formalize the fixed-point computation of K_dag(pi), give pseudocode for the verifier-visible dependency closure, and check one projected-dDNNF FormulaEval example plus one unread-enable-bit counterexample against the Γ_{dag} inequality.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0121: Hardness-Magnification Bridge Realization: L121 least-closed support audit

Learning. Cycle 121 turns K_dag(pi) into a finite auditable fixed-point object. The valid contribution is sharper than the previous transparency slogan: least prefix-closed reachable support is sufficient for the Γ_{dag} parser and necessary for extensional safety via a first-hidden-row falsifier. The remaining full-system gap is exactly $RealSATInfluenceRealizer_N$ for real SAT-semantic FormulaEval, not generic relativization, natural proofs, or P vs NP folklore.

Pressure. The restricted proof is complete only for transparent extensional FormulaEval. Full semantic SAT FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: proof syntax must nonrelativizingly determine and charge every real SAT influence before use.

Next. Write the formal L121.1 proof skeleton as theorem text: fixed-point pseudocode for K_{dag}, induction invariant per rule type, charge table for bEF/SR_h/FormulaEval/$projected - dDNNF$, and the unread-enable-bit counterexample with $\theta < \epsilon$.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0122: Hardness-Magnification Bridge Realization

Learning. Cycle 122 upgrades K_{dag} from a named minimal support object to a referee-auditable fixed-point proof packet. The valid theorem is restricted but paper-relevant: least prefix-closed reachable FormulaEval support is sufficient for Γ_{dag} line induction and necessary for extensional safety by a first-hidden-row falsifier. The full semantic case is still blocked exactly at $RealSATInfluenceRealizer_N$ not by generic barrier folklore or by the P vs NP conjecture itself.

Pressure. The restricted theorem is valid for transparent extensional FormulaEval, but it does not settle full semantic FormulaEval. The named gap is $RealSATInfluenceRealizer_N$: real SAT-semantic reasoning may determine row influence without a verifier-visible row set, and this requires a nonrelativizing charged realizer or a rule-specific no-go.

Next. Write the paper-ready L122 module: formal theorem statement, fixed-point pseudocode, line-induction proof, projected-dDNNF charge example, unread-enable-bit counterexample, q-trichotomy corollary, and a separate $RealSATInfluenceRealizer_N$ open-boundary paragraph.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive

β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0123: Hardness-Magnification Bridge Realization

Learning. Cycle 123 closes a proof-audit gap rather than repeating the magnification slogan: K_{dag} is an implementable least fixed point, projected-dDNNF gives a concrete transparent positive case, and the unread-enable-bit/private-row construction gives a precise necessity falsifier. The valid result is a scoped parser/falsifier theorem for beta-zero parity magnification; full semantic FormulaEval is still blocked exactly at $RealSATInfluenceRealizer_N$.

Pressure. $RealSATInfluenceRealizer_N$ remains unproved for full semantic FormulaEval: a real SAT-semantic rule might force r* nonrelativizingly from charged rows even when no extensional support certificate lists it.

Next. Write the referee-checkable trace for the projected-dDNNF example: list gate fields, parent pointers, projection maps, RowSet certificates, K_0, K_1,... closure additions, U_N and X_N charges, then flip one unread enable bit to exhibit the first-hidden-row countermodel and verify the Γ_{dag} threshold numerically for qepsilon.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route,

state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0124: Hardness-Magnification Bridge Realization

Learning. Cycle 124 makes the semantic boundary sharper: bounded Tseitin self-reduction is foldable into the least-support theorem only when every restriction child is declared and charged. The exact threshold is $\kappa + \theta < \epsilon$ for the new row expansion. Hidden branch-pruning is a concrete private-row falsifier, so full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N^{arb}$ rather than at generic barrier folklore.

Pressure. The proof does not cover arbitrary full semantic FormulaEval. The named remaining gap is $RealSATInfluenceRealizer_N^{arb}$: every semantic inference must uniformly reveal all rows whose labels can affect later proof use before the inference is consumed.

Next. Write the $FE_{\mathrm{TSR},decl}$ rule schema as bit fields: row id, Tseitin code, pivot list, child constructor, parent pointers, and EF derivation handles; then check the fixed-point K_{TSR} enumerator on a one-line bounded-SR example and a hidden satisfying-branch counterexample.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0125: Hardness-Magnification Bridge Realization

Learning. Cycle 125 converts the TSR semantic boundary into a theorem-shaped split. Declared bounded TSR is validly absorbed by the least-support parser with charge $N^{1+\kappa+\theta+o(1)}$, giving a falsifier exactly when $\kappa+\theta < \epsilon$. Hidden semantic branch-pruning is not a free extension of FormulaEval: it has a first-hidden-row private-row no-go unless a nonrelativizing $RealSATInfluenceRealizer_N^{arb}$ supplies charged influence rows. This is a scoped parser/falsifier contribution, not evidence for P $\neq$ NP.

Pressure. $RealSATInfluenceRealizer_N^{arb}$ for hidden semantic branch-pruning: the derivation does not extract unlisted rows whose relevance is certified only by actual SAT semantics.

Next. Write the referee-auditable TSR_{decl} proof block: child-row bit fields, fixed-point pseudocode, Γ_{TSR} induction case, and a two-world hidden-pruning countermodel with a named first hidden child row r_star.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it tests whether a meta-complexity carrier gives a weaker source obligation than the original P vs NP/P-poly target; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0126: Hardness-Magnification Bridge Realization

Learning. Cycle 126 converts declared bounded TSR from a semantic warning into a charged fixed-point rule case. The valid contribution is a restricted theorem: declared TSR rows are absorbed by K_{dag} with threshold $\kappa+\theta < \epsilon$, while hidden branch-pruning is a precise private-row falsifier. Full semantic FormulaEval is still not proved; it is isolated at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. The derivation does not cover arbitrary semantic branch-pruning where real SAT semantics decide which children matter without a syntactic declaration. The named missing lemma is $RealSATInfluenceRealizer_N^{arb}$: from proof syntax and N alone, uniformly list all semantically influencing TSR/FormulaEval rows before use and charge them in Γ.

Next. Formalize the $\mathrm{Psys}_{sym}^{dag+declTSR(h)}$ grammar in one page: exact row-index fields, TSR parent/child encodings, local verifier predicate, K_{dag}^{TSR} fixed-point pseudocode, and the declared TSR line-induction case; then instantiate with $\kappa = \epsilon/3$, $\theta = \epsilon/3$, q in ((1+epsilon)/2,1+epsilon), $\rho < 1+\epsilon$ to verify all charges remain subthreshold except the intended q-density pressure.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0127: Hardness-Magnification Bridge Realization

Learning. Cycle 127 adds a concrete rule-level proof packet: declared bounded TSR is absorbed by the least closed support cone with exact charge $N^{1+\kappa+\theta+o(1)}$, while hidden branch pruning has a first-unlisted-child falsifier. This improves the paper theorem boundary without claiming P $\neq$ NP or a general H_N lower bound.

Pressure. The positive derivation is complete only for declared TSR syntax. Full real-SAT semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: a uniform, advice-free, nonrelativizing procedure must list all live child rows and charge them before the semantic rule is used.

Next. Write the verifier bit fields for one declared TSR line: root row id, restriction-node path, pivot variable, child row ids, Tseitin map hash, occurrence-neighborhood list, parent pointers, and expansion certificate; then prove the single-line induction inequality adding exactly N times the declared child count to $\Gamma_{dag+\mathrm{TSR}}$.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0128: Hardness-Magnification Bridge Realization

Learning. Cycle 128 closes a sharper declared-TSR support sublemma: complete child declarations compose with the least support fixed point and cost exactly $N^{1+\kappa+\theta+o(1)}$, while hidden

branch pruning has a first-unlisted-child private-row falsifier. The contribution remains a scoped parser/falsifier theorem, not evidence for P $\neq$ NP.

Pressure. The declared complete-child schema has no current derivation gap beyond writing the final syntax checker. The full semantic rule remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which must list all influencing rows without SAT-truth advice.

Next. Write the paper-ready TSR rule schema table and verify on one toy projected-dDNNF plus TSR line: compute K_{TSR}, A_{TSR}, B_{TSR}, R_{TSR}, and then flip the first unlisted child in the hidden-pruning variant.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0129: Hardness-Magnification Bridge Realization

Learning. Cycle 129 turns declared bounded TSR from a semantic-warning slogan into a line-induction rule case for the least support theorem. Complete child declaration adds exactly $N^{1+\kappa+\theta+o(1)}$ to Γ_{DTSR} and is valid below $\kappa + \theta < \epsilon$; hidden branch pruning is refuted by a first-unlisted-child falsifier unless a nonrelativizing real-SAT influence realizer is supplied.

Pressure. No blocking gap for the restricted complete-child declared TSR rule case. The full semantic FormulaEval/TSR system remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which must uniformly list and charge semantically influencing rows before use.

Next. Write the paper-ready L129 sublemma proof: give pseudocode for K_{DTSR} fixed-point enumeration, a table of declared TSR bit fields, the local verifier for child occurrence neighborhoods, and the two-world first-unlisted-child countermodel; then run the live inference-quality packet validation.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0130: Hardness-Magnification Bridge Realization

Learning. Cycle 130 closes a real proof-delivery subcase: declared bounded TSR is not merely compatible with transparent support but is an explicit fixed-point rule with charge $N^{1+\kappa+\theta+o(1)}$. The exact boundary is now complete declaration versus first-unlisted-child falsifier; full semantic pruning remains open only through the nonrelativizing $RealSATInfluenceRealizer_N^{arb}$.

Pressure. Full semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: the derivation does not show that real SAT semantics can uniformly list all influential pruned children without advice and before use.

Next. Run the bit-field audit for one concrete DTSR verifier line: list parent row id, active descriptor id, restriction mask, child row id, Tseitin extension map, local identity tag, and downstream use pointer; verify that K_{DTSR} reaches every used child and compute the exact theta+kappa ledger for the example.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The

current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0131: Hardness-Magnification Bridge Realization

Learning. Cycle 131 turns declared bounded TSR into an auditable fixed-point rule case: complete child declarations are sufficient for the Γ_{DTSR} parser and necessary up to the first-unlisted-child falsifier. The valid contribution is a route-level theorem/countermodel boundary for beta-zero parity magnification certificates, not progress on the main P vs NP conjecture.

Pressure. The restricted declared-TSR theorem has no current internal gap. The full semantic pruning case remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$: an advice-free nonrelativizing procedure must list all real-SAT influencing rows and charge them before use.

Next. Run the reviewer audit on L131.1: instantiate one toy projected-dDNNF FormulaEval line plus one declared TSR parent with two restriction children, compute K_{DTSR} by the worklist, verify Γ_{DTSR} numerically as $N^{1+\kappa+\theta+o(1)}$, then flip the first unlisted child in the hidden-pruning variant to validate the private-row falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0132: Hardness-Magnification Bridge Realization

Learning. Cycle 132 upgrades declared bounded TSR from a rule-case slogan to a fixed-point parser theorem with explicit bit fields, closure algorithm, ledger, and necessity falsifier. The valid contribution is the restricted $TransparentRowSupport_N^{\mathrm{DTSR}}$ theorem/countermodel pair; full semantic pruning remains quarantined exactly at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. $RealSATInfluenceRealizer_N^{arb}$: arbitrary semantic branch-pruning may be valid over real SAT yet not expose an advice-free row list in the proof syntax. The present theorem covers declared DTSR and transparent support only.

Next. Write the paper-ready L132 proof block: pseudocode for K_DTSR(pi), a table of DTSR bit fields and verifier checks, the five line-induction cases, and the first-unlisted-child countermodel; then test one projected-dDNNF+DTSR positive example and one unread-enable-bit hidden-pruning counterexample.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0133: Hardness-Magnification Bridge Realization

Learning. Cycle 133 upgrades declared bounded TSR from a compatible rule case to a live inference-quality theorem packet: complete child declarations are sufficient for the Γ_{DTSR} parser and necessary up to a first-unlisted-child falsifier. The valid contribution is a scoped $TransparentRowSupport_N^{\mathrm{DTSR}}$ theorem/countermodel boundary; full semantic pruning remains exactly blocked at $RealSATInfluenceRealizer_N^{arb}$

Pressure. Full semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: no proof here uniformly lists all real-SAT-influencing rows when the branch choice is determined by semantic satisfiability rather than declared syntax.

Next. Attack $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic pruning rule: bounded Tseitin self-reduction with a SAT-truth branch-elimination premise. Either produce a uniform charged list of all influencing children or formalize the first semantic line where the private-row countermodel survives.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0134: Hardness-Magnification Bridge Realization

Learning. Cycle 134 sharpens the DTSR boundary: complete declaration must be counterfactual, not merely actual-branch. This yields a valid restricted Γ_{CTSR} parser theorem and a sharper private-row falsifier for hidden adaptive pruning. The remaining full semantic escape is exactly a nonrelativizing $RealSATInfluenceRealizer_N^{arb}$, not generic barrier folklore or evidence for P $\neq$ NP.

Pressure. The restricted counterfactual DTSR theorem is proof-shaped, but full semantic adaptive pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: one must prove that real SAT semantics uniformly determines and charges every hidden influential row, or accept the private-row no-go.

Next. Instantiate the counterfactual DTSR closure on a two-level nested TSR proof with one Tseitin seed family; compute the exact child count, K_{CTSR} fixed point, Γ_{CTSR} ledger, and first-unlisted-child countermodel transcript.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0135: Hardness-Magnification Bridge Realization

Learning. Cycle 135 upgrades declared TSR to counterfactual declared TSR: complete counterfactual child support is sufficient for the Γ_{CTSR} parser and necessary for extensional safety. The exact new falsifier is first-hidden-child adaptive pruning; the only full semantic escape is a charged nonrelativizing $RealSATInfluenceRealizer_N^{arb}$. This is a route-level theorem/countermodel boundary, not evidence for P $\neq$ NP.

Pressure. The two-world private-row argument is a no-go for extensional or relativizing hidden support, not a proof against real SAT-specific semantic pruning. Full semantic pruning remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$.

Next. Resolve $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic rule: bounded Tseitin self-reduction with adaptive unsat-branch pruning. Either produce a syntax-and-N computable influence row list R_A with charge in Γ_{real}, or formalize the first unchargeable semantic inference as a private-row no-realizer theorem.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0136: Hardness-Magnification Bridge Realization

Learning. Cycle 136 turns counterfactual declared TSR from a boundary slogan into a bitfield-level closed-support theorem: K_CTSR(pi) is a finite fixed point, Γ_{CTSR} is derived by line induction, and first-hidden-child adaptive pruning is the exact falsifier for extensional safety. The valid contribution remains a scoped parser/falsifier theorem for beta-zero parity magnification certificates; it does not prove H_N lower bounds or P $\neq$ NP.

Pressure. The derivation does not handle arbitrary semantic branch pruning. The named open bridge is $RealSATInfluenceRealizer_N^{arb}$: from real SAT semantics and proof syntax alone, uniformly list every influencing child row with charged overhead before the semantic rule is used.

Next. Select one concrete full semantic pruning rule beyond CTSR declarations, preferably adaptive Tseitin branch pruning with real SAT contradiction tests, and attempt either a charged $RealSATInfluenceRealizer_N^{arb}$ or a minimal first-unchargeable-row countermodel.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0137: Hardness-Magnification Bridge Realization

Learning. Cycle 137 improves the promoted CTSR packet by proving minimality pressure, not just sufficiency: complete counterfactual child support is the least valid transparent object for adaptive TSR. Removing one reachable child gives a concrete first-hidden-child falsifier; adding all children gives the exact Γ_{CTSR} threshold $\kappa + \theta < \epsilon$. The learning is a scoped parser/countermodel contribution, not a lower bound for H_N and not P $\neq$ NP progress.

Pressure. The derivation does not handle full semantic branch pruning where real SAT itself proves the omitted child determined by charged rows. That is exactly $RealSATInfluenceRealizer_N^{arb}$: an advice-free, nonrelativizing realizer must list and charge all influencing rows before the semantic rule is used.

Next. Write the standalone L137 first-hidden-child theorem: specify the CTSR bit fields, define the two row-oracle worlds, prove transcript equality on K_{CTSR} minus r, prove final parity disagreement, and compute the Γ_{CTSR} threshold for $\kappa + \theta < \epsilon$ with q-trichotomy support density.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0138: Hardness-Magnification Bridge Realization

Learning. Cycle 138 identifies the exact minimal CTSR object as reachable counterfactual frontier closure. This improves the promoted packet: actual-branch declarations are not valid transparent support, while full reachable child declarations give the Γ_{CTSR} parser with threshold $\kappa + \theta < \epsilon$. The result is a scoped parser/countermodel theorem and live inference-quality packet, not evidence for P $\neq$ NP.

Pressure. The two-world necessity proof is valid for extensional row-label or occurrence-local semantics, but it does not refute a real SAT semantic derivation proving that the hidden child is impossible unless $RealSATInfluenceRealizer_N^{arb}$ fails for that derivation.

Next. Write the referee-facing CTSRFrontierCompleteness proof: give closure pseudocode for K_{CTSR}, prove termination and minimality, verify one adaptive TSR line bit-by-bit, and instantiate the first-hidden-child falsifier on a one-node unread-enable-bit example.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it separates true hardness magnification from projection or padding arguments that only move proof debt; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0139: Hardness-Magnification Bridge Realization

Learning. Cycle 139 improves the CTSR frontier packet by adding a safe EqSAT quotient rule: duplicate counterfactual child rows reduce Γ only when a same-theory certificate is surfaced and charged. Otherwise quotienting is exactly where the private-row falsifier attacks. This is a valid scoped parser/countermodel contribution and still not evidence for P $\neq$ NP.

Pressure. $RealSATInfluenceRealizer_N^{arb}$ remains open for fully semantic adaptive pruning that never exposes counterfactual children or EqSAT certificate edges yet may be sound for real SAT instances.

Next. Instantiate $\Gamma^{=}_{\mathrm{CTSR}}$ on a projected-dDNNF FormulaEval proof with two Tseitin-equivalent child formulas: compute K before and after certified EqSAT quotienting, then remove one certificate and exhibit the first uncertified quotient-collision private-row falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0140: Hardness-Magnification Bridge Realization: QCTSR Certified-Quotient Parser Boundary

Learning. Cycle 140 turns safe EqSAT quotienting from a slogan into a ledger transformation: duplicate counterfactual CTSR rows may be removed only through a surfaced same-theory certificate forest whose dependencies are in K_Q. The exact new falsifier is the first uncertified quotient merge. This strengthens the scoped parser/countermodel contribution and remains separate from proving any lower bound or P $\neq$ NP.

Pressure. The derivation does not handle arbitrary real-SAT semantic pruning. It requires either surfaced same-theory EqSAT certificates or a future $RealSATInfluenceRealizer_N^{arb}$ that uniformly lists and charges all semantic influences before use.

Next. Instantiate K_Q on a toy projected-dDNNF FormulaEval proof with two CTSR levels and three EqSAT quotient classes; compute |RepIdx|, C_{Eq}, Γ_{QCTSR}, then delete one quotient certificate to exhibit the first-hidden-merge falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem.

The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0141: Hardness-Magnification Bridge Realization

Learning. The new contribution is that quotient compression in counterfactual TSR is not a free Γ reduction. It is valid only as a dependency-closed, acyclic same-theory certificate transformation; otherwise the first uncertified merge gives a private-row falsifier. This closes a proof-audit loophole in the restricted transparent-support theorem while preserving the separation between route-level certificate collapse and the main P vs NP conjecture.

Pressure. The derivation is complete only for syntactic same-theory quotient certificates. It blocks for full semantic FormulaEval or adaptive pruning where the set of influencing rows is determined by real SAT truth rather than proof-visible dependencies; this is exactly $RealSATInfluenceRealizer_N^{arb}$.

Next. Instantiate one two-merge CTSR proof toy model: one certified EqSAT quotient with charged forest and one uncertified merge. Write the local verifier fields, compute R_Q and C_Q, and demonstrate transcript agreement plus parity disagreement for the uncertified merge.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0142: Hardness-Magnification Bridge Realization

Learning. Cycle 142 makes quotient compression proof-carrying: row deletion is valid only after a ranked same-theory certificate is charged in Γ_{QCTSR}. Acyclicity is the new finite audit condition; cyclic, adaptive, or advice-chosen merges are concrete countermodels, not generic barrier folklore.

Pressure. The argument does not realize hidden semantic FormulaEval or adaptive SAT branch pruning; $RealSATInfluenceRealizer_N^{arb}$ remains the named nonrelativizing open lemma.

Next. Write the finite verifier for K_Q and ranked F_Q on a toy projected-dDNNF plus CTSR example with one duplicate child pair; compute Γ savings, then remove one certificate edge to exhibit the private-row falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0143: Hardness-Magnification Bridge Realization

Learning. Cycle 143 turns quotient compression into a proof-carrying ledger rule: Γ may shrink only through ranked acyclic same-theory certificates already in K_Q. Unranked quotienting is not a harmless optimization; it is exactly a private-row falsifier.

Pressure. This does not solve $RealSATInfluenceRealizer_N^{arb}$ for full semantic FormulaEval; it only handles proof-carrying same-theory quotient compression.

Next. Instantiate the six-row QCTSR transcript, list row IDs, quotient certificate dependencies, rank labels, and show the first uncertified merge produces two agreeing visible transcripts with opposite H_N parity.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0144: Hardness-Magnification Bridge Realization: ranked QCTSR ledger validation

Learning. Cycle 144 closes a proof-audit loophole: quotient compression in counterfactual TSR is valid exactly as proof-carrying ranked same-theory compression, not as semantic row deletion. The contribution is a scoped parser/falsifier theorem: ranked QCTSR preserves the Γ line induction, while the first unranked quotient merge is a concrete private-row falsifier. This improves the paper theorem boundary without giving any H_N lower bound or P $\neq$ NP result.

Pressure. The positive proof is complete only for restricted $\mathrm{Psys}_{\mathrm{QCTSR}}$. Full semantic FormulaEval or hidden adaptive pruning still requires $RealSATInfluenceRealizer_N^{arb}$, an advice-free nonrelativizing theorem that lists and charges all real SAT influence rows before use.

Next. Write the referee-checkable K_Q closure pseudocode with rank ordering, then test it on a two-child Tseitin-equivalent TSR merge and on the same example with the certificate omitted to exhibit the first-unranked-merge falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem; it searches the remaining plausible escape route: nonblackbox or subpolynomial-interface carriers. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0145: Hardness-Magnification Bridge Realization

Learning. Cycle 145 upgrades ranked QCTSR from a line-induction slogan to a finite verifier/minimality packet. Quotient compression is valid only when proof-carrying same-theory certificates are ranked, dependency-closed, and charged before use. The exact obstruction is the first rejected quotient merge, which yields a private-row falsifier. This strengthens the paper parser/countermodel boundary without proving H_N lower bounds or P $\neq$ NP.

Pressure. The derivation is complete for surface QCTSR syntax with a specified EqSAT/CTSR same-theory checker. It does not handle arbitrary semantic FormulaEval or hidden adaptive pruning unless $RealSATInfluenceRealizer_N^{arb}$ uniformly lists and charges the same influenced rows before use.

Next. Instantiate the finite verifier on one toy QCTSR proof with two EqSAT-equivalent counterfactual TSR children: compute K_Q, ranks, B_Q, and Γ_{QCTSR}; then delete one certificate edge and explicitly write the two-world private-row falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0146: Hardness-Magnification Bridge Realization

Learning. Cycle 146 upgrades ranked QCTSR from a finite local verifier to a composable fixed-point line-induction theorem: quotient compression is valid only when proof-carrying same-theory certificates are ranked, acyclic, dependency-closed, and charged before use. The first rejected merge is a concrete private-row falsifier. This strengthens the transparent-support parser/countermodel paper module while preserving all nonclaims: no H_N lower bound, no P $\neq$ NP result, and no free hidden semantic FormulaEval.

Pressure. The derivation does not fold arbitrary hidden semantic FormulaEval or adaptive SAT branch pruning into K_Q. That remains the named $RealSATInfluenceRealizer_N^{arb}$ problem.

Next. Run the finite verifier on one projected-dDNNF/Tseitin-renaming example: list K_Q seeds, accepted quotient certificates, rank labels, computed Γ_{QCTSR}, and then delete one certificate to exhibit the first-rejected-merge private-row falsifier.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0147: Hardness-Magnification Bridge Realization

Learning. Cycle 147 closes a real proof-audit upgrade: ranked QCTSR quotient compression has a least, order-independent, proof-carrying support closure, so Γ reduction is valid only after lower-rank same-theory dependencies are charged. The sharp falsifier is the first nondecreasing, cyclic, advice-chosen, or hidden semantic merge. This strengthens the paper parser/countermodel module without proving any H_N lower bound or P $\neq$ NP.

Pressure. No blocking gap remains for restricted ranked QCTSR syntax. The broader full-semantic FormulaEval system remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which would have to surface all real SAT-semantic influences with charges before use.

Next. Instantiate the closure verifier on a three-row QCTSR toy transcript: two counterfactual child rows, one EqSAT certificate forest, and one attempted cyclic merge; compute K_Q, Γ_{QCTSR}, and the first-rejected-merge private-row falsifier explicitly.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0148: Hardness-Magnification Bridge Realization

Learning. Cycle 148 turns ranked QCTSR from an order-independent closure statement into a representative-stable $TransparentRowSupport_N$ rule case. The valid contribution is a restricted theorem/countermodel pair: proof-carrying quotient compression preserves Γ line induction, while the first unranked, cyclic, advice-chosen, or hidden semantic merge yields a private-row falsifier. This closes a proof-audit loophole without proving any H_N lower bound or P $\neq$ NP; full semantic pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. Full semantic FormulaEval with hidden adaptive pruning remains blocked at $RealSATInfluenceReali$ no advice-free nonrelativizing procedure is proved that lists all real SAT influences before the semantic rule is used.

Next. Write the finite K_{QCTSR} verifier on a projected-dDNNF example with one certified duplicate row and one unread-enable hidden merge; compute $U_Q, N|K_Q|, B_{\mathrm{CTSR}}, C_Q, E_{pi}$ and show exactly where the hidden merge fails the valid support ledger.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0149: Hardness-Magnification Bridge Realization

Learning. Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$.

Pressure. The derivation does not cover arbitrary real-SAT semantic pruning or FormulaEval comprehension unless $RealSATInfluenceRealizer_N^{arb}$ uniformly lists the influencing rows and charges them before use.

Next. Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P $\neq$ NP.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is adapt_then_run. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0150: Hardness-Magnification Bridge Realization

Learning. Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P $\neq$ NP.

Pressure. The derivation does not cover a semantic pruning step that obtains a quotient or child deletion from real SAT truth without a surfaced same-theory certificate; that remains exactly $RealSATInfluenceRealizer_N^{arb}$.

Next. Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For the proof-complexity branch, separate fixed-family proof hardness from language hardness by naming the proof system, shortcut algorithm, and semantic lower-bound target.

cycle-0151: Hardness-Magnification Bridge Realization

Learning. Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined.

Pressure. The derivation does not realize arbitrary semantic SAT pruning; $RealSATInfluenceRealizer_N^{arb}$ remains the named nonrelativizing bridge for full Psys_{sym}.

Next. Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0152: Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure

Learning. Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evidence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result.

Pressure. The restricted PrefixStableQrepTransparentSupport proof is theorem-shaped; the unresolved extension remains $RealSATInfluenceRealizer_N^{arb}$ for hidden full semantic SAT pruning and branch selection.

Next. Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.

When to stop. Stop or quarantine this P vs NP branch only after it states the source object, target class, complexity model, transfer inequality, quantifier strength, and barrier status; quarantine if two sharpened attempts still cannot say whether the route implies SAT $\notin$ P/poly, NP $\not\subset$ P/poly, or only a weaker/proxy lower bound.

Do not stop prematurely if. Do not stop before the branch has produced a concrete source-to-target transfer theorem, an explicit obstruction lemma, or a barrier-aware reason why the route cannot reach the P vs NP/P/poly target.

How it adds to the global problem. This move adds to the P vs NP problem because it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is backtrack_to_sharpen. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0153: Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit

Learning. Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_{I}$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress.

Pressure. The derivation does not cover arbitrary semantic FormulaEval or adaptive SAT-pruning rules that may realize influence through real SAT semantics without exposing row identifiers; that remains $RealSATInfluenceRealizer_N^{arb}$.

Next. Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state

the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

cycle-0154: Hardness-Magnification Bridge Realization

Learning. Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress.

Pressure. The derivation does not cover arbitrary semantic SAT branch pruning or FormulaEval rules whose influencing rows are not determined by proof syntax before use; this is exactly $RealSATInfluenceRealizer_N^{arb}$.

Next. Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

When to stop. Stop or quarantine this black-box substitution branch only after the source carrier, SAT-query length exponent β, interface size exponent q, source-threshold exponent, and target class have been explicitly computed; quarantine if every sharpened interface still has positive β and therefore only excludes a bounded range of SAT circuit exponents rather than NP subset P/poly.

Do not stop prematurely if. Do not stop before deriving the transfer inequality from SAT $\in$ SIZE(n^c) to the carrier upper bound, identifying whether $\beta = 0$, $\beta > 0$, or the argument is genuinely nonblackbox, and recording the barrier status of the proposed escape.

How it adds to the global problem. This move adds to the P vs NP problem because it identifies whether the transfer loses all-exponent strength through a positive target-query exponent β; it keeps barrier status and nonuniform/advice leakage attached to the actual transfer theorem. The current branch-control decision is continue_run_next. Payoff criterion: For this route, state the exact barrier premise it uses or escapes: relativizing, natural, algebrizing, nonuniform, or advice-leaking; promotion requires the escape to be attached to the specific transfer theorem.

Latest 40 Timeline Steps

This terminal appendix records the most recent timeline steps included in the paper build, so the LaTeX artifact preserves the current end of the marathon rather than only the judged argument window.

- cycle-0115 – Hardness-Magnification Bridge Realization – Cycle 115 adds a minimality proof obligation to the promoted transparent-support theorem pair. Transparent FormulaEval is not just sufficient for a valid Γ_{trans} parser; hidden influence is exactly what the private-row/unread-enable-bit falsifier exploits. Thus the full-system boundary is a named nonrelativizing $RealSATInfluenceRealiz$ lemma, while the paper-level contribution remains a scoped parser/falsifier result rather than evidence for P $\neq$ NP. – Gap: The transparent theorem and hidden-support countermodel

are proof-shaped for occurrence-visible fragments, but the full semantic case is blocked by $RealSATInfluenceRealizer_N$: one must show that real SAT semantics forces every influential row into a charged support set. – Next: Formalize the private-row independence lemma for one full symbolic FormulaEval rule with an unread enable bit: write the two transcripts, the charged constraint set, the flipped row r, and the proof that all visible lines agree while H_N^{SAT} parity differs; if independence fails, record the exact same-theory constraint as a $RealSATInfluenceRealizer_N$ candidate.

- cycle-0116 – Hardness-Magnification Bridge Realization: Transparent FormulaEval Minimality Audit – Cycle 116 closes the minimality audit for the transparent FormulaEval theorem pair. The valid paper claim is now a restricted parser/falsifier boundary: every surfaced influence is charged in Γ_{trans}, and every unsurfaced nonsemantic influence admits a private-row falsifier. The only remaining full-system route is the named nonrelativizing $RealSATInfluenceRealizer_N$; this is not evidence for P $\neq$ NP. – Gap: Full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: private-row spoofing is a relativizing falsifier for hidden support, but it cannot refute genuinely real-SAT semantic influence without a same-theory realization or a concrete semantic no-go. – Next: Instantiate $RealSATInfluenceRealizer_N$ or refute it for one concrete strong rule: FormulaEval with Tseitin-extension equality plus bounded self-reduction; list exact bit fields, RowSet extraction, same-theory expansion certificates, and the first semantic inference that cannot be charged.

- cycle-0117 – Hardness-Magnification Bridge Realization: Transparent FormulaEval Boundary – Cycle 117 upgrades the promoted theorem pair from sufficiency plus informal minimality to a local safety iff for extensional FormulaEval: surfaced influence is exactly what makes the Γ_{trans} parser valid, and unsurfaced nonsemantic influence is exactly what the private-row/unread-enable-bit falsifier exploits. The full semantic case is not dismissed by a barrier slogan; it is isolated as the nonrelativizing $RealSATInfluenceRealizer_N$ obligation. This is a paper-level route-boundary result, not a proof of P $\neq$ NP. – Gap: The derivation is complete for extensional FormulaEval rules but still blocked for full semantic FormulaEval at $RealSATInfluenceRealizer_N$, which must nonrelativizingly force real SAT influence into charged same-theory support. – Next: Write the paper-ready theorem statement as three clauses: $TransparentRowSupport_N$ positive Γ_{trans} induction; extensional hidden-support private-row/unread-enable-bit countermodel; $RealSATInfluenceRealizer_N$ open semantic escape with overhead R_N and explicit non-claims.

- cycle-0118 – Hardness-Magnification Bridge Realization – Cycle 118 adds a compositional repair to the FormulaEval boundary: local surfaced influence is not enough unless hidden influences are closed under later proof use. The valid restricted theorem is $\mathrm{Psys}_{sym}^{ext}$ plus charged $RealSATInfluenceRealizer_N$ rows implies Γ_{comp} line induction and the LB_N falsifier window. The necessity direction is now a last-unsafe-line private-row theorem. Full semantic FormulaEval remains open exactly at a nonrelativizing realizer lemma, not at generic relativization, natural-proofs, or P vs NP folklore. – Gap: The last-unsafe-line argument is valid in the extensional label model. For real SAT semantics, a hidden row may be forced by nonrelativizing formula identities, self-reduction constraints, or EqSAT links without being syntactically visible. That exact gap is $RealSATInfluenceRealizer_N$. – Next: Run a finite proof audit on $\mathrm{Psys}_{sym}^{ext}$: instantiate one guarded FormulaEval line, compute I_l, K_{idx}, R_{FE}, and Γ_{comp}, then verify the last-unsafe-line two-world construction or identify the first real SAT-semantic rule that forces a nonrelativizing realizer charge.

- cycle-0119 – Hardness-Magnification Bridge Realization, cycle 119: compositional transparent

support closure – Cycle 119 turns compositional closure from a warning into a theorem-shaped invariant: transparent FormulaEval support must be prefix-closed under later symbolic use, and subthreshold Γ_{comp} then gives a same-model LB_N falsifier. The necessity direction is a last-unsafe-line private-row theorem for extensional support. Full semantic FormulaEval remains open exactly at $RealSATInfluenceRealizer_N$, not at generic barrier folklore or the main P vs NP conjecture. – Gap: The derivation does not prove full Psys_{sym} semantic FormulaEval parsing; it is blocked exactly at $RealSATInfluenceRealizer_N$ for rules whose influence is forced by real SAT semantics but not surfaced as generated-row support. – Next: Write the finite prefix-closure verifier for $TransparentRowSupport_N$: input pi,N; output Cl_t for each line, Gamma_prefix(t), and either a valid support-closed derivation certificate or the first unsafe line with its private-row/unread-enable-bit countermodel.

- cycle-0120 – Hardness-Magnification Bridge Realization: least-closed transparent FormulaEval support – Cycle 120 strengthens the promoted theorem pair by identifying the minimal valid charged object: the least prefix-closed reachable FormulaEval support cone K_dag(pi), not the full selector zoo. The positive line induction uses Gamma_dag=Gamma_bEF+U(K_dag)+X(K_dag), and the necessity side is a first-hidden-reachable-row falsifier. Full semantic FormulaEval remains quarantined exactly at $RealSATInfluenceRealizer_N$; this is a scoped parser/falsifier contribution, not progress toward proving P $\neq$ NP. – Gap: Full semantic FormulaEval over real SAT is still blocked at $RealSATInfluenceRealizer_N$: no proof currently converts semantic influence of an uncharged formula row into an advice-free, prefix-closed, charged support certificate. – Next: Write the proof-audit version of L120.1: formalize the fixed-point computation of K_dag(pi), give pseudocode for the verifier-visible dependency closure, and check one projected-dDNNF FormulaEval example plus one unread-enable-bit counterexample against the Γ_{dag} inequality.

- cycle-0121 – Hardness-Magnification Bridge Realization: L121 least-closed support audit – Cycle 121 turns K_dag(pi) into a finite auditable fixed-point object. The valid contribution is sharper than the previous transparency slogan: least prefix-closed reachable support is sufficient for the Γ_{dag} parser and necessary for extensional safety via a first-hidden-row falsifier. The remaining full-system gap is exactly $RealSATInfluenceRealizer_N$ for real SAT-semantic FormulaEval, not generic relativization, natural proofs, or P vs NP folklore. – Gap: The restricted proof is complete only for transparent extensional FormulaEval. Full semantic SAT FormulaEval remains blocked at $RealSATInfluenceRealizer_N$: proof syntax must nonrelativizingly determine and charge every real SAT influence before use. – Next: Write the formal L121.1 proof skeleton as theorem text: fixed-point pseudocode for K_{dag}, induction invariant per rule type, charge table for bEF/SR_h/FormulaEval/$projected - dDNNF$, and the unread-enable-bit counterexample with $\theta < \epsilon$.

- cycle-0122 – Hardness-Magnification Bridge Realization – Cycle 122 upgrades K_{dag} from a named minimal support object to a referee-auditable fixed-point proof packet. The valid theorem is restricted but paper-relevant: least prefix-closed reachable FormulaEval support is sufficient for Γ_{dag} line induction and necessary for extensional safety by a first-hidden-row falsifier. The full semantic case is still blocked exactly at $RealSATInfluenceRealizer_N$, not by generic barrier folklore or by the P vs NP conjecture itself. – Gap: The restricted theorem is valid for transparent extensional FormulaEval, but it does not settle full semantic FormulaEval. The named gap is $RealSATInfluenceRealizer_N$: real SAT-semantic reasoning may determine row influence without a verifier-visible row set, and this requires a nonrelativizing charged realizer or a rule-specific no-go. – Next: Write the paper-ready L122 module: formal theorem statement, fixed-point pseudocode, line-induction proof, projected-dDNNF charge example, unread-enable-bit

counterexample, q-trichotomy corollary, and a separate $RealSATInfluenceRealizer_N$ open-boundary paragraph.

- cycle-0123 – Hardness-Magnification Bridge Realization – Cycle 123 closes a proof-audit gap rather than repeating the magnification slogan: K_{dag} is an implementable least fixed point, projected-dDNNF gives a concrete transparent positive case, and the unread-enable-bit/private-row construction gives a precise necessity falsifier. The valid result is a scoped parser/falsifier theorem for beta-zero parity magnification; full semantic FormulaEval is still blocked exactly at $RealSATInfluenceRealizer_N$. – Gap: $RealSATInfluenceRealizer_N$ remains unproved for full semantic FormulaEval: a real SAT-semantic rule might force r* nonrelativizingly from charged rows even when no extensional support certificate lists it. – Next: Write the referee-checkable trace for the projected-dDNNF example: list gate fields, parent pointers, projection maps, RowSet certificates, K_0, K_1,... closure additions, U_N and X_N charges, then flip one unread enable bit to exhibit the first-hidden-row countermodel and verify the Γ_{dag} threshold numerically for $q < \epsilon$, $q = \epsilon$, and $q > \epsilon$.

- cycle-0124 – Hardness-Magnification Bridge Realization – Cycle 124 makes the semantic boundary sharper: bounded Tseitin self-reduction is foldable into the least-support theorem only when every restriction child is declared and charged. The exact threshold is $\kappa + \theta < \epsilon$ for the new row expansion. Hidden branch-pruning is a concrete private-row falsifier, so full semantic FormulaEval remains blocked at $RealSATInfluenceRealizer_N^{arb}$ rather than at generic barrier folklore. – Gap: The proof does not cover arbitrary full semantic FormulaEval. The named remaining gap is $RealSATInfluenceRealizer_N^{arb}$: every semantic inference must uniformly reveal all rows whose labels can affect later proof use before the inference is consumed. – Next: Write the $FE_{\mathrm{TSR},decl}$ rule schema as bit fields: row id, Tseitin code, pivot list, child constructor, parent pointers, and EF derivation handles; then check the fixed-point K_{TSR} enumerator on a one-line bounded-SR example and a hidden satisfying-branch counterexample.

- cycle-0125 – Hardness-Magnification Bridge Realization – Cycle 125 converts the TSR semantic boundary into a theorem-shaped split. Declared bounded TSR is validly absorbed by the least-support parser with charge $N^{1+\kappa+\theta+o(1)}$, giving a falsifier exactly when $\kappa + \theta < \epsilon$. Hidden semantic branch-pruning is not a free extension of FormulaEval: it has a first-hidden-row private-row no-go unless a nonrelativizing $RealSATInfluenceRealizer_N^{arb}$ supplies charged influence rows. This is a scoped parser/falsifier contribution, not evidence for P $\neq$ NP. – Gap: $RealSATInfluenceRealizer_N^{arb}$ for hidden semantic branch-pruning: the derivation does not extract unlisted rows whose relevance is certified only by actual SAT semantics. – Next: Write the referee-auditable TSR_{decl} proof block: child-row bit fields, fixed-point pseudocode, Γ_{TSR} induction case, and a two-world hidden-pruning countermodel with a named first hidden child row r_star.

- cycle-0126 – Hardness-Magnification Bridge Realization – Cycle 126 converts declared bounded TSR from a semantic warning into a charged fixed-point rule case. The valid contribution is a restricted theorem: declared TSR rows are absorbed by K_{dag} with threshold $\kappa + \theta < \epsilon$, while hidden branch-pruning is a precise private-row falsifier. Full semantic FormulaEval is still not proved; it is isolated at $RealSATInfluenceRealizer_N^{arb}$. – Gap: The derivation does not cover arbitrary semantic branch-pruning where real SAT semantics decide which children matter without a syntactic declaration. The named missing lemma is $RealSATInfluenceRealizer_N^{arb}$: from proof syntax and N alone, uniformly list all semantically influencing TSR/FormulaEval rows before use and charge them in Γ. – Next: Formalize the $\mathrm{Psys}_{sym}^{dag+declTSR(h)}$ grammar in one page: exact row-index fields, TSR parent/child encodings, local verifier predicate, K_{dag}^{TSR} fixed-

point pseudocode, and the declared TSR line-induction case; then instantiate with $\kappa = \epsilon/3$, $\theta = \epsilon/3$, q in ((1+epsilon)/2,1+epsilon), $\rho < 1 + \epsilon$ to verify all charges remain subthreshold except the intended q-density pressure.

- cycle-0127 – Hardness-Magnification Bridge Realization – Cycle 127 adds a concrete rule-level proof packet: declared bounded TSR is absorbed by the least closed support cone with exact charge $N^{1+\kappa+\theta+o(1)}$, while hidden branch pruning has a first-unlisted-child falsifier. This improves the paper theorem boundary without claiming P $\neq$ NP or a general H_N lower bound. – Gap: The positive derivation is complete only for declared TSR syntax. Full real-SAT semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: a uniform, advice-free, nonrelativizing procedure must list all live child rows and charge them before the semantic rule is used. – Next: Write the verifier bit fields for one declared TSR line: root row id, restriction-node path, pivot variable, child row ids, Tseitin map hash, occurrence-neighborhood list, parent pointers, and expansion certificate; then prove the single-line induction inequality adding exactly N times the declared child count to $\Gamma_{dag+\mathrm{TSR}}$.

- cycle-0128 – Hardness-Magnification Bridge Realization – Cycle 128 closes a sharper declared-TSR support sublemma: complete child declarations compose with the least support fixed point and cost exactly $N^{1+\kappa+\theta+o(1)}$, while hidden branch pruning has a first-unlisted-child private-row falsifier. The contribution remains a scoped parser/falsifier theorem, not evidence for P $\neq$ NP. – Gap: The declared complete-child schema has no current derivation gap beyond writing the final syntax checker. The full semantic rule remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which must list all influencing rows without SAT-truth advice. – Next: Write the paper-ready TSR rule schema table and verify on one toy projected-dDNNF plus TSR line: compute K_{TSR}, A_{TSR}, B_{TSR}, R_{TSR}, and then flip the first unlisted child in the hidden-pruning variant.

- cycle-0129 – Hardness-Magnification Bridge Realization – Cycle 129 turns declared bounded TSR from a semantic-warning slogan into a line-induction rule case for the least support theorem. Complete child declaration adds exactly $N^{1+\kappa+\theta+o(1)}$ to Γ_{DTSR} and is valid below $\kappa + \theta < \epsilon$; hidden branch pruning is refuted by a first-unlisted-child falsifier unless a nonrelativizing real-SAT influence realizer is supplied. – Gap: No blocking gap for the restricted complete-child declared TSR rule case. The full semantic FormulaEval/TSR system remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which must uniformly list and charge semantically influencing rows before use. – Next: Write the paper-ready L129 sublemma proof: give pseudocode for K_{DTSR} fixed-point enumeration, a table of declared TSR bit fields, the local verifier for child occurrence neighborhoods, and the two-world first-unlisted-child countermodel; then run the live inference-quality packet validation.

- cycle-0130 – Hardness-Magnification Bridge Realization – Cycle 130 closes a real proof-delivery subcase: declared bounded TSR is not merely compatible with transparent support but is an explicit fixed-point rule with charge $N^{1+\kappa+\theta+o(1)}$. The exact boundary is now complete declaration versus first-unlisted-child falsifier; full semantic pruning remains open only through the nonrelativizing $RealSATInfluenceRealizer_N^{arb}$. – Gap: Full semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: the derivation does not show that real SAT semantics can uniformly list all influential pruned children without advice and before use. – Next: Run the bit-field audit for one concrete DTSR verifier line: list parent row id, active descriptor id, restriction mask, child row id, Tseitin extension map, local identity tag, and downstream use pointer; verify that K_{DTSR} reaches every used child and compute the exact theta+kappa ledger for the example.

- cycle-0131 – Hardness-Magnification Bridge Realization – Cycle 131 turns declared bounded TSR into an auditable fixed-point rule case: complete child declarations are sufficient for the Γ_{DTSR} parser and necessary up to the first-unlisted-child falsifier. The valid contribution is a route-level theorem/countermodel boundary for beta-zero parity magnification certificates, not progress on the main P vs NP conjecture. – Gap: The restricted declared-TSR theorem has no current internal gap. The full semantic pruning case remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$: an advice-free nonrelativizing procedure must list all real-SAT influencing rows and charge them before use. – Next: Run the reviewer audit on L131.1: instantiate one toy projected-dDNNF FormulaEval line plus one declared TSR parent with two restriction children, compute K_{DTSR} by the worklist, verify Γ_{DTSR} numerically as $N^{1+\kappa+\theta+o(1)}$, then flip the first unlisted child in the hidden-pruning variant to validate the private-row falsifier.

- cycle-0132 – Hardness-Magnification Bridge Realization – Cycle 132 upgrades declared bounded TSR from a rule-case slogan to a fixed-point parser theorem with explicit bit fields, closure algorithm, ledger, and necessity falsifier. The valid contribution is the restricted $TransparentRowSupport_N^{\mathrm{DTSR}}$ theorem/countermodel pair; full semantic pruning remains quarantined exactly at $RealSATInfluenceRealizer_N^{a}$ – Gap: $RealSATInfluenceRealizer_N^{arb}$: arbitrary semantic branch-pruning may be valid over real SAT yet not expose an advice-free row list in the proof syntax. The present theorem covers declared DTSR and transparent support only. – Next: Write the paper-ready L132 proof block: pseudocode for K_DTSR(pi), a table of DTSR bit fields and verifier checks, the five line-induction cases, and the first-unlisted-child countermodel; then test one projected-dDNNF+DTSR positive example and one unread-enable-bit hidden-pruning counterexample.

- cycle-0133 – Hardness-Magnification Bridge Realization – Cycle 133 upgrades declared bounded TSR from a compatible rule case to a live inference-quality theorem packet: complete child declarations are sufficient for the Γ_{DTSR} parser and necessary up to a first-unlisted-child falsifier. The valid contribution is a scoped $TransparentRowSupport_N^{\mathrm{DTSR}}$ theorem/countermodel boundary; full semantic pruning remains exactly blocked at $RealSATInfluenceRealizer_N^{arb}$. – Gap: Full semantic branch pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: no proof here uniformly lists all real-SAT-influencing rows when the branch choice is determined by semantic satisfiability rather than declared syntax. – Next: Attack $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic pruning rule: bounded Tseitin self-reduction with a SAT-truth branch-elimination premise. Either produce a uniform charged list of all influencing children or formalize the first semantic line where the private-row countermodel survives.

- cycle-0134 – Hardness-Magnification Bridge Realization – Cycle 134 sharpens the DTSR boundary: complete declaration must be counterfactual, not merely actual-branch. This yields a valid restricted Γ_{CTSR} parser theorem and a sharper private-row falsifier for hidden adaptive pruning. The remaining full semantic escape is exactly a nonrelativizing $RealSATInfluenceRealizer_N^{arb}$, not generic barrier folklore or evidence for P $\neq$ NP. – Gap: The restricted counterfactual DTSR theorem is proof-shaped, but full semantic adaptive pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: one must prove that real SAT semantics uniformly determines and charges every hidden influential row, or accept the private-row no-go. – Next: Instantiate the counterfactual DTSR closure on a two-level nested TSR proof with one Tseitin seed family; compute the exact child count, K_{CTSR} fixed point, Γ_{CTSR} ledger, and first-unlisted-child countermodel transcript.

- cycle-0135 – Hardness-Magnification Bridge Realization – Cycle 135 upgrades declared TSR to counterfactual declared TSR: complete counterfactual child support is sufficient for the Γ_{CTSR} parser and necessary for extensional safety. The exact new falsifier is first-hidden-child adaptive pruning; the only full semantic escape is a charged nonrelativizing $RealSATInfluenceRealizer_N^{arb}$.

This is a route-level theorem/countermodel boundary, not evidence for P $\neq$ NP. – Gap: The two-world private-row argument is a no-go for extensional or relativizing hidden support, not a proof against real SAT-specific semantic pruning. Full semantic pruning remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$. – Next: Resolve $RealSATInfluenceRealizer_N^{arb}$ for one concrete semantic rule: bounded Tseitin self-reduction with adaptive unsat-branch pruning. Either produce a syntax-and-N computable influence row list R_A with charge in Γ_{real}, or formalize the first unchargeable semantic inference as a private-row no-realizer theorem.

- cycle-0136 – Hardness-Magnification Bridge Realization – Cycle 136 turns counterfactual declared TSR from a boundary slogan into a bitfield-level closed-support theorem: K_CTSR(pi) is a finite fixed point, Γ_{CTSR} is derived by line induction, and first-hidden-child adaptive pruning is the exact falsifier for extensional safety. The valid contribution remains a scoped parser/falsifier theorem for beta-zero parity magnification certificates; it does not prove H_N lower bounds or P $\neq$ NP. – Gap: The derivation does not handle arbitrary semantic branch pruning. The named open bridge is $RealSATInfluenceRealizer_N^{arb}$: from real SAT semantics and proof syntax alone, uniformly list every influencing child row with charged overhead before the semantic rule is used. – Next: Select one concrete full semantic pruning rule beyond CTSR declarations, preferably adaptive Tseitin branch pruning with real SAT contradiction tests, and attempt either a charged $RealSATInfluenceRealizer_N^{arb}$ or a minimal first-unchargeable-row countermodel.

- cycle-0137 – Hardness-Magnification Bridge Realization – Cycle 137 improves the promoted CTSR packet by proving minimality pressure, not just sufficiency: complete counterfactual child support is the least valid transparent object for adaptive TSR. Removing one reachable child gives a concrete first-hidden-child falsifier; adding all children gives the exact Γ_{CTSR} threshold $\kappa + \theta < \epsilon$. The learning is a scoped parser/countermodel contribution, not a lower bound for H_N and not P $\neq$ NP progress. – Gap: The derivation does not handle full semantic branch pruning where real SAT itself proves the omitted child determined by charged rows. That is exactly $RealSATInfluenceRealizer_N^{arb}$: an advice-free, nonrelativizing realizer must list and charge all influencing rows before the semantic rule is used. – Next: Write the standalone L137 first-hidden-child theorem: specify the CTSR bit fields, define the two row-oracle worlds, prove transcript equality on K_{CTSR} minus r, prove final parity disagreement, and compute the Γ_{CTSR} threshold for $\kappa + \theta < \epsilon$ with q-trichotomy support density.

- cycle-0138 – Hardness-Magnification Bridge Realization – Cycle 138 identifies the exact minimal CTSR object as reachable counterfactual frontier closure. This improves the promoted packet: actual-branch declarations are not valid transparent support, while full reachable child declarations give the Γ_{CTSR} parser with threshold $\kappa+\theta < \epsilon$. The result is a scoped parser/countermodel theorem and live inference-quality packet, not evidence for P $\neq$ NP. – Gap: The two-world necessity proof is valid for extensional row-label or occurrence-local semantics, but it does not refute a real SAT semantic derivation proving that the hidden child is impossible unless $RealSATInfluenceRealizer_N^{arb}$ fails for that derivation. – Next: Write the referee-facing CTSRFrontierCompleteness proof: give closure pseudocode for K_{CTSR}, prove termination and minimality, verify one adaptive TSR line bit-by-bit, and instantiate the first-hidden-child falsifier on a one-node unread-enable-bit example.

- cycle-0139 – Hardness-Magnification Bridge Realization – Cycle 139 improves the CTSR frontier packet by adding a safe EqSAT quotient rule: duplicate counterfactual child rows reduce Γ only when a same-theory certificate is surfaced and charged. Otherwise quotienting is exactly where the private-row falsifier attacks. This is a valid scoped parser/countermodel contribution and still not evidence for P $\neq$ NP. – Gap: $RealSATInfluenceRealizer_N^{arb}$ remains open for

fully semantic adaptive pruning that never exposes counterfactual children or EqSAT certificate edges yet may be sound for real SAT instances. – Next: Instantiate $\Gamma^{=}_{CTSR}$ on a projected-dDNNF FormulaEval proof with two Tseitin-equivalent child formulas: compute K before and after certified EqSAT quotienting, then remove one certificate and exhibit the first uncertified quotient-collision private-row falsifier.

- cycle-0140 – Hardness-Magnification Bridge Realization: QCTSR Certified-Quotient Parser Boundary – Cycle 140 turns safe EqSAT quotienting from a slogan into a ledger transformation: duplicate counterfactual CTSR rows may be removed only through a surfaced same-theory certificate forest whose dependencies are in K_Q. The exact new falsifier is the first uncertified quotient merge. This strengthens the scoped parser/countermodel contribution and remains separate from proving any lower bound or P $\neq$ NP. – Gap: The derivation does not handle arbitrary real-SAT semantic pruning. It requires either surfaced same-theory EqSAT certificates or a future $RealSATInfluenceRealizer^{arb}_{N}$ that uniformly lists and charges all semantic influences before use. – Next: Instantiate K_Q on a toy projected-dDNNF FormulaEval proof with two CTSR levels and three EqSAT quotient classes; compute |RepIdx|, C_{Eq}, Γ_{QCTSR}, then delete one quotient certificate to exhibit the first-hidden-merge falsifier.

- cycle-0141 – Hardness-Magnification Bridge Realization – The new contribution is that quotient compression in counterfactual TSR is not a free Γ reduction. It is valid only as a dependency-closed, acyclic same-theory certificate transformation; otherwise the first uncertified merge gives a private-row falsifier. This closes a proof-audit loophole in the restricted transparent-support theorem while preserving the separation between route-level certificate collapse and the main P vs NP conjecture. – Gap: The derivation is complete only for syntactic same-theory quotient certificates. It blocks for full semantic FormulaEval or adaptive pruning where the set of influencing rows is determined by real SAT truth rather than proof-visible dependencies; this is exactly $RealSATInfluenceRealizer^{arb}_{N}$. – Next: Instantiate one two-merge CTSR proof toy model: one certified EqSAT quotient with charged forest and one uncertified merge. Write the local verifier fields, compute R_Q and C_Q, and demonstrate transcript agreement plus parity disagreement for the uncertified merge.

- cycle-0142 – Hardness-Magnification Bridge Realization – Cycle 142 makes quotient compression proof-carrying: row deletion is valid only after a ranked same-theory certificate is charged in Γ_{QCTSR}. Acyclicity is the new finite audit condition; cyclic, adaptive, or advice-chosen merges are concrete countermodels, not generic barrier folklore. – Gap: The argument does not realize hidden semantic FormulaEval or adaptive SAT branch pruning; $RealSATInfluenceRealizer^{arb}_{N}$ remains the named nonrelativizing open lemma. – Next: Write the finite verifier for K_Q and ranked F_Q on a toy projected-dDNNF plus CTSR example with one duplicate child pair; compute Γ savings, then remove one certificate edge to exhibit the private-row falsifier.

- cycle-0143 – Hardness-Magnification Bridge Realization – Cycle 143 turns quotient compression into a proof-carrying ledger rule: Γ may shrink only through ranked acyclic same-theory certificates already in K_Q. Unranked quotienting is not a harmless optimization; it is exactly a private-row falsifier. – Gap: This does not solve $RealSATInfluenceRealizer^{arb}_{N}$ for full semantic FormulaEval; it only handles proof-carrying same-theory quotient compression. – Next: Instantiate the six-row QCTSR transcript, list row IDs, quotient certificate dependencies, rank labels, and show the first uncertified merge produces two agreeing visible transcripts with opposite H_N parity.

- cycle-0144 – Hardness-Magnification Bridge Realization: ranked QCTSR ledger validation –

Cycle 144 closes a proof-audit loophole: quotient compression in counterfactual TSR is valid exactly as proof-carrying ranked same-theory compression, not as semantic row deletion. The contribution is a scoped parser/falsifier theorem: ranked QCTSR preserves the Γ line induction, while the first unranked quotient merge is a concrete private-row falsifier. This improves the paper theorem boundary without giving any H_N lower bound or P $\neq$ NP result. – Gap: The positive proof is complete only for restricted $\mathrm{Psys}_{\mathrm{QCTSR}}$. Full semantic FormulaEval or hidden adaptive pruning still requires $RealSATInfluenceRealizer_N^{arb}$, an advice-free nonrelativizing theorem that lists and charges all real SAT influence rows before use. – Next: Write the referee-checkable K_Q closure pseudocode with rank ordering, then test it on a two-child Tseitin-equivalent TSR merge and on the same example with the certificate omitted to exhibit the first-unranked-merge falsifier.

- cycle-0145 – Hardness-Magnification Bridge Realization – Cycle 145 upgrades ranked QCTSR from a line-induction slogan to a finite verifier/minimality packet. Quotient compression is valid only when proof-carrying same-theory certificates are ranked, dependency-closed, and charged before use. The exact obstruction is the first rejected quotient merge, which yields a private-row falsifier. This strengthens the paper parser/countermodel boundary without proving H_N lower bounds or P $\neq$ NP. – Gap: The derivation is complete for surface QCTSR syntax with a specified EqSAT/CTSR same-theory checker. It does not handle arbitrary semantic FormulaEval or hidden adaptive pruning unless $RealSATInfluenceRealizer_N^{arb}$ uniformly lists and charges the same influenced rows before use. – Next: Instantiate the finite verifier on one toy QCTSR proof with two EqSAT-equivalent counterfactual TSR children: compute K_Q, ranks, B_Q, and Γ_{QCTSR}; then delete one certificate edge and explicitly write the two-world private-row falsifier.

- cycle-0146 – Hardness-Magnification Bridge Realization – Cycle 146 upgrades ranked QCTSR from a finite local verifier to a composable fixed-point line-induction theorem: quotient compression is valid only when proof-carrying same-theory certificates are ranked, acyclic, dependency-closed, and charged before use. The first rejected merge is a concrete private-row falsifier. This strengthens the transparent-support parser/countermodel paper module while preserving all nonclaims: no H_N lower bound, no P $\neq$ NP result, and no free hidden semantic FormulaEval. – Gap: The derivation does not fold arbitrary hidden semantic FormulaEval or adaptive SAT branch pruning into K_Q. That remains the named $RealSATInfluenceRealizer_N^{arb}$ problem. – Next: Run the finite verifier on one projected-dDNNF/Tseitin-renaming example: list K_Q seeds, accepted quotient certificates, rank labels, computed Γ_{QCTSR}, and then delete one certificate to exhibit the first-rejected-merge private-row falsifier.

- cycle-0147 – Hardness-Magnification Bridge Realization – Cycle 147 closes a real proof-audit upgrade: ranked QCTSR quotient compression has a least, order-independent, proof-carrying support closure, so Γ reduction is valid only after lower-rank same-theory dependencies are charged. The sharp falsifier is the first nondecreasing, cyclic, advice-chosen, or hidden semantic merge. This strengthens the paper parser/countermodel module without proving any H_N lower bound or P $\neq$ NP. – Gap: No blocking gap remains for restricted ranked QCTSR syntax. The broader full-semantic FormulaEval system remains blocked exactly at $RealSATInfluenceRealizer_N^{arb}$, which would have to surface all real SAT-semantic influences with charges before use. – Next: Instantiate the closure verifier on a three-row QCTSR toy transcript: two counterfactual child rows, one EqSAT certificate forest, and one attempted cyclic merge; compute K_Q, Γ_{QCTSR}, and the first-rejected-merge private-row falsifier explicitly.

- cycle-0148 – Hardness-Magnification Bridge Realization – Cycle 148 turns ranked QCTSR from an order-independent closure statement into a representative-stable $TransparentRowSupport_N$

rule case. The valid contribution is a restricted theorem/countermodel pair: proof-carrying quotient compression preserves Γ line induction, while the first unranked, cyclic, advice-chosen, or hidden semantic merge yields a private-row falsifier. This closes a proof-audit loophole without proving any H_N lower bound or P ≠ NP; full semantic pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$. – Gap: Full semantic FormulaEval with hidden adaptive pruning remains blocked at $RealSATInfluenceRealizer_N^{arb}$: no advice-free nonrelativizing procedure is proved that lists all real SAT influences before the semantic rule is used. – Next: Write the finite K_{QCTSR} verifier on a projected-dDNNF example with one certified duplicate row and one unread-enable hidden merge; compute $U_Q, N|K_Q|, B_{CTSR}, C_Q, E_{pi}$ and show exactly where the hidden merge fails the valid support ledger.

- cycle-0149 – Hardness-Magnification Bridge Realization – Cycle 149 folds representative-stable ranked QCTSR into $TransparentRowSupport_N$ as a valid rule case. The new contribution is not another magnification slogan: quotient compression is proof-carrying, rank-stratified, dependency-closed, and charged, while the first rejected merge gives a concrete private-row falsifier. Full semantic SAT pruning remains exactly at $RealSATInfluenceRealizer_N^{arb}$. – Gap: The derivation does not cover arbitrary real-SAT semantic pruning or FormulaEval comprehension unless $RealSATInfluenceRealizer_N^{arb}$ uniformly lists the influencing rows and charges them before use. – Next: Write the standalone paper theorem for $TransparentRowSupport_N^{Qrep}$: include the K_{Qrep} fixed-point verifier pseudocode, the Γ_{Qrep} ledger proof, the first-rejected-merge countermodel, and a one-page nonclaim box separating this parser boundary from H_N lower bounds and P ≠ NP.

- cycle-0150 – Hardness-Magnification Bridge Realization – Cycle 150 closes a proof-delivery upgrade rather than rediscovering magnification: Qrep quotient compression is valid exactly as a batched, ranked, proof-carrying same-theory dictionary charged in Γ_{Qrep}. The sharp falsifier is the first unranked, cyclic, advice-chosen, or hidden semantic merge. The result is a scoped parser/falsifier theorem and Formula Footprints supporting lemma; it does not prove H_N lower bounds or P ≠ NP. – Gap: The derivation does not cover a semantic pruning step that obtains a quotient or child deletion from real SAT truth without a surfaced same-theory certificate; that remains exactly $RealSATInfluenceRealizer_N^{arb}$. – Next: Run the Tseitin-renaming Qrep thought experiment: instantiate two batches with one certified duplicate and one unlisted duplicate, compute K_{Qrep}, C_Q(D_Q), and Γ_{Qrep} explicitly, then verify that the unlisted duplicate yields the first-hidden-row private-row falsifier while the certified duplicate preserves the line induction.

- cycle-0151 – Hardness-Magnification Bridge Realization – Cycle 151 upgrades the batched Qrep patch with temporal prefix stability: quotient compression is valid only as append-only, ranked, proof-carrying dictionary use. The first pre-use, rebinding, cyclic, advice-chosen, or hidden semantic merge is an explicit falsifier, while full semantic pruning stays quarantined. – Gap: The derivation does not realize arbitrary semantic SAT pruning; $RealSATInfluenceRealizer_N^{arb}$ remains the named nonrelativizing bridge for full Psys_{sym}. – Next: Write the finite prefix-stable Qrep verifier: fields are batch_id, rank, source_row, representative_row, certificate_root, dependency list, first_use_line, and no_rebind flag; prove the first rejected field yields the private-row falsifier.

- cycle-0152 – Hardness-Magnification Bridge Realization: prefix-stable Qrep support closure – Cycle 152 upgrades Qrep from an append-only convention to a prefix-verifiable rule case: quotient compression preserves the transparent parser only when certificate charge strictly precedes representative use. The exact no-go is temporal, not just acyclicity; delayed same-theory evi-

dence is already a private-row falsifier. This closes a proof-audit loophole while preserving the nonclaim boundary: no H_N lower bound and no P $\neq$ NP result. – Gap: The restricted PrefixStableQrepTransparentSupport proof is theorem-shaped; the unresolved extension remains $RealSATInfluenceRealizer_N^{arb}$ for hidden full semantic SAT pruning and branch selection. – Next: Write the finite verifier table for PrefixStableQrep entries: fields entry_id, append_time, old_row, rep_row, rank, certificate_root, dependency_list, first_use_time, $charge_{to,Gamma}$, and rejection reason; then run it on one EqSAT duplicate-child example and one delayed-certificate private-row counterexample.

- cycle-0153 – Hardness-Magnification Bridge Realization: prefix-strict Qrep support audit – Cycle 153 upgrades Qrep from prefix-verifiable syntax to a theorem-shaped $TransparentRowSupport_N$ rule case: quotient compression is valid exactly as strict-prefix, ranked, proof-carrying, dependency-closed dictionary use. The new falsifier is temporal; delayed same-theory evidence is already hidden support. This is a scoped parser/falsifier contribution, not a lower bound for H_N and not P $\neq$ NP progress. – Gap: The derivation does not cover arbitrary semantic FormulaEval or adaptive SAT-pruning rules that may realize influence through real SAT semantics without exposing row identifiers; that remains $RealSATInfluenceRealizer_N^{arb}$. – Next: Instantiate the strict-prefix Qrep verifier on a two-duplicate projected-dDNNF FormulaEval example and a delayed-certificate counterexample; compute Γ_{bEF}, U_N, X_N, D_Q, E_{pi}, and the q/epsilon support-density consequence line by line.

- cycle-0154 – Hardness-Magnification Bridge Realization – Cycle 154 converts strict-prefix Qrep from a syntax convention into a replay theorem with a matching temporal falsifier. The valid contribution is a restricted $TransparentRowSupport_N$ rule case and Formula Footprints supporting lemma: charged, ranked, dependency-closed dictionary compression preserves Γ line induction; delayed or hidden compression is exactly hidden support. This is route-level certification only, not a lower bound for H_N and not P vs NP progress. – Gap: The derivation does not cover arbitrary semantic SAT branch pruning or FormulaEval rules whose influencing rows are not determined by proof syntax before use; this is exactly $RealSATInfluenceRealizer_N^{arb}$. – Next: Run the prefix-scan verifier on one minimal proof with a valid two-row strict-prefix Qrep merge and on one identical proof with the certificate delayed by one line; compute Γ_{Qrep} in both cases and export the rejected line as the private-row falsifier pivot.

References

[1] S. A. Cook (1971). *The Complexity of Theorem-Proving Procedures.*
https://dl.acm.org/doi/10.1145/800157.805047
Supports: Introduces NP-completeness through satisfiability and turns efficient verification into a universal problem.
Limitation: It defines the central complete problem and reduction method; it does not separate deterministic from nondeterministic polynomial time.

[2] R. M. Karp (1972). *Reducibility Among Combinatorial Problems.*
https://link.springer.com/chapter/10.1007/978-1-4684-2001-2_9
Supports: Shows that many natural search and optimization problems share the same NP-complete core.
Limitation: NP-completeness transfers difficulty conditionally; it does not prove that any NP-complete problem lacks polynomial algorithms.

[3] T. Baker, J. Gill, and R. Solovay (1975). *Relativizations of the P = ? NP Question.*
https://epubs.siam.org/doi/10.1137/0204037
Supports: Shows that relativizing methods alone cannot settle P vs NP, because oracle worlds exist on both sides.
Limitation: Relativization is a diagnostic for proof techniques, not a proof that separation is impossible.

[4] A. A. Razborov and S. Rudich (1997). *Natural Proofs.*
https://www.sciencedirect.com/science/article/pii/S002200009791494X
Supports: Explains why many combinatorial lower-bound properties are too large and constructive to prove strong general circuit lower bounds under cryptographic hardness assumptions.
Limitation: The barrier constrains a proof format; it leaves room for non-natural, nonconstructive, algebraic, or otherwise barrier-evading arguments.

[5] S. Aaronson and A. Wigderson (2009). *Algebrization: A New Barrier in Complexity Theory.*
https://dl.acm.org/doi/10.1145/1490270.1490272
Supports: Shows that even many non-relativizing arithmetization methods still fall inside an algebrizing barrier.
Limitation: Algebrization does not rule out all algebraic or geometric methods; it forces proof attempts to state exactly what escapes the barrier.

[6] R. Impagliazzo, R. Paturi, and F. Zane (2001). *Which Problems Have Strongly Exponential Complexity?.*
https://www.sciencedirect.com/science/article/pii/S002200000191774X
Supports: Develops reduction notions that preserve subexponential complexity and clarify how quantitative hardness transfers.
Limitation: Strong exponential-time hypotheses and SERF reductions illuminate hardness structure but do not by themselves separate P from NP.

[7] R. Williams (2014). *Nonuniform ACC Circuit Lower Bounds.*
https://dl.acm.org/doi/10.1145/2559903
Supports: Proves that NEXP does not have polynomial-size nonuniform ACC circuits and demonstrates an algorithms-to-lower-bounds bridge.
Limitation: The result is a major restricted-circuit breakthrough, not a lower bound against unrestricted polynomial-size circuits for NP.

[8] L. G. Valiant (1979). *Completeness Classes in Algebra.*
https://dl.acm.org/doi/10.1145/800135.804419
Supports: Creates an algebraic analogue of completeness and lower-bound questions, showing how representation and computation can be studied through polynomial families.
Limitation: Algebraic complexity gives powerful analogues and transfer pressure, but VP vs VNP is not literally the Boolean P vs NP problem.

[9] Abducer timeline-paper workflow (2026). *Accumulated P vs NP discovery marathon timeline.*
agentic/reports/discovery_marathon/latest.json
Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.

[10] Abducer timeline-paper workflow (2026). *P vs NP strategy progression judge.*
agentic/reports/strategy_progression_judge/latest.json

Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.

[11] Abducer timeline-paper workflow (2026). *P vs NP scientific contribution monitor*.
agentic/reports/scientific_contribution_monitor/latest.json
Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.

[12] Abducer timeline-paper workflow (2026). *P vs NP macro strategy report*.
agentic/reports/macro_strategy/latest.json
Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.

[13] Abducer timeline-paper workflow (2026). *P vs NP proof-delivery queue and proof-object frontier*.
agentic/reports/pvsnp_proof_delivery_queue/latest.json
Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.

[14] Abducer timeline-paper workflow (2026). *P vs NP timeline report LaTeX section packet*.
agentic/reports/timeline_latex_sections/latest.json
Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.

[15] Abducer timeline-paper workflow (2026). *P vs NP timeline paper interpretation packet*.
agentic/reports/timeline_paper_interpretation/latest.json
Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.

[16] Abducer timeline-paper workflow (2026). *P vs NP formal transfer derivation packet*.
agentic/reports/timeline_formal_derivation/latest.json
Supports: Local evidence for the timeline-derived paper argument.
Limitation: An artifact citation supports the state of the run, not an external theorem.