

PHYSICAL TOUCH OF VIRTUAL OBJECTS

ROKAS ANDRIJAUSKAS 4129184

Masters Project in Engineering (Robot Systems)
Supervisor: Xiaofeng Xiong

June 2025



The Maersk Mc-Kinney Moeller Institute
University of Southern Denmark

Character count: 40329

Abstract

Many companies are struggling to combine Robotics and Machine Learning . .

Contents

Contents	ii
1 Introduction	1
1.1 Background	1
1.2 Problem statement	1
1.3 Objective	2
1.4 Research question	2
2 Exoskeleton	3
2.1 Background	3
2.2 Analysis and Design 1	11
2.3 Implementation 1	12
2.4 Analysis and Design 2	20
2.5 Conclusion	20
3 Algorithms	22
3.1 Background	22
3.2 Analysis and Design	23
3.3 Implementation	23
3.4 Conclusion	23
4 Discussion	24
5 Conclusion	25
A Appendix	26
Bibliography	27

1 Introduction

1.1 Background

Recent advancements in computer hardware and software have enabled nearly photorealistic and real-time simulation of virtual worlds. Technologies such as augmented reality (AR) and virtual reality (VR) enhance the immersion of these simulated world by overlaying information over the user's field of view. Since the technology is still in its early stages, there is still a lot of unsolved problems and progress to be made. The immersion into virtual worlds is usually achieved through the use of a headset. Early headsets were really bulky, had low resolution and short battery life. Naturally most of the research was focused on tackling these problems. In the present day we have consumer grade devices like meta quest 3 and apple vision pro that offer excelent battery life, sharp visuals and immersive audio. In the future we could expect this technology to shrink to the size of regular pair of glasses. Resarchers at Meta are already stepping in that direction with ther recently unveiled Orion glasses.

The hardware improvements also made the creation of Artificial Intelligence (AI) possible. It was theorized as early as 1950s by Alan Turing if machines are capable of thinking [27]. In 1959 Arthur Samuel coined the term 'machine learning', but Ii was only in 1990s that hardware and algorithms were sufficiently advanced that machine learning began to gain traction. Due to well-defined environments and rules, games were the first domain to notice the impact of AI. In 1997, Deep Blue [2] managed to beat the world chess champion Garry Kasparov. As computers following Moore's law [21] grew in power, more breakthroughs began to emerge. Currently, in 2025, the AI is capable creating images, videos, music, text, research podcasts and even interactive worlds.

The artificial intelligence also gave rise to the robotics industry. AI is transforming robots from rigid, pre-programmed machines into intelligent systems capable of performing increasingly complex tasks. Robots are often trained in simulated environments as this allows for faster and safer training without needing to worry about demaging robot or the environment.

1.2 Problem statement

Despite the fact that VR and AR technologies are rapidly improving, there is still a major problem, these technologies usually immerse only two senses: sight

and hearing, but we, as humans, have five: sight, hearing, taste, smell, and touch. This means that there is still a lot of room for improvement as inclusion of additional senses would provide a more immersive VR/AR experience.

1.3 Objective

The thesis aims to address the limitation of VR technology by incorporating the sense of touch into the computer-simulated virtual worlds. There are two objectives, first, following engineering design process, will be focused on developing a portable exoskeleton capable of giving its user an immersive sense of touch in VR. Second, will be dedicated to exploring if the developed exoskeleton could aid in the process of training robots in simulated world.

1.4 Research question

Can a portable exoskeleton that gives its users the ability to touch virtual objects be created in a way that it is a viable solution to aid in the training of the robots in the simulated environments?

2 Exoskeleton

This chapter delves into the research, development and testing of the portable exoskeleton.

2.1 Background

In this section a comparison of physics world simulators and state of the art exoskeletons that attempt to incorporate touch into virtual environments will be made.

Virtual environment

The hard requirements for the choice of the simulator for this thesis are simple, it must have:

1. VR support. Users should be able to interact with the environment.
2. Support of the soft-body physics.

A great to have features for the simulator are the following:

1. Free and open-source, so the research in this thesis could be easily accessible and replicated.
2. Fast, so the development would go smoothly on an affordable computer.
3. Popular, it is easier to fix problems if we can find people in forums who already had them.
4. Easy to learn, it would be great to have more time on research and implementation than learning the engine.
5. Used in robotics applications.

Numerous physics engines have been developed in which virtual environments can be created. Most notable are [5]: Mujoco, Gazebo, CoppeliaSim, Webots, PyBullet and SOFA.

Multi-Joint dynamics with Contact (MuJoCo) [26] is a popular physics engine that required a commercial license up until recently. In 2021 Google Deepmind acquired the simulator and made it freely available for everyone [7]. In 2022, they open-sourced and published it on Github. The MuJoCo is widely used

in research due to its contact stability [29]. State of the art research leverages MuJoCo for training robotic manipulator policies in simulation. It is worth noting that MuJoCo lacks built-in functionality for inverse kinematics or path planning.

Gazebo is another popular robotics simulator that is widely used in research. One of the things that makes it so appealing is support of Robotics Operating System [22] (ROS). ROS houses a expansive set of libraries and tools for building robotics applications. ROS-based software is platform and language agnostic making incorporation of user developed libraries very easy. The working principle that allows for this seamless integration is Publish/Subscribe model. ROS processes called nodes, communicate between each other by publishing messages to topics and receiving messages from subscribed topics allowing interprocess communication. A study has shown that if the robot model in Gazebo was created properly, the code that was used in simulation can be directly reused in real robot without any modifications [25]. Unfortunately the engine does not support soft-body physics natively. There are however attempts to bridge this gap between rigid-body and soft-body physics. One study developed a ROS-Gazebo Toolbox that allows user to bring Articulated Soft Robots in the simulation with satisfactory Sim2Real performance [18]

CoppeliaSim, formerly known as V-REP [24], has an easy learning curve with it's GUI driven design and user- centric feature including forward and inverse kinematics, sensor simulation, motion and path planning. Built around a distributed control architecture, the engine supports scripts written in Lua or Python and plugins written in C/C++ that act as synchronous controllers. This is useful in multi-robot setups. It also has ROS support, but unlike Gazebo, it is secondary to the engine's design. CoppeliaSim supports 5 different physics engines (MuJoCo, Bullet Physics, ODE, Newton and Vortex Dynamics), but the support for soft body and deformable objects is lacking.

Webots [19], started in 1996, is an open-source simulator witten in C++. It has a large collection of sensors, actuator and robot models. The simulator is beginner friendly with polished GUI that makes it easy to build models from scratch. One study comparing robot simulators has shown that Webots was least resource intensive, it the lowest CPU usage compared to CoppeliaSim and Gazebo [1]. These reasons make the simulator appealing for fast prototyping and multi-robot simulation purposes. Despite these great features the simulator lacks soft-body dynamics support.

Bullet is a professional library written in C++. It is videly used in games, visual effects and robotics applications. It can simulate Soft-Body as well as Rigid-Body physics with discrete and continuous collision detection. The PyBullet is a library with Python bindings that interact with the Bullet engine.

Simulator	Force Sensor	Inverse Kinematics	Soft-Body	VR	ROS
MuJoCo	✓	✗	✓	✓	✗
Gazebo	✓	✓	✗	✓	✓
CoppeliaSim	✓	✓	✗	✓	✓
Webots	✓	✗	✗	✓	✓
PyBullet	✓	✓	✓	✓	✗

Table 2.1: Feature Comparison of Popular Physics Simulators for Robotics Applications

This approach merges best of both worlds, the C++ speed and Python’s ease of use. PyBullet also has reinforcement learning, robotics simulation and VR support.

From the examined physics engines only MuJoCo and PyBullet support deformable objects and virtual reality. PyBullet was chosen as the physics engine for this thesis as it has a well documented VR section and broader VR support. Teleoperation with MuJoCo is only available through the use of MuJoCo HAPTIX [14] whereas PyBullet support a variety of VR controllers.

Exoskeletons

The human skin is the largest organ of the body, it plays a crucial role in the perception of touch and temperature. The density of touch receptors varies significantly across different skin regions. The palms of the hand, especially fingertips are one of the most touch sensitive parts of the body. These areas have a heightened sensitivity, because hands serve as the primary interface for interacting with the environment, feeling the objects temperature, texture and weight. Given the complexity and cost associated with the development of a full body exoskeleton, the focus of this thesis will exclusively be on create an exoskeleton for the hand only. There have already been multiple attempts to create an exoskeleton that enable user to feel the virtual objects. Some of which have even become commercially available.

Types of Feedback

There are multiple forms of haptic feedback a simple touch can provide. This section explore the different types of feedback and their significance in virtual interactions.

Transient contact and normal force play a fundamental role in perceiving the stiffness of an object. One study has shown that transient vibration combined with visuo-haptic illusion could successfully simulate this form of contact [4]. The results indicate that this type of contact can be modeled without requiring complex mechatronic or control systems.

Lateral stretch of the skin provide information about the weight of the object, while the stick-slip condition offers insight into when an object is about to be dropped. This information allows people to instinctively react by either gripping the object tighter to prevent slippage or try to catch it mid-air if it has already slipped. Various approaches and design methodologies have been investigated to replicate these tactile sensations in virtual environments [20][3].

Beyond force, pressure and friction feedback, the human skin is also adept at recognizing the texture of the objects. One study has shown that it is feasible to simulate texture perception using vibratory-only feedback by leveraging the spatial information of skin interactions with textured surfaces [28]. This suggests that a combination of finely tuned vibrations and high-resolution sensor data could enable realistic textural perception in virtual environments.

Temperature feedback is another important component of realistic haptic interactions. Temperature can provide important information about the type of material we are in contact with. Different heat flows and temperature gradients are experienced when touching objects due to the different thermal conductivity coefficients between materials. For example, when touching a metal or a wooden surface, even if both objects are at the same temperature, the metal will feel significantly colder than the wood. This is because the metal has much greater thermal conductivity than the wood. A wearable device that achieves temperature feedback has been proposed for the VR setting [10]. It contains a film with high thermal conductivity controller by Peltier element, which is coupled with a water-cooling heatsink in order to achieve the dynamic temperature simulation.

Although various studies have proposed solutions that simulate the individual aspects of the sense of touch, integrating multiple feedback modalities into a single, compact and lightweight exoskeleton remains a formidable engineering challenge. Combining force, texture, temperature, and friction feedback into a light, ergonomic and mass produced glove could be the goal for the future of haptic systems, however this thesis will exclusively focus on incorporating the sense the normal force exerted by the objects, as this is arguably the most important aspect of the touch as it allows users to feel the presence of the object.

Tracking

Hand tracking can be divided into two main categories: global position tracking and local position tracking. Global position tracking determines the whereabouts of the hand's location in the world space and local position tracking provides detailed information on the configuration and movement of the hand. Several technologies exist that can be attached to the exoskeleton to provide global position tracking.

Vive Tracker, the first commercially available VR tracker developed by HTC enable object and body tracking in virtual reality environments. They are compact, their dimensions are $70.9 \times 79.0 \times 44.1$ mm, lightweight, weighting only 75g and fully wireless, with battery life of up to 7.5 hours. These trackers can be attached to various body parts, such as hands, feet, or the waists, enabling accurate tracking of position and orientation in three-dimensional space. Their adaptability makes them a convenient off the shelf solution at a reasonable price point. The current market price is around 130€ per piece.

OptiTrack is a high-precision camera-based tracking system. They track the position of special reflective markers with a great accuracy. These markers are designed to reflect the infrared light emitted by OptiTrack camera system. By affixing these special reflective markers to an object of interest, the object can be successfully tracked. This method does not require a battery source on the exoskeleton, the marker are light, weighting only a couple of grams and they have no mechanical parts and the system offers a sub-millimeter precision. This method could provide an unparalleled user experience, but it does cost thousands and require significant setup in the room, making it a suitable option for research and industry applications rather than commercial use case.

To minimize costs and leverage existing VR hardware, some exoskeleton designs opt to incorporate standard VR controllers for global position tracking. These type of exoskeletons typically have a mount specifically designed for some type of VR controller, such as those used in HTC Vive or Oculus systems. This comes at almost no additional cost, but it also has significant the drawbacks. Firstly, the mount, buttons and other components inside the controller add unnecessary weight, secondly the form factor is designed to fit snugly in the palm of the hand, rather than be placed on the back of the hand, adding unnecessary bulk. These factors can potentially impact user's comfort and dexterity.

The local position tracking methods vary in complexity and accuracy. Valve Index Knuckles controllers utilize a proximity sensors to detect whether a user's finger is touching the controller or not. This allows for basic finger tracking, but it is limited in only 5 Degrees of Freedom (DOF) where each finger is in a binary state, either extended or flexed. This limits the realism of virtual hand interactions.

Data gloves provide a more refined finger tracking solution, offering continuous finger state tracking. Some data gloves [8] achieve that using flex capacitive stretch sensors. These sensors work due to their physical properties that resistance changes based on mechanical deformation. While they offer an accurate tracking, due to the nature how these sensors work, they are susceptible to

wear and thus have a limited life cycle. Modern flex capacitive stretch sensors achieve life cycle of over 1 million cycles, making their wear less of an issue. Some data gloves [16] achieve local position tracking using multiple inertial measurement units. This approach has an advantage of improved life cycle, as the sensors are purely electronic, but these type of gloves do experience “data drifting” which requires frequent recalibration. Moreover the reliability of IMU sensor is compromised in environments with strong or nearby magnetic fields making them unreliable to use with motor based exoskeletons.

Vision-based tracking solutions, such as Leap Motion, offer the highest number of degrees of freedom. These vision systems provide highly detailed motion capture without relying on extra mechanical or electrical sensors on the hand. However, these systems do only provide the tracking if the hands are in camera’s field of view and may lose accuracy in cases where the view of the hands is obstructed. This could be a problem with bulky exoskeletons, where the configuration of the hand is difficult to determine from the vision alone. This proves a need for further validation of the reliability of vision-based systems when wearing an exoskeleton in case this method is chosen to be used.

As tracking technology continues to evolve, the challenge remains achieving the best combination of precision, latency, and wearability. The ideal tracking solution for virtual reality systems using exoskeletons depends strongly on the use case, but it would likely be one that is the best compromise between precision, price, and comfort.

Prototypes and Products

Dexta Robotics has been conducting research on human-machine-interactions for virtual and mixed reality applications since 2014. The company believes that the user interface fundamentally defines the user experience. Just the way motion controllers took over console controllers in the virtual reality space, the next significant step could involve the adoption of glove-based controllers over the motion controllers to achieve a more intuitive, button free and hands-like experience. Their latest model, the Dexmo Force Feedback Gloves are currently available to purchase privately for enterprises or research institutions. These gloves are meant to be used in a variety of applications, including VR arcades, training simulations, entertainment, academic institutions and other scientific research facilities. While a consumer edition is still under development, the current model demonstrates promising potential. The design of the Dexmo gloves relies on rigid kinematic linkages actuated by compact gear motors. The motors were specifically designed and manufactured in-house in order to provide the small form factor. The motors are capable of providing 0.5N of torque each, allowing for significant, yet safe force feedback. Additionally, the system is fully wireless, it is powered by a battery which provides

a needed energy for up to six hours. The choice of materials and in-house built parts ensures that the entire system remains lightweight, the whole glove weights under 300 grams. In order to achieve precise local position tracking, the gloves use rotational sensors, offering 11 degrees of freedom (DOM) for the movement.




Figure 2.1: Design of Dexmo Glove

The Sensaglove Nova 2 uses a different approach for the force feedback. It utilizes magnetic friction brakes to transfer the force to the fingertips via mechanical wires. Each brake is capable of delivering up to 20 newtons of force, allowing for stronger haptic interactions. In addition to the force feedback, the glove integrates vibrotactile feedback to the fingertips using voice coil actuators. A hybrid approach is used for the local position tracking. The hybrid approach combines sensor-based finger tracking with computer vision hand tracking algorithms in order to achieve a more accurate finger tracking with more degrees of freedom.

DextrES [11] research paper proposes a more innovative yet experimental approach. They rely on flexible metal strips to generate an electrically-controlled friction force. Such design is much more compact and light as it does not rely on motors. The haptic glove that weighs only 8g is capable of generating up to 20N of holding force for each finger. Despite being lightweight, flexible and providing strong feedback, this approach has a drawback: due to the principal of breaking, the glove can only resist and stop the movement exerted by the hand, but the virtual objects can not push against the virtual hand in order to pull your physical fingers backwards.

A distinct approach to data collection for the purpose of robot arm learning from demonstration has been proposed [6]. The system has a gripper like form factor making the data collection intuitive. The glove uses displacement and inertial measurement unit sensors in order to capture position, orientation and gripper opening displacement information. However, unlike previously mentioned gloves, this exoskeleton provides no force feedback, its primary




Figure 2.2: Design of Sensaglove Nova 2




Figure 2.3: Design of DextrES

function is to interact with real objects rather than simulated ones. This research paper was included in this section for interesting gripper like form factor. The exoskeleton does not need to be a glove if the goal of interaction with the simulated virtual environment is to teach robots to perform tasks.

Interesting approaches has been proposed for variable stiffness control using the principle of jamming. This principle relies on changing the mechanical properties of materials by altering their internal friction or structure. One such implementation is HJ-Haptic [15], it uses this principle to provide stiffness feedback in bilateral teleoperation of robotic gripper. The device consists of flexible, honeycomb-structured layers that, when compressed through vacuum-induced suction, press together, increasing their internal friction, thereby altering the perceived stiffness. The stiffness increases linearly with the increase in pressure, allowing easy control of force feedback. A related approach has been

proposed in the development of a lightweight AR glove [12]. It uses 3d printed fibers in order to achieve the layer-jamming technique for force feedback. This method ensures minimal weight and flexible finger movement, making it a promising candidate for wearable haptic interfaces.

Lastly, many exoskeleton researchers opt to use series elastic actuators (SEAs). This approach allows the motor to be placed outside the exoskeleton, reducing the weight and worry of needing to fit all of the components compactly on the hand. SEAs transmit the motor torque through Bowden cables. Between the motor and the load a spring is placed, to introduce compliance and enhance safety. The transmitted force is often calculated by measuring the deflection of the springs and applying a Hooke's Law, allowing for position and torque control [17], [23].

These developments in haptic exoskeletons, gloves and various prototypes exploring different mechanisms for enhancing virtual touch experiences shows that the field is evolving rapidly. While many of these technologies remain in the experimental or enterprise-focused stages, continued research and refinement is likely to bring them closer to widespread consumer adoption.

2.2 Analysis and Design 1

A design using magnetic friction brakes is not an ideal solution as it provides feedback primarily during the squeezing of virtual object, during releasing the brakes are disengaged and no resistance is felt. This may be a good solution for VR simulations consisting of only rigid objects, but since this thesis is focused on soft objects an exoskeleton with servo motors will be used. The purpose of the first design is to get a good idea of the scope of the project, make a working prototype quickly and detect the possible issues with the project early on. The prototype, which from now on will be referred to as RoboGripVR V1, consists of two Dynamixel XM540-W270-R servo motors connected in daisy-chain using single line of RS-485 communication. The Dynamixel XM540-W270-R is a high-performance and precision servo motor from Robotis, this motor can provide 10.6 Nm of torque at 12V. The SMPS2Dynamixel is a power converter for the motors and U2D2 is a USB communication converter that enables to control and operate DYNAMIXEL motors using a personal computer (PC) Fig 2.4.

This design is not in the glove form, so it does not have sensors for global position tracking. The squeezing motion can be performed using thumb and index finger.




Figure 2.4: Design of RoboGripVR V1

2.3 Implementation 1

The PyBullet environment for testing this design consists of a table, soft ball and a robotiq 140 gripper Fig 2.5. The table and gripper were imported using a Unified Robot Description Format (URDF) an XML-based file format used to describe the physical and kinematic properties of a robot. The soft ball was created using open source 3D modeling software - Blender. The blender file exported as .obj provides only the surface mech. To obtain volumetric mesh needed to simulate the soft body, open source software - GMSH was used.



Figure 2.5: PyBullet environment for testing RoboGripVR V1

The gripper has stroke range of 0 to 0.127 units in the simulation. It is controlled by a single motor using position control. A function that controls the robotiq gripper based on distance instead of angle was created by linearly spacing 100 points of gripper's stroke range, measuring the angle of the motor and

the distance between the fingerpads in simulation and fitting this data using a polynomial Fig 2.6.




Figure 2.6: Polynomial fitting of data between gripper’s motor angle and distance between finger pads

The Dynamixel motors are controlled with the python files provided in their SDK. The distance between finger pads can be calculated using simple trigonometry Eq 2.1, Fig 2.7. This distance obtained from the motors is scaled and applied to the simulation every frame.

$$\begin{aligned} p_1 &= r_1 \cdot \cos(a_1) \\ p_2 &= r_2 \cdot \cos(a_2) \\ d_{total} &= -p_1 + d_0 + p_2 \end{aligned} \quad (2.1)$$




Figure 2.7: Diagram of distance calculation for RoboGripVR V1

The PyBullet’s Neo-Hookean model was used for soft-body simulation. While linear models like Hooker’s Law can be used to model small strains, materials

that undergo large deformations need to use a hyperelastic model that account for their nonlinearities. Neo-Hookean is a simple form of hyperelastic model. It is characterized by strain energy density function, which defines the energy stored in the material due to deformation. The Neo-Hookean model decouples this energy into two parts, deviatoric that handles shear deformations and volumetric part that deals with volume changes. The model is configured by material dependant Lamé parameters that describe the mechanical behavior of isotropic solids. The first Lamé parameter λ is related to the volumetric changes and the second Lamé parameter (shear modulus) μ is used to describe the material's resistance to shear deformation. Both of these parameters can be calculated [9] from material properties E (Young's modulus) and ν (Poisson's ratio) Eq 2.2, 2.3.

$$\mu = \frac{E}{2(1 + \nu)} \quad (2.2)$$

$$\lambda = \frac{E\nu}{(1 + \nu)(1 - 2\nu)} \quad (2.3)$$

A study [13] has shown that it is possible predict these parameters using data driven model to accurately simulate real world soft models in PyBullet. It also mentions that soft-bodies tend to become unstable (implode or explode) when Lamé parameters are set too low or to high. Another reason for soft-body instability is that the simulation is run in discrete time steps, the lack of fidelity can cause numerical issues during sudden application of large forces. Some solvers use adaptive time stepping to overcome this issue, but such feature is unavailable in PyBullet. It's a common practice to set PyBullet's time step to 1/250 of a second, but this value turned out to have poor stability during the experiments. A value of 1/1000 was used as it yielded much better stability. Another factor that influenced stability was the mesh itself. Multiple balls were created using icosphere mesh with varying subdivision setting Fig 2.8. Increasing subdivisions increases the resolution of the mesh, making the ball appear smoother, but it also increases the vertex count potentially making soft body simulation unstable or slower. A ball with 2 subdivisions was used as it yielded the best performance and stability.

The normal forces between soft ball and gripper pads are obtained using PyBullet's function `getContactPoints`. The reaction forces R_l and R_r in PyBullet are assumed to be distributed symetrically and can be represented with total resultant force as a sum of individual forces at the centroid of the contact area. In order to achieve the force feedback in the exoskeleton, the reaction forces from simulation are converted to motor torques Eq 2.4

$$\begin{aligned} \tau_l &= R_l d_l \\ \tau_r &= R_r d_r \end{aligned} \quad (2.4)$$




Figure 2.8: Varying subdivision setting




Figure 2.9: Force diagrams

XM540-W270-T/R are smart servo motors; they have several control modes available: Current Control Mode, Velocity Control Mode, Position Control Mode ($0\ 360\ [^\circ]$) and PWM Control Mode (Voltage Control Mode). The current control mode and PWM control mode could both be suitable in this scenario, so they will be tested and comparison between them will be made.

PWM control

The Pulse Width Modulation (PWM) is a low level motor control mode and is the final step in all of the control modes. It can give fine grain control over the motors if the available control modes are not satisfactory. Additionally, not all motors provide multiple control modes, it is common for direct current (DC) motors to only use PWM control as a means to change the speed of the motor. PWM signal is a square wave with the signal either being on (set to the maximum voltage) or off (zero voltage). The average voltage delivered to

the motor depends on the duty cycle, a ratio of the "on" time to the total period of the signal. For the motor used $PWM \in \mathbb{Z} \cap [-885, 885]$, where 0 would be duty cycle 0%, 885 duty cycle 100% in counter clock wise (CCW) direction and -885 duty cycle 100% in clock wise (CW) direction.

$$V_{out} = V_{max} \cdot DutyCycle \quad (2.5)$$

The motor torque holds a linear relationship to the supplied current Eq 2.6, where k_t is torque constant. From the XM540-W270-T/R motor's datasheet, we can see that stall torque is 10.6 [Nm] (at 12.0 [V], 4.4 [A]). Using this information the torque constant can be calculated: $k_t = \tau/I = 10.6/4.4 = 2.409$

$$\tau = k_t \cdot I \quad (2.6)$$

The motor can measure the supplied current, thus the goal of PWM control will be to reach and maintain a goal current instead of torque as the value can be converted back to the torque later on. The PID controller diagram can be seen in Fig 2.10, the motor's servo arm is placed against a fixed support, once the PWM signal is set, the reaction force from the fixed support generate resistance that is measured by the motor in form of current.




Figure 2.10: Diagram of PID controller

The K_p , K_i and K_d gains need to be tuned. When the transfer function is known, analytical methods such as root locus could be used to tune a PID controller to meet performance requirements. However, for model-free systems, manual tuning is commonly employed, or heuristic approaches like Ziegler–Nichols can be used to obtain initial controller parameters. Manual tuning was employed, but it proved to be difficult and time consuming. It was also very easy to get stuck in a local minima as drastic changes in gains require to restart tuning process. During this trial and error phase an interesting idea occurred to me. By employing evolutionary algorithm (EA), variety of gains could be tested autonomously based on desired fitness function. When the

ball in simulation is squeezed the reaction forces and thus the target currents will be changing rapidly. Intuitively, a good fitness function should encompass rapid changes. For this reason a target current is chosen as a step function Eq 2.7 and the fitness of the individuals will be a sum of absolute errors, meaning the best performing members of the population will be able to reach the target signal with minimal rise time and steady state error.

$$f(\text{iteration}) = \begin{cases} 0.2 & \text{if } 600 < \text{iteration} < 1200 \\ 0.1 & \text{otherwise, where iteration} \leq 1800 \end{cases} \quad (2.7)$$

A population of size 150 was initialized. Each member was assigned random P, I, and D values in ranges $[0, 1024]$, $[0, 512]$, and $[0, 64]$, respectively. The algorithm was trained for 20 generations with a mutation rate of 0.1. The top-performing member of the population has the PID values $K_p = 28.809$, $K_I = 503.211$, and $K_D = 0.191$ with the fitness value of 2.295. This is a significant improvement as the fitness for a manually tuned controller is 8.824.

After the training the PID controller was tested against a more varied target function that includes triangle and sinusoidal waves Fig 2.11. The controller is able to follow the target quite well, the fitness for this function is 54.8. On average in the testing function the present current is delayed by 17 iterations, which equates to 131.059ms with average iteration time being 7.709ms






Figure 2.11: Function for testing trained PID values

The exoskeleton was also tested by squeezing the virtual ball. The sensation subjectively feels convincing, but looking at the Fig 2.12 it is evident that the significant delay in reaching target current results in a discrepancy between the forces according to the simulation and forces that are felt. Note that the

controller is disengaged when the target current is zero, otherwise the PWM controller generates resistance instead of being in freewheeling condition.



(a) Current



(b) PWM

Figure 2.12: Squeezing the virtual ball 5 times using PWM control

Current control

This control mode allows the current to be controlled directly. Internally it works similarly to the controller we have implemented in the section above.

As seen in Fig 2.13 when tested, this controller has a much better performance compare to out implemented PWM control, with fitness (sum of absolute errors) being 18.823 and reaching target current in less than 8ms (one iteration, exact time is unknown as this is as fast as we can measure). This performance can be attributed to Dynamixel having well-tuned PID loops optimized for their hardware and low latency feedback due to motor performing controlling internally without the need of slow communication and signal conversion to the PC.




Figure 2.13: Current control test

When squeezing the virtual ball (Fig 2.14) we can see that the current is followed closely, but subjectively the experience does not feel smooth, rapid oscillations in target current occur. By taking a closer look to a single squeeze Fig 2.16a we can see how uneven the target current is. This issues could be mitigated by processing the signal using exponential smoothing Eq 2.8. A variety of different window size values have been tested and plotted 2.15. Increasing the window size provides smoother signal but adds a higher delay. For the controller a windows size of 10 is used as it provides a smoother signal without much delay 2.16b. This controller still does struggle to maintain low target current when suddenly introduced with external forces from the fingers.

$$S_t = \alpha X_t + (1 - \alpha)S_{t-1}, \quad \text{where } \alpha = \frac{2}{K + 1} \quad (2.8)$$

where:

- S_t is the smoothed value at time t ,
- X_t is the actual value at time t ,
- α is the smoothing factor, calculated using window size K ,
- S_{t-1} is the previous smoothed value.




Figure 2.14: Squeezing the virtual ball 5 times using Current control





Figure 2.15: Exponential smoothing with different window sizes

2.4 Analysis and Design 2

The purpose of a second design is to make the exoskeleton wearable. Ideally it should be easy to make, cost-effective, durable and functional.

2.5 Conclusion



(a) No target current smoothing


(b) Target current exponential smoothing with $K=10$

Figure 2.16: Influence of exponential smoothing when squeezing a virtual ball

3 Algorithms

In order to test if the proposed exoskeleton can aid in the training of the robots, a simulated environment with a task has been created in which an UR5 robot arm will have to pick-and-place virtual balls of varying stiffness into appropriate boxes. This task will be performed using three different methods: a classical approach, where the robot trajectory is generated from points, a reinforcement learning approach, where the robot aims to perform a task by trial and error, while learning from the past mistakes and trying to maximize some reward metric specified by the user and lastly, inverse reinforcement learning, where the rewards are learned from human demonstration instead of being specified before the reinforcement learning model is trained.

3.1 Background

Classical Approach to Control

In 1961, Unimate, the first industrial robot, which worked on General Motors assembly line, was created. The Unimate was a hydraulically operated 5 degrees of freedom arm that performed pick-and-place tasks. The robot could be programmed by manually moving a robot arm to the a desired position and recording the position. Then the robot could replay the movement by moving to the same position. This resulted in the first of it's kind point-to-point movement which is still a standard feature in many robotic arms today. Such control method is quite simple, but it does require manual programming, meaning it is most suited for simple, repetitive tasks in well known environments. Besides that, the point-to-point movement has two obvious disadvantages. Firstly, the robot movement does not appear smooth, secondly, there must be no obstacles between the points. These problems have been adressed in modern robotic control. The most simple way to move between two points is use linear interpolation. Similarly, orientation can be interpolated, depending on the representation chosen. For example, if orientation is represented as quaternions, a spherical linear interpolation (SLERP) can be used. This is because quaternion is a rotation representation on 4D unit sphere and in order to move between two points a sphere, the movement should be done on a following a geodesic. In theory linear interpolation results in constant velocity motion, but in practice this means that at the beginning of the motion robot will need an infinite acceleration to achieve desired velocity instantly and at the end of the movement, it will need infinite deacceleration to stop immediately. Objects with mass resist changes in motion due to inertia. The higher

the object's mass is, the more force will be needed to accelerate it. The resistance to rotation also depends on the shape of the object, which is described by the moment of inertia. As robot is a system constrained by physical limitations, it will not experience infinite acceleration, but the motors will likely apply the maximum torque they are capable of during the brief moments at the beginning and the end of the motion. This increases wear and tear of the motor and other components, leading to the decreased lifespan of the robot. This issue can be mitigated by using a parabolic trajectory instead. Assuming the start velocity of zero and end velocity of zero, the parabolic trajectory will have a velocity profile that linearly increases until it reaches the half point of the trajectory and linearly decreases until it reaches zero again at the end of the trajectory. Consequently, the acceleration during first and second half of the movement will have much lower maximum value and will be constant, non-zero during majority of the motion. This leads to least wear and tear, but also slower movement. Fine control between trajectory duration and maximum acceleration can be achieved by merging these two methods. Linear trajectories with parabolic blends have a linear part in the middle and parabolic at the start end end of the interpolation.

Talk about RRT

Talk about splines

Reinforcement Learning Approach to Control

Inverse Reinforcement Learning

3.2 Analysis and Design

3.3 Implementation

3.4 Conclusion

4 Discussion

Summing up all the main parts 1 to n conclusions.

5 Conclusion

Overall our project was a success.

A Appendix

We include here the API documentation for our library.

Bibliography

- [1] Angel Ayala, Francisco Cruz, Diego Campos, Rodrigo Rubio, Bruno J. T. Fernandes, and Richard Dazeley. A comparison of humanoid robot simulators: A quantitative approach. *CoRR*, abs/2008.04627, 2020.
- [2] Murray Campbell, A. Joseph Hoane, and Feng hsiung Hsu. Deep blue. *Artificial Intelligence*, 134(1):57–83, 2002.
- [3] Inrak Choi, Heather Culbertson, Mark R. Miller, Alex Olwal, and Sean Follmer. Grability: A wearable haptic interface for simulating weight and grasping in virtual reality. In *Proceedings of the 30th Annual ACM Symposium on User Interface Software and Technology*, UIST '17, page 119–130, New York, NY, USA, 2017. Association for Computing Machinery.
- [4] Inrak Choi, Yiwei Zhao, Eric J. Gonzalez, and Sean Follmer. Augmenting perceived softness of haptic proxy objects through transient vibration and visuo-haptic illusion in virtual reality. *IEEE Transactions on Visualization and Computer Graphics*, 27(12):4387–4400, 2021.
- [5] Jack Collins, Shelvin Chand, Anthony Vanderkop, and Gerard Howard. A review of physics simulators for robotic applications. *IEEE Access*, PP:1–1, 03 2021.
- [6] Hengtai Dai, Zhenyu Lu, Mengyuan He, and Chenguang Yang. A gripper-like exoskeleton design for robot grasping demonstration. In *Actuators*, volume 12, page 39. MDPI, 2023.
- [7] DeepMind. Open-sourcing mujoco. <https://deepmind.google/discover/blog/open-sourcing-mujoco/>, May 2022.
- [8] Liufeng Fan, Zhan Zhang, Biao Zhu, Decheng Zuo, Xintong Yu, and Yiwei Wang. Smart-data-glove-based gesture recognition for amphibious communication. *Micromachines*, 14(11), 2023.
- [9] FEBio. Febio user manual - neo-hookean model. <https://help.febio.org/docs/FEBioUser-3-7/UM37-4.1.4.17.html>, 2023.
- [10] X. Guo, Y. Zhang, W. Wei, W. Xu, and D. Wang. Thermaltex: A two-modal tactile display for delivering surface texture and thermal information. In *Haptics: Science, Technology, Applications: 12th International Conference, EuroHaptics 2020, Leiden, The Netherlands, September 6–9, 2020, Proceedings*, page 288–296, Berlin, Heidelberg, 2020. Springer-Verlag.

- [11] Ronan Hinchet, Velko Vechev, Herbert Shea, and Otmar Hilliges. Dextres: Wearable haptic feedback for grasping in vr via a thin form-factor electrostatic brake. In *Proceedings of the 31st Annual ACM Symposium on User Interface Software and Technology*, UIST '18, page 901–912, New York, NY, USA, 2018. Association for Computing Machinery.
- [12] Saurabh Jadhav, Mohamad Majit, Benjamin Shih, Jürgen Schulze, and Michael Tolley. Variable stiffness devices using fiber jamming for application in soft robotics and wearable haptics. *Soft Robotics*, 9, 02 2021.
- [13] Fan-Chien Kao, Zhi-Ren Chen, Chung-Shan Shih, Shao-Huang Lu, and Pei-Chun Lin. Bridging mechanical behavior differences of deformable soft objects in simulation and experiments using a data-driven model. In *2024 IEEE International Conference on Advanced Intelligent Mechatronics (AIM)*, pages 1297–1302, 2024.
- [14] Vikash Kumar and Emanuel Todorov. Mujoco haptix: A virtual reality system for hand manipulation. In *2015 IEEE-RAS 15th International Conference on Humanoid Robots (Humanoids)*, pages 657–663, 2015.
- [15] Thomas Kwok, Bohan Zhang, and Wai Chow. A wearable stiffness-rendering haptic device with a honeycomb jamming mechanism for bilateral teleoperation. *Machines*, 13:27, 01 2025.
- [16] Bor-Shing Lin, I-Jung Lee, Pei-Ying Chiang, Shih-Yuan Huang, and Chih-Wei Peng. A modular data glove system for finger and hand motion capture based on inertial sensors. *Journal of Medical and Biological Engineering*, 39, 06 2018.
- [17] Dario Marconi, Andrea Baldoni, Zach McKinney, Marco Cempini, Simona Crea, and Nicola Vitiello. A novel hand exoskeleton with series elastic actuation for modulated torque transfer. *Mechatronics*, 61:69–82, 2019.
- [18] Riccardo Mengacci, Giacomo Zambella, Giorgio Grioli, Domenico Caporale, Manuel G. Catalano, and Antonio Bicchi. An open-source ros-gazebo toolbox for simulating robots with compliant actuators. *Frontiers in Robotics and AI*, 8:713083, 2021. Published 2021 Aug 11.
- [19] Olivier Michel. Cyberbotics ltd. webotsTM: professional mobile robot simulation. *International Journal of Advanced Robotic Systems*, 1(1):5, 2004.
- [20] Kouta Minamizawa, Souichiro Fukamachi, Hiroyuki Kajimoto, Naoki Kawakami, and Susumu Tachi. Gravity grabber: wearable haptic display to present virtual mass sensation. In *ACM SIGGRAPH 2007 Emerging Technologies*, SIGGRAPH '07, page 8–es, New York, NY, USA, 2007. Association for Computing Machinery.

- [21] Gordon E Moore. Cramming more components onto integrated circuits. *Proceedings of the IEEE*, 86(1):82–85, 1998.
- [22] Morgan Quigley, Ken Conley, Brian Gerkey, Josh Faust, Tully Foote, Jeremy Leibs, Rob Wheeler, and Andrew Ng. Ros: an open-source robot operating system. volume 3, 01 2009.
- [23] Eric M. Refour, Bijo Sebastian, Raghuraj J. Chauhan, and Pinhas Ben-Tzvi. A general purpose robotic hand exoskeleton with series elastic actuation. *Journal of Mechanisms and Robotics*, 11(6):060902, December 2019. Epub 2019 Sep 10.
- [24] Eric Rohmer, Surya P. N. Singh, and Marc Freese. V-rep: A versatile and scalable robot simulation framework. In *2013 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 1321–1326, 2013.
- [25] Kenta Takaya, Toshinori Asai, Valeri Kroumov, and Florentin Smarandache. Simulation environment for mobile robots testing using ros and gazebo. pages 96–101, 10 2016.
- [26] E. Todorov, T. Erez, and Y. Tassa. Mujoco: A physics engine for model-based control. In *IEEE International Conference on Intelligent Robots and Systems*, pages 5026–5033. IEEE, October 2012.
- [27] A. M. TURING. I.—computing machinery and intelligence. *Mind*, LIX(236):433–460, 10 1950.
- [28] Michael Wiertlewski, José Lozada, and Vincent Hayward. The spatial spectrum of tangential skin displacement can encode tactual texture. *Robotics, IEEE Transactions on*, 27:461 – 472, 07 2011.
- [29] Jaemin Yoon, Bukun Son, and Dongjun Lee. Comparative study of physics engines for robot simulation with mechanical interaction. *Applied Sciences*, 13(2), 2023.