

No PCA

June 6, 2026

1 NO PCA First

```
[1]: import pandas as pd
      from sklearn.decomposition import PCA
      from sklearn.cluster import KMeans
      import matplotlib.pyplot as plt
      from sklearn.cluster import DBSCAN
      import seaborn as sns
      from sklearn.metrics import silhouette_score
```

1.1 Loading the data

```
[2]: # Load data and extract features
df = pd.read_csv("../data/Qualifying_scaled_for_clustering.csv")
identifiers = ['track', 'global_corner_id', 'driver_number']
features = df.drop(columns=identifiers)
```

1.2 Finding the ideal number of clusters

```
[4]: wcss = []
      silhouette_scores = []
      k_values = range(1, 11)

      for k in k_values:
          kmeans = KMeans(n_clusters=k, random_state=42)
          cluster_labels = kmeans.fit_predict(features)
          wcss.append(kmeans.inertia_)

          # Silhouette score is only defined for 2 <= k <= n_samples - 1
          if k > 1:
              score = silhouette_score(features, cluster_labels)
              silhouette_scores.append(score)


      # Plot WCSS (Elbow Method)
      plt.figure(figsize=(10, 6))
      plt.plot(k_values, wcss, marker='o', linestyle='--')
      plt.title('Elbow Method For Optimal k')
```


```

plt.xlabel('Number of clusters (k)')
plt.ylabel('WCSS')
plt.grid(True)
plt.show()

# Plot Silhouette Scores
plt.figure(figsize=(10, 6))
k_values_sil = range(2, 11)
plt.plot(k_values_sil, silhouette_scores, marker='s', linestyle='-', color='green')
plt.title('Silhouette Score For Optimal k')
plt.xlabel('Number of clusters (k)')
plt.ylabel('Silhouette Score')
plt.grid(True)
plt.show()

```





The Silhouette score peaks at $k=2$, suggesting it as the mathematical optimum. However, $k=3$ is distinctly the next best option. Combined with the Elbow method, $k=3$ remains the most practical choice for defining real-world driving styles. The overall low scores indicate overlapping clusters, which is expected when clustering raw, uncompressed F1 telemetry data without dimensionality reduction.

1.3 K-Means

```
[ ]: # Run K-Means and save labels to the original dataframe
kmeans = KMeans(n_clusters=3, random_state=42)
df['kmeans_cluster'] = kmeans.fit_predict(features)
```

1.4 DBSCAN

```
[ ]: # Run DBSCAN and save labels to the original dataframe
dbscan = DBSCAN(eps=0.7, min_samples=5)
df['dbscan_cluster'] = dbscan.fit_predict(features)
```

1.5 Visualization - HEATMAP

```
[ ]: # Calculate feature means for K-Means
kmeans_means = df.groupby('kmeans_cluster')[features.columns].mean()

# Plot K-Means Heatmap
plt.figure(figsize=(14, 6))
```


```


sns.heatmap(kmeans_means.T, annot=True, cmap='coolwarm', fmt=".2f", center=0)
plt.title('K-Means Cluster Profiles')
plt.xlabel('Cluster ID')
plt.ylabel('Feature')
plt.tight_layout()
plt.show()

# Calculate feature means for DBSCAN
dbscan_means = df.groupby('dbscan_cluster')[features.columns].mean()
dbscan_means.index = [f'Noise (-1)' if c == -1 else f'Cluster {c}' for c in dbscan_means.index]

# Plot DBSCAN Heatmap
plt.figure(figsize=(14, 6))
sns.heatmap(dbscan_means.T, annot=True, cmap='coolwarm', fmt=".2f", center=0)
plt.title('DBSCAN Cluster Profiles')
plt.xlabel('Cluster ID')
plt.ylabel('Feature')
plt.tight_layout()
plt.show()

```






We can see that k-means provided clearer and better results, for example, cluster 0 resembles drivers who drive slowly and carefully, with lower speeds overall.

1.6 Visualization - BARPLOT

```
[ ]: # Plot K-Means Bar Chart
kmeans_means.T.plot(kind='bar', figsize=(15, 6), colormap='viridis')
plt.title('K-Means: Feature Means per Cluster')
plt.xlabel('Feature')
plt.ylabel('Average Value (Z-Score)')
plt.legend(title='Cluster', bbox_to_anchor=(1.05, 1), loc='upper left')
plt.tight_layout()
plt.show()

# Plot DBSCAN Bar Chart
dbscan_means.T.plot(kind='bar', figsize=(15, 6), colormap='plasma')
plt.title('DBSCAN: Feature Means per Cluster')
plt.xlabel('Feature')
plt.ylabel('Average Value (Z-Score)')
plt.legend(title='Cluster', bbox_to_anchor=(1.05, 1), loc='upper left')
plt.tight_layout()
plt.show()
```



We can use the bar plot of the K-Means to easily understand the characteristics of the different clusters:


Cluster 0: Low speeds, almost no braking

Cluster 1: High speed, low braking, aggressive driving

Cluster 2: Low speeds, some braking, overall smooth driving

```
[ ]: # 1. Macro: Driver vs. K-Means Cluster distribution
driver_cluster_dist = pd.crosstab(df['driver_number'], df['kmeans_cluster'])

plt.figure(figsize=(12, 6))
sns.heatmap(driver_cluster_dist, annot=True, fmt="d", cmap="Blues")
plt.title('Corner Counts: Driver vs. K-Means Cluster')
plt.xlabel('K-Means Cluster')
plt.ylabel('Driver Number')
plt.show()
```



This visualization reveals individual driving habits by highlighting the most common cornering style assigned to each driver.

1.7 final clustering

```
[ ]: driver_profiles = pd.crosstab(df['driver_number'], df['kmeans_cluster'],
    ↪normalize='index')
driver_profiles.columns = [f'Driving Style {c}' for c in driver_profiles.
    ↪columns]

kmeans_drivers = KMeans(n_clusters=3, random_state=42)
driver_profiles['Driver_Style_Cluster'] = kmeans_drivers.
    ↪fit_predict(driver_profiles)


driver_profiles_sorted = driver_profiles.sort_values('Driver_Style_Cluster')
cluster_labels = driver_profiles_sorted.pop('Driver_Style_Cluster')

plt.figure(figsize=(12, 8))
sns.heatmap(driver_profiles_sorted, annot=True, fmt=".1%", cmap="YlGnBu",
    ↪vmin=0, vmax=1)

y_labels = [f"Driver {idx} (Style {c})" for idx, c in
    ↪zip(driver_profiles_sorted.index, cluster_labels)]
plt.yticks(ticks=[i + 0.5 for i in range(len(y_labels))], labels=y_labels,
    ↪rotation=0)
```

```
plt.title('Driver Profiles: Corner Style Distribution')
plt.ylabel('Driver Number & Style Cluster')
plt.xlabel('Corner Telemetry Style')
plt.tight_layout()
plt.show()

driver_profiles_sorted['Driver_Style_Cluster'] = cluster_labels
```



By applying a second clustering step to these corner distributions, we classify drivers into distinct overall ‘driving styles’.

1.8 PCA to show driver clusters

```
[ ]: # Reduce driver profiles to 2D for the scatter plot
pca_drivers = PCA(n_components=2, random_state=42)
driver_features = driver_profiles.drop(columns=['Driver_Style_Cluster'])
pca_drivers_2d = pca_drivers.fit_transform(driver_features)

pca_df = pd.DataFrame(data=pca_drivers_2d, columns=['PC1', 'PC2'],
    ↪ index=driver_profiles.index)
pca_df['Driver_Style_Cluster'] = driver_profiles['Driver_Style_Cluster']
```

```

# Transform high-dimensional cluster centers into the 2D PCA space
centroids_2d = pca_drivers.transform(kmeans_drivers.cluster_centers_)

# Plot the results
plt.figure(figsize=(12, 8))
sns.set_style("whitegrid")
sns.scatterplot(x='PC1', y='PC2', hue='Driver_Style_Cluster', data=pca_df,
               palette='Set1', s=100)

# Plot the centroids as large black 'X' markers
plt.scatter(
    centroids_2d[:, 0],
    centroids_2d[:, 1],
    marker='X',
    s=300,
    color='black',
    label='Centroids',
    zorder=10
)

# Annotate each point with the driver number
for idx, row in pca_df.iterrows():
    plt.annotate(
        str(int(idx)),
        (row['PC1'], row['PC2']),
        textcoords="offset points",
        xytext=(5, 5),
        ha='left',
        fontsize=10,
        fontweight='bold'
    )

plt.title('Driver Style Clusters (2D PCA Projection)')
plt.xlabel('PC1 (Driver Profile Variance)')
plt.ylabel('PC2 (Driver Profile Variance)')


# Update legend to include the centroids
plt.legend(title='Driver Cluster & Centroids')
plt.tight_layout()
plt.show()

```

```

/Users/idomac/Documents/F1-Project/F1-Clustering-
Project/venv/lib/python3.13/site-packages/sklearn/utils/validation.py:2827:
UserWarning: X does not have valid feature names, but PCA was fitted with
feature names
  warnings.warn(

```



The final visualization identifies three distinct groups of drivers, each representing a unique driving style.

Without applying PCA first, the boundaries between driving styles became blurred and the clusters were closer together, indicating suboptimal clustering.