


STAT 526 HW 3

Satoshi Ido (ID: 34788706)

20 February 2023

Q1-a

```
x <- (-150:150)/25; plot(x,1-1/(1+exp(x)),type="l",ylab="p")
  lines(x,pnorm(x),col=2); lines(x,1-exp(-exp(x)),col=3)
  lines(c(-6,6),c(.5,.5),lty=2,col=1)
lines(x,pnorm(x,sd=1.7),col=6)
```



Q1-e

```
df <- data.frame(
  x = c(14, 29, 6, 25, 18, 4, 18, 12, 22, 6, 30, 11, 30, 5,
        20, 13, 9, 32, 24, 13, 19, 4, 28, 22),
  y = c(0, 0, 0, 1, 1, 0, 0, 0, 1, 0, 1, 0, 1, 0, 1, 0,
        0, 1, 0, 1, 0, 0, 1, 1)
)
```

train the glm

```
df.lgt0 <- glm(y ~ x, family = binomial, data = df)
summary(df.lgt0)
```

```
##
## Call:
## glm(formula = y ~ x, family = binomial, data = df)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -2.0201  -0.5988  -0.2745   0.6294   1.8319
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept) -4.21134    1.66304  -2.532  0.0113 *
## x             0.21078    0.08187   2.574  0.0100 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 32.601  on 23  degrees of freedom
## Residual deviance: 20.978  on 22  degrees of freedom
## AIC: 24.978
##
## Number of Fisher Scoring iterations: 5
```


```
anova(df.lgt0)
```


```
## Analysis of Deviance Table
##
## Model: binomial, link: logit
##
## Response: y
##
## Terms added sequentially (first to last)
##
##      Df Deviance Resid. Df Resid. Dev
## NULL                23      32.601
## x      1      11.623        22      20.978
```


```
summary(df.lgt0)
```


```
##
## Call:
## glm(formula = y ~ x, family = binomial, data = df)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -2.0201  -0.5988  -0.2745   0.6294   1.8319
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept) -4.21134     1.66304  -2.532   0.0113 *
## x             0.21078     0.08187   2.574   0.0100 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 32.601  on 23  degrees of freedom
## Residual deviance: 20.978  on 22  degrees of freedom
## AIC: 24.978
##
## Number of Fisher Scoring iterations: 5
```

```
plot(df.lgt0)
```









```
df.lgt1 <- glm(y ~ 1, family = binomial(link = probit), data = df)
df.lgt1
```

```
##
## Call: glm(formula = y ~ 1, family = binomial(link = probit), data = df)
##
## Coefficients:
## (Intercept)
## -0.2104
##
## Degrees of Freedom: 23 Total (i.e. Null); 23 Residual
## Null Deviance: 32.6
## Residual Deviance: 32.6 AIC: 34.6
```