



AnythingLLM Developer API 1.0.0 OAS 3.0

API endpoints that enable programmatic reading, writing, and updating of your AnythingLLM instance. UI supplied by Swagger.io.

Servers

/api

Authorize

Authentication

GET /v1/auth

Verify the attached Authentication header contains a valid API token.

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	Valid auth token was found. Media type application/json Controls Accept header. Example Value Schema <pre>{ "authenticated": true</pre>	No links

Code	Description	Links
	}	
401	Unauthorized	No links
403	Forbidden	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "message": "Invalid API Key" }</pre>	

Admin



GET	/v1/admin/is-multi-user-mode	
GET	/v1/admin/users	
POST	/v1/admin/users/new	
POST	/v1/admin/users/{id}	
DELETE	/v1/admin/users/{id}	
GET	/v1/admin/invites	
POST	/v1/admin/invite/new	
DELETE	/v1/admin/invite/{id}	
GET	/v1/admin/workspaces/{workspaceId}/users	
POST	/v1/admin/workspaces/{workspaceId}/update-users	
POST	/v1/admin/workspaces/{workspaceSlug}/manage-users	

POST	/v1/admin/workspace-chats	 
POST	/v1/admin/preferences	 

Documents

^

POST

/v1/document/upload



Upload a new file to AnythingLLM to be parsed and prepared for embedding.

Parameters

Try it out

No parameters

Request body

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "success": true, "error": null, "documents": [{ "location": "custom-documents/anythingllm.txt-6e8be64c-c162-4b43-9997-b068c0071e8b.json", "name": "anythingllm.txt-6e8be64c-c162-4b43-9997-b068c0071e8b.json", "url": "file:///Users/tim/Documents/anything-llm/collector/ho tdir/anythingllm.txt", "title": "anythingllm.txt", "docAuthor": "Unknown", }]}</pre>	No links

Code	Description	Links
	<pre>"description": "Unknown", "docSource": "a text file uploaded by the user.", "chunkSource": "anythingllm.txt", "published": "1/16/2024, 3:07:00 PM", "wordCount": 93, "token_count_estimate": 115 }] }</pre>	
401	Unauthorized	No links
403	Forbidden	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "message": "Invalid API Key" }</pre>	
500	Internal Server Error	No links

POST

/v1/document/upload/{folderName}



Upload a new file to a specific folder in AnythingLLM to be parsed and prepared for embedding. If the folder does not exist, it will be created.

Parameters

Try it out

Name	Description
folderName * required string (path)	Target folder path (defaults to 'custom-documents' if not provided) <i>Example</i> : my-folder my-folder

Request body

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "success": true, "error": null, "documents": [{ "location": "custom-documents/anythingllm.txt-6e8be64c-c162-4b43-9997-b068c0071e8b.json", "name": "anythingllm.txt-6e8be64c-c162-4b43-9997-b068c0071e8b.json", "url": "file://Users/tim/Documents/anything-llm/collector/ho tdir/anythingllm.txt", "title": "anythingllm.txt", "docAuthor": "Unknown", "description": "Unknown", "docSource": "a text file uploaded by the user.", "chunkSource": "anythingllm.txt", "published": "1/16/2024, 3:07:00 PM", "wordCount": 93, "token_count_estimate": 115 }]}</pre>	No links
401	Unauthorized	No links
403	Forbidden Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key"}</pre>	No links
500	Internal Server Error Media type application/json	No links

Code

Description

Links

Example Value

Schema

```
{  "success": false,  "error": "Document processing API is not online. Document will not be processed automatically."}
```

POST

/v1/document/upload-link



Upload a valid URL for AnythingLLM to scrape and prepare for embedding. Optionally, specify a comma-separated list of workspace slugs to embed the document into post-upload.

Parameters

Try it out

No parameters

Request body required

application/json

Link of web address to be scraped and optionally a comma-separated list of workspace slugs to embed the document into post-upload.

Example Value

Schema

```
{  "link": "https://anythingllm.com",  "addToWorkspaces": "workspace1,workspace2",  "scraperHeaders": {    "Authorization": "Bearer token123",    "My-Custom-Header": "value"  }}
```

Responses

Code

Description

Links

200

OK

No links

Media type

application/json

Code	Description	Links
	Controls Accept header. Example Value Schema <pre>{ "success": true, "error": null, "documents": [{ "id": "c530dbe6-bff1-4b9e-b87f-710d539d20bc", "url": "file://useanything_com.html", "title": "useanything_com.html", "docAuthor": "no author found", "description": "No description found.", "docSource": "URL link uploaded by the user.", "chunkSource": "https:anythingllm.com.html", "published": "1/16/2024, 3:46:33 PM", "wordCount": 252, "pageContent": "AnythingLLM is the best....", "token_count_estimate": 447, "location": "custom-documents/url-useanything_com-c530dbe6-bff1-4b9e-b87f-710d539d20bc.json" }]}</pre>	
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key"}</pre>	
500	Internal Server Error	No links

POST

/v1/document/raw-text



Upload a file by specifying its raw text content and metadata values without having to upload a file.

Parameters

Try it out

No parameters

Request body required

application/json

Text content and metadata of the file to be saved to the system. Use metadata-schema endpoint to get the possible metadata keys

Example Value Schema

```
{
  "textContent": "This is the raw text that will be saved as a document in AnythingLLM.",
  "addToWorkspaces": "workspace1,workspace2",
  "metadata": {
    "title": "This key is required. See in /server/endpoints/api/document/index.js:287",
    "keyOne": "valueOne",
    "keyTwo": "valueTwo",
    "etc": "etc"
  }
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "success": true, "error": null, "documents": [{ "id": "c530dbe6-bff1-4b9e-b87f-710d539d20bc", "url": "file://my-document.txt", "title": "hello-world.txt", "docAuthor": "no author found", "description": "No description found.", "docSource": "My custom description set during upload", "chunkSource": "no chunk source specified", "published": "1/16/2024, 3:46:33 PM", "wordCount": 252, "pageContent": "AnythingLLM is the best....", "token_count_estimate": 447, "location": "custom-documents/raw-my-doc-text-c530dbe6-bff1-4b9e-b87f-710d539d20bc.json" }] }</pre>	No links

Code	Description	Links
	<pre>] }</pre>	
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json	
	Example Value Schema	
	<pre>{ "message": "Invalid API Key" }</pre>	
422	Unprocessable Entity	No links
500	Internal Server Error	No links

GET /v1/documents  

List of all locally-stored documents in instance

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK	No links
	Media type application/json Controls Accept header.	
	Example Value Schema	
	<pre>{ "localFiles": {</pre>	

Code	Description	Links
	<pre>"name": "documents", "type": "folder", "items": [{ "name": "my-stored-document.json", "type": "file", "id": "bb07c334-4dab-4419-9462-9d00065a49a1", "url": "file://my-stored-document.txt", "title": "my-stored-document.txt", "cached": false }] }</pre>	
401	Unauthorized	No links
403	Forbidden	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "message": "Invalid API Key" }</pre>	
500	Internal Server Error	No links

GET

/v1/documents/folder/{folderName}



Get all documents stored in a specific folder.

Parameters

Try it out

Name	Description
folderName * required string (path)	Name of the folder to retrieve documents from folderName

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "folder": "custom-documents", "documents": [{ "name": "document1.json", "type": "file", "cached": false, "pinnedWorkspaces": [], "watched": false, "more": "data" }, { "name": "document2.json", "type": "file", "cached": false, "pinnedWorkspaces": [], "watched": false, "more": "data" }]}</pre>	No links
401	Unauthorized	No links
403	Forbidden Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key"}</pre>	No links
500	Internal Server Error	No links

Check available filetypes and MIMEs that can be uploaded.

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "types": { "application/mbox": [".mbox"], "application/pdf": [".pdf"], "application/vnd.oasis.opendocument.text": [".odt"], "application/vnd.openxmlformats-officedocument.wordprocessingml.document": [".docx"], "text/plain": [".txt", ".md"] }}</pre>	No links
401	Unauthorized	No links
403	Forbidden Media type application/json	No links

Code	Description	Links
	Example Value Schema <pre>{ "message": "Invalid API Key" }</pre>	
404	Not Found	No links
500	Internal Server Error	No links

GET

/v1/document/metadata-schema

 

Get the known available metadata schema for when doing a raw-text upload and the acceptable type of value for each key.

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "schema": { "keyOne": "string number nullable", "keyTwo": "string number nullable", "specialKey": "number", "title": "string" } }</pre>	No links
401	Unauthorized	No links

Code	Description	Links
403	Forbidden Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key" }</pre>	No links
500	Internal Server Error	No links

GET

/v1/document/{docName}



Get a single document by its unique AnythingLLM document name

Parameters

Try it out

Name	Description
docName ★ required string (path)	Unique document name to find (name in /documents) docName

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "localFiles": {</pre>	No links

Code	Description	Links
	<pre>"name": "documents", "type": "folder", "items": [{ "name": "my-stored-document.txt-uuid1234.json", "type": "file", "id": "bb07c334-4dab-4419-9462-9d00065a49a1", "url": "file://my-stored-document.txt", "title": "my-stored-document.txt", "cached": false }] }</pre>	
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json	
	Example Value Schema	
	<pre>{ "message": "Invalid API Key" }</pre>	
404	Not Found	No links
500	Internal Server Error	No links

POST /v1/document/create-folder



Create a new folder inside the documents storage directory.

Parameters

Try it out

No parameters

Request body required

application/json

Name of the folder to create.

Example Value Schema

```
{
  "name": "new-folder"
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "success": true, "message": null }</pre>	No links
401	Unauthorized	No links
403	Forbidden Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key" }</pre>	No links
500	Internal Server Error	No links

DELETE /v1/document/remove-folder



Remove a folder and all its contents from the documents storage directory.

Parameters

Try it out

No parameters

Request body required

application/json

Name of the folder to remove.

Example Value Schema

```
{
  "name": "my-folder"
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "success": true, "message": "Folder removed successfully" }</pre>	No links
401	Unauthorized	No links
403	Forbidden Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key" }</pre>	No links
500	Internal Server Error	No links

POST

/v1/document/move-files



Move files within the documents storage directory.

Parameters

Try it out

No parameters

Request body required

application/json

Array of objects containing source and destination paths of files to move.

Example Value Schema

```
{
  "files": [
    {
      "from": "custom-documents/file.txt-fc4beeeb-e436-454d-8bb4-e5b8979cb48f.json",
      "to": "folder/file.txt-fc4beeeb-e436-454d-8bb4-e5b8979cb48f.json"
    }
  ]
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "success": true, "message": null }</pre>	No links
401	Unauthorized	No links
403	Forbidden	No links

Code	Description	Links
	Media type application/json Example ValueSchema <pre>{ "message": "Invalid API Key" }</pre>	
500	Internal Server Error	No links

Workspaces

POST

/v1/workspace/new

Create a new workspace

Parameters

Try it out

No parameters

Request body required

application/json

JSON object containing workspace configuration.

Example Value

```
{  
  "name": "My New Workspace",  
  "similarityThreshold": 0.7,  
  "openAiTemp": 0.7,  
  "openAiHistory": 20,  
  "openAiPrompt": "Custom prompt for responses",  
  "queryRefusalResponse": "Custom refusal message",  
  "chatMode": "chat",  
  "topN": 4  
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example ValueSchema <pre>{ "workspace": { "id": 79, "name": "Sample workspace", "slug": "sample-workspace", "createdAt": "2023-08-17 00:45:03", "openAiTemp": null, "lastUpdatedAt": "2023-08-17 00:45:03", "openAiHistory": 20, "openAiPrompt": null }, "message": "Workspace created"}</pre>	No links
400	Bad Request	No links
403	Forbidden Media type application/json Example ValueSchema <pre>{ "message": "Invalid API Key"}</pre>	No links
500	Internal Server Error	No links

GET

/v1/workspaces



List all current workspaces

Parameters

Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example ValueSchema <pre>{ "workspaces": [{ "id": 79, "name": "Sample workspace", "slug": "sample-workspace", "createdAt": "2023-08-17 00:45:03", "openAiTemp": null, "lastUpdatedAt": "2023-08-17 00:45:03", "openAiHistory": 20, "openAiPrompt": null, "threads": [] }]}</pre>	No links
401	Unauthorized	No links
403	Forbidden Media type application/json Example ValueSchema <pre>{ "message": "Invalid API Key"}</pre>	No links
500	Internal Server Error	No links

GET

/v1/workspace/{slug}



Get a workspace by its unique slug.

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace to find

slug

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "workspace": [{ "id": 79, "name": "My workspace", "slug": "my-workspace-123", "createdAt": "2023-08-17 00:45:03", "openAiTemp": null, "lastUpdatedAt": "2023-08-17 00:45:03", "openAiHistory": 20, "openAiPrompt": null, "documents": [], "threads": [] }]}</pre>	No links
401	Unauthorized	No links
403	Forbidden Media type application/json Example Value Schema	No links

Code	Description	Links
	<pre>{ "message": "Invalid API Key" }</pre>	
500	Internal Server Error	No links

DELETE

/v1/workspace/{slug}



Deletes a workspace by its slug.

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace to delete
	slug

Responses

Code	Description	Links
200	OK	No links
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links

Media type

application/json

Example Value Schema

```
{  
  "message": "Invalid API Key"  
}
```

Code	Description	Links
500	Internal Server Error	No links

POST

/v1/workspace/{slug}/update



Update workspace settings by its unique slug.

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace to find

slug

Request body required

application/json

JSON object containing new settings to update a workspace. All keys are optional and will not update unless provided

Example Value

```
{  "name": "Updated Workspace Name",  "openAiTemp": 0.2,  "openAiHistory": 20,  "openAiPrompt": "Respond to all inquires and questions in binary - do not respond in any other format."}
```

Responses

Code	Description	Links
200	OK	No links

Media type

application/json

Controls Accept header.

Code	Description	Links
	Example ValueSchema <pre>{ "workspace": { "id": 79, "name": "My workspace", "slug": "my-workspace-123", "createdAt": "2023-08-17 00:45:03", "openAiTemp": null, "lastUpdatedAt": "2023-08-17 00:45:03", "openAiHistory": 20, "openAiPrompt": null, "documents": [] }, "message": null}</pre>	
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json	
	Example ValueSchema <pre>{ "message": "Invalid API Key"}</pre>	
500	Internal Server Error	No links

GET

/v1/workspace/{slug}/chats



Get a workspaces chats regardless of user by its unique slug.

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace to find

slug

Name	Description
apiSessionId string (query)	Optional apiSessionId to filter by apiSessionId
limit integer (query)	Optional number of chat messages to return (default: 100) limit
orderBy string (query)	Optional order of chat messages (asc or desc) orderBy

Responses

Code	Description	Links
200	OK	No links

Media type

application/json

Controls Accept header.

Example Value Schema

```
{
  "history": [
    {
      "role": "user",
      "content": "What is AnythingLLM?",
      "sentAt": 1692851630
    },
    {
      "role": "assistant",
      "content": "AnythingLLM is a platform that allows you to
convert notes, PDFs, and other source materials into a chatbo
t. It ensures privacy, cites its answers, and allows multiple
people to interact with the same documents simultaneously. It
is particularly useful for businesses to enhance the visibilit
y and readability of various written communications such as SO
Ps, contracts, and sales calls. You can try it out with a free
trial to see if it meets your business needs.",
      "sources": [
        {
          "source": "object about source document and snippets
used"
        }
      ]
    }
  ]
}
```

Code	Description	Links
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "message": "Invalid API Key"}</pre>	
500	Internal Server Error	No links

POST

/v1/workspace/{slug}/update-embeddings



Add or remove documents from a workspace by its unique slug.

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace to find
	slug

Request body required

application/json

JSON object of additions and removals of documents to add to update a workspace. The value should be the folder + filename with the exclusions of the top-level documents path.

Example Value

```
{  "adds": [    "custom-documents/my-pdf.pdf-hash.json"  ],  "deletes": [    "custom-documents/anythingllm.txt-hash.json"  ]}
```

```
]
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "workspace": { "id": 79, "name": "My workspace", "slug": "my-workspace-123", "createdAt": "2023-08-17 00:45:03", "openAiTemp": null, "lastUpdatedAt": "2023-08-17 00:45:03", "openAiHistory": 20, "openAiPrompt": null, "documents": [] }, "message": null }</pre>	No links
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key" }</pre>	
500	Internal Server Error	No links

Add or remove pin from a document in a workspace by its unique slug.

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace to find
	slug

Request body required

application/json

JSON object with the document path and pin status to update.

Example Value

```
{
  "docPath": "custom-documents/my-pdf.pdf-hash.json",
  "pinStatus": true
}
```

Responses

Code	Description	Links
200	OK	No links
	Media type	
	application/json	
	Controls Accept header.	
	Example Value	Schema
	<pre>{ "message": "Pin status updated successfully" }</pre>	
401	Unauthorized	No links
404	Document not found	No links

Code	Description	Links
500	Internal Server Error	No links

POST

/v1/workspace/{slug}/chat



Execute a chat with a workspace

Parameters

Try it out

Name	Description
slug * required string (path)	slug

Request body required

application/json

Send a prompt to the workspace and the type of conversation (query or chat).

Query: Will not use LLM unless there are relevant sources from vectorDB & does not recall chat history.

Chat: Uses LLM general knowledge w/custom embeddings to produce output, uses rolling chat history.

Example Value

```
{
  "message": "What is AnythingLLM?",
  "mode": "query | chat",
  "sessionId": "identifier-to-partition-chats-by-external-id",
  "attachments": [
    {
      "name": "image.png",
      "mime": "image/png",
      "contentString": "..."
    }
  ],
  "reset": false
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": "chat-uuid", "type": "abort textResponse", "textResponse": "Response to your query", "sources": [{ "title": "anythingllm.txt", "chunk": "This is a context chunk used in the answer of the prompt by the LLM," }], "close": true, "error": "null text string of the failure mode."}</pre>	No links
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key"}</pre>	
500	Internal Server Error	No links

POST

/v1/workspace/{slug}/stream-chat



Execute a streamable chat with a workspace

Parameters

Try it out

NameDescription

slug * required

string

(path)

slug

Request body required

application/json

Send a prompt to the workspace and the type of conversation (query or chat).
Query: Will not use LLM unless there are relevant sources from vectorDB & does not recall chat history.
Chat: Uses LLM general knowledge w/custom embeddings to produce output, uses rolling chat history.

Example Value

```
{
  "message": "What is AnythingLLM?",
  "mode": "query | chat",
  "sessionId": "identifier-to-partition-chats-by-external-id",
  "attachments": [
    {
      "name": "image.png",
      "mime": "image/png",
      "contentString": "... "
    }
  ],
  "reset": false
}
```

Responses

Code	Description	Links
200	OK Media type text/event-stream Controls Accept header. Example Value Schema [{ "id": "uuid-123", "type": "abort textResponseChunk", "textResponse": "First chunk", "sources": [], "close": false,	No links

Code	Description	Links
	<pre>"error": "null text string of the failure mode." }, { "id": "uuid-123", "type": "abort textResponseChunk", "textResponse": "chunk two", "sources": [], "close": false, "error": "null text string of the failure mode." }, { "id": "uuid-123", "type": "abort textResponseChunk", "textResponse": "final chunk of LLM output!", "sources": [{ "title": "anythingllm.txt", "chunk": "This is a context chunk used in the answer o</pre>	

400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links

Media type

application/json

Example Value Schema

```
{
  "message": "Invalid API Key"
}
```

POST /v1/workspace/{slug}/vector-search



Perform a vector similarity search in a workspace

Parameters

Try it out

Name	Description
slug ★ required string (path)	Unique slug of workspace to search in slug

Request body required

application/json

Query to perform vector search with and optional parameters

Example Value

```
{
  "query": "What is the meaning of life?",
  "topN": 4,
  "scoreThreshold": 0.75
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "results": [{ "id": "5a6bee0a-306c-47fc-942b-8ab9bf3899c4", "text": "Document chunk content...", "metadata": { "url": "file://document.txt", "title": "document.txt", "author": "no author specified", "description": "no description found", "docSource": "post:123456", "chunkSource": "document.txt", "published": "12/1/2024, 11:39:39 AM", "wordCount": 8, "tokenCount": 9 }, "distance": 0.541887640953064, "score": 0.45811235904693604 }] }</pre>	No links
400	Bad Request	No links
401	Unauthorized	No links

Code	Description	Links
500	Internal Server Error	No links

System Settings



GET	/v1/system/env-dump	
GET	/v1/system	
GET	/v1/system/vector-count	
POST	/v1/system/update-env	
GET	/v1/system/export-chats	
DELETE	/v1/system/remove-documents	

Workspace Threads



POST

/v1/workspace/{slug}/thread/new

Create a new workspace thread

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace slug

Request body

application/json

Optional userId associated with the thread, thread slug and thread name

Example Value

```
{
  "userId": 1,
  "name": "Name",
  "slug": "thread-slug"
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "thread": { "id": 1, "name": "Thread", "slug": "thread-uuid", "user_id": 1, "workspace_id": 1 }, "message": null }</pre>	No links
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key" }</pre>	
500	Internal Server Error	No links

Update thread name by its unique slug.

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace slug
threadSlug * required string (path)	Unique slug of thread threadSlug

Request body required

application/json

JSON object containing new name to update the thread.

Example Value

```
{
  "name": "Updated Thread Name"
}
```

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "thread": { "id": 1, "name": "Updated Thread Name", "slug": "thread-uuid",</pre>	No links

Code	Description	Links
	<pre>"user_id": 1, "workspace_id": 1 }, "message": null }</pre>	
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type	
	application/json	
	Example Value Schema	
	<pre>{ "message": "Invalid API Key" }</pre>	
500	Internal Server Error	No links

DELETE /v1/workspace/{slug}/thread/{threadSlug}



Delete a workspace thread

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace slug
threadSlug * required string (path)	Unique slug of thread threadSlug

Responses

Code	Description	Links
200	Thread deleted successfully	No links
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
Media type		
application/json		
Example Value Schema		
<pre>{ "message": "Invalid API Key"}</pre>		
500	Internal Server Error	No links

GET /v1/workspace/{slug}/thread/{threadSlug}/chats



Get chats for a workspace thread

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace
threadSlug * required string (path)	Unique slug of thread

Responses

Code	Description	Links
200	OK Media type application/json Controls Accept header. Example Value Schema <pre>{ "history": [{ "role": "user", "content": "What is AnythingLLM?", "sentAt": 1692851630 }, { "role": "assistant", "content": "AnythingLLM is a platform that allows you to convert notes, PDFs, and other source materials into a chatbot. It ensures privacy, cites its answers, and allows multiple people to interact with the same documents simultaneously. It is particularly useful for businesses to enhance the visibility and readability of various written communications such as SOPs, contracts, and sales calls. You can try it out with a free trial to see if it meets your business needs.", "sources": [{ "source": "object about source document and snippets used" }] }]}</pre>	No links
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key"}</pre>	
500	Internal Server Error	No links

POST

/v1/workspace/{slug}/thread/{threadSlug}/chat



Chat with a workspace thread

Parameters

Try it out

Name	Description
slug * required string (path)	Unique slug of workspace
threadSlug * required string (path)	Unique slug of thread

Request body required

application/json

Send a prompt to the workspace thread and the type of conversation (query or chat).

Example Value

```
{
  "message": "What is AnythingLLM?",
  "mode": "query | chat",
  "userId": 1,
  "attachments": [
    {
      "name": "image.png",
      "mime": "image/png",
      "contentString": "..."
    }
  ],
  "reset": false
}
```

Responses

Code	Description	Links
200	OK	No links

Code	Description	Links
	Media type application/json Controls Accept header. Example Value Schema <pre>{ "id": "chat-uuid", "type": "abort textResponse", "textResponse": "Response to your query", "sources": [{ "title": "anythingllm.txt", "chunk": "This is a context chunk used in the answer of the prompt by the LLM." }], "close": true, "error": "null text string of the failure mode."}</pre>	
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
	Media type application/json Example Value Schema <pre>{ "message": "Invalid API Key"}</pre>	
500	Internal Server Error	No links

POST

/v1/workspace/{slug}/thread/{threadSlug}/stream-chat



Stream chat with a workspace thread

Parameters

Try it out

Name		Description
slug * required string (path)		Unique slug of workspace slug
threadSlug * required string (path)		Unique slug of thread threadSlug
Request body required		application/json
Send a prompt to the workspace thread and the type of conversation (query or chat). Example Value <pre>{ "message": "What is AnythingLLM?", "mode": "query chat", "userId": 1, "attachments": [{ "name": "image.png", "mime": "image/png", "contentString": "..." }], "reset": false}</pre>		
Responses		
Code	Description	Links
200	OK Media type text/event-stream Controls Accept header. Example Value Schema [{ "id": "uuid-123", "type": "abort textResponseChunk",	No links

Code	Description	Links
	<pre>"textResponse": "First chunk", "sources": [], "close": false, "error": "null text string of the failure mode." }, { "id": "uuid-123", "type": "abort textResponseChunk", "textResponse": "chunk two", "sources": [], "close": false, "error": "null text string of the failure mode." }, { "id": "uuid-123", "type": "abort textResponseChunk", "textResponse": "final chunk of LLM output!", "sources": [{ "title": "anythingllm.txt", "url": "https://anythingllm.com/docs/...", "score": 0.9 }] }</pre>	
400	Bad Request	No links
401	Unauthorized	No links
403	Forbidden	No links
Media type		
application/json		
Example Value Schema		
<pre>{ "message": "Invalid API Key" }</pre>		

User Management

GET	/v1/users	 
GET	/v1/users/{id}/issue-auth-token	 

OpenAI Compatible Endpoints

GET	/v1/openai/models	 
POST	/v1/openai/chat/completions	 

POST	/v1/openai/embeddings	 
GET	/v1/openai/vector_stores	 

Embed

Schemas 
InvalidAPIKey