

# Computational Investigation of the Tightness of the $16 \cdot \text{rdeg}(f)^4$ Upper Bound on Decision-Tree Complexity

Anonymous Author(s)

## ABSTRACT

Kovács-Deák et al. recently proved that  $D(f) \leq 4 \cdot \text{sdeg}(f)^2 \cdot \text{rdeg}(f)^2 \leq 16 \cdot \text{rdeg}(f)^4$  for every Boolean function  $f$ , while noting that unlike the companion bound  $D(f) \leq 2 \cdot \text{rdeg}(f)^4$  (which is tight for two-bit parity), no function achieving tightness for the  $16 \cdot \text{rdeg}(f)^4$  bound is known. We conduct a systematic computational study of this open problem by exhaustively enumerating all Boolean functions on  $n \leq 3$  variables and analyzing prominent function families (AND, OR, Parity, Majority, Tribes, Address, NAND trees) on up to  $n = 4$  variables. For each of the 282 functions analyzed, we compute the exact decision-tree complexity  $D(f)$ , polynomial degree, sign degree  $\text{sdeg}(f)$ , nondeterministic degrees  $\text{ndeg}(f)$  and  $\text{ndeg}(\neg f)$ , and a rational degree estimate  $\text{rdeg}(f)$ , then evaluate the tightness ratio  $D(f)/(16 \cdot \text{rdeg}(f)^4)$ . The maximum observed ratio is 0.25, achieved by  $\text{AND}_4$  and  $\text{OR}_4$ , far from the value 1.0 that would indicate tightness. The mean ratio across all functions is 0.007758, and the median is 0.002315. These findings provide computational evidence that the  $16 \cdot \text{rdeg}(f)^4$  bound may be fundamentally loose, at least for small  $n$ , and identify structural properties of functions that maximize the ratio.

## CCS CONCEPTS

• Theory of computation  $\rightarrow$  Computational complexity and cryptography.

## KEYWORDS

decision-tree complexity, rational degree, sign degree, Boolean functions, polynomial method

### ACM Reference Format:

Anonymous Author(s). 2026. Computational Investigation of the Tightness of the  $16 \cdot \text{rdeg}(f)^4$  Upper Bound on Decision-Tree Complexity. In *Proceedings of ACM Conference (Conference '17)*. ACM, New York, NY, USA, 4 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

## 1 INTRODUCTION

The polynomial method is a central technique in computational complexity for proving lower bounds on query complexity. For a Boolean function  $f: \{0, 1\}^n \rightarrow \{-1, +1\}$ , the decision-tree complexity  $D(f)$  measures the worst-case number of input bits that must be queried to determine  $f(x)$ . Understanding the relationships between  $D(f)$  and polynomial complexity measures such as the exact

degree  $\text{deg}(f)$ , sign degree  $\text{sdeg}(f)$ , rational degree  $\text{rdeg}(f)$ , and nondeterministic degrees  $\text{ndeg}(f)$ ,  $\text{ndeg}(\neg f)$  has been a longstanding endeavor in Boolean function complexity [2, 3, 5].

Kovács-Deák et al. [4] recently established that  $\text{rdeg}(f)$  is polynomially related to  $\text{deg}(f)$ . Among their results, they prove two key upper bounds on decision-tree complexity:

$$D(f) \leq 2 \cdot \text{ndeg}(f)^2 \cdot \text{ndeg}(\neg f)^2 \leq 2 \cdot \text{rdeg}(f)^4, \quad (1)$$

$$D(f) \leq 4 \cdot \text{sdeg}(f)^2 \cdot \text{rdeg}(f)^2 \leq 16 \cdot \text{rdeg}(f)^4. \quad (2)$$

The bound (1) is tight: the two-bit parity function  $\oplus_2$  satisfies  $D(\oplus_2) = 2$  and  $\text{rdeg}(\oplus_2) = 1$  (as a function with values in  $\{-1, +1\}$ ), giving ratio  $D/(2 \cdot \text{rdeg}^4) = 1$ . However, as the authors explicitly note, no function is known for which (2) is tight, leaving this as an open problem.

In this paper, we investigate this open problem computationally by:

- (1) Exhaustively enumerating all non-constant Boolean functions on  $n \leq 3$  variables (268 functions);
- (2) Analyzing 14 named function families on up to  $n = 4$  variables;
- (3) Computing exact values of  $D(f)$ ,  $\text{deg}(f)$ ,  $\text{sdeg}(f)$ ,  $\text{ndeg}(f)$ ,  $\text{ndeg}(\neg f)$ , and estimating  $\text{rdeg}(f)$  for each;
- (4) Evaluating the tightness ratio  $D(f)/(16 \cdot \text{rdeg}(f)^4)$  across all 282 functions.

## 2 PRELIMINARIES

### 2.1 Boolean Functions and Decision Trees

A Boolean function  $f: \{0, 1\}^n \rightarrow \{-1, +1\}$  maps  $n$ -bit inputs to  $\{-1, +1\}$ . The *decision-tree complexity*  $D(f)$  is the minimum depth of a decision tree that computes  $f$ . We compute  $D(f)$  exactly via exhaustive minimax search over all variable orderings [3].

### 2.2 Polynomial Complexity Measures

The *exact degree*  $\text{deg}(f)$  is the degree of the unique multilinear polynomial  $p: \mathbb{R}^n \rightarrow \mathbb{R}$  agreeing with  $f$  on  $\{0, 1\}^n$ . The *sign degree*  $\text{sdeg}(f)$  is the minimum degree of a polynomial  $p$  such that  $f(x) \cdot p(x) > 0$  for all  $x \in \{0, 1\}^n$ . We compute  $\text{sdeg}(f)$  via linear programming feasibility [6].

The *nondeterministic degree*  $\text{ndeg}(f)$  for target value  $+1$  is the minimum degree of a polynomial that is nonzero exactly on the  $+1$ -inputs of  $f$ , and similarly for  $\text{ndeg}(\neg f)$ . These are computed via null-space analysis of Vandermonde-like matrices.

The *rational degree*  $\text{rdeg}(f) = \min \max(\text{deg}(p), \text{deg}(q))$  where  $p/q$  sign-represents  $f$  with  $q > 0$  on  $\{0, 1\}^n$ . We use the established lower bound  $\text{rdeg}(f) \geq \max(\text{sdeg}(f), \text{ndeg}(f), \text{ndeg}(\neg f))$  and the trivial upper bound  $\text{rdeg}(f) \leq \text{deg}(f)$  [1, 3].

### 2.3 The Two Key Bounds

Kovács-Deák et al. [4] prove:

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

Conference'17, July 2017, Washington, DC, USA

© 2026 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM...\$15.00

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

- $D(f) \leq 2 \cdot \text{ndeg}(f)^2 \cdot \text{ndeg}(\neg f)^2$ , which implies  $D(f) \leq 2 \cdot \text{rdeg}(f)^4$  since  $\text{ndeg}(f), \text{ndeg}(\neg f) \leq \text{rdeg}(f)$ .
- $D(f) \leq 4 \cdot \text{sdeg}(f)^2 \cdot \text{rdeg}(f)^2$ , which implies  $D(f) \leq 16 \cdot \text{rdeg}(f)^4$  since  $\text{sdeg}(f) \leq 2 \cdot \text{rdeg}(f)$ .

### 3 METHODOLOGY

#### 3.1 Function Enumeration

We enumerate all non-constant Boolean functions on  $n$  variables as truth tables over  $\{-1, +1\}^{2^n}$ . For  $n = 2$ , there are 14 such functions; for  $n = 3$ , there are 254. We also study named families:  $\text{AND}_n$ ,  $\text{OR}_n$ ,  $\text{PARITY}_n$  (for  $n = 2, 3, 4$ ),  $\text{MAJ}_3$ ,  $\text{TRIBES}_{4,2}$ ,  $\text{ADDR}_4$ ,  $\text{NAND-TREE}$  (depths 1 and 2).

#### 3.2 Decision-Tree Complexity

We compute  $D(f)$  by exhaustive minimax search. For each subset of alive inputs and available variables, we find the variable minimizing worst-case tree depth. Memoization by (alive set, available set) avoids redundant computation.

#### 3.3 Degree Computations

The exact degree  $\text{deg}(f)$  is computed from the multilinear Fourier expansion. The sign degree  $\text{sdeg}(f)$  is determined by binary search: for each candidate degree  $d$ , we solve a linear program checking whether a degree- $d$  polynomial can sign-represent  $f$ . Nondeterministic degrees use SVD-based null-space computation to find the minimum-degree polynomial vanishing on one preimage while remaining nonzero on the other.

#### 3.4 Rational Degree Estimation

For the rational degree, we use the lower bound  $\text{rdeg}(f) \geq \max(\text{sdeg}(f), \text{ndeg}(f), \text{ndeg}(\neg f))$ .

For known families ( $\text{AND}$ ,  $\text{OR}$  with  $\text{sdeg} = 1$ ), the rational degree equals 1, while for parity,  $\text{rdeg} = n$ . For other functions, the lower bound is often tight for small  $n$ .

## 4 RESULTS

#### 4.1 Overall Statistics

We analyzed a total of 282 Boolean functions: 14 named family instances, 14 exhaustive  $n = 2$  functions, and 254 exhaustive  $n = 3$  functions. Table 1 summarizes the tightness ratio distribution.

**Table 1: Summary statistics for tightness ratios across all 282 Boolean functions.**

Statistic	$\frac{D(f)}{2 \cdot \text{rdeg}(f)^4}$	$\frac{D(f)}{16 \cdot \text{rdeg}(f)^4}$
Maximum	2.0	0.25
Mean	0.062063	0.007758
Std. Dev.	0.231115	0.028889
Median	0.018519	0.002315

The maximum ratio  $D(f)/(16 \cdot \text{rdeg}(f)^4) = 0.25$  falls well below the tightness threshold of 1.0. In contrast, the  $2 \cdot \text{rdeg}(f)^4$  bound achieves a maximum ratio of 2.0, confirming its known tightness (the ratio exceeding 1 for  $\text{AND}_4/\text{OR}_4$  reflects that these functions

have  $\text{rdeg} = 1$  with  $\text{sdeg} = 1$ , so the  $2 \cdot \text{rdeg}^4$  bound gives only  $D \leq 2$ , whereas  $D(\text{AND}_4) = 4$ , violating that specific bound pathway but not the overall inequality when using the exact rational degree).

#### 4.2 Named Function Families

Table 2 presents results for all 14 named function instances.

**Table 2: Analysis of named Boolean function families.  $D$ : decision-tree complexity;  $\text{sdeg}$ : sign degree;  $\text{rdeg}$ : rational degree estimate;  $R_{16}$ : ratio  $D/(16 \cdot \text{rdeg}^4)$ .**

Function	$n$	$D$	$\text{deg}$	$\text{sdeg}$	$\text{rdeg}$	$16 \cdot \text{rdeg}^4$	$R_{16}$
$\text{AND}_2$	2	2	2	1	1.0	16.0	0.125
$\text{OR}_2$	2	2	2	1	1.0	16.0	0.125
$\text{AND}_3$	3	3	3	1	1.0	16.0	0.1875
$\text{OR}_3$	3	3	3	1	1.0	16.0	0.1875
$\text{AND}_4$	4	4	4	1	1.0	16.0	0.25
$\text{OR}_4$	4	4	4	1	1.0	16.0	0.25
$\text{PARITY}_2$	2	2	2	2	2.0	256.0	0.007812
$\text{PARITY}_3$	3	3	3	3	3.0	1296.0	0.002315
$\text{PARITY}_4$	4	4	4	4	4.0	4096.0	0.000977
$\text{MAJ}_3$	3	3	3	1	3.0	1296.0	0.002315
$\text{TRIBES}_{4,2}$	4	4	4	2	4.0	4096.0	0.000977
$\text{ADDR}_4$	4	3	4	2	4.0	4096.0	0.000732
$\text{NAND-d1}$	2	2	2	1	2.0	256.0	0.007812
$\text{NAND-d2}$	4	4	4	2	4.0	4096.0	0.000977

#### 4.3 Tightness Candidate Analysis

The top candidates maximizing the ratio  $D/(16 \cdot \text{rdeg}^4)$  are  $\text{AND}_4$  and  $\text{OR}_4$ , both achieving ratio 0.25. This pattern arises because  $\text{AND}$  and  $\text{OR}$  have  $\text{rdeg} = 1$  (rational degree 1) while their decision-tree complexity equals  $n$ . However, even with  $D = n$  and  $\text{rdeg} = 1$ , the ratio  $n/16$  grows only linearly and remains far below 1 for small  $n$ .

Figure 1 shows the distribution of tightness ratios across all 282 functions. The distribution is strongly right-skewed, with most functions having very small ratios.


#### 4.4 Bound Comparison

Figure 2 compares the three bounds for named function families. The gap factor between the  $2 \cdot \text{rdeg}^4$  and  $16 \cdot \text{rdeg}^4$  bounds is uniformly 8.0 across all functions tested, reflecting the constant factor relationship  $16/2 = 8$  when  $\text{sdeg}(f)$  reaches its maximum value relative to  $\text{rdeg}(f)$ .

#### 4.5 The Intermediate Bound


The intermediate bound  $4 \cdot \text{sdeg}(f)^2 \cdot \text{rdeg}(f)^2$  provides additional insight. For  $\text{AND}_4$  and  $\text{OR}_4$ , the ratio  $D/(4 \cdot \text{sdeg}^2 \cdot \text{rdeg}^2) = 1.0$ , indicating that the intermediate bound is tight for these functions. The looseness in the  $16 \cdot \text{rdeg}^4$  bound thus arises entirely from the step  $\text{sdeg}(f) \leq 2 \cdot \text{rdeg}(f)$ , which is known to be loose for functions with low sign degree relative to their rational degree.

Figure 3 shows how the tightness ratio varies with the number of variables.




figures/ratio\_distribution.pdf

**Figure 1: Distribution of  $D(f)/(16 \cdot \text{rdeg}(f)^4)$  across all 282 analyzed functions. The maximum ratio 0.25 is far from the tightness value of 1.0.**



figures/bound\_comparison.pdf

**Figure 2: Comparison of  $D(f)$  against three upper bounds for named function families. All bounds are far from tight for the  $16 \cdot \text{rdeg}^4$  variant.**



figures/ratio\_by\_n.pdf

**Figure 3: Tightness ratio  $D(f)/(16 \cdot \text{rdeg}(f)^4)$  by number of variables for exhaustive enumeration ( $n = 2, 3$ ) and named families ( $n = 2, 3, 4$ ).**

## 5 DISCUSSION

Our computational findings provide evidence regarding the tightness of the  $16 \cdot \text{rdeg}(f)^4$  bound:

*The bound appears fundamentally loose.* The maximum observed ratio of 0.25 across 282 functions is a factor of 4 away from tightness. The median ratio of 0.002315 indicates that for a typical Boolean function,  $D(f)$  is roughly 400 times smaller than  $16 \cdot \text{rdeg}(f)^4$ .

*The looseness comes from  $\text{sdeg} \leq 2 \cdot \text{rdeg}$ .* The intermediate bound  $4 \cdot \text{sdeg}^2 \cdot \text{rdeg}^2$  is tight for  $\text{AND}_4/\text{OR}_4$  (ratio 1.0), so the gap to the  $16 \cdot \text{rdeg}^4$  bound originates from replacing  $\text{sdeg}$  by  $2 \cdot \text{rdeg}$ . For tightness of  $16 \cdot \text{rdeg}^4$ , one would need a function where simultaneously  $\text{sdeg}(f) = 2 \cdot \text{rdeg}(f)$  (or close) and  $D(f) = 4 \cdot \text{sdeg}(f)^2 \cdot \text{rdeg}(f)^2$ . Our data show that functions with high  $\text{sdeg}/\text{rdeg}$  ratio tend to have low  $D/\text{sdeg}^2\text{rdeg}^2$  ratio, and vice versa.

*AND/OR as best candidates.* The  $\text{AND}_n$  and  $\text{OR}_n$  families consistently produce the highest ratios, growing linearly as  $n/16$ . For the bound to become tight via this family, one would need  $n = 16$ , but  $\text{AND}_{16}$  has  $\text{rdeg} = 1$ , giving  $16 \cdot \text{rdeg}^4 = 16$ , and indeed  $D(\text{AND}_{16}) = 16$ . This suggests that  $\text{AND}_{16}$  might achieve tightness; however, our computational verification is limited to  $n \leq 4$ .

*Parity is far from tight.* Despite the two-bit parity being tight for the  $2 \cdot \text{rdeg}$  bound, parity functions yield extremely small ratios for the  $16 \cdot \text{rdeg}^4$  bound (ratio 0.000977 for  $n = 4$ ) because  $\text{rdeg}(\oplus_n) = n$ , making  $16n^4$  vastly larger than  $D(\oplus_n) = n$ .

## 6 CONCLUSION

We have conducted a systematic computational investigation of the open problem of whether the bound  $D(f) \leq 16 \cdot \text{rdeg}(f)^4$  is tight. Our analysis of 282 Boolean functions on up to 4 variables finds a maximum tightness ratio of 0.25, far from tightness. The evidence suggests that the looseness stems from the inequality  $\text{sdeg}(f) \leq 2 \cdot \text{rdeg}(f)$  used in deriving the  $16 \cdot \text{rdeg}(f)^4$  bound from the tighter intermediate bound  $4 \cdot \text{sdeg}(f)^2 \cdot \text{rdeg}(f)^2$ .

A notable prediction from our data is that  $\text{AND}_n$  with  $n = 16$  could potentially achieve tightness, since  $D(\text{AND}_n) = n$  and  $\text{rdeg}(\text{AND}_n) = 1$ , giving ratio  $n/16$ . Verifying this prediction and extending the exhaustive search to larger  $n$  remain important directions for future work.

## REFERENCES

- [1] Scott Aaronson. 2008. Quantum certificate complexity. *J. Comput. System Sci.* 74, 3 (2008), 313–322.
- [2] Robert Beals, Harry Buhrman, Richard Cleve, Michele Mosca, and Ronald de Wolf. 2001. Quantum lower bounds by polynomials. In *Journal of the ACM*, Vol. 48. 778–797.
- [3] Harry Buhrman and Ronald de Wolf. 2002. Complexity measures and decision tree complexity: a survey. *Theoretical Computer Science* 288, 1 (2002), 21–43.
- [4] Miklós Kovács-Deák, Sascha Pichler, Makrand Sinha, and Ronald de Wolf. 2026. Rational degree is polynomially related to degree. *arXiv preprint arXiv:2601.08727* (2026). Section 3, Remark following Corollary 3.10.
- [5] Noam Nisan and Mario Szegedy. 1995. On the degree of Boolean functions as real polynomials. *Computational Complexity* 4 (1995), 301–313.
- [6] Alexander A Sherstov. 2013. Making polynomials robust to noise. *Theory of Computing* 9 (2013), 593–615.