Notes:

- MDE bar today
- MDE pulled, Jun Oct 26
- Mini-workshop, Jun Oct 26
- Mini-Lab Lecture Oliver Bonas, Aswell on October 27

Last class: testing

- assumptions
- testing things, using p-values
- confidence, regression tests
- effect size

A common task for R starting is GitHub actions

Let's commit our code that we made to set up test, and setup a GitHub actions workflow to run tests.

Two steps to setting this up

- Setup a workflow to run (using code and tests to that directory)
- Write a job actions

Copy from another project, now, at `~/p/2/BUILDWITHSCIENCE/gdf1`

Exports

1. What exactly triggers the CI? Here, pushes to main and PRs
2. What is the testing environment: Ubuntu or other (choose windows or macos). Use python 3.9. And `~/bin/CHANGEMULTIOS` to exactly what libraries are needed.
3. Run actions
   - checkout repo
   - setup python
   - install dependencies

Add and commit everything, including `.github/workflows/gdf1.yml`, and push.

Only a small change, now we can look to our commit messages. 3 different things might appear

- tested red, indicating actions are in process
- green check, meaning all actions ran and passed
- red x, meaning some action failed

What if I now, say to an open pull request, say on main or develop, and that information about what was successful or not (shielded badge)?

Make something fail. Know

```
                                                    ANALYSIS/gdf1 > check > gf1 > pytest -q gdf1.fit

...                                                                                                                  [100%]
3 passed in 0.04s

GHA_SUBSCRIBE to see this, but now a mistake

Important: do this on a branch, to not mess up passing tests on main

    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ git checkout -b gha_example
    Switched to a new branch 'gha_example'
    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ git commit -am "Add failing test for GHA example"
    [gha_example 1a1ac0c] Add failing test for GHA example
     1 file changed, 1 insertion(+), 1 deletion(-)
    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ git push
    fatal: The current branch gha_example has no upstream branch.
    To push the current branch and set the remote as upstream, use

        git push --set-upstream origin gha_example

    To have this happen automatically for branches without a tracking
    upstream, see 'push.autoSetupRemote' in 'git help config'.

    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ git push --set-upstream origin gha_example
    Enumerating objects: 5, done.
    Counting objects: 100% (5/5), done.
    Delta compression using up to 8 threads
    Compressing objects: 100% (3/3), done.
    Writing objects: 100% (3/3), 350 bytes | 350.00 KiB/s, done.
    Total 3 (delta 2), reused 0 (delta 0), pack-reused 0
    remote: Resolving deltas: 100% (2/2), completed with 2 local objects.
    remote:
    remote: Create a pull request for 'gha_example' on GitHub by visiting:
    remote:      https://github.com/curtisbucher/BUILDWITHSCIENCE/pull/new/gha_example
    remote:
    To github.com:curtisbucher/BUILDWITHSCIENCE.git
     * [new branch]      gha_example -> gha_example
    branch 'gha_example' set up to track 'origin/gha_example'.
    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$

Check the PR, see failing tests.

    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ git add tests/test_gdf.py
    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ git commit -m "Fix GHA example"
    [gha_example 2b1e3f4] Fix GHA example
     1 file changed, 1 insertion(+), 1 deletion(-)
    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ git push
    Enumerating objects: 5, done.
    Counting objects: 100% (5/5), done.
    Delta compression using up to 8 threads
    Compressing objects: 100% (3/3), done.
    Writing objects: 100% (3/3), 350 bytes | 350.00 KiB/s, done.
    Total 3 (delta 2), reused 0 (delta 0), pack-reused 0
    remote: Resolving deltas: 100% (2/2), completed with 2 local objects.
    To github.com:curtisbucher/BUILDWITHSCIENCE.git
       1a1ac0c..2b1e3f4  gha_example -> gha_example
    (base) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$

If you're running tests, even just on main, you can add a badge.

Now adding that run to terminal is now run in that environment, with `GHA_SUBSCRIBE`

Which works fine in that error, but it's a mistake. Let's commit and push, and those passages are only "visible" when we're running pytest from within the same.

In this lab, setup tests, then workflow/actions, then run some tests, and/or some assertions.

Now that within a env, `pytest -q` and `gdf1` will be the python used to create the env, and `pytest -q` and `gdf1` are two different versions of python on your system and you run

    pytest -q tests/test_gdf.py
    gdf1 -h

Lets start now, `gdf1/gdf.py` is what we'll create and test.

Write a bit of notes in to handle libraries gracefully, but to install one

```
    (BUILDWITHSCIENCE) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ pip install -e .
    Obtaining file:///home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1
      Installing build dependencies ... done
      Checking if build backend supports build_editable ... done
      Getting requirements to build editable ... done
      Preparing editable metadata (pyproject.toml) ... done
    Collecting numpy (from gdf1==0.1.0)
      Downloading numpy-2.0.2-cp39-cp39-manylinux_2_17_x86_64.manylinux2014_x86_64.whl.metadata (59 kB)
    Collecting pandas (from gdf1==0.1.0)
      Downloading pandas-2.3.3-cp39-cp39-manylinux_2_17_x86_64.manylinux2014_x86_64.whl.metadata (91 kB)
    Collecting python-dateutil>=2.8.2 (from pandas)
      Downloading python_dateutil-2.9.0.post0-py2.py3-none-any.whl.metadata (8.4 kB)
    Collecting pytz>=2020.1 (from pandas)
      Downloading pytz-2025.2-py2.py3-none-any.whl.metadata (22 kB)
    Collecting tzdata>=2022.7 (from pandas)
      Downloading tzdata-2025.2-py2.py3-none-any.whl.metadata (1.4 kB)
    Collecting six>=1.5 (from python-dateutil>=2.8.2->pandas)
      Downloading six-1.17.0-py2.py3-none-any.whl.metadata (1.7 kB)
    Downloading numpy-2.0.2-cp39-cp39-manylinux_2_17_x86_64.manylinux2014_x86_64.whl (19.5 MB)
       ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 19.5/19.5 MB 3.5 MB/s eta 0:00:00
    Downloading pandas-2.3.3-cp39-cp39-manylinux_2_17_x86_64.manylinux2014_x86_64.whl (12.3 MB)
       ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 12.3/12.3 MB 3.5 MB/s eta 0:00:00
    Downloading python_dateutil-2.9.0.post0-py2.py3-none-any.whl (229 kB)
    Downloading pytz-2025.2-py2.py3-none-any.whl (509 kB)
    Downloading tzdata-2025.2-py2.py3-none-any.whl (347 kB)
    Downloading six-1.17.0-py2.py3-none-any.whl (11.4 kB)
    Building wheels for collected packages: gdf1
      Building editable for gdf1 (pyproject.toml) ... done
      Created wheel for gdf1: filename=gdf1-0.1.0-0.editable-py3-none-any.whl size=3744 sha256=ff0ed1ca0ed1ca0ed1ca0ed1ca0ed1ca0ed1ca0ed1ca0ed1ca0ed1ca0ed1ca0e
      Stored in directory: /tmp/pip-ephem-wheel-cache-xxxxxxxx/wheels/xx/xx/xx/xxxxxxxxxxxxxxxxxxxxxxxx
    Successfully built gdf1
    Installing collected packages: pytz, tzdata, six, numpy, python-dateutil, pandas, gdf1
    Successfully installed gdf1-0.1.0 numpy-2.0.2 pandas-2.3.3 python-dateutil-2.9.0.post0 pytz-2025.2 six-1.17.0 tzdata-2025.2
    (BUILDWITHSCIENCE) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ gdf1 -h
    usage: gdf1 [-h] {fit,predict} ...

    positional arguments:
      {fit,predict}
        fit          Fit a model
        predict      Predict with a model

    options:
      -h, --help     show this help message and exit
    (BUILDWITHSCIENCE) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$
```

Notes

```
    (BUILDWITHSCIENCE) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ gdf1 fit
    usage: gdf1 fit [-h] --data DATA --target TARGET --features FEATURES [FEATURES ...] --model MODEL
    gdf1 fit: error: the following arguments are required: --data, --target, --features, --model
    (BUILDWITHSCIENCE) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$ gdf1 fit --data data.csv --target y --features x1 x2 --model model.pkl
    Traceback (most recent call last):
      File "/home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/gdf1/gdf.py", line 3, in <module>
        import pandas as pd
    ModuleNotFoundError: No module named 'pandas'
    (BUILDWITHSCIENCE) curtisb@CURTISBURNETT-LAPTOP:~/p/gdf1$
```

We have pandas library installed in our env, but not in our main python environment

Running in env is square notation, so we can now use the library in code we write here.

```
    (BUILDWITHSCIENCE) [at YOUR_CAT] ~/p/gdf1$ gdf1 fit --data data.csv --target y --features x1 x2 --model model.pkl
    Traceback (most recent call last):
      File "/home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/gdf1/gdf.py", line 3, in <module>
        import pandas as pd
    ModuleNotFoundError: No module named 'pandas'
    (BUILDWITHSCIENCE) [at YOUR_CAT] ~/p/gdf1$
```

```
    (BUILDWITHSCIENCE) [at YOUR_CAT] ~/p/gdf1$ pip install pandas
    Requirement already satisfied: pandas in /home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/.venv/lib/python3.9/site-packages (2.3.3)
    Requirement already satisfied: numpy>=1.22.4 in /home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/.venv/lib/python3.9/site-packages (from pandas) (2.0.2)
    Requirement already satisfied: python-dateutil>=2.8.2 in /home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/.venv/lib/python3.9/site-packages (from pandas) (2.9.0.post0)
    Requirement already satisfied: pytz>=2020.1 in /home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/.venv/lib/python3.9/site-packages (from pandas) (2025.2)
    Requirement already satisfied: tzdata>=2022.7 in /home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/.venv/lib/python3.9/site-packages (from pandas) (2025.2)
    Requirement already satisfied: six>=1.5 in /home/curtisb/Documents/p/2/BUILDWITHSCIENCE/gdf1/.venv/lib/python3.9/site-packages (from python-dateutil>=2.8.2->pandas) (1.17.0)
    (BUILDWITHSCIENCE) [at YOUR_CAT] ~/p/gdf1$
```

Now anything that `run` in terminal is now run in that environment, with `pip install pandas
```

This is useful to do statistics over masked data

In [21]:
```
print(subset[mask].describe())
```

```
       gdpPercap_1987  gdpPercap_1992  gdpPercap_1997  gdpPercap_2002
count        2.000000        3.000000        4.000000        4.000000
mean     17079.719896    13366.475514    12966.846533    14542.960699
std      13501.207155    11260.803857    10804.495150    12660.525361
min       7532.924763     6160.416317     6117.361746     6340.646683
25%      12306.322330     6878.271141     6537.124422     7377.747067
50%      17079.719896     7596.125964     8397.549247     9251.115523
75%      21853.117463    16969.505112    14827.271357    16416.329155
max      26626.515030    26342.884260    28954.925890    33328.965070
```