

# EMS CONTROLLER

**ENERGY MANAGEMENT SYSTEM** 













## **DATASHEET**

EMS	
Power Supply	24Vdc Or 100~280Vac
Functionalities	Cortex A8 800MHz On-chip: 512M DDR3 RAM, 256M Flash Energy management and monitoring Data logging and cloud access Algorithms for efficient control on battery and inverter 7" color touch screen SD card OS compatibility: Android and Linux
Protections	Overload for USB port Short Circuits Yes
Environmental And Climatic Conditions	Minimum temperature -10 °C Maximum temperature +65 °C Relative humidity 90%
Communications	CAN Bus RS232/422/485 for inverter and power meter USB Device for firmware update and mass storage SD card slot for data storage Ethernet Wi-Fi extension slot
Warranty	3 Years





#### Alpha Energy Storage Solution Co., Ltd.

**Tel.** 0086-(0)512-68287609 **Fax**. 0086-(0)512-68280679 E-mail. info@alpha-ess.com www.alpha-ess.com 1-B302, Creative Industrial Park, No. 328, Xinghu Street, SIP Suzhou.

Germany: Tel. +49 176 - 999 2 88 66 E-mail. europe@alpha-ess.com www.alpha-ess.de Paul-Ehrlich-Straße 1 bis 1c, 63225 Langen

### Australia:

Tel. +61-(0)412 953 647

E-mail. australia@alpha-ess.com

www.alpha-ess.com.au

Unit 601 68Mcevoy St, Alexandria Nsw 2015, Australia