
Path Layer UDP Substrate (PLUS) Technical Considerations

Brian Trammell, PLUS BoF IETF 96 Berlin - 21 July 2016




PARENTAL ADVISORY EXPLICIT COOPERATION

Explicit Cooperation


- "Implicit cooperation" between endpoints and middleboxes already widespread in the Internet,
 - where "cooperation" may be the wrong term: some hacks and workarounds are quite hostile.
- Explicit cooperation under endpoint control may be a way to reduce tension in this tussle
 - Declarative, advisory signaling with no trust required between endpoint and path.
- Encrypt everything devices on path don't need to see (including transport headers), to prevent future unauthorized "implicit cooperation".

Three and a half mechanisms to make the path layer explicit


- Sender Path Signaling
- Path Receiver Signaling
 - with encrypted feedback to sender
- Direct Path Sender Signaling




Sender to Path (sender-side)




Sender to Path (on-path)




Sender to Path (receiver-side)




Sender to Path Transport State Signaling




Path to Receiver (sender-side)




Path to Receiver (on-path)




Path to Receiver (receiver-side)




Receiver Feedback




Path Direct to Sender (sender-side)




Path Direct to Sender (on-path)



Path Direct to Sender (feedback)



Anatomy of the Path Layer



- UDP encapsulation
 - userspace implementation
 - ports for NAT
 - ~95% deployable today
- encoding for signaling mechanisms
- crypto to protect transport headers and above

meanwhile, on the spud@ietf.org list...


Is this a user tracking and network neutrality violation machine?

- Will it be possible for a middlebox to use PLUS to insert user identifiers in the server-bound stream of a clientserver protocol?
 - No, unless the client specifically requests it.
 - (Note: possible without PLUS, out of band, today)
- Will it be possible to use PLUS to require a client to insert a particular kind of metadata into a stream?
 - Bad news: yes; no technical solution exists here.
 - (Worse news: also many ways to do this without PLUS)
 - Good news: PLUS brings transparency to this behavior.

Can we make transport innovation work without explicit cooperation?


- draft-herbert-transports-over-udp
 - x over DTLS over UDP.
 - Make transport innovation possible with crypto.
 - Breaks middleboxes.
 - This is a feature.

 Equivalent to PLUS when neither endpoint decides to expose anything to the path.



Can we use IPv6 extension headers?


- IPv6 extension headers can be used to implement PLUS mechanisms
 - Ignore IPv4 in future deployments
 - DO to expose to path: hack, but more deployable
 - HBH to communicate with path: cleaner, but less deployable
- DO/HBH already supported in most socket APIs
- Together with draft-herbert-transportsover-udp, meets PLUS requirements?
- But: more impaired than UDP (draft-ietf-v6ops-ipv6-ehs-in-real-world-02)



Can we use UDP Options?

draft-touch-tsvwg-udp-options

- add option space to UDP in a "gap" between the UDP and IP lengths of a packet.
- Allows optional data to be added to existing UDP applications in a backward compatible manner.
- Proposal: use this option space for PLUS
 - Are these the same problem?
 - Must be in-kernel: no userspace implementation.



Do we need to choose now?

and in conclusion...

Things we need

- A mechanism for making widespread cooperation between endpoints and middleboxes explicit
- Endpoint control over explicit cooperation
- A clear boundary between what the path can see and what it cannot, enforced by encryption
- A design for this facility that deploys on the endpoints from day zero
- All this without requiring a trust relationship between the endpoints and middleboxes