

ACME Persistent DNS Challenge

draft-ietf-acme-dns-persist

A long-lived DNS TXT record, carrying an `accounturi` and a `persistUntil` expiry, authorizes one CA account to issue for a domain with no action needed at each issuance.

Shiloh Heurich (Fastly)


Henry Birge-Lee (Crosslayer Labs)

Michael Slaughter (Amazon Trust Services)

IETF 126 ACME WG — Vienna

The Substitution Gap

Mode 3a — raw accounturi



Fail closed: the fix must make a substituted record validate for **no** account, so a poisoned value transfers authorization to nobody.

Since IETF 125: Choosing a Binding Mechanism

Three approaches to substitution hardening

Approach	Outcome
Authenticated POST to supplied <code>accounturi</code>	Closed: requires a live endpoint and online client
<code>pubkey:</code> hash of the account key	Closed: new wire format; DNS update on rollover
Hash name + key + account URL	Selected (open draft): offline binding with rollover continuity

Goal: restore non-transferability; keep offline provisioning and rollover.

Offline Binding with Account Continuity

The client and CA independently construct the same hashed `accounturi` :

```
<accountHashPrefix><hash-alg>/<base64url hash value>  
H(length_of_domain || domain_name || key || account_URL)
```

Example:

```
_validation-persist.example.com. IN TXT "example.ca accounturi=https://example.ca/acme/hash/sha-256/47DEQpj8HBSa..."
```

- `domain_name` prevents cross-name reuse; `key` supplies the client-computed proof
- `account_URL` binds the value to one account; the 1-octet length plus the fixed-length `key` make every field boundary unambiguous
- `sha-256` identifies SHA-256 (`H`); future algorithms use different tokens
- The CA **recomputes** and string-compares; prior-key matching supports rollover continuity
- `accountHashPrefix` (new directory `meta` field) lets the client build the URI offline

Why this design: a poisoned value fails validation instead of transferring authorization, without requiring a live account endpoint or a public-key URI scheme.

Mandatory Hashed-URI Binding

The post-`-01` working copy grew three `accounturi` modes. The current `-02` direction **collapses them to one**:

Working mode	<code>accounturi</code>	<code>-02</code> disposition
3a	ACME account URL (raw)	Dropped: leaves the substitution gap open
3b	Alternative CA-assigned URI	Redefined: the client-computed hashed URI is the sole form
3c	Subscriber-account URI (many)	Dropped: remains available under CA/B Forum BR 3.2.2.4.22 and CA policy (CP/CPS)

No raw-URL downgrade.

Ask: any WG objection before we publish `-02` along these lines?

Final Construction Review

Settled in review

- Exact recomputation over a fixed field structure makes length extension irrelevant
- `account_URL` provides RFC 8657 §5.4 uniqueness; the record's FQDN adds per-name privacy and prevents cross-name reuse

Interoperability edits before -02

- Use the unpadded base64url RFC 7638 thumbprint ACME libraries already produce
- Make `sha-256` mandatory; future tokens come from the RFC 6920 registry (non-truncated, at least 256 bits)
- Bound prior-key acceptance by time without adding a client key hint

Privacy limit

HTTP-01 exposes the account-key thumbprint on the CA's cleartext validation fetch; hashing is best-effort anti-correlation, not strong unlinkability.

What Lands in -02, and Why

Land now: author-settled and scoped

- Avoid provisioning an already-expired record ([#38](#))
- Separate DNS cache lifetime from authorization lifetime ([#42](#))
- Align challenge-object naming with ACME JSON ([#56](#))
- Discover issuer names before creating an order ([#60](#))

Defer past -02

- IP validation ([#32](#)): defer to keep this revision focused
- Subdomains ([#33](#)): choose RFC 9444 reuse or a new signal
- Error codes ([#39](#)): decide whether to register challenge-specific errors
- Mismatch behavior ([#59](#)) and substitution binding ([#64](#)) close with the hashed URI
- Privacy analysis ([#61](#)): keep open

Path Forward

Settled fixes in the -02 candidate

- Rotation-text rewrite, RFC 8657 clarification, base64url thumbprint with new vectors
- RFC 6920 hash tokens (mandatory `sha-256`), HTTP-01 privacy caveat, and the four scoped fixes
- IANA early review requested for the new directory metadata

Two extensions, two states

- **Current author proposal — keep** `domain_name = "*" (client MAY / CA MUST):` authors aligned, WG review pending; a DNS observer can link the account's domains; one record reused across names
- **Post-IETF design — key rollover durability:** not author-settled; bounded `keyRolloverWindow` vs. non-breaking records, both must preserve non-transferability

Submission blackout: gather feedback Thursday, confirm on-list, then publish -02 .

Room ask: objections to the star-form proposal? Input for the rollover design?

Questions & Discussion

- Any objection to dropping 3a and 3c and making the hashed URI mandatory?
- Input on the post-IETF rollover design: bounded prior-key window vs. records that survive rollover?
- Authors propose keeping the domain-omitted `*` form (client MAY / CA MUST): objections?

Parallel CA/Browser Forum work (BR Method 3.2.2.4.22):

[#674](#) one-to-many `accounturis` · [#675](#) parameter-key case-sensitivity

[#676](#) `policy=wildcard` · [#677](#) separate validation method for dns-persist-01

Mailing list: acme@ietf.org

GitHub: [current](#) `-02` candidate and discussion · [repository](#)

Draft: <https://datatracker.ietf.org/doc/draft-ietf-acme-dns-persist/>