ACME Persistent DNS Challenge

draft-ietf-acme-dns-persist

A long-lived DNS TXT record, carrying a hashed `accounturi` and an optional `persistUntil` expiry, authorizes one CA account to issue for a domain or IP address with no DNS change at each issuance.

Shiloh Heurich (Fastly)
Henry Birge-Lee (Crosslayer Labs)
Michael Slaughter (Amazon Trust Services)

IETF 127 ACME WG — San Francisco

Since IETF 126 (Vienna)

Published in `-02` (Sept 2026)

- **Mandatory hashed `accounturi`**: `H(len || domain_name || key || account_URL)` under `accountHashPrefix` (#64)
- **Domain-omitted `*` opt-out**: client MAY / CA MUST
- **Rollover durability**: CAs retain witnessed account-key thumbprints for account lifetime; account deactivation overrides retention (#69)
- **`persistUntil` clamp**: clamps authorization `expires`
- **Directory `issuerDomainNames`**: pre-order discovery (#60)

Landed in `-03`

- **Hash & CNAMEs (#89):** ASCII A-labels; exact `issuer-domain-name`; follow CNAMEs, hash pre-alias `R` (or `*`)
- **`accountHashPrefix` (#81):** client/publisher **MUST** verify RFC 8659 `value` + URI chars; no fallback
- **Parameters (#80):** case-insensitive recognized tags (no dupes); `persistUntil` **MUST** be ASCII digits `≤ 2^63-1` (valid `≤ T`)
- **Account & issuer rules:** no account-URL reassignment; `issuerDomainNames` stable + migration **SHOULD**

Subdomain Validation: `ancestorDomain` (#33)

Request-only selector (PR #84)

```
POST /chall/abc  →  { "ancestorDomain": "example.com" }
```

- **Three names:** cert identifier `F`, authz `identifier.value` `A` (`*.` stripped), record domain `R`
- Default `{}` sets `R = A` (including base wildcard `*.example.com`)
- Subdomain or deeper wildcard (`*.dept.example.com`) sends `"ancestorDomain": "example.com"`
- Challenge Object schema unchanged

Guardrails & RFC 9444

- **CA MUST recognize:** no silent fallback to `A`
- **Length MUST (`R` & `A`):** VDN ≤ 253 octets; overlong `_validation-persist.<A>` → `malformed`
- **Proper ancestor:** strict suffix of `A`; public suffixes **SHOULD NOT** (incl. suffix wildcard/9444; `unauthorized`)
- **Record at `R`:** requires `policy=wildcard`; hashes `R` (or `*`)
- **Locks `R`:** first accepted POST fixes `R`; RFC 9444 (`subdomainAuthAllowed`) coexists

Why: Client names the record location; no DNS tree walk.

IP Validation: `_ip-validation-persist` (#32)

Additive profile for ACME `ip` identifiers (RFC 8738) in the reverse DNS tree (PR #85):

```
_ip-validation-persist.1.2.0.192.in-addr.arpa. IN TXT "authority.example; accounturi=https://ca.example/account-hash/sha-256/CnwSwHOHJbE-..."
```

- **Normalized Reverse Zone Domain Name (`R`):** lowercase `.in-addr.arpa` (4 reversed octets) or `.ip6.arpa` (32 reversed hex nibbles, 72 octets)
- **Distinct node name:** `_ip-validation-persist.<R>` (IANA Node Names + ACME Validation Methods `ip` registrations; no `PTR` indirection)
- **Digest `domain_name` input:** normalized `R` (or `*`) prior to following any CNAME aliases — deterministic across RFC 2317 CNAME delegation
- **Exact-address scope:** single IP only (`policy=wildcard` ignored; `ancestorDomain` rejected with `malformed` ; caches typed by `ip` vs `dns`)

Why: Same record format; separate node name keeps `ip` and `dns` apart.

`persistExpired` Error Type (#39 / PR #86)

Registers `urn:ietf:params:acme:error:persistExpired` (RFC 8555 §9.7.4):

Rule	Requirement
1. Privacy Gate (`MUST NOT`)	CA **MUST NOT** return `persistExpired` if any record at the queried name validates, or if no record at that name is otherwise qualifying for the CA and **live requesting account** and failed solely due to an expired `persistUntil` (order-independent across RRsets).
2. Diagnostic (`SHOULD` / `MAY`)	When eligible on a challenge attempt, CA **SHOULD** return `persistExpired`, and **MAY** return `unauthorized` for uniform disclosure.

- **Boundary & RRsets:** valid `≤ T`, expired `> T`; `persistExpired` when eligible (`unauthorized` vs `malformed` per CA)
- **JIT & clients:** JIT falls back to `pending`; clients check `persistUntil` locally and handle `persistExpired` or `unauthorized`

Why this split: Actionable expiration diagnostics with zero cross-account or cross-CA expiration oracle.

Certificate-Key Attestation Conjunction (#76)

Why DNS parameters and CAA alone cannot express `dns-persist-01` **AND** `device-attest-01`:

- Authorization `challenges` (RFC 8555 §7.1.4) and CAA `validationmethods` (RFC 8657 §4) are **disjunctive (`OR`)**; unknown TXT parameters are `MUST ignore`

Informative order-policy guidance (PR #87)

1. **Order `authorizations` (RFC 8555 §7.1.3):** CA policy includes both domain (incl. wildcard/subordinate) and non-waivable attestation authorizations
2. **Finalization CSR key check (RFC 8555 §7.4):** all Order authorizations `valid` + CSR public key matches attested key across JIT or reuse
3. **Key-rotation renewal:** JIT reuses `_validation-persist`; new Order obtains fresh attestation for the rotated CSR key (`device-attest` informative)

Why: Orders already require every authorization; no new syntax.

Mailing-List Implementation Feedback (Oct 13)

From Seo Suchan's Pebble `-02` implementation report:

1. Keep `https://` prefix

- **RFC 8657 §5.4:** `accounturi` URIs include an authority component
- **Zero directory savings:** pre-provisioning already uses directory `issuerDomainNames`
- **No BCP 35 hold:** avoids IANA scheme; matches servercert PR #9
- **Rebrands (§4.5):** dual-acceptance migration covers prefix, account URLs, and `issuerDomainNames`

2. Keep inner `key` on SHA-256

```
H(len || domain_name || key || account_URL)
                            ^^^ 43-octet RFC 7638
```

- **Matches RFC 8555 §8.1:** reuses the exact `keyAuthorization` thumbprint clients and CAs already compute
- **One stored value per key:** CA retention table stores **one** 43-byte thumbprint per key regardless of outer `<hash-alg>`

Direction: Keep `https://` `accountHashPrefix` and fixed SHA-256 key input.

Implementation Status & Path to WGLC

Issue & PR Status

- **Clarifications & MUSTs:**
  - #74, #75, #77–#83, #89 + pre-WGLC review
- **New in `-03`:**
  - PR #84: `#33` `ancestorDomain` + RFC 9444
  - PR #85: `#32` `_ip-validation-persist`
  - PR #86: `#39` `persistExpired`
  - PR #87: `#76` attestation conjunction
- **All tracked issues addressed**

Implementations & CABF

- **Servers:** Pebble (#536 merged, `-02` PR #566); Boulder `-01` (`-02` #9127)
- **Clients:** lego merged (#2871); cert-manager PR (#9487)
- **CAs:** Let's Encrypt, Fastly / Certainly, Amazon Trust Services, Google Trust Services
- **No old-draft interop:** `-03` clients require `accountHashPrefix` (skip `-01`)
- **CA/B Forum:** Method 23 (servercert PR #9: cites `-02`, `-03` next)

Next step: Request **WGLC** on `-03`.

Questions & Discussion

- Feedback on how `-03` resolves `#32`, `#33`, `#39`, and `#76`
- Is `-03` ready for **Working Group Last Call**?

Mailing list: acme@ietf.org

GitHub: repository

Draft: https://datatracker.ietf.org/doc/draft-ietf-acme-dns-persist/