
Workgroup:	Network Working Group
Internet-Draft:	draft-ietf-rpp-json-00
Published:	6 July 2026
Intended Status:	Standards Track
Expires:	7 January 2027
Authors:	M. Wullink P. Kowalik <i>SIDN Labs</i> <i>DENIC</i>

JSON for RESTful Provisioning Protocol (RPP)

Abstract

This document defines the rules for representing the RESTful Provisioning Protocol (RPP) data objects, as defined in [I-D.ietf-rpp-data-objects], using the JavaScript Object Notation (JSON) Data Interchange Format [RFC8259]. It specifies how RPP primitive types, common data types, component objects, resource objects, and associations are mapped to JSON and JSON Schema, and provides normative JSON Schema definitions and worked examples for domain name, contact, and host data objects.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 7 January 2027.

Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	6
1.1. Motivation	7
2. Terminology	7
3. Conventions Used in This Document	8
4. JSON Representation Rules	8
4.1. Primitive Type Mappings	8
4.2. Cardinality Rules	9
4.3. Mutability Rules	10
4.4. Association Rules	10
4.4.1. Labelled associations	11
4.4.2. Aggregation	11
4.4.3. Composition	11
4.4.4. Labelled Aggregation	12
4.4.5. Dictionary Aggregation	13
4.4.6. Labelled Composition	13
4.4.7. Dictionary Composition	14
4.5. Object Identifier Rules	14
4.6. External Type Embedding Rules	15
4.7. Process Data Embedding Rules	15
4.8. JSON Schema Definition Rules	16
4.8.1. RPP Profiles and Validation	17
5. Update Rules	17
5.1. Full	17
5.2. Partial	17
5.3. Schema	19
5.3.1. Examples	20

6. JSON Schema Definitions	22
6.1. Common Data Types Schemas	22
6.1.1. Identifier	22
6.1.2. Client Identifier	22
6.1.3. Phone Number	23
6.2. Component Objects Schemas	23
6.2.1. Period Object	23
6.2.2. Provisioning Metadata Object	24
6.2.3. Status Object	24
6.2.4. DNS Resource Record Object	25
6.2.5. DNS Operational Controls Object	26
6.2.6. DNS Data Object	27
6.2.7. Authorization Information Object	27
6.2.8. JSContact Card Object	28
6.2.9. Restore Report Object	30
6.2.10. Organisation Role Object	31
6.2.11. Processes Object	32
6.3. Process Object Schemas	32
6.3.1. Create Process Object	32
6.3.2. Renew Process Object	33
6.3.3. Transfer Process Object	34
6.3.3.1. Create	34
6.3.3.2. Read	35
6.3.3.3. Approve	36
6.3.3.4. Cancel	36
6.3.3.5. Reject	37
6.3.4. Restore Process Object	37
6.4. Domain Name Data Object	38
6.4.1. Create	38
6.4.2. Read	39

6.4.3. Update	40
6.4.4. Renew	41
6.4.5. Transfer	41
6.4.6. Reference	44
6.5. Contact Data Object	44
6.5.1. JSContact Profile for RPP	44
6.5.2. Create	44
6.5.3. Read	45
6.5.4. Update	45
6.5.5. Transfer	46
6.5.6. Reference	46
6.6. Host Data Object	47
6.6.1. Create	47
6.6.2. Read	47
6.6.3. Update	48
6.6.4. Reference	48
6.7. Organisation Data Object	49
6.7.1. Create	49
6.7.2. Read	49
6.7.3. Update	50
6.7.4. Reference	51
6.8. User Data Object	52
6.8.1. Create	52
6.8.2. Read	53
6.8.3. Update	53
6.8.4. Reference	54
7. Examples	54
7.1. Domain Name	54
7.1.1. Create	54
7.1.2. Create Process Data	56

7.1.3. Read	56
7.1.4. Update	57
7.1.5. Delete	58
7.1.6. Renew	58
7.1.7. Transfer Request	59
7.1.8. Transfer Query	60
7.1.9. Transfer Approve	60
7.1.10. Transfer Cancel	60
7.1.11. Transfer Reject	60
7.1.12. Restore Request	61
7.1.13. Restore Report	62
7.1.14. Restore Query	62
7.2. Contact	63
7.2.1. Create	63
7.2.2. Read	65
7.2.3. Update	66
7.2.4. Delete	68
7.2.5. Transfer Request	68
7.2.6. Transfer Query	69
7.2.7. Transfer Cancel / Approve	69
7.2.8. Transfer Reject	69
7.3. Host	69
7.3.1. Create	69
7.3.2. Read	71
7.3.3. Update	72
7.3.4. Delete	73
7.3.5. Restore Request	73
7.3.6. Restore Report	74
7.3.7. Restore Query	75

7.4. Organisation	76
7.4.1. Create	76
7.4.2. Read	78
7.4.3. Update	79
7.4.4. Delete	80
7.4.5. Reference	80
7.5. User	80
7.5.1. Create	80
7.5.2. Read	81
7.5.3. Update	81
7.5.4. Delete	81
7.5.5. Reference	81
8. IANA Considerations	81
9. Internationalization Considerations	82
10. Security Considerations	82
11. Acknowledgments	82
12. Change History	82
12.1. Version draft-wullink-rpp-json-02 to draft-ietf-rpp-json-00	82
12.2. Version 01 to 02	82
12.3. Version 00 to 01	82
13. References	82
13.1. Normative References	82
13.2. Informative References	83
Authors' Addresses	84

1. Introduction

The RESTful Provisioning Protocol (RPP) defines a set of data objects for managing foundational registry resources including domain names, contacts, and hosts. The data model is defined in [\[I-D.ietf-rpp-data-objects\]](#) independently of any particular representation format. This document defines the JSON [\[RFC8259\]](#) representation of those data objects.

JSON has emerged as the de facto standard data format for modern RESTful APIs. Its widespread adoption across tools, libraries, and developer communities makes it well suited as the primary representation format for RPP. This document provides the normative rules and JSON Schema definitions required for implementations to produce and consume RPP messages in JSON.

The separation between the abstract data model and its concrete JSON representation ensures that the protocol's semantic foundation remains stable while enabling the adoption of JSON across diverse deployment environments.

1.1. Motivation

The RESTful Provisioning Protocol (RPP) introduces a new provisioning mechanism that aligns more closely with modern cloud infrastructure, enhancing the scalability of server deployments. While RESTful protocols do not mandate a specific media type for resource description, the widespread adoption of JSON in web services has established it as the de facto standard for modern APIs. The increasing availability of tools, software libraries, and a skilled workforce has led several registries to adopt JSON for data exchange within their API ecosystems. Registries supporting JSON can offer a unified API ecosystem that extends beyond domain name and IP address provisioning, maintaining a consistent technology stack, data formats, and developer experience.

JSON's syntax, known for its straightforwardness and minimal verbosity, significantly eases the tasks of writing, reading, and maintaining code. This simplicity is especially advantageous for the rapid comprehension and integration of provisioning APIs.

The lightweight nature of JSON can result in faster processing and data transfers, a critical aspect in high-volume transaction environments such as domain registration. Enhanced API response times can lead to more efficient domain lookups, registrations, and updates. JSON parsing is typically fast and well-supported by standard libraries, contributing to improved system performance amid frequent interactions between RPP clients and servers.

However, the absence of a standardized JSON format for domain provisioning has led to the emergence of TLD-specific implementations that lack interoperability, increasing the development effort required for integration. Similarly, at the registrar level, the absence of standards has resulted in numerous incompatible API implementations provided to clients and resellers. Standardizing a JSON format for domain provisioning within the RPP framework could mitigate these challenges, reducing fragmentation and simplifying integration efforts across the domain registration industry.

2. Terminology

In this document, the following terminology is used.

RPP Data Objects - The abstract data model definitions for domain name, contact, and host resources, as specified in [[I-D.ietf-rpp-data-objects](#)].

RESTful Provisioning Protocol - A RESTful protocol for provisioning heterogeneous database objects.

JSON Schema - A vocabulary that allows annotation and validation of JSON documents, as described in [[JSON-SCHEMA](#)].

EPP Compatibility Profile - A set of additional constraints defined in [[I-D.ietf-rpp-data-objects](#)] that a server **MUST** adhere to when supporting both RPP and EPP concurrently.

3. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

JSON is case sensitive. Unless stated otherwise, JSON specifications and examples provided in this document MUST be interpreted in the character case presented. The examples in this document assume that request and response messages are properly formatted JSON documents. Indentation and white space in examples are provided only to illustrate element relationships and for improving readability, and are not REQUIRED features of the protocol.

All JSON Schema definitions in this document use JSON Schema draft 2020-12 [JSON-SCHEMA], and where not provided with a `$schema` keyword, the following default applies:

```
"$schema": "https://json-schema.org/draft/2020-12/schema"
```

4. JSON Representation Rules

This section defines the normative rules for representing the RPP data model in JSON. The data model is specified in [I-D.ietf-rpp-data-objects], which defines all primitive types, common data types, component objects, resource objects, and associations independently of any concrete representation format. The rules in this section specify how those abstract definitions map to JSON and JSON Schema version 2020-12.

4.1. Primitive Type Mappings

RPP primitive types MUST be represented in JSON as follows:

RPP Primitive Type	JSON Type	Notes
String	string	Unicode character sequence
Integer	number	Whole number, positive or negative
Boolean	boolean	true or false
Decimal	string	Base-10 fractional value with exact representation within a defined precision. Number is encoded into string same as "number" in [RFC8259] without exponent part "ext".
Date	string	Full-date as per [RFC3339], e.g. "2025-10-27"
Timestamp	string	Date-time in UTC as per [RFC3339], e.g. "2025-10-27T09:42:51Z"
URL	string	Uniform Resource Locator as per [RFC1738]

RPP Primitive Type	JSON Type	Notes
Binary	string	Base64-encoded binary data

Table 1

4.2. Cardinality Rules

The cardinality of each data element in the RPP data model **MUST** be represented as follows in JSON:

Rule 1: A data element with cardinality 1 (exactly one) **MUST** be represented as a JSON property and **MUST** be present in the containing JSON object. The element **MUST** be listed under `required` in the corresponding JSON Schema.

```
{
  "type": "object",
  "properties": {
    "name": { "type": "string" }
  },
  "required": ["name"]
}
```

Rule 2: A data element with cardinality 0-1 (zero or one) **MUST** be represented as an optional JSON property. The element **MUST NOT** be listed under `required` in the corresponding JSON Schema. When absent, the element **MUST** be omitted from the JSON object (not represented as `null`).

```
{
  "type": "object",
  "properties": {
    "expiryDate": { "type": "string", "format": "date-time" }
  }
}
```

Rule 3: A data element with cardinality 0+ (zero or more) **MUST** be represented as an optional JSON array. When no values are present, the property **MUST** be omitted or represented as an empty array.

```
{
  "type": "object",
  "properties": {
    "status": {
      "type": "array",
      "items": { "$ref": "#/$defs/status" }
    }
  }
}
```

Rule 4: A data element with cardinality 1+ (one or more) MUST be represented as a required JSON array with "minItems": 1 and the element MUST be listed under required in the corresponding JSON Schema.

```
{
  "type": "object",
  "properties": {
    "records": {
      "type": "array",
      "items": { "$ref": "#/$defs/dnsRecord" },
      "minItems": 1
    }
  },
  "required": ["records"]
}
```

4.3. Mutability Rules

Data elements in the RPP data model carry a mutability attribute: create-only, read-only, or read-write. These MUST be represented in JSON Schema as follows:

Rule 5: Data elements with mutability read-only MUST be annotated with "readOnly": true in the JSON Schema. Clients MUST NOT include read-only properties in create or update request bodies. Servers MUST ignore any read-only properties provided by a client in a request.

```
{
  "repositoryId": {
    "type": "string",
    "readOnly": true
  }
}
```

Rule 6: Data elements with mutability create-only MUST be annotated with "writeOnly": true in the JSON Schema for request schemas, and excluded from update request schemas. Servers MUST reject requests that attempt to modify a create-only element after object creation.

Rule 7: Data elements with mutability read-write have no additional annotation. They MAY appear in both request and response bodies.

4.4. Association Rules

The RPP data model defines several association types between objects, the following rules specify their JSON representations. A Aggregation represents a relationship between two independent objects, where one object references another. A Composition represents a parent-child relationship where the child object is embedded within the parent object and cannot exist independently.

4.4.1. Labelled associations

Some associations between objects carry a string label that provides additional context for the relationship. The label is not an identifier of the target object, but rather a descriptor of the association itself. Labelled associations can occur in both aggregations and compositions. When representing labelled associations in JSON, the property `label` MUST be included alongside the reference to the target object. A property with the name `object` MUST be used to contain the reference to the target object, which can be either limited representation containing at minimum the primary object identifier for aggregations or an embedded object for compositions.

4.4.2. Aggregation

An `Aggregation[Type]` represents a relationship between two independent objects. When the cardinality allows more than one target, it MUST be represented as a JSON array. Each element of the array MUST be the identifier of the referenced object.

Rule 8: `Aggregation[Type]` with cardinality 0+ or 1+ MUST be represented as a JSON array of embedded objects. Each object in the array MUST include the data elements of the referenced object type that are relevant to the context (at minimum the primary identifier field). Other data elements of the referenced object type MAY be included as needed to provide additional context for the client, but are not required. The JSON Schema MUST allow for the presence of these additional fields.

Example: domain nameservers (`Aggregation[Host Data Object]`) in a read response, returning a limited object representation containing only the primary identifier field `hostName`:

```
{
  "@type": "domainName",
  "name": "name.example",
  "nameservers": [
    { "@type": "host", "hostName": "ns1.name.example" },
    { "@type": "host", "hostName": "ns2.name.example" }
  ]
}
```

4.4.3. Composition

A `Composition[Type]` represents a parent-child relationship where the child's lifecycle is bound to the parent and the child cannot exist independently of the parent. In JSON, the child object MUST be fully embedded within the parent object. The JSON representation of a composition is the same as that of an aggregation. The distinction between the two is semantic and does not affect the JSON structure.

```

{
  "@type": "domainName",
  "name": "name.example",
  "nameservers": [
    {
      "@type": "host",
      "hostName": "ns1.name.example",
      "provMetadata": {
        "@type": "provMetadata",
        "repositoryId": "NS1EXAMPLE-REP",
        "spClientId": "ClientX"
      },
      "status": [ { "@type": "status", "label": "ok" } ],
      "dns": {
        "@type": "dnsData",
        "records": [
          {
            "@type": "dnsRecord",
            "name": "@",
            "type": "ns",
            "rdata": { "nsdname": "ns1.name.example." }
          },
          {
            "@type": "dnsRecord",
            "name": "ns1.name.example.",
            "type": "a",
            "rdata": { "address": "192.0.2.1" }
          }
        ]
      }
    }
  ]
}

```

4.4.4. Labelled Aggregation

A `LabelledAggregation[Type]` is a relationship between two independent objects where each association carries a string label. Multiple associations with the same label are allowed.

Rule 9: `LabelledAggregation[Type]` with cardinality 0+ MUST be represented as a JSON array of objects. Each object in the array MUST contain a `label` property (string) alongside the identifier of the referenced object. The object MUST include at least the primary identifier field of the referenced object type. Other data elements of the referenced object type MAY be included as needed to provide additional context for the client, but are not required. The JSON Schema MUST allow for the presence of these additional fields.

Example: domain contacts (`LabelledAggregation[Contact Object]`):

```
"contacts": [
  {
    "label": "admin",
    "object": {
      "@type": "contact",
      "id": "ABC-8013"
    }
  },
  {
    "label": "tech",
    "object": {
      "@type": "contact",
      "id": "ABC-8014"
    }
  }
]
```

4.4.5. Dictionary Aggregation

A DictionaryAggregation[Type] is a relationship between two independent objects where each association carries a unique string label that serves as a dictionary key.

Rule 10: DictionaryAggregation[Type] MUST be represented as a JSON object where each key is the unique label and the corresponding value is the referenced object, the object MUST include at least the primary identifier field of the referenced object type. Other data elements of the referenced object type MAY be included as needed to provide additional context for the client, but are not required. The JSON Schema MUST allow for the presence of these additional fields.

Example: domain contacts keyed by unique role (DictionaryAggregation[Contact Object]):

```
"contacts": {
  "admin": {
    "@type": "contact",
    "id": "ABC-8013"
  },
  "tech": {
    "@type": "contact",
    "id": "ABC-8014"
  }
}
```

4.4.6. Labelled Composition

A LabelledComposition[Type] is a parent-child relationship where each embedded child carries a string label. Multiple instances with the same label are allowed.

Rule 11: LabelledComposition[Type] with cardinality 0+ MUST be represented as a JSON array of embedded objects. Each object in the array MUST contain a label property alongside the data elements of the composed type.

Example: remarks (LabelledComposition[Remark Object]):

```
"remarks": [  
  {  
    "label": "public",  
    "object": {  
      "@type": "remark",  
      "description": "This domain is used for test purposes."  
    }  
  },  
  {  
    "label": "private",  
    "object": {  
      "@type": "remark",  
      "description": "Internal note for the sponsoring client."  
    }  
  }  
]
```

4.4.7. Dictionary Composition

A DictionaryComposition[Type] is a parent-child relationship where each embedded child carries a unique string label used as a dictionary key.

Rule 12: DictionaryComposition[Type] MUST be represented as a JSON object where each key is the unique label and the corresponding value is the fully embedded child object.

Example: remarks keyed by scope (DictionaryComposition[Remark Object]):

```
"remarks": {  
  "public": {  
    "@type": "remark",  
    "description": "This domain is used for test purposes."  
  },  
  "private": {  
    "@type": "remark",  
    "description": "Internal note for the sponsoring client."  
  }  
}
```

4.5. Object Identifier Rules

Rule 13: When a resource or component object is referenced by identifier (for example in an aggregation), the identifier MUST be represented as a JSON string using the value of the object's primary identifier data element.

Rule 14: When a resource or component object is embedded (as in a composition), all data elements of the object MUST be represented as properties of a JSON object according to the rules of this section.

4.6. External Type Embedding Rules

RPP data objects may include data elements whose types are defined by external specifications (e.g., JSContact in [RFC9553]). When embedding a value of an externally defined type into a JSON representation, the following rules apply, in order of preference:

Rule 15: If the external type has a native JSON representation (i.e., the external specification defines how the type is represented using the JSON format), the value **MUST** be embedded as a valid JSON element using the native JSON representation defined by that specification.

Rule 16: If the external type does not have a native JSON representation but has a native UTF-8 encoded text representation, the value **MUST** be embedded as a JSON `string` using the UTF-8 encoding.

Rule 17: If the external type has neither a native JSON nor a native UTF-8 text representation, the binary representation of the value **MUST** be Base64-encoded ([RFC4648], Section 4) and embedded as a JSON `string`.

4.7. Process Data Embedding Rules

As defined in [I-D.ietf-rpp-core], a uniform interface operation **MAY** require process data in addition to the object representation data. This section defines how such process data **MUST** be represented in JSON when transmitted together with the object representation in a single request body.

Rule 18: Process data accompanying a uniform interface operation **MUST** be represented using the `processes` data element of the owning resource object (see Processes Object), following the Aggregation rules for the corresponding process type (for example `createProcess` for creation-specific inputs). Each embedded process object **MUST** be a valid JSON representation of the process object. This applies uniformly regardless of whether the resource object already exists.

Example: a domain create request body carrying a two-year registration period as process data embedded in a `createProcess` process object under `processes`:

```
{
  "@type": "domainName",
  "name": "example.example",
  "nameservers": [
    { "@type": "host", "hostName": "ns1.example.example" },
    { "@type": "host", "hostName": "ns2.example.example" }
  ],
  "processes": {
    "@type": "processes",
    "createProcess": [
      {
        "@type": "createProcess",
        "period": {
          "@type": "period",
          "value": 2,
          "unit": "y"
        }
      }
    ]
  }
}
```

4.8. JSON Schema Definition Rules

Rule 20: Each RPP component object and resource object MUST have a corresponding JSON Schema definition. Object definitions MUST be placed in the `$defs` keyword of the JSON Schema document.

Rule 21: Identifier fields MUST use `"type": "string"` in JSON Schema.

Rule 22: Enumeration constraints on string fields MUST be expressed using the `"enum"` keyword in JSON Schema.

Example (Transfer Status enum):

```
"trStatus": {
  "type": "string",
  "enum": ["pending", "clientApproved", "clientCancelled",
    "clientRejected", "serverApproved", "serverCancelled"]
}
```

Rule 23: Each JSON Schema definition for an RPP object MUST include a `"required"` array listing all data elements with cardinality 1 or 1+.

Rule 24: JSON Schema definitions for extendible RPP objects MUST NOT use `"additionalProperties": false` or `"unevaluatedProperties": false`. However, before validation, schemas on every property level MUST be enriched with `"unevaluatedProperties": false` property to prevent the presence of undeclared properties in JSON instances. JSON Schemas for Object type MAY use `"additionalProperties": true` to allow for free key definition.

Rule 25: Every RPP object representation MUST include a "@type" property whose value is the object's identifier as registered in the IANA RPP Data Object Registry. This property enables identification and allows clients and servers to unambiguously determine the type of an object. The "@type" property MUST be included in the JSON Schema "properties" object for each RPP object definition with a "const" constraint fixing the value to the object's registered identifier. The "@type" property MUST be listed in the "required" array of the corresponding JSON Schema definition.

Example (Domain Name Data Object):

```
{
  "@type": "domainName",
  "name": "example.example"
}
```

Rule 26: When a transfer request or other operation requires authorization information (e.g., EPP-style authinfo), the client MUST NOT include the authInfo object in the JSON request body. Instead, the client MUST convey the authorization information using the RPP-Authorization HTTP request header as defined in [I-D.ietf-rpp-core]. Servers MUST reject any request that includes an authInfo object in the JSON body with an appropriate error response.

4.8.1. RPP Profiles and Validation

RPP profiles, such as the EPP Compatibility Profile defined in [I-D.ietf-rpp-data-objects], may impose additional constraints on top of the base RPP data model. These additional constraints MUST be enforced by implementations through validation rules that go beyond what can be expressed in JSON Schema. Such validation rules MUST be clearly documented in the profile specification and implemented by both clients and servers when operating under that profile. For example, the EPP Compatibility Profile requires that certain fields be present in specific object types, and that certain identifier fields conform to EPP syntax rules. These constraints cannot be fully captured in JSON Schema and therefore require additional validation logic in implementations.

5. Update Rules

NOTE: The update rules in this section are still under discussion and may be subject to change. Feedback from the community is welcome.

5.1. Full

A full update operation replaces the entire state of a resource object with the new representation provided in the request, all required properties MUST be included in the new representation.

5.2. Partial

A partial update operation allows clients to update specific properties of a resource object, while leaving other properties unchanged. A partial update MUST use JSON Patch [RFC6902] and an RPP extension to support the match property for matching of array elements.

The match property is used to identify a specific element in an array, it is a JSON object that contains key-value pairs corresponding to the properties of the array elements. The server uses the match property to locate the specific element in the array that should be

updated, removed, or replaced. The server MUST compare every key and corresponding value in the `match` object against the properties of each element in the array. If an element matches all key-value pairs in the `match` object, it is considered a match.

If the righthand side of the `match` property contains a complex datatype (object or array), the `match` property MUST contain a key named `object`, the value of which is a JSON object that contains the properties to be matched against. The server MUST compare the properties of the nested object against the corresponding properties of the array element. If all properties match, the element is considered a match.

The server MUST NOT allow recursive matching of nested data structures. The `match` property is only used for matching elements in the immediate array specified by the `path` property of the JSON Patch operation. If the array elements contain nested objects or arrays, the server MUST NOT attempt to match against those nested structures.

Example domain object for matching an array element with a specific key-value pair:

```
{
  "@type": "domainName",
  "name": "example.example",
  "contacts": [
    { "label": "admin", "object": { "@type": "contact", "id":
"REG-100" } },
    { "label": "tech", "object": { "@type": "contact", "id":
"REG-200" } },
    { "label": "tech", "object": { "@type": "contact", "id":
"REG-300" } }
  ]
}
```

Example match object for matching the array element with the "tech" label and the contact ID "REG-200" in the `contacts` array of the domain object above:

```
{
  "match": {
    "label": "tech",
    "object": { "@type": "contact", "id": "REG-200" }
  }
}
```

For the `remove` operation, if multiple matched elements are found, then the server MUST remove all matched elements. For the `replace` operation, if multiple matched elements are found, then the server MUST return an error response indicating that the operation is ambiguous and cannot be performed. If a match does not have any results, then the server MUST return an error response indicating that the specified element could not be found.

The following rules apply for partial updates:

- Rule 25: JSON Patch operations other than "add", "remove" and "replace" MUST NOT be used.
- Rule 26: If a JSONPointer path points to field using a JSON simple data type (e.g. string or number) then the "value" property MUST be provided and its type MUST match the type of the target field.

- Rule 27: If a JSONPointer path points to an object, then the "value" property MUST be provided and contain a valid object, the new object's "@type" property MUST match the "@type" of the target object.
- Rule 28: If a JSONPointer path points to an array, then:
 - The "match" property MUST be provided to identify the specific element to be updated.
 - The "match" property MUST only be used for matching array elements of the same type, and the rules 26 and 27 apply.
 - The value of the "op" property determines the action to be taken on the matched element:
 - The "add" operation, appends the new value to the array.
 - The "remove" operation, removes the specified value from the array.
 - The "replace" operation, replaces the existing value at the matching array element with the specified value.
 - If the value of the "op" property is "replace", and there is a matching element, then the element MUST be fully replaced with the new value provided in the "value" property. The new value MUST include all required fields for the object type.
- Rule 29: If any of the JSONPointer paths in the request fail to match an existing field or element in the target resource object, the server MUST reject the complete request with an appropriate error response.

5.3. Schema

A partial update request body MUST be a JSON array of patch operation objects. Each operation MUST include an op and a path property. The value property MUST be present for add and replace operations. The match property MUST be present when the path points to an array property and is used to identify the specific array element to operate on.

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/partialUpdate",
  "$defs": {
    "partialUpdate": {
      "type": "array",
      "items": { "$ref": "#/$defs/patchOperation" },
      "minItems": 1
    },
    "patchOperation": {
      "oneOf": [
        { "$ref": "#/$defs/patchAdd" },
        { "$ref": "#/$defs/patchRemove" },
        { "$ref": "#/$defs/patchReplace" }
      ]
    },
    "patchAdd": {
      "type": "object",
      "properties": {
        "op": { "type": "string", "const": "add" },
        "path": { "type": "string" },
        "value": {}
      },
      "required": ["op", "path", "value"],
      "additionalProperties": false
    }
  }
}
```

```
"patchRemove": {
  "type": "object",
  "properties": {
    "op": { "type": "string", "const": "remove" },
    "path": { "type": "string" },
    "match": { "type": "object" }
  },
  "required": ["op", "path"],
  "additionalProperties": false
},
"patchReplace": {
  "type": "object",
  "properties": {
    "op": { "type": "string", "const": "replace" },
    "path": { "type": "string" },
    "match": { "type": "object" },
    "value": {}
  },
  "required": ["op", "path", "value"],
  "additionalProperties": false
}
}
```

5.3.1. Examples

Example JSON document used by partial update examples below:

```
{
  "@type": "domainName",
  "name": "example.example",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "EXAMPLE1-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "1999-04-03T22:00:00.0Z"
  },
  "nameservers": [
    { "@type": "host", "hostName": "ns1.example.example" },
    { "@type": "host", "hostName": "ns2.example.example" }
  ],
  "registrant": { "@type": "contact", "id": "jd1234" },
  "contacts": [
    { "label": "admin", "object": { "@type": "contact", "id": "sh8013" } },
    { "label": "tech", "object": { "@type": "contact", "id": "sh8013" } }
  ],
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "expiryDate": "2027-01-01T00:00:00.0Z"
}
```

Example of a partial update request to change the registrant of a domain name from "jd1234" to "jd1234-new":

```
[
  {
    "op": "replace",
    "path": "/registrant",
    "value": {
      "@type": "contact",
      "id": "jd1234-new"
    }
  }
]
```

Example of a partial update request to change the status of a domain name from "ok" to "clientProhibited":

```
[
  {
    "op": "replace",
    "path": "/status",
    "match": {
      "label": "ok"
    },
    "value": {
      "@type": "status",
      "label": "clientProhibited"
    }
  }
]
```

Example of a partial update request for adding a additional tech contact to a domain name:

```
[
  {
    "op": "add",
    "path": "/contacts",
    "value": {
      "label": "tech",
      "object": {
        "@type": "contact",
        "id": "sh8014"
      }
    }
  }
]
```

6. JSON Schema Definitions

This section provides normative JSON Schema definitions for RPP component objects and resource objects. All schemas use JSON Schema draft 2020-12 [JSON-SCHEMA].

6.1. Common Data Types Schemas

This section defines shared data types that are based on the primitive data types above and are re-used across multiple data object definitions.

6.1.1. Identifier

Identifiers are character strings with a specified minimum length, a specified maximum length, and a specified format outlined in [Section 2.8](#) of [RFC5730]. Identifiers for certain object types MAY have additional constraints imposed either by server policy, object-specific specifications, or both.

In JSON, an Identifier MUST be represented as a `string` value conforming to the `roidType` syntax defined in [Section 2.8](#) of [RFC5730]: one to eight word characters optionally preceded by an underscore, followed by a hyphen and one or more word characters, with a maximum total length of 89 characters.

```
{
  "$defs": {
    "identifier": {
      "type": "string",
      "pattern": "^(\\w|_){1,8}-\\w{1,}$",
      "maxLength": 89
    }
  }
}
```

6.1.2. Client Identifier

Client identifiers are character strings with a specified minimum length, a specified maximum length, and a specified format. Client identifiers use the `clIDType` syntax described in [RFC5730].

In JSON, a Client Identifier MUST be represented as a `string` value.

```
{
  "$defs": {
    "clientIdentifier": {
      "type": "string",
      "minLength": 3,
      "maxLength": 16,
      "pattern": "^[a-zA-Z0-9]([-a-zA-Z0-9]*[a-zA-Z0-9])?$"
    }
  }
}
```

6.1.3. Phone Number

Telephone number syntax is derived from structures defined in [\[ITU.E164.2005\]](#). Telephone numbers described in this specification are character strings that MUST begin with a plus sign ("+", ASCII value 0x002B), followed by a country code defined in [\[ITU.E164.2005\]](#), followed by a dot (".", ASCII value 0x002E), followed by a sequence of digits representing the telephone number. An optional "x" (ASCII value 0x0078) separator with additional digits representing extension information can be appended to the end of the value.

In JSON, a Phone Number MUST be represented as a `string` value conforming to the pattern described above.

```
{
  "$defs": {
    "phoneNumber": {
      "type": "string",
      "pattern": "^\\+[0-9]{1,3}\\.[0-9]+( x[0-9]+)?$"
    }
  }
}
```

6.2. Component Objects Schemas

6.2.1. Period Object

```
{
  "$defs": {
    "period": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "period" },
        "value": {
          "type": "integer",
          "minimum": 1,
          "maximum": 99
        },
        "unit": {
          "type": "string",
          "enum": ["y", "m"]
        }
      },
      "required": ["@type", "value", "unit"]
    }
  }
}
```

6.2.2. Provisioning Metadata Object

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- upClientId and upDate MUST NOT be present if the object has never been modified.
- trDate MUST NOT be present if the object has never been transferred.
- In EPP Compatibility Profile, repositoryId MUST be provided.

```
{
  "$defs": {
    "provMetadata": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "provMetadata",
"readOnly": true },
        "repositoryId": { "type": "string", "readOnly": true },
        "spClientId": { "$ref": "#/$defs/clientIdentifier", "readOnly":
true },
        "crClientId": { "$ref": "#/$defs/clientIdentifier", "readOnly":
true },
        "crDate": { "type": "string", "format": "date-time", "readOnly":
true },
        "upClientId": { "$ref": "#/$defs/clientIdentifier", "readOnly":
true },
        "upDate": { "type": "string", "format": "date-time", "readOnly":
true },
        "trDate": { "type": "string", "format": "date-time", "readOnly":
true }
      },
      "required": ["@type", "spClientId"]
    }
  }
}
```

6.2.3. Status Object

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- label MUST use camelCase notation using only ASCII alphabetic characters. Labels set explicitly by the server MUST use the prefix "server"; labels set explicitly by a client MUST use the prefix "client"; all other labels MUST NOT use either prefix. The allowed set of label values depends on the provisioning object type and MAY be extended by extensions.
- due: Servers MAY restrict the ability of clients to set or update this value.
- When the RGP feature is supported, the following additional status labels MAY appear on objects that support RGP: addPeriod, autoRenewPeriod, renewPeriod, transferPeriod, redemptionPeriod, pendingRestore, rgpPendingDelete. The labels redemptionPeriod, pendingRestore, and rgpPendingDelete MUST only appear alongside the standard pendingDelete status.

```
{
  "$defs": {
    "status": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "status" },
        "label": { "type": "string", "pattern": "[a-zA-Z]+$" },
        "reason": { "type": "string" },
        "due": { "type": "string", "format": "date-time" }
      },
      "required": ["@type", "label"]
    }
  }
}
```

6.2.4. DNS Resource Record Object

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- name MUST be a syntactically valid DNS host name in zone file string representation. Both absolute FQDNs (with trailing dot) and relative host names are allowed, as well as the @ symbol representing the domain name itself.
- type MUST be a valid string representation of a DNS resource record type as defined in [\[RFC1035\]](#). Values MUST be converted to lower case. Allowed values MAY be further constrained by server policy.
- In EPP Compatibility Profile ([\[RFC5732\]](#)), the following record types MUST be supported: ns, a, and aaaa. With DNSSEC Extension [\[RFC5910\]](#), ds and dnskey MUST additionally be supported.
- class, if present, MUST be chosen from Section 3.2.4 (CLASS values) of [\[RFC1035\]](#). A client SHOULD omit this element; the server MUST assume IN as the default.
- The fields within rdata MUST match the expected structure for the given record type (see RDATA structures below).

RDATA structures required in EPP Compatibility Profile:

- NS records ([\[RFC1035\]](#), Section 3.3.11): nsdname
- A records ([\[RFC1035\]](#), Section 3.4.1): address
- AAAA records ([\[RFC3596\]](#), Section 2.2): address
- DS records ([\[RFC4034\]](#), Section 5, with DNSSEC Extension): keyTag, algorithm, digestType, digest
- DNSKEY records ([\[RFC4034\]](#), Section 2, with DNSSEC Extension): flags, protocol, algorithm, publicKey

All rdata property names MUST be written in camelCase and all values MUST use the string data type.

```
{
  "$defs": {
    "dnsRecord": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "dnsRecord" },
        "name": { "type": "string" },
        "class": { "type": "string" },
        "type": { "type": "string" },
        "rdata": { "type": "object", "unevaluatedProperties": true }
      },
      "required": ["@type", "name", "type", "rdata"]
    }
  }
}
```

6.2.5. DNS Operational Controls Object

The DNS Operational Controls Object contains operational control parameters that a client MAY use to influence server-side DNS behaviour for a set of DNS records. A server MAY ignore these values, e.g. for policy reasons. This structure is aligned with [\[I-D.simmen-rpp-dns-data\]](#).

```
{
  "$defs": {
    "dnsControls": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "dnsControls" },
        "ttl": {
          "type": "object",
          "propertyNames": {
            "pattern": "^[a-z]+$"
          },
          "additionalProperties": { "type": "integer", "minimum": 1 }
        },
        "maxSigLifetime": {
          "type": "object",
          "propertyNames": {
            "pattern": "^[a-z]+$"
          },
          "additionalProperties": { "type": "integer", "minimum": 1 }
        }
      },
      "required": ["@type"]
    }
  }
}
```

6.2.6. DNS Data Object

The DNS Data Object is a container for DNS resource records and associated operational controls for a provisioned object. This structure groups DNS records together with control parameters that influence server-side DNS behaviour. It is aligned with [\[I-D.simmen-rpp-dns-data\]](#).

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- In EPP Compatibility Profile with DNSSEC Extension [\[RFC5910\]](#), records of type `ds` and `dnskey` MUST be supported in addition to `ns`, `a`, and `aaaa`. A server MUST support either `ds` or `dnskey` or both. If provided with only `dnskey`, a server MUST calculate the DS record.

```
{
  "$defs": {
    "dnsData": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "dnsData" },
        "records": {
          "type": "array",
          "items": { "$ref": "#/$defs/dnsRecord" }
        },
        "controls": { "$ref": "#/$defs/dnsControls" }
      },
      "required": ["@type"]
    }
  }
}
```

6.2.7. Authorization Information Object

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- `method` MUST be one of the values registered in the IANA RPP Authorization Method Registry as defined in [\[I-D.ietf-rpp-core\]](#). In EPP Compatibility Profile, this value MUST be `"authinfo"` for standard password-based authorization.
- The Authorization Information Object is immutable. When authorization information changes, a new instance MUST be created rather than modifying the existing one. The value of `authdata` MAY be omitted from read responses, depending on the method and server policy.

```
{
  "$defs": {
    "authInfo": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "authInfo" },
        "method": { "type": "string" },
        "authdata": { "type": "string" }
      },
      "required": ["@type", "method", "authdata"]
    }
  }
}
```

6.2.8. JSContact Card Object

The Contact Data Object uses version 2.0 of JSContact [\[RFC9982\]](#) to represent contact information. The Contact object is defined below according to the RPP JSContact Profile [TODO Add Ref].

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- `addresses[*].countryCode` MUST be a valid two-character ISO 3166-1 [\[ISO3166-1\]](#) alpha-2 code when present.
- `localizations` MUST be fully expanded; nested PatchObject-style keys (e.g., `"addresses/addr/full"`) are NOT allowed.
- When `phones[*].features` is absent, the number MUST be treated as a voice number.

```
{
  "$defs": {
    "Card": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "Card" },
        "version": { "type": "string", "const": "2.0" },
        "kind": { "type": "string", "enum": ["individual", "org"] },
        "language": { "type": "string" },
        "name": {
          "type": "object",
          "properties": {
            "full": { "type": "string" },
            "components": {
              "type": "array",
              "items": {
                "type": "object",
                "properties": {
                  "kind": { "type": "string", "enum": ["given",
"surname"] },
                  "value": { "type": "string" }
                },
                "required": ["kind", "value"]
              }
            }
          }
        }
      }
    }
  }
}
```

```
    },
    "organizations": {
      "type": "object",
      "additionalProperties": {
        "type": "object",
        "properties": {
          "name": { "type": "string" }
        }
      }
    },
    "addresses": {
      "type": "object",
      "additionalProperties": {
        "type": "object",
        "properties": {
          "full": { "type": "string" },
          "countryCode": { "type": "string", "pattern": "^[A-Z]{2}$" },
          "components": {
            "type": "array",
            "items": {
              "type": "object",
              "properties": {
                "kind": { "type": "string", "enum": ["name", "locality",
"region", "postcode", "country"] },
                "value": { "type": "string" }
              },
              "required": ["kind", "value"]
            }
          }
        }
      }
    },
    "phones": {
      "type": "object",
      "additionalProperties": {
        "type": "object",
        "properties": {
          "number": { "type": "string" },
          "features": {
            "type": "object",
            "additionalProperties": {
              "type": "boolean"
            }
          }
        },
        "required": ["number"]
      }
    },
    "emails": {
      "type": "object",
      "additionalProperties": {
        "type": "object",
        "properties": {
          "address": { "type": "string", "format": "email" }
        },
        "required": ["address"]
      }
    }
  }
```

```
    },
    "links": {
      "type": "object",
      "additionalProperties": {
        "type": "object",
        "properties": {
          "uri": { "type": "string", "format": "uri" },
          "kind": { "type": "string", "const": "contact" }
        },
        "required": ["uri"]
      }
    },
    "localizations": { "type": "object" },
    "required": ["@type", "version"]
  }
}
```

6.2.9. Restore Report Object

The Restore Report Object contains the redemption grace period restore report submitted by the sponsoring client as required by the RGP process ([RFC3915]).

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- At least one and at most two statements MUST be provided.
- `restoreTime` MAY be omitted when the restore report is submitted inline within the restore request in a single-step process.
- In EPP Compatibility Profile, `restoreTime` MUST be present as defined in [RFC3915].
- In EPP Compatibility Profile, exactly two statements MUST be present as defined in [RFC3915].

```
{
  "$defs": {
    "restoreReport": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "restoreReport" },
        "preData": { "type": "string" },
        "postData": { "type": "string" },
        "deleteTime": { "type": "string", "format": "date-time" },
        "restoreTime": { "type": "string", "format": "date-time" },
        "restoreReason": { "type": "string" },
        "statements": {
          "type": "array",
          "items": { "type": "string" },
          "minItems": 1,
          "maxItems": 2
        },
        "other": { "type": "string" }
      },
      "required": ["@type", "statements"]
    }
  }
}
```

6.2.10. Organisation Role Object

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- type MUST only use values registered in the IANA "EPP Organization Role Values" registry ([RFC8543]).

```
{
  "$defs": {
    "organisationRole": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "organisationRole" },
        "status": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": ["ok", "linked", "clientLinkProhibited",
"serverLinkProhibited"]
          }
        },
        "roleId": { "type": "string" }
      },
      "required": ["@type"]
    }
  }
}
```

6.2.11. Processes Object

The Processes Object is a read-only container grouping the currently active Process Objects on the owning resource object, keyed by process type. Each key holds an array of the corresponding Process Object's read representation, per the Aggregation rules.

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/processes",
  "$defs": {
    "processes": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "processes",
"readOnly": true },
        "createProcess": {
          "type": "array",
          "items": { "$ref": "#/$defs/createProcess.read" },
          "readOnly": true
        },
        "renewProcess": {
          "type": "array",
          "items": { "$ref": "#/$defs/renewProcess.read" },
          "readOnly": true
        },
        "transferProcess": {
          "type": "array",
          "items": { "$ref": "#/$defs/transferProcess.read" },
          "readOnly": true
        },
        "restoreProcess": {
          "type": "array",
          "items": { "$ref": "#/$defs/restoreProcess.read" },
          "readOnly": true
        }
      },
      "required": ["@type"]
    }
  }
}
```

6.3. Process Object Schemas

6.3.1. Create Process Object

The Create Process Object carries the process-specific inputs for a resource creation operation, such as the requested registration period. It is submitted as an element of the createProcess array under the processes data element of the owning resource object (see Processes Object), following the same Aggregation representation as the other process types.

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/createProcess.create",
  "$defs": {
    "createProcess.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "createProcess" },
        "period": { "$ref": "#/$defs/period" }
      },
      "required": ["@type"]
    }
  }
}
```

Read response schema (read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/createProcess.read",
  "$defs": {
    "createProcess.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "createProcess", "readOnly":
true },
        "period": { "$ref": "#/$defs/period", "readOnly": true }
      },
      "required": ["@type"]
    }
  }
}
```

6.3.2. Renew Process Object

Renew request schema (create-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/renewProcess.create",
  "$defs": {
    "renewProcess.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "renewProcess" },
        "expiryDate": { "type": "string", "format": "date-time" },
        "renewalPeriod": { "$ref": "#/$defs/period" }
      },
      "required": ["@type"]
    }
  }
}
```

Renew response schema (read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/renewProcess.read",
  "$defs": {
    "renewProcess.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "renewProcess",
"readOnly": true },
        "expiryDate": { "type": "string", "format": "date-time", "readOnly":
true }
      },
      "required": ["@type"]
    }
  }
}
```

6.3.3. Transfer Process Object

6.3.3.1. Create

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.create",
  "$defs": {
    "transferProcess.create": {
      "type": "object",
      "oneOf": [
        {
          "properties": {
            "@type": { "type": "string", "const": "transferProcess" },
            "transferDir": {
              "type": "string",
              "const": "push"
            },
            "gainingClientId": { "$ref": "#/$defs/clientIdentifier" }
          },
          "required": [
            "@type", "transferDir", "gainingClientId"
          ]
        },
        {
          "properties": {
            "@type": { "type": "string", "const": "transferProcess" },
            "transferDir": {
              "type": "string",
              "const": "pull"
            }
          },
          "required": [
            "@type", "transferDir"
          ]
        }
      ]
    }
  }
}
```

6.3.3.2. Read

Read response schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.read",
  "$defs": {
    "transferProcess.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "transferProcess", "readOnly":
true },
        "trStatus": {
          "type": "string",
          "enum": ["pending", "clientApproved", "clientCancelled",
            "clientRejected", "serverApproved", "serverCancelled"],
          "readOnly": true
        },
        "transferDir": {
          "type": "string",
          "enum": ["pull", "push"],
          "readOnly": true
        },
        "gainingClientId": { "$ref": "#/$defs/clientIdentifier", "readOnly":
true },
        "reqClientId": { "$ref": "#/$defs/clientIdentifier", "readOnly":
true},
        "requestDate": { "type": "string", "format": "date-time", "readOnly":
true },
        "actClientId": { "$ref": "#/$defs/clientIdentifier", "readOnly":
true },
        "actionDate": { "type": "string", "format": "date-time", "readOnly":
true }
      },
      "required": [
        "@type", "transferDir", "trStatus", "reqClientId",
        "requestDate", "actClientId", "actionDate"
      ]
    }
  }
}
```

6.3.3.3. Approve

The Approve operation MUST always have a request body, which may be an empty JSON object. The server can identify the transfer process to be approved based on the request URL and the authenticated client's permissions. There is no Approve request schema defined in this specification.

The Approve response schema MUST equal the read response schema.

6.3.3.4. Cancel

The Cancel operation, which is similar to a delete operation, has no request body, the server can identify the transfer process to be cancelled based on the request URL and the authenticated client's permissions. Because the Cancel operation has no request body, it is not possible to extend the request schema with additional properties.

The Cancel response schema MUST equal the read response schema or an empty response.

6.3.3.5. Reject

Reject request schema:

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.reject",
  "$defs": {
    "transferProcess.reject": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "transferProcess" },
        "reason": { "type": "string" }
      },
      "required": ["@type"]
    }
  }
}
```

Reject response schema MUST equal the read response schema.

6.3.4. Restore Process Object

The Restore Process Object represents the current state of a restore request for an object that has entered the Redemption Grace Period (RGP). It is returned as a response for all restore operations.

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- requestDate MUST NOT be present if no restore request has been submitted yet.
- reportDate MUST NOT be present if no restore report has been accepted yet.
- reportDueDate MUST NOT be present when restoreStatus is not "pendingRestore".

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/restoreProcess.create",
  "$defs": {
    "restoreProcess.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "restoreProcess" },
        "restoreReport": { "$ref": "#/$defs/restoreReport" }
      },
      "required": ["@type"]
    }
  }
}
```

Read response schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/restoreProcess.read",
  "$defs": {
    "restoreProcess.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "restoreProcess",
"readOnly": true },
        "restoreStatus": {
          "type": "string",
          "enum": ["pendingRestore", "restored", "rgpPendingDelete"],
          "readOnly": true
        },
        "requestDate": { "type": "string", "format": "date-time",
"readOnly": true },
        "reportDate": { "type": "string", "format": "date-time",
"readOnly": true },
        "reportDueDate": { "type": "string", "format": "date-time",
"readOnly": true }
      },
      "required": ["@type", "restoreStatus"]
    }
  }
}
```

6.4. Domain Name Data Object

The Domain Name Data Object represents a domain name and its associated provisioning data.

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- name MUST be a fully qualified domain name conforming to the syntax described in [\[RFC1035\]](#). Servers MAY restrict allowable domain names to a specific namespace for which they are authoritative. The implicit trailing dot MUST NOT be included.

6.4.1. Create

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/domainObject.create",
  "$defs": {
    "domainObject.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "domainName" },
        "name": { "type": "string", "writeOnly": true },
        "registrant": { "$ref": "#/$defs/contactObject.reference" },
        "contacts": {
          "type": "array",
          "items": {
            "type": "object",
            "properties": {
              "label": { "type": "string" },
              "object": { "$ref": "#/$defs/contactObject.reference" }
            },
            "required": ["label", "object"]
          }
        },
        "nameservers": {
          "type": "array",
          "items": { "$ref": "#/$defs/hostObject.reference" }
        },
        "dns": { "$ref": "#/$defs/dnsData" },
        "authInfo": { "$ref": "#/$defs/authInfo" },
        "processes": {
          "type": "object",
          "properties": {
            "@type": { "type": "string", "const": "processes" },
            "createProcess": {
              "type": "array",
              "items": { "$ref": "#/$defs/createProcess.create" },
              "maxItems": 1
            }
          },
          "required": ["@type"]
        }
      },
      "required": ["@type", "name"]
    }
  }
}
```

6.4.2. Read

Read response schema (read-write and read-only properties):

```

{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/domainObject.read",
  "$defs": {
    "domainObject.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "domainName", "readOnly":
true },
        "name": { "type": "string", "readOnly": true },
        "provMetadata": { "$ref": "#/$defs/provMetadata" },
        "status": {
          "type": "array",
          "items": { "$ref": "#/$defs/status" },
          "readOnly": true
        },
        "registrant": { "$ref": "#/$defs/contactObject.reference" },
        "contacts": {
          "type": "array",
          "items": {
            "type": "object",
            "properties": {
              "label": { "type": "string" },
              "object": { "$ref": "#/$defs/contactObject.reference" }
            },
            "required": ["label", "object"]
          }
        },
        "nameservers": {
          "type": "array",
          "items": { "$ref": "#/$defs/hostObject.reference" }
        },
        "dns": { "$ref": "#/$defs/dnsData" },
        "subordinateHosts": {
          "type": "array",
          "items": { "$ref": "#/$defs/hostObject.reference" },
          "readOnly": true
        },
        "expiryDate": { "type": "string", "format": "date-time", "readOnly":
true },
        "authInfo": { "$ref": "#/$defs/authInfo" },
        "processes": { "$ref": "#/$defs/processes", "readOnly": true }
      },
      "required": ["@type", "name", "provMetadata"]
    }
  }
}

```

6.4.3. Update

Update request schema (read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/domainObject.update",
  "$defs": {
    "domainObject.update": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "domainName" },
        "registrant": { "$ref": "#/$defs/contactObject.reference" },
        "contacts": {
          "type": "array",
          "items": {
            "type": "object",
            "properties": {
              "label": { "type": "string" },
              "object": { "$ref": "#/$defs/contactObject.reference" }
            },
            "required": ["label", "object"]
          }
        },
        "nameservers": {
          "type": "array",
          "items": { "$ref": "#/$defs/hostObject.reference" }
        },
        "dns": { "$ref": "#/$defs/dnsData" },
        "authInfo": { "$ref": "#/$defs/authInfo" }
      },
      "required": ["@type"]
    }
  }
}
```

6.4.4. Renew

Renew minimal response schema (only expire date):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/renewProcess.create.domain",
  "$defs": {
    "renewProcess.create.domain": {
      "$ref": "#/$defs/renewProcess.create"
    }
  }
}
```

6.4.5. Transfer

Create request for Domain Transfer Process Object schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.create.domain",
  "$defs": {
    "transferProcess.create.domain": {
      "allOf": [
        { "$ref": "#/$defs/transferProcess.create" },
        {
          "properties": {
            "transferPeriod": { "$ref": "#/$defs/period" }
          }
        }
      ]
    }
  }
}
```

Read response for Domain Transfer Process Object schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.read.domain",
  "$defs": {
    "transferProcess.read.domain": {
      "allOf": [
        { "$ref": "#/$defs/transferProcess.read" },
        {
          "properties": {
            "expiryDate": { "type": "string", "format": "date-time",
"readOnly": true }
          }
        }
      ]
    }
  }
}
```

Both Approve and Delete (Cancel) operations have no request body, the server can identify the transfer process to be approved or cancelled based on the request URL and the authenticated client's permissions.

Delete (Cancel) response Domain Transfer Process Object schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.delete.domain",
  "$defs": {
    "transferProcess.delete.domain": {
      "$ref": "#/$defs/transferProcess.read.domain"
    }
  }
}
```

Approve response Domain Transfer Process Object schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.approve.domain",
  "$defs": {
    "transferProcess.approve.domain": {
      "$ref": "#/$defs/transferProcess.read.domain"
    }
  }
}
```

Reject request Domain Object schema:

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.reject.domain",
  "$defs": {
    "transferProcess.reject.domain": {
      "$ref": "#/$defs/transferProcess.reject"
    }
  }
}
```

Reject response schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.reject.domain",
  "$defs": {
    "transferProcess.reject.domain": {
      "$ref": "#/$defs/transferProcess.read.domain"
    }
  }
}
```

6.4.6. Reference

Reference schema (identifier only):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/domainObject.reference",
  "$defs": {
    "domainObject.reference": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "domainName", "readOnly":
true },
        "name": { "type": "string", "readOnly": true }
      },
      "required": ["@type", "name"]
    }
  }
}
```

6.5. Contact Data Object

This document uses version 2.0 of JSContact [RFC9982] for the JSON representation of Contact Data Object contact information. The contact's name, postal address, phone numbers, email addresses, and other contact details are encapsulated in a JSContact Card object embedded in the `contactInfo` property.

6.5.1. JSContact Profile for RPP

Since JSContact is a general-purpose representation of contact data, this document defines a restricted usage profile for use within RPP, see [TODO: ref to RPP JSContact profile here: <https://github.com/SIDN/ietf-rpp-jscontact-profile>].

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- `card.name.full` MUST be provided in EPP Compatibility Profile.
- `card.addresses.addr` MUST be provided in EPP Compatibility Profile, containing at least `countryCode` and a `"locality"` kind component.
- `card.emails.email.address` MUST be provided in EPP Compatibility Profile.
- `card.addresses[*].countryCode` MUST be a valid two-character ISO 3166-1 [ISO3166-1] alpha-2 code when present.

6.5.2. Create

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/contactObject.create",
  "$defs": {
    "contactObject.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "contact" },
        "id": { "type": "string" },
        "contactInfo": { "$ref": "#/$defs/Card" },
        "authInfo": { "$ref": "#/$defs/authInfo" }
      },
      "required": ["@type", "id", "contactInfo"],
      "unevaluatedProperties": false
    }
  }
}
```

6.5.3. Read

Read response schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/contactObject.read",
  "$defs": {
    "contactObject.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "contact", "readOnly": true },
        "id": { "type": "string", "readOnly": true },
        "provMetadata": { "$ref": "#/$defs/provMetadata" },
        "status": {
          "type": "array",
          "items": { "$ref": "#/$defs/status" },
          "readOnly": true
        },
        "contactInfo": { "$ref": "#/$defs/Card" },
        "authInfo": { "$ref": "#/$defs/authInfo" }
      },
      "required": ["@type", "id", "provMetadata", "contactInfo"],
      "unevaluatedProperties": false
    }
  }
}
```

6.5.4. Update

Update request schema (read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/contactObject.update",
  "$defs": {
    "contactObject.update": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "contact" },
        "contactInfo": { "$ref": "#/$defs/Card" },
        "authInfo": { "$ref": "#/$defs/authInfo" },
        "processes": { "$ref": "#/$defs/processes", "readOnly": true }
      },
      "required": ["@type", "contactInfo"],
      "unevaluatedProperties": false
    }
  }
}
```

6.5.5. Transfer

Transfer create request for Contact Object schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/transferProcess.create.contact",
  "$defs": {
    "transferProcess.create.contact": {
      "$ref": "#/$defs/transferProcess.create"
    }
  }
}
```

6.5.6. Reference

Reference schema (identifier only):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/contactObject.reference",
  "$defs": {
    "contactObject.reference": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "contact", "readOnly":
true },
        "id": { "type": "string", "readOnly": true }
      },
      "required": ["@type", "id"]
    }
  }
}
```

6.6. Host Data Object

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- `hostName` MUST be a syntactically valid fully qualified host name.
- If the host name is subordinate to a domain for which the server is authoritative, the superordinate domain MUST already exist in the server.

6.6.1. Create

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/hostObject.create",
  "$defs": {
    "hostObject.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "host" },
        "hostName": { "type": "string", "format": "hostname" },
        "dns": { "$ref": "#/$defs/dnsData" }
      },
      "required": ["@type", "hostName"]
    }
  }
}
```

6.6.2. Read

Read response schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/hostObject.read",
  "$defs": {
    "hostObject.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "host", "readOnly":
true },
        "hostName": { "type": "string", "format": "hostname" },
        "provMetadata": { "$ref": "#/$defs/provMetadata" },
        "status": {
          "type": "array",
          "items": { "$ref": "#/$defs/status" },
          "readOnly": true
        },
        "dns": { "$ref": "#/$defs/dnsData" },
        "processes": { "$ref": "#/$defs/processes", "readOnly": true }
      },
      "required": ["@type", "hostName", "provMetadata"]
    }
  }
}
```

6.6.3. Update

TODO

6.6.4. Reference

Reference schema (identifier only):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/hostObject.reference",
  "$defs": {
    "hostObject.reference": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "host", "readOnly":
true },
        "hostName": { "type": "string", "format": "hostname",
"readOnly": true }
      },
      "required": ["@type", "hostName"]
    }
  }
}
```

6.7. Organisation Data Object

The following constraints cannot be expressed in JSON Schema and MUST be enforced by implementations:

- `id` MUST be a server-unique identifier conforming to the Identifier syntax.
- `status` MUST always contain at least one value. `pendingCreate`, `ok`, `hold`, and `terminated` are mutually exclusive. `ok` MAY only be combined with `linked`.
- `parent`, if present, MUST reference a known Organisation Object. Circular parent references MUST be rejected.
- `contacts` keys MUST be contact type values registered in the IANA "EPP Organisation Contact Types" registry ([RFC8543]).

6.7.1. Create

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/organisationObject.create",
  "$defs": {
    "organisationObject.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "organisation" },
        "id": { "$ref": "#/$defs/identifier" },
        "roles": {
          "type": "object",
          "additionalProperties": { "$ref": "#/$defs/organisationRole" },
          "minProperties": 1
        },
        "parent": { "$ref": "#/$defs/organisationObject.reference" },
        "contactInfo": { "$ref": "#/$defs/Card" },
        "contacts": {
          "type": "array",
          "items": {
            "type": "object",
            "properties": {
              "label": { "type": "string" },
              "object": { "$ref": "#/$defs/contactObject.reference" }
            },
            "required": ["label", "object"]
          }
        },
        "required": ["@type", "id", "roles"]
      }
    }
  }
}
```

6.7.2. Read

Read response schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/organisationObject.read",
  "$defs": {
    "organisationObject.read": {
      "allOf": [
        { "$ref": "#/$defs/organisationObject.create" },
        {
          "properties": {
            "provMetadata": { "$ref": "#/$defs/provMetadata", "readOnly":
true },
            "status": {
              "type": "array",
              "items": { "$ref": "#/$defs/status" },
              "readOnly": true
            },
            "users": {
              "type": "array",
              "items": {
                "type": "object",
                "properties": {
                  "label": { "type": "string" },
                  "object": { "$ref": "#/$defs/userObject.reference" }
                },
                "required": ["label", "object"]
              }
            }
          },
          "required": ["provMetadata", "status"]
        }
      ]
    }
  }
}
```

6.7.3. Update

Update request schema (read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/organisationObject.update",
  "$defs": {
    "organisationObject.update": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "organisation" },
        "roles": {
          "type": "object",
          "additionalProperties": { "$ref": "#/$defs/organisationRole" }
        },
        "parent": { "$ref": "#/$defs/organisationObject.reference" },
        "contactInfo": { "$ref": "#/$defs/Card" },
        "contacts": {
          "type": "array",
          "items": {
            "type": "object",
            "properties": {
              "label": { "type": "string" },
              "object": { "$ref": "#/$defs/contactObject.reference" }
            },
            "required": ["label", "object"]
          }
        },
        "status": {
          "type": "array",
          "items": { "$ref": "#/$defs/status" },
          "readOnly": true
        },
        "users": {
          "type": "array",
          "items": {
            "type": "object",
            "properties": {
              "label": { "type": "string" },
              "object": { "$ref": "#/$defs/userObject.reference" }
            },
            "required": ["label", "object"]
          }
        }
      },
      "required": ["@type"]
    }
  }
}
```

6.7.4. Reference

Reference schema (identifier only):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/organisationObject.reference",
  "$defs": {
    "organisationObject.reference": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "organisation", "readOnly":
true },
        "id": { "$ref": "#/$defs/identifier", "readOnly": true }
      },
      "required": ["@type", "id"]
    }
  }
}
```

6.8. User Data Object

The User Data Object represents a user linked to an Organisation Object. The lifecycle of a User Object is bound to its owning Organisation Object.

Note: User status values are plain strings, not Status Objects.

6.8.1. Create

Create request schema (create-only and read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/userObject.create",
  "$defs": {
    "userObject.create": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "user" },
        "organisationId": { "$ref": "#/$defs/organisationObject.reference" },
        "details": { "$ref": "#/$defs/contactObject.reference" },
        "status": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": ["active", "suspended", "deactivated", "pending"]
          }
        },
        "description": { "type": "string", "const": "user" }
      },
      "required": ["@type", "organisationId", "details"]
    }
  }
}
```

6.8.2. Read

Read response schema (read-write and read-only properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/userObject.read",
  "$defs": {
    "userObject.read": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "user", "readOnly": true },
        "organisationId": { "$ref": "#/$defs/organisationObject.reference" },
        "userId": { "$ref": "#/$defs/identifier", "readOnly": true },
        "details": { "$ref": "#/$defs/contactObject.reference" },
        "status": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": ["active", "suspended", "deactivated", "pending"]
          }
        },
        "description": { "type": "string", "const": "user" }
      },
      "required": ["@type", "userId", "details", "status"]
    }
  }
}
```

6.8.3. Update

Update request schema (read-write properties):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/userObject.update",
  "$defs": {
    "userObject.update": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "user" },
        "details": { "$ref": "#/$defs/contactObject.reference" },
        "status": {
          "type": "array",
          "items": {
            "type": "string",
            "enum": ["active", "suspended", "deactivated", "pending"]
          }
        }
      },
      "required": ["@type"]
    }
  }
}
```

6.8.4. Reference

Reference schema (identifier only):

```
{
  "$schema": "https://json-schema.org/draft/2020-12/schema",
  "$ref": "#/$defs/userObject.reference",
  "$defs": {
    "userObject.reference": {
      "type": "object",
      "properties": {
        "@type": { "type": "string", "const": "user", "readOnly": true },
        "id": { "$ref": "#/$defs/identifier", "readOnly": true }
      },
      "required": ["@type", "id"]
    }
  }
}
```

7. Examples

This section provides examples that follow the JSON representation rules and JSON Schema definitions specified in the previous sections. The examples illustrate typical request and response messages for domain name, contact, and host resources.

7.1. Domain Name

7.1.1. Create

Example domain create request:

```
{
  "@type": "domainName",
  "name": "example.example",
  "nameservers": [
    { "@type": "host", "hostName": "ns1.example.example" },
    { "@type": "host", "hostName": "ns2.example.example" }
  ],
  "registrant": { "@type": "contact", "id": "jd1234" },
  "contacts": [
    { "label": "admin", "object": { "@type": "contact", "id": "sh8013" } },
    { "label": "tech", "object": { "@type": "contact", "id": "sh8013" } }
  ],
  "authInfo": {
    "@type": "authInfo",
    "method": "authinfo",
    "authdata": "2fooBAR"
  },
  "processes": {
    "@type": "processes",
    "createProcess": [
      {
        "@type": "createProcess",
        "period": {
          "@type": "period",
          "value": 2,
          "unit": "y"
        }
      }
    ]
  }
}
```

Example domain create response from a server with RGP support:

```
{
  "@type": "domainName",
  "name": "example.example",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "EXAMPLE1-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "1999-04-03T22:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" },
    { "@type": "status", "label": "addPeriod" }
  ],
  "expiryDate": "2001-04-03T22:00:00.0Z"
}
```

7.1.2. Create Process Data

Example Create Process Object for a two-year registration period, as embedded above in `processes.createProcess`:

```
{
  "@type": "createProcess",
  "period": {
    "@type": "period",
    "value": 2,
    "unit": "y"
  }
}
```

7.1.3. Read

Example domain read response:

```
{
  "@type": "domainName",
  "name": "example.example",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "EXAMPLE1-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientY",
    "crDate": "1999-04-03T22:00:00.0Z",
    "upClientId": "ClientX",
    "upDate": "1999-12-03T09:00:00.0Z",
    "trDate": "2000-04-08T09:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "registrant": { "@type": "contact", "id": "jd1234" },
  "contacts": [
    { "label": "admin", "object": { "@type": "contact", "id": "sh8013" } },
    { "label": "tech", "object": { "@type": "contact", "id": "sh8013" } }
  ],
  "nameservers": [
    {
      "@type": "host",
      "hostName": "ns1.example.example"
    },
    {
      "@type": "host",
      "hostName": "ns2.example.example"
    }
  ],
  "subordinateHosts": [
    {
      "@type": "host",
      "hostName": "ns1.example.example"
    }
  ]
}
```

```
    },
    {
      "@type": "host",
      "hostName": "ns2.example.example"
    }
  ],
  "expiryDate": "2005-04-03T22:00:00.0Z",
  "authInfo": {
    "@type": "authInfo",
    "method": "authinfo",
    "authdata": "2fooBAR"
  },
  "processes": {
    "@type": "processes",
    "createProcess": [
      {
        "@type": "createProcess",
        "period": {
          "@type": "period",
          "value": 2,
          "unit": "y"
        }
      }
    ]
  }
}
```

7.1.4. Update

Example domain update request (read-write properties):

```
{
  "@type": "domainName",
  "registrant": { "@type": "contact", "id": "sh8013" },
  "authInfo": {
    "@type": "authInfo",
    "method": "authinfo",
    "authdata": "2BARfoo"
  }
}
```

Example domain update response:

```
{
  "@type": "domainName",
  "name": "example.example",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "EXAMPLE1-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientY",
    "crDate": "1999-04-03T22:00:00.0Z",
    "upClientId": "ClientX",
    "upDate": "2000-01-15T09:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "registrant": { "@type": "contact", "id": "sh8013" }
}
```

7.1.5. Delete

The domain delete operation takes the domain name as the resource identifier in the request. No request body is required.

Example domain delete response (minimal, server may return full representation):

```
{
  "@type": "domainName",
  "name": "example.example",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "EXAMPLE1-REP",
    "spClientId": "ClientX"
  }
}
```

7.1.6. Renew

The renew operation creates a Renew Process Object. The optional `expiryDate` in the request is the *current* expiry date, sent by the client for server-side validation to prevent duplicate renewals. The response returns a Renew Process Object containing the *new* expiry date.

Example domain renew request:

```
{
  "@type": "renewProcess",
  "expiryDate": "2005-04-03T22:00:00.0Z",
  "renewalPeriod": {
    "@type": "period",
    "value": 5,
    "unit": "y"
  }
}
```

Example domain renew response:

```
{
  "@type": "renewProcess",
  "expiryDate": "2010-04-03T22:00:00.0Z"
}
```

7.1.7. Transfer Request

Authorization information for the transfer MUST be conveyed using the RPP-Authorization HTTP header (see Rule 21), not in the JSON request body.

Example domain transfer request (pull transfer)

```
{
  "@type": "transferProcess",
  "transferDir": "pull",
  "transferPeriod": {
    "@type": "period",
    "value": 1,
    "unit": "y"
  }
}
```

Example domain transfer response (Transfer Process Object):

```
{
  "@type": "transferProcess",
  "trStatus": "pending",
  "transferDir": "pull",
  "reqClientId": "ClientX",
  "requestDate": "2000-06-08T22:00:00.0Z",
  "actClientId": "ClientY",
  "actionDate": "2000-06-13T22:00:00.0Z",
  "expiryDate": "2002-09-08T22:00:00.0Z"
}
```

7.1.8. Transfer Query

Example domain transfer query response (Transfer Process Object):

```
{
  "@type": "transferProcess",
  "trStatus": "pending",
  "transferDir": "pull",
  "reqClientId": "ClientX",
  "requestDate": "2000-06-06T22:00:00.0Z",
  "actClientId": "ClientY",
  "actionDate": "2000-06-11T22:00:00.0Z",
  "expiryDate": "2002-09-08T22:00:00.0Z"
}
```

7.1.9. Transfer Approve

The Transfer approve operation has request body with an empty JSON object, the server can identify the transfer process to be approved based on the request URL and the authenticated client's permissions.

Example domain transfer approve request with empty JSON object:

```
{
  "@type": "transferProcess"
}
```

The response is the Transfer Process Object, similar to the transfer create and query responses.

7.1.10. Transfer Cancel

The Transfer cancel operation has an empty request body, the server can identify the transfer process to be cancelled based on the request URL and the authenticated client's permissions.

The response is the Transfer Process Object, similar to the transfer create and query responses.

7.1.11. Transfer Reject

Example domain transfer reject request

```
{
  "@type": "transferProcess",
  "reason": "Client rejected the transfer request."
}
```

The transfer reject response is the Transfer Process Object, similar to the transfer create and query responses.

7.1.12. Restore Request

Example domain restore request (without inline report; object transitions to pendingRestore state):

```
{
  "@type": "restoreProcess"
}
```

Example domain restore response (Restore Process Object, server requires a report):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "pendingRestore",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDueDate": "2025-01-27T15:30:00.0Z"
}
```

Example domain restore request with inline restore report (single-step; object restored immediately):

```
{
  "@type": "restoreProcess",
  "restoreReport": {
    "@type": "restoreReport",
    "preData": "Domain example.example was registered on 2024-01-15 with
registrant jd1234.",
    "postData": "Domain example.example is being restored with the same
registration data.",
    "deleteTime": "2025-01-10T12:00:00.0Z",
    "restoreTime": "2025-01-20T15:30:00.0Z",
    "restoreReason": "Domain deleted in error by client operator.",
    "statements": [
      "The information in this report is true to the best of my
knowledge.",
      "I have a valid reason for restoring this domain name."
    ]
  }
}
```

Example domain restore response with inline report (Restore Process Object, immediately restored):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "restored",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDate": "2025-01-20T15:30:00.0Z"
}
```

7.1.13. Restore Report

Example domain restore report request:

```
{
  "@type": "restoreProcess",
  "restoreReport": {
    "@type": "restoreReport",
    "preData": "Domain example.example was registered on 2024-01-15 with
registrant jd1234.",
    "postData": "Domain example.example is being restored with the same
registration data.",
    "deleteTime": "2025-01-10T12:00:00.0Z",
    "restoreTime": "2025-01-20T15:30:00.0Z",
    "restoreReason": "Domain deleted in error by client operator.",
    "statements": [
      "The information in this report is true to the best of my
knowledge.",
      "I have a valid reason for restoring this domain name."
    ]
  }
}
```

Example domain restore report response (Restore Process Object):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "restored",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDate": "2025-01-22T09:15:00.0Z"
}
```

7.1.14. Restore Query

The Restore Query operation takes no request body (Parameters: None).

Example domain restore query response (Restore Process Object, object in pendingRestore state):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "pendingRestore",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDueDate": "2025-01-27T15:30:00.0Z"
}
```

Example domain restore query response (Restore Process Object, object restored):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "restored",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDate": "2025-01-22T09:15:00.0Z"
}
```

7.2. Contact

7.2.1. Create

Example contact create request:

```
{
  "@type": "contact",
  "id": "jd1234",
  "contactInfo": {
    "@type": "Card",
    "version": "2.0",
    "kind": "individual",
    "name": {
      "full": "John Doe",
      "components": [
        { "kind": "given", "value": "John" },
        { "kind": "surname", "value": "Doe" }
      ]
    },
    "organizations": {
      "org": { "name": "Example Inc." }
    },
    "addresses": {
      "addr": {
        "components": [
          { "kind": "name", "value": "123 Example Dr., Suite
100" },
          { "kind": "locality", "value": "Dulles" },
          { "kind": "region", "value": "VA" },
          { "kind": "postcode", "value": "20166-6503" },
          { "kind": "country", "value": "United States" }
        ],
        "countryCode": "US"
      }
    },
    "phones": {
      "voice": { "number": "tel:+1-703-555-5555" },
      "fax": { "features": { "fax": true }, "number": "tel:
+1-703-555-5556" }
    },
    "emails": {
      "email": { "address": "jdoe@example.example" }
    }
  },
  "authInfo": {
    "@type": "authInfo",
    "method": "authinfo",
    "authdata": "2fooBAR"
  }
}
```

Example contact create response:

```

{
  "@type": "contact",
  "id": "jd1234",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "JD1234-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "1999-04-03T22:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "contactInfo": {
    "@type": "Card",
    "version": "2.0",
    "kind": "individual",
    "name": {
      "full": "John Doe",
      "components": [
        { "kind": "given", "value": "John" },
        { "kind": "surname", "value": "Doe" }
      ]
    },
    "organizations": {
      "org": { "name": "Example Inc." }
    },
    "addresses": {
      "addr": {
        "components": [
          { "kind": "name", "value": "123 Example Dr., Suite
100" },
          { "kind": "locality", "value": "Dulles" },
          { "kind": "region", "value": "VA" },
          { "kind": "postcode", "value": "20166-6503" },
          { "kind": "country", "value": "United States" }
        ],
        "countryCode": "US"
      }
    },
    "phones": {
      "voice": { "number": "tel:+1-703-555-5555" },
      "fax": { "features": { "fax": true }, "number": "tel:
+1-703-555-5556" }
    },
    "emails": {
      "email": { "address": "jdoe@example.example" }
    }
  }
}

```

7.2.2. Read

Example contact read response:

```

{
  "@type": "contact",
  "id": "jd1234",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "JD1234-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "1999-04-03T22:00:00.0Z",
    "upClientId": "ClientX",
    "upDate": "2000-01-15T09:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "contactInfo": {
    "@type": "Card",
    "version": "2.0",
    "kind": "individual",
    "name": {
      "full": "John Doe",
      "components": [
        { "kind": "given", "value": "John" },
        { "kind": "surname", "value": "Doe" }
      ]
    },
    "organizations": {
      "org": { "name": "Example Inc." }
    },
    "addresses": {
      "addr": {
        "components": [
          { "kind": "name", "value": "123 Example Dr., Suite
100" },
          { "kind": "locality", "value": "Dulles" },
          { "kind": "region", "value": "VA" },
          { "kind": "postcode", "value": "20166-6503" },
          { "kind": "country", "value": "United States" }
        ],
        "countryCode": "US"
      }
    },
    "phones": {
      "voice": { "number": "tel:+1-703-555-5555" }
    },
    "emails": {
      "email": { "address": "jdoe@example.example" }
    }
  }
}

```

7.2.3. Update

Example contact update request:

```
{
  "@type": "contact",
  "contactInfo": {
    "@type": "Card",
    "version": "2.0",
    "addresses": {
      "addr": {
        "components": [
          { "kind": "name", "value": "456 New Street, Suite
200" },
          { "kind": "locality", "value": "Reston" },
          { "kind": "region", "value": "VA" },
          { "kind": "postcode", "value": "20190" },
          { "kind": "country", "value": "United States" }
        ],
        "countryCode": "US"
      }
    },
    "phones": {
      "voice": { "number": "tel:+1-703-555-5556" }
    },
    "emails": {
      "email": { "address": "jdoe-new@example.example" }
    }
  }
}
```

Example contact update response:

```
{
  "@type": "contact",
  "id": "jd1234",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "JD1234-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "1999-04-03T22:00:00.0Z",
    "upClientId": "ClientX",
    "upDate": "2025-06-01T10:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "contactInfo": {
    "@type": "Card",
    "version": "2.0",
    "kind": "individual",
    "name": {
      "full": "John Doe",
      "components": [
        { "kind": "given", "value": "John" },
        { "kind": "surname", "value": "Doe" }
      ]
    }
  }
}
```

```
    "organizations": {
      "org": { "name": "Example Inc." }
    },
    "addresses": {
      "addr": {
        "components": [
          { "kind": "name",      "value": "456 New Street, Suite
200" },
          { "kind": "locality", "value": "Reston" },
          { "kind": "region",   "value": "VA" },
          { "kind": "postcode", "value": "20190" },
          { "kind": "country",  "value": "United States" }
        ],
        "countryCode": "US"
      }
    },
    "phones": {
      "voice": { "number": "tel:+1-703-555-5556" }
    },
    "emails": {
      "email": { "address": "jdoe-new@example.example" }
    }
  }
}
```

7.2.4. Delete

The contact delete operation takes the contact identifier as the resource identifier. No request body is required.

7.2.5. Transfer Request

Authorization information for the transfer **MUST** be conveyed using the RPP-
Authorization HTTP header (see Rule 21), not in the JSON request body.

Example contact transfer request (pull transfer)

```
{
  "@type": "transferProcess",
  "transferDir": "pull"
}
```

Example contact transfer response (Transfer Process Object):

```
{
  "@type": "transferProcess",
  "trStatus": "pending",
  "transferDir": "pull",
  "reqClientId": "ClientX",
  "requestDate": "2000-06-08T22:00:00.0Z",
  "actClientId": "ClientY",
  "actionDate": "2000-06-13T22:00:00.0Z"
}
```

7.2.6. Transfer Query

Example contact transfer query response (Transfer Process Object):

```
{
  "@type": "transferProcess",
  "trStatus": "pending",
  "transferDir": "pull",
  "reqClientId": "ClientX",
  "requestDate": "2000-06-06T22:00:00.0Z",
  "actClientId": "ClientY",
  "actionDate": "2000-06-11T22:00:00.0Z"
}
```

7.2.7. Transfer Cancel / Approve

Transfer cancel and approve responses return the Transfer Process Object. The response structure is the same as the Transfer Query response above. The `trStatus` value reflects the outcome of the operation (e.g. `"clientCancelled"`, `"clientRejected"`, or `"clientApproved"`).

7.2.8. Transfer Reject

Example Contact Transfer Reject request

```
{
  "@type": "transferProcess",
  "reason": "Client rejected the transfer request."
}
```

The transfer reject response is the Transfer Process Object, similar to the transfer create and query responses.

7.3. Host

7.3.1. Create

Example host create request:

```
{
  "@type": "host",
  "hostName": "ns1.example.example",
  "dns": {
    "@type": "dnsData",
    "records": [
      {
        "@type": "dnsRecord",
        "name": "@",
        "type": "ns",
        "rdata": { "nsdname": "ns1.example.example." }
      },
      {
        "@type": "dnsRecord",
        "name": "ns1.example.example.",
        "type": "a",
        "rdata": { "address": "192.0.2.1" }
      },
      {
        "@type": "dnsRecord",
        "name": "ns1.example.example.",
        "type": "aaaa",
        "rdata": { "address": "2001:db8::1" }
      }
    ]
  }
}
```

Example host create response:

```
{
  "@type": "host",
  "hostName": "ns1.example.example",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "NS1EXAMPLE-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "1999-04-03T22:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "dns": {
    "@type": "dnsData",
    "records": [
      {
        "@type": "dnsRecord",
        "name": "@",
        "type": "ns",
        "rdata": { "nsdname": "ns1.example.example." }
      },
      {
        "@type": "dnsRecord",
        "name": "ns1.example.example.",
        "type": "a",
        "rdata": { "address": "192.0.2.1" }
      },
      {
        "@type": "dnsRecord",
        "name": "ns1.example.example.",
        "type": "aaaa",
        "rdata": { "address": "2001:db8::1" }
      }
    ]
  }
}
```

7.3.2. Read

Example host read response:

```
{
  "@type": "host",
  "hostName": "ns1.example.example",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "NS1EXAMPLE-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientY",
    "crDate": "1999-04-03T22:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ],
  "dns": {
    "@type": "dnsData",
    "records": [
      {
        "@type": "dnsRecord",
        "name": "@",
        "type": "ns",
        "rdata": { "nsdname": "ns1.example.example." }
      },
      {
        "@type": "dnsRecord",
        "name": "ns1.example.example.",
        "type": "a",
        "rdata": { "address": "192.0.2.1" }
      }
    ]
  }
}
```

7.3.3. Update

Example host update request:

```
{
  "@type": "host",
  "hostName": "ns1.example.example",
  "dns": {
    "@type": "dnsData",
    "records": [
      {
        "@type": "dnsRecord",
        "name": "@",
        "type": "ns",
        "rdata": { "nsdname": "ns1.example.example." }
      },
      {
        "@type": "dnsRecord",
        "name": "ns1.example.example.",
        "type": "a",
        "rdata": { "address": "198.51.100.1" }
      }
    ]
  }
}
```

7.3.4. Delete

The host delete operation takes the host name as the resource identifier. No request body is required. The server **SHOULD** reject the request if the host object is associated with any domain name objects.

7.3.5. Restore Request

Example host restore request (without inline report; object transitions to pendingRestore state):

```
{
  "@type": "restoreProcess"
}
```

Example host restore request response (Restore Process Object, server requires a report):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "pendingRestore",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDueDate": "2025-01-27T15:30:00.0Z"
}
```

Example host restore request with inline restore report (single-step; object restored immediately):

```
{
  "@type": "restoreProcess",
  "restoreReport": {
    "@type": "restoreReport",
    "preData": "Host ns1.example.example was registered on 2024-01-15 by
ClientX.",
    "postData": "Host ns1.example.example is being restored with the same
registration data.",
    "deleteTime": "2025-01-10T12:00:00.0Z",
    "restoreTime": "2025-01-20T15:30:00.0Z",
    "restoreReason": "Host deleted in error by client operator.",
    "statements": [
      "The information in this report is true to the best of my
knowledge.",
      "I have a valid reason for restoring this host object."
    ]
  }
}
```

Example host restore response with inline report (Restore Process Object, immediately restored):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "restored",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDate": "2025-01-20T15:30:00.0Z"
}
```

7.3.6. Restore Report

Example host restore report request:

```
{
  "@type": "restoreProcess",
  "restoreReport": {
    "@type": "restoreReport",
    "preData": "Host ns1.example.example was registered on 2024-01-15 by
ClientX.",
    "postData": "Host ns1.example.example is being restored with the same
registration data.",
    "deleteTime": "2025-01-10T12:00:00.0Z",
    "restoreTime": "2025-01-20T15:30:00.0Z",
    "restoreReason": "Host deleted in error by client operator.",
    "statements": [
      "The information in this report is true to the best of my
knowledge.",
      "I have a valid reason for restoring this host object."
    ]
  }
}
```

Example host restore report response (Restore Process Object):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "restored",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDate": "2025-01-22T09:15:00.0Z"
}
```

7.3.7. Restore Query

The Restore Query operation takes no request body (Parameters: None).

Example host restore query response (Restore Process Object, object in pendingRestore state):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "pendingRestore",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDueDate": "2025-01-27T15:30:00.0Z"
}
```

Example host restore query response (Restore Process Object, object restored):

```
{
  "@type": "restoreProcess",
  "restoreStatus": "restored",
  "requestDate": "2025-01-20T15:30:00.0Z",
  "reportDate": "2025-01-22T09:15:00.0Z"
}
```

7.4. Organisation

7.4.1. Create

Example organisation create request:

```
{
  "@type": "organisation",
  "id": "ORG-12345",
  "roles": { "registrar":
    {
      "@type": "organisationRole",
      "roleId": "1234"
    }
  },
  "parent": { "@type": "organisation", "id": "ORG-9999" },
  "contactInfo": {
    "@type": "Card",
    "version": "2.0",
    "kind": "org",
    "name": {
      "full": "Example Registrar Inc."
    },
    "addresses": {
      "addr": {
        "components": [
          { "kind": "name", "value": "Meander 501" },
          { "kind": "locality", "value": "Arnhem" },
          { "kind": "region", "value": "Gelderland" },
          { "kind": "postcode", "value": "6825MD" },
          { "kind": "country", "value": "Netherlands" }
        ],
        "countryCode": "NL"
      }
    },
    "emails": {
      "email": { "address": "registrar@example.example" }
    }
  },
  "contacts": [
    { "label": "admin", "object": { "@type": "contact", "id":
"CID-1001" } },
    { "label": "tech", "object": { "@type": "contact", "id":
"CID-1002" } }
  ]
}
```

Example organisation create response:

```
{
  "@type": "organisation",
  "id": "ORG-12345",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "ORG12345-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "2025-03-15T10:00:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "ok" }
  ]
}
```

```
    ],
    "roles": { "registrar":
      {
        "@type": "organisationRole",
        "status": ["ok"],
        "roleId": "1234"
      }
    },
    "parent": { "@type": "organisation", "id": "ORG-9999" },
    "contactInfo": {
      "@type": "Card",
      "version": "2.0",
      "kind": "org",
      "name": {
        "full": "Example Registrar Inc."
      },
      "addresses": {
        "addr": {
          "components": [
            { "kind": "name", "value": "Meander 501" },
            { "kind": "locality", "value": "Arnhem" },
            { "kind": "region", "value": "Gelderland" },
            { "kind": "postcode", "value": "6825MD" },
            { "kind": "country", "value": "Netherlands" }
          ],
          "countryCode": "NL"
        }
      },
      "emails": {
        "email": { "address": "registrar@example.example" }
      }
    },
    "contacts": [
      { "label": "admin", "object": { "@type": "contact", "id":
"CID-1001" } },
      { "label": "tech", "object": { "@type": "contact", "id":
"CID-1002" } }
    ],
    "users": [
      { "label": "admin", "object": { "@type": "user", "id": "UID-5001" } }
    ]
  }
}
```

7.4.2. Read

Example organisation read response:

```
{
  "@type": "organisation",
  "id": "ORG-12345",
  "provMetadata": {
    "@type": "provMetadata",
    "repositoryId": "ORG12345-REP",
    "spClientId": "ClientX",
    "crClientId": "ClientX",
    "crDate": "2025-03-15T10:00:00.00Z",
  }
}
```

```
    "upClientId": "ClientX",
    "upDate": "2025-06-01T08:30:00.0Z"
  },
  "status": [
    { "@type": "status", "label": "linked" }
  ],
  "roles": { "registrar":
    {
      "@type": "organisationRole",
      "status": ["ok"],
      "roleId": "1234"
    }
  },
  "parent": { "@type": "organisation", "id": "ORG-9999" },
  "contactInfo": {
    "@type": "Card",
    "version": "2.0",
    "kind": "org",
    "name": {
      "full": "Example Registrar Inc."
    }
  },
  "addresses": {
    "addr": {
      "components": [
        { "kind": "name", "value": "Meander 501" },
        { "kind": "locality", "value": "Arnhem" },
        { "kind": "region", "value": "Gelderland" },
        { "kind": "postcode", "value": "6825MD" },
        { "kind": "country", "value": "Netherlands" }
      ],
      "countryCode": "NL"
    }
  },
  "emails": {
    "email": { "address": "registrar@example.example" }
  },
  "contacts": [
    { "label": "admin", "object": { "@type": "contact", "id":
"CID-1001" } },
    { "label": "tech", "object": { "@type": "contact", "id":
"CID-1002" } }
  ],
  "users": [
    { "label": "admin", "object": { "@type": "user", "id": "UID-5001" } }
  ]
}
```

7.4.3. Update

Example organisation update request:

```
{
  "@type": "organisation",
  "roles": { "registrar":
    {
      "@type": "organisationRole",
      "status": ["clientLinkProhibited"],
      "roleId": "1234"
    }
  },
  "status": [
    { "@type": "status", "label": "clientLinkProhibited" }
  ],
  "contacts": [
    { "label": "admin", "object": { "@type": "contact", "id":
      "CID-2001" } },
    { "label": "tech", "object": { "@type": "contact", "id":
      "CID-2002" } }
  ]
}
```

7.4.4. Delete

The organisation delete operation takes the organisation identifier as the resource identifier. No request body is required. The server **MUST** reject the request if the organisation object is associated with any other objects.

7.4.5. Reference

Example organisation reference (used when referencing an organisation from another object):

```
{
  "@type": "organisation",
  "id": "ORG-12345"
}
```

7.5. User

7.5.1. Create

Example user create request:

```
{
  "@type": "user",
  "details": { "@type": "contact", "id": "USER-1234" },
  "status": ["active"]
}
```

Example user create response:

```
{
  "@type": "user",
  "userId": "UID-5001",
  "details": { "@type": "contact", "id": "USER-1234" },
  "status": ["active"]
}
```

7.5.2. Read

Example user read response:

```
{
  "@type": "user",
  "organisationId": { "@type": "organisation", "id": "ORG-12345" },
  "userId": "UID-5001",
  "details": { "@type": "contact", "id": "USER-1234" },
  "status": ["active"]
}
```

7.5.3. Update

Example user update request (suspend the user):

```
{
  "@type": "user",
  "status": ["suspended"]
}
```

7.5.4. Delete

The user delete operation takes the user identifier as the resource identifier in the context of the owning organisation. No request body is required.

7.5.5. Reference

Example user reference (used when referencing a user from an organisation object):

```
{
  "@type": "user",
  "id": "UID-5001"
}
```

8. IANA Considerations

TODO

9. Internationalization Considerations

TODO

10. Security Considerations

TODO

11. Acknowledgments

TODO

12. Change History

12.1. Version draft-wullink-rpp-json-02 to draft-ietf-rpp-json-00

- Added "Update Rules" section, describing update requests (Issue #54)
- Added schema and examples for Transfer approve/reject/cancel operations (Issue #28)
- Added Organisation and User Object JSON schemas and examples. (Issue #57)
- Added schema and examples for the Renew Process Object. (Issue #45)
- Added representation for embedding of process data in uniform interface operations (especially create). (Issue #60)
- Added JSContact as External Type Embedding (Issue #43).

12.2. Version 01 to 02

- Adjust rule 19 and all schemas to match it.

12.3. Version 00 to 01

- Updated all examples and schemas to be based on RPP Data Object and no longer on EPP XML schemas. (Issue #15)
- Updated labelled and dictionary aggregation rules (Issue #17)
- Added required "@type" property to all JSON Schema definitions. (Issue #20)
- Updated all example domain names to use the .example TLD. (Issue #26)

13. References

13.1. Normative References

[I-D.ietf-rpp-core] Wullink, M. and P. Kowalik, "RESTful Provisioning Protocol (RPP)", Work in Progress, Internet-Draft, draft-ietf-rpp-core-00, 6 July 2026, <<https://datatracker.ietf.org/doc/html/draft-ietf-rpp-core-00>>.

[I-D.ietf-rpp-data-objects] Kowalik, P. and M. Wullink, "RESTful Provisioning Protocol (RPP) Data Objects", Work in Progress, Internet-Draft, draft-ietf-rpp-data-objects-01, 3 July 2026, <<https://datatracker.ietf.org/doc/html/draft-ietf-rpp-data-objects-01>>.

- [ISO3166-1] International Organization for Standardization, "Codes for the representation of names of countries and their subdivisions - Part 1: Country code", ISO 3166-1:2020, 2020, <<https://www.iso.org/standard/72482.html>>.
- [ITU.E164.2005] International Telecommunication Union, "The international public telecommunication numbering plan", ITU-T Recommendation E.164, February 2005.
- [RFC1035] Mockapetris, P., "Domain names - implementation and specification", STD 13, RFC 1035, DOI 10.17487/RFC1035, November 1987, <<https://www.rfc-editor.org/info/rfc1035>>.
- [RFC1738] Berners-Lee, T., Masinter, L., and M. McCahill, "Uniform Resource Locators (URL)", RFC 1738, DOI 10.17487/RFC1738, December 1994, <<https://www.rfc-editor.org/info/rfc1738>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet: Timestamps", RFC 3339, DOI 10.17487/RFC3339, July 2002, <<https://www.rfc-editor.org/info/rfc3339>>.
- [RFC3915] Hollenbeck, S., "Domain Registry Grace Period Mapping for the Extensible Provisioning Protocol (EPP)", RFC 3915, DOI 10.17487/RFC3915, September 2004, <<https://www.rfc-editor.org/rfc/rfc3915>>.
- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", RFC 4648, DOI 10.17487/RFC4648, October 2006, <<https://www.rfc-editor.org/info/rfc4648>>.
- [RFC5730] Hollenbeck, S., "Extensible Provisioning Protocol (EPP)", STD 69, RFC 5730, DOI 10.17487/RFC5730, August 2009, <<https://www.rfc-editor.org/info/rfc5730>>.
- [RFC5732] Hollenbeck, S., "Extensible Provisioning Protocol (EPP) Host Mapping", STD 69, RFC 5732, DOI 10.17487/RFC5732, August 2009, <<https://www.rfc-editor.org/info/rfc5732>>.
- [RFC6902] Bryan, P., Ed. and M. Nottingham, Ed., "JavaScript Object Notation (JSON) Patch", RFC 6902, DOI 10.17487/RFC6902, April 2013, <<https://www.rfc-editor.org/info/rfc6902>>.
- [RFC8259] Bray, T., Ed., "The JavaScript Object Notation (JSON) Data Interchange Format", STD 90, RFC 8259, DOI 10.17487/RFC8259, December 2017, <<https://www.rfc-editor.org/info/rfc8259>>.
- [RFC8543] Zhou, L., Kong, N., Yao, J., Gould, J., and G. Zhou, "Extensible Provisioning Protocol (EPP) Organization Mapping", RFC 8543, DOI 10.17487/RFC8543, March 2019, <<https://www.rfc-editor.org/info/rfc8543>>.
- [RFC9553] Stepanek, R. and M. Loffredo, "JSContact: A JSON Representation of Contact Data", RFC 9553, DOI 10.17487/RFC9553, May 2024, <<https://www.rfc-editor.org/info/rfc9553>>.
- [RFC9982] Stepanek, R., "JSContact Version 2.0: A JSON Representation of Contact Data", RFC 9982, DOI 10.17487/RFC9982, May 2026, <<https://www.rfc-editor.org/info/rfc9982>>.

13.2. Informative References

[I-D.simmen-rpp-dns-data]

Simmen, C. and P. Kowalik, "DNS data representation for use in RESTful Provisioning Protocol (RPP)", Work in Progress, Internet-Draft, draft-simmen-rpp-dns-data-01, 20 October 2025, <<https://datatracker.ietf.org/doc/html/draft-simmen-rpp-dns-data-01>>.

[JSON-SCHEMA] JSON Schema, "JSON Schema: A Media Type for Describing JSON Documents", 2020, <<https://json-schema.org/draft/2020-12/json-schema-core>>.

[RFC3596] Thomson, S., Huitema, C., Ksinant, V., and M. Souissi, "DNS Extensions to Support IP Version 6", STD 88, RFC 3596, DOI 10.17487/RFC3596, October 2003, <<https://www.rfc-editor.org/info/rfc3596>>.

[RFC4034] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Resource Records for the DNS Security Extensions", RFC 4034, DOI 10.17487/RFC4034, March 2005, <<https://www.rfc-editor.org/info/rfc4034>>.

[RFC5910] Gould, J. and S. Hollenbeck, "Domain Name System (DNS) Security Extensions Mapping for the Extensible Provisioning Protocol (EPP)", RFC 5910, DOI 10.17487/RFC5910, May 2010, <<https://www.rfc-editor.org/info/rfc5910>>.

Authors' Addresses

Maarten Wullink

SIDN Labs

Email: maarten.wullink@sidn.nl

URI: <https://sidn.nl/>

Pawel Kowalik

DENIC

Email: pawel.kowalik@denic.de

URI: <https://denic.de/>