

Basic R tutorial

February 22, 2024

Contents

Problem 3: Learning Bayesian networks from protein data	1
Preparation to run the code	1
Loading data	1
Variables and observations	1
Visualisation of transformed data	1
Defining functions	2
Default parameters	3
Different parameters	4
Retraining the best BN	5
Render this .rmd into a pdf	6

Problem 3: Learning Bayesian networks from protein data

Preparation to run the code

Setting seed for reproducibility and loading packages.

```
set.seed(42)
library("GGally")
library("BiDAG")
library("igraph")
```

Loading data

```
data <- read.table("2005_sachs_2_cd3cd28icam2_log_std.csv", sep=";", header=TRUE)
```


Variables and observations

```
num_variables <- ncol(data)
num_observations <- nrow(data)
```

Visualisation of transformed data

TODO: must resize the plot

```
pair_plot <- ggpairs(data, progress=FALSE)
pair_plot
```



Defining functions

```
splitting_data <- function(data) {
  # Shuffling data
  indices <- 1:nrow(data)
  indices <- sample(length(indices))

  # Splitting data
  train_size <- ceiling(nrow(data)*0.8)
  train_indices <- indices[1:train_size]
  test_indices <- indices[(train_size+1):(length(indices))]

  # Checking if there is no overlap
  if(length(unique(c(train_indices, test_indices))) != length(c(train_indices, test_indices))) {
    print("Overlap!")
  }

  train_data <- data[row.names(data) %in% train_indices, ]
  test_data <- data[row.names(data) %in% test_indices, ]

  split_data <- list("train_data"=train_data, "test_data"=test_data)

  return(split_data)
}
```

```

training_BN <- function(data, bgepar) {
  library("BiDAG")
  init_score_par <- scoreparameters("bge", data$train_data, bgepar)
  learnt_BN <- iterativeMCMC(init_score_par, verbose=FALSE)
  return(learnt_BN)
}

testing_BN <- function(data, BN, bgepar) {
  library("BiDAG")
  test_score_par <- scoreparameters("bge", data$test_data, bgepar)
  test_score <- scoreagainstDAG(test_score_par, BN$DAG)
  return(mean(test_score))
}

plot_DAG <- function(BN) {
  library("igraph")
  g <- graph_from_adjacency_matrix(BN$DAG)
  plot(g)
}

get_number_of_edges <- function(BN) {
  library("igraph")
  return(length(E(graph_from_adjacency_matrix(BN$DAG))))
}

```

Default parameters


```

bgepar <- list(am=1, aw=NULL, edgepf=1)
split_data <- splitting_data(data)
learnt_BN <- training_BN(split_data, bgepar)

mean_test_score <- testing_BN(split_data, learnt_BN, bgepar)
print(paste0("Average BGe score on testing data: ", mean_test_score))

## [1] "Average BGe score on testing data: -12.7214725878423"
plot_DAG(learnt_BN)

```



Different parameters

```
library(parallel)
library(doParallel)
```

TODO: make pretty-printing of results

```
# Set the number of cores to use
num_cores <- detectCores()
```

```
# Register parallel backend
cl <- makeCluster(num_cores)
registerDoParallel(cl)
```

```
ams <- c(10−5, 10−3, 10−1, 10, 102)
```

```
res <- foreach(am = ams, .combine=c) %dopar% {
  set.seed(42)
  bgepar <- list(am=am, aw=NULL, edgepf=1)
  numbers_of_edges <- c()
  mean_test_scores <- c()
  for(i in 1:10) {
    RNGkind("L'Ecuyer-CMRG")
    split_data <- splitting_data(data)
    learnt_BN <- training_BN(split_data, bgepar)
    number_of_edges <- get_number_of_edges(learnt_BN)
```

```

    numbers_of_edges <- append(numbers_of_edges, number_of_edges)
    mean_test_score <- testing_BN(split_data, learnt_BN, bgepar)
    mean_test_scores <- append(mean_test_scores, mean_test_score)
  }
  return(c(am, mean(numbers_of_edges), mean(mean_test_scores)))
}

stopCluster(cl)

res_m <- t(matrix(data=res, nrow=5, ncol=3, byrow=TRUE))
rownames(res_m) <- c("Parameter am", "Average number of edges", "Average BGe score of the test data")
print(res_m)

##               [,1]      [,2]      [,3]      [,4]      [,5]
## Parameter am    0.00001  0.00100  0.10000  10.00000 100.00000
## Average number of edges  7.00000  7.00000  9.10000  13.40000 16.70000
## Average BGe score of the test data -12.73416 -12.73416 -12.70972 -12.80457 -13.58552

```

Retraining the best BN

The best BN (based on the highest BGe score) was the one with $\alpha_m = 10^{-1}$.

```


set.seed(42)
bgepar <- list(am=10^(-1), aw=NULL, edgepf=1)
split_data <- splitting_data(data)
learnt_BN <- training_BN(split_data, bgepar)

mean_test_score <- testing_BN(split_data, learnt_BN, bgepar)
print(paste0("Average BGe score on testing data: ", mean_test_score))

## [1] "Average BGe score on testing data: -12.7526167482605"

plot_DAG(learnt_BN)

```



Render this .rmd into a pdf

```
library(rmarkdown)
render("1/1.Rmd", pdf_document(TRUE), "1.pdf") # TRUE adds table of content
```