

1. Write SQL query that extracts the year, month, and day from the date attribute for the orders table. Display them as three separate attributes alongside the id attribute and the original date attribute (resulting in total of 5 attributes).

The screenshot shows the SQL Studio interface. The SQL editor contains the following query:

```
1 use mydb;
2
3
4 /*1. Write SQL query that extracts the year, month, and day from the date attribute for the orders table.
5 Display them as three separate attributes alongside the id attribute and the original date attribute (resulting in total of 5 attributes).
6 */
7
8 SELECT
9     id, date,
10     YEAR(date) AS year,
11     MONTH(date) AS month,
12     DAY(date) AS day
13 FROM
14     orders;
```

The Result Grid shows the following data:

id	date	year	month	day
10248	1996-07-04	1996	7	4
10249	1996-07-05	1996	7	5
10250	1996-07-08	1996	7	8
10251	1996-07-08	1996	7	8
10252	1996-07-09	1996	7	9
10253	1996-07-10	1996	7	10
10254	1996-07-11	1996	7	11
10255	1996-07-12	1996	7	12
10256	1996-07-15	1996	7	15
10257	1996-07-16	1996	7	16
10258	1996-07-17	1996	7	17
10259	1996-07-18	1996	7	18
10260	1996-07-19	1996	7	19
10261	1996-07-19	1996	7	19
10262	1996-07-22	1996	7	22
10263	1996-07-23	1996	7	23
10264	1996-07-24	1996	7	24
10265	1996-07-25	1996	7	25
10266	1996-07-26	1996	7	26
10267	1996-07-29	1996	7	29
10268	1996-07-30	1996	7	30

The Output pane shows the following message:

```
1 11:36:56 use mydb 0 row(s) affected
2 11:38:34 SELECT id, date, YEAR(date) AS year, MONTH(date) AS month, DAY(date) AS day FROM orders LIMIT 0, 1... 196 row(s) returned
```

2. Write SQL query that adds one day to the date attribute for the orders table. Display the id attribute, the original date attribute, and the result of the addition on the screen.

The screenshot shows the SQL Studio interface. The SQL editor contains the following query:

```
9     MONTH(date) AS month,
10     DAY(date) AS day
11 FROM
12     orders;
13
14
15 /*
16 2. Write SQL query that adds one day to the date attribute for the orders table. Display the id attribute,
17 the original date attribute, and the result of the addition on the screen.
18 */
19
20 SELECT
21     id, date,
22     DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one
23 FROM
24     orders;
```

The Result Grid shows the following data:

id	date	date_plus_one
10248	1996-07-04	1996-07-05
10249	1996-07-05	1996-07-06
10250	1996-07-08	1996-07-09
10251	1996-07-08	1996-07-09
10252	1996-07-09	1996-07-10
10253	1996-07-10	1996-07-11
10254	1996-07-11	1996-07-12
10255	1996-07-12	1996-07-13
10256	1996-07-15	1996-07-16
10257	1996-07-16	1996-07-17
10258	1996-07-17	1996-07-18
10259	1996-07-18	1996-07-19
10260	1996-07-19	1996-07-20
10261	1996-07-19	1996-07-20
10262	1996-07-22	1996-07-23
10263	1996-07-23	1996-07-24
10264	1996-07-24	1996-07-25
10265	1996-07-25	1996-07-26
10266	1996-07-26	1996-07-27
10267	1996-07-29	1996-07-30
10268	1996-07-30	1996-07-31

The Output pane shows the following messages:

```
1 11:36:56 use mydb 0 row(s) affected
2 11:38:34 SELECT id, date, YEAR(date) AS year, MONTH(date) AS month, DAY(date) AS day FROM orders LIMIT 0, 1... 196 row(s) returned
3 11:42:02 SELECT id, date, DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one FROM orders LIMIT 0, 1000 196 row(s) returned
```

A OneDrive notification is visible in the bottom right corner:

Увімкнення с резервного к Автоматично документи та щоб захистити доступ звідусі

Нагадати знову за:

1 тиждень

Почнімо!

3. Write a SQL query that displays the number of seconds since the epoch (timestamp value) for the date attribute in the orders table. To do this, find and apply the necessary function. Display the id attribute, the original date attribute, and the result of the function on the screen.

The screenshot shows the SQL Studio interface. The SQL editor contains the following query:

```

/*
3. Write a SQL query that displays the number of seconds since the epoch (timestamp value) for the date attribute in the orders table.
To do this, find and apply the necessary function.
Display the id attribute, the original date attribute, and the result of the function on the screen.
*/
SELECT
  id, date,
  UNIX_TIMESTAMP(date) AS timestamp_value
FROM
  orders;

```

The Result Grid shows the following data:

id	date	timestamp_value
10248	1996-07-04	836456400.000000
10249	1996-07-05	836542800.000000
10250	1996-07-08	836802000.000000
10251	1996-07-08	836802000.000000
10252	1996-07-09	836888400.000000
10253	1996-07-10	836974800.000000
10254	1996-07-11	837061200.000000
10255	1996-07-12	837147600.000000
10256	1996-07-15	837406800.000000
10257	1996-07-16	837493200.000000
10258	1996-07-17	837579600.000000
10259	1996-07-18	837666000.000000
10260	1996-07-19	837752400.000000
10261	1996-07-19	837752400.000000
10262	1996-07-22	838011600.000000
10263	1996-07-23	838098000.000000
10264	1996-07-24	838184400.000000
10265	1996-07-25	838270800.000000
10266	1996-07-26	838357200.000000
10267	1996-07-29	838616400.000000
10268	1996-07-30	838702800.000000

The Output pane shows the following actions:

#	Time	Action	Message
1	11:36:56	use mydb	0 row(s) affected
2	11:38:34	SELECT id, date, YEAR(date) AS year, MONTH(date) AS month, DAY(date) AS day FROM orders LIMIT 0, 1...	196 row(s) returned
3	11:42:02	SELECT id, date, DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one FROM orders LIMIT 0, 1000	196 row(s) returned
4	11:45:20	SELECT id, date, DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one FROM orders LIMIT 0, 1000	196 row(s) returned
5	11:46:21	SELECT id, date, UNIX_TIMESTAMP(date) AS timestamp_value FROM orders LIMIT 0, 1000	196 row(s) returned

4. Write a SQL query that counts how many rows the order table contains with date attribute falling between 1996-07-10 00:00:00 and 1996-10-08 00:00:00.

The screenshot shows the SQL Studio interface. The SQL editor contains the following query:

```

/*
4. Write a SQL query that counts how many rows
the order table contains with date attribute falling between 1996-07-10 00:00:00 and 1996-10-08 00:00:00.
*/
SELECT COUNT(*) AS orders_count
FROM orders
WHERE date BETWEEN '1996-07-10 00:00:00' AND '1996-10-08 00:00:00';

```

The Result Grid shows the following data:

orders_count
71

The Output pane shows the following actions:

#	Time	Action	Message
1	11:36:56	use mydb	0 row(s) affected
2	11:38:34	SELECT id, date, YEAR(date) AS year, MONTH(date) AS month, DAY(date) AS day FROM orders LIMIT 0, 1...	196 row(s) returned
3	11:42:02	SELECT id, date, DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one FROM orders LIMIT 0, 1000	196 row(s) returned
4	11:45:20	SELECT id, date, DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one FROM orders LIMIT 0, 1000	196 row(s) returned
5	11:46:21	SELECT id, date, UNIX_TIMESTAMP(date) AS timestamp_value FROM orders LIMIT 0, 1000	196 row(s) returned
6	11:49:43	SELECT COUNT(*) AS orders_count FROM orders WHERE date BETWEEN '1996-07-10 00:00:00' AND '1996-10-08 00:00:00'	1 row(s) returned

5. Write a SQL query that displays the id attribute , the date attribute and JSON object {"id": <row id attribute>, "date": <row date attribute>} from the orders table. Use a function to create the JSON object.

SQL File 1* x

Limit to 1000 rows

```

33 FROM
34     orders;
35
36 /*
37 4. Write a SQL query that counts how many rows
38 the order table contains with date attribute falling between 1996-07-10 00:00:00 and 1996-10-08 00:00:00.
39 */
40 • SELECT COUNT(*) AS orders_count
41 FROM orders
42 WHERE date BETWEEN '1996-07-10 00:00:00' AND '1996-10-08 00:00:00';
43
44 /*
45 5. Write a SQL query that displays the id attribute ,
46 the date attribute and JSON object {"id": <row id attribute>, "date": <row date attribute>}
47 from the orders table. Use a function to create the JSON object.
48 */
49 • SELECT
50     id, date,
51     JSON_OBJECT('id', id, 'date', date) AS json_data
52 FROM
53     orders;
54

```

Result Grid

	id	date	json_data
▶	10248	1996-07-04	{"id": 10248, "date": "1996-07-04"}
	10249	1996-07-05	{"id": 10249, "date": "1996-07-05"}
	10250	1996-07-08	{"id": 10250, "date": "1996-07-08"}
	10251	1996-07-08	{"id": 10251, "date": "1996-07-08"}
	10252	1996-07-09	{"id": 10252, "date": "1996-07-09"}
	10253	1996-07-10	{"id": 10253, "date": "1996-07-10"}
	10254	1996-07-11	{"id": 10254, "date": "1996-07-11"}
	10255	1996-07-12	{"id": 10255, "date": "1996-07-12"}
	10256	1996-07-15	{"id": 10256, "date": "1996-07-15"}
	10257	1996-07-16	{"id": 10257, "date": "1996-07-16"}
	10258	1996-07-17	{"id": 10258, "date": "1996-07-17"}

Result 6 x

Output

Action Output

#	Time	Action	Message
✓ 1	11:36:56	use mydb	0 row(s) affected
✓ 2	11:38:34	SELECT id, date, YEAR(date) AS year, MONTH(date) AS month, DAY(date) AS day FROM orders LIMIT 0, 1...	196 row(s) returned
✓ 3	11:42:02	SELECT id, date, DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one FROM orders LIMIT 0, 1000	196 row(s) returned
✓ 4	11:45:20	SELECT id, date, DATE_ADD(date, INTERVAL 1 DAY) AS date_plus_one FROM orders LIMIT 0, 1000	196 row(s) returned
✓ 5	11:46:21	SELECT id, date, UNIX_TIMESTAMP(date) AS timestamp_value FROM orders LIMIT 0, 1000	196 row(s) returned
✓ 6	11:49:43	SELECT COUNT(*) AS orders_count FROM orders WHERE date BETWEEN '1996-07-10 00:00:00' AND '1996-10-08 00:00:00'	1 row(s) returned
✓ 7	11:53:44	SELECT id, date, JSON_OBJECT(id, id, 'date', date) AS json_data FROM orders LIMIT 0, 1000	196 row(s) returned

Read Only

Conti