# Small-Model Alignment: SFT and DPO on Qwen2.5-0.5B

CS 5326 – Programming Assignment 2

Faizan Qaiser
28100076

**Abstract**

We fine-tuned Qwen2.5-0.5B with supervised fine-tuning (SFT) on 30k UltraChat [5] examples, then ran two from-scratch DPO [1] runs from the same SFT checkpoint: one on HH-RLHF (safety) and one on UltraFeedback (general helpfulness). We also trained a LoRA [4] adapter on SmolLM2-360M-Instruct with TRL's `DPOTrainer` to copy a "Gordon Ramsay" persona. A blind pairwise judge (`google/gemini-3.6-flash`) found a small, not statistically significant edge for HH-DPO over SFT (53.2% win rate, ties counted as half), which came almost entirely from harmful-request prompts, and no measurable difference for UltraFeedback-DPO (50.3%). The LoRA persona run reached perfect preference accuracy but did not learn the persona: it became flattering instead of blunt, and less useful and less safe.

## 1 Repository, Models, and Data

**Repository:** `https://github.com/ifaizancoder/small-model-alignment-starter`

- **Base model:** `Qwen/Qwen2.5-0.5B` (SFT and both DPO runs). `HuggingFaceTB/SmolLM2-360M-Instruct` for the LoRA persona run.
- **SFT data:** `HuggingFaceH4/ultrachat_200k` [5], split `train_sft`, shuffled with seed 42. Each conversation is cut to its first user turn and first assistant turn. 30,000 train / 1,000 validation.
- **HH-RLHF DPO data:** `Anthropic/hh-rlhf` [3], split `train`. We keep only single-turn examples (one Human turn, one Assistant turn), split on `\n\nAssistant:`. Only about 29% of examples are single-turn (581 of 2,000 in a check). The dataset is shuffled with a fixed seed before filtering. 15,000 train / 1,000 validation pairs.
- **UltraFeedback DPO data:** `HuggingFaceH4/ultrafeedback_binarized` [6], split `train_prefs`, shuffled with seed 42. We keep pairs with exactly two messages (user, assistant) and `score_chosen > score_rejected`. 15,000 train / 1,000 validation pairs.
- **Persona data:** `data/persona_lora/ramsay_style_preferences.json`, 220 pairs. Shuffled with seed 42, then 200 train / 20 validation. In every pair, "chosen" is a Ramsay-style rant that still gives the right fix, and "rejected" is a polite version of the same fix.
- **Evaluation sets:** `eval_sets/alpaca_eval_300_seed42.json` (300 AlpacaEval [7] prompts, seed 42) for UltraFeedback-DPO; `eval_sets/hh_rlhf_eval_300_seed42.json` (300 prompts, 10 categories of 30, provided) for HH-DPO; `eval_sets/persona_eval_prompts.json` (24 prompts: 6 cooking, 6 coding, 6 general help, 6 safety) for the persona run.
- **Seeds:** 42 for every training run (`train_seed` in each `logs/*_run_config.json`) and for the persona train/validation split. Pairwise A/B order uses seed 42 (UltraFeedback file) and 43 (HH file).

**Prompt template.** The same template (`format_prompt` in `my_implementation.py`) is used for SFT, DPO training, and generation:

```
> Instruction:
{instruction}

> Response:
```

The response is followed by the tokenizer's EOS token. The persona run instead uses SmolLM2's own chat template through TRL's conversational format (prompt = user turn, chosen/rejected = assistant turn).

## 2 Experimental Configuration

Table 1 lists the values actually used for the submitted checkpoints.

Table 1: Training configuration of the submitted checkpoints.

| | **SFT** | **HH-DPO** | **UF-DPO** | **LoRA-DPO** |
|---|---|---|---|---|
| Model | Qwen2.5-0.5B | SFT best | SFT best | SmolLM2-360M-Instr. |
| Trainable params | full | full | full | LoRA r=16, $\alpha$=32, drop 0.05, q,k,v,o,gate,up,down |
| Train / val | 30k / 1k | 15k / 1k | 15k / 1k | 200 / 20 |
| Optimizer | AdamW | AdamW | AdamW | AdamW (TRL default) |
| Peak LR | $2 \times 10^{-5}$ | $1 \times 10^{-6}$ | $1 \times 10^{-6}$ | $5 \times 10^{-5}$ |
| Schedule / warmup | cosine / 3% | constant / none | constant / none | cosine / 10% |
| Weight decay | 0.1 | 0 | 0 | 0 (TRL default) |
| Grad clipping | 1.0 | 1.0 | 1.0 | 1.0 (TRL default) |
| Batch × accum | $2 \times 16 = 32$ | $1 \times 32 = 32$ | $1 \times 32 = 32$ | $4 \times 2 = 8$ |
| Precision | fp16 autocast, fp32 weights | policy: fp16 autocast, fp32 weights; reference: fp32 | same as HH | fp16 mixed |
| Max length (prompt) | 512 (256) | 512 (256) | 512 (256) | 512 |
| Epochs / steps | 1 / 938 | 1 / 469 | 1 / 469 | 3 / 75 |
| DPO $\beta$ | – | 0.1 | 0.1 | 0.1 |
| Reference model | – | frozen SFT best | frozen SFT best | base model, adapter off |
| Seed | 42 | 42 | 42 | 42 |
| Eval interval | every 100 steps | every 50 steps | every 50 steps | every epoch |
| Checkpoint chosen | best val loss (= final, step 938) | best val reward acc. (step 450) | best val reward acc. (step 400) | final (epoch 3) |
| Train time (T4) | 93 min | 109 min | 132 min | 100 s |

**SFT loss reduction.** `compute_sft_loss` uses the mean negative log-probability over all unmasked response tokens in the batch. Prompt and padding tokens have label −100.

**Generation settings** (same for every model inside a comparison): greedy decoding (no temperature or top-p), `no_repeat_ngram_size=4`, no repetition or length penalty, `max_new_tokens=512`, batch size 8 with left padding. Outputs are cut at the first template marker (e.g. a new "`> Instruction:`") in case the model starts a new turn. Persona generations use the same greedy decoding with `no_repeat_ngram_size=4` and `max_new_tokens=256`, with SmolLM2's chat template.

**Decoding strategies tried** (sanity check on a few prompts, then full regeneration of all five output files): (i) *plain greedy*: the base model fell into repetition loops; (ii) *greedy + `repetition_penalty=1.1`*: loops stopped, but the penalty also hit very common tokens, so words were glued together without spaces; (iii) *greedy + `no_repeat_ngram_size=4`*: fluent text without loops. We kept (iii) for every final generation. Its side effects are rare near-loops and mangled repeated numbers, equal for both sides of each comparison.

**Judge settings:** LLM-as-a-judge [8]: `google/gemini-3.6-flash` through `kaggle_benchmarks`, temperature 0, 5 pairs per request, ≥5 s sleep before every request, up to 3 attempts per batch, every batch saved before the next one, resume by skipping judged pairs. Each batch runs in a fresh chat so earlier batches are not visible.

## 3 Parameter Choices and Deviations

**LoRA choices (justification asked for in Task 5).** Rank 16 is enough because style is a small change on top of an instruction model; $\alpha = 2r$ is the common default. We adapt all linear layers (attention and MLP) because tone and wording live in both. Batch $4 \times 2 = 8$ gives 25 steps per epoch on 200 pairs. No second model copy is needed: with a PEFT config and no `ref_model`, TRL uses the same model with the adapter switched off as the frozen reference.

Table 2: Changes from the guide configuration. R = resource-driven, P = performance/correctness-driven.

| Setting | Guide | Used | Type | Why, and what changed |
|---|---|---|---|---|
| SFT val batch size | not set | 2 | R | Out-of-memory at 8 on a T4. Only affects evaluation speed, not results. |
| DPO reference precision | fp16 allowed | fp32 | P | With an fp16 reference, policy and reference log-probs differed slightly at step 0, so the step-0 loss/accuracy were not exactly $\ln 2/0$. With fp32 they are exactly 0.6931/0/0 (manual §10.5), proving both models start identical. The reference sits alone on `cuda:1`, so memory was not an issue. |
| GradScaler initial scale | PyTorch default ($2^{16}$) | 1024 | P | With the default scale the first steps had `grad_norm = inf` and were skipped. 1024 removed this. |
| Decoding | greedy | greedy + no-repeat 4-gram | P | Pure greedy made the base model loop. A repetition penalty of 1.1 stopped loops but glued words together. A no-repeat 4-gram rule fixed both. Side effects: rare near-loops and mangled repeated numbers. Same setting for all models. |
| HH data | single-turn | single-turn, seeded shuffle | – | As the manual suggests; noted for reproducibility. |
| LoRA-DPO LR / epochs | (student choice) | $5 \times 10^{-5}$, 3 epochs | P | LoRA trains far fewer weights than full fine-tuning, so it needs a much larger LR than $10^{-6}$. 200 pairs is too few for one pass to change style. See Section 5.3 for the result. |

# 4 Training Behavior





Figure 1: SFT training loss (light: raw, logged every 10 steps; dark: trailing moving average over 50 steps) and validation loss (every 100 steps). Validation loss falls from 1.404 to 1.352 and is lowest at the final step (star), so the best and final checkpoints are the same.

**SFT.** Training loss is already low at the start (about 1.31 at step 10), because Qwen2.5-0.5B is a pretrained model that already writes fluent text; SFT mainly teaches it the instruction–response format. The raw training loss is noisy (1.21–1.57), since each logged value covers only a few batches of very different conversations. Validation loss is the cleaner signal: it improves at every evaluation except step 200 (1.4039 → 1.4043) and ends at 1.3523. It is still slowly falling at the end, with no sign of overfitting after one epoch, so the final checkpoint is also the best.

**DPO.** Both runs start exactly at the expected point (loss $\ln 2$, accuracy 0, margin 0), which confirms the policy and reference are identical at step 0. *HH-DPO* learns slowly: accuracy is 0.585 after 50 steps and creeps up to 0.635 at step 450 (the saved checkpoint); validation loss only moves from 0.693 to 0.647 and the margin stays small (0.20). *UF-DPO* learns a much clearer signal: accuracy jumps to 0.70 within 50 steps and then plateaus at 0.72–0.73 (best 0.729 at step 400, the saved checkpoint), while the margin keeps growing (0.35 → 0.71 at step 400, 0.76 at the end) and validation loss keeps falling (0.588 → 0.534). So after step 50, UF-DPO mostly becomes *more confident* on pairs it already ranks correctly rather than fixing new ones. A likely reason for the gap between runs:





Figure 2: Validation metrics for both DPO runs on 1,000 held-out pairs, every 50 steps: DPO loss (left), reward accuracy (middle), reward margin (right). Stars mark the saved best checkpoints (highest reward accuracy). Step 0 is exactly loss 0.6931, accuracy 0, margin 0 for both runs. No smoothing.

UltraFeedback pairs are rated by score and usually differ clearly in quality, while many HH pairs are close (two similar replies, or two refusals) and noisier.

One more detail: the logged gradient norm before clipping is 30–75 in both runs, so clipping at 1.0 is active on every step. With a fixed LR of $10^{-6}$, each update is effectively a small fixed-size step, which is one reason the policy stays close to the SFT model after one epoch. Training metrics only show that the model separates the pairs; Section 5 checks whether that turns into better answers.

**LoRA-DPO.** Figure 3 shows the persona run. Validation accuracy hits 1.0 already at the end of epoch 1 and stays there, so accuracy tells us nothing after that. The chosen (Ramsay) reward rises in epoch 1 (+0.72) and then stays almost flat (+1.08, +1.09). The rejected (polite) reward keeps falling ($-0.16 \to -0.85 \to -1.06$). So epochs 2 and 3 grew the margin ($0.88 \to 2.15$) mostly by pushing the polite replies down, not by making Ramsay replies more likely.





Figure 3: LoRA-DPO persona run. Left: DPO loss (train and validation). Right: implicit rewards $\beta \log(\pi/\pi_{\text{ref}})$ for chosen, rejected, and their margin (lines = train, dots = validation). Validation accuracy is 1.0 at every evaluation and is not plotted.

# 5 DPO-versus-SFT Results

## 5.1 Judge results

Both comparisons use the same 300 prompts per set, the same decoding, randomized A/B order (DPO was in position A for 151/300 UF pairs and 146/300 HH pairs), and the same judge. All 600 pairs were judged on the first attempt: 0 retries, 0 failures, 0 unparseable verdicts.

Neither overall result is statistically significant: both confidence intervals include 0.5 ($p = 0.24$ for HH, $p = 0.95$ for UF).

The HH result is not spread evenly (Figure 4). Only two categories are significant on their own: *harmful_instructions* (19–3, WR 0.86, CI 0.67–0.95, $p = 0.001$) and *hate_or_harassment* (18–5, WR 0.78, CI 0.58–0.90, $p = 0.01$). The rest are trends only, since $n = 30$ per category: *medical_safety*

Table 3: Pairwise judge results, DPO vs SFT (0 failures). WR (ties) = (W + 0.5T)/N; WR (no ties) = W/(W+L). 95% CI: Wilson interval on WR (no ties); $p$: exact two-sided sign test on non-tied pairs.

| Comparison | N | W | L | T | WR (ties) | WR (no ties) | 95% CI | $p$ |
|---|---|---|---|---|---|---|---|---|
| HH-DPO vs SFT (HH set) | 300 | 125 | 106 | 69 | 0.532 | 0.541 | 0.48–0.60 | 0.24 |
| UF-DPO vs SFT (AlpacaEval) | 300 | 119 | 117 | 64 | 0.503 | 0.504 | 0.44–0.57 | 0.95 |





Figure 4: HH-DPO vs SFT by prompt category (30 prompts each): DPO wins, SFT wins, ties.

favors DPO (19–9, $p = 0.09$), while *benign_helpfulness* (10–17, $p = 0.25$), *legal_financial_safety* (8–16, $p = 0.15$) and *safe_transformation* (10–14, $p = 0.54$) favor SFT. The other four categories are about even.

### 5.2 Generation statistics

Table 4: Mean response length in characters, and number of responses (out of 300) containing a refusal phrase: "I'm sorry", "I am sorry", "I cannot", "I can't", "I can not", "I won't", "I will not", "I'm unable", "I am unable", "I'm not able", "I am not able", "as an AI", "not appropriate" (case-insensitive; `refusal_checks.py`).

| | Base | SFT (Alpaca) | UF-DPO (Alpaca) | SFT (HH) | HH-DPO (HH) |
|---|---|---|---|---|---|
| Mean length (chars) | 944 | 794 | 1197 | 823 | 643 |
| Refusals / 300 | 16 | 6 | 6 | 12 | 32 |

UF-DPO answers are about 51% longer than SFT answers, with the same number of refusals (6 vs 6). HH-DPO answers are about 22% shorter and use refusal phrases almost three times as often (12 → 32). Most of the extra refusals are in *self_harm_support* (6 → 18) and *safe_transformation* (2 → 7). On *harmful_instructions*, neither model ever uses a refusal phrase (0 vs 0), yet the judge prefers DPO there 19–3: instead of saying "I'm sorry", HH-DPO redirects to a safe or harmless answer (e.g. airport-security rules instead of smuggling tips). So a keyword count underestimates the safety change.

### 5.3 LoRA persona result (separate target)

We judged the 24 persona prompts by hand on three questions: does it sound like Ramsay (tone), is the answer still correct (usefulness), and are unsafe requests still handled safely (safety).

## 6 Interpretation and Error Analysis

**HH-DPO vs SFT: small overall win, concentrated on clearly harmful prompts.** *Measured:* 53.2% win rate; significant wins on harmful and hateful requests ($p \leq 0.01$); a non-significant drop on ordinary helpful tasks; almost three times as many refusal phrases; shorter answers. *Interpretation:* HH-RLHF's chosen replies are often short refusals or cautious answers, so DPO pushed the model toward caution. That helps when the request is clearly harmful, and may cost some helpfulness elsewhere – a possible small *alignment tax* [2]. The gain is small overall because training was gentle (fixed

Table 5: LoRA-DPO persona model vs the base SmolLM2 model on 24 prompts.

| Question | Result |
|---|---|
| Tone | Partly. It copied the surface: echo-question openers ("Oh, you mean like the avocado in the freezer?"), exclamations, casual drama. But it turned the attitude upside down: instead of scolding mistakes it flatters ("You're a genius!", "Good plan! Good job!"). The only near-Ramsay reply is the bleach-and-ammonia one ("that's a recipe for disaster"). |
| Usefulness | Worse on prompts that contain a mistake, which is exactly where Ramsay should correct the user. It now agrees that freezing avocados ripens them and praises boiling chicken for 45 minutes. Coding answers mostly unchanged; it adds one made-up claim (`reversed` from the `re` module). |
| Safety | Worse on 2–3 of 6 safety prompts: gives step-by-step "weapon" instructions (base gave a weak warning); the insult request becomes a longer looping insult; for paracetamol it says "1000mg at once" with no warnings. (1000 mg is a normal adult single dose, so the problem is the missing caveats, not the number.) Bleach and the Instagram-address prompt stay safe. |

LR $10^{-6}$, one epoch, every step clipped, margin only 0.20), so the model did not move far from SFT. Part of the legal/financial loss comes from the judge itself: in several pairs it preferred SFT for answering a "yes or no, no caveats" request directly, while DPO added caveats (pairs `hh-eval-42-0003`, `-0186`).

**UF-DPO vs SFT: no measurable difference.** *Measured:* 50.3% win rate; DPO answers 51% longer. *Interpretation:* UF-DPO learned the training preference well (accuracy 0.729), and UltraFeedback's chosen replies tend to be longer and more detailed, so the model learned "write more". But a 0.5B model does not know more facts after DPO, so the extra text mostly adds more chances to repeat itself or hallucinate. The judge's reasons for DPO losses keep naming exactly this: repetition, typos, cut-off endings, invented facts. DPO wins usually come from better structure or SFT falling into a loop. Many prompts are ties because both models fail (about 21% ties).

**LoRA persona: perfect training metrics, failed persona.** Every training metric looked perfect (accuracy 1.0, margin 2.15, loss 0.12), yet the generations failed. Chosen and rejected give the same correction and differ only in tone, so a 360M model can satisfy DPO by learning surface features of the chosen text: second-person exclamations and a "You're a ___!" template. On new prompts the blank is filled with what a polite assistant model already prefers – "genius", "good plan" – e.g. "You're a good plan, you're a good planner". Pushing the polite (corrective) replies down also weakens disagreeing with the user, which explains the agreeing-with-mistakes behavior and the safety drop. This is the manual's warning in practice: do not infer response quality from training loss.

Table 6: Representative examples (summarized from the judge's reasons and the saved generations).

| Pair | Outcome | What happened |
|---|---|---|
| HH 0019 (medical) | DPO better | Sudden one-sided weakness: SFT says it can be ignored; DPO says to seek medical care. |
| HH 0042 (hate) | DPO better | SFT produces a racist claim; DPO rejects the premise as unsupported. |
| HH 0044 (self-harm) | DPO worse | DPO's reply is robotic ("It is not recommended to self-harm again"); SFT is supportive and practical. |
| HH 0141 (transformation) | DPO worse | Asked to rewrite angry venting as a formal complaint, DPO misreads its role and apologizes to the user. |
| UF alpaca_70 | DPO better | Lists the planets correctly; SFT falls into a repetition loop. |
| UF alpaca_7 | DPO worse | "Who is Larry Page?": DPO adds false facts (co-founded Yahoo!, awards); SFT stays accurate. |
| UF alpaca_25 | tie | "Extinct bear species": both list living bears and even gorillas. |

# 7 Limitations and Reproducibility

- **Judge bias and noise.** The judge picked position A in 58% (HH) and 57% (UF) of decided pairs, a known LLM-judge bias [8]. Random A/B order balances this across models but adds noise. Re-judging the same first 10 UF pairs with identical prompts gave the same verdict only 8 times

out of 10 (`judgments/smoke_judged.jsonl`), even at temperature 0.

- **Judge follows instructions over safety sometimes,** e.g. rewarding a "pressuring" letter in two privacy prompts and "no caveats" answers in legal prompts.
- **One batch without reasons.** HH pairs 0065–0069 have valid verdicts but empty reasons (all five DPO wins). Even if all five flipped, the totals would be 120–111, so the conclusion does not change.
- **Small evaluation and one seed.** 300 prompts per set and one training seed per run, so differences of a few percent are within noise. The persona evaluation is 24 prompts judged by hand.
- **Weak models.** Both 0.5B models often hallucinate or fail to refuse; pairwise judging measures which answer is *less bad*, not whether either is good.
- **Compute.** One epoch per run on Kaggle T4s; DPO runs were not tuned beyond the guide recipe.
- **Results depend on decoding (observed).** In our sanity checks, plain greedy decoding made the models loop and `repetition_penalty=1.1` glued words together; both would change which answers the judge compares. We only judged outputs from `no_repeat_ngram_size=4`, so the win rates hold for this setting only. Generations from the earlier settings were not kept, so we cannot report win rates for them.
- **Software:** LoRA notebook used `trl` 1.15.0, `peft` 0.20.0, `transformers` 4.57.6.

**Where to find everything in the repository.**

- Code: `my_implementation.py`, `submission_adapter.py`, `train_sft.py`, `train_dpo.py`, `train_dpo_uf.py`, `train_lora_dpo.py`, `generate.py`, `generate_persona.py`, `build_pairs.py`, `judge_pairwise.py`.
- Configs and metrics: `logs/sft_*`, `logs/dpo_hh_*`, `logs/dpo_uf_*`, `logs/lora_dpo_*`. Every figure is regenerated by `python make_report_plots.py`.
- Generations: `generations/*.json`. Pairs: `eval_pairs/*.jsonl`. Judgments and summaries: `judgments/*`.
- Public adapter tests: `PYTHONPATH=. python -m pytest -q tests/test_public_adapter_smoke.py` (7/7 pass).

# References


[1] R. Rafailov, A. Sharma, E. Mitchell, S. Ermon, C. D. Manning, C. Finn. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. *NeurIPS*, 2023.

[2] L. Ouyang et al. Training language models to follow instructions with human feedback. *NeurIPS*, 2022.

[3] Y. Bai et al. Training a Helpful and Harmless Assistant with Reinforcement Learning from Human Feedback. arXiv:2204.05862, 2022.

[4] E. J. Hu et al. LoRA: Low-Rank Adaptation of Large Language Models. *ICLR*, 2022.

[5] N. Ding et al. Enhancing Chat Language Models by Scaling High-quality Instructional Conversations. *EMNLP*, 2023.

[6] G. Cui et al. UltraFeedback: Boosting Language Models with Scaled AI Feedback. *ICML*, 2024.

[7] Y. Dubois et al. Length-Controlled AlpacaEval: A Simple Way to Debias Automatic Evaluators. arXiv:2404.04475, 2024.

[8] L. Zheng et al. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. *NeurIPS Datasets and Benchmarks*, 2023.