

# Large Scale Distributed Deep Networks

Yifu Huang

School of Computer Science, Fudan University  
huangyifu@fudan.edu.cn

COMP630030 Data Intensive Computing Report, 2013

# Outline

- 1 Motivation
- 2 Software Framework: DistBelief
- 3 Distributed Algorithm
  - Downpour SGD
  - Sandblaster L-BFGS
- 4 Experiments
- 5 Discussion

# Motivation

- Why I choose this paper [1]?
  - Google + Stanford
  - Jeffrey Dean + Andrew Y. Ng
- Why we need large scale distributed deep networks?
  - Large model can dramatically improve performance
    - Training examples + model parameters
  - Exist methods have limitations
    - GPU, MapReduce, GraphLab
- What can we learn from this paper?
  - Best parallelism design ideas for deep networks up to now
    - Model parallelism + data parallelism

# Motivation


- Why I choose this paper [1]?
  - Google + Stanford
  - Jeffrey Dean + Andrew Y. Ng
- Why we need large scale distributed deep networks?
  - Large model can dramatically improve performance
    - Training examples + model parameters
  - Exist methods have limitations
    - GPU, MapReduce, GraphLab
- What can we learn from this paper?
  - Best parallelism design ideas for deep networks up to now
    - Model parallelism + data parallelism

# Motivation

- Why I choose this paper [1]?
  - Google + Stanford
  - Jeffrey Dean + Andrew Y. Ng
- Why we need large scale distributed deep networks?
  - Large model can dramatically improve performance
    - Training examples + model parameters
  - Exist methods have limitations
    - GPU, MapReduce, GraphLab
- What can we learn from this paper?
  - Best parallelism design ideas for deep networks up to now
    - Model parallelism + data parallelism

# Preliminaries

- Neural Networks [6]




- Deep Networks [7]

- Multiple hidden layers
- This will allow us to compute much more complex features of the input

# Preliminaries

- Neural Networks [6]



- Deep Networks [7]

- Multiple hidden layers
- This will allow us to compute much more complex features of the input

# Software Framework: DistBelief

- Model parallelism
  - “Inside” parallelism
  - Multi-thread + message passing -> large scale
- User defines
  - Computation in node, message upward/downward
- Framework manages
  - Synchronization, data transfer
- Performance depends on
  - Connectivity structure, computational needs



# Software Framework: DistBelief

- Model parallelism
  - “Inside” parallelism
  - Multi-thread + message passing -> large scale
- User defines
  - Computation in node, message upward/downward
- Framework manages
  - Synchronization, data transfer
- Performance depends on
  - Connectivity structure, computational needs

# Software Framework: DistBelief


- Model parallelism
  - “Inside” parallelism
  - Multi-thread + message passing -> large scale
- User defines
  - Computation in node, message upward/downward
- Framework manages
  - Synchronization, data transfer
- Performance depends on
  - Connectivity structure, computational needs

# Software Framework: DistBelief

- Model parallelism
  - “Inside” parallelism
  - Multi-thread + message passing -> large scale
- User defines
  - Computation in node, message upward/downward
- Framework manages
  - Synchronization, data transfer
- Performance depends on
  - Connectivity structure, computational needs

# Software Framework: DistBelief (cont.)

- An example of model parallelism in DistBelief



# Distributed Algorithm

- Data parallelism
  - “Outside” parallelism
  - Multiple model instances optimize a single objective -> high speed
- A centralized sharded parameter server
  - Different model replicas retrieve/update their own parameters
- Load balance, robust
  - Tolerate variance in the processing speed of different model replicas
  - The wholesale failure may be taken offline or restart at random

# Distributed Algorithm

- Data parallelism
  - “Outside” parallelism
  - Multiple model instances optimize a single objective -> high speed
- A centralized sharded parameter server
  - Different model replicas retrieve/update their own parameters
- Load balance, robust
  - Tolerate variance in the processing speed of different model replicas
  - The wholesale failure may be taken offline or restart at random

# Distributed Algorithm

- Data parallelism
  - “Outside” parallelism
  - Multiple model instances optimize a single objective -> high speed
- A centralized sharded parameter server
  - Different model replicas retrieve/update their own parameters
- Load balance, robust
  - Tolerate variance in the processing speed of different model replicas
  - The wholesale failure may be taken offline or restart at random

# Outline

- 1 Motivation
- 2 Software Framework: DistBelief
- 3 Distributed Algorithm
  - Downpour SGD
  - Sandblaster L-BFGS
- 4 Experiments
- 5 Discussion



# Downpour SGD

- SGD [8]
  - Minimize the object function  $F(\omega)$
  - Update parameters  $\omega' = \omega - \eta \Delta \omega$
  - asynchronous SGD [3]
- Downpour
  - Massive parameters retrieved and updated



- Adagrad learning rate [4]
  - $\eta_{i,k} = \gamma / \sqrt{\sum_{j=1}^K \Delta \omega_{i,j}^2}$
  - Improve both robust and scale

# Downpour SGD

- SGD [8]
  - Minimize the object function  $F(\omega)$
  - Update parameters  $\omega' = \omega - \eta \Delta \omega$
  - asynchronous SGD [3]
- Downpour
  - Massive parameters retrieved and updated



- Adagrad learning rate [4]
  - $\eta_{i,k} = \gamma / \sqrt{\sum_{j=1}^K \Delta \omega_{i,j}^2}$
  - Improve both robust and scale

# Downpour SGD


- SGD [8]
  - Minimize the object function  $F(\omega)$
  - Update parameters  $\omega' = \omega - \eta \Delta \omega$
  - asynchronous SGD [3]
- Downpour
  - Massive parameters retrieved and updated



- Adagrad learning rate [4]
  - $\eta_{i,K} = \gamma / \sqrt{\sum_{j=1}^K \Delta \omega_{i,j}^2}$
  - Improve both robust and scale

# Downpour SGD (cont.)

- Algorithm visualization



# Downpour SGD (cont.)

- Algorithm pseudo code

---

**Algorithm 1.1:** DOWNPOURSGDCLIENT( $\alpha, n_{\text{fetch}}, n_{\text{push}}$ )

---

**procedure** STARTASYNCHRONOUSLYFETCHINGPARAMETERS(*parameters*)  
*parameters*  $\leftarrow$  GETPARAMETERSFROMPARAMSERVER()

**procedure** STARTASYNCHRONOUSLYPUSHINGGRADIENTS(*accruedgradients*)  
 SENDGRADIENTSTOPARAMSERVER(*accruedgradients*)  
*accruedgradients*  $\leftarrow$  0

**main**

**global** *parameters, accruedgradients*

*step*  $\leftarrow$  0

*accruedgradients*  $\leftarrow$  0

**while true**

**do** {

**if** (*step* mod  $n_{\text{fetch}}$ ) == 0

**then** STARTASYNCHRONOUSLYFETCHINGPARAMETERS(*parameters*)

*data*  $\leftarrow$  GETNEXTMINIBATCH()

*gradient*  $\leftarrow$  COMPUTEGRADIENT(*parameters*, *data*)

*accruedgradients*  $\leftarrow$  *accruedgradients* + *gradient*

*parameters*  $\leftarrow$  *parameters* -  $\alpha$  \* *gradient*

**if** (*step* mod  $n_{\text{push}}$ ) == 0

**then** STARTASYNCHRONOUSLYPUSHINGGRADIENTS(*accruedgradients*)

*step*  $\leftarrow$  *step* + 1

}

1

2

3

# Outline

- 1 Motivation
- 2 Software Framework: DistBelief
- 3 Distributed Algorithm**
  - Downpour SGD
  - **Sandblaster L-BFGS**
- 4 Experiments
- 5 Discussion

# Sandblaster L-BFGS

- BFGS [9]
  - An iterative method for solving unconstrained nonlinear optimization
  - Compute an approximation to the Hessian matrix  $B$
  - Limited-memory BFGS [10]
- Sandblaster
  - Massive commands issued by coordinator



- Load balancing scheme
  - Dynamic work assigned by coordinator

# Sandblaster L-BFGS

- BFGS [9]
  - An iterative method for solving unconstrained nonlinear optimization
  - Compute an approximation to the Hessian matrix  $B$
  - Limited-memory BFGS [10]
- Sandblaster
  - Massive commands issued by coordinator



- Load balancing scheme
  - Dynamic work assigned by coordinator



# Sandblaster L-BFGS


- BFGS [9]
  - An iterative method for solving unconstrained nonlinear optimization
  - Compute an approximation to the Hessian matrix  $B$
  - Limited-memory BFGS [10]
- Sandblaster
  - Massive commands issued by coordinator



- Load balancing scheme
  - Dynamic work assigned by coordinator

# Sandblaster L-BFGS (cont.)

- Algorithm visualization



# Sandblaster L-BFGS (cont.)

- Algorithm pseudo code

---

**Algorithm 1.2:** SANDBLASTERLBFGS()

---

```

procedure REPLICA.PROCESSPORTION(portion)
  if (!hasParametersForStep)
    then parameters  $\leftarrow$  GETPARAMETERSFROMPARAMSERVER()
  data  $\leftarrow$  GETDATAPORTION(portion)
  gradient  $\leftarrow$  COMPUTEGRADIENT(parameters, data)
  localAccruedGradients  $\leftarrow$  localAccruedGradients + gradient


procedure PARAMETERSERVER.PERFORMOPERATION(operation)
  PerformOperation

main
  step  $\leftarrow$  0
  while true
    comment: PS: ParameterServer
    PS.accruedgradients  $\leftarrow$  0
    while (batchProcessed < batchSize)
      for all (modelReplicas) comment: Loop is parallel and asynchronous
        if (modelReplica.Available)
          then { REPLICA.PROCESSPORTION(modelReplica) } ① ②
          batchProcessed  $\leftarrow$  batchProcessed + portion
        if (modelReplica.WorkDone and timeToSendGradients)
          then { SENDGRADIENTS(modelReplica) }
          PS.accruedGradients  $\leftarrow$  PS.accruedGradients + gradient
      COMPUTELBFGSDIRECTION(PS.Gradients, PS.History, PS.Direction) ③
      LINESearch(PS.Parameters, PS.Direction)
      PS.UPDATEPARAMETERS(PS.parameters, PS.accruedGradients)
    step  $\leftarrow$  step + 1
  
```

---


# Experiments

- Setup
  - Object recognition in still images [5]
  - Acoustic processing for speech recognition [2]
- Model parallelism benchmarks





# Experiments

- Setup
  - Object recognition in still images [5]
  - Acoustic processing for speech recognition [2]
- Model parallelism benchmarks




# Experiments (cont.)

## • Optimization method comparisons



# Experiments (cont.)

## • Optimization method comparisons



# Discussion

- Contributions
  - Increase the scale and speed of deep networks training
- Drawbacks
  - There is no guarantee that parameters are consistent



# Discussion

- Contributions
  - Increase the scale and speed of deep networks training
- Drawbacks
  - There is no guarantee that parameters are consistent

# References |

- [1] Large Scale Distributed Deep Networks. NIPS. 2012.
- [2] Building High-level Features Using Large Scale Unsupervised Learning. ICML. 2012.
- [3] Hogwild!: A Lock-Free Approach to Parallelizing Stochastic Gradient Descent. NIPS. 2011.
- [4] Adaptive subgradient methods for online learning and stochastic optimization. JMLR. 2011.
- [5] Improving the speed of neural networks on cpus. NIPS. 2011.
- [6] [http://ufldl.stanford.edu/wiki/index.php/Neural\\_Networks](http://ufldl.stanford.edu/wiki/index.php/Neural_Networks)
- [7] [http://ufldl.stanford.edu/wiki/index.php/Deep\\_Networks:\\_Overview](http://ufldl.stanford.edu/wiki/index.php/Deep_Networks:_Overview)
- [8] [http://ufldl.stanford.edu/wiki/index.php/Gradient\\_checking\\_and\\_advanced\\_optimization](http://ufldl.stanford.edu/wiki/index.php/Gradient_checking_and_advanced_optimization)

# References II

- [9] <http://en.wikipedia.org/wiki/BFGS>
- [10] [http://en.wikipedia.org/wiki/Limited-memory\\_BFGS](http://en.wikipedia.org/wiki/Limited-memory_BFGS)