

Fithian et al. (2014) NSW

```
library(maptools)
#> Loading required package: sp
#> Checking rgeos availability: FALSE
#> Note: when rgeos is not available, polygon geometry computations in maptools depend on gpcl
#> which has a restricted licence. It is disabled by default;
#> to enable gpclib, type gpclibPermit()
library(ppjsdm)
library(raster)
library(sf)
#> Linking to GEOS 3.6.2, GDAL 2.2.3, PROJ 4.9.3
library(spatstat)
#> Loading required package: spatstat.data
#> Loading required package: nlme
#>
#> Attaching package: 'nlme'
#> The following object is masked from 'package:raster':
#>
#>   getData
#> Loading required package: rpart
#>
#> spatstat 1.62-2 (nickname: 'Shape-shifting lizard')
#> For an introduction to spatstat, type 'beginner'
#>
#> Attaching package: 'spatstat'
#> The following objects are masked from 'package:raster':
#>
#>   area, rotate, shift
remove(list = ls())

source("../R/get_nsw.R")

set.seed(1)
```

This vignette explains how to use the `ppjsdm` package with the NSW dataset from Fithian et al. (2014). We begin by loading the data with only the most prevalent species.

```
number_of_species <- 4 # Includes the most prevalent species from the plot

nsw <- get_nsw(prevalent = number_of_species)
configuration <- nsw$configuration
window <- nsw$window
```

The point configuration is plotted below.

```
par(mar = c(5, 4, 4, 13) + 0.1)
plot(configuration, window = window)
```

Points in the configuration

