

Problem Analysis — First Day Contest

Ivan Kazmenko

St. Petersburg State University

Sunday, August 24, 2014

Additive Class — Preliminaries

In this problem, you have to find how many elements of the additive class of a and b belong to $[l, r]$.

Additive Class — Preliminaries

In this problem, you have to find how many elements of the additive class of a and b belong to $[l, r]$.

- Let $d = \text{GCD}(a, b)$.
 $a \leftarrow \frac{a}{d}, b \leftarrow \frac{b}{d}, l \leftarrow \lceil \frac{l}{d} \rceil, r \leftarrow \lfloor \frac{r}{d} \rfloor$.

Additive Class — Preliminaries

In this problem, you have to find how many elements of the additive class of a and b belong to $[l, r]$.

- Let $d = \text{GCD}(a, b)$.
 $a \leftarrow \frac{a}{d}, b \leftarrow \frac{b}{d}, l \leftarrow \lceil \frac{l}{d} \rceil, r \leftarrow \lfloor \frac{r}{d} \rfloor$.
- Now $\text{GCD}(a, b) = 1$.
Every $u \geq a \cdot b$ belongs to the class.
Every $v < a \cdot b$ has 0 or 1 representation as $x \cdot a + y \cdot b$.

Additive Class — Preliminaries

In this problem, you have to find how many elements of the additive class of a and b belong to $[l, r]$.

- Let $d = \text{GCD}(a, b)$.
 $a \leftarrow \frac{a}{d}, b \leftarrow \frac{b}{d}, l \leftarrow \lceil \frac{l}{d} \rceil, r \leftarrow \lfloor \frac{r}{d} \rfloor$.
- Now $\text{GCD}(a, b) = 1$.
Every $u \geq a \cdot b$ belongs to the class.
Every $v < a \cdot b$ has 0 or 1 representation as $x \cdot a + y \cdot b$.
- $f(l, r) = g(r) - g(l - 1)$.

Additive Class — Illustration

Example: $a = 17$, $b = 10$.

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	sum	diff
0	x	x	2	2
17	x	.	.	x	x	.	.	x	.	.	.	4	2
34	x	.	.	x	.	.	x	.	.	.	x	.	.	x	.	.	x	6	2
51	x	.	.	x	.	.	x	.	.	x	x	.	.	x	.	.	x	7	1
68	x	.	x	x	.	.	x	.	.	x	x	.	x	x	.	.	x	9	2
85	x	.	x	x	.	x	x	.	.	x	x	.	x	x	.	x	x	11	2
102	x	.	x	x	.	x	x	.	x	x	x	.	x	x	.	x	x	12	1
119	x	x	x	x	.	x	x	.	x	x	x	x	x	x	.	x	x	14	2
136	x	x	x	x	x	x	x	.	x	x	x	x	x	x	x	x	x	16	2
153	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	17	1

Additive Class — Illustration

Example: $a = 17$, $b = 10$.

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	sum	diff
0	x	x	2	2
17	x	.	.	x	x	.	.	x	.	.	.	4	2
34	x	.	.	x	.	.	x	.	.	.	x	.	.	x	.	.	x	6	2
51	x	.	.	x	.	.	x	.	.	x	x	.	.	x	.	.	x	7	1
68	x	.	x	x	.	.	x	.	.	x	x	.	x	x	.	.	x	9	2
85	x	.	x	x	.	x	x	.	.	x	x	.	x	x	.	x	x	11	2
102	x	.	x	x	.	x	x	.	x	x	x	.	x	x	.	x	x	12	1
119	x	x	x	x	.	x	x	.	x	x	x	x	x	x	.	x	x	14	2
136	x	x	x	x	x	x	x	.	x	x	x	x	x	x	x	x	x	16	2
153	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	17	1

The **diff** column: Euclid's algorithm (continued fraction).

$$\frac{17}{10} = 1 + \frac{1}{\frac{10}{7}} = 1 + \frac{1}{1 + \frac{1}{\frac{7}{3}}} = 1 + \frac{1}{1 + \frac{1}{2 + \frac{1}{3}}} = [1; 1, 2, 3]$$

Additive Class — Illustration

Last line: shift the table.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	sum	diff
0	x	1	1
17	.	.	x	x	.	.	x	3	2
34	.	.	x	.	.	x	.	.	.	x	.	.	x	.	.	x	.	5	2
51	.	.	x	.	.	x	.	.	x	x	.	.	x	.	.	x	.	6	1
68	.	x	x	.	.	x	.	.	x	x	.	x	x	.	.	x	.	8	2
85	.	x	x	.	x	x	.	.	x	x	.	x	x	.	x	x	.	10	2
102	.	x	x	.	x	x	.	x	x	x	.	x	x	.	x	x	.	11	1
119	x	x	x	.	x	x	.	x	x	x	x	x	x	.	x	x	.	13	2
136	x	x	x	x	x	x	.	x	x	x	x	x	x	x	x	x	.	15	2
153	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	17	2

Additive Class — Illustration

Last line: shift the table.

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	sum	diff
0	x	1	1
17	.	.	x	x	.	.	x	3	2
34	.	.	x	.	.	x	.	.	.	x	.	.	x	.	.	x	.	5	2
51	.	.	x	.	.	x	.	.	x	x	.	.	x	.	.	x	.	6	1
68	.	x	x	.	.	x	.	.	x	x	.	x	x	.	.	x	.	8	2
85	.	x	x	.	x	x	.	.	x	x	.	x	x	.	x	x	.	10	2
102	.	x	x	.	x	x	.	x	x	x	.	x	x	.	x	x	.	11	1
119	x	x	x	.	x	x	.	x	x	x	x	x	x	.	x	x	.	13	2
136	x	x	x	x	x	x	.	x	x	x	x	x	x	x	x	x	.	15	2
153	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	17	2

The **diff** column is cyclically shifted by $(a^{-1} \bmod b)$ upwards.

Board Blitz — Solution 1

In this problem, you have to quickly find the final position in a game on a square board.

Board Blitz — Solution 1

In this problem, you have to quickly find the final position in a game on a square board.

- Pack the board into bits: `int64`.

Board Blitz — Solution 1

In this problem, you have to quickly find the final position in a game on a square board.

- Pack the board into bits: `int64`.
- Movement: bit shift $(+8, +1, -8, -1)$.

Board Blitz — Solution 1

In this problem, you have to quickly find the final position in a game on a square board.

- Pack the board into bits: `int64`.
- Movement: bit shift $(+8, +1, -8, -1)$.
- Rotation: 1. Naive $O(\text{bits})$.

Board Blitz — Solution 1

In this problem, you have to quickly find the final position in a game on a square board.

- Pack the board into bits: `int64`.
- Movement: bit shift $(+8, +1, -8, -1)$.
- Rotation: 1. Naive $O(\text{bits})$.
- Rotation: 2. Clever $O(\log(\text{bits}))$.

Board Blitz — Solution 1

In this problem, you have to quickly find the final position in a game on a square board.

- Pack the board into bits: `int64`.
- Movement: bit shift $(+8, +1, -8, -1)$.
- Rotation: 1. Naive $O(\text{bits})$.
- Rotation: 2. Clever $O(\log(\text{bits}))$.
- Rotation: 3. Blunt $O(\text{bits}/K)$ with 2^K precalculation.

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.
- 1. Pretend: only one player, only moving, only `right`.
Off the board after 8 turns.

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.
- 1. Pretend: only one player, only moving, only `right`.
Off the board after 8 turns.
- 2. Pretend: only one player, only moving, only `left` and `right`.
Probability of $8 \times \text{right}$: $1/2^8$.

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.
- ...
- 2. Pretend: only one player, only moving, only left and right.
Probability of $8 \times \text{right}$: $1/2^8$.
- 3. Pretend: only one player, only moving.
Probability of $8 \times \text{right}$: $1/2^8$, time $\times 2$.

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.
- ...
- 3. Pretend: only one player, only moving.
Probability of $8 \times \text{right}$: $1/2^8$, time $\times 2$.
- 4. Pretend: only one player, allow rotation.
Probability of $8 \times \text{"right"}$: $1/2^8$, time $\times 4$.
Turn our argument with the rotation!

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.
- ...
- 4. Pretend: only one player, allow rotation.
Probability of $8 \times \text{"right"}$: $1/2^8$, time $\times 4$.
Turn our argument with the rotation!
- 5. Pretend: nothing.
Probability of $8 \times \text{"right"}$: $1/2^8$, time $\times 8$.

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.
- ...
- 5. Pretend: nothing.
Probability of $8 \times \text{"right"}$: $1/2^8$, time $\times 8$.
- Conclusion: a piece's expected lifetime is $2^8 \cdot 8 = 2048$ moves (upper bound).

Board Blitz — Solution 2

In this problem, you have to quickly find the final position in a game on a square board.

- Estimate the lifetime of a particular game piece.
- ...
- 5. Pretend: nothing.
Probability of $8 \times \text{"right"}$: $1/2^8$, time $\times 8$.
- Conclusion: a piece's expected lifetime is $2^8 \cdot 8 = 2048$ moves (upper bound).
- Simulate only the last 10 000 moves by slow but simple code.

Divisor Count — Preliminaries

In this problem, you have to find the first n integers which have exactly k divisors.

Divisor Count — Preliminaries

In this problem, you have to find the first n integers which have exactly k divisors.

- Consider all factorizations of k : $k = a_1 \cdot a_2 \cdot \dots \cdot a_r$.

Divisor Count — Preliminaries

In this problem, you have to find the first n integers which have exactly k divisors.

- Consider all factorizations of k : $k = a_1 \cdot a_2 \cdot \dots \cdot a_r$.
- Number with k divisors: $p_1^{a_1-1} \cdot p_2^{a_2-1} \cdot \dots \cdot p_r^{a_r-1}$ (p_i are primes).

Divisor Count — Preliminaries

In this problem, you have to find the first n integers which have exactly k divisors.

- Consider all factorizations of k : $k = a_1 \cdot a_2 \cdot \dots \cdot a_r$.
- Number with k divisors: $p_1^{a_1-1} \cdot p_2^{a_2-1} \cdot \dots \cdot p_r^{a_r-1}$ (p_i are primes).

Minimum such number?

Divisor Count — Preliminaries

In this problem, you have to find the first n integers which have exactly k divisors.

- Consider all factorizations of k : $k = a_1 \cdot a_2 \cdot \dots \cdot a_r$.
- Number with k divisors: $p_1^{a_1-1} \cdot p_2^{a_2-1} \cdot \dots \cdot p_r^{a_r-1}$ (p_i are primes).

Minimum such number?

- Consecutive primes: $p_1 = 2, p_2 = 3, \dots$

Divisor Count — Preliminaries

In this problem, you have to find the first n integers which have exactly k divisors.

- Consider all factorizations of k : $k = a_1 \cdot a_2 \cdot \dots \cdot a_r$.
- Number with k divisors: $p_1^{a_1-1} \cdot p_2^{a_2-1} \cdot \dots \cdot p_r^{a_r-1}$ (p_i are primes).

Minimum such number?

- Consecutive primes: $p_1 = 2, p_2 = 3, \dots$
- Non-increasing powers: $a_1 \geq a_2 \geq \dots \geq a_r$.

Divisor Count — Example 1

In this problem, you have to find the first n integers which have exactly k divisors.

Divisor Count — Example 1

In this problem, you have to find the first n integers which have exactly k divisors.

Example: $k = 12$.

- $12 = 12$
 $x = 2^{11} = 2048$

Divisor Count — Example 1

In this problem, you have to find the first n integers which have exactly k divisors.

Example: $k = 12$.

- $12 = 12$
 $x = 2^{11} = 2048$
- $12 = 6 \cdot 2$
 $x = 2^5 \cdot 3^1 = 96$

Divisor Count — Example 1

In this problem, you have to find the first n integers which have exactly k divisors.

Example: $k = 12$.

- $12 = 12$
 $x = 2^{11} = 2048$
- $12 = 6 \cdot 2$
 $x = 2^5 \cdot 3^1 = 96$
- $12 = 4 \cdot 3$
 $x = 2^3 \cdot 3^2 = 72$

Divisor Count — Example 1

In this problem, you have to find the first n integers which have exactly k divisors.

Example: $k = 12$.

- $12 = 12$
 $x = 2^{11} = 2048$
- $12 = 6 \cdot 2$
 $x = 2^5 \cdot 3^1 = 96$
- $12 = 4 \cdot 3$
 $x = 2^3 \cdot 3^2 = 72$
- $12 = 3 \cdot 2 \cdot 2$
 $x = 2^2 \cdot 3^1 \cdot 5^1 = 60$

Divisor Count — Example 1

In this problem, you have to find the first n integers which have exactly k divisors.

Example: $k = 12$.

- $12 = 12$
 $x = 2^{11} = 2048$
- $12 = 6 \cdot 2$
 $x = 2^5 \cdot 3^1 = 96$
- $12 = 4 \cdot 3$
 $x = 2^3 \cdot 3^2 = 72$
- $12 = 3 \cdot 2 \cdot 2$
 $x = 2^2 \cdot 3^1 \cdot 5^1 = 60$

We compare the numbers by putting them into a priority queue.

Divisor Count — Generating

In this problem, you have to find the first n integers which have exactly k divisors.

Generating next numbers:

- $2^{11} \rightarrow 3^{11} \rightarrow 5^{11} \rightarrow 7^{11} \rightarrow 11^{11} \rightarrow 13^{11} \rightarrow \dots$

Divisor Count — Generating

In this problem, you have to find the first n integers which have exactly k divisors.

Generating next numbers:

- $2^{11} \longrightarrow 3^{11} \longrightarrow 5^{11} \longrightarrow 7^{11} \longrightarrow 11^{11} \longrightarrow 13^{11} \longrightarrow \dots$
- $2^5 \cdot 3^1 \longrightarrow 2^1 \cdot 3^5$ and $2^5 \cdot 5^1$

Divisor Count — Generating

In this problem, you have to find the first n integers which have exactly k divisors.

Generating next numbers:

- $2^{11} \longrightarrow 3^{11} \longrightarrow 5^{11} \longrightarrow 7^{11} \longrightarrow 11^{11} \longrightarrow 13^{11} \longrightarrow \dots$
- $2^5 \cdot 3^1 \longrightarrow 2^1 \cdot 3^5$ and $2^5 \cdot 5^1$
- $2^3 \cdot 3^2 \longrightarrow 2^2 \cdot 3^3$ and $2^3 \cdot 5^2$

Divisor Count — Generating

In this problem, you have to find the first n integers which have exactly k divisors.

Generating next numbers:

- $2^{11} \rightarrow 3^{11} \rightarrow 5^{11} \rightarrow 7^{11} \rightarrow 11^{11} \rightarrow 13^{11} \rightarrow \dots$
- $2^5 \cdot 3^1 \rightarrow 2^1 \cdot 3^5$ and $2^5 \cdot 5^1$
- $2^3 \cdot 3^2 \rightarrow 2^2 \cdot 3^3$ and $2^3 \cdot 5^2$
- $2^2 \cdot 3^1 \cdot 5^1 \rightarrow 2^2 \cdot 3^1 \cdot 7^1$ and $2^1 \cdot 3^2 \cdot 5^1$
 - $2^2 \cdot 3^1 \cdot 7^1 \rightarrow 2^2 \cdot 5^1 \cdot 7^1$ and $2^2 \cdot 3^1 \cdot 11^1$ and $2^1 \cdot 3^2 \cdot 7^1$
 - $2^1 \cdot 3^2 \cdot 5^1 \rightarrow 2^1 \cdot 3^2 \cdot 7^1$ and $2^1 \cdot 3^1 \cdot 5^2$
 - \dots

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:
- $3^3 \cdot 7^1 \cdot 11^3 \cdot 17^2 \cdot 29^1$ (swapping adjacent powers 2 and 3)

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:
- $3^3 \cdot 7^1 \cdot 11^3 \cdot 17^2 \cdot 29^1$ (swapping adjacent powers 2 and 3)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^1 \cdot 29^2$ (swapping adjacent powers 4 and 5)

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:
- $3^3 \cdot 7^1 \cdot 11^3 \cdot 17^2 \cdot 29^1$ (swapping adjacent powers 2 and 3)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^1 \cdot 29^2$ (swapping adjacent powers 4 and 5)
- $5^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ (shifting element 1 to next prime)

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:
- $3^3 \cdot 7^1 \cdot 11^3 \cdot 17^2 \cdot 29^1$ (swapping adjacent powers 2 and 3)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^1 \cdot 29^2$ (swapping adjacent powers 4 and 5)
- $5^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ (shifting element 1 to next prime)
- $3^3 \cdot 7^3 \cdot 13^1 \cdot 17^2 \cdot 29^1$ (shifting element 3 to next prime)

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:
- $3^3 \cdot 7^1 \cdot 11^3 \cdot 17^2 \cdot 29^1$ (swapping adjacent powers 2 and 3)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^1 \cdot 29^2$ (swapping adjacent powers 4 and 5)
- $5^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ (shifting element 1 to next prime)
- $3^3 \cdot 7^3 \cdot 13^1 \cdot 17^2 \cdot 29^1$ (shifting element 3 to next prime)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 23^2 \cdot 29^1$ (shifting element 4 to next prime)

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:
- $3^3 \cdot 7^1 \cdot 11^3 \cdot 17^2 \cdot 29^1$ (swapping adjacent powers 2 and 3)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^1 \cdot 29^2$ (swapping adjacent powers 4 and 5)
- $5^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ (shifting element 1 to next prime)
- $3^3 \cdot 7^3 \cdot 13^1 \cdot 17^2 \cdot 29^1$ (shifting element 3 to next prime)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 23^2 \cdot 29^1$ (shifting element 4 to next prime)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 31^1$ (shifting element 5 to next prime)

Divisor Count — Example 2

In this problem, you have to find the first n integers which have exactly k divisors.

A more complex example:

- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ produces:
- $3^3 \cdot 7^1 \cdot 11^3 \cdot 17^2 \cdot 29^1$ (swapping adjacent powers 2 and 3)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^1 \cdot 29^2$ (swapping adjacent powers 4 and 5)
- $5^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 29^1$ (shifting element 1 to next prime)
- $3^3 \cdot 7^3 \cdot 13^1 \cdot 17^2 \cdot 29^1$ (shifting element 3 to next prime)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 23^2 \cdot 29^1$ (shifting element 4 to next prime)
- $3^3 \cdot 7^3 \cdot 11^1 \cdot 17^2 \cdot 31^1$ (shifting element 5 to next prime)

Priority queue size limit: the remaining number of values to output.

Divisor Count — Tests

In this problem, you have to find the first n integers which have exactly k divisors.

Interesting test cases:

Divisor Count — Tests

In this problem, you have to find the first n integers which have exactly k divisors.

Interesting test cases:

- $k = 103\,680$:

897 612 484 786 617 600, 994 651 672 331 116 800, -1 , -1 ,

Divisor Count — Tests

In this problem, you have to find the first n integers which have exactly k divisors.

Interesting test cases:

- $k = 103\,680$:
897 612 484 786 617 600, 994 651 672 331 116 800, -1 , -1 ,
- $k = 11\,520$:
initial priority queue size is 201.

Divisor Count — Tests

In this problem, you have to find the first n integers which have exactly k divisors.

Interesting test cases:

- $k = 103\,680$:
897 612 484 786 617 600, 994 651 672 331 116 800, -1 , -1 ,
- $k = 11\,520$:
initial priority queue size is 201.
- $k = 1$:
the only such number is 1.

Domino Tiling — Outline

In this problem, you have to transform one domino tiling of a rectangle into another by moving dominoes along cycles.

Domino Tiling — Outline

In this problem, you have to transform one domino tiling of a rectangle into another by moving dominoes along cycles.

- If a domino is present in both tilings, we will not touch it.

Domino Tiling — Outline

In this problem, you have to transform one domino tiling of a rectangle into another by moving dominoes along cycles.


- If a domino is present in both tilings, we will not touch it.
- If a cell belongs to different dominoes, we have to touch it at least once.

Domino Tiling — Outline


In this problem, you have to transform one domino tiling of a rectangle into another by moving dominoes along cycles.

- If a domino is present in both tilings, we will not touch it.
- If a cell belongs to different dominoes, we have to touch it at least once.
- At least once \longrightarrow exactly once.

Domino Tiling — Example




Domino Tiling — Example



One step of the algorithm:

- Pick a cell which belongs to different dominoes.


Domino Tiling — Example



One step of the algorithm:

- Pick a cell which belongs to different dominoes.
- Move to another cell along the domino on board 1.


Domino Tiling — Example



One step of the algorithm:

- Pick a cell which belongs to different dominoes.
- Move to another cell along the domino on board 1.
- Move to yet another cell along the domino on board 2.


Domino Tiling — Example



One step of the algorithm:

- Pick a cell which belongs to different dominoes.
- Move to another cell along the domino on board 1.
- Move to yet another cell along the domino on board 2.
- ...


Domino Tiling — Example



One step of the algorithm:

- Pick a cell which belongs to different dominoes.
- Move to another cell along the domino on board 1.
- Move to yet another cell along the domino on board 2.
- ...
- The process could have started from board 2 (in reverse).


Domino Tiling — Example



One step of the algorithm:

- Pick a cell which belongs to different dominoes.
- Move to another cell along the domino on board 1.
- Move to yet another cell along the domino on board 2.
- ...
- The process could have started from board 2 (in reverse).
- So, we will get a cycle.

Domino Tiling — Example



One step of the algorithm:

- Pick a cell which belongs to different dominoes.
- Move to another cell along the domino on board 1.
- Move to yet another cell along the domino on board 2.
- ...
- The process could have started from board 2 (in reverse).
- So, we will get a cycle.
- Move the dominoes along this cycle once to remove it completely.

Hourglass — Solution?

In this problem, you have to solve a puzzle involving a planar board and pieces.

Hourglass — Solution?

In this problem, you have to solve a puzzle involving a planar board and pieces.

How to solve it?

Hourglass — Solution?

In this problem, you have to solve a puzzle involving a planar board and pieces.

How to solve it?

Constructive solution?
What if n is up to 100?

Hourglass — Brute Force

In this problem, you have to solve a puzzle involving a planar board and pieces.

Hourglass — Brute Force

In this problem, you have to solve a puzzle involving a planar board and pieces.

- Key: the order in which we try the moves

Hourglass — Brute Force

In this problem, you have to solve a puzzle involving a planar board and pieces.

- Key: the order in which we try the moves
- Pruning: **polynomial** check vs. **exponential** branching

Hourglass — Brute Force

In this problem, you have to solve a puzzle involving a planar board and pieces.

- Key: the order in which we try the moves
- Pruning: **polynomial** check vs. **exponential** branching
- DFS (brute force) or BFS (beam search)

Hourglass — Brute Force

In this problem, you have to solve a puzzle involving a planar board and pieces.


- Key: the order in which we try the moves
- Pruning: **polynomial** check vs. **exponential** branching
- DFS (brute force) or BFS (beam search)
- Simplification: consider 1D version

k -th Meander — Section

In this problem, you have to find the lexicographically k -th meander of order n .

k -th Meander — Section

In this problem, you have to find the lexicographically k -th meander of order n .



- .
- [.]
- [] . []
- [] [.]
- [] . []
- [[] .] []
- [[.]] []
- [.] []
- . []
- [.]
- .

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.
- Transitions: one per O, D, U, C.

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.
- Transitions: one per O, D, U, C.
- The number of meanders for $n = 15$ is 602 188 541 928.

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.
- Transitions: one per O, D, U, C.
- The number of meanders for $n = 15$ is 602 188 541 928.
- It is > 6 times larger than 10^{11} .

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.
- Transitions: one per O, D, U, C.
- The number of meanders for $n = 15$ is 602 188 541 928.
- It is > 6 times larger than 10^{11} .
- Lazy dynamic programming: create only the states we need.

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.
- Transitions: one per O, D, U, C.
- The number of meanders for $n = 15$ is 602 188 541 928.
- It is > 6 times larger than 10^{11} .
- Lazy dynamic programming: create only the states we need.
 - First, recursively find the number c of child states if we make the current transition.

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.
- Transitions: one per O, D, U, C.
- The number of meanders for $n = 15$ is 602 188 541 928.
- It is > 6 times larger than 10^{11} .
- Lazy dynamic programming: create only the states we need.
 - First, recursively find the number c of child states if we make the current transition.
 - If the number $k > c$, decrease it by c and proceed with the next transition ($C < D < O < U$).

k -th Meander — Dynamic Programming

In this problem, you have to find the lexicographically k -th meander of order n .

- State: bracket sequence (with length) and intersection point.
- Transitions: one per O, D, U, C.
- The number of meanders for $n = 15$ is 602 188 541 928.
- It is > 6 times larger than 10^{11} .
- Lazy dynamic programming: create only the states we need.
 - First, recursively find the number c of child states if we make the current transition.
 - If the number $k > c$, decrease it by c and proceed with the next transition ($C < D < O < U$).
 - Otherwise, print the transition sign and descend by the current transition.

k -th Meander — Reference

In this problem, you have to find the lexicographically k -th meander of order n .

An article on the topic:

- Iwan Jensen, Enumerations of plane meanders:
<http://arxiv.org/abs/cond-mat/9910313>

Records and Cycles — Preliminaries

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Records and Cycles — Preliminaries

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Records:

$$f(n, k) = f(n - 1, k - 1) + (n - 1) \cdot f(n - 1, k).$$

Records and Cycles — Preliminaries

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Records:

$$f(n, k) = f(n - 1, k - 1) + (n - 1) \cdot f(n - 1, k).$$

- Cycles:

$$g(n, k) = g(n - 1, k - 1) + (n - 1) \cdot g(n - 1, k).$$

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Let us transform one cycle into one record.

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Let us transform one cycle into one record.
- Find the cycle containing 1, let its length be l .

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Let us transform one cycle into one record.
- Find the cycle containing 1, let its length be l .
- Put l on the left and $1, 2, \dots, (l - 1)$ after it in their order on the cycle.

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Let us transform one cycle into one record.
- Find the cycle containing 1, let its length be l .
- Put l on the left and $1, 2, \dots, (l-1)$ after it in their order on the cycle.
- Next, find the cycle containing the remaining minimum, let its length be m .

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Let us transform one cycle into one record.
- Find the cycle containing 1, let its length be l .
- Put l on the left and $1, 2, \dots, (l - 1)$ after it in their order on the cycle.
- Next, find the cycle containing the remaining minimum, let its length be m .
- Put $l + m$ on the left and $(l + 1), (l + 2), \dots, (l + m - 1)$ after it in their order on the cycle.

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Let us transform one cycle into one record.
- Find the cycle containing 1, let its length be l .
- Put l on the left and $1, 2, \dots, (l-1)$ after it in their order on the cycle.
- Next, find the cycle containing the remaining minimum, let its length be m .
- Put $l+m$ on the left and $(l+1), (l+2), \dots, (l+m-1)$ after it in their order on the cycle.
- ...

Records and Cycles — Solution 1

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

- Let us transform one cycle into one record.
- Find the cycle containing 1, let its length be l .
- Put l on the left and $1, 2, \dots, (l-1)$ after it in their order on the cycle.
- Next, find the cycle containing the remaining minimum, let its length be m .
- Put $l+m$ on the left and $(l+1), (l+2), \dots, (l+m-1)$ after it in their order on the cycle.
- ...
- Can be done in linear total time.

Records and Cycles — Cycles to Records

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform cycles into records ($p \rightarrow u$).

Records and Cycles — Cycles to Records

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform cycles into records ($p \rightarrow u$).

- Suppose we already placed s elements.
Find the *least* unprocessed element r .

Records and Cycles — Cycles to Records

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform cycles into records ($p \rightarrow u$).

- Suppose we already placed s elements.
Find the *least* unprocessed element r .
- Find its cycle $(r, p(r), p(p(r)), \dots)$.
Let its length be l .

Records and Cycles — Cycles to Records

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform cycles into records ($p \rightarrow u$).

- Suppose we already placed s elements.
Find the *least* unprocessed element r .
- Find its cycle $(r, p(r), p(p(r)), \dots)$.
Let its length be l .
- Put numbers $s + l, s + l - 1, \dots, s + 1$
into u at places $r, p(r), p(p(r))$.

Records and Cycles — Cycles to Records

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform cycles into records ($p \rightarrow u$).

- Suppose we already placed s elements.
Find the *least* unprocessed element r .
- Find its cycle $(r, p(r), p(p(r)), \dots)$.
Let its length be l .
- Put numbers $s + l, s + l - 1, \dots, s + 1$
into u at places $r, p(r), p(p(r))$.
- Repeat until $s = n$.

Records and Cycles — Records to Cycles

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform records into cycles ($u \rightarrow p$).

Records and Cycles — Records to Cycles

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform records into cycles ($u \rightarrow p$).

- Suppose we already processed s elements.
Find the *leftmost* unprocessed element r .

Records and Cycles — Records to Cycles

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform records into cycles ($u \rightarrow p$).

- Suppose we already processed s elements.
Find the *leftmost* unprocessed element r .
- Find the positions of elements $r, r-1, \dots, s+1$.
Let them be $v(r), v(r-1), \dots, v(s+1)$.

Records and Cycles — Records to Cycles

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform records into cycles ($u \rightarrow p$).

- Suppose we already processed s elements.
Find the *leftmost* unprocessed element r .
- Find the positions of elements $r, r-1, \dots, s+1$.
Let them be $v(r), v(r-1), \dots, v(s+1)$.
- Put numbers $v(r-1), v(r-2), \dots, v(s+1), v(r)$
into p at places $v(r), v(r-1), \dots, v(s+2), v(s+1)$.

Records and Cycles — Records to Cycles

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

Let us transform records into cycles ($u \rightarrow p$).

- Suppose we already processed s elements.
Find the *leftmost* unprocessed element r .
- Find the positions of elements $r, r-1, \dots, s+1$.
Let them be $v(r), v(r-1), \dots, v(s+1)$.
- Put numbers $v(r-1), v(r-2), \dots, v(s+1), v(r)$
into p at places $v(r), v(r-1), \dots, v(s+2), v(s+1)$.
- Repeat until $s = n$.

Records and Cycles — Records to Cycles

Example $C \rightarrow R$:

$p = 2\ 6\ 8\ 5\ 4\ 3\ 7\ 1$

$p = (1\ 2\ 6\ 3\ 8)\ (4\ 5)\ (7)$

$q = 8\ 1\ 6\ 5\ 4\ 2\ 7\ 3$

$u = .\ .\ .\ .\ .\ .\ .\ .$

$u = 5\ 4\ 2\ .\ .\ 3\ .\ 1$

$u = 5\ 4\ 2\ 7\ 6\ 3\ .\ 1$

$u = 5\ 4\ 2\ 7\ 6\ 3\ 8\ 1$

Example $R \rightarrow C$:

$u = 5\ 4\ 2\ 7\ 6\ 3\ 8\ 1$

records: 5 7 8

$v = 8\ 3\ 6\ 2\ 1\ 5\ 4\ 7$

$p = .\ .\ .\ .\ .\ .\ .\ .$ [5 4 3 2 1 on places 1 2 6 3 8]

$p = 2\ 6\ 8\ .\ .\ 3\ .\ 1$ [7 6 on places 4 5]

$p = 2\ 6\ 8\ 5\ 4\ 3\ .\ 1$ [8 on place 7]

$p = 2\ 6\ 8\ 5\ 4\ 3\ 7\ 1$

Records and Cycles — Solution 2

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

The only requirement is to have no contradictions.

Records and Cycles — Solution 2

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

The only requirement is to have no contradictions.

- Random permutation with k records/cycles?

Records and Cycles — Solution 2

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

The only requirement is to have no contradictions.

- Random permutation with k records/cycles?
- $f(n, k) = f(n - 1, k - 1) + (n - 1) \cdot f(n - 1, k)$

Records and Cycles — Solution 2

In this problem, you have to construct a bijection which maps every permutation of length n with k cycles to a permutation of length n with k records.

The only requirement is to have no contradictions.

- Random permutation with k records/cycles?
- $f(n, k) = f(n - 1, k - 1) + (n - 1) \cdot f(n - 1, k)$
- Next permutation with k records/cycles?

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to generate a cell?

- $s_1 = s_0 \cdot a + c$

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to generate a cell?

- $s_1 = s_0 \cdot a + c$
- $\begin{pmatrix} s_1 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to generate a cell?

- $s_1 = s_0 \cdot a + c$
- $\begin{pmatrix} s_1 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- $\begin{pmatrix} s_2 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to generate a cell?

- $s_1 = s_0 \cdot a + c$
- $\begin{pmatrix} s_1 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- $\begin{pmatrix} s_2 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- 1. Naive: $O(h \cdot w)$.

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to generate a cell?

- $s_1 = s_0 \cdot a + c$
- $\begin{pmatrix} s_1 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- $\begin{pmatrix} s_2 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- 1. Naive: $O(h \cdot w)$.
- 2. Repeated squaring: $O(\log(h \cdot w))$.

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to generate a cell?

- $s_1 = s_0 \cdot a + c$
- $\begin{pmatrix} s_1 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- $\begin{pmatrix} s_2 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- 1. Naive: $O(h \cdot w)$.
- 2. Repeated squaring: $O(\log(h \cdot w))$.
- 3. Blunt: $O(1)$ with $O(h + w)$ precalculation.

Rock-Paper-Scissors walk — Field

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to generate a cell?

- $s_1 = s_0 \cdot a + c$
- $\begin{pmatrix} s_1 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- $\begin{pmatrix} s_2 \\ 1 \end{pmatrix} = \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} a & c \\ 0 & 1 \end{pmatrix} \cdot \begin{pmatrix} s_0 \\ 1 \end{pmatrix}$
- 1. Naive: $O(h \cdot w)$.
- 2. Repeated squaring: $O(\log(h \cdot w))$.
- 3. Blunt: $O(1)$ with $O(h + w)$ precalculation.
- Another method: linear functions instead of matrices.

Rock-Paper-Scissors walk — Path

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

Rock-Paper-Scissors walk — Path

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to find a path?

- Just find the closest cell each time.

Rock-Paper-Scissors walk — Path

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to find a path?

- Just find the closest cell each time.
- Don't forget to look back!

Rock-Paper-Scissors walk — Path

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to find a path?

- Just find the closest cell each time.
- Don't forget to look back!
- The board can be $100 \times 65\,536$ or $65\,536 \times 100$.

Rock-Paper-Scissors walk — Path

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to find a path?

- Just find the closest cell each time.
- Don't forget to look back!
- The board can be $100 \times 65\,536$ or $65\,536 \times 100$.
- $\left(\frac{2}{3}\right)^{100} = 2.459654... \cdot 10^{-18}$ but $\left(\frac{2}{3}\right)^{10} = 0.017341....$

Rock-Paper-Scissors walk — Path

In this problem, you have to travel from one corner of a checkered field to the opposite corner conforming to certain rules and avoiding making too much moves.

How to find a path?

- Just find the closest cell each time.
- Don't forget to look back!
- The board can be $100 \times 65\,536$ or $65\,536 \times 100$.
- $\left(\frac{2}{3}\right)^{100} = 2.459654... \cdot 10^{-18}$ but $\left(\frac{2}{3}\right)^{10} = 0.017341....$
- Speedup: visit each row from right to left, break if found.

Set Operations — Grouping

In this problem, you have to perform operations with sets according to the given expression.

Set Operations — Grouping

In this problem, you have to perform operations with sets according to the given expression.

Consider eight (2^3) possible classes of elements.

Set Operations — Grouping

In this problem, you have to perform operations with sets according to the given expression.

Consider eight (2^3) possible classes of elements.

element	in A	in B	in C
0	0	0	0
1	0	0	1
2	0	1	0
3	0	1	1
4	1	0	0
5	1	0	1
6	1	1	0
7	1	1	1

Set Operations — Grouping

In this problem, you have to perform operations with sets according to the given expression.

Consider eight (2^3) possible classes of elements.

- Solve the problem once for $A = \{4, 5, 6, 7\}$, $B = \{2, 3, 6, 7\}$ and $C = \{1, 3, 5, 7\}$.

Set Operations — Grouping

In this problem, you have to perform operations with sets according to the given expression.

Consider eight (2^3) possible classes of elements.

- Solve the problem once for $A = \{4, 5, 6, 7\}$, $B = \{2, 3, 6, 7\}$ and $C = \{1, 3, 5, 7\}$.
- For each given triple (A, B, C) , distribute the elements $\{1, 2, \dots, n\}$ into eight classes.

Set Operations — Grouping

In this problem, you have to perform operations with sets according to the given expression.

Consider eight (2^3) possible classes of elements.

- Solve the problem once for $A = \{4, 5, 6, 7\}$, $B = \{2, 3, 6, 7\}$ and $C = \{1, 3, 5, 7\}$.
- For each given triple (A, B, C) , distribute the elements $\{1, 2, \dots, n\}$ into eight classes.
- For each class, we know whether it is present in the answer.

Set Operations — Grouping

In this problem, you have to perform operations with sets according to the given expression.

Consider eight (2^3) possible classes of elements.

- Solve the problem once for $A = \{4, 5, 6, 7\}$, $B = \{2, 3, 6, 7\}$ and $C = \{1, 3, 5, 7\}$.
- For each given triple (A, B, C) , distribute the elements $\{1, 2, \dots, n\}$ into eight classes.
- For each class, we know whether it is present in the answer.
- Result: $O(|S| + t)$ instead of $O(|S| \cdot t)$.

Contest Developers:

- Natalya Ginzburg
- Ivan Kazmenko
- Pavel Kunyavskiy

Questions?